| | |
|---|---|
| WEATHERLY NO. | 400 |
| CATALOG NO. | AUTOMOTIVE 431-2080<br>INDUSTRIAL 35093 |
| EDITION | 2019 |
| SUPERSEDES | 431-2080 (2014)<br>35093 (2015) |

# HYDRAULIC & FLEET HOSE PRODUCTS











- A 3,000 psi coupling on a 3,000 psi hose doesn't always equal a 3,000 psi assembly.
- One of the most important and oftentimes overlooked factors in hydraulic hose assembly performance is the hose/coupling interface.
- You can't just design a hose. You can't just design a coupling. You must design a system (a **MegaSys**tem).

Unless you have a hose and coupling specifically designed for each other, you may end up with a hose assembly with a lower pressure rating, reduced life, or even worse, a catastrophic failure.

Hose outside diameter and crimp outside diameter are only two of the variables affecting assembly performance.

As variation or tolerances increase even slightly for each component a significant reduction in hose assembly life is guaranteed and the risk for catastrophic failure increases.




THE NEXT TIME YOU GRAB ANY HOSE AND A COUPLING ASK YOURSELF:

- Who is the manufacturer of these components?
- Have these components been designed together?
- Validated together? And if not, what are the risks I am assuming?
- Am I willing to accept an assembly with a guarantee for reduced impulse life and performance?
- Am I willing to risk catastrophic failure?

# Avoid injury to yourself and others by following these important hose assembly steps

## WARNING

**Never underestimate the power of a blown hydraulic assembly.**

**Serious injury, death and destruction of property can result from rupture or blow-apart of a hydraulic hose assembly that is:**

- **Damaged or worn out**
- **Assembled or installed incorrectly**
- **Wrong for application**

1. **Receive hands-on training** with Gates recommended equipment.
2. Follow current Gates **operating manuals and crimp data.**
3. Use only new (unused) Gates recommended hose and couplings **with Gates crimpers.**
4. **Wear safety glasses.**

### Select and Install Assemblies With Care

1. **Select proper hose assemblies for the application.** Many factors and conditions affecting the inside and outside diameter of the hose must be taken into account.
2. Hose assembly routing **must not** create an injury hazard or damage hose. Refer to the standards, regulations and directories that apply in the countries where the equipment is sold and used.
3. Select hydraulic components so that the application's temperature, pressure and bend radius **do not exceed** recommended component limits.
4. Hose **must not** be stretched, kinked, crushed or twisted during installation or use. Hose **must not** be bent to less than the minimum bend radius.
5. Use **only non-conductive** non-thermoplastic hose for **non-conductive** applications. For instance: cherry pickers. All other Gates hoses are electrically conductive, unless specified otherwise.
6. **DO NOT use standard hydraulic hose to convey gases or steam over 500 PSI. Use only products rated for this service.**
7. **DO NOT use hydraulic hose in place of permanent piping.**

### Follow Good Maintenance Practices

1. **Establish a program** of inspection, testing and replacement of hose assemblies from factors including:
   - Severity of application
   - Frequency of equipment use
   - Past performance of hose assemblies
2. **Only** properly trained persons should inspect, test or service hose assemblies. Update training periodically.
3. **Document** maintenance, inspections and testing.
4. **AVOID FLUID INJECTION INJURIES**
   - Fluid under pressure can cause serious injury. It can be almost invisible escaping from a pinhole, and it can pierce the skin into the body.



   - Do not touch a pressurized hydraulic hose assembly or attempt to find a hydraulic system leak with any part of your body.
   - If fluid punctures the skin, **even if no pain is felt, a serious emergency exists.** Obtain medical assistance immediately. **Failure to do so can result in loss of the injured body part or death.**
5. Stay out of hazardous areas while testing hose assemblies under pressure. **Use proper safety protection.**

## OTHER SAFETY INFORMATION

Many factors affect the selection, crimping, installation and maintenance of hose assemblies. This catalog, Gates Corporation, the hydraulic equipment maker, the Society of Automotive Engineers Recommended Practice SAE J1273 and the International Organization for Standardization Practices for hydraulic hose assemblies ISO 17165-2 have useful information about selecting, crimping, installing and servicing hydraulic hose assemblies. For further information, please contact your local Gates representative or call Gates Corporation.

Gates recommends hose and coupling combinations in this catalog only after completing extensive testing.

Evaluation of a hose and coupling combination requires considerable impulse testing and cannot be determined by a simple burst or pressure hold test. Gates disclaims all liability for any hose assembly made in violation of Gates recommendations, procedures and current crimp data. Crimp data is updated on average every year. For the most up-to-date crimp data, visit our website at www.gates.com/ecrimp.

The consumer's exclusive remedy with respect to any claim shall be a refund of the purchase price or replacement of the product at the option of Gates. In no event shall Gates be liable for any incidental or consequential damages whatsoever.

# TABLE OF CONTENTS


**MegaSys® Hydraulic Hose** ..... A4 - A8
**MXT™ Hose** ..... A9
**Multi Master GMV MegaFlex and Industrial Hose** ... A10
**Abrasion-Resistant Covers** ..... A11
**Couplings** ..... A12 - A14
**LifeGuard® Line-of-Sight Sleeving System** ..... A15
**Training Opportunities** ..... A16
**Website and International Symbols** ..... A17
**Hydraulic Hose and Assemblies Service Life** ..... A18
**Hose Specification Tables**
- Spiral Wire ..... A19 - A31
- Wire Braid ..... A32 - A54
- Thermoplastic ..... A54 - A60
- Transfer ..... A61 - A64
- Return ..... A64 - A67
- Lock-On ..... A67 - A70
- Fleet ..... A70 - A84
- Specialty ..... A85 - A87
- Industrial Hose ..... A87 - A101

**Equipment** ..... B1 - B22
**Selecting the Proper Hose** ..... C1 - C2
**Characteristics of Hose Stock Types** ..... C3
**Gates Hydraulic Hose Selection Guide** ..... C4 - C6
**Additional Temperature Limits for Gates Hydraulic Hose** ..... C7
**Type Approval and Hose Selection Guide** ..... C8
**SAE Recommended Practices for Hydraulic Hose Assemblies** ..... C9 - C11
**Motor Vehicle Safety Standard for Brake Hose** ... C12
**How to Make Hose Assemblies of Specific Lengths** .. C13
**How to Describe Gates Hydraulic Hose Assemblies** .. C14 - C15
**Hose Assembly Routing Tips** ..... C16 - C17
**Installation of LifeGuard® Line-of-Sight Sleeving** .. C18
**Coupling Selection** ..... C19 - C21
**Sealing Types for Hydraulic Couplings** ..... C22 - C24
**Coupling/Thread Identification Tools** ..... C25 - 26
**Thread Chart** ..... C27
**Coupling Identification** ..... C28 - C43
**Gates Global Part Numbering System** ..... C44 - C53
**Coupling/Thread Configurations** ..... C54 - C58
**Chemical Resistance Ratings** ..... C59
**Chemical Resistance Table** ..... C60 - C68
**Nomographic Chart** ..... C69
**Properties of C14 PTFE Tube** ..... C70
**Electrostatic Discharge** ..... C71
**Effusion/Corrosion for PTFE Hose and Hose Assemblies** ..... C72
**Hydraulic System Pressure Drop** ..... C73
**Fahrenheit-Celsius Conversion** ..... C74
**Conversions** ..... C75 - C76
**Tightening and Torque Recommendations for Hydraulic Couplings** ..... C77
**Coupling and Adapter Installation Torque Recommendations** ..... C78
**G8K Couplings** ..... D1 - D3
**GlobalSpiral™ Couplings**
- GlobalSpiral™ Couplings ..... E1 - E50
- GlobalSpiral™ Plus Couplings (GSP) ..... E51 - E67
- GlobalSpiral™ MAX Pressure Couplings (GSM) .. E68 - E84

**Stainless Steel Spiral Couplings** ..... F1 - F6
**MegaCrimp® Couplings** ..... G1 - G55
**Stainless Steel Braid Couplings** ..... H1 - H7
**Power Crimp® Couplings** ..... I1 - I9
**Field Attachable G1 and G2 Couplings** ..... J1 - J8
**Field Attachable C5 Couplings**
- Field Attachable for C5CXH, C5C, C5D & C5M Hose ..... K1 - K13
- Field Attachable for C5E Hose ..... K14 - K21

**C14 Couplings** ..... L1 - L11
**GL Couplings** ..... M1 - M10
**GLX® Couplings** ..... N1 - N5
**PCTS Thermoplastic Couplings** ..... O1 - O3
**PolarSeal® (ACA) Couplings** ..... P1 - P41
**PolarSeal® II (ACC) Couplings** ..... Q1 - Q15
**PolarSeal® II (ACB) Couplings** ..... R1 - R31
**Power Steering Couplings** ..... S1
**Adapters**
- SAE to SAE ..... T1 - T48
- SAE to SAE - High Pressure ..... T49 - T56
- British to SAE ..... T57 - T69
- Metric Conversion ..... T70 - T75
- International to International ..... T76 - T82
- Japanese Conversion ..... T83 - T86
- Ermeto ..... 787 - T88

**Quick Disconnect Couplers**
- G940 Series (Agriculture Standard-Ball Valve) .. U1 - U2
- G940 and G941 Series (Agricultural) ..... U3
- G941 Series (Agriculture Standard-Poppet Valve) . U4
- G942 Series (John Deere Old Style) ..... U5
- G943 Series (International Harvester Old Style) U6
- G944 Series (J.I. Case Old Style) ..... U7



| | |
|---|---|
| WEATHERLY NO. | 400 |
| CATALOG NO. | AUTOMOTIVE 431-2080<br>INDUSTRIAL 35093 |
| EDITION | 2019 |
| SUPERSEDES | 431-2080 (2014)<br>35093 (2015) |

G945 Series (Industrial ISO 7241-1 - Series B) U8 - U9
G949 Series (Flush Face - HTMA)..... U10 - U13
G950 Series (Flush Face - High Pressure) ..... U14 - U15
G951 Series (Wing Nut) ..... U16 - U17
G952 Series (High Pressure Wing Nut)..... U18 - U19
G953 Series (Very High Pressure)..... U20
G956 Series (Industrial ISO 7241 - Series A).. U21 - U22
G959 Series (Agriculture QD Adapters) ..... U23 - U24

**Ball Valves**
Two Way Block Style ..... V1 - V2
Two Way Round Style Large ID ..... V3
Three Way Block Style ..... V4

**Live Swivels**..... W1 - W5

**Assembly Fabrication** ..... X1 - X7

**Accessories**
Nylon Protective Sleeve ..... Y1 - Y3
Hose Guards ..... Y4 - Y6
HeatGuard® ..... Y7 - Y8
Gates OE-Style Clamp Collars ..... Y9
Vinyl Bend Restrictor..... Y10
Flange Fittings ..... Y11 - Y13
O-Rings ..... Y14 - Y16
Tube Nuts and Sleeves..... Y17 - Y20
Diagnostic Equipment..... Y21

**Equipment and Parts**..... Z1 - Z4

**Kits**..... ..... AA1 - AA6

**Air Brake Hose Assembies**..... AB1 - AB3

**Brass**
Air Brake Couplings for Rubber Hose ..... AC1 - AC6
Brass Lock-On Field Attachable Couplings for LOC & LOL Hose ..... AC7 - AC15
Single Bead..... AC16 - AC20
Barb Stem..... AC21 - AC23

**Index**..... ..... i - lii

**GATES CORPORATION LIMITED LIFETIME WARRANTY**

Gates Corporation ("Gates") product is warranted to be free from defects in material or workmanship for the life of the product (or the published recommended replacement interval specified by Gates.) Gates will, at its option, replace or repair any merchandise proved defective in material or workmanship during the warranty period. In no event will Gates honor any warranty claim unless it is notified of the claim within six (6) months of the expiration of the warranty period. This shall be the sole remedy for breach of warranty.

Damage to the product due to abuse, misuse, improper use, inadequate maintenance, or failure to follow published installation, use and service recommendations automatically voids this warranty. For warranty service, please contact the Customer Service Department of Gates Corporation, 1144 15th Street, Suite 1400, Denver, CO 80202

**ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE HEREBY EXPRESSLY DISCLAIMED. IN NO EVENT WILL GATES BE LIABLE TO ANY PARTY FOR CONSEQUENTIAL, INCIDENTAL, SPECIAL, EXEMPLARY AND INDIRECT DAMAGES, INCLUDING BUT NOT LIMITED TO LOST PROFITS, REGARDLESS OF WHETHER SUCH DAMAGES WERE REASONABLY FORESEEABLE, OR WHETHER GATES HAD KNOWLEDGE THAT THEY COULD OCCUR.**

Some states do not allow the exclusion or limitation of incidental or consequential damages, and some states do not allow limitations on how long an implied warranty lasts, so the above limitation and exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

# INTERNATIONAL SYMBOLS USED IN CATALOG COLUMN HEADINGS

| DESCR | Description |
|---|---|
|  | **Hose/Tube Inside Diameter (I.D.)** |
|  | **Hose/Tube Outside Diameter (O.D.)** |
|  | **Thread Size** |
|  | **Working Pressure (psi)** |
|  | **Minimum Burst Pressure (psi)** |
|  | **Minimum Bend Radius** |
|  | **Vacuum** |

| | |
|---|---|
| **A** | **Hose/Tube Diameter** |
| **C** | **Cut-Off** |
| **F** | **Flange Head Thickness** |
| **H1** | **Stem Hex** |
| **H2** | **Nut Hex** |
| **L** | **Length** |
| **M** | **Flange Diameter** |
| **T** | **Drop** |




**As advanced hydraulic systems are designed and engineered into more and more high-powered, high-pressure equipment, the importance of high-quality, flexible, durable hose assemblies that won't fail has never been more critical.**

As the industry leader in hydraulic hose technology, Gates has developed an integrated solution to meet the expanding needs of today's hydraulic systems – and tomorrow's.

Gates MegaSys® hydraulic hose and coupling products offer a combination of technology, performance and flexibility that is unmatched by anything on the market today – or for the foreseeable future!

The fully integrated MegaSys hose line is designed to provide maximum flexibility and performance in a wide range of high-pressure hydraulic applications while simplifying hose selection and assembly fabrication.

MegaSys products and features save time, space and money. Color-coded laylines and constant pressure ratings through all sizes make hose identification and selection easier and faster while reducing inventory requirements. Couplings provide leak-free performance. A bend radius up to one-third the SAE specification enables use of shorter hose lengths and savings of up to 64%. It all adds up to more value for your money.

# CONSTANT PRESSURE HOSE

The MegaSys® line consists of constant pressure spiral-wire and wire-braid hose that can be bent up to one-third SAE specifications. Combined with innovative couplings specifically designed to crimp on these hose, leak-free performance is guaranteed up to maximum working pressures as high as 8,000 psi.

### MegaSys Benefits

- Simplifies hose selection with constant pressure ratings
- Bends up to one-third SAE bend radius specifications
- Saves overall hose assembly length
- Facilitates easier routing in tight applications
- Requires fewer bent tube fittings
- Eases installation with higher flexibility
- Lowers inventory requirements
- Extends life in bending, flexing applications
- Available with abrasion-resistant XtraTuff® or MegaTuff® covers
- Reduces costs by as much as 64 percent



# MEGASYS® HOSE LAYLINE SYSTEM

These newly developed laylines are used exclusively on MegaSys® hose. Distinctive design and pressure color coding makes MegaSys hose easy to identify in stock or in service.




**Field 1**
Gates Logo

**Field 2**
Registered Product Family Name

**Field 3**
Hose Description
3,000 psi = Blue
4,000 psi = Purple
5,000 psi = Red
6,000 psi = Orange
8,000 psi = Gold


**Field 4**
Coupling Icon
G = MegaCrimp®
GS = GlobalSpiral™
GSP = GlobalSpiral™ Plus

**Field 5**
Size/Pressure

**Field 6**
Industry Specifications

**Field 7**
MSHA Approval

# MEGASYS HOSES BEND, BEND – AND BEND SOME MORE




**Up to One-Third SAE Bend Radius Specification**

Illustration of 16M3K hose flexibility and reduced hose length requirements

# MEGASYS® SPIRAL-WIRE CONSTANT PRESSURE HOSE

### EFG3K, EFG4K, EFG5K, EFG6K and G8K Hoses

- Each hose features a constant working pressure
- Four alternating layers (six in some larger sizes) of spiraled, high-tensile steel
- Nitrile tube for use with biodegradable hydraulic fluids (Polychloroprene for G8K)
- Tested to industry-leading 1,000,000 impulse cycles
- Temperature range -40°F to +250°F (-40°C to +121°C)
- Available with abrasion-resistant XtraTuff® or MegaTuff® cover
- "L" Versions -70°F to +212°F (-57°C to +100°C)

**MegaSys Hose Pressure Color Key**

| | |
|---|---|
| 3000 psi | M3K/EFG3K |
| 4000 psi | M4K/EFG4K |
| 5000 psi | M5K/EFG5K |
| 6000 psi | M6K/EFG6K |
| 8000 psi | G8K |















# MEGASYS® WIRE-BRAID CONSTANT PRESSURE HOSE

### M3K, M4K, M5K and M6K Hoses

- Each hose features a constant working pressure
- Two braids of high-tensile steel wire (one braid in M3K -3, -4, -5, -6 and -8 sizes)
- Nitrile tube for use with biodegradable hydraulic fluids
- Tested to industry-leading 600,000 cycles
- Temperature range -40°F to +212°F (-40°C to +100°C)
- Available with abrasion-resistant XtraTuff® or MegaTuff® covers
- "H" Versions -40°F to +250°F (-40°C to +121°C)
- "L" Versions -70°F to +212°F (-57°C to +100°C)

**MegaSys Hose Pressure Color Key**

| | |
|---|---|
| 3000 psi | M3K/EFG3K * |
| 4000 psi | M4K/EFG4K |
| 5000 psi | M5K/EFG5K |
| 6000 psi | M6K/EFG6K |

* M3K working pressure = 3250 psi














Gates revolutionized hose selection with the introduction of MegaSys® hoses. Use the charts below for easy hose selection. Just find the required pressure and the chart will show you which hose meets that pressure in the applicable size.

## SAE Specifications (Chart colors do not correspond to MegaSys hose color key system)




Exceeds SAE 100R1
Exceeds SAE 100R2
Exceeds SAE 100R12
Exceeds SAE 100R13
Exceeds SAE 100R15
*M3K Exceeds SAE 100R17
**M4K Exceeds SAE 100R19
**Note:** M3K working pressure = 3250 psi

## European Norm (EN) Specifications (Chart colors do not correspond to MegaSys hose color key system)




Exceeds 1SN/1SC
Exceeds 2SN/2SC
Exceeds 4SP
Exceeds 4SH

# MegaSys® Constant Pressure Hose and ISO 18752

The progression of the Gates MegaSys® products spans over three decades, beginning in the 1980's with the innovative SAE half-bend radius MegaFlex® products M2T® and M1T (now M3K). Gates MegaSys evolved to Constant Pressure specifications and was the forerunner that drove SAE, EN and ISO to follow the Gates engineering lead.

ISO Standard 18752 released in 2006, differs from SAE J517 that reflects the design practices of users who construct hydraulic systems based on performance and pressure requirements.


ISO 18752 is the International Standard specifying requirements for nine classes, four grades and seven types of wire- or textile-reinforced hydraulic hoses and hose assemblies of nominal sizes. Each class has a single maximum working pressure for all sizes.

Hoses are classified according to their resistance to impulse into four grades: A, B, C and D. Each grade is classified by outside diameter into standard types (AS, BS and CS) and compact types (AC, BC, CC and DC).

The MegaSys products exceed the SAE and EN specifications and are aligned and exceed the performance matrix requirements of ISO 18752.

| PSI | 18752 ISO A | 18752 ISO B | 18752 ISO C | 18752 ISO D |
|---|---|---|---|---|
| 3000 PSI | M3K* | M3K | M3KH | EFG3K |
| 4000 PSI | M4K* | M4K | M4KH | EFG4K |
| 5000 PSI | M5K* | M5K | EFG5K | EFG5K |
| 6000 PSI | M6K* | M6K | EFG6K | 12EFG6K |

* Exceeds cycle requirements by 2.5X




# Features + Benefits

- Patent-pending in the U.S.
- Proprietary application of materials science and processing technology
- More flexible with lower force-to-bend for faster and more ergonomic installation
- Lighter weight for easier handling
- Tested to 3 times impulse criteria (600,000 cycles)
- Consolidate inventory with a universal, multi-use hose
- Compatible with MegaCrimp® Couplings and Gates Crimpers

# INTRODUCING MULTI MASTER® GMV™ MEGAFLEX®



## ONE HOSE. FOUR USES. ULTIMATE FLEXIBILITY.

One hose engineered for four industrial applications: fuel, hydraulic return, coolant, and water, Gates Multi Master® GMV™ MegaFlex® delivers superior performance and ultimate flexibility.

We believe operating challenges are made to be overcome. That's why thousands of industrial facilities, global operations, and OE manufacturers around the world choose Gates hose and hydraulic systems to power their most demanding fluid power applications.

### MULTI-USE HOSE WITH SUPERIOR PERFORMANCE.


### FEATURES + BENEFITS

| | |
|---|---|
| One multi-use hose that meets SAE 100R4, J30R5, J20R5* (*except tube dimensions) | Consolidate inventory and meet global requirements |
| Industry-leading flexibility | Solves complex routings through tight spaces using less hose |
| Easy installation with 1:1 bend radius | Time saving and kink free |
| Light weight and ergonomic | Easy handling with lower risk of strain |
| ARPM Class A Tube | Provides maximum oil resistance |
| Sizes range from 3/4" to 6" and working pressures 150 to 350psi | Superior performance for multiple applications |
| MSHA approved cover | Flame resistant for critical and mining applications |

## INDUSTRIAL HOSE

New to the hydraulic Catalog is a select group of Industrial Hoses. These are common hoses in all types of industry from mobile to stationary and can be crimped with hydraulic couplings to increase inventory flexibility. Please refer to your local sales representative for pricing questions.

For a full range of Industrial Hose see the Industrial Hose, Couplings and Equipment catalog (39496-000).




# MEGATUFF® AND XTRATUFF® COVERS

Nothing is harder on hydraulic hose covers than constant abrasion. Rubbed against metal or other hose, most standard hydraulic hoses – even ones with spring guards or nylon sleeving – can't take the punishment.

There's no industry standard for hose cover performance. Historically, Gates leads the pack in establishing engineering specs, and hose covers are no exception.

## JUDGE US BY OUR COVERS







## MegaTuff®

Gates MegaTuff hoses are exceptionally resistant to abrasion. The specially bonded cover stays put and won't peel as some competitive hose covers do.


- Maintain flexibility and minimum bend radius
- Resistant to oil, ozone and UV rays
- Tested to 1,000,000 ISO6945 metal-to-hose rubbing cycles without failure




## XtraTuff®

Made of special hybrid compounds, Gates XtraTuff covers are versatile, flexible and easy to manage.

- Increase service life
- Lower maintenance
- Eliminate the need for costly hose protectors
- Lower installation friction



# SOLID, LEAK-FREE COUPLINGS

**The majority of hydraulic hose failures occur at the couplings due to blow-offs or leaks. Gates has designed and engineered innovative, robust couplings for MegaSys hose that provide connections you can count on for superior performance – guaranteed.**

## MegaCrimp® Couplings G25





**Key Features**

- Robust “bite-the-wire” crimp
- Low profile
- Full-stem insertion
- Full-length crimp
- Tested to an industry-leading 1 million impulse cycles
- Simplifies inventory management
- TuffCoat® plating for 347% better corrosion resistance SAE Standard

**MegaCrimp - The Versatile “No-Weep” Coupling with the Patented “C” Insert**

It’s what’s inside the pre-assembled MegaCrimp® coupling that gives it world-class, leak-proof performance. It is designed with a patented “C” insert, attached to the ferrule, that accommodates hose of different constructions and wall thicknesses. The insert’s design ensures crimping forces are evenly distributed to form a concentric seal.

The “C” insert simplifies inventory requirements since one MegaCrimp coupling size can accommodate various hose outside diameters, on both one- and two-wire braid hydraulic hose.

## GlobalSpiral™ Couplings G20



**Key Features**

- “Bite-the-wire” crimp for improved coupling retention
- Over 90 thread configurations
- Tested to an industry-leading 1,000,000 impulse cycles
- 6,000 psi working pressure for easy to manage inventory
- +250˚F temperature capability for longer assembly life
- TuffCoat® plating for 347% better corrosion resistance SAE Standard
- Qualified on wire braid hoses for maximum inventory coverage

**GlobalSpiral Couplings No-Skive Convenience, Reduced Inventory**

GlobalSpiral™ couplings are specially engineered to provide superior performance for extreme high-pressure, high-impulse spiral-wire hydraulic hose applications. They can be used with all Gates MegaSys® four- and six-spiral wire hose up to 6,000 psi.

The innovative, two-piece, no-skive design reduces assembly time, labor, fabrication errors and contamination of the fluid power system. The work area stays clean, and the odors, dust, and fire hazard normally created by skiving are eliminated. In addition, the two-piece design reduces parts inventory by 30 percent because only one stem is required for all spiral-wire hose types.

# TUFFCOAT® AND TUFFCOAT® XTREME™ PLATING

### Up to 583% Better than the 144-Hour SAE Standard

Just as hoses need a rubber cover to protect the metal reinforcement inside, hydraulic couplings need plating to prevent deterioration of the metal. When hydraulic fittings begin to rust, the base metal is being eaten away by oxidation.

Red rust can eventually damage a hydraulic system in several ways:

- Contaminate hydraulic fluids
- Compromise fitting connections and adjacent components
- Create leak paths
- Make maintenance more difficult


TuffCoat® plating sets the global standard for corrosion resistance. Gates has removed all hexavalent chromium from its plating process. This metal, common in industrial plating, is toxic to the environment. Gates engineered TuffCoat plating to be stronger and more resistant to corrosion, without the toxicity of hexavalent chromium.

### TuffCoat: One Tough Plating for All Gates Standard Couplings

All Gates couplings are protected, at the minimum, with TuffCoat plating. In ASTM B117 salt spray tests, TuffCoat plating resisted red rust formation for 500 hours. That's nearly 347% greater than the SAE 144-hour standard.


### TuffCoat XTreme: An Extra Measure of Protection


TuffCoat XTreme offers 840 hours of red rust corrosion resistance based on ASTM B117 salt spray testing. That's 583% greater than the SAE 144-hour standard.



# FULL-TORQUE NUT™ TECHNOLOGY

### Over-Torque Protection




One of the most common causes of hydraulic leaks is a cracked coupling nut or seat due to over-torque.

Gates has engineered a solution – Full-Torque Nut™ technology which is standard on all MegaCrimp® and GlobalSpiral™ couplings.

Full-Torque Nut couplings are stronger and more durable than traditional staked-nut fittings.
A large holding shoulder evenly distributes stress forces at the nut for higher resistance against cracking, even when inadvertently over-torqued. Increase equipment uptime by eliminating damaged couplings and leaks from too much torque.

# INTERNATIONAL AND NORTH AMERICAN THREAD IDENTIFICATION KITS

### Identifying Thread Styles is Easier Than Ever



**North American Thread ID Kit**
**Part Number:** 70270
**Product Number:** 7369-0016

Kit includes carrying case, 45 anodized aluminum gauges sized from 1/8–27 to 2-1/2–12 for pipe and 5/16–24 to 2-1/2–12 for UN/UNF threads, male and female. Also includes pocket thread ID kit.

**International Thread ID Kit**
**Part Number:** 70264
**Product Number:** 7369-0015

Being able to identify metric and British hydraulic couplings is essential, as sales growth of these couplings continues to outpace sales growth of couplings with more traditional North American thread types. Includes 21 metric and 10 British thread gauges, male and female. Also includes carrying case and pocket thread ID kit.

See pages C24 and C25 for additional coupling and thread identification tools.

# THERE'S A BETTER WAY TO PROTECT EQUIPMENT OPERATORS AGAINST HYDRAULIC HOSE FAILURE.

A burst or pinhole leak in a hydraulic system can cause serious problems – especially for anything or anyone located within a three-foot line-of-sight. Personal injury. Fluid burns and injection. Fires and explosions. Electrical shock. Mechanical failure.

Now, Gates has engineered the first effective, economical alternative to costly metal shielding or rerouting of hose lines. The LifeGuard® sleeving system is designed to protect operators, equipment and the environment from the hazards of catastrophic hydraulic hose failure – a level of protection previously unavailable.




**LIFEGUARD SLEEVE** **HOSE ONLY** **LIFEGUARD SLEEVE** **HOSE ONLY**



The LifeGuard sleeve contained and effectively redirected fluid during 10,000 psi (68.9 MPa) burst tests while hose without sleeving exploded, releasing a large amount of fluid in the immediate area.

### How the System Works

The LifeGuard sleeve is slipped onto the hose and clamped at each end. If a hose burst or pinhole leak occurs, escaping pressures and fluids are contained by the exceptionally strong sleeving material. Fluids then exit the system via openings created by the specially designed channel clamps at each end. A noticeable pool of leaking fluid serves as positive verification that a failure has occurred so corrective action can be taken immediately to replace the hose assembly. LifeGuard sleeving correlates to a variety of industry standards, including ISO 3457 and MSHA's flame-resistance requirements.

- Provides containment of up to 10,000 psi (68.9 MPa) bursts
- Protects against 5,000 psi (34.5 MPa) pinhole leaks at +212°F (+100°C) for up to five minutes
- Handles hydraulic fluids and biodiesel fuel
- Allows fluid to safely escape down the length of the assembly
- Creates noticeable spill for hose failure detection
- Correlates to ISO 3457 and meets MSHA's flame-resistance requirements
- No other sleeve provides this level of protection
- Patented system includes Gates hose, couplings, sleeve and channel clamps


# GATES CUSTOMER SOLUTIONS CENTER

Fluid Power Workshops

The Gates Customer Solutions Center (CSC) in Englewood, Colorado is a state-of-the-art facility dedicated to leading the industry in customer-focused product development and training in fluid power technology. Staffed by over 80 of the top engineers, scientists and technicians in the industry, the facility is headquarters for understanding and meeting customers fluid power needs.

# TRAINING WORKSHOPS FOR SALES ASSOCIATES AND YOUR CUSTOMERS

Gates Replacement market division is offering Hydraulic Training classes to help counter personnel, store managers, technicians and outside sales people increase their hydraulic knowledge to help grow business. Classes will be held at the Gates Customer Solutions Center (CSC). The sessions will combine comprehensive classroom training with individual hands-on activities and group problem solving projects.







# CLASS INFORMATION

**Contact your local Gates representative for more information.**

**Topics to be covered:**

- Identify key components of a typical hydraulic system and explain their function
- Understand basic safety issues associated with hydraulic systems
- Duplicate existing hydraulic assemblies using the S.T.A.M.P.E.D. procedure
- Inspect systems for problematic hose routing and identify potential hose failures
- Hands-on assembly fabrication and coupling identification
- Identify accessories that prolong the life of hose and couplings
- Learn about hoses and couplings found outside of traditional hydraulic systems

Attendees will be given a tour of the Gates Customer Solution Center.

# CUSTOM PROGRAMS

Let us design a program specifically for your company's needs. We can design courses to cover equipment, safety, sales, basic knowledge and much more – we are ready to help your employees become hydraulic product experts.

# GET CONNECTED – VISIT OUR WEBSITE

**With technology expanding at ever increasing rates, get the most up-to-date information from our website.**

Check out what's new at www.gates.com

**Features to look for:**

- New product announcements
- Updated hydraulic information
- Electronic product literature
- Email updates on new products and promotions
- Downloadable catalogs: www.gates.com/catalogs
- Electronic crimp data: www.gates.com/ecrimp
- Safety training: www.gates.com/safehydraulics
- Gates rep and distributor locator: www.gates.com/contact

**Product Application Engineers**

Technical Questions on Products

303-744-5070

fppasupport@gates.com

**Account Representatives**

Fluid Power Customer Service

800-366-3128 - Industrial

800-678-4143 - Automotive

# INTERNATIONAL SYMBOLS USED IN CATALOG COLUMN HEADINGS

| DESCR | Description |
|---|---|
|  | **Hose/Tube Inside Diameter (I.D.)** |
|  | **Hose/Tube Outside Diameter (O.D.)** |
|  | **Thread Size** |
|  | **Working Pressure (psi)** |
|  | **Minimum Burst Pressure (psi)** |
|  | **Minimum Bend Radius** |
|  | **Vacuum** |

| | |
|---|---|
| **A** | **Hose/Tube Diameter** |
| **C** | **Cut-Off** |
| **F** | **Flange Head Thickness** |
| **H1** | **Stem Hex** |
| **H2** | **Nut Hex** |
| **L** | **Length** |
| **M** | **Flange Diameter** |
| **T** | **Drop** |

# Crimp with the Precision of Gates

**Quickly Find Hose and Hydraulic Crimp Specifications**

Gates eCrimp® database allows Gates end users and distributors to find and print the most up-to-date crimp specifications for Gates hydraulic and industrial hose products. It provides crimping instructions, crimp diameter, maintenance and troubleshooting information for all Gates crimpers.

**eCrimp:**

- Reduces downtime with hose assembly guides
- Eliminates potential dangers of an improperly crimped hose
- Quickly and easily finds exact crimping specifications from your browser
- Allows you to create custom reports around the products which you use most

Go to gates.com/ecrimp for more information on the web version and mobile app.

# GETTING THE BEST SERVICE LIFE FROM GATES HYDRAULIC HOSE AND ASSEMBLIES

How long will a hydraulic hose assembly last? It depends on how it's used. This catalog and other Gates literature show the recommended limits for our assemblies (and also the hose and couplings used to make assemblies). These limits include installation, maintenance, and conditions of use. These limits MUST be followed or the assembly can fail resulting in personal injury or property damage. If you do not have this important information, you can get it at no cost from your local Gates distributor or Gates field representative.

Hose assemblies in use should be inspected regularly for leaks, kinks, cover blisters, gouges, abrasion and other damage. Damaged or worn assemblies must be replaced immediately. You can increase assembly life if you do the following:

**Hose Assembly Installation[1] –** Hydraulic hose assembly installations should comply with hydraulic hose routing and plumbing standards per SAE J1273 for the proper application of hose assemblies. SAE J1273 recommended practices can be found in this catalog.

**Working Pressure –** The hydraulic system pressure should not exceed the rated working pressure of the hose. Pressure surges or peaks exceeding the rated working pressure are destructive and must be taken into account when selecting a hose.

**Minimum Burst Pressure –** Burst pressures are pressures referred to in this catalog which were intended for destructive testing purposes and for design safety factors only.

**Temperature Range[2] –** Do not expose hose to internal or external temperatures exceeding the recommended limits. Consult additional technical data when hydraulic fluids contain emulsions or solutions. The fluid manufacturer's recommended maximum operating temperature for any given fluid must not be exceeded, regardless of hose temperature range.

**Fluid Compatibility –** The hydraulic assembly (tube, cover, reinforcement and couplings) must be fluid compatible. The correct hose must be used because phosphate ester and petroleum-based hydraulic fluids have drastically different chemical characteristics. Many hose are compatible with one or the other, but not all fluids. For example, Gates G2XH, MegaTech® and C5D hose are capable of handling phosphate ester and petroleum-based hydraulic fluids.

**Minimum Bend Radius –** Do not bend or flex hose to a radius smaller than the minimum recommended and do not subject hose to tension or torque. This can place excessive stress on the reinforcement and severely reduce the ability of the hose to withstand pressure.

**Hose Size –** Hose size (inside diameter) must be capable of handling the required flow volume. Too small an I.D. for a given volume of flow results in excessive fluid pressure and heat generation which can result in tube damage.

**Hose Routing –** Restrain, protect or guide hose, with clamps if necessary, to minimize the risk of damage due to excessive flexing, whipping or contacting other moving parts or corrosives. Determine hose lengths and configurations that protect from abrasion, snagging or kinking and provide leak-resistant connections.

**Hose Length –** Correct hose length should include considerations for length changes under pressure, machine vibration and motion, and hose assembly routing.

**Hose Applications –** Select the proper hose for the application. Suction applications (Gates GMV or G4H) and special fluid or high temperature capabilities are among the applications requiring particular consideration and a specific hose. When additional information is required, contact your local Gates representative.

**NOTE:** Do not use Gates hydraulic hose in place of permanent piping.

**Hose Shelf Life**

Storage environment, along with rubber materials can vary the shelf life limit. Shelf life is difficult to quantify as many variables affect the hose. Proper storage precautions can result in three to five years shelf life. Beyond this time there can be a significant service life decrease, depending on storage environment variables. Some variables include:

- Temperature – Hose should be stored in a cool, dry area never exceeding +100°F (+38°C). If stored below freezing, pre-warming may be required prior to handling, testing and placing into service.
- Direct sunlight, rain, heaters or being near electrical equipment
- Humidity and ozone
- Oil, solvents, corrosive materials or fumes
- Insects or rodents
- Radioactivity
- Space allowance and bends

Store hose in original container. Never stack hose too high, as its weight can crush hose at the bottom of the stack.

Gates recommends hose in extended storage be visually inspected and tested prior to use. Hose judged marginal should be replaced to avoid potential failure, property damage or bodily injury. Store hose on a first-in/first-out basis. Unusually long storage, or poor storage environment can deteriorate hose, reduce performance and may lead to premature failure.

1 SAE provides helpful video and print information that supplements this summary. Contact SAE at 1-877-606-7323 or at www.sae.org.

2 Actual service life at temperatures approaching the recommended limit will depend on the particular application and the fluid being used in the hose. Intermittent (up to 10 percent of operating time) refers to momentary temperature surges. Detrimental effects increase with increased exposure to elevated temperatures.

## G8K SPIRAL WIRE HOSE

### SPIRAL WIRE




| | |
|---|---|
| RECOMMENDED FOR | Ultra high–pressure, high–impulse applications such as hydrostatic transmissions, for use in the construction, agriculture, forestry, underground or open–pit mining, or other industries on applications where extremely high–pressure capability is required. G8K hose and couplings offer industry–leading bend radius capability, which leads to ease of routing and installation, longer hose life in flexing applications, and fewer bent tube fitting requirements. |
| TUBE | Black, oil resistant Polychloroprene tube material allows for the high pressure, high temperature performance required in these demanding applications. See Hose Stock Characteristics. |
| REINFORCEMENT | Six alternating layers of high–tensile steel wire spiral construction. |
| COVER | Black, oil resistant, synthetic rubber (Polychloroprene), with color coded layline. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | G8K Couplings (G19) Section D<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 71096 | 12G8KXCTN | 4651-1639 | 100 | 3/4 | 1.36 | 8000 | 32000 | 9.5 |
| 71097 | 16G8KXCTN | 4651-1631 | 100 | 1 | 1.66 | 8000 | 32000 | 12.0 |

## EFG6K SPIRAL WIRE HOSE - SAE 100R15

### SPIRAL WIRE




| | |
|---|---|
| RECOMMENDED FOR | Extremely high–pressure, high–impulse applications such as hydrostatic transmissions. EFG6K is designed to meet or exceed all requirements of SAE 100R15 specifications and performance requirements of EN 856 4SP (–6, –8, –10 and –12), EN 856 4SH (–12, –16, and –20) and ISO 3862 Type R15 (–6, –8, –10, –12, –16, –24). Compatible with biodegradable hydraulic fluids like polyolester, polyglycol and vegetable oil as well as standard petroleum–based fluids. Available in 121' through 200' continuous lengths. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Four (six for –20, –24 and –32) alternating layers of spiraled, high–tensile steel. |
| COVER | Black, oil resistant, synthetic rubber (Polychloroprene), with color coded layline. Also available with unique abrasion resistant MegaTuff® cover. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (G20) Section E<br>GlobalSpiral™ MAX Pressure Couplings (–24 = G24), (–32 = G23) Section E<br>Stainless Steel Spiral Couplings (–6 through –20) (G18) Section F<br>(See Crimp Data Manual 428–7365 or eCrimp) |

For Biodegradable Hydraulic Fluids. Meets Flame Resistance Acceptance Designation "MSHA 2G". Tested to Industry Leading 1,000,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85465 | 6EFG6K X25FT | 4651-4032 | 1 | 3/8 | .80 | 6000 | 24000 | 2.5 |
| 70404 | 6EFG6KX100REEL | 4651-5028 | 100 | 3/8 | .80 | 6000 | 24000 | 2.5 |
| 70866 | 6EFG6KXCTN | 4651-1396 | 100 | 3/8 | .80 | 6000 | 24000 | 2.5 |
| 70163 | 6EFG6KXREEL | 4651-0123 | 300 | 3/8 | .80 | 6000 | 24000 | 2.5 |

## EFG6K SPIRAL WIRE HOSE - SAE 100R15 - CONTINUED

### SPIRAL WIRE - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85466 | 8EFG6K X25FT | 4651-4033 | 1 | 1/2 | .95 | 6000 | 24000 | 3.5 |
| 70405 | 8EFG6KX100REEL | 4651-5029 | 100 | 1/2 | .95 | 6000 | 24000 | 3.5 |
| 70865 | 8EFG6KXCTN | 4651-1371 | 100 | 1/2 | .95 | 6000 | 24000 | 3.5 |
| 70978 | 8EFG6KXLL | 4651-1613 | 200 | 1/2 | .95 | 6000 | 24000 | 3.5 |
| 70164 | 8EFG6KXREEL | 4651-0124 | 240 | 1/2 | .95 | 6000 | 24000 | 3.5 |
| 85467 | 10EFG6K X25FT | 4651-4034 | 1 | 5/8 | 1.09 | 6000 | 24000 | 4.0 |
| 70815 | 10EFG6KXCTN | 4651-1368 | 100 | 5/8 | 1.09 | 6000 | 24000 | 4.0 |
| 70735 | 10EFG6KXLL | 4651-1397 | 200 | 5/8 | 1.09 | 6000 | 24000 | 4.0 |
| 70165 | 10EFG6KXREEL | 4651-0125 | 200 | 5/8 | 1.09 | 6000 | 24000 | 4.0 |
| 85468 | 12EFG6K X25FT | 4651-4035 | 1 | 3/4 | 1.24 | 6000 | 24000 | 4.7 |
| 70839 | 12EFG6KXCTN | 4651-1288 | 100 | 3/4 | 1.24 | 6000 | 24000 | 4.7 |
| 70736 | 12EFG6KXLL | 4651-1398 | 200 | 3/4 | 1.24 | 6000 | 24000 | 4.7 |
| 70168 | 12EFG6KXREEL | 4651-0128 | 200 | 3/4 | 1.24 | 6000 | 24000 | 4.7 |
| 85469 | 16EFG6K X25FT | 4651-4036 | 1 | 1 | 1.53 | 6000 | 24000 | 6.0 |
| 70836 | 16EFG6KXCTN | 4651-1289 | 100 | 1 | 1.53 | 6000 | 24000 | 6.0 |
| 70737 | 16EFG6KXLL | 4651-1399 | 200 | 1 | 1.53 | 6000 | 24000 | 6.0 |
| 85470 | 20EFG6K X25FT | 4651-4037 | 1 | 1 1/4 | 1.97 | 6000 | 24000 | 8.2 |
| 70837 | 20EFG6KXCTN | 4651-1290 | 50 | 1 1/4 | 1.97 | 6000 | 24000 | 8.2 |
| 70738 | 20EFG6KXLL | 4651-1400 | 200 | 1 1/4 | 1.97 | 6000 | 24000 | 8.2 |
| 85426 | 24EFG6K X25FT | 4651-1574 | 1 | 1 1/2 | 2.26 | 6000 | 24000 | 10.0 |
| 71065 | 24EFG6KXCTN | 4651-1531 | 50 | 1 1/2 | 2.26 | 6000 | 24000 | 10.0 |
| | 24EFG6KXLL | 4651-1572 | 200 | 1 1/2 | 2.26 | 6000 | 24000 | 10.0 |
| 71100 | 32EFG6KXCTN | 4651-1759 | 50 | 2 | 2.80 | 6000 | 24000 | 25.0 |
| 71099 | 32EFG6KXLL | 4651-1758 | 200 | 2 | 2.80 | 6000 | 24000 | 25.0 |

# EFG6K SPIRAL WIRE HOSE - SAE 100R15 - MEGATUFF® COVER

## SPIRAL WIRE




| | |
|---|---|
| RECOMMENDED FOR | Extremely high–pressure, high–impulse applications such as hydrostatic transmissions. EFG6K is designed to meet or exceed all requirements of SAE 100R15 specifications and performance requirements of EN 856 4SP (–6, –8, –10 and –12), EN 856 4SH (–12, –16, and –20) and ISO 3862 Type R15 (–6, –8, –10, –12, –16, –24). Compatible with biodegradable hydraulic fluids like polyolester, polyglycol and vegetable oil as well as standard petroleum–based fluids. Available in 121' through 200' continuous lengths. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Four (six for –20, –24 and –32) alternating layers of spiraled, high–tensile steel. |
| COVER | Black, oil, abrasion and weather resistant MegaTuff® cover with color coded layline. Also available in Standard cover. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (G20) Section E<br>GlobalSpiral™ MAX Pressure Couplings (–24 = G24), (–32 = G23) Section E<br>Stainless Steel Spiral Couplings (–6 through –20) (G18) Section F<br>(See Crimp Data Manual 428–7365 or eCrimp) |

For Biodegradable Hydraulic Fluids. Meets Flame Resistance Acceptance Designation "MSHA 2G". MegaTuff® hose lasts up to 300 times longer than standard hose during hose–to–hose and hose–to–metal abrasion tests per ISO 6945. Tested to Industry Leading 1,000,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85471 | 6EFG6K-MTF X25FT | 4651-4038 | 1 | 3/8 | .80 | 6000 | 24000 | 2.5 |
| 70849 | 6EFG6K-MTFXCTN | 4651-1435 | 100 | 3/8 | .80 | 6000 | 24000 | 2.5 |
| 85472 | 8EFG6K-MTF X25FT | 4651-4039 | 1 | 1/2 | .95 | 6000 | 24000 | 3.5 |
| 70867 | 8EFG6K-MTFXCTN | 4651-1609 | 100 | 1/2 | .95 | 6000 | 24000 | 3.5 |
| 85473 | 10EFG6K-MTF X25FT | 4651-4040 | 1 | 5/8 | 1.09 | 6000 | 24000 | 4.0 |
| 70880 | 10EFG6K-MTFXCTN | 4651-1416 | 100 | 5/8 | 1.09 | 6000 | 24000 | 4.0 |
| 85474 | 12EFG6K-MTF X25FT | 4651-4041 | 1 | 3/4 | 1.24 | 6000 | 24000 | 4.7 |
| 70868 | 12EFG6K-MTFXCTN | 4651-1606 | 100 | 3/4 | 1.24 | 6000 | 24000 | 4.7 |
| 85475 | 16EFG6K-MTF X25FT | 4651-4042 | 1 | 1 | 1.53 | 6000 | 24000 | 6.0 |
| 70869 | 16EFG6K-MTFXCTN | 4651-1604 | 100 | 1 | 1.53 | 6000 | 24000 | 6.0 |
| 85476 | 20EFG6K-MTF X25FT | 4651-4043 | 1 | 1 1/4 | 1.97 | 6000 | 24000 | 8.2 |
| 70870 | 20EFG6K-MTFXCTN | 4651-1601 | 50 | 1 1/4 | 1.97 | 6000 | 24000 | 8.2 |
| | 20EFG6K-MTFXLL | 4651-0013 | 121 | 1 1/4 | 1.97 | 6000 | 24000 | 8.2 |
| 70991 | 24EFG6K-MTFXCTN | 4651-1754 | 50 | 1 1/2 | 2.26 | 6000 | 24000 | 10.0 |
| | 24EFG6K-MTFXLL | 4651-1755 | 200 | 1 1/2 | 2.26 | 6000 | 24000 | 10.0 |
| 71098 | 32EFG6K-MTFXCTN | 4651-1757 | 50 | 2 | 2.80 | 6000 | 24000 | 25.0 |

## EFG6KL LOW TEMP SPIRAL WIRE HOSE

### SPIRAL WIRE

| | |
|---|---|
| RECOMMENDED FOR | Extremely high–pressure hydraulic applications in low–temperature environments. Compatible with biodegradable hydraulic fluids like polyolester, polyglycol and vegetable oil as well as standard petroleum–based fluid. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Four or six alternating layers of spiraled, high–tensile wire. |
| COVER | Black, oil resistant, synthetic rubber (Polychloroprene), with color coded layline. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –70°F to +212°F (–57°C to +100°C). |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (G20) Section E<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Tested to Industry Leading 1,000,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70250 | 10EFG6KLXCTN | 4651-0160 | 100 | 5/8 | 1.09 | 6000 | 24000 | 4.0 |
| 70257 | 12EFG6KLXCTN | 4651-0038 | 100 | 3/4 | 1.24 | 6000 | 24000 | 4.8 |
| 70259 | 16EFG6KLXCTN | 4651-0039 | 100 | 1 | 1.53 | 6000 | 24000 | 6.0 |

## EFG5K SPIRAL WIRE HOSE - SAE 100R13

### SPIRAL WIRE

| | |
|---|---|
| RECOMMENDED FOR | Extremely high–pressure high–impulse applications. Exceeds all requirements of ISO 18752 Grade D (except for –24) and SAE 100R13 and performance requirements of EN 856 4SH (–16 and –20), EN 856 4SP (–10, and –12), EN 856 R13 and ISO 3862 Type R13 (–12, –16, –20, –24, –32). Compatible with biodegradable hydraulic fluids like polyolester, polyglycol and vegetable oil as well as standard petroleum–based fluids. Available in 121' through 200' continuous lengths. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Four (six for –20, –24 and –32) alternating layers of spiraled, high–tensile steel. |
| COVER | Black, oil resistant, synthetic rubber (Polychloroprene), with color coded layline. Also available with unique abrasion resistant MegaTuff® or XtraTuff® covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (G20) Section E<br>GlobalSpiral™ MAX Pressure Couplings (–24 = G24), (–32 = G23) Section E<br>Stainless Steel Spiral Couplings (–6 through –20) (G18) Section F<br>(See Crimp Data Manual 428–7365 or eCrimp) |




For Biodegradable Hydraulic Fluids. Meets Flame Resistance Acceptance Designation "MSHA 2G". Tested to Industry Leading 1,000,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85453 | 6EFG5K X25FT | 4651-4020 | 1 | 3/8 | .80 | 5000 | 20000 | 2.5 |
| 70402 | 6EFG5KX100REEL | 4651-5026 | 100 | 3/8 | .80 | 5000 | 20000 | 2.5 |
| 70871 | 6EFG5KXCTN | 4651-1424 | 100 | 3/8 | .80 | 5000 | 20000 | 2.5 |
| 70160 | 6EFG5KXREEL | 4651-0120 | 300 | 3/8 | .80 | 5000 | 20000 | 2.5 |
| 85454 | 8EFG5K X25FT | 4651-4021 | 1 | 1/2 | .95 | 5000 | 20000 | 3.5 |
| 70403 | 8EFG5KX100REEL | 4651-5027 | 100 | 1/2 | .95 | 5000 | 20000 | 3.5 |
| 70864 | 8EFG5KXCTN | 4651-1372 | 100 | 1/2 | .95 | 5000 | 20000 | 3.5 |

## EFG5K SPIRAL WIRE HOSE - SAE 100R13 - CONTINUED

### SPIRAL WIRE - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70977 | 8EFG5KXLL | 4651-1612 | 200 | 1/2 | .95 | 5000 | 20000 | 3.5 |
| 70161 | 8EFG5KXREEL | 4651-0121 | 240 | 1/2 | .95 | 5000 | 20000 | 3.5 |
| 85455 | 10EFG5K X25FT | 4651-4022 | 1 | 5/8 | 1.09 | 5000 | 20000 | 4.0 |
| 70814 | 10EFG5KXCTN | 4651-1340 | 100 | 5/8 | 1.09 | 5000 | 20000 | 4.0 |
| 70728 | 10EFG5KXLL | 4651-1390 | 200 | 5/8 | 1.09 | 5000 | 20000 | 4.0 |
| 70162 | 10EFG5KXREEL | 4651-0122 | 200 | 5/8 | 1.09 | 5000 | 20000 | 4.0 |
| 85456 | 12EFG5K X25FT | 4651-4023 | 1 | 3/4 | 1.24 | 5000 | 20000 | 4.7 |
| 70838 | 12EFG5KXCTN | 4651-1285 | 100 | 3/4 | 1.24 | 5000 | 20000 | 4.7 |
| 70729 | 12EFG5KXLL | 4651-1391 | 200 | 3/4 | 1.24 | 5000 | 20000 | 4.7 |
| 70167 | 12EFG5KXREEL | 4651-0127 | 200 | 3/4 | 1.24 | 5000 | 20000 | 4.7 |
| 85457 | 16EFG5K X25FT | 4651-4024 | 1 | 1 | 1.53 | 5000 | 20000 | 6.0 |
| 70834 | 16EFG5KXCTN | 4651-1286 | 100 | 1 | 1.53 | 5000 | 20000 | 6.0 |
| 70730 | 16EFG5KXLL | 4651-1392 | 200 | 1 | 1.53 | 5000 | 20000 | 6.0 |
| 85458 | 20EFG5K X25FT | 4651-4025 | 1 | 1 1/4 | 1.97 | 5000 | 20000 | 8.2 |
| 70835 | 20EFG5KXCTN | 4651-1287 | 50 | 1 1/4 | 1.97 | 5000 | 20000 | 8.2 |
| 70734 | 20EFG5KXLL | 4651-1393 | 200 | 1 1/4 | 1.97 | 5000 | 20000 | 8.2 |
| 85432 | 24EFG5K X25FT | 4651-1742 | 1 | 1 1/2 | 2.26 | 5000 | 20000 | 10.0 |
| 71056 | 24EFG5KXCTN | 4651-1455 | 50 | 1 1/2 | 2.26 | 5000 | 20000 | 10.0 |
| | 24EFG5KXLL | 4651-2208 | 200 | 1 1/2 | 2.26 | 5000 | 20000 | 10.0 |
| 85436 | 32EFG5K X25FT | 4651-1746 | 1 | 2 | 2.80 | 5000 | 20000 | 25.0 |
| 71059 | 32EFG5KXCTN | 4651-1456 | 50 | 2 | 2.80 | 5000 | 20000 | 25.0 |
| | 32EFG5KXLL | 4651-0059 | 200 | 2 | 2.80 | 5000 | 20000 | 25.0 |
| | 40EFG5K X CRATE* | 4651-1817 | 200 | 2 1/2 | 3.35 | 5000 | 20000 | 30.0 |

**Crimped assemblies available from Gates or factory quality assemblies can be made with the GC96TSI–3.*

# EFG5K SPIRAL WIRE HOSE - SAE 100R13 - MEGATUFF® COVER

## SPIRAL WIRE




| | |
|---|---|
| RECOMMENDED FOR | Extremely high–pressure hydraulic applications. EFG5K exceeds all requirements of ISO 18752 Grade D (except for –24) and is designed to meet or exceed all requirements of SAE 100R13 specifications and performance requirements of EN 856 4SH (–16 and –20), EN 856 4SP (–10, and –12), EN 856 R13 and ISO 3862 Type R13 (–12, –16, –20, –24, –32). Compatible with biodegradable hydraulic fluids like polyolester, polyglycol and vegetable oil as well as standard petroleum–based fluids. Available in 121' through 200' continuous lengths. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Four (six for –20, –24 and –32) alternating layers of spiraled, high–tensile steel. |
| COVER | Black, oil, abrasion and weather resistant MegaTuff® cover with color coded layline. Also available with unique abrasion resistant XtraTuff® or Standard covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (G20) Section E<br>GlobalSpiral™ MAX Pressure Couplings (–24 = G24), (–32 = G23) Section E<br>Stainless Steel Spiral Couplings (G18) Section F<br>(See Crimp Data Manual 428–7365 or eCrimp) |

For Biodegradable Hydraulic Fluids. Meets Flame Resistance Acceptance Designation "MSHA 2G". MegaTuff® hose lasts up to 300 times longer than standard hose during hose–to–hose and hose–to–metal abrasion tests per ISO 6945. Tested to Industry Leading 1,000,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85459 | 6EFG5K-MTF X25FT | 4651-4026 | 1 | 3/8 | .80 | 5000 | 20000 | 2.5 |
| 70872 | 6EFG5K-MTFXCTN | 4651-1436 | 100 | 3/8 | .80 | 5000 | 20000 | 2.5 |
| 85460 | 8EFG5K-MTF X25FT | 4651-4027 | 1 | 1/2 | .94 | 5000 | 20000 | 3.5 |
| 70873 | 8EFG5K-MTFXCTN | 4651-1608 | 100 | 1/2 | .94 | 5000 | 20000 | 3.5 |
| 70861 | 8EFG5K-MTFXLL | 4651-1573 | 1200 | 1/2 | .94 | 5000 | 20000 | 3.5 |
| 85461 | 10EFG5K-MTF X25FT | 4651-4028 | 1 | 5/8 | 1.09 | 5000 | 20000 | 4.0 |
| 70879 | 10EFG5K-MTFXCTN | 4651-1410 | 100 | 5/8 | 1.09 | 5000 | 20000 | 4.0 |
| 85462 | 12EFG5K-MTF X25FT | 4651-4029 | 1 | 3/4 | 1.24 | 5000 | 20000 | 4.7 |
| 70874 | 12EFG5K-MTFXCTN | 4651-1605 | 100 | 3/4 | 1.24 | 5000 | 20000 | 4.7 |
| 85463 | 16EFG5K-MTF X25FT | 4651-4030 | 1 | 1 | 1.53 | 5000 | 20000 | 6.0 |
| 70875 | 16EFG5K-MTFXCTN | 4651-1603 | 100 | 1 | 1.53 | 5000 | 20000 | 6.0 |
| 70739 | 16EFG5K-MTFXLL | 4651-4001 | 200 | 1 | 1.53 | 5000 | 20000 | 6.0 |
| 85464 | 20EFG5K-MTF X25FT | 4651-4031 | 1 | 1 1/4 | 1.97 | 5000 | 20000 | 8.2 |
| 70876 | 20EFG5K-MTFXCTN | 4651-1600 | 50 | 1 1/4 | 1.97 | 5000 | 20000 | 8.2 |
| 70740 | 20EFG5K-MTFXLL | 4651-4002 | 200 | 1 1/4 | 1.97 | 5000 | 20000 | 8.2 |
| 85433 | 24EFG5K-MTF X25FT | 4651-1743 | 1 | 1 1/2 | 2.26 | 5000 | 20000 | 10.0 |
| 71055 | 24EFG5K-MTFXCTN | 4651-2203 | 50 | 1 1/2 | 2.26 | 5000 | 20000 | 10.0 |
| | 24EFG5K-MTFXLL | 4651-2204 | 200 | 1 1/2 | 2.26 | 5000 | 20000 | 10.0 |
| 85437 | 32EFG5K-MTF X25FT | 4651-1747 | 1 | 2 | 2.80 | 5000 | 20000 | 25.0 |
| 71063 | 32EFG5K-MTFXCTN | 4651-1522 | 50 | 2 | 2.80 | 5000 | 20000 | 25.0 |
| | 32EFG5K-MTFXLL | 4651-2211 | 200 | 2 | 2.80 | 5000 | 20000 | 25.0 |

## EFG5K SPIRAL WIRE HOSE - SAE 100R13 - XTRATUFF® COVER

### SPIRAL WIRE




| | |
|---|---|
| RECOMMENDED FOR | Extremely high–pressure high–impulse applications. Exceeds all requirements of ISO 18752 Grade D (except for –24) and exceeds all performance SAE 100R13, EN 856 R13 and ISO 3862 Type R13. Compatible with biodegradable hydraulic fluids like polyolester, polyglycol and vegetable oil as well as standard petroleum–based fluids. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Four (six for –20) alternating layers of spiraled, high–tensile steel. |
| COVER | Black, oil resistant, synthetic rubber (XtraTuff® Nitrile), with color coded layline. Also available with unique abrasion resistant MegaTuff® or Standard cover. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (G20) Section E<br>Stainless Steel Spiral Couplings (G18) Section F<br>(See Crimp Data Manual 428–7365 or eCrimp) |

For Biodegradable Hydraulic Fluids. Meets Flame Resistance Acceptance Designation "MSHA 2G". Tested to Industry Leading 1,000,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70475 | 6EFG5K-XTFXLL | 4651-0364 | 200 | 3/8 | .80 | 5000 | 20000 | 2.5 |
| 70470 | 6EFG5K-XTFXREEL | 4651-0370 | 300 | 3/8 | .80 | 5000 | 20000 | 2.5 |
| 70481 | 8EFG5K-XTFXLL | 4651-0365 | 200 | 1/2 | .95 | 5000 | 20000 | 3.5 |
| 70476 | 8EFG5K-XTFXREEL | 4651-0371 | 230 | 1/2 | .95 | 5000 | 20000 | 3.5 |
| 70482 | 10EFG5K-XTFXREEL | 4651-0372 | 220 | 5/8 | 1.09 | 5000 | 20000 | 4.0 |
| 70491 | 12EFG5K-XTFXLL | 4651-0367 | 200 | 3/4 | 1.24 | 5000 | 20000 | 4.7 |
| 70484 | 12EFG5K-XTFXREEL | 4651-0373 | 200 | 3/4 | 1.24 | 5000 | 20000 | 4.7 |
| 70510 | 20EFG5K-XTFXCTN | 4651-0375 | 50 | 1 1/4 | 1.97 | 5000 | 20000 | 8.2 |
| 70494 | 20EFG5K-XTFXLL | 4651-0369 | 200 | 1 1/4 | 1.97 | 5000 | 20000 | 8.2 |

## EFG5KL LOW TEMP SPIRAL WIRE HOSE

### SPIRAL WIRE




| | |
|---|---|
| RECOMMENDED FOR | Extremely high–pressure hydraulic applications in low–temperature environments. Compatible with biodegradable hydraulic fluids like polyolester, polyglycol and vegetable oil as well as standard petroleum–based fluid. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Four or six alternating layers of spiraled, high–tensile wire. |
| COVER | Black, oil resistant, synthetic rubber (Polychloroprene), with color coded layline. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –70°F to +212°F (–57°C to +100°C). |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (G20) Section E<br>GlobalSpiral™ MAX Pressure Couplings (–24 = G24), (–32 = G23) Section E<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Tested to Industry Leading 1,000,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70180 | 6EFG5KLXCTN | 4651-0074 | 100 | 3/8 | .80 | 5000 | 20000 | 2.5 |
| 70181 | 8EFG5KLXCTN | 4651-0131 | 100 | 1/2 | .95 | 5000 | 20000 | 3.5 |
| 70182 | 10EFG5KLXCTN | 4651-0078 | 100 | 5/8 | 1.09 | 5000 | 20000 | 4.0 |

## EFG5KL LOW TEMP SPIRAL WIRE HOSE - CONTINUED

### SPIRAL WIRE - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70256 | 12EFG5KLXCTN | 4651-0020 | 100 | 3/4 | 1.24 | 5000 | 20000 | 4.8 |
| 70258 | 16EFG5KLXCTN | 4651-0019 | 120 | 1 | 1.53 | 5000 | 20000 | 6.0 |
| 70183 | 20EFG5KLXCTN | 4651-0058 | 50 | 1 1/4 | 1.97 | 5000 | 20000 | 8.2 |
| 70087 | 24EFG5KLXCTN | 4651-0079 | 50 | 1 1/2 | 2.26 | 5000 | 20000 | 10.0 |

## ID5K SPIRAL WIRE HOSE - ISO 18752 GRADE D

### SPIRAL WIRE

| | |
|---|---|
| RECOMMENDED FOR | Extremely high–pressure, high–impulse applications. Tested up to 2.3 million impulse cycles. Exceeds ISO 18752, Class 350, Grade D, Type DC. Meets SAE 100R13. |
| TUBE | Black, oil resistant, synthetic rubber (HNBR). |
| REINFORCEMENT | Four alternating layers of spiraled, high–tensile strength steel. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (Polychloroprene). |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). |
| COUPLING RECOMMENDATION | Permanent no–skive GlobalSpiral™ (with GSID1F–4 Ferrules). (See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70178 | 10ID5KXCTN | 4651-0165 | 100 | 5/8 | 1.00 | 5000 | 20000 | 4.0 |
| 70177 | 10ID5KXLL | 4651-0166 | 200 | 5/8 | 1.00 | 5000 | 20000 | 4.0 |
| 70112 | 12ID5KXCTN | 4651-0167 | 100 | 3/4 | 1.14 | 5000 | 20000 | 4.7 |
| 70113 | 12ID5KXLL | 4651-0168 | 200 | 3/4 | 1.14 | 5000 | 20000 | 4.7 |
| 70117 | 16ID5KXCTN | 4651-0169 | 100 | 1 | 1.45 | 5000 | 20000 | 6.0 |
| 70118 | 16ID5KXLL | 4651-0170 | 200 | 1 | 1.45 | 5000 | 20000 | 6.0 |

# EFG4K SPIRAL WIRE HOSE - SAE 100R12

## SPIRAL WIRE




| | |
|---|---|
| RECOMMENDED FOR | Very high–pressure, high–impulse applications. Exceeds all requirements of ISO 18752 Grade D*, SAE 100R12, EN 856 R12 and ISO 3862 Type R12. *(Sizes 3/8", 1/2" and 5/8" exceed ISO 18752 Grade D performance but does not meet OD requirements). Compatible with biodegradable hydraulic fluids like polyolester, polyglycol and vegetable oil as well as standard petroleum–based fluids. Available in 121' through 200' continuous lengths. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Four alternating layers of spiraled, high–tensile steel wire. |
| COVER | Black, oil resistant, synthetic rubber (Polychloroprene), with color coded layline. Also available with unique abrasion resistant MegaTuff® or XtraTuff® covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (G20) Section E<br>GlobalSpiral™ One–Piece Couplings (MC 4–20) (–20 only) Section E<br>Stainless Steel Spiral Couplings (G18) Section F<br>(See Crimp Data Manual 428–7365 or eCrimp) |

For Biodegradable Hydraulic Fluids. Meets Flame Resistance Acceptance Designation "MSHA 2G". Tested to Industry Leading 1,000,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85477 | 6EFG4K X25FT | 4651-4005 | 1 | 3/8 | .80 | 4000 | 16000 | 2.5 |
| 85491 | 6EFG4K X50FT | 4651-1430 | 1 | 3/8 | .80 | 4000 | 16000 | 2.5 |
| 70400 | 6EFG4KX100REEL | 4651-5024 | 100 | 3/8 | .80 | 4000 | 16000 | 2.5 |
| 70811 | 6EFG4KXCTN | 4651-1338 | 100 | 3/8 | .80 | 4000 | 16000 | 2.5 |
| 70157 | 6EFG4KXREEL | 4651-0117 | 300 | 3/8 | .80 | 4000 | 16000 | 2.5 |
| 85478 | 8EFG4K X25FT | 4651-4006 | 1 | 1/2 | .94 | 4000 | 16000 | 3.5 |
| 85492 | 8EFG4K X50FT | 4651-1431 | 1 | 1/2 | .94 | 4000 | 16000 | 3.5 |
| 70401 | 8EFG4KX100REEL | 4651-5025 | 100 | 1/2 | .94 | 4000 | 16000 | 3.5 |
| 70863 | 8EFG4KXCTN | 4651-1339 | 100 | 1/2 | .94 | 4000 | 16000 | 3.5 |
| 70976 | 8EFG4KXLL | 4651-1611 | 200 | 1/2 | .94 | 4000 | 16000 | 3.5 |
| 70158 | 8EFG4KXREEL | 4651-0118 | 240 | 1/2 | .94 | 4000 | 16000 | 3.5 |
| 85479 | 10EFG4K X25FT | 4651-4007 | 1 | 5/8 | 1.09 | 4000 | 16000 | 4.0 |
| 70813 | 10EFG4KXCTN | 4651-1367 | 100 | 5/8 | 1.09 | 4000 | 16000 | 4.0 |
| | 10EFG4KXLL | 4651-1614 | 200 | 5/8 | 1.09 | 4000 | 16000 | 4.0 |
| 70159 | 10EFG4KXREEL | 4651-0119 | 200 | 5/8 | 1.09 | 4000 | 16000 | 4.0 |
| 85480 | 12EFG4K X25FT | 4651-4011 | 1 | 3/4 | 1.21 | 4000 | 16000 | 4.7 |
| 85494 | 12EFG4K X50FT | 4651-1432 | 1 | 3/4 | 1.21 | 4000 | 16000 | 4.7 |
| 70831 | 12EFG4KXCTN | 4651-1282 | 100 | 3/4 | 1.21 | 4000 | 16000 | 4.7 |
| 70717 | 12EFG4KXLL | 4651-1385 | 200 | 3/4 | 1.21 | 4000 | 16000 | 4.7 |
| 70166 | 12EFG4KXREEL | 4651-0126 | 200 | 3/4 | 1.21 | 4000 | 16000 | 4.7 |
| 85481 | 16EFG4K X25FT | 4651-4012 | 1 | 1 | 1.50 | 4000 | 16000 | 6.0 |
| 85495 | 16EFG4K X50FT | 4651-1433 | 1 | 1 | 1.50 | 4000 | 16000 | 6.0 |
| 70807 | 16EFG4K X100FT | 4651-1460 | 100 | 1 | 1.50 | 4000 | 16000 | 6.0 |
| 70832 | 16EFG4KXCTN | 4651-1283 | 100 | 1 | 1.50 | 4000 | 16000 | 6.0 |
| 70718 | 16EFG4KXLL | 4651-1386 | 200 | 1 | 1.50 | 4000 | 16000 | 6.0 |
| 85482 | 20EFG4K X25FT | 4651-4013 | 1 | 1 1/4 | 1.85 | 4000 | 16000 | 8.2 |
| 85438 | 20EFG4K X50FT | 4651-1520 | 1 | 1 1/4 | 1.85 | 4000 | 16000 | 8.2 |
| 70833 | 20EFG4KXCTN | 4651-1284 | 50 | 1 1/4 | 1.85 | 4000 | 16000 | 8.2 |
| 70719 | 20EFG4KXLL | 4651-1387 | 200 | 1 1/4 | 1.85 | 4000 | 16000 | 8.2 |
| | 48EFG4K X CRATE* | 4651-1818 | 200 | 3 | 3.86 | 4000 | 16000 | 35.0 |

**Crimped assemblies available from Gates or factory quality assemblies can be made with the GC96TSI–3.*

# EFG4K SPIRAL WIRE HOSE - SAE 100R12 - MEGATUFF® COVER

## SPIRAL WIRE

| | |
|---|---|
| RECOMMENDED FOR | Very high–pressure, high–impulse extremely abrasive applications. Exceeds all requirements of ISO 18752 Grade D*, SAE 100R12, EN 856 R12 and ISO 3862 Type R12. *(Sizes 3/8", 1/2" and 5/8" exceed ISO 18752 Grade D performance but does not meet OD requirements). Compatible with biodegradable hydraulic fluids like polyolester, polyglycol and vegetable oil as well as standard petroleum–based fluids. Available in 121' through 200' continuous lengths. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Four alternating layers of spiraled, high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant MegaTuff® cover with color coded layline. Also available with unique abrasion resistant XtraTuff® or Standard covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (G20) Section E<br>GlobalSpiral™ One–Piece Couplings (MC 4–20) (–20 only) Section E<br>Stainless Steel Spiral Couplings (G18) Section F<br>(See Crimp Data Manual 428–7365 or eCrimp) |




For Biodegradable Hydraulic Fluids. Meets Flame Resistance Acceptance Designation "MSHA 2G". MegaTuff® hose lasts up to 300 times longer than standard hose during hose–to–hose and hose–to–metal abrasion tests per ISO 6945. Tested to Industry Leading 1,000,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85483 | 6EFG4K-MTF X25FT | 4651-4014 | 1 | 3/8 | .80 | 4000 | 16000 | 2.5 |
| 70945 | 6EFG4K-MTFXCTN | 4651-1610 | 100 | 3/8 | .80 | 4000 | 16000 | 2.5 |
| 85484 | 8EFG4K-MTF X25FT | 4651-4015 | 1 | 1/2 | .94 | 4000 | 16000 | 3.5 |
| 70946 | 8EFG4K-MTFXCTN | 4651-1607 | 100 | 1/2 | .94 | 4000 | 16000 | 3.5 |
| 85485 | 10EFG4K-MTF X25FT | 4651-4016 | 1 | 5/8 | 1.09 | 4000 | 16000 | 4.0 |
| 70947 | 10EFG4K-MTFXCTN | 4651-1404 | 100 | 5/8 | 1.09 | 4000 | 16000 | 4.0 |
| 85486 | 12EFG4K-MTF X25FT | 4651-4017 | 1 | 3/4 | 1.21 | 4000 | 16000 | 4.7 |
| 70877 | 12EFG4K-MTFXCTN | 4651-1405 | 100 | 3/4 | 1.21 | 4000 | 16000 | 4.7 |
| 70726 | 12EFG4K-MTFXLL | 4651-1388 | 200 | 3/4 | 1.21 | 4000 | 16000 | 4.7 |
| 85487 | 16EFG4K-MTF X25FT | 4651-4018 | 1 | 1 | 1.50 | 4000 | 16000 | 6.0 |
| 70948 | 16EFG4K-MTFXCTN | 4651-1406 | 100 | 1 | 1.50 | 4000 | 16000 | 6.0 |
| 70727 | 16EFG4K-MTFXLL | 4651-1389 | 200 | 1 | 1.50 | 4000 | 16000 | 6.0 |
| 85488 | 20EFG4K-MTF X25FT | 4651-4019 | 1 | 1 1/4 | 1.85 | 4000 | 16000 | 8.2 |
| 70949 | 20EFG4K-MTFXCTN | 4651-1602 | 50 | 1 1/4 | 1.85 | 4000 | 16000 | 8.2 |
| | 20EFG4K-MTFXLL | 4651-1638 | 200 | 1 1/4 | 1.85 | 4000 | 16000 | 8.2 |

# EFG4K SPIRAL WIRE HOSE - SAE 100R12 - XTRATUFF® COVER

## SPIRAL WIRE




| | |
|---|---|
| RECOMMENDED FOR | Very high–pressure, high–impulse abrasive applications. Exceeds all requirements of ISO 18752 Grade D*, SAE 100R12, EN 856 R12 and ISO 3862 Type R12. *(Sizes 3/8", 1/2" and 5/8" exceed ISO 18752 Grade D performance but does not meet OD requirements). Compatible with biodegradable hydraulic fluids like polyolester, polyglycol and vegetable oil as well as standard petroleum based fluids. Available in 121' through 200' continuous lengths. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Four alternating layers of spiraled, high–tensile steel wire. |
| COVER | Black, oil and abrasion resistant, synthetic rubber (XtraTuff® Nitrile), with color coded layline. Also available with unique abrasion resistant MegaTuff® or Standard covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (G20) Section E<br>GlobalSpiral™ One–Piece Couplings (MC 4–20) (–20 only) Section E<br>Stainless Steel Spiral Couplings (G18) Section F<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Tested to Industry Leading 1,000,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70410 | 6EFG4K-XTFXLL | 4651-0251 | 200 | 3/8 | .80 | 4000 | 16000 | 2.5 |
| 70411 | 6EFG4K-XTFXREEL | 4651-0263 | 300 | 3/8 | .80 | 4000 | 16000 | 2.5 |
| 70412 | 8EFG4K-XTFXLL | 4651-0253 | 200 | 1/2 | .94 | 4000 | 16000 | 3.5 |
| 70413 | 8EFG4K-XTFXREEL | 4651-0264 | 230 | 1/2 | .94 | 4000 | 16000 | 3.5 |
| 70511 | 10EFG4K-XTFXLL | 4651-0255 | 200 | 5/8 | 1.09 | 4000 | 16000 | 4.0 |
| 70512 | 12EFG4K-XTFXCTN | 4651-0256 | 100 | 5/8 | 1.09 | 4000 | 16000 | 4.0 |
| 70414 | 12EFG4K-XTFXLL | 4651-0257 | 200 | 3/4 | 1.21 | 4000 | 16000 | 4.7 |
| 70415 | 12EFG4K-XTFXREEL | 4651-0266 | 200 | 3/4 | 1.21 | 4000 | 16000 | 4.7 |
| 70416 | 16EFG4K-XTFXCTN | 4651-0258 | 100 | 1 | 1.50 | 4000 | 16000 | 6.0 |
| 70417 | 16EFG4K-XTFXLL | 4651-0259 | 200 | 1 | 1.50 | 4000 | 16000 | 6.0 |
| 70418 | 20EFG4K-XTFXCTN | 4651-0260 | 50 | 1 1/4 | 1.85 | 4000 | 16000 | 8.2 |
| 70419 | 20EFG4K-XTFXLL | 4651-0261 | 200 | 1 1/4 | 1.85 | 4000 | 16000 | 8.2 |

## EFG4KL LOW TEMP SPIRAL WIRE HOSE

### SPIRAL WIRE

| | |
|---|---|
| RECOMMENDED FOR | Very high–pressure hydraulic applications in low–temperature environments. Compatible with biodegradable hydraulic fluids like polyolester, polyglycol and vegetable oil as well as standard petroleum–based fluid. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Four alternating layers of spiraled, high–tensile wire. |
| COVER | Black, oil resistant, synthetic rubber (Polychloroprene), with color coded layline. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –70°F to +212°F (–57°C to +100°C). |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (G20) Section E<br>GlobalSpiral™ One–Piece Couplings (MC 4–20) (–20 only) Section E<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Tested to Industry Leading 1,000,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 77001 | 12EFG4KLXCTN | 4651-0023 | 100 | 3/4 | 1.24 | 4000 | 16000 | 4.8 |
| 77002 | 16EFG4KLXCTN | 4651-0024 | 100 | 1 | 1.53 | 4000 | 16000 | 6.0 |
| 70086 | 20EFG4KLXCTN | 4651-0075 | 50 | 1 1/4 | 1.85 | 4000 | 16000 | 8.3 |

## EFG3K SPIRAL WIRE HOSE - SAE 100R12

### SPIRAL WIRE

| | |
|---|---|
| RECOMMENDED FOR | Very high–pressure, high–impulse applications. Exceeds all requirements for ISO 18752 Grade D, SAE 100R12, EN 856 R12, and performance requirements of EN 856 4SP, and ISO 3862 Type R12. Compatible with biodegradable hydraulic fluids like polyolester, polyglycol and vegetable oil as well as standard petroleum–based fluids. Available in 121' through 200' continuous lengths. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Four alternating layers of spiraled, high–tensile steel wire. |
| COVER | Black, oil resistant, synthetic rubber (Polychloroprene), with color coded layline. Also available with unique abrasion resistant MegaTuff® cover. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–20) (G20) Section E<br>GlobalSpiral™ One–Piece Couplings (MC 4–20) (–20 only) Section E<br>GlobalSpiral™ Plus Couplings (–24 and –32) (G22) Section E<br>Stainless Steel Braid Couplings (–24 and –32) (G17) Section H<br>Stainless Steel Spiral Couplings (–20) (G18) Section F<br>(See Crimp Data Manual 428–7365 or eCrimp) |




For Biodegradable Hydraulic Fluids. Meets Flame Resistance Acceptance Designation "MSHA 2G". Tested to Industry Leading 1,000,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85489 | 20EFG3K X25FT | 4651-4003 | 1 | 1 1/4 | 1.85 | 3000 | 12000 | 8.2 |
| 85497 | 20EFG3K X50FT | 4651-1434 | 1 | 1 1/4 | 1.85 | 3000 | 12000 | 8.2 |
| 70539 | 20EFG3KXCTN | 4651-1381 | 100 | 1 1/4 | 1.85 | 3000 | 12000 | 8.2 |
| 70707 | 20EFG3KXLL | 4651-1384 | 200 | 1 1/4 | 1.85 | 3000 | 12000 | 8.2 |
| 85430 | 24EFG3K X25FT | 4651-1740 | 1 | 1 1/2 | 2.11 | 3000 | 12000 | 10.0 |
| 71054 | 24EFG3KXCTN | 4651-1451 | 50 | 1 1/2 | 2.11 | 3000 | 12000 | 10.0 |
| | 24EFG3KXLL | 4651-2207 | 200 | 1 1/2 | 2.11 | 3000 | 12000 | 10.0 |
| 85434 | 32EFG3K X25FT | 4651-1744 | 1 | 2 | 2.63 | 3000 | 12000 | 12.5 |

## EFG3K SPIRAL WIRE HOSE - SAE 100R12 - CONTINUED

### SPIRAL WIRE - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| | 32EFG3KX50INC | 4651-2209 | 200 | 2 | 2.63 | 3000 | 12000 | 12.5 |
| 71058 | 32EFG3KXCTN | 4651-1452 | 50 | 2 | 2.63 | 3000 | 12000 | 12.5 |
| 70265 | 32EFG3KXLL | 4651-2210 | 200 | 2 | 2.63 | 3000 | 12000 | 12.5 |

## EFG3K SPIRAL WIRE HOSE - SAE 100R12 - MEGATUFF® COVER

### SPIRAL WIRE

| | |
|---|---|
| RECOMMENDED FOR | Very high–pressure, high–impulse applications. Exceeds all requirements for ISO 18752 Grade D, exceeds all performance requirements for SAE 100R12, EN 856 R12, performance requirements of EN 856 4SP and ISO 3862 Type R12. Compatible with biodegradable hydraulic fluids like polyolester, polyglycol and vegetable oil as well as standard petroleum–based fluids. Available in 121' through 200' continuous lengths. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Four alternating layers of spiraled, high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant MegaTuff® cover with color coded layline. Also available in Standard cover. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–20) (G20) Section E<br>GlobalSpiral™ One–Piece Couplings (MC 4–20) (–20 only) Section E<br>GlobalSpiral™ Plus Couplings (–24 and –32) (G22) Section E<br>(See Crimp Data Manual 428–7365 or eCrimp) |




For Biodegradable Hydraulic Fluids. Meets Flame Resistance Acceptance Designation "MSHA 2G". MegaTuff® hose lasts up to 300 times longer than standard hose during hose–to–hose and hose–to–metal abrasion tests per ISO 6945. Tested to Industry Leading 1,000,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85490 | 20EFG3K-MTF X25FT | 4651-4004 | 1 | 1 1/4 | 1.85 | 3000 | 12000 | 8.2 |
| 70950 | 20EFG3K-MTFXCTN | 4651-1425 | 100 | 1 1/4 | 1.85 | 3000 | 12000 | 8.2 |
| 70951 | 20EFG3K-MTFXLL | 4651-1427 | 200 | 1 1/4 | 1.85 | 3000 | 12000 | 8.2 |
| 85431 | 24EFG3K-MTF X25FT | 4651-1741 | 1 | 1 1/2 | 2.11 | 3000 | 12000 | 10.0 |
| 71053 | 24EFG3K-MTFXCTN | 4651-2201 | 50 | 1 1/2 | 2.11 | 3000 | 12000 | 10.0 |
| | 24EFG3K-MTFXLL | 4651-2202 | 200 | 1 1/2 | 2.11 | 3000 | 12000 | 10.0 |
| 85435 | 32EFG3K-MTF X25FT | 4651-1745 | 1 | 2 | 2.63 | 3000 | 12000 | 25.0 |
| 71057 | 32EFG3K-MTFXCTN | 4651-2205 | 50 | 2 | 2.63 | 3000 | 12000 | 25.0 |
| | 32EFG3K-MTFXLL | 4651-2206 | 200 | 2 | 2.63 | 3000 | 12000 | 25.0 |

## GLOBAL M6K MEGA6000™ HOSE

### WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic applications. Provides tighter than standard minimum bend radius and greater flexibility for easier plumbing. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (Nitrile and PVC), with color coded layline. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G<br>Stainless Steel Braid Couplings (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G". Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70599 | 4M6KXREEL | 4657-2697 | 440 | 1/4 | .58 | 6000 | 24000 | 2.0 |

## GLOBAL M5K MEGA5000™ HOSE

### WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic applications. Exceeds ISO 18752 Grade B. Provides tighter than standard minimum bend radius and greater flexibility for easier plumbing. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (Nitrile and PVC –4, –5, –6), (Polychloroprene –8) with color coded layline. Also available with unique abrasion resistant MegaTuff® or XtraTuff® covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 and –8) (G20) Section E<br>MegaCrimp® Couplings (G25) Section G<br>Stainless Steel Braid Couplings (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G". Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85607 | 4M5K X50FT | 4657-4122 | 1 | 1/4 | .55 | 5000 | 20000 | 2.0 |
| 70596 | 4M5KXREEL | 4657-1100 | 440 | 1/4 | .55 | 5000 | 20000 | 2.0 |
| 70449 | 5M5KXREEL | 4657-8006 | 350 | 5/16 | .61 | 5000 | 20000 | 2.2 |
| 85606 | 6M5K X50FT | 4657-4121 | 1 | 3/8 | .70 | 5000 | 20000 | 2.5 |
| 70597 | 6M5KXREEL | 4657-2695 | 330 | 3/8 | .70 | 5000 | 20000 | 2.5 |
| 85608 | 8M5K X50FT | 4657-4123 | 1 | 1/2 | .86 | 5000 | 20000 | 3.5 |
| 70598 | 8M5KXREEL | 4657-2650 | 220 | 1/2 | .86 | 5000 | 20000 | 3.5 |

## GLOBAL M5K MEGA5000™ HOSE - MEGATUFF® COVER

### WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic applications. Exceeds ISO 18752 Grade B. Provides tighter than standard minimum bend radius and greater flexibility for easier plumbing. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant MegaTuff® cover with color coded layline. Also available with unique abrasion resistant XtraTuff® or Standard covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 and –8) (G20) Section E<br>MegaCrimp® Couplings (G25) Section G<br>Stainless Steel Braid Couplings (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G". Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70386 | 4M5K-MTFXREEL | 4657-8011 | 440 | 1/4 | .55 | 5000 | 20000 | 2.0 |
| 70343 | 5M5K-MTFXREEL | 4657-8012 | 350 | 5/16 | .61 | 5000 | 20000 | 2.2 |
| 70340 | 6M5K-MTFXREEL | 4657-8013 | 330 | 3/8 | .70 | 5000 | 20000 | 2.5 |
| 70329 | 8M5K-MTFXREEL | 4657-8014 | 220 | 1/2 | .86 | 5000 | 20000 | 3.5 |

## GLOBAL M5K MEGA5000™ HOSE - XTRATUFF® COVER

### WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic applications. Exceeds ISO 18752 Grade B. Provides tighter than standard minimum bend radius and greater flexibility for easier plumbing. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (XtraTuff® Nitrile), with color coded layline. Also available with unique abrasion resistant MegaTuff® or Standard covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 and –8) (G20) Section E<br>MegaCrimp® Couplings (G25) Section G<br>Stainless Steel Braid Couplings (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G". Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70423 | 4M5K-XTFXREEL | 4657-8007 | 440 | 1/4 | .55 | 5000 | 20000 | 2.0 |
| 70428 | 5M5K-XTFXREEL | 4657-8008 | 375 | 5/16 | .61 | 5000 | 20000 | 2.2 |
| 70430 | 6M5K-XTFXREEL | 4657-8009 | 330 | 3/8 | .70 | 5000 | 20000 | 2.5 |
| 70399 | 8M5K-XTFXREEL | 4657-8010 | 220 | 1/2 | .86 | 5000 | 20000 | 3.5 |

# GLOBAL M4K MEGA4000™ HOSE - SAE 100R19

## WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic applications. Exceeds ISO 18752 Grade B, SAE 100R19 and ISO 11237 R19. Allows for tighter minimum bend radius, increased working pressure and improved impulse cycles than industry standards. Provides greater performance, flexibility, easier routing and plumbing of mobile and stationary hydraulic platforms. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (Nitrile and PVC), with color coded layline. Also available with unique abrasion resistant MegaTuff® or XtraTuff® covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –16) (G20) Section E<br>MegaCrimp® Couplings (–4 through –12) (G25) Section G<br>Stainless Steel Braid Couplings (–4 through –8) (G17) Section H<br>Stainless Steel Spiral Couplings (–12 and –16) (G18) Section F<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G" and ISO 11237 R19. Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | ⟷ | ↕ | | | R |
|---|---|---|---|---|---|---|---|---|
| 85616 | 4M4K X50FT | 4657-1238 | 1 | 1/4 | .55 | 4000 | 16000 | 1.5 |
| | 4M4KXBALE | 4657-5779 | 5600 | 1/4 | .55 | 4000 | 16000 | 1.5 |
| 70829 | 4M4KXREEL | 4657-1467 | 440 | 1/4 | .55 | 4000 | 16000 | 1.5 |
| 70457 | 5M4KXREEL | 4657-8015 | 350 | 5/16 | .61 | 4000 | 16000 | 1.8 |
| 85617 | 6M4K X50FT | 4657-4867 | 1 | 3/8 | .70 | 4000 | 16000 | 2.0 |
| | 6M4KXBALE | 4657-5775 | 3800 | 3/8 | .70 | 4000 | 16000 | 2.0 |
| 70821 | 6M4KXREEL | 4657-1458 | 330 | 3/8 | .70 | 4000 | 16000 | 2.0 |
| 85618 | 8M4K X50FT | 4657-4868 | 1 | 1/2 | .82 | 4000 | 16000 | 2.8 |
| | 8M4KXBALE | 4657-5776 | 2200 | 1/2 | .82 | 4000 | 16000 | 2.8 |
| 70822 | 8M4KXREEL | 4657-1459 | 220 | 1/2 | .82 | 4000 | 16000 | 2.8 |
| 85619 | 10M4K X50FT | 4657-4869 | 1 | 5/8 | .99 | 4000 | 16000 | 3.0 |
| | 10M4KXBALE | 4657-5777 | 1750 | 5/8 | .99 | 4000 | 16000 | 3.0 |
| 70823 | 10M4KXREEL | 4657-1460 | 220 | 5/8 | .99 | 4000 | 16000 | 3.0 |
| 85620 | 12M4K X50FT | 4657-4870 | 1 | 3/4 | 1.17 | 4000 | 16000 | 3.8 |
| | 12M4KXBALE | 4657-5778 | 1250 | 3/4 | 1.17 | 4000 | 16000 | 3.8 |
| 70824 | 12M4KXREEL | 4657-1461 | 220 | 3/4 | 1.17 | 4000 | 16000 | 3.8 |
| 71064 | 16M4KXREEL | 4657-4051 | 165 | 1 | 1.52 | 4000 | 16000 | 4.5 |

# GLOBAL M4K MEGA4000™ HOSE - SAE 100R19 - MEGATUFF® COVER

## WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic applications. Exceeds ISO 18752 Grade B, SAE 100R19 and ISO 11237 R19. Allows for tighter minimum bend radius, increased working pressure and improved impulse cycles than industry standards. Provides greater performance, flexibility, easier routing and plumbing of mobile and stationary hydraulic platforms. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant MegaTuff® cover with color coded layline. Also available with unique abrasion resistant XtraTuff® or Standard covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –16) (G20) Section E<br>MegaCrimp® Couplings (–4 through –12) (G25) Section G<br>Stainless Steel Braid Couplings (–4 through –8) (G17) Section H<br>Stainless Steel Spiral Couplings (–12 and –16) (G18) Section F<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G" and ISO 11237 R19. MegaTuff® hose lasts up to 300 times longer than standard hose during hose–to–hose and hose–to–metal abrasion tests per ISO 6945. Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85519 | 4M4K-MTF X50FT | 4657-1239 | 1 | 1/4 | .55 | 4000 | 16000 | 1.5 |
| 70830 | 4M4K-MTFXREEL | 4657-1477 | 350 | 1/4 | .55 | 4000 | 16000 | 1.5 |
| 70326 | 5M4K-MTFXREEL | 4657-8017 | 350 | 5/16 | .61 | 4000 | 16000 | 1.8 |
| 85520 | 6M4K-MTF X50FT | 4657-4020 | 1 | 3/8 | .70 | 4000 | 16000 | 2.0 |
| 70825 | 6M4K-MTFXREEL | 4657-1479 | 330 | 3/8 | .70 | 4000 | 16000 | 2.0 |
| 85521 | 8M4K-MTF X50FT | 4657-4021 | 1 | 1/2 | .82 | 4000 | 16000 | 2.8 |
| | 8M4K-MTFXBALE | 4657-5016 | 3200 | 1/2 | .82 | 4000 | 16000 | 2.8 |
| 70826 | 8M4K-MTFXREEL | 4657-1480 | 220 | 1/2 | .82 | 4000 | 16000 | 2.8 |
| 85522 | 10M4K-MTF X50FT | 4657-4022 | 1 | 5/8 | .99 | 4000 | 16000 | 3.0 |
| 70827 | 10M4K-MTFXREEL | 4657-1481 | 220 | 5/8 | .99 | 4000 | 16000 | 3.0 |
| 85524 | 12M4K-MTF X50FT | 4657-4024 | 1 | 3/4 | 1.17 | 4000 | 16000 | 3.8 |
| 70828 | 12M4K-MTFXREEL | 4657-1482 | 190 | 3/4 | 1.17 | 4000 | 16000 | 3.8 |
| 71103 | 16M4K-MTFXREEL | 4657-4053 | 165 | 1 | 1.52 | 4000 | 16000 | 4.5 |

# GLOBAL M4K MEGA4000™ HOSE - SAE 100R19 - XTRATUFF® COVER

## WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic applications. Exceeds ISO 18752 Grade B, SAE 100R19 and ISO 11237 R19. Allows for tighter minimum bend radius, increased working pressure and improved impulse cycles than industry standards. Provides greater performance, flexibility, easier routing and plumbing of mobile and stationary hydraulic platforms. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (XtraTuff® Nitrile), with color coded layline. Also available with unique abrasion resistant MegaTuff® or Standard covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –16) (G20) Section E<br>MegaCrimp® Couplings (–4 through –12) (G25) Section G<br>Stainless Steel Braid Couplings (–4 through –8) (G17) Section H<br>Stainless Steel Spiral Couplings (–12 and –16) (G18) Section F<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G" and ISO 11237 R19. Tested to Industry Leading 600,000 impulse cycles. XtraTuff® hose lasts up to 25 times longer than standard hose during hose–to–hose and hose–to–metal abrasion tests per ISO 6945.

| Part No. | Description | Product No. | Standard Pack | ⊖ | ↕O | | | R |
|---|---|---|---|---|---|---|---|---|
| 85541 | 4M4K-XTF X50FT | 4657-2616 | 1 | 1/4 | .55 | 4000 | 16000 | 1.5 |
| 70693 | 4M4K-XTFXREEL | 4657-2281 | 440 | 1/4 | .55 | 4000 | 16000 | 1.5 |
| 70459 | 5M4K-XTFXREEL | 4657-8016 | 350 | 5/16 | .61 | 4000 | 16000 | 1.8 |
| 85542 | 6M4K-XTF X50FT | 4657-2615 | 1 | 3/8 | .70 | 4000 | 16000 | 2.0 |
| 70694 | 6M4K-XTFXREEL | 4657-2283 | 330 | 3/8 | .70 | 4000 | 16000 | 2.0 |
| 85543 | 8M4K-XTF X50FT | 4657-2614 | 1 | 1/2 | .82 | 4000 | 16000 | 2.8 |
| 70695 | 8M4K-XTFXREEL | 4657-2284 | 220 | 1/2 | .82 | 4000 | 16000 | 2.8 |
| 70696 | 10M4K-XTFXREEL | 4657-2285 | 220 | 5/8 | .99 | 4000 | 16000 | 3.0 |
| 70697 | 12M4K-XTFXREEL | 4657-2286 | 220 | 3/4 | 1.17 | 4000 | 16000 | 3.8 |
| 71104 | 16M4K-XTFXREEL | 4657-4052 | 165 | 1 | 1.52 | 4000 | 16000 | 4.5 |

# GLOBAL M4KH MEGA4000™ HOSE - HIGH-TEMP - SAE 100R19

## WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic applications at elevated temperatures. Exceeds ISO 18752 Grade C, SAE 100R19 and ISO 11237 R19. Allows for tighter minimum bend radius, increased working pressure and improved impulse cycles than industry standards. Provides greater performance, flexibility, easier routing and plumbing of mobile and stationary hydraulic platforms. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (Polychloroprene), with color coded layline. Also available with unique abrasion resistant MegaTuff® cover. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –12) (G20) Section E<br>MegaCrimp® Couplings (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G" and ISO 11237 R19. Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85540 | 4M4KH X50FT | 4657-4098 | 1 | 1/4 | .55 | 4000 | 16000 | 2.0 |
| 70901 | 4M4KHXREEL | 4657-2381 | 440 | 1/4 | .55 | 4000 | 16000 | 2.0 |
| 85546 | 6M4KH X50FT | 4657-4099 | 1 | 3/8 | .70 | 4000 | 16000 | 2.5 |
| 70902 | 6M4KHXREEL | 4657-2383 | 330 | 3/8 | .70 | 4000 | 16000 | 2.5 |
| 85547 | 8M4KH X50FT | 4657-4100 | 1 | 1/2 | .82 | 4000 | 16000 | 3.5 |
| 70903 | 8M4KHXREEL | 4657-2384 | 220 | 1/2 | .82 | 4000 | 16000 | 3.5 |
| 85548 | 10M4KH X50FT | 4657-4101 | 1 | 5/8 | .99 | 4000 | 16000 | 4.0 |
| 70904 | 10M4KHXREEL | 4657-2385 | 220 | 5/8 | .99 | 4000 | 16000 | 4.0 |
| 85549 | 12M4KH X50FT | 4657-2619 | 1 | 3/4 | 1.17 | 4000 | 16000 | 4.7 |
| 70905 | 12M4KHXREEL | 4657-2386 | 220 | 3/4 | 1.17 | 4000 | 16000 | 4.7 |

# GLOBAL M4KH MEGA4000™ HOSE - HIGH-TEMP - SAE 100R19 - MEGATUFF® COVER

## WIRE BRAID




| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic applications at elevated temperatures. Exceeds ISO 18752 Grade C, SAE 100R19 and ISO 11237 R19. Allows for tighter minimum bend radius, increased working pressure and improved impulse cycles than industry standards. Provides greater performance, flexibility, easier routing and plumbing of mobile and stationary hydraulic platforms. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant MegaTuff® cover with color coded layline. Also available in Standard cover. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –12) (G20) Section E<br>MegaCrimp® Couplings (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Meets Flame Resistance Acceptance Designation "MSHA 2G" and ISO 11237 R19. MegaTuff® hose lasts up to 300 times longer than standard hose during hose–to–hose and hose–to–metal abrasion tests per ISO 6945. Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85448 | 4M4KH-MTF X50FT | 4657-4093 | 1 | 1/4 | .55 | 4000 | 16000 | 2.0 |
| 70956 | 4M4KH-MTFXREEL | 4657-2157 | 440 | 1/4 | .55 | 4000 | 16000 | 2.0 |
| 85449 | 6M4KH-MTF X50FT | 4657-4094 | 1 | 3/8 | .70 | 4000 | 16000 | 2.5 |
| 70957 | 6M4KH-MTFXREEL | 4657-2159 | 330 | 3/8 | .70 | 4000 | 16000 | 2.5 |
| 85450 | 8M4KH-MTF X50FT | 4657-4095 | 1 | 1/2 | .82 | 4000 | 16000 | 3.5 |
| 70958 | 8M4KH-MTFXREEL | 4657-2160 | 220 | 1/2 | .82 | 4000 | 16000 | 3.5 |
| 85451 | 10M4KH-MTF X50FT | 4657-4096 | 1 | 5/8 | .99 | 4000 | 16000 | 4.0 |
| 70959 | 10M4KH-MTFXREEL | 4657-2161 | 220 | 5/8 | .99 | 4000 | 16000 | 4.0 |
| 85452 | 12M4KH-MTF X50FT | 4657-4097 | 1 | 3/4 | 1.17 | 4000 | 16000 | 4.7 |
| 70973 | 12M4KH-MTFXREEL | 4657-2396 | 190 | 3/4 | 1.17 | 4000 | 16000 | 4.7 |

## GLOBAL M4KL MEGA4000™ POLARFLEX® HOSE - SAE 100R19

### WIRE BRAID




| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic applications in low–temperature environments. Exceeds ISO 18752 Grade B, SAE 100R19 and ISO 11237 R19. Allows for tighter minimum bend radius, increased working pressure and improved impulse cycles than industry standards. Provides greater performance, flexibility, easier routing and plumbing of mobile and stationary hydraulic platforms. |
| TUBE | Black, oil resistant (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant synthetic rubber (Polychloroprene), with color coded layline. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –70°F to +212°F (–57°C to +100°C). |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –16) (G20) Section E<br>MegaCrimp® Couplings (–4 through –12) (G25) Section G<br>Stainless Steel Braid Couplings (–4 through –8) (G17) Section H<br>Stainless Steel Spiral Couplings (–12 and –16) (G18) Section F<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Meets Flame Resistance Acceptance Designation "MSHA 2G". Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70148 | 4M4KLXREEL | 4657-4470 | 440 | 1/4 | .54 | 4000 | 16000 | 2.0 |
| 70149 | 5M4KLXREEL | 4657-4471 | 350 | 5/16 | .60 | 4000 | 16000 | 2.3 |
| 70150 | 6M4KLXREEL | 4657-4472 | 330 | 3/8 | .69 | 4000 | 16000 | 2.5 |
| 70151 | 8M4KLXREEL | 4657-4473 | 220 | 1/2 | .82 | 4000 | 16000 | 3.5 |
| 70152 | 10M4KLXREEL | 4657-4474 | 220 | 5/8 | .98 | 4000 | 16000 | 4.0 |
| 70153 | 12M4KLXREEL | 4657-4475 | 220 | 3/4 | 1.16 | 4000 | 16000 | 6.0 |
| 70154 | 16M4KLXREEL | 4657-4476 | 165 | 1 | 1.52 | 4000 | 16000 | 6.0 |

## GLOBAL M3K MEGA3000® HOSE - SAE 100R17

### WIRE BRAID




| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic oil lines. Exceeds ISO 18752 Grade B, SAE 100R17 and ISO 11237 R17 working pressure, minimum bend radius requirements and performance requirements of EN 857 1SC. M3K hose has smaller exterior dimensions and significantly tighter bend radius than other SAE 100R1 and 100R2 hose. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Braided, high–tensile steel wire. –4, –5, –6 and –8 sizes are one braid; –10, –12 and –16 sizes are two braid. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (Nitrile and PVC), with color coded layline. Also available with unique abrasion resistant MegaTuff® or XtraTuff® covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –16) (G20) Section E<br>MegaCrimp® Couplings (G25) Section G<br>Power Crimp® Couplings (–3) Section I<br>Stainless Steel Braid Couplings (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Meets Flame Resistance Acceptance Designation "MSHA 2G" and ISO 11237 R17. Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70352 | 3M3KXREEL | 4657-8068 | 440 | 3/16 | .43 | 3250 | 13000 | 1.3 |

## GLOBAL M3K MEGA3000® HOSE - SAE 100R17 - CONTINUED

### WIRE BRAID - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85624 | 4M3K X50FT | 4657-4874 | 1 | 1/4 | .48 | 3250 | 13000 | 1.5 |
| | 4M3KXBALE | 4657-5743 | 6000 | 1/4 | .48 | 3250 | 13000 | 1.5 |
| | 4M3KXLG REEL | 4657-1176 | 1400 | 1/4 | .48 | 3250 | 13000 | 1.5 |
| 70485 | 4M3KXREEL | 4657-1157 | 440 | 1/4 | .48 | 3250 | 13000 | 1.5 |
| 85609 | 5M3K X50FT | 4657-2502 | 1 | 5/16 | .60 | 3250 | 13000 | 1.8 |
| 70575 | 5M3KXREEL | 4657-2216 | 385 | 5/16 | .60 | 3250 | 13000 | 1.8 |
| 85625 | 6M3K X50FT | 4657-4875 | 1 | 3/8 | .63 | 3250 | 13000 | 2.0 |
| | 6M3KXBALE | 4657-5744 | 4500 | 3/8 | .63 | 3250 | 13000 | 2.0 |
| | 6M3KXLG REEL | 4657-1177 | 1000 | 3/8 | .63 | 3250 | 13000 | 2.0 |
| 70486 | 6M3KXREEL | 4657-1158 | 330 | 3/8 | .63 | 3250 | 13000 | 2.0 |
| 85626 | 8M3K X50FT | 4657-4876 | 1 | 1/2 | .80 | 3250 | 13000 | 2.8 |
| | 8M3KXBALE | 4657-5745 | 2800 | 1/2 | .80 | 3250 | 13000 | 2.8 |
| | 8M3KXLG REEL | 4657-1178 | 1000 | 1/2 | .80 | 3250 | 13000 | 2.8 |
| 70487 | 8M3KXREEL | 4657-1159 | 220 | 1/2 | .80 | 3250 | 13000 | 2.8 |
| 85627 | 10M3K X50FT | 4657-4877 | 1 | 5/8 | .99 | 3250 | 13000 | 3.0 |
| | 10M3KXBALE | 4657-5746 | 1800 | 5/8 | .99 | 3250 | 13000 | 3.0 |
| | 10M3KXLG REEL | 4657-0233 | 800 | 5/8 | .99 | 3250 | 13000 | 3.0 |
| 70488 | 10M3KXREEL | 4657-1173 | 220 | 5/8 | .99 | 3250 | 13000 | 3.0 |
| 85628 | 12M3K X50FT | 4657-4878 | 1 | 3/4 | 1.15 | 3250 | 13000 | 3.8 |
| | 12M3KXBALE | 4657-5747 | 1250 | 3/4 | 1.15 | 3250 | 13000 | 3.8 |
| 70489 | 12M3KXREEL | 4657-0679 | 220 | 3/4 | 1.15 | 3250 | 13000 | 3.8 |
| 85629 | 16M3K X50FT | 4657-4879 | 1 | 1 | 1.48 | 3250 | 13000 | 4.5 |
| | 16M3KXBALE | 4657-5748 | 700 | 1 | 1.48 | 3250 | 13000 | 4.5 |
| 70490 | 16M3KXREEL | 4657-1163 | 165 | 1 | 1.48 | 3250 | 13000 | 4.5 |

# GLOBAL M3K MEGA3000® HOSE - SAE 100R17 - MEGATUFF® COVER

## WIRE BRAID




| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic oil lines. Exceeds ISO 18752 Grade B, SAE 100R17 and ISO 11237 R17 working pressure, minimum bend radius requirements and performance requirements of EN 857 1SC. M3K hose has smaller exterior dimensions and significantly tighter bend radius than other SAE 100R1 and 100R2 hose. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Braided, high–tensile steel wire. –4, –5, –6 and –8 sizes are one braid; –10, –12 and –16 sizes are two braid. |
| COVER | Black, oil, abrasion and weather resistant MegaTuff® cover with color coded layline. Also available with unique abrasion resistant XtraTuff® or Standard covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –16) (G20) Section E<br>MegaCrimp® Couplings (G25) Section G<br>Stainless Steel Braid Couplings (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Meets Flame Resistance Acceptance Designation "MSHA 2G" and ISO 11237 R17. MegaTuff® hose lasts up to 300 times longer than standard hose during hose–to–hose and hose–to–metal abrasion tests per ISO 6945. Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85525 | 4M3K-MTF X50FT | 4657-4025 | 1 | 1/4 | .48 | 3250 | 13000 | 1.5 |
| | 4M3K-MTFXBALE | 4657-5769 | 5600 | 1/4 | .48 | 3250 | 13000 | 1.5 |
| | 4M3K-MTFXLG REEL | 4657-1180 | 1400 | 1/4 | .48 | 3250 | 13000 | 1.5 |
| 70565 | 4M3K-MTFXREEL | 4657-1181 | 440 | 1/4 | .48 | 3250 | 13000 | 1.5 |
| 85526 | 6M3K-MTF X50FT | 4657-4026 | 1 | 3/8 | .63 | 3250 | 13000 | 2.0 |
| | 6M3K-MTFXBALE | 4657-5770 | 3800 | 3/8 | .63 | 3250 | 13000 | 2.0 |
| | 6M3K-MTFXLG REEL | 4657-1192 | 1000 | 3/8 | .63 | 3250 | 13000 | 2.0 |
| 70566 | 6M3K-MTFXREEL | 4657-1182 | 330 | 3/8 | .63 | 3250 | 13000 | 2.0 |
| 85527 | 8M3K-MTF X50FT | 4657-4027 | 1 | 1/2 | .80 | 3250 | 13000 | 2.8 |
| | 8M3K-MTFXBALE | 4657-5771 | 2500 | 1/2 | .80 | 3250 | 13000 | 2.8 |
| | 8M3K-MTFXLG REEL | 4657-1193 | 1000 | 1/2 | .80 | 3250 | 13000 | 2.8 |
| 70567 | 8M3K-MTFXREEL | 4657-1183 | 330 | 1/2 | .80 | 3250 | 13000 | 2.8 |
| 85528 | 10M3K-MTF X50FT | 4657-4028 | 1 | 5/8 | .99 | 3250 | 13000 | 3.0 |
| | 10M3K-MTFXBALE | 4657-5772 | 2500 | 5/8 | .99 | 3250 | 13000 | 3.0 |
| 70559 | 10M3K-MTFXREEL | 4657-1184 | 220 | 5/8 | .99 | 3250 | 13000 | 3.0 |
| 85529 | 12M3K-MTF X50FT | 4657-4029 | 1 | 3/4 | 1.15 | 3250 | 13000 | 3.8 |
| 70560 | 12M3K-MTFXREEL | 4657-1185 | 220 | 3/4 | 1.15 | 3250 | 13000 | 3.8 |
| 85530 | 16M3K-MTF X50FT | 4657-4030 | 1 | 1 | 1.48 | 3250 | 13000 | 4.8 |
| | 16M3K-MTFXBALE | 4657-5774 | 800 | 1 | 1.48 | 3250 | 13000 | 4.8 |
| 70562 | 16M3K-MTFXREEL | 4657-1186 | 165 | 1 | 1.48 | 3250 | 13000 | 4.8 |

# GLOBAL M3K MEGA3000® HOSE - SAE 100R17 - XTRATUFF® COVER

## WIRE BRAID




| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic oil lines. Exceeds ISO 18752 Grade B, SAE 100R17 and ISO 11237 R17 working pressure, minimum bend radius requirements and performance requirements of EN 857 1SC. M3K hose has smaller exterior dimensions and significantly tighter bend radius than other SAE 100R1 and 100R2 hose. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Braided, high–tensile steel wire. –4, –5, –6 and –8 sizes are one braid; –10, –12 and –16 sizes are two braid. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (XtraTuff® Nitrile), with color coded layline. Also available with unique abrasion resistant MegaTuff® or Standard covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –16) (G20) Section E<br>MegaCrimp® Couplings (G25) Section G<br>Power Crimp® Couplings (–3) Section I<br>Stainless Steel Braid Couplings (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Meets Flame Resistance Acceptance Designation "MSHA 2G" and ISO 11237 R17. Tested to Industry Leading 600,000 impulse cycles. XtraTuff® hose lasts up to 25 times longer than standard hose during hose–to–hose and hose–to–metal abrasion tests per ISO 6945.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70969 | 3M3K-XTFXREEL | 4657-8069 | 440 | 3/16 | .43 | 3250 | 13000 | 1.3 |
| | 4M3K-XTFXBALE | 4657-2434 | 5600 | 1/4 | .48 | 3250 | 13000 | 1.5 |
| 70569 | 4M3K-XTFXREEL | 4657-1097 | 440 | 1/4 | .48 | 3250 | 13000 | 1.5 |
| | 5M3K-XTFXBALE | 4657-2628 | 4400 | 5/16 | .60 | 3250 | 13000 | 1.8 |
| | 6M3K-XTFXBALE | 4657-2627 | 4800 | 3/8 | .63 | 3250 | 13000 | 2.0 |
| 70570 | 6M3K-XTFXREEL | 4657-1098 | 330 | 3/8 | .63 | 3250 | 13000 | 2.0 |
| | 8M3K-XTFXBALE | 4657-1099 | 2500 | 1/2 | .80 | 3250 | 13000 | 2.8 |
| 70571 | 8M3K-XTFXREEL | 4657-2248 | 220 | 1/2 | .80 | 3250 | 13000 | 2.8 |
| 70572 | 10M3K-XTFXREEL | 4657-2249 | 220 | 5/8 | .99 | 3250 | 13000 | 3.0 |
| 70573 | 12M3K-XTFXREEL | 4657-2250 | 220 | 3/4 | 1.15 | 3250 | 13000 | 3.8 |
| 70574 | 16M3K-XTFXREEL | 4657-2307 | 165 | 1 | 1.48 | 3250 | 13000 | 4.5 |

## GLOBAL M3KH MEGA3000® HOSE - HIGH-TEMP - SAE 100R17

### WIRE BRAID




| | |
|---|---|
| RECOMMENDED FOR | Elevated temperature high–pressure hydraulic oil lines. Exceeds ISO 18752 Grade C, SAE 100R17 and ISO 11237 R17 requirements and performance requirements of EN 857 1SC. M3KH hose has smaller exterior dimensions and significantly tighter bend radius than other SAE 100R1 and 100R2 hose. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Braided, high–tensile steel wire. –4, –5, –6 and –8 sizes are one braid; –10, –12 and –16 sizes are two braid. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (Polychloroprene), with color coded layline. Also available with unique abrasion resistant MegaTuff® cover. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –16) (G20) Section E<br>MegaCrimp® Couplings (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Meets Flame Resistance Acceptance Designation "MSHA 2G" and ISO 11237 R17. Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70898 | 4M3KHXREEL | 4657-2664 | 440 | 1/4 | .48 | 3250 | 13000 | 2.0 |
| 70789 | 5M3KHXREEL | 4657-4055 | 330 | 5/16 | .60 | 3250 | 13000 | 2.2 |
| 70899 | 6M3KHXREEL | 4657-2696 | 330 | 3/8 | .65 | 3250 | 13000 | 2.5 |
| 70953 | 8M3KHXREEL | 4657-1360 | 220 | 1/2 | .80 | 3250 | 13000 | 3.5 |
| 70954 | 10M3KHXREEL | 4657-1361 | 220 | 5/8 | .99 | 3250 | 13000 | 4.0 |
| 70955 | 12M3KHXREEL | 4657-1362 | 220 | 3/4 | 1.15 | 3250 | 13000 | 4.8 |
| 70907 | 16M3KHXREEL | 4657-1363 | 165 | 1 | 1.48 | 3250 | 13000 | 6.0 |

## GLOBAL M3KH MEGA3000® HOSE - HIGH-TEMP - SAE 100R17 - MEGATUFF® COVER

### WIRE BRAID




| | |
|---|---|
| RECOMMENDED FOR | Elevated temperature high–pressure hydraulic oil lines. Exceeds ISO 18752 Grade C, SAE 100R17 and ISO 11237 R17 working pressure, minimum bend radius requirements and performance requirements of EN 857 1SC. M3KH hose has smaller exterior dimensions and significantly tighter bend radius than other SAE 100R1 and 100R2 hose. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Braided, high–tensile steel wire. –4, –6 and –8 sizes are one braid; –10, –12 and –16 sizes are two braid. |
| COVER | Black, oil, abrasion and weather resistant MegaTuff® cover with color coded layline. Also available in Standard cover. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –16) (G20) Section E<br>MegaCrimp® Couplings (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Meets Flame Resistance Acceptance Designation "MSHA 2G" and ISO 11237 R17. MegaTuff® hose lasts up to 300 times longer than standard hose during hose–to–hose and hose–to–metal abrasion tests per ISO 6945. Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 71030 | 4M3KH-MTFXREEL | 4657-2321 | 440 | 1/4 | .48 | 3250 | 13000 | 2.0 |

## GLOBAL M3KH MEGA3000® HOSE - HIGH-TEMP - SAE 100R17 - MEGATUFF® COVER - CONTINUED

### WIRE BRAID - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 71031 | 6M3KH-MTFXREEL | 4657-2323 | 330 | 3/8 | .63 | 3250 | 13000 | 2.5 |
| 71032 | 8M3KH-MTFXREEL | 4657-2324 | 330 | 1/2 | .80 | 3250 | 13000 | 3.5 |
| 71033 | 10M3KH-MTFXREEL | 4657-2325 | 220 | 5/8 | .99 | 3250 | 13000 | 4.0 |
| 71034 | 12M3KH-MTFXREEL | 4657-2326 | 220 | 3/4 | 1.15 | 3250 | 13000 | 4.8 |
| 71035 | 16M3KH-MTFXREEL | 4657-2327 | 165 | 1 | 1.48 | 3250 | 13000 | 6.0 |

## MXT™ MEGASYS® WIRE BRAID HOSE - SAE 100R16

### WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic oil lines. Meets SAE 100R16 dimensions and performance. Meets SAE 100R17 (6, 8, 10, and 12) dimension and performance. Meets SAE 100R2 performance. Meets SAE 100R19 (6, and 8) performance. MXT hose has smaller exterior dimensions, lower force to bend and significantly tighter bend radius than all SAE specs listed above. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Patent–Pending, Gates–Engineered, high–tensile steel wire braid reinforcement. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (nitrile), with color coded layline. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (–6 through –16) (G25) Section G (See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G". Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85047 | 6MXT X50FT | 4657-9799 | 1 | 3/8 | .68 | 4800 | 19200 | 2.5 |
| 70348 | 6MXTX100REEL | 4657-9800 | 100 | 3/8 | .68 | 4800 | 19200 | 2.5 |
| 70336 | 6MXTXBALE | 4657-9661 | 3000 | 3/8 | .68 | 4800 | 19200 | 2.5 |
| 70367 | 6MXTXLRG REEL | 4657-9807 | 1500 | 3/8 | .68 | 4800 | 19200 | 2.5 |
| 70276 | 6MXTXREEL | 4657-9660 | 400 | 3/8 | .68 | 4800 | 19200 | 2.5 |
| 85048 | 8MXT X50FT | 4657-9801 | 1 | 1/2 | .80 | 4000 | 16000 | 2.75 |
| 70354 | 8MXTX100REEL | 4657-9802 | 100 | 1/2 | .80 | 4000 | 16000 | 2.75 |
| 70337 | 8MXTXBALE | 4657-9663 | 2500 | 1/2 | .80 | 4000 | 16000 | 2.75 |
| 70374 | 8MXTXLRG REEL | 4657-9808 | 1000 | 1/2 | .80 | 4000 | 16000 | 2.75 |
| 70283 | 8MXTXREEL | 4657-9662 | 330 | 1/2 | .80 | 4000 | 16000 | 2.75 |
| 85051 | 10MXT X50FT | 4657-9803 | 1 | 5/8 | .95 | 3625 | 14500 | 3.0 |
| 70338 | 10MXTXBALE | 4657-9665 | 1750 | 5/8 | .95 | 3625 | 14500 | 3.0 |
| 70289 | 10MXTXREEL | 4657-9664 | 220 | 5/8 | .95 | 3625 | 14500 | 3.0 |
| 85052 | 12MXT X50FT | 4657-9804 | 1 | 3/4 | 1.08 | 3125 | 12500 | 4.75 |
| 70355 | 12MXTX50REEL | 4657-9805 | 50 | 3/4 | 1.08 | 3125 | 12500 | 4.75 |
| 70342 | 12MXTXBALE | 4657-9667 | 1500 | 3/4 | 1.08 | 3125 | 12500 | 4.75 |
| 70327 | 12MXTXREEL | 4657-9666 | 220 | 3/4 | 1.08 | 3125 | 12500 | 4.75 |
| 85053 | 16MXTX50FT | 4657-9806 | 1 | 1 | 1.38 | 2400 | 9600 | 6.0 |
| 70344 | 16MXTXBALE | 4657-9669 | 1200 | 1 | 1.38 | 2400 | 9600 | 6.0 |
| 70335 | 16MXTXREEL | 4657-9668 | 165 | 1 | 1.38 | 2400 | 9600 | 6.0 |

# M2T® MEGAFLEX® 2-WIRE BRAID HOSE - SAE 100R16

## WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic oil lines. Exceeds SAE 100R16, SAE 100R2, ISO 11237 2SC R16 and ISO 1436 2SN R2 requirements and performance requirements of EN 857 2SC and EN 853 2SN. M2T hose has smaller exterior dimensions and significantly tighter bend radius. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (Nitrile and PVC), with color coded layline. Also available with unique abrasion resistant MegaTuff® or XtraTuff® covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –16) (G20) Section E<br>GlobalSpiral™ Plus Couplings (–24 and –32) (G22) Section E<br>MegaCrimp® Couplings (–4 through –20) (G25) Section G<br>Stainless Steel Braid Couplings (–4 through –16) (G17) Section H<br>Stainless Steel Spiral Couplings (–20 and –24) (G18) Section F<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G" and ISO 11237 2SC R16. Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85600 | 4M2T X50FT | 4657-1553 | 1 | 1/4 | .56 | 6000 | 24000 | 1.5 |
| 71102 | 4M2TX150REEL | 4657-4422 | 150 | 1/4 | .56 | 6000 | 24000 | 1.5 |
| | 4M2TXBALE | 4657-5728 | 5600 | 1/4 | .56 | 6000 | 24000 | 1.5 |
| 70390 | 4M2TXREEL | 4657-1552 | 550 | 1/4 | .56 | 6000 | 24000 | 1.5 |
| 85601 | 6M2T X50FT | 4657-1550 | 1 | 3/8 | .70 | 5000 | 20000 | 2.0 |
| 70260 | 6M2TX100REEL | 4657-4607 | 100 | 3/8 | .70 | 5000 | 20000 | 2.0 |
| | 6M2TXBALE | 4657-5729 | 3000 | 3/8 | .69 | 5000 | 20000 | 2.0 |
| | 6M2TXLRG REEL | 4657-1492 | 1500 | 3/8 | .70 | 5000 | 20000 | 2.0 |
| 70391 | 6M2TXREEL | 4657-1555 | 385 | 3/8 | .70 | 5000 | 20000 | 2.0 |
| 85602 | 8M2TX50FT | 4657-1561 | 1 | 1/2 | .82 | 4300 | 17200 | 2.8 |
| 70261 | 8M2TX100REEL | 4657-4608 | 100 | 1/2 | .82 | 4300 | 17200 | 2.8 |
| | 8M2TXBALE | 4657-5730 | 2500 | 1/2 | .82 | 4300 | 17200 | 2.8 |
| | 8M2TXLRG REEL | 4657-1493 | 1000 | 1/2 | .82 | 4300 | 17200 | 2.8 |
| 70392 | 8M2TXREEL | 4657-1559 | 330 | 1/2 | .82 | 4300 | 17200 | 2.8 |
| 85603 | 10M2T X50FT | 4657-1564 | 1 | 5/8 | .95 | 3800 | 15200 | 3.0 |
| | 10M2TXBALE | 4657-5577 | 1750 | 5/8 | .95 | 3800 | 15200 | 3.0 |
| 70393 | 10M2TXREEL | 4657-1563 | 220 | 5/8 | .95 | 3800 | 15200 | 3.0 |
| 85604 | 12M2T X50FT | 4657-1568 | 1 | 3/4 | 1.11 | 3500 | 14000 | 3.8 |
| 70262 | 12M2TX50REEL | 4657-4609 | 50 | 3/4 | 1.11 | 3500 | 14000 | 3.8 |
| | 12M2TXBALE | 4657-5732 | 1500 | 3/4 | 1.11 | 3500 | 14000 | 3.8 |
| 70394 | 12M2TXREEL | 4657-1567 | 220 | 3/4 | 1.11 | 3500 | 14000 | 3.8 |
| 85605 | 16M2T X50FT | 4657-1572 | 1 | 1 | 1.39 | 2500 | 10000 | 4.5 |
| 70395 | 16M2TXREEL | 4657-1571 | 165 | 1 | 1.39 | 2500 | 10000 | 4.5 |
| 80302 | 20M2T X25FT | 4657-4540 | 1 | 1 1/4 | 1.67 | 2300 | 9200 | 8.3 |
| 70025 | 20M2TXCTN | 4657-4534 | 120 | 1 1/4 | 1.67 | 2300 | 9200 | 8.3 |
| 80048 | 24M2T X25FT | 4657-4610 | 1 | 1 1/2 | 2.00 | 2000 | 8000 | 10.0 |
| 80303 | 24M2T X50FT | 4657-4541 | 1 | 1 1/2 | 2.00 | 2000 | 8000 | 10.0 |
| 70145 | 24M2TXCTN | 4657-4491 | 120 | 1 1/2 | 2.00 | 2000 | 8000 | 10.0 |
| 80049 | 32M2T X25FT | 4657-4611 | 1 | 2 | 2.53 | 1500 | 6000 | 12.5 |
| 80304 | 32M2T X50FT | 4657-4542 | 1 | 2 | 2.53 | 1500 | 6000 | 12.5 |
| 70146 | 32M2TXCTN | 4657-4492 | 120 | 2 | 2.53 | 1500 | 6000 | 12.5 |

# M2T® MEGAFLEX® 2-WIRE BRAID HOSE - SAE 100R16 - MEGATUFF® COVER

## WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | Ultra high abrasion resistant high–pressure hydraulic oil lines. Exceeds SAE 100R16, SAE 100R2, ISO 11237 2SC R16 and ISO 1436 2SN R2 working pressure, minimum bend radius requirements and performance requirements of EN 857 2SC and EN 853 2SN. M2T hose has smaller exterior dimensions and significantly tighter bend radius. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant MegaTuff® cover with color coded layline. Also available with unique abrasion resistant XtraTuff® or Standard covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –16) (G20) Section E<br>MegaCrimp® Couplings (G25) Section G<br>Stainless Steel Braid Couplings (–4 through –16) (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G" and ISO 11237 2SC R16. MegaTuff® hose lasts up to 300 times longer than standard hose during hose–to–hose and hose–to–metal abrasion tests per ISO 6945. Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | ⟷ | ⌀ | | | R |
|---|---|---|---|---|---|---|---|---|
| 85534 | 4M2T-MTF X50FT | 4657-4034 | 1 | 1/4 | .56 | 6000 | 24000 | 1.5 |
| | 4M2T-MTFXBALE | 4657-5764 | 5600 | 1/4 | .56 | 6000 | 24000 | 1.5 |
| 70387 | 4M2T-MTFXREEL | 4657-0222 | 350 | 1/4 | .56 | 6000 | 24000 | 1.5 |
| 85535 | 6M2T-MTF X50FT | 4657-4035 | 1 | 3/8 | .70 | 5000 | 20000 | 2.0 |
| | 6M2T-MTFXBALE | 4657-5765 | 2400 | 3/8 | .70 | 5000 | 20000 | 2.0 |
| 70388 | 6M2T-MTFXREEL | 4657-0223 | 330 | 3/8 | .70 | 5000 | 20000 | 2.0 |
| 85536 | 8M2T-MTF X50FT | 4657-4036 | 1 | 1/2 | .82 | 4300 | 17200 | 2.8 |
| | 8M2T-MTFXBALE | 4657-5766 | 2200 | 1/2 | .82 | 4300 | 17200 | 2.8 |
| 70389 | 8M2T-MTFXREEL | 4657-0224 | 330 | 1/2 | .82 | 4300 | 17200 | 2.8 |
| 85537 | 10M2T-MTF X50FT | 4657-4037 | 1 | 5/8 | .95 | 3800 | 15200 | 3.0 |
| 70407 | 10M2T-MTFXREEL | 4657-0225 | 220 | 5/8 | .95 | 3800 | 15200 | 3.0 |
| 85538 | 12M2T-MTF X50FT | 4657-4038 | 1 | 3/4 | 1.11 | 3500 | 14000 | 3.8 |
| 70408 | 12M2T-MTFXREEL | 4657-0226 | 220 | 3/4 | 1.11 | 3500 | 14000 | 3.8 |
| 85539 | 16M2T-MTF X50FT | 4657-4039 | 1 | 1 | 1.39 | 2500 | 10000 | 4.5 |
| 70409 | 16M2T-MTFXREEL | 4657-0227 | 165 | 1 | 1.39 | 2500 | 10000 | 4.5 |

# M2T® MEGAFLEX® 2-WIRE BRAID HOSE - SAE 100R16 - XTRATUFF® COVER

## WIRE BRAID




| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic oil lines. Exceeds SAE 100R16, SAE 100R2, ISO 11237 2SC R16 and ISO 1436 2SN R2 working pressure, minimum bend radius requirements and performance requirements of EN 857 2SC and EN 853 2SN. M2T hose has smaller exterior dimensions and significantly tighter bend radius. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (XtraTuff® Nitrile), with color coded layline. Also available with unique abrasion resistant MegaTuff® or Standard covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –16) (G20) Section E<br>GlobalSpiral™ Plus Couplings (–24 and –32) (G22) Section E<br>MegaCrimp® Couplings (G25) Section G<br>Stainless Steel Braid Couplings (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Meets Flame Resistance Acceptance Designation "MSHA 2G" and ISO 11237 2SC R16. Tested to Industry Leading 600,000 impulse cycles. XtraTuff® hose lasts up to 25 times longer than standard hose during hose–to–hose and hose–to–metal abrasion tests per ISO 6945.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 71061 | 4M2T-XTFXREEL | 4657-4138 | 350 | 1/4 | .56 | 6000 | 24000 | 1.5 |
| 71038 | 6M2T-XTFXREEL | 4657-4302 | 330 | 3/8 | .70 | 5000 | 20000 | 2.0 |
| 71040 | 8M2T-XTFXREEL | 4657-4304 | 330 | 1/2 | .82 | 4300 | 17200 | 2.8 |
| 71043 | 10M2T-XTFXREEL | 4657-4307 | 220 | 5/8 | .95 | 3800 | 15200 | 3.0 |
| 71046 | 12M2T-XTFXREEL | 4657-4310 | 220 | 3/4 | 1.11 | 3500 | 14000 | 3.8 |
| 71049 | 16M2T-XTFXREEL | 4657-4313 | 165 | 1 | 1.39 | 2500 | 10000 | 4.5 |
| 70221 | 20M2T-XTFXCTN | 4657-4651 | 130 | 1 1/4 | 1.67 | 2300 | 9200 | 8.3 |
| 70100 | 24M2T-XTFXCTN | 4657-4652 | 130 | 1 1/2 | 2.00 | 2000 | 8000 | 10.0 |
| 70101 | 32M2T-XTFXCTN | 4657-4653 | 130 | 2 | 2.53 | 1500 | 6000 | 12.5 |

## CM2TDL MEGAFLEX® CONNECTED DUAL-LINE 2-WIRE BRAID - SAE 100R16 - XTRATUFF® COVER

### WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | High abrasive high–pressure hydraulic oil lines joined together for easier plumbing and routing. Meets SAE 100R16 requirements. CM2T hose has smaller exterior dimensions and significantly tighter bend radius. Exceeds performance standards of EN 857 2SC and ISO/DIS 1436. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (XtraTuff® Nitrile), with color coded layline. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (G20) Section E<br>MegaCrimp® Couplings (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G". Tested to Industry Leading 600,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85389 | 6CM2TDL-XTF X50FT | 4657-4980 | 1 | 3/8 | .70 | 4800 | 19200 | 3.5 |
| 71151 | 6CM2TDL-XTFXCTN | 4657-4974 | 215 | 3/8 | .70 | 4800 | 19200 | 3.5 |
| 85390 | 8CM2TDL-XTF X50FT | 4657-4981 | 1 | 1/2 | .82 | 4000 | 16000 | 5.0 |
| 71152 | 8CM2TDL-XTFXCTN | 4657-4975 | 180 | 1/2 | .82 | 4000 | 16000 | 5.0 |

## GLOBAL G2 2-WIRE BRAID HOSE - SAE 100R2 TYPE AT

### WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | High–pressure hydraulic oil lines. Meets or exceeds the requirements of SAE 100R2, ISO 1436 2SN R2 and EN 853 2SN. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil and abrasion resistant, synthetic rubber (Nitrile and PVC). See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | Field Attachable Type T Couplings (–4 through –16) (G28) Section J<br>GlobalSpiral™ Couplings (–6 through –16) (G20) Section E<br>MegaCrimp® Couplings (–4 through –16) (G25) Section G<br>Power Crimp® Couplings (–3) Section I<br>Stainless Steel Braid Couplings (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 86620 | 3G2 X50FT | 4657-0029 | 1 | 3/16 | .52 | 6025 | 24100 | 3.5 |
| 70233 | 3G2XREEL | 4657-2182 | 440 | 3/16 | .52 | 6025 | 24100 | 3.5 |
| 86621 | 4G2 X50FT | 4657-4941 | 1 | 1/4 | .59 | 5800 | 23200 | 4.0 |
| 71101 | 4G2X150REEL | 4657-4421 | 150 | 1/4 | .59 | 5800 | 23200 | 4.0 |
| | 4G2XBALE | 4657-5708 | 4000 | 1/4 | .59 | 5800 | 23200 | 4.0 |
| 70605 | 4G2XREEL | 4657-0125 | 550 | 1/4 | .59 | 5800 | 23200 | 4.0 |
| 86622 | 6G2 X50FT | 4657-4916 | 1 | 3/8 | .74 | 4800 | 19200 | 5.0 |
| 86632 | 6G2 X100FT | 4657-4906 | 1 | 3/8 | .74 | 4800 | 19200 | 5.0 |
| | 6G2XBALE | 4657-5709 | 3000 | 3/8 | .74 | 4800 | 19200 | 5.0 |

## GLOBAL G2 2-WIRE BRAID HOSE - SAE 100R2 TYPE AT - CONTINUED

### WIRE BRAID - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70606 | 6G2XREEL | 4657-0126 | 400 | 3/8 | .74 | 4800 | 19200 | 5.0 |
| 86623 | 8G2 X50FT | 4657-4918 | 1 | 1/2 | .86 | 4000 | 16000 | 7.0 |
| 86634 | 8G2 X100FT | 4657-4908 | 1 | 1/2 | .86 | 4000 | 16000 | 7.0 |
| | 8G2XBALE | 4657-5710 | 2250 | 1/2 | .86 | 4000 | 16000 | 7.0 |
| 70607 | 8G2XREEL | 4657-0127 | 330 | 1/2 | .86 | 4000 | 16000 | 7.0 |
| 86626 | 10G2 X50FT | 4657-1965 | 1 | 5/8 | .99 | 3625 | 14500 | 8.0 |
| | 10G2XBALE | 4657-5711 | 1800 | 5/8 | .99 | 3625 | 14500 | 8.0 |
| 70610 | 10G2XREEL | 4657-0132 | 220 | 5/8 | .99 | 3625 | 14500 | 8.0 |
| 86624 | 12G2 X50FT | 4657-4943 | 1 | 3/4 | 1.15 | 3100 | 12400 | 9.5 |
| 86635 | 12G2 X50FT REEL | 4657-4909 | 1 | 3/4 | 1.15 | 3100 | 12400 | 9.5 |
| | 12G2XBALE | 4657-5712 | 1250 | 3/4 | 1.15 | 3100 | 12400 | 9.5 |
| 70608 | 12G2XREEL | 4657-0128 | 220 | 3/4 | 1.15 | 3100 | 12400 | 9.5 |
| 86625 | 16G2 X50FT | 4657-4945 | 1 | 1 | 1.48 | 2400 | 9600 | 12.0 |
| | 16G2XBALE | 4657-1094 | 700 | 1 | 1.48 | 2400 | 9600 | 12.0 |
| 70609 | 16G2XREEL | 4657-0129 | 165 | 1 | 1.48 | 2400 | 9600 | 12.0 |

## GLOBAL G2H HIGH-TEMP 2-WIRE BRAID HOSE - SAE 100R2 TYPE AT

### WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | High–temperature high–pressure hydraulic oil lines. Meets or exceeds the requirements of SAE 100R2, ISO 1436 2SN R2 and EN 853 2SN. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil resistant, synthetic rubber (CSM). Also available with unique abrasion resistant MegaTuff® cover. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +275°F (–40°C to +135°C) constant and +300°F (+149°C) intermittent (up to 10% of operating time). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | Field Attachable Type T Couplings (–20 and –24) (G28) Section J<br>GlobalSpiral™ Couplings (–20) (G20) Section E<br>GlobalSpiral™ Plus Couplings (–24 and –32) (G22) Section E<br>MegaCrimp® Couplings (–20) (G25) Section G<br>Stainless Steel Braid Couplings (–24 and –32) (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 86520 | 20G2H X50FT | 4657-0925 | 1 | 1 1/4 | 1.86 | 1825 | 6500 | 16.5 |
| 70230 | 20G2HXCTN | 4657-0930 | 120 | 1 1/4 | 1.86 | 1825 | 6500 | 16.5 |
| 85427 | 24G2H X25FT | 4657-4331 | 1 | 1 1/2 | 2.11 | 1300 | 5200 | 20.0 |
| 86518 | 24G2H X50FT | 4657-0927 | 1 | 1 1/2 | 2.11 | 1300 | 5200 | 20.0 |
| 70241 | 24G2HXCTN | 4657-0931 | 120 | 1 1/2 | 2.11 | 1300 | 5200 | 20.0 |
| 85428 | 32G2H X25FT | 4657-4332 | 1 | 2 | 2.62 | 1175 | 4700 | 25.0 |
| 86519 | 32G2H X50FT | 4657-0926 | 1 | 2 | 2.62 | 1175 | 4700 | 25.0 |
| 70242 | 32G2HXCTN | 4657-0932 | 120 | 2 | 2.62 | 1175 | 4700 | 25.0 |

## GLOBAL G2H HIGH-TEMP - MEGATUFF® COVER - SAE 100R2 TYPE AT

### WIRE BRAID




| | |
|---|---|
| RECOMMENDED FOR | High–temperature high–pressure hydraulic oil lines. Meets or exceeds the requirements of SAE 100R2, ISO 1436 2SN R2 and EN 853 2SN. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil and abrasion resistant, synthetic rubber and MegaTuff® cover. Also available in Standard cover. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +275°F (–40°C to +135°C) constant and +300°F (+149°C) intermittent (up to 10% of operating time). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | Field Attachable Type T Couplings (–20 and –24) (G28) Section J<br>GlobalSpiral™ Couplings (–20) (G20) Section E<br>GlobalSpiral™ Plus Couplings (–24 and –32) (G22) Section E<br>MegaCrimp® Couplings (–20) (G25) Section G<br>Stainless Steel Braid Couplings (–24 and –32) (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Meets Flame Resistance Acceptance Designation "MSHA 2G". MegaTuff® hose lasts up to 300 times longer than standard hose during hose–to–hose and hose–to–metal abrasion tests per ISO 6945.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70897 | 20G2H-MTFXCTN | 4657-2573 | 100 | 1 1/4 | 1.87 | 1825 | 6500 | 16.5 |
| 70188 | 24G2H-MTFXCTN | 4657-2151 | 100 | 1 1/2 | 2.15 | 1300 | 5200 | 20.0 |
| 70189 | 32G2H-MTFXCTN | 4657-2152 | 100 | 2 | 2.65 | 1175 | 4700 | 25.0 |

## GLOBAL G2XH 2-WIRE BRAID XTREME® HEAT HOSE - SAE 100R2 TYPE AT

### WIRE BRAID




| | |
|---|---|
| RECOMMENDED FOR | Extremely high–temperature high–pressure hydraulic applications where pressure or temperature requirements exceed SAE 100R2, ISO 1436 2SN R2 and EN 853 2SN or where resistance to either petroleum–base or phosphate ester fluids is required. Meets SAE J1942 requirements. |
| TUBE | Black, oil and chemical resistant, synthetic rubber (CPE). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Blue, oil and abrasion resistant, thin synthetic rubber (CSM). See Hose Stock Characteristics. |
| TEMPERATURE RANGE | Petroleum–base fluids: –40°F to +300°F (–40°C to +149°C). Phosphate esters fluids as recommended by the fluid manufacturer, but within a range of –40°F to +212°F. For water emulsions: Max. +225°F Pressure lines, Max +180°F Return lines. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (G20) Section E<br>GlobalSpiral™ Plus Couplings (–24 and –32) (G22) Section E<br>MegaCrimp® Couplings (G25) Section G<br>Stainless Steel Braid Couplings (–24 and –32) (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85798 | 4G2XH X50FT | 4657-4008 | 1 | 1/4 | .59 | 6000 | 24000 | 4.0 |
| 70966 | 4G2XHXREEL | 4657-2541 | 550 | 1/4 | .59 | 6000 | 24000 | 4.0 |
| 85799 | 6G2XH X50FT | 4657-4009 | 1 | 3/8 | .74 | 5000 | 20000 | 5.0 |
| 70967 | 6G2XHXREEL | 4657-2542 | 400 | 3/8 | .74 | 5000 | 20000 | 5.0 |
| 85800 | 8G2XH X50FT | 4657-4010 | 1 | 1/2 | .86 | 4250 | 17000 | 7.0 |

## GLOBAL G2XH 2-WIRE BRAID XTREME® HEAT HOSE - SAE 100R2 TYPE AT - CONTINUED

### WIRE BRAID - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70968 | 8G2XHXREEL | 4657-2543 | 330 | 1/2 | .86 | 4250 | 17000 | 7.0 |
| 85801 | 10G2XH X50FT | 4657-4011 | 1 | 5/8 | .99 | 3625 | 14500 | 8.0 |
| 70803 | 10G2XHXREEL | 4657-2544 | 220 | 5/8 | .99 | 3625 | 14500 | 8.0 |
| 85802 | 12G2XH X50FT | 4657-4012 | 1 | 3/4 | 1.15 | 3100 | 12400 | 9.5 |
| 70909 | 12G2XHXREEL | 4657-2545 | 220 | 3/4 | 1.15 | 3100 | 12400 | 9.5 |
| 85803 | 16G2XH X50FT | 4657-4013 | 1 | 1 | 1.48 | 2500 | 10000 | 12.0 |
| 70878 | 16G2XHXREEL | 4657-2546 | 165 | 1 | 1.48 | 2500 | 10000 | 12.0 |
| 70990 | 20G2XHXCTN | 4657-4988 | 130 | 1 1/4 | 1.86 | 2250 | 9000 | 16.5 |
| 70988 | 24G2XHXCTN | 4657-4989 | 130 | 1 1/2 | 2.15 | 1800 | 7200 | 20.0 |
| 70989 | 32G2XHXCTN | 4657-4990 | 130 | 2 | 2.65 | 1500 | 6000 | 25.0 |

## GLOBAL G2L POLARFLEX® HOSE - SAE 100R2 TYPE AT

### WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | Low–temperature high–pressure hydraulic oil lines. Meets or exceeds the requirements of SAE 100R2, ISO 1436 2SN R2 and EN 853 2SN. Qualified to Mil–DTL–13531 Type II Class B. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil and abrasion resistant, thin synthetic rubber (Polychloroprene). See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –70°F to +212°F (–57°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | Field Attachable Type T Couplings (–4 through –24) (G28) Section J<br>GlobalSpiral™ Couplings (–6 through –20) (G20) Section E<br>GlobalSpiral™ Plus Couplings (–24 and –32) (G22) Section E<br>MegaCrimp® Couplings (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85732 | 4G2L X50FT | 4657-2475 | 1 | 1/4 | .59 | 5800 | 23200 | 4.0 |
| 70286 | 4G2LXREEL | 4657-2202 | 440 | 1/4 | .59 | 5800 | 23200 | 4.0 |
| 85733 | 6G2L X50FT | 4657-2476 | 1 | 3/8 | .74 | 4800 | 19200 | 5.0 |
| 70287 | 6G2LXREEL | 4657-2203 | 385 | 3/8 | .74 | 4800 | 19200 | 5.0 |
| 85734 | 8G2L X50FT | 4657-2477 | 1 | 1/2 | .86 | 4000 | 16000 | 7.0 |
| 70290 | 8G2LXREEL | 4657-2204 | 330 | 1/2 | .86 | 4000 | 16000 | 7.0 |
| 85735 | 10G2L X50FT | 4657-2478 | 1 | 5/8 | .99 | 3625 | 14500 | 8.0 |
| 70291 | 10G2LXREEL | 4657-2205 | 220 | 5/8 | .99 | 3625 | 14500 | 8.0 |
| 85736 | 12G2L X50FT | 4657-2479 | 1 | 3/4 | 1.15 | 3100 | 12400 | 9.5 |
| 70292 | 12G2LXREEL | 4657-2206 | 220 | 3/4 | 1.15 | 3100 | 12400 | 9.5 |
| 85737 | 16G2L X50FT | 4657-2480 | 1 | 1 | 1.48 | 2400 | 9600 | 12.0 |
| 70293 | 16G2LXREEL | 4657-2207 | 165 | 1 | 1.48 | 2400 | 9600 | 12.0 |
| 85707 | 20G2L X50FT | 4657-4102 | 1 | 1 1/4 | 1.84 | 1825 | 7300 | 16.5 |
| 70294 | 20G2LXCTN | 4657-2208 | 120 | 1 1/4 | 1.84 | 1825 | 7300 | 16.5 |
| 85708 | 24G2L X50FT | 4657-4103 | 1 | 1 1/2 | 2.12 | 1300 | 5200 | 20.0 |
| 70314 | 24G2LXCTN | 4657-2315 | 120 | 1 1/2 | 2.12 | 1300 | 5200 | 20.0 |
| 85709 | 32G2L X50FT | 4657-4104 | 1 | 2 | 2.62 | 1175 | 4700 | 25.0 |
| 70315 | 32G2LXCTN | 4657-2316 | 120 | 2 | 2.62 | 1175 | 4700 | 25.0 |

## M-XP™ MILLION IMPULSE XTRA PERFORMANCE WIRE BRAID HOSE

### WIRE BRAID




| | |
|---|---|
| RECOMMENDED FOR | High–pressure, high impulse life hydraulic applications. Provides tighter than standard minimum bend radius and greater flexibility for easier plumbing. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (Nitrile and PVC –4 and –6), (Polychloroprene –8 through –12). See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –12) (G20) Section E<br>MegaCrimp® Couplings (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Meets Flame Resistance Acceptance Designation "MSHA 2G". Tested to Industry Leading 1,000,000 impulse cycles.

| Part No. | Description | Product No. | Standard Pack | ⟷ | ↕ | | | R |
|---|---|---|---|---|---|---|---|---|
| 71105 | 4M-XPXREEL | 4657-4216 | 440 | 1/4 | .55 | 4000 | 16000 | 2.0 |
| 71106 | 6M-XPXREEL | 4657-4217 | 330 | 3/8 | .70 | 4000 | 16000 | 2.5 |
| 71107 | 8M-XPXREEL | 4657-4218 | 220 | 1/2 | .82 | 4000 | 16000 | 3.5 |
| 71108 | 10M-XPXREEL | 4657-4219 | 220 | 5/8 | .96 | 4000 | 16000 | 4.0 |
| 71109 | 12M-XPXREEL | 4657-4220 | 220 | 3/4 | 1.17 | 4000 | 16000 | 4.7 |

## GLOBAL G1 1-WIRE BRAID HOSE - SAE 100R1 TYPE AT

### WIRE BRAID




| | |
|---|---|
| RECOMMENDED FOR | Medium–pressure hydraulic lines. Meets or exceeds the requirements of SAE 100R1, ISO 1436 1SNR1 and EN 853 1SN. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | One braid of high–tensile steel wire. |
| COVER | Black, oil and abrasion resistant, synthetic rubber (Nitrile and PVC). See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | Field Attachable Type T Couplings (G27) Section J<br>GlobalSpiral™ Couplings (–6 through –20) (G20) Section E<br>GlobalSpiral™ Plus Couplings (–24 and –32) (G22) Section E<br>MegaCrimp® Couplings (–4 through –20) (G25) Section G<br>Power Crimp® Couplings (–3) Section I<br>Power Crimp® Grease Couplings (–3) Section I<br>Stainless Steel Braid Couplings (except –3, –5 & –16) (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | ⟷ | ↕ | | | R |
|---|---|---|---|---|---|---|---|---|
| | 3G1XBALE | 4657-5700 | 7600 | 3/16 | .47 | 3625 | 14500 | 3.0 |
| 70200 | 3G1XCTN | 4657-0618 | 800 | 3/16 | .47 | 3625 | 14500 | 3.0 |
| 70611 | 3G1XREEL | 4657-0599 | 440 | 3/16 | .47 | 3625 | 14500 | 3.0 |
| 86611 | 4G1 X50FT | 4657-4940 | 1 | 1/4 | .53 | 3275 | 13100 | 4.0 |
| | 4G1XBALE | 4657-5717 | 5600 | 1/4 | .53 | 3275 | 13100 | 4.0 |
| 70600 | 4G1XREEL | 4657-0120 | 440 | 1/4 | .53 | 3275 | 13100 | 4.0 |
| 70199 | 5G1XCTN | 4657-0031 | 550 | 5/16 | .60 | 3125 | 12500 | 4.5 |

## GLOBAL G1 1-WIRE BRAID HOSE - SAE 100R1 TYPE AT - CONTINUED

### WIRE BRAID - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70970 | 5G1XREEL | 4657-0116 | 350 | 5/16 | .60 | 3125 | 12500 | 4.5 |
| 86612 | 6G1 X50FT | 4657-4915 | 1 | 3/8 | .68 | 2600 | 10400 | 5.0 |
| 86631 | 6G1 X100FT | 4657-4905 | 1 | 3/8 | .68 | 2600 | 10400 | 5.0 |
| | 6G1XBALE | 4657-5703 | 3800 | 3/8 | .68 | 2600 | 10400 | 5.0 |
| 70601 | 6G1XREEL | 4657-0121 | 385 | 3/8 | .68 | 2600 | 10400 | 5.0 |
| 86613 | 8G1 X50FT | 4657-4917 | 1 | 1/2 | .80 | 2325 | 9300 | 7.0 |
| 86633 | 8G1 X100FT | 4657-4907 | 1 | 1/2 | .80 | 2325 | 9300 | 7.0 |
| | 8G1XBALE | 4657-5704 | 2800 | 1/2 | .80 | 2325 | 9300 | 7.0 |
| | 8G1XLG REEL | 4657-2645 | 500 | 1/2 | .80 | 2325 | 9300 | 7.0 |
| 70602 | 8G1XREEL | 4657-0122 | 330 | 1/2 | .80 | 2325 | 9300 | 7.0 |
| | 10G1XBALE | 4657-5705 | 1550 | 5/8 | .93 | 1900 | 7600 | 8.0 |
| 70612 | 10G1XREEL | 4657-0115 | 220 | 5/8 | .93 | 1900 | 7600 | 8.0 |
| 86614 | 12G1 X50FT | 4657-4942 | 1 | 3/4 | 1.09 | 1525 | 6100 | 9.0 |
| | 12G1XBALE | 4657-5706 | 1400 | 3/4 | 1.09 | 1525 | 6100 | 9.0 |
| 70603 | 12G1XREEL | 4657-0123 | 220 | 3/4 | 1.09 | 1525 | 6100 | 9.0 |
| 86615 | 16G1 X50FT | 4657-4944 | 1 | 1 | 1.40 | 1300 | 5200 | 12.0 |
| | 16G1XBALE | 4657-5707 | 700 | 1 | 1.40 | 1300 | 5200 | 12.0 |
| 70604 | 16G1XREEL | 4657-0124 | 165 | 1 | 1.40 | 1300 | 5200 | 12.0 |
| | 20G1XBALE | 4657-5702 | 600 | 1 1/4 | 1.71 | 925 | 3700 | 16.0 |
| 70271 | 20G1XCTN | 4657-0646 | 120 | 1 1/4 | 1.71 | 925 | 3700 | 16.0 |
| 70278 | 24G1XCTN | 4657-2489 | 120 | 1 1/2 | 1.96 | 725 | 2900 | 20.0 |
| 70279 | 32G1XCTN | 4657-2490 | 120 | 2 | 2.51 | 600 | 2400 | 25.0 |

## GLOBAL G1H 1-WIRE BRAID HOSE - HIGH-TEMP - SAE 100R1 TYPE AT

### WIRE BRAID

| | |
|---|---|
| RECOMMENDED FOR | High–temperature medium–pressure hydraulic oil lines. Meets or exceeds SAE 100R1 Type AT 2003 Revision. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | One braid of high–tensile steel wire. |
| COVER | Black, oil and abrasion resistant, synthetic rubber (CSM). See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +275°F (–40°C to +135°C) constant and +300°F (+149°C) intermittent (up to 10% of operating time). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (G20) Section E<br>GlobalSpiral™ Plus Couplings (–24 and –32) (G22) Section E<br>MegaCrimp® Couplings (G25) Section G<br>Stainless Steel Braid Couplings (–4 through –32, except –16 & –24) (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85922 | 4G1H X50FT | 4657-4105 | 1 | 1/4 | .53 | 2750 | 11000 | 4.0 |
| 70755 | 4G1HXREEL | 4657-2175 | 440 | 1/4 | .53 | 2750 | 11000 | 4.0 |
| 85923 | 6G1H X50FT | 4657-4106 | 1 | 3/8 | .69 | 2250 | 9000 | 5.0 |
| 70756 | 6G1HXREEL | 4657-2176 | 385 | 3/8 | .69 | 2250 | 9000 | 5.0 |

## GLOBAL G1H 1-WIRE BRAID HOSE - HIGH-TEMP - SAE 100R1 TYPE AT - CONTINUED

### WIRE BRAID - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85924 | 8G1H X50FT | 4657-4107 | 1 | 1/2 | .80 | 2000 | 8000 | 7.0 |
| 70757 | 8G1HXREEL | 4657-2177 | 330 | 1/2 | .80 | 2000 | 8000 | 7.0 |
| 85925 | 10G1H X50FT | 4657-4108 | 1 | 5/8 | .94 | 1500 | 6000 | 8.0 |
| 70758 | 10G1HXREEL | 4657-2178 | 220 | 5/8 | .94 | 1500 | 6000 | 8.0 |
| 85938 | 12G1H X50FT | 4657-2617 | 1 | 3/4 | 1.10 | 1250 | 5000 | 9.5 |
| | 12G1HXBALE | 4657-2536 | 1500 | 3/4 | 1.10 | 1250 | 5000 | 9.5 |
| 70759 | 12G1HXREEL | 4657-2179 | 220 | 3/4 | 1.10 | 1250 | 5000 | 9.5 |
| 85934 | 16G1H X50FT | 4657-4109 | 1 | 1 | 1.41 | 1000 | 4000 | 12.0 |
| 70760 | 16G1HXREEL | 4657-2180 | 165 | 1 | 1.41 | 1000 | 4000 | 12.0 |
| 85935 | 20G1H X50FT | 4657-4110 | 1 | 1 1/4 | 1.71 | 925 | 3700 | 16.0 |
| 70211 | 20G1HXCTN | 4657-0940 | 120 | 1 1/4 | 1.71 | 925 | 3700 | 16.0 |
| 85936 | 24G1H X50FT | 4657-4111 | 1 | 1 1/2 | 1.96 | 725 | 2900 | 20.0 |
| 70212 | 24G1HXCTN | 4657-0934 | 120 | 1 1/2 | 1.96 | 725 | 2900 | 20.0 |
| 85937 | 32G1H X50FT | 4657-4112 | 1 | 2 | 2.51 | 600 | 2400 | 25.0 |
| 70213 | 32G1HXCTN | 4657-0935 | 120 | 2 | 2.51 | 600 | 2400 | 25.0 |

## TH7 HYDRAULIC HOSE - SAE 100R7

### THERMOPLASTIC

| | |
|---|---|
| RECOMMENDED FOR | Petroleum, water–base and synthetic hydraulic fluids. Applications include: power and telephone mobile equipment (cherry pickers), lubrication lines, blowout preventer control lines, hydraulic lifts and farm and construction machinery. TH7 hose meets or exceeds performance requirements of SAE 100R7 with a significantly tighter bend radius. |
| TUBE | 100% seamless Nylon that easily handles a broad range of hydraulic fluids, including phosphate esters and water glycol. See Hose Stock Characteristics. |
| REINFORCEMENT | Synthetic fiber. |
| COVER | Black Urethane that resists hydraulic fluids, high temperatures, aging and weathering. Black TH7 is perforated for use in general hydraulic and pneumatic service. |
| TEMPERATURE RANGE | –65°F to +200°F (–54°C to +93°C) continuous service for petroleum and synthetic oils. Maximum of +158°F (+70°C) for water, water/oil emulsions and water glycol. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G<br>Swage PCTS Couplings (–2 and –3) (G51) Section O<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 71011 | 2TH7XCTN | 4467-1154 | 250 | 1/8 | .32 | 3000 | 12000 | .50 |
| 85401 | 3TH7 X50FT | 4467-1194 | 1 | 3/16 | .41 | 3000 | 12000 | .75 |
| 71012 | 3TH7XCTN | 4467-1155 | 250 | 3/16 | .41 | 3000 | 12000 | .75 |
| 85402 | 4TH7 X50FT | 4467-1195 | 1 | 1/4 | .50 | 2750 | 11000 | 1.5 |
| 71013 | 4TH7XCTN | 4467-1157 | 250 | 1/4 | .50 | 2750 | 11000 | 1.5 |
| 85403 | 5TH7 X50FT | 4467-1160 | 1 | 5/16 | .56 | 2500 | 10000 | 2.25 |
| 71014 | 5TH7XCTN | 4467-1159 | 250 | 5/16 | .56 | 2500 | 10000 | 2.25 |
| 85404 | 6TH7 X50FT | 4467-1162 | 1 | 3/8 | .64 | 2250 | 9000 | 2.75 |
| 71015 | 6TH7XCTN | 4467-1161 | 250 | 3/8 | .64 | 2250 | 9000 | 2.75 |
| 85405 | 8TH7 X50FT | 4467-1164 | 1 | 1/2 | .80 | 2000 | 8000 | 3.75 |
| 71021 | 8TH7XCTN | 4467-1207 | 250 | 1/2 | .80 | 2000 | 8000 | 3.75 |
| 85406 | 12TH7 X50FT | 4467-1193 | 1 | 3/4 | 1.05 | 1250 | 5000 | 5.0 |

## TH7 HYDRAULIC HOSE - SAE 100R7 - CONTINUED

### THERMOPLASTIC - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 71070 | 12TH7XCTN | 4467-1165 | 200 | 3/4 | 1.05 | 1250 | 5000 | 5.0 |
| 85407 | 16TH7 X50FT | 4467-1197 | 1 | 1 | 1.32 | 1000 | 4000 | 8.0 |
| 71071 | 16TH7XCTN | 4467-1196 | 200 | 1 | 1.32 | 1000 | 4000 | 8.0 |

## TH7NC NON CONDUCTIVE HYDRAULIC HOSE - SAE 100R7

### THERMOPLASTIC

| | |
|---|---|
| RECOMMENDED FOR | Petroleum and synthetic hydraulic fluids. Applications include: power and telephone mobile equipment (cherry pickers), lubrication lines, blowout preventer control lines, hydraulic lifts and farm and construction machinery. Orange color TH7NC meets SAE 100R7 non–conductivity requirements and meets or exceeds performance requirements of SAE 100R7 with a significantly tighter bend radius. Meets ANSI A92.2 for vehicle mounted aerial devices. |
| TUBE | –2, –12, and –16: 100% seamless Nylon that easily handles a broad range of hydraulic fluids, including phosphate esters and water glycol; –3 through –8 Polyester. See Hose Stock Characteristics. |
| REINFORCEMENT | Synthetic fiber and Nylon (–2 only). |
| COVER | Orange Urethane that resists hydraulic fluids, high temperatures, aging and weathering. Orange TH7NC is non–perforated for applications requiring electrical non–conductivity. Meets SAE 100R7 Electrical Conductivity Test. Maximum leakage shall not exceed 50 microamperes when subjected to 75 kV/Ft. for five minutes. (Orange is industry accepted color for non–conductive hose). |
| TEMPERATURE RANGE | –65°F to +200°F (–54°C to +93°C) continuous service for petroleum and synthetic oils. Maximum of +158°F (+70°C) for water, water/oil emulsions and water glycol. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G<br>Swage PCTS Couplings (–2 and –3) (G51) Section O<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 71072 | 2TH7NCXCTN | 4467-1166 | 250 | 1/8 | .32 | 3000 | 12000 | .50 |
| 85408 | 3TH7NC X50FT | 4467-1205 | 1 | 3/16 | .41 | 3000 | 12000 | .75 |
| 71073 | 3TH7NCXCTN | 4467-1167 | 250 | 3/16 | .41 | 3000 | 12000 | .80 |
| 85409 | 4TH7NC X50FT | 4467-1170 | 1 | 1/4 | .50 | 2750 | 11000 | 1.5 |
| 71016 | 4TH7NCXCTN | 4467-1169 | 250 | 1/4 | .50 | 2750 | 11000 | 1.5 |
| 85410 | 5TH7NC X50FT | 4467-1172 | 1 | 5/16 | .56 | 2500 | 10000 | 2.25 |
| 71074 | 5TH7NCXCTN | 4467-1171 | 250 | 5/16 | .56 | 2500 | 10000 | 2.25 |
| 85411 | 6TH7NC X50FT | 4467-1174 | 1 | 3/8 | .64 | 2250 | 9000 | 2.75 |
| 71017 | 6TH7NCXCTN | 4467-1173 | 250 | 3/8 | .64 | 2250 | 9000 | 2.75 |
| 85412 | 8TH7NC X50FT | 4467-1206 | 1 | 1/2 | .80 | 2000 | 8000 | 3.75 |
| 71018 | 8TH7NCXCTN | 4467-1175 | 250 | 1/2 | .80 | 2000 | 8000 | 3.75 |
| 85413 | 12TH7NC X50FT | 4467-1200 | 1 | 3/4 | 1.05 | 1250 | 5000 | 5.0 |
| 71075 | 12TH7NCXCTN | 4467-1177 | 200 | 3/4 | 1.05 | 1250 | 5000 | 5.0 |
| 85414 | 16TH7NC X50FT | 4467-1199 | 1 | 1 | 1.32 | 1000 | 4000 | 6.5 |
| 71076 | 16TH7NCXCTN | 4467-1198 | 200 | 1 | 1.32 | 1000 | 4000 | 6.5 |

## TH7DL DUAL LINE HYDRAULIC HOSE - SAE 100R7

### THERMOPLASTIC

| | |
|---|---|
| RECOMMENDED FOR | Petroleum, water–base and synthetic hydraulic fluids. Applications include: power and telephone mobile equipment (cherry pickers), lubrication lines, blowout preventer control lines, hydraulic lifts and farm and construction machinery. TH7DL hose meets or exceeds performance requirements of SAE 100R7 with significantly tighter bend radius. |
| TUBE | 100% seamless Nylon that easily handles a broad range of hydraulic fluids, including phosphate esters and water glycol. See Hose Stock Characteristics. |
| REINFORCEMENT | Synthetic fiber. |
| COVER | Black Urethane that resists hydraulic fluids, high temperatures, aging and weathering. Black TH7DL is perforated for use in general hydraulic and pneumatic service. |
| TEMPERATURE RANGE | –65°F to +200°F (–54°C to +93°C) continuous service for petroleum and synthetic oils. Maximum of +158°F (+70°C) for water, water/oil emulsions and water glycol. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G (See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 71084 | 4TH7DLXCTN | 4472-0220 | 250 | 1/4 | .50 | 2750 | 11000 | 1.5 |
| 85422 | 5TH7DL X50FT | 4472-0222 | 1 | 5/16 | .56 | 2500 | 10000 | 2.25 |
| 71085 | 5TH7DLXCTN | 4472-0221 | 250 | 5/16 | .56 | 2500 | 10000 | 2.25 |
| 71022 | 6TH7DLXCTN | 4472-0223 | 250 | 3/8 | .64 | 2250 | 9000 | 2.75 |
| 71086 | 8TH7DLXCTN | 4472-0224 | 250 | 1/2 | .80 | 2000 | 8000 | 3.75 |

## TH7NCDL NON CONDUCTIVE DUAL LINE HYDRAULIC HOSE - SAE 100R7

### THERMOPLASTIC

| | |
|---|---|
| RECOMMENDED FOR | Petroleum, water–base and synthetic hydraulic fluids. Applications include: power and telephone mobile equipment (cherry pickers), lubrication lines, blowout preventer control lines, hydraulic lifts and farm and construction machinery. Orange color TH7NCDL meets SAE 100R7 non–conductivity requirements and meets or exceeds performance requirements of SAE 100R7 with significantly tighter bend radius. Meets ANSI A92.2 for vehicle mounted aerial devices. |
| TUBE | Nylon |
| REINFORCEMENT | Synthetic fiber. |
| COVER | Orange Urethane that resists hydraulic fluids, high temperatures, aging and weathering. Orange TH7NCDL is non–perforated for applications requiring electrical non–conductivity. Meets SAE 100R7 Electrical Conductivity Test. Maximum leakage shall not exceed 50 microamperes when subjected to 75 kV/Ft. for five minutes. (Orange is industry accepted color for non–conductive hose.) |
| TEMPERATURE RANGE | –65°F to +200°F (–54°C to +93°C) continuous service for petroleum and synthetic oils. Maximum of +158°F (+70°C) for water, water/oil emulsions and water glycol. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G (See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85786 | 4TH7NCDL X50FT | 4472-0226 | 1 | 1/4 | .50 | 2750 | 11000 | 1.5 |
| 71087 | 4TH7NCDLXCTN | 4472-0225 | 250 | 1/4 | .50 | 2750 | 11000 | 1.5 |
| 85424 | 6TH7NCDL X50FT | 4472-0228 | 1 | 3/8 | .64 | 2250 | 9000 | 2.75 |

## TH7NCDL NON CONDUCTIVE DUAL LINE HYDRAULIC HOSE - SAE 100R7 - CONTINUED

### THERMOPLASTIC - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 71088 | 6TH7NCDLXCTN | 4472-0227 | 250 | 3/8 | .64 | 2250 | 9000 | 2.75 |
| 71089 | 8TH7NCDLXCTN | 4472-0229 | 250 | 1/2 | .80 | 2000 | 8000 | 3.75 |

## TH7S HYDRAULIC HOSE - SAE 100R7

### THERMOPLASTIC

| | |
|---|---|
| RECOMMENDED FOR | Petroleum and synthetic hydraulic fluids. Applications include power and mobile equipment, lifts and construction machinery. TH7S hose meets or exceeds performance requirements of SAE 100R7 with a significantly tighter bend radius. |
| TUBE | Polyester |
| REINFORCEMENT | Synthetic fiber. |
| COVER | Black Urethane that resists hydraulic fluids, high temperatures, aging and weathering. Black TH7S is perforated for use in general hydraulic and pneumatic service. |
| TEMPERATURE RANGE | –65°F to +200°F (–54°C to +93°C) continuous service for petroleum and synthetic oils. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85653 | 4TH7SX50FT | 4467-8653 | 1 | 1/4 | .50 | 2750 | 11999 | 1.25 |
| 71112 | 4TH7SXCTN | 4467-9112 | 250 | 1/4 | .50 | 2750 | 11999 | 1.25 |
| 85654 | 5TH7SX50FT | 4467-8654 | 1 | 5/16 | .56 | 2500 | 10000 | 1.75 |
| 71113 | 5TH7SXCTN | 4467-9113 | 250 | 5/16 | .56 | 2500 | 10000 | 1.75 |
| 85655 | 6TH7SX50FT | 4467-8655 | 1 | 3/8 | .64 | 2250 | 9000 | 2.0 |
| 71114 | 6TH7SXCTN | 4467-9114 | 250 | 3/8 | .64 | 2250 | 9000 | 2.0 |
| 85656 | 8TH7SX50FT | 4467-8656 | 1 | 1/2 | .80 | 2000 | 8000 | 3.0 |
| 71115 | 8TH7SXCTN | 4467-9115 | 250 | 1/2 | .80 | 2000 | 8000 | 3.0 |

## TH7SNC NON CONDUCTIVE HYDRAULIC HOSE - SAE 100R7

### THERMOPLASTIC

| | |
|---|---|
| RECOMMENDED FOR | Orange color TH7SNC meets SAE 100R7 non–conductivity requirements and meets or exceeds performance requirements of SAE 100R7 with a significantly tighter bend radius. Meets ANSI A92.2 for vehicle mounted aerial devices. |
| TUBE | Nylon |
| REINFORCEMENT | Synthetic fiber. |
| COVER | Orange Urethane that resists hydraulic fluids, high temperatures, aging and weathering. Orange THS7NC is non–perforated for applications requiring electrical non–conductivity. Meets SAE 100R7 Electrical Conductivity Test. Maximum leakage shall not exceed 50 microamperes when subjected to 75 kV/Ft. for five minutes. (Orange is industry accepted color for non–conductive hose). |
| TEMPERATURE RANGE | –65°F to +200°F (–54°C to +93°C) continuous service for petroleum and synthetic oils. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | ⟷ | ↕ | | | R |
|---|---|---|---|---|---|---|---|---|
| 85668 | 6TH7SNCX50FT | 4467-0017 | 1 | 3/8 | .64 | 2250 | 9000 | 2.0 |
| 85669 | 8TH7SNCX50FT | 4467-0019 | 1 | 1/2 | .80 | 2000 | 8000 | 3.0 |

## TH8 HYDRAULIC HOSE - SAE 100R8

### THERMOPLASTIC

| | |
|---|---|
| RECOMMENDED FOR | Use with petroleum, water base and synthetic hydraulic fluids. Applications include: power and telephone mobile equipment (cherry pickers), lubrication lines, blowout preventer control lines, hydraulic lifts and farm and construction machinery. TH8 hose meets or exceeds performance requirements of SAE 100R8 with a significantly tighter bend radius. Multiline available. |
| TUBE | 100% seamless Nylon that easily handles a broad range of hydraulic fluids, including phosphate esters and water glycol. See Hose Stock Characteristics. |
| REINFORCEMENT | Polyester. |
| COVER | Black Urethane resists hydraulic fluids, high temperatures, aging and weathering. Black TH8 cover is perforated for use in general hydraulic and pneumatic service. |
| TEMPERATURE RANGE | –65°F to +200°F (–54°C to +93°C) continuous service for petroleum and synthetic oils. Maximum of +158°F (+70°C) for water, water/oil emulsions and water glycol. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (–4 through –16) (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | ⟷ | ↕ | | | R |
|---|---|---|---|---|---|---|---|---|
| 85415 | 3TH8 X50FT | 4467-1201 | 1 | 3/16 | .50 | 5000 | 20000 | 1.5 |
| 71077 | 3TH8XCTN | 4467-1178 | 250 | 3/16 | .50 | 5000 | 20000 | 1.5 |
| 85416 | 4TH8 X50FT | 4467-1180 | 1 | 1/4 | .61 | 5000 | 20000 | 2.0 |
| 71078 | 4TH8XCTN | 4467-1179 | 250 | 1/4 | .61 | 5000 | 20000 | 2.0 |
| 85417 | 6TH8 X50FT | 4467-1182 | 1 | 3/8 | .75 | 4000 | 16000 | 2.5 |
| 71079 | 6TH8XCTN | 4467-1181 | 250 | 3/8 | .75 | 4000 | 16000 | 2.5 |
| 85418 | 8TH8 X50FT | 4467-1202 | 1 | 1/2 | .87 | 3500 | 14000 | 4.0 |
| 71019 | 8TH8XCTN | 4467-1183 | 250 | 1/2 | .87 | 3500 | 14000 | 4.0 |
| 71080 | 12TH8XCTN | 4467-1184 | 200 | 3/4 | 1.13 | 2250 | 9000 | 6.5 |
| 71081 | 16TH8XCTN | 4467-1185 | 200 | 1 | 1.45 | 2000 | 8000 | 10.0 |

## TH8NC NON CONDUCTIVE HYDRAULIC HOSE - SAE 100R8

### THERMOPLASTIC

| | |
|---|---|
| RECOMMENDED FOR | Use with petroleum, water base and synthetic hydraulic fluids. Applications include: power and telephone mobile equipment (cherry pickers), lubrication lines, blowout preventer control lines, hydraulic lifts and farm and construction machinery. TH8NC hose (orange cover) meets SAE 100R8 non–conductivity requirements. TH8NC hose meets or exceeds performance requirements of SAE 100R8 with a significantly tighter bend radius. Multiline available. |
| TUBE | 100% seamless Nylon that easily handles a broad range of hydraulic fluids, including phosphate esters and water glycol. See Hose Stock Characteristics. |
| REINFORCEMENT | Polyester. |
| COVER | Orange Urethane resists hydraulic fluids, high temperatures, aging and weathering. TH8NC is non–perforated for applications requiring electrical non–conductivity. Meets SAE 100R8 Electrical Conductivity Test. Maximum leakage shall not exceed 50 microamperes when subjected to 75 kV/Ft. for five minutes. (Orange is industry accepted color for non–conductive hose). |
| TEMPERATURE RANGE | –65°F to +200°F (–54°C to +93°C) continuous service for petroleum and synthetic oils. Maximum of +158°F (+70°C) for water, water/oil emulsions and water glycol. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G (See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85419 | 4TH8NC X50FT | 4467-1187 | 1 | 1/4 | .61 | 5000 | 20000 | 2.0 |
| 71020 | 4TH8NCXCTN | 4467-1186 | 250 | 1/4 | .61 | 5000 | 20000 | 2.0 |
| 85420 | 6TH8NC X50FT | 4467-1203 | 1 | 3/8 | .75 | 4000 | 16000 | 2.5 |
| 71082 | 6TH8NCXCTN | 4467-1204 | 250 | 3/8 | .75 | 4000 | 16000 | 2.5 |
| 85421 | 8TH8NC X50FT | 4467-1190 | 1 | 1/2 | .87 | 3500 | 14000 | 4.0 |
| 71083 | 8TH8NCXCTN | 4467-1189 | 250 | 1/2 | .87 | 3500 | 14000 | 4.0 |

## TH18 CONSTANT PRESSURE HYDRAULIC HOSE - SAE 100R18

### THERMOPLASTIC

| | |
|---|---|
| RECOMMENDED FOR | TH18 hose meets or exceeds performance requirements of SAE 100R18 with a significantly tighter bend radius. Suitable for petroleum or synthetic–based hydraulic fluids in hydraulic systems. TH18 is ideal for industrial and agricultural applications exposed to low temperatures or cyclic and quick temperature changes. Remains highly flexible in cold weather conditions and is resistant to hydraulic fluids, high temperatures, aging and weathering. |
| TUBE | Polyester elastomer. |
| REINFORCEMENT | Synthetic fiber. |
| COVER | Black Urethane perforated. |
| TEMPERATURE RANGE | –67°F to +212°F (–55°C to +100°C) continuous service for petroleum and synthetic oils. Maximum of +158°F (+70°C) for water–based fluids. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (with TuffCoat® plating) (G25) Section G (See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 71001 | 4TH18XCTN | 4467-0006 | 250 | 1/4 | .48 | 3000 | 12000 | 1.4 |
| 71002 | 5TH18XCTN | 4467-0007 | 250 | 5/16 | .56 | 3000 | 12000 | 1.8 |
| 71003 | 6TH18XCTN | 4467-0008 | 250 | 3/8 | .65 | 3000 | 12000 | 1.8 |
| 71004 | 8TH18XCTN | 4467-0009 | 250 | 1/2 | .89 | 3000 | 12000 | 2.8 |

## TH18 CONSTANT PRESSURE HYDRAULIC HOSE - SAE 100R18 - CONTINUED

### THERMOPLASTIC - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 71005 | 10TH18XCTN | 4467-0010 | 250 | 5/8 | 1.03 | 3000 | 12000 | 3.9 |

## TH18NC CONSTANT PRESSURE NON CONDUCTIVE HYDRAULIC HOSE - SAE 100R18

### THERMOPLASTIC

| | |
|---|---|
| RECOMMENDED FOR | TH18NC hose meets or exceeds performance requirements of SAE 100R18 with a significantly tighter bend radius. Suitable for petroleum or synthetic–based hydraulic fluids in hydraulic systems. TH18NC non–conductive hose are suitable for use in high–voltage applications. Remains highly flexible in cold weather conditions and is resistant to hydraulic fluids, high temperatures, aging and weathering. |
| TUBE | Polyester elastomer. |
| REINFORCEMENT | Synthetic fiber. |
| COVER | Special Urethane, orange (industry–accepted color for non–conductive hose), non–perforated for applications requiring electrical non–conductivity. Meets SAE 100R18 Electrical Conductivity Test. Maximum leakage shall not exceed 50 microamperes when subjected to 75 kV/Ft. for five minutes. |
| TEMPERATURE RANGE | –67°F to +212°F (–55°C to +100°C) continuous service for petroleum and synthetic oils. Maximum of +158°F (+70°C) for water–based fluids. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 71006 | 4TH18NCXCTN | 4467-0011 | 250 | 1/4 | .48 | 3000 | 12000 | 1.4 |
| 71007 | 5TH18NCXCTN | 4467-0012 | 250 | 5/16 | .56 | 3000 | 12000 | 1.8 |
| 71008 | 6TH18NCXCTN | 4467-0013 | 250 | 3/8 | .65 | 3000 | 12000 | 1.8 |
| 71009 | 8TH18NCXCTN | 4467-0014 | 250 | 1/2 | .89 | 3000 | 12000 | 2.8 |
| 71010 | 10TH18NCXCTN | 4467-0015 | 250 | 5/8 | 1.03 | 3000 | 12000 | 3.9 |

## G3H HIGH-TEMP 2-FIBER BRAID HOSE - SAE 100R3

### TRANSFER

| | |
|---|---|
| RECOMMENDED FOR | Hydraulic oil lines, anti–freeze solutions or water. Meets or exceeds requirements of SAE 100R3. |
| TUBE | Black, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two fiber braids. |
| COVER | Black, oil and abrasion resistant, synthetic rubber (Polychloroprene). See Hose Stock Characteristics. |
| TEMPERATURE RANGE | For hydraulic oil lines –40°F to +275°F (–40°C to +135°C) constant and +300°F (+149°C) intermittent (up to 10% of operating time). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GLX® Couplings (–8, –12, –16, and –20) (G44) Section N<br>MegaCrimp® Couplings (–4, –6, –8 and –10) (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | ⊖ | | | | R | ○ |
|---|---|---|---|---|---|---|---|---|---|
| 85951 | 4G3H X25FT | 3319-4263 | 1 | 1/4 | .56 | 1250 | 5000 | 3.0 | 28 |
| 70127 | 4G3HXCTN | 3319-0088 | 455 | 1/4 | .56 | 1250 | 5000 | 3.0 | 28 |
| 85950 | 5G3H X50FT | 3319-4717 | 1 | 5/16 | .66 | 1200 | 4800 | 3.5 | 28 |
| 70420 | 5G3HXCTN | 3319-4287 | 330 | 5/16 | .66 | 1200 | 4800 | 3.5 | 28 |
| 85952 | 6G3H X25FT | 3319-4262 | 1 | 3/8 | .75 | 1125 | 4500 | 4.0 | 28 |
| 70128 | 6G3HXCTN | 3319-0087 | 350 | 3/8 | .75 | 1125 | 4500 | 4.0 | 28 |
| 85953 | 8G3H X25FT | 3319-4261 | 1 | 1/2 | .94 | 1000 | 4000 | 5.0 | 28 |
| 70126 | 8G3HXCTN | 3319-0090 | 225 | 1/2 | .94 | 1000 | 4000 | 5.0 | 28 |
| 70421 | 10G3HXCTN | 3319-4288 | 200 | 5/8 | 1.10 | 900 | 3600 | 5.5 | 28 |
| 85954 | 12G3H X25FT | 3319-4265 | 1 | 3/4 | 1.25 | 750 | 3000 | 6.0 | 28 |
| 70119 | 12G3HXCTN | 3319-0091 | 160 | 3/4 | 1.25 | 750 | 3000 | 6.0 | 28 |
| 85955 | 16G3H X25FT | 3319-4264 | 1 | 1 | 1.50 | 565 | 2260 | 8.0 | 20 |
| 70120 | 16G3HXCTN | 3319-0092 | 120 | 1 | 1.50 | 565 | 2260 | 8.0 | 20 |
| 85956 | 20G3H X50FT | 3319-4718 | 1 | 1 1/4 | 1.75 | 375 | 1500 | 10.0 | 15 |
| 70121 | 20G3HXCTN | 3319-0071 | 120 | 1 1/4 | 1.75 | 375 | 1500 | 10.0 | 15 |
| 85957 | 24G3H X50FT | 3319-4719 | 1 | 1 1/2 | 1.94 | 300 | 1200 | 12.0 | 10 |
| 70422 | 24G3HXCTN | 3319-4289 | 131 | 1 1/2 | 1.94 | 300 | 1200 | 12.0 | 10 |

## GTH HIGH-TEMP 1-FIBER BRAID HOSE - SAE 100R6

### TRANSFER

| | |
|---|---|
| RECOMMENDED FOR | Hydraulic oil lines, heavy–duty transmission oil cooler lines and glycol anti–freeze solutions. Meets or exceeds requirements of SAE 100R6. |
| TUBE | Black, specially compounded, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | One fiber braid. |
| COVER | Black, oil and abrasion resistant, synthetic rubber (Polychloroprene). See Hose Stock Characteristics. |
| TEMPERATURE RANGE | For hydraulic oil lines –40°F to +275°F (–40°C to +135°C) constant and +300°F (+149°C) intermittent (up to 10% of operating time). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G<br>Power Crimp® Couplings (–3) Section I<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | ⊖ | | | | R | ○ |
|---|---|---|---|---|---|---|---|---|---|
| 70106 | 3GTHXCTN | 3319-3301 | 715 | 3/16 | .44 | 500 | 2000 | 2.0 | 28 |

## GTH HIGH-TEMP 1-FIBER BRAID HOSE - SAE 100R6 - CONTINUED

### TRANSFER - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 70107 | 4GTHXCTN | 3319-3305 | 775 | 1/4 | .50 | 400 | 1600 | 2.5 | 28 |
| 86687 | 5GTH X50FT | 3319-0305 | 1 | 5/16 | .56 | 400 | 1600 | 3.0 | 28 |
| 70105 | 5GTH XBULK | 3319-3309 | 250 | 5/16 | .56 | 400 | 1600 | 3.0 | 28 |
| 70108 | 5GTHXCTN | 3319-3310 | 650 | 5/16 | .56 | 400 | 1600 | 3.0 | 28 |
| 86618 | 8GTH X50FT | 3319-3317 | 1 | 1/2 | .78 | 400 | 1600 | 4.0 | 18 |
| 70110 | 8GTHXCTN | 3319-3320 | 400 | 1/2 | .78 | 400 | 1600 | 4.0 | 18 |
| 70131 | 8GTHXREEL | 3319-3323 | 200 | 1/2 | .78 | 400 | 1600 | 4.0 | 18 |
| 86695 | 10GTH X25FT | 3319-4268 | 1 | 5/8 | .91 | 350 | 1400 | 5.0 | 15 |
| 70111 | 10GTHXCTN | 3319-3325 | 250 | 5/8 | .91 | 350 | 1400 | 5.0 | 15 |
| 70130 | 12GTHXCTN | 3319-3335 | 225 | 3/4 | 1.06 | 300 | 1200 | 5.5 | 15 |
| 70746 | 16GTHXCTN | 3319-3345 | 165 | 1 | 1.13 | 250 | 1000 | 8.0 | 10 |

## GTHX HIGH-TEMP FIBER SPIRAL HOSE - SAE 100R6

### TRANSFER

| | |
|---|---|
| RECOMMENDED FOR | Hydraulic oil lines, heavy–duty transmission oil cooler lines and glycol anti–freeze solutions. Meets or exceeds requirements of SAE 100R6. |
| TUBE | Black, specially compounded, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Spiraled synthetic fiber. |
| COVER | Black, oil and abrasion resistant, synthetic rubber (Polychloroprene). See Hose Stock Characteristics. |
| TEMPERATURE RANGE | For hydraulic oil lines –40°F to +275°F (–40°C to +135°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G (See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 86688 | 6GTHX X50FT | 3289-0005 | 1 | 3/8 | .63 | 400 | 1600 | 3.0 | 28 |
| 70109 | 6GTHX XREEL | 3289-0002 | 300 | 3/8 | .63 | 400 | 1600 | 3.0 | 28 |

## M500 WIRE BRAID HOSE

### TRANSFER

| | |
|---|---|
| RECOMMENDED FOR | Pilot lines, grease lines and pressure return lines, 500 psi or less pressure applications. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). |
| REINFORCEMENT | One braid of high–tensile steel wire. |
| COVER | Black, oil and abrasion resistant, synthetic rubber, flame resistance (Nitrile and PVC). Also available with unique abrasion resistant MegaTuff® or XtraTuff® covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –16) (G20) Section E<br>MegaCrimp® Couplings (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85442 | 4M500 X50FT | 4657-4087 | 1 | 1/4 | .48 | 500 | 2000 | 2.0 |
| 70747 | 4M500XREEL | 4657-8027 | 440 | 1/4 | .48 | 500 | 2000 | 2.0 |
| 85443 | 6M500 X50FT | 4657-4088 | 1 | 3/8 | .63 | 500 | 2000 | 2.5 |
| 70748 | 6M500XREEL | 4657-8028 | 330 | 3/8 | .63 | 500 | 2000 | 2.5 |
| 85444 | 8M500 X50FT | 4657-4089 | 1 | 1/2 | .76 | 500 | 2000 | 3.5 |
| 70749 | 8M500XREEL | 4657-8029 | 220 | 1/2 | .76 | 500 | 2000 | 3.5 |
| 85445 | 10M500 X50FT | 4657-4090 | 1 | 5/8 | .93 | 500 | 2000 | 4.0 |
| 70752 | 10M500XREEL | 4657-8030 | 220 | 5/8 | .93 | 500 | 2000 | 4.0 |
| 85446 | 12M500 X50FT | 4657-4091 | 1 | 3/4 | 1.09 | 500 | 2000 | 4.7 |
| 70770 | 12M500XREEL | 4657-8031 | 220 | 3/4 | 1.09 | 500 | 2000 | 4.7 |
| 85447 | 16M500 X50FT | 4657-4092 | 1 | 1 | 1.40 | 500 | 2000 | 6.0 |
| 70974 | 16M500XREEL | 4657-8032 | 165 | 1 | 1.40 | 500 | 2000 | 6.0 |

## M500 WIRE BRAID HOSE - MEGATUFF® COVER

### TRANSFER

| | |
|---|---|
| RECOMMENDED FOR | Pilot lines, grease lines and pressure return lines, 500 psi or less pressure applications. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). |
| REINFORCEMENT | One braid of high–tensile steel wire. |
| COVER | Black, oil and abrasion resistant MegaTuff® cover. Also available with unique abrasion resistant XtraTuff® or Standard covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 and –8) (G20) Section E<br>MegaCrimp® Couplings (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70985 | 4M500-MTFXREEL | 4657-8039 | 440 | 1/4 | .48 | 500 | 2000 | 2.0 |
| 70986 | 6M500-MTFXREEL | 4657-8040 | 330 | 3/8 | .63 | 500 | 2000 | 2.5 |
| 70987 | 8M500-MTFXREEL | 4657-8041 | 220 | 1/2 | .76 | 500 | 2000 | 3.5 |

## M500 WIRE BRAID HOSE - XTRATUFF® COVER

### TRANSFER

| | |
|---|---|
| RECOMMENDED FOR | Pilot lines, grease lines and pressure return lines, 500 psi or less pressure applications. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). |
| REINFORCEMENT | One braid of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant, synthetic rubber (XtraTuff® Nitrile). Also available with unique abrasion resistant MegaTuff® or Standard covers. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). |
| COUPLING RECOMMENDATION | GlobalSpiral™ Couplings (–6 through –16) (G20) Section E<br>MegaCrimp® Couplings (–6 through –16) (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70979 | 4M500-XTFXREEL | 4657-8033 | 440 | 1/4 | .48 | 500 | 2000 | 2.0 |
| 70980 | 6M500-XTFXREEL | 4657-8034 | 330 | 3/8 | .63 | 500 | 2000 | 2.5 |
| 70981 | 8M500-XTFXREEL | 4657-8035 | 220 | 1/2 | .76 | 500 | 2000 | 3.5 |
| 70982 | 10M500-XTFXREEL | 4657-8036 | 220 | 5/8 | .93 | 500 | 2000 | 4.0 |
| 70983 | 12M500-XTFXREEL | 4657-8037 | 220 | 3/4 | 1.09 | 500 | 2000 | 4.7 |
| 70984 | 16M500-XTFXREEL | 4657-8038 | 165 | 1 | 1.40 | 500 | 2000 | 6.0 |

## MULTI MASTER® GMV™ MEGAFLEX® RETURN LINE AND SUCTION HOSE - SAE 100R4

### RETURN

| | |
|---|---|
| RECOMMENDED FOR | Meets or exceeds SAE 100R4. Meets SAE J30R5 and SAE J20R5* (*except tube dimensions). Applications requiring excellent flexibility and maximum resistance to air, water, coolant, petroleum lubricating oils, and refined fuels. Ideal for hydraulic return and suction lines, transferring refined fuels or other petroleum products, and coolant lines. |
| TUBE | Type C (Nitrile). Black. |
| REINFORCEMENT | Synthetic, high tensile textile reinforcement with steel wire helix. |
| COVER | Type A (Polychloroprene). Black, corrugated. |
| TEMPERATURE RANGE | –40°F to +275°F (–40°C to +135°C). Laboratory tested for normal service. Increased operating temperatures will reduce hose assembly service life. Warning: Do not convey fuels over +120°F (+49°C) and for coolant applications (20R5) max temperature is +212°F (+100°C). |
| COUPLING RECOMMENDATION | GL Couplings (G43) Section M<br>GlobalSpiral™ Plus Couplings (–24 and –32) (G22) Section E<br>MegaCrimp® Couplings (–12 through –20) (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 85746 | MULTI MASTER 12GMV MEGAFLEX 3/4X25FT | 4688-2373 | 1 | 3/4 | 1.20 | 350 | 1400 | .8 | 30 |
| 70295 | MULTI MASTER 12GMV MEGAFLEX 3/4XCTN | 4688-2282 | 100 | 3/4 | 1.20 | 350 | 1400 | .80 | 30 |
| 85752 | MULTI MASTER 16GMV MEGAFLEX 1X25FT | 4688-2374 | 1 | 1 | 1.41 | 300 | 1200 | 1.0 | 30 |
| 70296 | MULTI MASTER 16GMV MEGAFLEX 1XCTN | 4688-2284 | 100 | 1 | 1.41 | 300 | 1200 | 1.0 | 30 |
| 85753 | MULTI MASTER 20GMV MEGAFLEX 1 1/4X25FT | 4688-2375 | 1 | 1 1/4 | 1.66 | 250 | 1000 | 1.3 | 30 |

## MULTI MASTER® GMV™ MEGAFLEX® RETURN LINE AND SUCTION HOSE - SAE 100R4 - CONTINUED

### RETURN - CONTINUED

| Part No. | Description | Product No. | Standard Pack | ⊖ | ⟷ | ◔ | ◔ | R | ○ |
|---|---|---|---|---|---|---|---|---|---|
| 70298 | MULTI MASTER 20GMV MEGAFLEX 1 1/4XCTN | 4688-2286 | 100 | 1 1/4 | 1.66 | 250 | 1000 | 1.3 | 30 |
| 85754 | MULTI MASTER 24GMV MEGAFLEX 1 1/2X25FT | 4688-2376 | 1 | 1 1/2 | 1.90 | 150 | 600 | 1.5 | 30 |
| 70299 | MULTI MASTER 24GMV MEGAFLEX 1 1/2XCTN | 4688-2288 | 100 | 1 1/2 | 1.90 | 160 | 600 | 1.5 | 30 |
| 85755 | MULTI MASTER 32GMV MEGAFLEX 2X25FT | 4688-2377 | 1 | 2 | 2.39 | 150 | 600 | 2.0 | 30 |
| 70302 | MULTI MASTER 32GMV MEGAFLEX 2XCTN | 4688-2290 | 100 | 2 | 2.39 | 150 | 600 | 2.0 | 30 |
| 85756 | MULTI MASTER 40GMV MEGAFLEX 2 1/2X25FT | 4688-2378 | 1 | 2 1/2 | 2.94 | 150 | 600 | 2.5 | 30 |
| 70306 | MULTI MASTER 40GMV MEGAFLEX 2 1/2XCTN | 4688-2300 | 100 | 2 1/2 | 2.94 | 150 | 600 | 2.5 | 30 |
| 85757 | MULTI MASTER 48GMV MEGAFLEX 3X25FT | 4688-2379 | 1 | 3 | 3.44 | 150 | 600 | 3.0 | 30 |
| 70307 | MULTI MASTER 48GMV MEGAFLEX 3XCTN | 4688-2292 | 100 | 3 | 3.44 | 150 | 600 | 3.0 | 30 |
| 85758 | MULTI MASTER 64GMV MEGAFLEX 4X25FT | 4688-2380 | 1 | 4 | 4.48 | 150 | 600 | 4.0 | 30 |
| 70317 | MULTI MASTER 64GMV MEGAFLEX 4XCTN | 4688-2294 | 100 | 4 | 4.48 | 150 | 600 | 4.0 | 30 |
| 70325 | MULTI MASTER 96GMV MEGAFLEX 6XCTN | 4688-2295 | 100 | 6 | 6.55 | 150 | 600 | 6.0 | 30 |

## GMV GLOBAL MEGAVAC® RETURN LINE AND SUCTION HOSE - SAE 100R4

### RETURN

| | |
|---|---|
| RECOMMENDED FOR | Petroleum and water base hydraulic fluids in suction lines or in low–pressure return lines. Meets or exceeds requirements of SAE 100R4. Uses half the bend radius of SAE 100R4. Meets marine ABS and DNV–GL with use of HeatGuard® high temp sleeve. |
| TUBE | Black, synthetic rubber is specifically designed for resistance to high temperatures (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Double spiral textile (braid for –12, –16 and –20) reinforced with a helical spiral–wire to prevent collapse. |
| COVER | Black synthetic rubber is oil and abrasion resistant (Polychloroprene). See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +275°F (–40°C to +135°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GL Couplings (G43) Section M<br>MegaCrimp® Couplings (G25) Section G<br>Use clamp over beaded nipple.<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | ⊖ | ⟷ | ◔ | ◔ | R | ○ |
|---|---|---|---|---|---|---|---|---|---|
| 85577 | 12GMV X25FT | 4504-0961 | 1 | 3/4 | 1.22 | 350 | 1400 | 2.5 | 25 |
| 70184 | 12GMVXCTN | 4504-0123 | 100 | 3/4 | 1.22 | 350 | 1400 | 2.5 | 25 |
| 85578 | 16GMV X25FT | 4504-0962 | 1 | 1 | 1.45 | 300 | 1200 | 3.0 | 25 |
| 70185 | 16GMVXCTN | 4504-0003 | 100 | 1 | 1.45 | 300 | 1200 | 3.0 | 25 |
| 85579 | 20GMV X25FT | 4504-0963 | 1 | 1 1/4 | 1.76 | 250 | 1000 | 4.0 | 25 |
| 70186 | 20GMVXCTN | 4504-0004 | 100 | 1 1/4 | 1.76 | 250 | 1000 | 4.0 | 25 |

# RLA 1-FIBER BRAID RETURN LINE AND LOW PRESSURE HOSE

## RETURN

| | |
|---|---|
| RECOMMENDED FOR | Low–pressure hydraulic oil return lines for general purpose water, glycol antifreeze solutions, conveying diesel fuel, gasoline or air. Meets SAE 30R2 performance requirements of both Type 1 and Type 2 for fuel and B20 constant contact up to +125°F biodiesel fuel transfer applications. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | One fiber braid (–3 to –10). Spiral braid (–12 to –16). |
| COVER | Black, synthetic rubber. Oil and abrasion resistant (Nitrile and PVC). See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). Air to +160°F (+71°C) only. For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GLX® Couplings (–12 and –16) (G44) Section N<br>MegaCrimp® Couplings (G25) Section G<br>Power Crimp® Couplings (–3) Section I<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 85940 | 3RLA X25FT | 3284-4028 | 1 | 3/16 | .41 | 250 | 1000 | 3.0 | 28 |
| 70040 | 3RLAXREEL | 3284-0110 | 550 | 3/16 | .41 | 250 | 1000 | 3.0 | 28 |
| 85941 | 4RLA X25FT | 3284-4029 | 1 | 1/4 | .50 | 250 | 1000 | 3.0 | 28 |
| 70041 | 4RLAXREEL | 3284-0120 | 550 | 1/4 | .50 | 250 | 1000 | 3.0 | 28 |
| 85942 | 5RLA X25FT | 3284-4030 | 1 | 5/16 | .56 | 250 | 1000 | 4.0 | 28 |
| 70042 | 5RLAXREEL | 3284-0130 | 550 | 5/16 | .56 | 250 | 1000 | 4.0 | 28 |
| 85943 | 6RLA-30R2X25FT | 3284-4031 | 1 | 3/8 | .66 | 250 | 1000 | 4.0 | 28 |
| 70043 | 6RLAXREEL | 3284-0140 | 550 | 3/8 | .66 | 250 | 1000 | 4.0 | 28 |
| 85944 | 8RLA X25FT | 3284-4032 | 1 | 1/2 | .81 | 200 | 800 | 5.0 | 20 |
| 70044 | 8RLAXREEL | 3284-0150 | 550 | 1/2 | .81 | 200 | 800 | 5.0 | 20 |
| 85945 | 10RLA X25FT | 3284-4033 | 1 | 5/8 | .94 | 200 | 800 | 6.0 | 15 |
| 70045 | 10RLAXREEL | 3284-0160 | 550 | 5/8 | .94 | 200 | 800 | 6.0 | 15 |
| 85946 | 12RLA-30R2X25FT | 3284-4088 | 1 | 3/4 | 1.09 | 200 | 800 | 6.0 | 10 |
| 70046 | 12RLA-30R2XREEL | 3284-0170 | 650 | 3/4 | 1.09 | 200 | 800 | 6.0 | 10 |
| 85947 | 16RLA-30R2X25FT | 3284-4181 | 1 | 1 | 1.34 | 160 | 640 | 8.0 | 10 |
| 70047 | 16RLA-30R2XREEL | 3284-0180 | 400 | 1 | 1.34 | 160 | 640 | 8.0 | 10 |

## RLC 3-FIBER BRAID RETURN LINE AND LOW PRESSURE HOSE

### RETURN

| | |
|---|---|
| RECOMMENDED FOR | Petroleum–based hydraulic oils, glycol antifreeze, air or water in low–pressure fluid transfer or hydraulic system return lines. Generally connected to 100R4 stems, beaded nipples, or tube type ports with worm gear clamps. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Three fiber braids. |
| COVER | Black, oil and abrasion resistant, synthetic rubber (Nitrile and PVC). See Hose Stock Characteristics. |
| TEMPERATURE RANGE | For hydraulic oil lines –40°F to +275°F (–40°C to +135°C) constant and +300°F (+149°C) intermittent (up to 10% of operating time); air to +160°F (+71°C) only. For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | Use barbed stem or beaded–tube with clamps only. (See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | ⊖ | | | | R | ○ |
|---|---|---|---|---|---|---|---|---|---|
| 70142 | 16RLCXCTN | 3319-0261 | 50 | 1 | 1.62 | 200 | 800 | 9.0 | 25 |
| 70074 | 20RLCXCTN | 3319-0263 | 50 | 1 1/4 | 1.88 | 200 | 800 | 10.0 | 25 |
| 70075 | 24RLCXCTN | 3319-0264 | 100 | 1 1/2 | 2.12 | 200 | 800 | 11.0 | 25 |
| 70143 | 28RLCXCTN | 3319-0265 | 50 | 1 3/4 | 2.38 | 200 | 800 | 12.0 | 25 |
| 70076 | 32RLCXCTN | 3319-0266 | 60 | 2 | 2.56 | 200 | 800 | 13.0 | 25 |
| 70070 | 36RLCXCTN | 3319-0267 | 50 | 2 1/4 | 2.87 | 150 | 600 | 14.0 | 25 |
| 70077 | 40RLCXCTN | 3319-0268 | 50 | 2 1/2 | 3.12 | 150 | 600 | 16.0 | 25 |
| 70078 | 48RLCXCTN | 3319-0270 | 50 | 3 | 3.62 | 150 | 600 | 20.0 | 25 |
| 70081 | 56RLCXCTN | 3319-0272 | 50 | 3 1/2 | 4.12 | 150 | 600 | 24.0 | 25 |
| 70144 | 72RLC X10FT | 3319-0273 | 10 | 4 1/2 | 5.19 | 100 | 400 | 54.0 | 25 |

## MEGATECH® LOC 1-FIBER BRAID HIGH-TEMP LOCK-ON HOSE

### LOCK–ON

| | |
|---|---|
| RECOMMENDED FOR | High–temperature (+300°F) transmission oil cooler lines, pressurized hot oil return lines and turbocharger oil supply lines. Not recommended for gasoline or diesel fuel applications. |
| TUBE | True–bore black tube specifically compounded for temperature and chemical resistance (CPE). |
| REINFORCEMENT | One fiber braid. |
| COVER | Oil and mildew resistant, textile braid, impregnated with synthetic rubber. |
| TEMPERATURE RANGE | –40°F to +300°F (–40°C to +149°C). |
| COUPLING RECOMMENDATION | Field Attachable LOC Couplings (G36) Section AC<br>MegaCrimp® Couplings (–16) (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | ⟷ | | | | R |
|---|---|---|---|---|---|---|---|---|
| 76993 | 4MEGATECHLOCXREEL | 4319-0106 | 575 | 1/4 | .50 | 300 | 1200 | 3.0 |
| 76994 | 6MEGATECHLOCXREEL | 4319-0107 | 600 | 3/8 | .64 | 300 | 1200 | 3.0 |
| 76995 | 8MEGATECHLOCXREEL | 4319-0108 | 335 | 1/2 | .78 | 300 | 1200 | 5.0 |
| 76996 | 10MEGATECHLOCXREEL | 4319-0109 | 260 | 5/8 | .91 | 300 | 1200 | 6.0 |
| 76997 | 12MEGATECHLOCXREEL | 4319-0110 | 220 | 3/4 | 1.08 | 300 | 1200 | 7.0 |
| 76998 | 16MEGATECHLOCXREEL | 4319-0111 | 200 | 1 | 1.33 | 300 | 1200 | 7.0 |

# LOC 1-FIBER BRAID LOCK-ON HOSE

## LOCK–ON

| | |
|---|---|
| RECOMMENDED FOR | Petroleum–based hydraulic oils, glycol anti–freeze compounds, water, engine lubricating oils and air. Lock–On hose and couplings are NOT recommended for vibration or pressure surge applications, such as permanent piping in residential or commercial buildings. Meets SAE 30R2, SAE 30R6 and SAE 30R7 performance requirements for fuel and B20 biodiesel fuel transfer applications up to +125°F. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | One fiber braid. |
| COVER | Oil and mildew resistant, textile braid, impregnated with synthetic rubber. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For air: –40°F to +160°F (–40°C to +71°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | Field Attachable LOC Couplings (G36) Section AC<br>Use clamp over G37 single bead and G38 barbed with clamp.<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 86691 | 4LOC X50FT | 4319-4935 | 1 | 1/4 | .52 | 300 | 1200 | 3.0 |
| 70030 | 4LOCXREEL | 4319-0112 | 300 | 1/4 | .52 | 300 | 1200 | 3.0 |
| 86630 | 5LOC X50FT | 4319-1794 | 1 | 5/16 | .56 | 300 | 1200 | 3.0 |
| 70231 | 5LOCXREEL | 4319-1793 | 350 | 5/16 | .56 | 300 | 1200 | 3.0 |
| 86692 | 6LOC X50FT | 4319-4936 | 1 | 3/8 | .64 | 300 | 1200 | 3.0 |
| 70031 | 6LOCXREEL | 4319-0113 | 300 | 3/8 | .64 | 300 | 1200 | 3.0 |
| 86693 | 8LOC X50FT | 4319-4937 | 1 | 1/2 | .80 | 300 | 1200 | 5.0 |
| 70032 | 8LOCXREEL | 4319-0114 | 300 | 1/2 | .80 | 300 | 1200 | 5.0 |
| 70033 | 10LOCXREEL | 4319-0115 | 250 | 5/8 | .90 | 300 | 1200 | 6.0 |
| 70034 | 12LOCXREEL | 4319-0116 | 225 | 3/4 | 1.00 | 300 | 1200 | 7.0 |

# LOL PLUS LOCK-ON HOSE

## LOCK–ON




| | |
|---|---|
| RECOMMENDED FOR | Petroleum–based hydraulic oils, water, glycol anti–freeze solutions, engine lubricating oils, and air. Lock–On hose and couplings are NOT recommended for pressure surge applications or critical applications, such as permanent piping in residential or commercial buildings. Do not use for gasoline or diesel fuels, unless approved by Gates H/C Product Application. |
| TUBE | Black, oil resistant, synthetic rubber highly resistant to oil and heat (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | One fiber braid. |
| COVER | Oil and abrasion resistant synthetic rubber (Nitrile and PVC). Available in black Polychloroprene (LOLA), blue (LOLB), green (LOLG), red (LOLR), yellow (LOLY) and gray (LOLC) colors. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). Air to +160°F (+71°C) only. For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | Field Attachable LOC Couplings (G36) Section AC<br>GLX® Couplings (–4, –6, –8 and –12) (G44) Section N<br>Use clamp over G37 single bead and G38 barbed with clamp.<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Black Cover Only Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | ⊖ | | | | R | ○ |
|---|---|---|---|---|---|---|---|---|---|
| 70650 | 3LOLAXREEL* | 3284-2500 | 300 | 3/16 | .41 | 300 | 1200 | 3.0 | 28 |
| 70651 | 3LOLBXREEL* | 3284-2510 | 300 | 3/16 | .41 | 300 | 1200 | 3.0 | 28 |
| 70655 | 3LOLCXREEL* ** | 3284-2520 | 300 | 3/16 | .41 | 300 | 1200 | 3.0 | 28 |
| 70652 | 3LOLGXREEL* ** | 3284-2530 | 300 | 3/16 | .41 | 300 | 1200 | 3.0 | 28 |
| 70653 | 3LOLRXREEL* | 3284-2540 | 300 | 3/16 | .41 | 300 | 1200 | 3.0 | 28 |
| 70654 | 3LOLYXREEL* ** | 3284-2560 | 300 | 3/16 | .41 | 300 | 1200 | 3.0 | 28 |
| 85961 | 4LOLA X50FT | 3284-2266 | 1 | 1/4 | .47 | 300 | 1200 | 3.0 | 28 |
| 70657 | 4LOLAXREEL | 3284-2501 | 475 | 1/4 | .47 | 300 | 1200 | 3.0 | 28 |
| 85967 | 4LOLB X25FT | 3284-2272 | 1 | 1/4 | .47 | 300 | 1200 | 3.0 | 28 |
| 70658 | 4LOLBXREEL | 3284-2511 | 475 | 1/4 | .47 | 300 | 1200 | 3.0 | 28 |
| 70662 | 4LOLCXREEL | 3284-2521 | 475 | 1/4 | .47 | 300 | 1200 | 3.0 | 28 |
| 85972 | 4LOLG X25FT | 3284-2277 | 1 | 1/4 | .47 | 300 | 1200 | 3.0 | 28 |
| 70659 | 4LOLGXREEL | 3284-2531 | 475 | 1/4 | .47 | 300 | 1200 | 3.0 | 28 |
| 85976 | 4LOLR X25FT | 3284-2281 | 1 | 1/4 | .47 | 300 | 1200 | 3.0 | 28 |
| 70660 | 4LOLRXREEL | 3284-2541 | 475 | 1/4 | .47 | 300 | 1200 | 3.0 | 28 |
| 70661 | 4LOLYXREEL | 3284-2561 | 475 | 1/4 | .47 | 300 | 1200 | 3.0 | 28 |
| 85960 | 5LOLA X25FT | 3284-2297 | 1 | 5/16 | .55 | 300 | 1200 | 3.0 | 28 |
| 85962 | 5LOLA X50FT | 3284-2267 | 1 | 5/16 | .55 | 300 | 1200 | 3.0 | 28 |
| 70664 | 5LOLAXREEL | 3284-2502 | 300 | 5/16 | .55 | 300 | 1200 | 3.0 | 28 |
| 85963 | 6LOLA X50FT | 3284-2268 | 1 | 3/8 | .63 | 300 | 1200 | 3.0 | 28 |
| 70665 | 6LOLAXREEL | 3284-2503 | 300 | 3/8 | .63 | 300 | 1200 | 3.0 | 28 |
| 85968 | 6LOLB X25FT | 3284-2273 | 1 | 3/8 | .63 | 300 | 1200 | 3.0 | 28 |
| 70666 | 6LOLBXREEL | 3284-2513 | 300 | 3/8 | .63 | 300 | 1200 | 3.0 | 28 |
| 70670 | 6LOLCXREEL | 3284-2523 | 300 | 3/8 | .63 | 300 | 1200 | 3.0 | 28 |
| 85973 | 6LOLG X25FT | 3284-2278 | 1 | 3/8 | .63 | 300 | 1200 | 3.0 | 28 |
| 70667 | 6LOLGXREEL | 3284-2533 | 300 | 3/8 | .63 | 300 | 1200 | 3.0 | 28 |
| 85977 | 6LOLR X25FT | 3284-2282 | 1 | 3/8 | .63 | 300 | 1200 | 3.0 | 28 |
| 70668 | 6LOLRXREEL | 3284-2543 | 300 | 3/8 | .63 | 300 | 1200 | 3.0 | 28 |
| 70669 | 6LOLYXREEL | 3284-2563 | 300 | 3/8 | .63 | 300 | 1200 | 3.0 | 28 |
| 85964 | 8LOLA X50FT | 3284-2269 | 1 | 1/2 | .77 | 300 | 1200 | 5.0 | 28 |
| 70672 | 8LOLAXREEL | 3284-2504 | 300 | 1/2 | .77 | 300 | 1200 | 5.0 | 28 |
| 85969 | 8LOLB X25FT | 3284-2274 | 1 | 1/2 | .77 | 300 | 1200 | 5.0 | 28 |
| 70673 | 8LOLBXREEL | 3284-2515 | 300 | 1/2 | .77 | 300 | 1200 | 5.0 | 28 |
| 70677 | 8LOLCXREEL | 3284-2525 | 300 | 1/2 | .77 | 300 | 1200 | 5.0 | 28 |
| 85974 | 8LOLG X25FT | 3284-2279 | 1 | 1/2 | .77 | 300 | 1200 | 5.0 | 28 |

**Couplings for this size are available on special order only.*
***Special hose, subject to minimum order requirements if not in inventory.*
NOTE: LOL Lock–On Hose is packaged in UPS shippable reels.

## LOL PLUS LOCK-ON HOSE - CONTINUED

### LOCK–ON - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 70674 | 8LOLGXREEL | 3284-2535 | 300 | 1/2 | .77 | 300 | 1200 | 5.0 | 28 |
| 85978 | 8LOLR X25FT | 3284-2283 | 1 | 1/2 | .77 | 300 | 1200 | 5.0 | 28 |
| 70675 | 8LOLRXREEL | 3284-2545 | 300 | 1/2 | .77 | 300 | 1200 | 5.0 | 28 |
| 70676 | 8LOLYXREEL | 3284-2565 | 300 | 1/2 | .77 | 300 | 1200 | 5.0 | 28 |
| 85965 | 10LOLA X50FT | 3284-2270 | 1 | 5/8 | .94 | 300 | 1200 | 6.0 | 28 |
| 70679 | 10LOLAXREEL | 3284-2505 | 250 | 5/8 | .94 | 300 | 1200 | 6.0 | 28 |
| 85970 | 10LOLB X25FT | 3284-2275 | 1 | 5/8 | .94 | 300 | 1200 | 6.0 | 28 |
| 70680 | 10LOLBXREEL | 3284-2517 | 250 | 5/8 | .94 | 300 | 1200 | 6.0 | 28 |
| 70684 | 10LOLCXREEL | 3284-2527 | 250 | 5/8 | .94 | 300 | 1200 | 6.0 | 28 |
| 70681 | 10LOLGXREEL* | 3284-2537 | 250 | 5/8 | .94 | 300 | 1200 | 6.0 | 28 |
| 70682 | 10LOLRXREEL* | 3284-2547 | 250 | 5/8 | .94 | 300 | 1200 | 6.0 | 28 |
| 70683 | 10LOLYXREEL* | 3284-2567 | 250 | 5/8 | .94 | 300 | 1200 | 6.0 | 28 |
| 85966 | 12LOLA X50FT | 3284-2271 | 1 | 3/4 | 1.06 | 300 | 1200 | 7.0 | 15 |
| 70686 | 12LOLAXREEL | 3284-2506 | 225 | 3/4 | 1.06 | 300 | 1200 | 7.0 | 15 |
| 85971 | 12LOLB X25FT | 3284-2276 | 1 | 3/4 | 1.06 | 300 | 1200 | 7.0 | 15 |
| 70687 | 12LOLBXREEL | 3284-2519 | 225 | 3/4 | 1.06 | 300 | 1200 | 7.0 | 15 |
| 70691 | 12LOLCXREEL | 3284-2529 | 225 | 3/4 | 1.06 | 300 | 1200 | 7.0 | 15 |
| 85975 | 12LOLG X25FT | 3284-2280 | 1 | 3/4 | 1.06 | 300 | 1200 | 7.0 | 15 |
| 70688 | 12LOLGXREEL | 3284-2536 | 225 | 3/4 | 1.06 | 300 | 1200 | 7.0 | 15 |
| 85979 | 12LOLR X25FT | 3284-2284 | 1 | 3/4 | 1.06 | 300 | 1200 | 7.0 | 15 |
| 70689 | 12LOLRXREEL | 3284-2549 | 225 | 3/4 | 1.06 | 300 | 1200 | 7.0 | 15 |
| 70690 | 12LOLYXREEL | 3284-2569 | 225 | 3/4 | 1.06 | 300 | 1200 | 7.0 | 15 |

**Special hose, subject to minimum order requirements if not in inventory.*
NOTE: LOL Lock–On Hose is packaged in UPS shippable reels.

## AB SERIES AIR BRAKE HOSE

### FLEET

| | |
|---|---|
| RECOMMENDED FOR | Truck, bus and mobile air brake systems. Can be used as flexible connector between frame and axle. Meets SAE J1402 specifications. Complies with DOT FMVSS 106 requirements. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). |
| COUPLING RECOMMENDATION | Gates G33 Series type air brake couplings. Section AC (See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | |
|---|---|---|---|---|---|---|---|
| 27240 | 3/8 X 50FT Rubber Air Brake | 3245-0601 | 1 | 3/8 | 3/4 | 225 | 1000 |
| 28760 | 3/8 X 250FT Reel Rubber Air Brake | 3245-0602 | 1 | 3/8 | 3/4 | 225 | 1000 |
| 27241 | 1/2 X 50FT Rubber Air Brake | 3245-0603 | 1 | 1/2 | 7/8 | 225 | 1000 |
| 28761 | 1/2 X 250FT Reel Rubber Air Brake | 3245-0604 | 1 | 1/2 | 7/8 | 225 | 1000 |

NOTE: Federal law requires registration with the Department of Transportation for anyone producing air brake hose assemblies with swaged or crimped fittings. See Engineering and Technical Data Section for compliance.

## HEAVY-DUTY GREEN STRIPE® AIR BRAKE HOSE

### FLEET

| | |
|---|---|
| RECOMMENDED FOR | Truck, bus and mobile air brake systems. Can be used as flexible connector between frame and axle. Exceeds SAE J1402 and Bendix specifications. Complies with DOT FMVSS 106 requirements. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). |
| COUPLING RECOMMENDATION | Gates G33 Series type air brake couplings. Section AC (See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | ⟷ | ↕ | | |
|---|---|---|---|---|---|---|---|
| 28304 | 3/8 X250 REEL GS RBR AB | 3245-4470 | 1 | 3/8 | 3/4 | 225 | 1000 |
| 27221 | 1/2" HD GS AIR BRAKE X50FT | 3245-4467 | 1 | 1/2 | 7/8 | 225 | 1000 |
| 27220 | 6ABGS X50FT | 3245-4468 | 1 | 3/8 | 3/4 | 225 | 1000 |

NOTE: Federal law requires registration with the Department of Transportation for anyone producing air brake hose assemblies with swaged or crimped fittings. See Engineering and Technical Data Section for compliance.

## GREEN STRIPE® VACUUM BRAKE HOSE

### FLEET

| | |
|---|---|
| RECOMMENDED FOR | Extra heavy–duty hose designed to fit most air brake systems on trucks, trailers and other heavy equipment. Exceeds SAE J1403, Type H requirements. Complies with DOT FMVSS 106VH requirements. |
| TEMPERATURE RANGE | –40°F to +257°F (–40°C to +125°C). |
| COUPLING RECOMMENDATION | Gates G33 Series type air brake couplings. Section AC (See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | ⟷ | ↕ | | ○ |
|---|---|---|---|---|---|---|---|
| 27212 | 5/8 X50FT VAC BRAKE | 3245-4476 | 1 | 5/8 | 1 1/16 | 800 | 30 |
| 27213 | 3/4 X50FT VAC BRAKE | 3145-4477 | 1 | 3/4 | 1 3/16 | 800 | 30 |

## TR500 HIGH-TEMP/AIR BRAKE/ENGINE HOSE

### FLEET

| | |
|---|---|
| RECOMMENDED FOR | Air brake hose, high temperature pressurized oil return lines and rotary oil/air compressor lines, engine and transmission coolant lines and lube oil lines. Meets or exceeds DOT FMVSS 106–74, SAE J1402 for air brake hose (–4, –6, –8, –10). Not recommended for gasoline or diesel fuel applications. |
| TUBE | Black Nitrile. See Hose Stock Characteristics. |
| REINFORCEMENT | One braid of high–tensile steel wire. |
| COVER | Oil and mildew resistant, textile braid, impregnated with synthetic rubber. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 85745 | 4TR500 X50FT | 4657-2600 | 1 | 1/4 | .51 | 500 | 2000 | 1.0 | 30 |
| 70881 | 4TR500XREEL | 4657-2228 | 250 | 1/4 | .51 | 500 | 2000 | 1.0 | 30 |
| 85747 | 6TR500 X50FT | 4657-2601 | 1 | 3/8 | .66 | 500 | 2000 | 1.8 | 30 |
| 70883 | 6TR500XREEL | 4657-2520 | 350 | 3/8 | .66 | 500 | 2000 | 1.8 | 30 |
| 85748 | 8TR500 X50FT | 4657-2602 | 1 | 1/2 | .80 | 500 | 2000 | 2.3 | 30 |
| 70884 | 8TR500XREEL | 4657-2521 | 350 | 1/2 | .80 | 500 | 2000 | 2.3 | 30 |
| 85749 | 10TR500 X50FT | 4657-2603 | 1 | 5/8 | .93 | 500 | 2000 | 2.8 | 30 |
| 70885 | 10TR500XREEL | 4657-2229 | 300 | 5/8 | .93 | 500 | 2000 | 2.8 | 30 |
| 85750 | 12TR500 X50FT | 4657-2604 | 1 | 3/4 | 1.04 | 500 | 2000 | 3.5 | 30 |
| 70886 | 12TR500XREEL | 4657-2230 | 200 | 3/4 | 1.04 | 500 | 2000 | 3.5 | 30 |
| 85751 | 16TR500 X50FT | 4657-2605 | 1 | 1 | 1.30 | 500 | 2000 | 4.5 | 30 |
| 70887 | 16TR500XREEL | 4657-2231 | 150 | 1 | 1.30 | 500 | 2000 | 4.5 | 30 |

NOTE: Federal law requires registration with the Department of Transportation for anyone producing air brake hose assemblies with swaged or crimped fittings. See Engineering and Technical Data Section for compliance.

## MEGATECH® G5TB OIL-AIR RETURN

### FLEET

| | |
|---|---|
| RECOMMENDED FOR | Pressurized hot oil return lines and rotary oil lines. |
| TUBE | True–bore black tube specifically compounded for temperature and chemical resistance (CPE). |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Blue, oil and mildew resistant textile braid, impregnated with synthetic rubber. |
| TEMPERATURE RANGE | Petroleum–base fluids: –40°F to +300°F (–40°C to +149°C). Phosphate esters fluids as recommended by the fluid manufacturer, but within a range of –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GL Couplings (–24 and –32) (G43) Section M<br>GlobalSpiral™ Plus Couplings (–24 and –32) (G22) Section E<br>MegaCrimp® Couplings (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85391 | 4MEGATECH G5TB X50FT | 4657-4070 | 1 | 1/4 | .58 | 3000 | 12000 | 2.0 |
| 71023 | 4MEGATECH G5TBXREEL | 4657-2183 | 400 | 1/4 | .58 | 3000 | 12000 | 2.0 |
| 85392 | 6MEGATECH G5TB X50FT | 4657-4071 | 1 | 3/8 | .76 | 3000 | 12000 | 2.5 |

## MEGATECH® G5TB OIL-AIR RETURN - CONTINUED

### FLEET - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 71024 | 6MEGATECH G5TBXREEL | 4657-2184 | 350 | 3/8 | .76 | 3000 | 12000 | 2.5 |
| 85393 | 8MEGATECH G5TB X50FT | 4657-4072 | 1 | 1/2 | .87 | 3000 | 12000 | 3.5 |
| 71025 | 8MEGATECH G5TBXREEL | 4657-2185 | 350 | 1/2 | .87 | 3000 | 12000 | 3.5 |
| 71066 | 10MEGATECH G5TBXREEL | 4657-2186 | 300 | 5/8 | .98 | 2000 | 8000 | 4.0 |
| 71067 | 12MEGATECH G5TBXREEL | 4657-2187 | 200 | 3/4 | 1.12 | 2000 | 8000 | 4.7 |
| 85396 | 16MEGATECH G5TB X50FT | 4657-4075 | 1 | 1 | 1.34 | 1000 | 4000 | 6.0 |
| 71026 | 16MEGATECH G5TBXREEL | 4657-2188 | 150 | 1 | 1.34 | 1000 | 4000 | 6.0 |
| 85398 | 20MEGATECH G5TB X25FT | 4657-4079 | 1 | 1 1/4 | 1.70 | 1000 | 4000 | 8.5 |
| 85397 | 20MEGATECH G5TB X50FT | 4657-4076 | 1 | 1 1/4 | 1.70 | 1000 | 4000 | 8.5 |
| 71027 | 20MEGATECH G5TBXCTN | 4657-2189 | 100 | 1 1/4 | 1.70 | 1000 | 4000 | 8.5 |
| 85395 | 24MEGATECH G5TB X25FT | 4657-4080 | 1 | 1 1/2 | 1.94 | 500 | 2000 | 9.5 |
| 85394 | 24MEGATECH G5TB X50FT | 4657-4077 | 1 | 1 1/2 | 1.94 | 500 | 2000 | 9.5 |
| 71028 | 24MEGATECH G5TBXCTN | 4657-2190 | 100 | 1 1/2 | 1.94 | 500 | 2000 | 9.5 |
| 85400 | 32MEGATECH G5TB X25FT | 4657-4081 | 1 | 2 | 2.53 | 500 | 2000 | 10.5 |
| 85399 | 32MEGATECH G5TB X50FT | 4657-4078 | 1 | 2 | 2.53 | 500 | 2000 | 10.5 |
| 71029 | 32MEGATECH G5TBXCTN | 4657-2191 | 100 | 2 | 2.53 | 500 | 2000 | 10.5 |

## MEGATECH® II - SAE 100R2 TYPE AT - ACP

### FLEET

| | |
|---|---|
| RECOMMENDED FOR | Multi–purpose high–pressure, high–temperature, air compressor lines, petroleum–base or phosphate ester hydraulic fluid supply lines. Meets or exceeds the requirements of SAE 100R2. |
| TUBE | Black, oil resistant, synthetic rubber (CPE). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Blue, oil and abrasion resistant, polyester braid. |
| TEMPERATURE RANGE | –40°F to +300°F (–40°C to +149°C). |
| COUPLING RECOMMENDATION | GlobalSpiral™ Plus Couplings (–24 and –32) (G22) Section E<br>MegaCrimp® Couplings (–20) (G25) Section G<br>Stainless Steel Braid Couplings (–24 and –32) (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70975 | 20ACP MEGATECHIIXCTN | 4657-8018 | 100 | 1 1/4 | 1.89 | 2250 | 9000 | 15.0 |
| 70858 | 24ACP MEGATECHIIXCTN | 4657-2484 | 100 | 1 1/2 | 2.13 | 1500 | 6000 | 20.0 |
| 70802 | 32ACP MEGATECHII XCTN50 | 4657-4734 | 50 | 2 | 2.61 | 1300 | 5200 | 25.0 |
| 70859 | 32ACP MEGATECHIIXCTN | 4657-2485 | 100 | 2 | 2.61 | 1300 | 5200 | 25.0 |

## MEGATECH® 3000 HIGH-TEMP OIL-AIR RETURN

### FLEET

| | |
|---|---|
| RECOMMENDED FOR | Pressurized hot oil return lines and rotary oil lines. |
| TUBE | True–bore black tube specifically compounded for temperature and chemical resistance (CPE). |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Oil and mildew resistant, textile braid, impregnated with synthetic rubber. |
| TEMPERATURE RANGE | Petroleum–base fluids: –40°F to +300°F (–40°C to +149°C). Phosphate esters fluids as recommended by the fluid manufacturer, but within a range of –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G (See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 70960 | 4MEGATECH 3000XREEL | 4657-2373 | 400 | 1/4 | .59 | 3000 | 12000 | 2.0 | 30 |
| 85987 | 4MEGATECH3000 X50FT | 4657-4116 | 1 | 1/4 | .59 | 3000 | 12000 | 2.0 | 30 |
| 70961 | 6MEGATECH 3000XREEL | 4657-2374 | 350 | 3/8 | .74 | 3000 | 12000 | 2.5 | 30 |
| 85988 | 6MEGATECH3000 X50FT | 4657-4117 | 1 | 3/8 | .74 | 3000 | 12000 | 2.5 | 30 |
| 70962 | 8MEGATECH 3000XREEL | 4657-2319 | 350 | 1/2 | .86 | 3000 | 12000 | 3.5 | 30 |
| 85989 | 8MEGATECH3000 X50FT | 4657-4118 | 1 | 1/2 | .86 | 3000 | 12000 | 3.5 | 30 |

## MEGATECH® 1000 HIGH-TEMP OIL-AIR RETURN

### FLEET

| | |
|---|---|
| RECOMMENDED FOR | Air brake hose, pressurized hot oil return lines and rotary oil/air compressor lines. Meets the requirements of DOT FMVSS 106–74, SAE J1402, for Air Brake Hose (–4, –6, –8, –10). Not recommended for gasoline or diesel fuel applications. |
| TUBE | Black tube specifically compounded for temperature and chemical resistance (CPE). See Hose Stock Characteristics. |
| REINFORCEMENT | One braid of high–tensile steel wire. |
| COVER | Oil and mildew resistant, textile braid, impregnated with synthetic rubber. |
| TEMPERATURE RANGE | Petroleum–base fluids: –40°F to +300°F (–40°C to +149°C). Phosphate esters fluids as recommended by the fluid manufacturer, but within a range of –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G (See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 70850 | 4MEGATECH 1000XREEL | 4657-2332 | 350 | 1/4 | .52 | 1000 | 4000 | 2.0 | 30 |
| 85980 | 4MEGATECH1000 X50FT | 4657-2503 | 1 | 1/4 | .52 | 1000 | 4000 | 2.0 | 30 |
| 70851 | 6MEGATECH 1000XREEL | 4657-2297 | 350 | 3/8 | .66 | 1000 | 4000 | 2.5 | 30 |
| 85981 | 6MEGATECH1000 X50FT | 4657-2504 | 1 | 3/8 | .66 | 1000 | 4000 | 2.5 | 30 |
| 70852 | 8MEGATECH 1000XREEL | 4657-2334 | 350 | 1/2 | .80 | 1000 | 4000 | 3.5 | 30 |
| 85982 | 8MEGATECH1000 X50FT | 4657-2505 | 1 | 1/2 | .80 | 1000 | 4000 | 3.5 | 30 |
| 70853 | 10MEGATECH 1000XREEL | 4657-2335 | 300 | 5/8 | .93 | 1000 | 4000 | 4.0 | 30 |
| 85983 | 10MEGATECH1000 X50FT | 4657-2506 | 1 | 5/8 | .93 | 1000 | 4000 | 4.0 | 30 |
| 70888 | 12MEGATECH 1000XREEL | 4657-2336 | 200 | 3/4 | 1.15 | 1000 | 4000 | 4.7 | 30 |

NOTE: Federal law requires registration with the Department of Transportation for anyone producing air brake hose assemblies with swaged or crimped fittings. See Engineering and Technical Data Section for compliance.

## MEGATECH® 1000 HIGH-TEMP OIL-AIR RETURN - CONTINUED

### FLEET - CONTINUED

| Part No. | Description | Product No. | Standard Pack | ⊖ | ↕ | | | R | ◯ |
|---|---|---|---|---|---|---|---|---|---|
| 85984 | 12MEGATECH1000 X50FT | 4657-4040 | 1 | 3/4 | 1.15 | 1000 | 4000 | 4.7 | 30 |
| 70889 | 16MEGATECH 1000XREEL | 4657-2337 | 150 | 1 | 1.37 | 1000 | 4000 | 6.0 | 30 |
| 85985 | 16MEGATECH1000 X50FT | 4657-4041 | 1 | 1 | 1.37 | 1000 | 4000 | 6.0 | 30 |
| 70890 | 20MEGATECH 1000XCTN | 4657-2338 | 100 | 1 1/4 | 1.68 | 1000 | 4000 | 8.5 | 30 |
| 85986 | 20MEGATECH1000 X50FT | 4657-4042 | 1 | 1 1/4 | 1.68 | 1000 | 4000 | 8.5 | 30 |

NOTE: Federal law requires registration with the Department of Transportation for anyone producing air brake hose assemblies with swaged or crimped fittings. See Engineering and Technical Data Section for compliance.

## MEGATECH® 500 HIGH-TEMP OIL-AIR RETURN

### FLEET

| | |
|---|---|
| RECOMMENDED FOR | Air brake hose, pressurized hot oil return lines and rotary oil/air compressor lines. Not recommended for gasoline or diesel fuel applications. |
| TUBE | Black tube specifically compounded for temperature and chemical resistance (CPE). See Hose Stock Characteristics. |
| REINFORCEMENT | One braid of high–tensile steel wire. |
| COVER | Oil and mildew resistant, textile braid, impregnated with synthetic rubber. |
| TEMPERATURE RANGE | Petroleum–base fluids: –40°F to +300°F (–40°C to +149°C). Phosphate esters fluids as recommended by the fluid manufacturer, but within a range of –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GL Couplings (G43) Section M<br>GlobalSpiral™ Plus Couplings (–24 and –32) (G22) Section E<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | ⊖ | ↕ | | | R | ◯ |
|---|---|---|---|---|---|---|---|---|---|
| 70854 | 24MEGATECH 500XCTN | 4657-0204 | 100 | 1 1/2 | 1.95 | 500 | 2000 | 15.0 | 30 |
| 85687 | 24MEGATECH500 X50FT | 4657-0061 | 1 | 1 1/2 | 1.95 | 500 | 2000 | 15.0 | 30 |
| 70855 | 32MEGATECH 500XCTN | 4657-0205 | 100 | 2 | 2.48 | 500 | 2000 | 18.0 | 30 |
| 85688 | 32MEGATECH500 X50FT | 4657-0062 | 1 | 2 | 2.48 | 500 | 2000 | 18.0 | 30 |
| 70856 | 40MEGATECH 500XCTN | 4657-0206 | 100 | 2 1/2 | 2.97 | 500 | 2000 | 22.0 | 30 |
| 70857 | 48MEGATECH 500XCTN | 4657-0207 | 100 | 3 | 3.50 | 500 | 2000 | 24.0 | 30 |

# MEGATECH® 250 HIGH-TEMP TRANSMISSION OIL COOLER (TOC) HOSE

## FLEET

| | |
|---|---|
| RECOMMENDED FOR | High–temperature (+300°F) transmission oil cooler lines, pressurized hot oil return lines and turbocharger oil supplies. |
| TUBE | Black tube specifically compounded for temperature and chemical resistance (CPE). See Hose Stock Characteristics. |
| REINFORCEMENT | One braid of high–tensile steel wire. |
| COVER | Oil and mildew resistant, textile braid, impregnated with synthetic rubber. |
| TEMPERATURE RANGE | Petroleum–base fluids: –40°F to +300°F (–40°C to +149°C). Phosphate esters fluids as recommended by the fluid manufacturer, but within a range of –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G (See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 70891 | 4MEGATECH 250XREEL | 4657-2339 | 250 | 1/4 | .52 | 250 | 1000 | 1.0 | 30 |
| 85759 | 4MEGATECH250 X50FT | 4657-0083 | 1 | 1/4 | .52 | 250 | 1000 | 1.0 | 30 |
| 70892 | 6MEGATECH 250XREEL | 4657-2340 | 350 | 3/8 | .64 | 250 | 1000 | 1.8 | 30 |
| 85760 | 6MEGATECH250 X50FT | 4657-0084 | 1 | 3/8 | .64 | 250 | 1000 | 1.8 | 30 |
| 70893 | 8MEGATECH 250XREEL | 4657-2341 | 350 | 1/2 | .78 | 250 | 1000 | 2.5 | 30 |
| 85761 | 8MEGATECH250 X50FT | 4657-0085 | 1 | 1/2 | .78 | 250 | 1000 | 2.5 | 30 |
| 70894 | 10MEGATECH 250XREEL | 4657-2342 | 300 | 5/8 | .93 | 250 | 1000 | 3.0 | 30 |
| 85762 | 10MEGATECH250 X50FT | 4657-0086 | 1 | 5/8 | .93 | 250 | 1000 | 3.0 | 30 |
| 70895 | 12MEGATECH 250XREEL | 4657-2343 | 200 | 3/4 | 1.06 | 250 | 1000 | 3.5 | 30 |
| 85763 | 12MEGATECH250 X50FT | 4657-0087 | 1 | 3/4 | 1.06 | 250 | 1000 | 3.5 | 30 |
| 70896 | 16MEGATECH 250XREEL | 4657-2344 | 150 | 1 | 1.36 | 250 | 1000 | 4.0 | 30 |
| 85764 | 16MEGATECH250 X50FT | 4657-0088 | 1 | 1 | 1.36 | 250 | 1000 | 4.0 | 30 |
| 70900 | 20MEGATECH 250XCTN | 4657-2345 | 120 | 1 1/4 | 1.65 | 250 | 1000 | 4.5 | 30 |
| 85765 | 20MEGATECH250 X50FT | 4657-0089 | 1 | 1 1/4 | 1.65 | 250 | 1000 | 4.5 | 30 |

# C5C HYDRAULIC HOSE - SAE 100R5

## FLEET




| | |
|---|---|
| RECOMMENDED FOR | Medium–pressure hydraulic petroleum–based oil lines in impulse applications, lube oil, air and water in applications such as air brakes, power steering (CAUTION: Intended for heavy–duty commercial vehicle use only), turbocharger oil supplies, tilt cab cylinders, transmission coolant and filtration lines. Meets or exceeds requirements of SAE 100R5 for traditional hydraulic applications, DOT FMVSS 106–74 Type AII and SAE J1402 Type AII for air brake applications (–4 to –12). Not recommended for gasoline or diesel fuel. |
| TUBE | Black, oil and heat–resistant synthetic rubber (Polychloroprene –4 and –5), (Nitrile –6 through –40). See Hose Stock Characteristics. |
| REINFORCEMENT | One braid of high–tensile carbon steel wire over one braid of polyester. |
| COVER | Black, oil and mildew resistant, polyester braid. |
| TEMPERATURE RANGE | Under SAE 100R5 (hydraulic) conditions –40°F to +212°F (–40°C to +100°C). All–purpose fleet application (hot lube oil lines) –40°F to +300°F (–40°C to +149°C). Air to +160°F (+71°C) only. Avoid continuous use at maximum temperature concurrent with maximum working pressures. For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | C5 Field Attachable Couplings (–4 through –32) (G34) Section K<br>C5X Field Attachable Couplings (–5, –8, and –12) (G34) Section K<br>(See Crimp Data Manual 428–7365 or eCrimp) |

DOT FMVSS 106–74 Type AII and SAE J1402 Type AII for air brake applications (–4 to –12).

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 86605 | 4C5C X50FT | 3658-1762 | 1 | 3/16 | .52 | 3000 | 12000 | 3.0 |
| 70589 | 4C5CXREEL | 3658-1775 | 440 | 3/16 | .52 | 3000 | 12000 | 3.0 |
| 86606 | 5C5C X50FT | 3658-1763 | 1 | 1/4 | .58 | 3000 | 12000 | 3.4 |
| 70590 | 5C5CXREEL | 3658-1776 | 385 | 1/4 | .58 | 3000 | 12000 | 3.4 |
| 86607 | 6C5C X50FT | 3658-1764 | 1 | 5/16 | .67 | 2250 | 9000 | 4.0 |
| 70591 | 6C5CXREEL | 3658-1777 | 385 | 5/16 | .67 | 2250 | 9000 | 4.0 |
| 86608 | 8C5C X50FT | 3658-1765 | 1 | 13/32 | .77 | 2000 | 8000 | 4.6 |
| 70592 | 8C5CXREEL | 3658-1778 | 330 | 13/32 | .77 | 2000 | 8000 | 4.6 |
| 86609 | 10C5C X50FT | 3658-1766 | 1 | 1/2 | .92 | 1750 | 7000 | 5.5 |
| 70593 | 10C5CXREEL | 3658-1779 | 275 | 1/2 | .92 | 1750 | 7000 | 5.5 |
| 86610 | 12C5C X50FT | 3658-1767 | 1 | 5/8 | 1.08 | 1500 | 6000 | 6.5 |
| 70594 | 12C5CXREEL | 3658-1780 | 220 | 5/8 | 1.08 | 1500 | 6000 | 6.5 |
| 86616 | 16C5C X50FT | 3658-1768 | 1 | 7/8 | 1.23 | 800 | 3200 | 7.4 |
| 70595 | 16C5CXREEL | 3658-1781 | 165 | 7/8 | 1.23 | 800 | 3200 | 7.4 |
| 86617 | 20C5C X25FT | 3658-1772 | 1 | 1 1/8 | 1.50 | 625 | 2500 | 9.0 |
| 70096 | 20C5CXCTN | 3658-1758 | 100 | 1 1/8 | 1.50 | 625 | 2500 | 9.0 |
| 70097 | 24C5CXCTN | 3658-1759 | 100 | 1 3/8 | 1.75 | 500 | 2000 | 10.5 |
| 70098 | 32C5CXCTN | 3658-1760 | 100 | 1 13/16 | 2.22 | 350 | 1400 | 13.3 |
| 70099 | 40C5CXCTN | 3658-1761 | 50 | 2 3/8 | 2.88 | 350 | 1400 | 24.0 |

NOTE: Federal law requires registration with the Department of Transportation for anyone producing air brake hose assemblies with swaged or crimped fittings. See Engineering and Technical Data Section for compliance.

# C5C-XH XTREME® HEAT HOSE - SAE 100R5

## FLEET

| | |
|---|---|
| RECOMMENDED FOR | Extremely high–temperature petroleum–based or phosphate ester fluids, turbo charger oil supply and hot lube oil lines. |
| TUBE | Black, oil and heat–resistant synthetic polymer tube (CPE). See Hose Stock Characteristics. |
| REINFORCEMENT | Braided, high–tensile wire and textile. |
| COVER | Blue, oil and mildew resistant polyester/textile braid. |
| TEMPERATURE RANGE | –40°F to +302°F (–40°C to +150°C). |
| COUPLING RECOMMENDATION | C5 Field Attachable Couplings (–6, –16 and –20) (G34) Section K<br>C5X Field Attachable Couplings (–5, –8, and –12) (G34) Section K<br>Crimp options are MegaCrimp®, GlobalSpiral™ (depending on size)<br>(See Crimp Data Manual 428–7365 or eCrimp) |




DOT FMVSS 106–74 Type AII and SAE J1402 Type AII for (–4 to –12).

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70095 | 4C5CXHXREEL | 3658-0150 | 440 | 3/16 | .52 | 3000 | 12000 | 3.4 |
| 86992 | 5C5CXH X50FT | 3658-4001 | 1 | 1/4 | .58 | 3000 | 12000 | 3.4 |
| 70992 | 5C5CXHXREEL | 3658-0151 | 385 | 1/4 | .58 | 3000 | 12000 | 3.4 |
| 86993 | 6C5CXH X50FT | 3658-4002 | 1 | 5/16 | .67 | 2250 | 9000 | 4.0 |
| 70993 | 6C5CXHXREEL | 3658-0152 | 385 | 5/16 | .67 | 2250 | 9000 | 4.0 |
| 86994 | 8C5CXH X50FT | 3658-4003 | 1 | 13/32 | .77 | 2000 | 8000 | 4.6 |
| 70994 | 8C5CXHXREEL | 3658-0153 | 330 | 13/32 | .77 | 2000 | 8000 | 4.6 |
| 86995 | 10C5CXH X50FT | 3658-4004 | 1 | 1/2 | .92 | 1750 | 7000 | 5.5 |
| 70995 | 10C5CXHXREEL | 3658-0154 | 275 | 1/2 | .92 | 1750 | 7000 | 5.5 |
| 86996 | 12C5CXH X50FT | 3658-4005 | 1 | 5/8 | 1.08 | 1500 | 6000 | 6.5 |
| 70996 | 12C5CXHXREEL | 3658-0155 | 220 | 5/8 | 1.08 | 1500 | 6000 | 6.5 |
| 86997 | 16C5CXH X50FT | 3658-4006 | 1 | 7/8 | 1.23 | 800 | 3200 | 7.4 |
| 70997 | 16C5CXHXREEL | 3658-0156 | 165 | 7/8 | 1.23 | 800 | 3200 | 7.4 |
| 86998 | 20C5CXH X50FT | 3658-4007 | 1 | 1 1/8 | 1.50 | 625 | 2500 | 9.0 |
| 70998 | 20C5CXHXCTN | 3658-0157 | 120 | 1 1/8 | 1.50 | 625 | 2500 | 9.0 |

# C5D HIGH-TEMP MULTI-FLUID HOSE

## FLEET




| | |
|---|---|
| RECOMMENDED FOR | Petroleum–based or phosphate ester fluids; diesel fuels and filtration lines, transmission coolant lines, hot lube oil lines, power steering (CAUTION: Intended for heavy–duty commercial vehicle use only), gasoline and turbocharger oil supplies. Tilt cab cylinder and air brakes. C5D (–4 to –12) meets or exceeds DOT FMVSS 106–74 Type All, SAE J1402 Type All. Not approved for bio–diesel above B5. |
| TUBE | Black, oil and heat–resistant, synthetic rubber (CPE). See Hose Stock Characteristics. |
| REINFORCEMENT | One braid of high–tensile steel wire over one braid of polyester. |
| COVER | Green for easy identification, oil and mildew resistant, polyester braid impregnated with synthetic rubber. |
| TEMPERATURE RANGE | –40°F to +300°F (–40°C to +149°C). Air to +250°F (+121°C) only, maximum phosphate esters to +212°F (+100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | C5 Field Attachable Couplings (G34) Section K<br>C5X Field Attachable Couplings (–5, –8, and –12) (G34) Section K<br>(See Crimp Data Manual 428–7365 or eCrimp) |

DOT FMVSS 106–74 Type All, SAE J1402 Type All (–4 to –12).

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85680 | 4C5D X50FT | 3658-0001 | 1 | 3/16 | .52 | 1500 | 6000 | 1.0 |
| 70540 | 4C5DXREEL | 3658-0020 | 440 | 3/16 | .52 | 1500 | 6000 | 1.0 |
| 85681 | 5C5D X50FT | 3658-0007 | 1 | 1/4 | .58 | 1500 | 6000 | 1.5 |
| 70541 | 5C5DXREEL | 3658-0027 | 385 | 1/4 | .58 | 1500 | 6000 | 1.5 |
| 85682 | 6C5D X50FT | 3658-0002 | 1 | 5/16 | .67 | 1500 | 6000 | 1.8 |
| 70542 | 6C5DXREEL | 3658-0021 | 385 | 5/16 | .67 | 1500 | 6000 | 1.8 |
| 85683 | 8C5D X50FT | 3658-0003 | 1 | 13/32 | .77 | 1250 | 5000 | 2.0 |
| 70543 | 8C5DXREEL | 3658-0022 | 330 | 13/32 | .77 | 1250 | 5000 | 2.0 |
| 85684 | 10C5D X50FT | 3658-0008 | 1 | 1/2 | .92 | 1250 | 5000 | 2.0 |
| 70544 | 10C5DXREEL | 3658-0028 | 275 | 1/2 | .92 | 1250 | 5000 | 2.0 |
| 85685 | 12C5D X50FT | 3658-0009 | 1 | 5/8 | 1.08 | 750 | 3000 | 2.3 |
| 70545 | 12C5DXREEL | 3658-0029 | 220 | 5/8 | 1.08 | 750 | 3000 | 2.3 |
| 85686 | 16C5D X50FT | 3658-0010 | 1 | 7/8 | 1.23 | 400 | 1600 | 3.5 |
| 70546 | 16C5DXREEL | 3658-0030 | 165 | 7/8 | 1.23 | 400 | 1600 | 3.5 |

NOTE: Federal law requires registration with the Department of Transportation for anyone producing air brake hose assemblies with swaged or crimped fittings. See Engineering and Technical Data Section for compliance.

## C5M MARINE FUEL LINE HOSE

### FLEET

| | |
|---|---|
| RECOMMENDED FOR | All commercial and recreational vessel fuel line applications. Suitable for marine diesel, gasoline, B100 Bio–Diesel, gasohol fuels and hot oil applications. |
| TUBE | Nitrile. See Hose Stock Characteristics. |
| REINFORCEMENT | One wire braid. |
| COVER | Nitrile and PVC. Blue. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –4°F to +212°F (–20°C to +100°C) continuous service. |
| COUPLING RECOMMENDATION | Brass or Carbon C5 Field Attachable Couplings (G34) Section K<br>C5X Field Attachable Couplings (–5, –8, and –12) (G34) Section K<br>GlobalSpiral™ Couplings (–10 and –12) (G20) Section E<br>MegaCrimp® Couplings (–5, –6, –8 and –16) (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70614 | 5C5MXREEL | 3658-1965 | 385 | 1/4 | .58 | 500 | 2000 | 1.3 |
| 86596 | 6C5M X50FT | 3658-4596 | 1 | 5/16 | .67 | 500 | 2000 | 1.3 |
| 70615 | 6C5MXREEL | 3658-1969 | 385 | 5/16 | .67 | 500 | 2000 | 1.3 |
| 86597 | 8C5M X50FT | 3658-4597 | 1 | 13/32 | .77 | 500 | 2000 | 1.8 |
| 70616 | 8C5MXREEL | 3658-1973 | 330 | 13/32 | .77 | 500 | 2000 | 1.8 |
| 86598 | 10C5M X50FT | 3658-4598 | 1 | 1/2 | .92 | 500 | 2000 | 2.3 |
| 70617 | 10C5MXREEL | 3658-1977 | 275 | 1/2 | .92 | 500 | 2000 | 2.3 |
| 86599 | 12C5M X50FT | 3658-4599 | 1 | 5/8 | 1.08 | 500 | 2000 | 2.8 |
| 70618 | 12C5MXREEL | 3658-1981 | 220 | 5/8 | 1.08 | 500 | 2000 | 2.8 |
| 86600 | 16C5M X50FT | 3658-4600 | 1 | 7/8 | 1.23 | 500 | 2000 | 3.5 |
| 70619 | 16C5MXREEL | 3658-1985 | 165 | 7/8 | 1.23 | 500 | 2000 | 3.5 |

## C5E HIGH-TEMP FLEXLINE HOSE

### FLEET

| | |
|---|---|
| RECOMMENDED FOR | Air brake hose, power steering (CAUTION: Intended for heavy–duty commercial vehicle use only), engine and transmission coolant lines, and hot (+300°F) lube oil lines. Not recommended for gasoline or diesel fuel. |
| TUBE | Black, oil and heat–resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | One braid of high–tensile steel wire over one braid of polyester. |
| COVER | Black, oil and heat resistant, textile braid impregnated with synthetic rubber. |
| TEMPERATURE RANGE | –40°F to +300°F (–40°C to +149°C). Air +250°F (+121°C) maximum only. For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | C5E Field Attachable Couplings (G35) Section K<br>(See Crimp Data Manual 428–7365 or eCrimp) |




DOT FMVSS 106 Type A1 and SAE J1402 Type A1 (–4 to –12).

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85690 | 4C5E X50FT | 3658-4990 | 1 | 3/16 | .49 | 1500 | 6000 | .80 |
| 70530 | 4C5EXREEL | 3658-0210 | 440 | 3/16 | .49 | 1500 | 6000 | .80 |
| 85691 | 5C5E X50FT | 3658-4991 | 1 | 1/4 | .55 | 1500 | 6000 | 1.0 |
| 70531 | 5C5EXREEL | 3658-0211 | 385 | 1/4 | .55 | 1500 | 6000 | 1.0 |

NOTE: Federal law requires registration with the Department of Transportation for anyone producing air brake hose assemblies with swaged or crimped fittings. See Engineering and Technical Data Section for compliance.

## C5E HIGH-TEMP FLEXLINE HOSE - CONTINUED

### FLEET - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85692 | 6C5E X50FT | 3658-4992 | 1 | 5/16 | .61 | 1500 | 6000 | 1.3 |
| 70532 | 6C5EXREEL | 3658-0212 | 385 | 5/16 | .61 | 1500 | 6000 | 1.3 |
| 85693 | 8C5E X50FT | 3658-4993 | 1 | 13/32 | .73 | 1250 | 5000 | 1.8 |
| 70193 | 8C5EXCTN | 3658-0203 | 475 | 13/32 | .73 | 1250 | 5000 | 1.8 |
| 70533 | 8C5EXREEL | 3658-0213 | 330 | 13/32 | .73 | 1250 | 5000 | 1.8 |
| 85694 | 10C5E X50FT | 3658-4994 | 1 | 1/2 | .83 | 1250 | 5000 | 2.3 |
| 70194 | 10C5EXCTN | 3658-0204 | 330 | 1/2 | .83 | 1250 | 5000 | 2.3 |
| 70534 | 10C5EXREEL | 3658-0214 | 275 | 1/2 | .83 | 1250 | 5000 | 2.3 |
| 85695 | 12C5E X50FT | 3658-4995 | 1 | 5/8 | .95 | 750 | 3000 | 3.0 |
| 70195 | 12C5EXCTN | 3658-0205 | 200 | 5/8 | .95 | 750 | 3000 | 3.0 |
| 70535 | 12C5EXREEL | 3658-0215 | 220 | 5/8 | .95 | 750 | 3000 | 3.0 |
| 85696 | 16C5E X50FT | 3658-4996 | 1 | 7/8 | 1.20 | 400 | 1600 | 3.5 |
| 70536 | 16C5EXREEL | 3658-0216 | 165 | 7/8 | 1.20 | 400 | 1600 | 3.5 |
| 85697 | 20C5E X25FT | 3658-4989 | 1 | 1 1/8 | 1.49 | 300 | 1200 | 4.5 |
| 70197 | 20C5EXCTN | 3658-0207 | 100 | 1 1/8 | 1.49 | 300 | 1200 | 4.5 |

NOTE: Federal law requires registration with the Department of Transportation for anyone producing air brake hose assemblies with swaged or crimped fittings. See Engineering and Technical Data Section for compliance.

## C14 PTFE HOSE - SAE 100R14 TYPE A - NONCONDUCTIVE

### FLEET

| | |
|---|---|
| RECOMMENDED FOR | Air compressor discharge, hot oil and fluids, hot and greasy environments. |
| TUBE | Type A–Nonconductive white, smooth bore Polytetrafluoroethylene (PTFE). See Hose Stock Characteristics. |
| COVER/REINFORCEMENT | One braid of 300 Series stainless steel wire. 304 Stainless. |
| TEMPERATURE RANGE | Dynamic: –65°F to +400°F (–54°C to +204°C). Static: –65°F to +450°F (–54°C to +232°C). |
| COUPLING RECOMMENDATION | Brass and Stainless Steel available.<br>C14 Couplings (G40) Section L<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | | 72ºF (22ºC) | 72ºF (22ºC) | 450ºF (232ºC) | 450ºF (232ºC) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 85700 | 4C14 X25FT | 7752-0425 | 1 | 3/16 | .31 | 1500 | 6000 | 2.0 | 3000 | 12000 | 1500 | 6000 |
| 70804 | 4C14XCTN | 7752-0400 | 400 | 3/16 | .31 | 1500 | 6000 | 2.0 | 3000 | 12000 | 1500 | 6000 |
| 85701 | 5C14 X25FT | 7752-0525 | 1 | 1/4 | .38 | 1500 | 6000 | 3.0 | 3000 | 12000 | 1500 | 6000 |
| 70805 | 5C14XCTN | 7752-0500 | 350 | 1/4 | .38 | 1500 | 6000 | 3.0 | 3000 | 12000 | 1500 | 6000 |
| 85702 | 6C14 X25FT | 7752-0625 | 1 | 5/16 | .45 | 1500 | 6000 | 4.0 | 2500 | 10000 | 1500 | 6000 |
| 70806 | 6C14XCTN | 7752-0600 | 300 | 5/16 | .45 | 1500 | 6000 | 4.0 | 2500 | 10000 | 1500 | 6000 |
| 85703 | 8C14 X25FT | 7752-0825 | 1 | 13/32 | .55 | 1000 | 4000 | 5.3 | 2000 | 8000 | 1000 | 4000 |
| 70808 | 8C14XCTN | 7752-0800 | 250 | 13/32 | .55 | 1000 | 4000 | 5.3 | 2000 | 8000 | 1000 | 4000 |
| 85704 | 10C14 X25FT | 7752-1025 | 1 | 1/2 | .65 | 800 | 3200 | 6.5 | 1500 | 6000 | 800 | 3200 |
| 70810 | 10C14XCTN | 7752-1000 | 200 | 1/2 | .65 | 800 | 3200 | 6.5 | 1500 | 6000 | 800 | 3200 |
| 85705 | 12C14 X25FT | 7752-1225 | 1 | 5/8 | .79 | 800 | 3200 | 7.8 | 1200 | 4800 | 800 | 2600 |
| 70812 | 12C14XCTN | 7752-1200 | 150 | 5/8 | .79 | 800 | 3200 | 7.8 | 1200 | 4800 | 800 | 2600 |
| 85706 | 16C14 X25FT | 7752-1625 | 1 | 7/8 | 1.03 | 800 | 3500 | 9.0 | 1000 | 4000 | 800 | 2200 |

NOTE: Electrostatic Discharge: Many applications involving PTFE hose do not require a conductive tube. But you must review the potential for electrostatic discharge for every application and be aware that static electricity can be hazardous. In those cases where electrostatic discharge can occur, conductive PTFE hose with a conductive tube (Gates C14CT) is recommended. For more information on electrostatic discharge, refer to Technical Data Section.

## C14 PTFE HOSE - SAE 100R14 TYPE A - NONCONDUCTIVE - CONTINUED

### FLEET - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | | 72ºF (22ºC) | 72ºF (22ºC) | 450ºF (232ºC) | 450ºF (232ºC) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 70816 | 16C14XCTN | 7752-1600 | 100 | 7/8 | 1.03 | 800 | 3500 | 9.0 | 1000 | 4000 | 800 | 2200 |

NOTE: Electrostatic Discharge: Many applications involving PTFE hose do not require a conductive tube. But you must review the potential for electrostatic discharge for every application and be aware that static electricity can be hazardous. In those cases where electrostatic discharge can occur, conductive PTFE hose with a conductive tube (Gates C14CT) is recommended. For more information on electrostatic discharge, refer to Technical Data Section.

## C14CT PTFE HOSE - SAE 100R14 TYPE B - CONDUCTIVE

### FLEET

| | |
|---|---|
| RECOMMENDED FOR | Air compressor discharge, hot oil and fluids, hot and greasy environments. |
| TUBE | Type B–Conductive black/white smooth bore Polytetrafluoroethylene (PTFE). See Hose Stock Characteristics. |
| COVER/REINFORCEMENT | One braid of 300 Series stainless steel wire. 304 Stainless. |
| TEMPERATURE RANGE | Dynamic: –65°F to +400°F (–54°C to +204°C). Static: –65°F to +450°F (–54°C to +232°C). |
| COUPLING RECOMMENDATION | Brass and Stainless Steel available.<br>C14 Couplings (G40) Section L<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | | 72ºF (22ºC) | 72ºF (22ºC) | 450ºF (232ºC) | 450ºF (232ºC) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 85730 | 6C14CT X25FT | 7752-3625 | 1 | 5/16 | .45 | 1500 | 6000 | 4.0 | 2500 | 10000 | 1500 | 6000 |
| 70906 | 6C14CTXCTN* | 7752-3600 | 300 | 5/16 | .45 | 1500 | 6000 | 4.0 | 2500 | 10000 | 1500 | 6000 |
| 85731 | 8C14CT X25FT | 7752-3825 | 1 | 13/32 | .55 | 1000 | 4000 | 5.3 | 2000 | 8000 | 1000 | 4000 |
| 70908 | 8C14CTXCTN* | 7752-3800 | 250 | 13/32 | .55 | 1000 | 4000 | 5.3 | 2000 | 8000 | 1000 | 4000 |

**Type B–Conductive Tube.*

NOTE: Electrostatic Discharge: Many applications involving PTFE hose do not require a conductive tube. But you must review the potential for electrostatic discharge for every application and be aware that static electricity can be hazardous. In those cases where electrostatic discharge can occur, conductive PTFE hose with a conductive tube (Gates C14CT) is recommended. For more information on electrostatic discharge, refer to Technical Data Section.

# POLARSEAL® HOSE

## FLEET

| | |
|---|---|
| RECOMMENDED FOR | Liquid and gaseous R134a and R12 refrigerants in automotive air conditioning and industrial systems; i.e., tractors construction trucks, mobile and stationary refrigeration units. Designed to minimize permeation of R134a refrigerant. Air conditioning refrigerant hose is manufactured in accordance with SAE J3062, while air conditioning hose assemblies must meet SAE J2064. |
| TUBE | Black, synthetic rubber (Polychloroprene). See Hose Stock Characteristics. |
| REINFORCEMENT | Two layers of spiral polyester. |
| COVER | Black synthetic rubber (EPDM). See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –22°F to +257°F (–30°C to +125°C). |
| BARRIER | Nylon liner. |
| COUPLING RECOMMENDATION | PolarSeal® Couplings (ACA) (G45) Section P<br>(See Crimp Data Manual 428–7365 or eCrimp) |




PolarSeal® (ACA) full dimension barrier hose. SAE J51, Type A2 Dimensions; SAE J51, Type D Performance; SAE J3062, Type C, Class II Performance.

| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 85664 | 6AC134A X25FT | 3353-0901 | 1 | 5/16 | .75 | 500 | 2000 | 2.0 | 24 |
| 70624 | 6AC134AXREEL | 3353-0903 | 340 | 5/16 | .75 | 500 | 2000 | 2.0 | 24 |
| 85665 | 8AC134A X25FT | 3353-0906 | 1 | 13/32 | .91 | 500 | 2000 | 3.0 | 24 |
| 70625 | 8AC134AXREEL | 3353-0908 | 235 | 13/32 | .91 | 500 | 2000 | 3.0 | 24 |
| 85666 | 10AC134A X25FT | 3353-0911 | 1 | 1/2 | 1.00 | 500 | 2000 | 4.0 | 24 |
| 70626 | 10AC134AXREEL | 3353-0913 | 210 | 1/2 | 1.00 | 500 | 2000 | 4.0 | 24 |
| 85667 | 12AC134A X25FT | 3353-0916 | 1 | 5/8 | 1.13 | 500 | 2000 | 5.0 | 24 |
| 70627 | 12AC134AXREEL | 3353-0918 | 175 | 5/8 | 1.13 | 500 | 2000 | 5.0 | 24 |

# POLARSEAL® II HOSE

## FLEET

| | |
|---|---|
| RECOMMENDED FOR | Most refrigerants blends and compressor lubricants in automotive and heavy–duty truck air conditioning systems where significant reduction in permeation and moisture ingression is desired. Low–permeation hose construction is used by more OEMs around the globe than any other refrigerant hose construction. Gates PolarSeal® II (ACC) derives its performance from a proprietary polyamide barrier and exceptional compounding. Compatible with R134a, R12 and the new R1234yf refrigerant. Air conditioning refrigerant hose is manufactured in accordance with SAE J3062, while air conditioning hose assemblies both hose and coupling meet SAE J2064. Change to SAE specification effective as of August 2015. |
| TUBE | Black, synthetic Elastomeric rubber. |
| REINFORCEMENT | Single–braid polyester. |
| COVER | Heat, moisture and ozone resistant black synthetic Elastomeric cover. |
| TEMPERATURE RANGE | –22°F to +257°F (–30°C to +125°C). |
| BARRIER | Nylon liner. |
| COUPLING RECOMMENDATION | PolarSeal® II Couplings (ACB) (G47) Section R<br>PolarSeal® II Couplings (ACC) (G46) Couplings with band clamp. Section Q<br>(See Crimp Data Manual 428–7365 or eCrimp) |




PolarSeal® II (ACC) reduced dimension barrier hose. SAE J3062, Type C, Class I Performance.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85384 | 6ACC-PSII X50FT | 3353-5007 | 1 | 5/16 | .62 | 350 | 1400 | 1.5 |

## POLARSEAL® II HOSE - CONTINUED

### FLEET - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 71090 | 6ACC-PSIIXREEL | 3353-5006 | 500 | 5/16 | .62 | 350 | 1400 | 1.5 |
| 85385 | 8ACC-PSII X50FT | 3353-5009 | 1 | 13/32 | .74 | 350 | 1400 | 2.0 |
| 71091 | 8ACC-PSIIXREEL | 3353-5008 | 500 | 13/32 | .74 | 350 | 1400 | 2.0 |
| 85386 | 10ACC-PSII X50FT | 3353-5011 | 1 | 1/2 | .83 | 350 | 1400 | 2.5 |
| 71092 | 10ACC-PSIIXREEL | 3353-5010 | 300 | 1/2 | .83 | 350 | 1400 | 2.5 |
| 85387 | 12ACC-PSII X50FT | 3353-5013 | 1 | 5/8 | .96 | 350 | 1400 | 3.0 |
| 71093 | 12ACC-PSIIXREEL | 3353-5012 | 250 | 5/8 | .96 | 350 | 1400 | 3.0 |

## PS188 POWER STEERING HOSE

### FLEET

| | |
|---|---|
| RECOMMENDED FOR | Power steering pressure lines. Designed to meet requirements of SAE J2050 specifications. |
| TUBE | Synthetic rubber specially compounded to provide resistance to high temperatures and power steering fluid (CSM). See Hose Stock Characteristics. |
| REINFORCEMENT | Two high strength nylon braids that resist high temperatures and allow for expansion for system noise dampening. |
| COVER | Black, synthetic rubber developed specifically to resist under hood environment (CSM). |
| TEMPERATURE RANGE | –40°F to +300°F (–40°C to +150°C). |
| COUPLING RECOMMENDATION | Permanent Power Steering Couplings (G50) Section S (See Crimp Data Manual 428–7365 or eCrimp) |




Designed to meet requirements of SAE J2050 specifications.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 86049 | 6PS188 X25FT | 3317-0107 | 1 | 3/8 | .71 | 1500 | 6000 | 3.25 |
| 86050 | 6PS188 X50FT | 3317-0108 | 1 | 3/8 | .71 | 1500 | 6000 | 3.25 |

## J2AT 2-WIRE BRAID JACK HOSE - 10,000 STATIC PRESSURE ONLY

### SPECIALTY

| | |
|---|---|
| RECOMMENDED FOR | Hydraulic jack applications. Meets Material Handling Institute specification IJ 100 for hydraulic hose and assemblies used with jacking systems. 10,000 Static Pressure Only. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil and abrasion resistant, synthetic rubber (Nitrile and PVC). Also available with unique abrasion resistant MegaTuff® cover. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +120°F (–40°C to +49°C). |
| COUPLING RECOMMENDATION | Use MegaCrimp® Male Pipe Long Nose Couplings on jack end of assembly for engagement. Section G (See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85650 | 4J2AT X50FT | 4657-4880 | 1 | 1/4 | .59 | 10000 | 20000 | 2.0 |
| 70800 | 4J2ATXREEL | 4657-1400 | 350 | 1/4 | .59 | 10000 | 20000 | 2.0 |
| 85651 | 6J2AT X50FT | 4657-4881 | 1 | 3/8 | .74 | 10000 | 20000 | 2.5 |
| 70801 | 6J2ATXREEL | 4657-1404 | 330 | 3/8 | .74 | 10000 | 20000 | 2.5 |

## J2AT 2-WIRE BRAID JACK HOSE - MEGATUFF® COVER - 10,000 STATIC PRESSURE ONLY

### SPECIALTY

| | |
|---|---|
| RECOMMENDED FOR | Ultra high abrasive hydraulic jack applications. Meets Material Handling Institute specification IJ 100 for hydraulic hose and assemblies used with jacking systems. 10,000 Static Pressure. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil and abrasion resistant, synthetic rubber and MegaTuff® cover. Also available in Standard cover. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +120°F (–40°C to +49°C). |
| COUPLING RECOMMENDATION | Use MegaCrimp® Male Pipe Long Nose Couplings on jack end of assembly for engagement. Section G (See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G". MegaTuff® hose lasts up to 300 times longer than standard hose during hose–to–hose and hose–to–metal abrasion tests per ISO 6945.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70469 | 4J2AT-MTFXREEL | 4657-1188 | 350 | 1/4 | .59 | 10000 | 20000 | 2.0 |
| 70471 | 6J2AT-MTFXREEL | 4657-1189 | 330 | 3/8 | .74 | 10000 | 20000 | 2.5 |

## HOT OILER 2-WIRE BRAID HOSE

### SPECIALTY

| | |
|---|---|
| RECOMMENDED FOR | Static pressure, hot oiler applications. Designed specifically to handle the transfer of hot oil at +275°F continuous, +300°F intermittent to clear the paraffin around the casing to help start the flow of oil to the surface. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil and abrasion resistant, synthetic rubber (CSM). See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +300°F (–40°C to +149°C). |
| COUPLING RECOMMENDATION | Field Attachable Type T Couplings (G28) Section J<br>GlobalSpiral™ Plus Couplings (G22) Section E<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 80040 | 24HOX75 | 4657-4674 | 1 | 1 1/2 | 2.15 | 2300 | 6900 | 20.0 |

## HOT OILER 2-WIRE BRAID HOSE - MEGATUFF® COVER

### SPECIALTY

| | |
|---|---|
| RECOMMENDED FOR | Static pressure, hot oiler applications. Designed specifically to handle the transfer of hot oil at +275°F continuous, +300°F intermittent to clear the paraffin around the casing to help start the flow of oil to the surface. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | Two braids of high–tensile steel wire. |
| COVER | Black, oil, abrasion and weather resistant MegaTuff® cover. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +300°F (–40°C to +149°C). |
| COUPLING RECOMMENDATION | Field Attachable Type T Couplings (G28) Section J<br>GlobalSpiral™ Plus Couplings (G22) Section E<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 70015 | 24HO-MTFXCTN | 4657-4463 | 120 | 1 1/2 | 2.15 | 2300 | 6900 | 20.0 |

## RFS RED FIRE SUPPRESSANT HOSE

### SPECIALTY

| | |
|---|---|
| RECOMMENDED FOR | Low–pressure powder fire suppressant applications in mining, forestry and firefighting equipment. The red cover is for easy visual identification in these applications. Meets performance requirements of SAE 100R1. |
| TUBE | Black, oil resistant, synthetic rubber (Nitrile). See Hose Stock Characteristics. |
| REINFORCEMENT | One braid of high–tensile steel wire. |
| COVER | Red, oil and abrasion resistant (Nitrile and PVC). |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G<br>Power Crimp® Couplings (–3) Section I<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| H24100-03F | 3RFSXREEL | 4657-2145 | 440 | 3/16 | .45 | 3000 | 12000 | 3.0 |
| H24100-04F | 4RFSXREEL | 4657-3314 | 440 | 1/4 | .53 | 2750 | 11000 | 4.0 |
| H24100-06F | 6RFSXREEL | 4657-3313 | 300 | 3/8 | .68 | 2250 | 9000 | 5.0 |
| H24100-08F | 8RFSXREEL | 4657-3315 | 330 | 1/2 | .80 | 2000 | 8000 | 7.0 |
| H24100-12F | 12RFSXREEL | 4657-3316 | 300 | 3/4 | 1.09 | 1250 | 5000 | 9.5 |
| H24100-16F | 16RFSXREEL | 4657-2155 | 165 | 1 | 1.41 | 1000 | 4000 | 12.0 |

## PLANT MASTER® 150-200

### INDUSTRIAL HOSE

| | |
|---|---|
| RECOMMENDED FOR | Air and water applications requiring maximum flexibility in any industry, including mining, construction, agriculture, vehicle repair and in–plant operations. Outstanding resistance to heat and ozone. Suitable for light agricultural spraying, such as dilute solutions of herbicides. |
| TUBE | Type P (EPDM). Black. |
| REINFORCEMENT | Synthetic, high tensile textile cord. |
| COVER | Type P (EPDM). All sizes through 1/2" are perforated. |
| TEMPERATURE RANGE | –40°F to +200°F (–40°C to +93°C) continuous service. |
| COUPLING RECOMMENDATION | GLX® Couplings (G44) Section N<br>Power Crimp® Couplings Section I<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 1/2X UPS RL 200 ADAPTA BLK | 3204-1414 | 250 | 1/2 | .81 | 200 | 600 | 5.0 | 25.0 |
| | 1/2X250FT PLANT MASTER 200 RED UPS SHIPPABLE | 3204-1377 | 250 | 1/2 | .81 | 200 | 600 | 5.0 | 25.0 |
| | 1/2X500FT CL PLANT MASTER 200 BLACK | 3204-4413 | 500 | 1/2 | .81 | 200 | 600 | 5.0 | 25.0 |
| | 1/2X500FT CL PLANT MASTER 200 RED | 3204-5328 | 500 | 1/2 | .81 | 200 | 600 | 5.0 | 25.0 |
| | 1/2X500FT PLANT MASTER 200 BLACK | 3204-1413 | 500 | 1/2 | .81 | 200 | 600 | 5.0 | 25.0 |
| | 1/2X500FT PLANT MASTER 200 RED | 3204-1328 | 500 | 1/2 | .81 | 200 | 600 | 5.0 | 25.0 |
| | 1/4X500FT CL PLANT MASTER 200 BLACK | 3204-4402 | 500 | 1/4 | .50 | 200 | 600 | 3.0 | 30.0 |

## PLANT MASTER® 150-200 - CONTINUED

### INDUSTRIAL HOSE - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 1/4X500FT CL PLANT MASTER 200 RED | 3204-5301 | 500 | 1/4 | .50 | 200 | 600 | 3.0 | 30.0 |
| | 1/4X500FT PLANT MASTER 200 BLACK | 3204-1401 | 500 | 1/4 | .50 | 200 | 600 | 3.0 | 30.0 |
| | 1/4X500FT PLANT MASTER 200 RED | 3204-1301 | 500 | 1/4 | .50 | 200 | 600 | 3.0 | 30.0 |
| | 1/4X500FT PLANT MASTER 200 RED UPS SHIPPABLE | 3204-1373 | 500 | 1/4 | .50 | 200 | 600 | 3.0 | 30.0 |
| | 1X UPS RL 200 ADAPTA BLK | 3204-1432 | 125 | 1 | 1.40 | 200 | 600 | 8.0 | 10.0 |
| | 1X125FT PLANT MASTER 200 RED UPS SHIPPABLE | 3204-1383 | 125 | 1 | 1.40 | 200 | 600 | 8.0 | 10.0 |
| | 1X400FT PLANT MASTER 150 BLACK | 3204-1428 | 400 | 1 | 1.40 | 150 | 450 | 8.0 | 10.0 |
| | 1X400FT PLANT MASTER 150 RED | 3204-1358 | 400 | 1 | 1.39 | 150 | 450 | 8.0 | 10.0 |
| | 1X400FT PLANT MASTER 200 BLACK | 3204-1431 | 400 | 1 | 1.40 | 200 | 600 | 8.0 | 10.0 |
| | 1X400FT PLANT MASTER 200 RED | 3204-1361 | 400 | 1 | 1.39 | 200 | 600 | 8.0 | 10.0 |
| | 3/4X200FT PLANT MASTER 200 RED UPS SHIPPABLE | 3204-1381 | 200 | 3/4 | 1.11 | 200 | 600 | 6.0 | 15.0 |
| | 3/4X500FT CL PLANT MASTER 200 BLACK | 3204-4422 | 500 | 3/4 | 1.11 | 200 | 600 | 6.0 | 15.0 |
| | 3/4X500FT CL PLANT MASTER 200 RED | 3204-5346 | 500 | 3/4 | 1.11 | 200 | 600 | 6.0 | 15.0 |
| | 3/4X500FT PLANT MASTER 200 BLACK | 3204-1422 | 500 | 3/4 | 1.11 | 200 | 600 | 6.0 | 15.0 |
| | 3/4X500FT PLANT MASTER 200 RED | 3204-1346 | 500 | 3/4 | 1.11 | 200 | 600 | 6.0 | 15.0 |
| | 3/8X UPS RL 200 ADAPTA BLK | 3204-1408 | 500 | 3/8 | .66 | 200 | 600 | 3.0 | 30.0 |
| | 3/8X400FT PLANT MASTER 200 RED UPS SHIPPABLE | 3204-1375 | 400 | 3/8 | .66 | 200 | 600 | 3.0 | 30.0 |
| | 3/8X500FT CL PLANT MASTER 200 BLACK | 3204-4407 | 500 | 3/8 | .66 | 200 | 600 | 3.0 | 30.0 |
| | 3/8X500FT CL PLANT MASTER 200 RED | 3204-5319 | 500 | 3/8 | .66 | 200 | 600 | 3.0 | 30.0 |
| | 3/8X500FT PLANT MASTER 200 BLACK | 3204-1407 | 500 | 3/8 | .66 | 200 | 600 | 3.0 | 30.0 |
| | 3/8X500FT PLANT MASTER 200 RED | 3204-1319 | 500 | 3/8 | .66 | 200 | 600 | 3.0 | 30.0 |
| | 5/8X250FT PLANT MASTER 200 RED UPS SHIPPABLE | 3204-1379 | 250 | 5/8 | .97 | 200 | 600 | 6.0 | 20.0 |
| | 5/8X500FT CL PLANT MASTER 200 RED | 3204-5337 | 500 | 5/8 | .97 | 200 | 600 | 6.0 | 20.0 |
| | 5/8X500FT PLANT MASTER 200 BLACK | 3204-1419 | 500 | 5/8 | .97 | 200 | 600 | 6.0 | 20.0 |
| | 5/8X500FT PLANT MASTER 200 RED | 3204-1337 | 500 | 5/8 | .97 | 200 | 600 | 6.0 | 20.0 |
| | 5/16X500FT PLANT MASTER 200 RED | 3204-1316 | 500 | 5/16 | .53 | 200 | 600 | 3.0 | 30.0 |

# PLANT MASTER® 250

## INDUSTRIAL HOSE

| | |
|---|---|
| RECOMMENDED FOR | Air and water applications requiring maximum flexibility in any industry, including mining, construction, agriculture, vehicle repair and in–plant operations. Outstanding resistance to heat and ozone. Suitable for light agricultural spraying, such as dilute solutions of herbicides. |
| TUBE | Type P (EPDM). Black. |
| REINFORCEMENT | Synthetic, high tensile textile cord. |
| COVER | Type P (EPDM). All sizes through 1/2" are perforated. |
| TEMPERATURE RANGE | –40°F to +200°F (–40°C to +93°C) continuous service. |
| COUPLING RECOMMENDATION | GLX® Couplings (G44) Section N<br>Power Crimp® Couplings Section I<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 1 1/2X200FT PLANT MASTER 250 BLACK | 3204-1437 | 200 | 1 1/2 | 1.98 | 250 | 750 | 12.0 | 10.0 |
| | 1 1/4X200FT PLANT MASTER 250 BLACK | 3204-1434 | 200 | 1 1/4 | 1.73 | 250 | 750 | 10.0 | 10.0 |
| | 1/2X500FT CL PLANT MASTER 250 BLACK | 3204-4432 | 500 | 1/2 | .81 | 250 | 750 | 5.0 | 25.0 |
| | 1/2X500FT CL PLANT MASTER 250 RED | 3204-5333 | 500 | 1/2 | .81 | 250 | 750 | 5.0 | 25.0 |
| | 1/2X500FT PLANT MASTER 250 BLACK | 3204-1416 | 500 | 1/2 | .81 | 250 | 750 | 5.0 | 25.0 |
| | 1/2X500FT PLANT MASTER 250 BLUE | 3204-1498 | 500 | 1/2 | .81 | 250 | 750 | 5.0 | 25.0 |
| | 1/2X500FT PLANT MASTER 250 RED | 3204-1331 | 500 | 1/2 | .81 | 250 | 750 | 5.0 | 25.0 |
| | 1/2X500FT PLANT MASTER 250 YELLOW | 3204-1528 | 500 | 1/2 | .81 | 250 | 750 | 5.0 | 25.0 |
| | 1/4X500FT CL PLANT MASTER 250 RED | 3204-5304 | 500 | 1/4 | .50 | 250 | 750 | 3.0 | 30.0 |
| | 1/4X500FT PLANT MASTER 250 RED | 3204-1304 | 500 | 1/4 | .50 | 250 | 750 | 3.0 | 30.0 |
| | 3/4X50FT PLANT MASTER 250 BLACK | 3204-5820 | 200 | 3/4 | 1.15 | 250 | 750 | 6.0 | 20.0 |
| | 3/4X50FT PLANT MASTER 250 RED | 3204-5420 | 200 | 3/4 | 1.15 | 250 | 750 | 6.0 | 20.0 |
| | 3/4X500FT CL PLANT MASTER 250 BLACK | 3204-4433 | 500 | 3/4 | 1.15 | 250 | 750 | 6.0 | 20.0 |
| | 3/4X500FT CL PLANT MASTER 250 RED | 3204-5349 | 500 | 3/4 | 1.11 | 250 | 750 | 6.0 | 20.0 |
| | 3/4X500FT PLANT MASTER 250 BLACK | 3204-1425 | 500 | 3/4 | 1.15 | 250 | 750 | 6.0 | 20.0 |
| | 3/4X500FT PLANT MASTER 250 BLUE | 3204-1500 | 500 | 3/4 | 1.15 | 250 | 750 | 6.0 | 20.0 |
| | 3/4X500FT PLANT MASTER 250 RED | 3204-1349 | 500 | 3/4 | 1.11 | 250 | 750 | 6.0 | 20.0 |
| | 3/8X500FT CL PLANT MASTER 250 BLACK | 3204-4431 | 500 | 3/8 | .66 | 250 | 750 | 3.0 | 30.0 |
| | 3/8X500FT CL PLANT MASTER 250 RED | 3204-5321 | 500 | 3/8 | .66 | 250 | 750 | 3.0 | 30.0 |
| | 3/8X500FT PLANT MASTER 250 BLACK | 3204-1410 | 500 | 3/8 | .66 | 250 | 750 | 3.0 | 30.0 |
| | 3/8X500FT PLANT MASTER 250 BLUE | 3204-1497 | 500 | 3/8 | .66 | 250 | 750 | 3.0 | 30.0 |
| | 3/8X500FT PLANT MASTER 250 RED | 3204-1322 | 500 | 3/8 | .66 | 250 | 750 | 3.0 | 30.0 |
| | 5/8X500FT CL PLANT MASTER 250 RED | 3204-5341 | 500 | 5/8 | .97 | 250 | 750 | 6.0 | 20.0 |
| | 5/8X500FT PLANT MASTER 250 RED | 3204-1340 | 500 | 5/8 | .97 | 250 | 750 | 6.0 | 20.0 |

# PLANT MASTER® 300

## INDUSTRIAL HOSE

| | |
|---|---|
| RECOMMENDED FOR | Air and water applications requiring maximum flexibility in any industry, including mining, construction, agriculture, vehicle repair and in–plant operations. Outstanding resistance to heat and ozone. Suitable for light agricultural spraying, such as dilute solutions of herbicides. |
| TUBE | Type P (EPDM). Black. |
| REINFORCEMENT | Synthetic, high tensile textile cord. |
| COVER | Type P (EPDM). All sizes through 1/2" are perforated. |
| TEMPERATURE RANGE | –40°F to +200°F (–40°C to +93°C) continuous service. |
| COUPLING RECOMMENDATION | GLX® Couplings (G44) Section N<br>Power Crimp® Couplings Section I<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 1/2X500FT CL PLANT MASTER 300 RED | 3204-5334 | 500 | 1/2 | .83 | 300 | 900 | 5.0 | 25.0 |
| | 1/2X500FT PLANT MASTER 300 RED | 3204-1334 | 500 | 1/2 | .83 | 300 | 900 | 5.0 | 25.0 |
| | 1/4X500FT CL PLANT MASTER 300 RED | 3204-5307 | 500 | 1/4 | .53 | 300 | 900 | 3.0 | 30.0 |
| | 1/4X500FT PLANT MASTER 300 RED | 3204-1307 | 500 | 1/4 | .53 | 300 | 900 | 3.0 | 30.0 |
| | 1X400FT CL PLANT MASTER 300 RED | 3204-0901 | 400 | 1 | 1.47 | 300 | 900 | 8.0 | 10.0 |
| | 1X400FT PLANT MASTER 300 RED | 3204-1364 | 400 | 1 | 1.47 | 300 | 900 | 8.0 | 10.0 |
| | 1X500FT PLANT MASTER 300 RED | 3204-1650 | 500 | 1 | 1.47 | 300 | 900 | 8.0 | 10.0 |
| | 3/4X50FT PLANT MASTER 300 BLUE | 3204-0560 | 200 | 3/4 | 1.15 | 300 | 900 | 6.0 | 15.0 |
| | 3/4X50FT PLANT MASTER 300 GREEN | 3204-0506 | 200 | 3/4 | 1.15 | 300 | 900 | 6.0 | 15.0 |
| | 3/4X50FT PLANT MASTER 300 RED | 3204-5675 | 200 | 3/4 | 1.15 | 300 | 900 | 6.0 | 15.0 |
| | 3/4X50FT PLANT MASTER 300 YELLOW | 3204-0558 | 200 | 3/4 | 1.15 | 300 | 900 | 6.0 | 15.0 |
| | 3/4X500FT CL PLANT MASTER 300 RED | 3204-5355 | 500 | 3/4 | 1.15 | 300 | 900 | 6.0 | 15.0 |
| | 3/4X500FT PLANT MASTER 300 BLUE | 3204-1505 | 500 | 3/4 | 1.15 | 300 | 900 | 6.0 | 15.0 |
| | 3/4X500FT PLANT MASTER 300 GREEN | 3204-1515 | 500 | 3/4 | 1.15 | 300 | 900 | 6.0 | 15.0 |
| | 3/4X500FT PLANT MASTER 300 RED | 3204-1355 | 500 | 3/4 | 1.15 | 300 | 900 | 6.0 | 15.0 |
| | 3/4X500FT PLANT MASTER 300 YELLOW | 3204-1525 | 500 | 3/4 | 1.15 | 300 | 900 | 6.0 | 15.0 |
| | 3/8X500FT CL PLANT MASTER 300 RED | 3204-5326 | 500 | 3/8 | .67 | 300 | 900 | 3.0 | 30.0 |
| | 3/8X500FT PLANT MASTER 300 RED | 3204-1325 | 500 | 3/8 | .67 | 300 | 900 | 3.0 | 30.0 |

## PLANT MASTER® XTREME® 501 AR

### INDUSTRIAL HOSE

| | |
|---|---|
| RECOMMENDED FOR | Applications requiring a premium–quality, multi–purpose hose with superior abrasion resistance for air, oil and some chemical applications. Excellent durability for extra–long life in these applications: mining, air drill, construction, poultry plants and other severe service. Good weather and ozone resistance. |
| TUBE | Type C (Nitrile). Black. |
| REINFORCEMENT | Synthetic, high tensile textile cord. |
| COVER | Type C4 (Carboxylated Nitrile). Yellow. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C) continuous service. |
| COUPLING RECOMMENDATION | GLX® Couplings (G44) Section N<br>MegaCrimp® Couplings (G25) Section G<br>Power Crimp® Couplings Section I<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | ⊖ | ⟟ | | | R | ○ |
|---|---|---|---|---|---|---|---|---|---|
| | 1 1/2XRL100FT PLANT MASTER XTREME 501 AR | 3202-0029 | 100 | 1 1/2 | 2.09 | 501 | 2004 | 12.0 | 10.0 |
| | 1 1/4X300FT PLANT MASTER XTREME 501 AR | 3202-0027 | 300 | 1 1/4 | 1.78 | 501 | 2004 | 10.0 | 10.0 |
| | 1/2X500 RL | 3202-0311 | 500 | 1/2 | .89 | 501 | 2004 | 5.0 | 25.0 |
| | 1/2X500FT PLANT MASTER XTREME 501 AR | 3202-0011 | 500 | 1/2 | .89 | 501 | 2004 | 5.0 | 25.0 |
| | 1/4X500 RL | 3202-0301 | 500 | 1/4 | .57 | 501 | 2004 | 3.0 | 30.0 |
| | 1/4X500FT PLANT MASTER XTREME 501 AR | 3202-0001 | 500 | 1/4 | .57 | 501 | 2004 | 3.0 | 30.0 |
| | 1X400FT PLANT MASTER XTREME 501 AR | 3202-0021 | 400 | 1 | 1.51 | 501 | 2004 | 8.0 | 10.0 |
| | 2XRL 100FT PLANT MASTER XTREME 501 AR | 3202-0032 | 100 | 2 | 2.64 | 501 | 2004 | 14.0 | 10.0 |
| | 3/4X500 RL | 3202-0316 | 500 | 3/4 | 1.22 | 501 | 2004 | 6.0 | 15.0 |
| | 3/4X500FT PLANT MASTER XTREME 501 AR | 3202-0016 | 500 | 3/4 | 1.22 | 501 | 2004 | 6.0 | 15.0 |
| | 3/8X500 RL | 3202-0306 | 500 | 3/8 | .75 | 501 | 2004 | 3.0 | 25.0 |
| | 3/8X500FT PLANT MASTER XTREME 501 AR | 3202-0006 | 500 | 3/8 | .75 | 501 | 2004 | 3.0 | 25.0 |

## PLANT MASTER® PLUS

### INDUSTRIAL HOSE

| | |
|---|---|
| RECOMMENDED FOR | Applications requiring maximum flexibility and good resistance to air, water and heat. For SAE oils intermittent contact only. |
| TUBE | Type B1 (Specially compounded elastomer). Black. |
| REINFORCEMENT | Synthetic, high tensile textile cord. |
| COVER | Type D3 (Specially compounded elastomer). For 2" Black only.<br>Type P (EPDM). Red. All sizes through 1/2" have perforated cover. |
| TEMPERATURE RANGE | –40°F to +200°F (–40°C to +93°C) continuous service. |
| COUPLING RECOMMENDATION | GLX® Couplings (G44) Section N<br>Power Crimp® Couplings Section I<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | ⊖ | ⟟ | | | R | ○ |
|---|---|---|---|---|---|---|---|---|---|
| | 1 1/2X200FT PLANT MASTER PLUS 250 | 3200-0016 | 200 | 1 1/2 | 1.98 | 250 | 750 | 12.0 | 10.0 |

## PLANT MASTER® PLUS - CONTINUED

### INDUSTRIAL HOSE - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 1 1/4X200FT PLANT MASTER PLUS 250 | 3200-0015 | 200 | 1 1/4 | 1.73 | 250 | 750 | 10.0 | 10.0 |
| | 1/2X500FT CL PLANT MASTER PLUS 250 | 3200-0208 | 500 | 1/2 | .81 | 250 | 750 | 4.0 | 25.0 |
| | 1/2X500FT CL PLANT MASTER PLUS 300 | 3200-0209 | 500 | 1/2 | .84 | 300 | 900 | 4.0 | 25.0 |
| | 1/2X500FT PLANT MASTER PLUS 250 | 3200-0008 | 500 | 1/2 | .81 | 250 | 750 | 4.0 | 25.0 |
| | 1/2X500FT PLANT MASTER PLUS 300 | 3200-0009 | 500 | 1/2 | .84 | 300 | 900 | 4.0 | 25.0 |
| | 1/4X500FT CL PLANT MASTER PLUS 250 | 3200-0202 | 500 | 1/4 | .50 | 250 | 750 | 2.0 | 30.0 |
| | 1/4X500FT PLANT MASTER PLUS 250 | 3200-0002 | 500 | 1/4 | .50 | 250 | 750 | 2.0 | 30.0 |
| | 1/4X500FT PLANT MASTER PLUS 300 | 3200-0003 | 600 | 1/4 | .57 | 300 | 900 | 2.0 | 30.0 |
| | 1X400FT PLANT MASTER PLUS 250 | 3200-0014 | 400 | 1 | 1.47 | 250 | 750 | 8.0 | 10.0 |
| | 2X100FT PLANT MASTER PLUS 200 | 3206-3968 | 100 | 2 | 2.56 | 200 | 600 | 16.5 | 4.0 |
| | 2XCTN PLANT MASTER PLUS 200 | 3200-1279 | 100 | 2 | 2.56 | 200 | 600 | 16.5 | 4.0 |
| | 3/4X500FT CL PLANT MASTER PLUS 250 | 3200-0212 | 500 | 3/4 | 1.15 | 250 | 750 | 5.0 | 20.0 |
| | 3/4X500FT CL PLANT MASTER PLUS 300 | 3200-0213 | 500 | 3/4 | 1.15 | 300 | 900 | 5.0 | 20.0 |
| | 3/4X500FT PLANT MASTER PLUS 250 | 3200-0012 | 500 | 3/4 | 1.15 | 250 | 750 | 5.0 | 20.0 |
| | 3/4X500FT PLANT MASTER PLUS 300 | 3200-0013 | 500 | 3/4 | 1.15 | 300 | 900 | 5.0 | 20.0 |
| | 3/8X500FT CL PLANT MASTER PLUS 250 | 3200-0206 | 500 | 3/8 | .66 | 250 | 750 | 3.0 | 30.0 |
| | 3/8X500FT CL PLANT MASTER PLUS 300 | 3200-0207 | 500 | 3/8 | .73 | 300 | 900 | 3.0 | 30.0 |
| | 3/8X500FT PLANT MASTER PLUS 250 | 3200-0006 | 500 | 3/8 | .66 | 250 | 750 | 3.0 | 30.0 |
| | 3/8X500FT PLANT MASTER PLUS 300 | 3200-0007 | 500 | 3/8 | .73 | 300 | 900 | 3.0 | 30.0 |
| | 5/8X500FT CL PLANT MASTER PLUS 250 | 3200-0210 | 500 | 5/8 | .98 | 250 | 750 | 5.0 | 20.0 |
| | 5/8X500FT PLANT MASTER PLUS 300 | 3200-0011 | 500 | 5/8 | .98 | 300 | 900 | 5.0 | 20.0 |

# PLANT MASTER® XTREME®

## INDUSTRIAL HOSE

| | |
|---|---|
| RECOMMENDED FOR | Applications requiring a premium grade spiral hose with excellent flexibility and maximum resistance to air, water, petroleum oils and lubricating oils, (to +212°F). Recommended for gasoline, kerosene and fuel oil transfer only (to +120°F). Excellent weather and ozone resistance. |
| TUBE | Type C (Nitrile). Black. |
| REINFORCEMENT | Synthetic, high tensile textile cord. |
| COVER | Type C2 (Modified Nitrile). Red. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C) continuous service. |
| COUPLING RECOMMENDATION | GLX® Couplings (G44) Section N<br>Power Crimp® Couplings Section I<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | ⊖ | ⟷ | | | R | ◯ |
|---|---|---|---|---|---|---|---|---|---|
| | 1 1/2X200FT PLANT MASTER XTREME 250 | 3205-0055 | 200 | 1 1/2 | 2.00 | 250 | 1000 | 12.0 | 10.0 |
| | 1 1/4X300FT PLANT MASTER XTREME 250 | 3205-0049 | 300 | 1 1/4 | 1.75 | 250 | 1000 | 10.0 | 10.0 |
| | 1/2X500 RL PREMO FLEX 250 | 3205-0230 | 500 | 1/2 | .85 | 250 | 1000 | 4.0 | 25.0 |
| | 1/2X500 RL PREMO FLEX 315 | 3205-0231 | 500 | 1/2 | .88 | 315 | 1260 | 4.0 | 25.0 |
| | 1/2X500FT PLANT MASTER XTREME 250 | 3205-0030 | 500 | 1/2 | .85 | 250 | 1000 | 4.0 | 25.0 |
| | 1/2X500FT PLANT MASTER XTREME 315 | 3205-0031 | 500 | 1/2 | .88 | 315 | 1260 | 4.0 | 25.0 |
| | 1/4X500 RL PREMO FLEX 250 | 3205-0215 | 500 | 1/4 | .50 | 250 | 1000 | 2.0 | 30.0 |
| | 1/4X500FT PLANT MASTER XTREME 250 | 3205-0015 | 500 | 1/4 | .50 | 250 | 1000 | 2.0 | 30.0 |
| | 1/4X500FT PLANT MASTER XTREME 315 | 3205-0016 | 600 | 1/4 | .57 | 315 | 1260 | 2.0 | 30.0 |
| | 1X400FT PLANT MASTER XTREME 250 | 3205-0046 | 400 | 1 | 1.47 | 250 | 1000 | 8.0 | 10.0 |
| | 3/4X500 RL PREMO FLEX 250 | 3205-0240 | 500 | 3/4 | 1.15 | 250 | 1000 | 5.0 | 20.0 |
| | 3/4X500 RL PREMO FLEX 315 | 3205-0241 | 500 | 3/4 | 1.19 | 315 | 1260 | 5.0 | 20.0 |
| | 3/4X500FT PLANT MASTER XTREME 250 | 3205-0040 | 500 | 3/4 | 1.15 | 250 | 1000 | 5.0 | 20.0 |
| | 3/4X500FT PLANT MASTER XTREME 315 | 3205-0041 | 500 | 3/4 | 1.19 | 315 | 1260 | 5.0 | 20.0 |
| | 3/8X500 RL PREMO FLEX 250 | 3205-0225 | 500 | 3/8 | .66 | 250 | 1000 | 3.0 | 30.0 |
| | 3/8X500 RL PREMO FLEX 315 | 3205-0226 | 500 | 3/8 | .73 | 315 | 1260 | 3.0 | 30.0 |
| | 3/8X500FT PLANT MASTER XTREME 250 | 3205-0025 | 500 | 3/8 | .66 | 250 | 1000 | 3.0 | 30.0 |
| | 3/8X500FT PLANT MASTER XTREME 315 | 3205-0026 | 500 | 3/8 | .73 | 315 | 1260 | 3.0 | 30.0 |
| | 5/8X500 RL PREMO FLEX 250 | 3205-0235 | 500 | 5/8 | .98 | 250 | 1000 | 5.0 | 20.0 |
| | 5/8X500 RL PREMO FLEX 315 | 3205-0236 | 500 | 5/8 | .98 | 315 | 1260 | 5.0 | 20.0 |
| | 5/8X500FT PLANT MASTER XTREME 315 | 3205-0036 | 500 | 5/8 | .98 | 315 | 1260 | 5.0 | 20.0 |

# PLANT MASTER® XTREME® 300 AR

## INDUSTRIAL HOSE

| | |
|---|---|
| RECOMMENDED FOR | Applications requiring a premium grade spiral hose with superior abrasion resistance, excellent flexibility and maximum resistance to air, water, petroleum oils and lubricating oils (to +212°F). Recommended for gasoline, kerosene, and fuel oil transfer only to +120°F. Good weather and ozone resistance. |
| TUBE | Type C (Nitrile). Black. |
| REINFORCEMENT | Synthetic, high tensile textile cord. |
| COVER | Type C4 (Carboxylated Nitrile). Black or Red. |
| TEMPERATURE RANGE | –40°F to +212°F (–40°C to +100°C) continuous service. |
| COUPLING RECOMMENDATION | GLX® Couplings (G44) Section N<br>MegaCrimp® Couplings (G25) Section G<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 1/2X500RL PREMOFLEX AR RED 300 | 3205-0408 | 600 | 1/2 | .84 | 300 | 1200 | 4.0 | 25.0 |
| | 1/2XRL PLANT MASTER XTREME 300 AR BLACK | 3205-0505 | 500 | 1/2 | .84 | 300 | 1200 | 4.0 | 25.0 |
| | 1/2XRL PREMO FLEX AR RED 300 | 3205-0403 | 500 | 1/2 | .84 | 300 | 1200 | 4.0 | 25.0 |
| | 1/4X500RL PREMOFLEX AR RED 300 | 3205-0406 | 600 | 1/4 | .53 | 300 | 1200 | 2.0 | 30.0 |
| | 1/4XRL PLANT MASTER XTREME 300 AR BLACK | 3205-0503 | 500 | 1/4 | .53 | 300 | 1200 | 2.0 | 30.0 |
| | 1/4XRL PREMO FLEX AR RED 300 | 3205-0401 | 500 | 1/4 | .53 | 300 | 1200 | 2.0 | 30.0 |
| | 1XRL PLANT MASTER XTREME 300 AR BLACK | 3205-0507 | 400 | 1 | 1.50 | 300 | 1200 | 8.0 | 10.0 |
| | 1XRL PREMO FLEX AR RED 300 | 3205-0405 | 400 | 1 | 1.50 | 300 | 1200 | 8.0 | 10.0 |
| | 3/4X500RL PREMOFLEX AR RED 300 | 3205-0409 | 500 | 3/4 | 1.19 | 300 | 1200 | 5.0 | 20.0 |
| | 3/4XRL PLANT MASTER XTREME 300 AR BLACK | 3205-0506 | 500 | 3/4 | 1.19 | 300 | 1200 | 5.0 | 20.0 |
| | 3/4XRL PREMO FLEX AR RED 300 | 3205-0404 | 500 | 3/4 | 1.19 | 300 | 1200 | 5.0 | 20.0 |
| | 3/8X500RL PREMOFLEX AR RED 300 | 3205-0407 | 500 | 3/8 | .70 | 300 | 1200 | 3.0 | 30.0 |
| | 3/8XRL PLANT MASTER XTREME 300 AR BLACK | 3205-0504 | 500 | 3/8 | 9.50 | 300 | 1200 | 3.0 | 30.0 |
| | 3/8XRL PREMO FLEX AR RED 300 | 3205-0402 | 500 | 3/8 | .70 | 300 | 1200 | 3.0 | 30.0 |

# PLANT MASTER® PLUS LOCK-ON

## INDUSTRIAL HOSE

| | |
|---|---|
| RECOMMENDED FOR | Air, water, oils, antifreeze solutions and applications where Lock–On fittings are used. |
| TUBE | Type C (Nitrile). Black. |
| REINFORCEMENT | Aramid tensile cord. |
| COVER | Type A (Polychloroprene). Black.<br>Type C2 (Modified Nitrile). Blue, red, yellow, green or gray. |
| TEMPERATURE RANGE | –20°F to +212°F (–29°C to +100°C) normal service. For air: +160°F (+71°C) only. For water emulsion, see Gates Hydraulic Hose Catalog. |
| COUPLING RECOMMENDATION | GLX® Couplings (G44) Section N<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 1/2X500FT PLANT MASTER PLUS 300 LOCK-ON BLACK | 3222-0185 | 500 | 1/2 | .81 | 300 | 1200 | 5.0 | 30.0 |
| | 1/2X500FT PLANT MASTER PLUS 300 LOCK-ON BLUE | 3222-0145 | 500 | 1/2 | .81 | 300 | 1200 | 5.0 | 30.0 |
| | 1/2X500FT PLANT MASTER PLUS 300 LOCK-ON GRAY | 3222-0285 | 500 | 1/2 | .81 | 300 | 1200 | 5.0 | 30.0 |
| | 1/2X500FT PLANT MASTER PLUS 300 LOCK-ON GREEN | 3222-0235 | 500 | 1/2 | .81 | 300 | 1200 | 5.0 | 30.0 |
| | 1/2X500FT PLANT MASTER PLUS 300 LOCK-ON RED | 3222-0335 | 500 | 1/2 | .81 | 300 | 1200 | 5.0 | 30.0 |
| | 3/8X500FT PLANT MASTER PLUS 300 LOCK-ON BLACK | 3222-0184 | 500 | 3/8 | .68 | 300 | 1200 | 3.0 | 30.0 |
| | 3/8X500FT PLANT MASTER PLUS 300 LOCK-ON BLUE | 3222-0144 | 500 | 3/8 | .68 | 300 | 1200 | 3.0 | 30.0 |
| | 3/8X500FT PLANT MASTER PLUS 300 LOCK-ON GRAY | 3222-0284 | 500 | 3/8 | .68 | 300 | 1200 | 3.0 | 30.0 |
| | 3/8X500FT PLANT MASTER PLUS 300 LOCK-ON GREEN | 3222-0234 | 500 | 3/8 | .68 | 300 | 1200 | 3.0 | 30.0 |
| | 3/8X500FT PLANT MASTER PLUS 300 LOCK-ON RED | 3222-0334 | 500 | 3/8 | .68 | 300 | 1200 | 3.0 | 30.0 |
| | 3/8X500FT PLANT MASTER PLUS 300 LOCK-ON YELLOW | 3222-0084 | 500 | 3/8 | .68 | 300 | 1200 | 3.0 | 30.0 |
| | PYTHON1/4BLKXREEL | 3222-0183 | 500 | 1/4 | .54 | 300 | 1200 | 3.0 | 30.0 |
| | PYTHON1/4BLUXREEL | 3222-0143 | 500 | 1/4 | .54 | 300 | 1200 | 3.0 | 30.0 |
| | PYTHON1/4GRYXREEL | 3222-0283 | 500 | 1/4 | .54 | 300 | 1200 | 3.0 | 30.0 |

## AG MASTER®

### INDUSTRIAL HOSE

| | |
|---|---|
| RECOMMENDED FOR | Designed for agricultural spraying applications, such as dilute solutions of herbicides and fertilizers. Can also be used for air and water applications requiring maximum flexibility in the agriculture industry. Outstanding resistance to heat and ozone. |
| TUBE | Type P (EPDM). Black. |
| REINFORCEMENT | Synthetic, high tensile textile cord. |
| COVER | Type P (EPDM). Black. All sizes through 1/2" are perforated. |
| TEMPERATURE RANGE | –40°F to +200°F (–40°C to +93°C) continuous service. |
| COUPLING RECOMMENDATION | GLX® Couplings (G44) Section N<br>(See Crimp Data Manual 428–7365 or eCrimp) |




| Part No. | Description | Product No. | Standard Pack | ⊖ | ⌀ | | R | ○ |
|---|---|---|---|---|---|---|---|---|
| | 1 1/2XRL AG MASTER 250 | 3204-1086 | 250 | 1 1/2 | 1.98 | 250 | 12.0 | 30.0 |
| | 1 1/4XRL AG MASTER 250 | 3204-1085 | 300 | 1 1/4 | 1.73 | 250 | 10.0 | 30.0 |
| | 1/2XRL AG MASTER 200 | 3204-1081 | 600 | 1/2 | .81 | 200 | 5.0 | 30.0 |
| | 1/4XRL AG MASTER 200 | 3204-1079 | 600 | 1/4 | .50 | 200 | 3.0 | 30.0 |
| | 1XRL AG MASTER 200 | 3204-1084 | 400 | 1 | 1.40 | 200 | 8.0 | 30.0 |
| | 3/4XRL AG MASTER 200 | 3204-1083 | 600 | 3/4 | 1.15 | 200 | 6.0 | 30.0 |
| | 3/8XRL AG MASTER 200 | 3204-1080 | 600 | 3/8 | .66 | 200 | 3.0 | 30.0 |
| | 5/8XRL AG MASTER 200 | 3204-1082 | 600 | 5/8 | .97 | 200 | 6.0 | 30.0 |

NOTE: Pressure ratings can only be obtained with proper coupling procedures.

## CLEAN MASTER® PRESSURE WASH

### INDUSTRIAL HOSE

| | |
|---|---|
| RECOMMENDED FOR | Hot and cold water high–pressure cleaning equipment where heavy–duty service is required. Specially compounded cover to handle pressure washer environment. |
| TUBE | Black Nitrile. |
| REINFORCEMENT | Braided, high–tensile steel wire. |
| COVER | Nitrile and PVC. Non–marking except for black. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). Laboratory tested for normal service. Increased operating temperatures will reduce hose assembly service life. |
| COUPLING RECOMMENDATION | MegaCrimp® Couplings (G25) Section G<br>Stainless Steel Braid Couplings (G17) Section H<br>(See Crimp Data Manual 428–7365 or eCrimp) |




Exceeds EN1829–2 and has significantly tighter bend radius.

| Part No. | Description | Product No. | Standard Pack | ⊖ | ⌀ | | | R | ○ |
|---|---|---|---|---|---|---|---|---|---|
| 71119 | 1/2XRL 300FT CLEAN MASTER PW3000 BLACK | 4657-9375 | 300 | 1/2 | .80 | 3000 | 12000 | 2.5 | 30.0 |
| 71120 | 1/2XRL 300FT CLEAN MASTER PW5000 BLACK | 4657-9387 | 300 | 1/2 | .86 | 5000 | 15000 | 2.5 | 30.0 |
| 71116 | 1/4XRL 300FT CLEAN MASTER PW4000 BLACK | 4657-9377 | 300 | 1/4 | .53 | 4000 | 12000 | 2.5 | 30.0 |
| 70841 | 1/4XRL 300FT CLEAN MASTER PW6000 BLACK | 4657-2410 | 300 | 1/4 | .59 | 6000 | 24000 | 2.0 | 30.0 |
| 85698 | 3/8X50FT CLEAN MASTER PW3000 YELLOW | 4657-0064 | 1 | 3/8 | .68 | 3000 | 12000 | 5.0 | 30.0 |
| 85729 | 3/8X50FT CLEAN MASTER PW4000 BLACK | 4657-9424 | 35 | 3/8 | .68 | 4000 | 16000 | 5.0 | 30.0 |

NOTE: Not recommended for Steam Hose. Use bend restrictors to extend service life.

## CLEAN MASTER® PRESSURE WASH - CONTINUED

### INDUSTRIAL HOSE - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 85728 | 3/8X50FT CLEAN MASTER PW4000 BLUE | 4657-9469 | 1 | 3/8 | .74 | 4000 | 16000 | 5.0 | 30.0 |
| 85725 | 3/8X50FT CLEAN MASTER PW5000 BLACK | 4657-2472 | 1 | 3/8 | .74 | 5000 | 20000 | 5.0 | 30.0 |
| 70845 | 3/8XRL 300FT CLEAN MASTER PW 2 WB 5000 BLACK | 4657-2407 | 300 | 3/8 | .74 | 5000 | 20000 | 2.5 | 30.0 |
| 70842 | 3/8XRL 300FT CLEAN MASTER PW3000 BLACK | 4657-2402 | 300 | 3/8 | .68 | 3000 | 12000 | 2.5 | 30.0 |
| 70848 | 3/8XRL 300FT CLEAN MASTER PW3000 YELLOW | 4657-2417 | 300 | 3/8 | .68 | 3000 | 12000 | 2.5 | 30.0 |
| 71118 | 3/8XRL 300FT CLEAN MASTER PW4000 BLACK | 4657-9379 | 300 | 3/8 | .68 | 4000 | 12000 | 2.5 | 30.0 |
| 71117 | 3/8XRL 300FT CLEAN MASTER PW4000 BLUE | 4657-9468 | 300 | 3/8 | .74 | 4000 | 12000 | 3.5 | 30.0 |
| 76393 | 3/8XRL 300FT CLEAN MASTER PW5000 BLUE | 4657-2429 | 300 | 3/8 | .74 | 5000 | 20000 | 2.5 | 30.0 |
| 85721 | 4PC6000 X50FT | 4657-2468 | 1 | 1/4 | .74 | 6000 | 24000 | 4.0 | 30.0 |
| 85722 | 6PC3000 X50FT | 4657-2469 | 1 | 3/8 | .68 | 3000 | 12000 | 2.5 | 30.0 |

NOTE: Not recommended for Steam Hose. Use bend restrictors to extend service life.

## CLEAN MASTER® PRESSURE WASH ASSEMBLIES

### INDUSTRIAL HOSE

| | |
|---|---|
| RECOMMENDED FOR | Standard–duty use on hot and cold water high–pressure cleaning equipment. Extremely flexible, lightweight and easy to handle. Tube specially compounded to handle high–pressure water service. Specially compounded cover to handle pressure washer environment. |
| TUBE | Black Nitrile. |
| REINFORCEMENT | Braided, high–tensile steel wire. |
| COVER | Black. Nitrile and PVC. |
| TEMPERATURE RANGE | –40°F to +250°F (–40°C to +121°C). Laboratory tested for normal service. Increased operating temperatures will reduce hose assembly service life. |



| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| A36040036 | | 3604-0036 | 5 | 1/2 | .76 | 3000 | 3.5 | 30.0 |
| A36040071 | | 3604-0071 | 5 | 3/8 | .63 | 3000 | 2.5 | 30.0 |
| A36040035 | 6PW6MP6MPX600BR | 3604-0035 | 25 | 3/8 | .63 | 3000 | 2.5 | 30.0 |

## LP350X HOSE

### INDUSTRIAL HOSE




| | |
|---|---|
| RECOMMENDED FOR | Liquid or gaseous propane, butane or any combination of these two mixtures up to 350 psi rated working pressure. Can be used for natural gas under certain conditions such as: open/outside areas and well ventilated factory buildings (if local building codes permit). Not recommended for residential or office buildings. Contact Denver Product Application (303) 744–5070 for inspection and assembly testing information. Meets UL Standard #21, CAN/CGA–8.1–M86, NFPA 58, Section 8–3, 5. |
| TUBE | Nitrile. See Hose Stock Characteristics. |
| REINFORCEMENT | Braided, high–tensile synthetic textile cord. |
| COVER | Black perforated Polychloroprene. See Hose Stock Characteristics. |
| TEMPERATURE RANGE | –40°F to +180°F (–40°C to +82°C). For water emulsions see Temperature Limits Table. |
| COUPLING RECOMMENDATION | GLX® Couplings (G44) Section N<br>Power Crimp® Couplings (–12) Section I<br>(See Crimp Data Manual 428–7365 or eCrimp) |

Application Note: No LP350 hose assemblies 60" or longer allowed per UL requirement.

| Part No. | Description | Product No. | Standard Pack | | | | | |
|---|---|---|---|---|---|---|---|---|
| 85717 | 4LP350X X50FT | 3220-1300 | 1 | 1/4 | .58 | 350 | 1750 | 3.0 |
| 85718 | 6LP350X X50FT | 3220-1123 | 1 | 3/8 | .70 | 350 | 1750 | 3.0 |
| 85719 | 8LP350X X50FT | 3220-1301 | 1 | 1/2 | .91 | 350 | 1750 | 5.0 |
| 85738 | 12LP350X X50FT | 3220-1302 | 1 | 3/4 | 1.24 | 350 | 1750 | 6.0 |

## LP350 HOSE

### INDUSTRIAL HOSE




| | |
|---|---|
| RECOMMENDED FOR | Liquid or gaseous propane, butane or any combination of these two mixtures. Can be used for natural gas (not to exceed 50 psi) under certain conditions such as: open/outside areas and well ventilated factory buildings (if local building codes permit). |
| TUBE | Type A (Chloroprene). Black. 1 1/2" – 3".<br>Type C (Nitrile). Black. 1/4" – 1 1/4". |
| REINFORCEMENT | Braided, synthetic high tensile cord. 1 1/4" – 3".<br>High tensile synthetic textile cord. 1/4" – 1". |
| COVER | Type A (Polychloroprene). Black. All sizes are perforated. |
| TEMPERATURE RANGE | –40°F to +180°F (–40°C to +82°C) continuous service. Warning: Do not convey LP Gas over +140°F (60°C). |
| COUPLING RECOMMENDATION | GLX® Couplings (1/4" to 1 1/4") (G44) Section N<br>Power Crimp® Couplings (3/4", 1 1/2" and 2" I.D.) Section I<br>(See Crimp Data Manual 428–7365 or eCrimp) |

| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 1 1/2X60FT FUEL MASTER LP350 | 3320-0935 | 60 | 1 1/2 | 2.25 | 350 | 1750 | 12.0 | 10.0 |
| | 1 1/4XRL FUEL MASTER LP350 | 3220-0855 | 300 | 1 1/4 | 1.85 | 350 | 1750 | 10.0 | 10.0 |
| | 1/2XBULK FUEL MASTER LP350 | 3220-1205 | 1000 | 1/2 | .91 | 350 | 1750 | 5.0 | 25.0 |
| | 1/2XRL FUEL MASTER LP350 | 3220-1204 | 700 | 1/2 | .91 | 350 | 1750 | 5.0 | 25.0 |
| | 1/4XRL FUEL MASTER LP350 | 3220-1200 | 700 | 1/4 | .58 | 350 | 1750 | 3.0 | 30.0 |

NOTE: Not recommended for residential, office buildings or as fuel line hose on compressed natural gas vehicles. Contact Denver Product Application (303) 744–5070 for inspection and assembly testing information.

## LP350 HOSE - CONTINUED

### INDUSTRIAL HOSE - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 1X100FT FUEL MASTER LP350 | 3220-1211 | 100 | 1 | 1.51 | 350 | 1750 | 8.0 | 15.0 |
| | 1X125FT FUEL MASTER LP350 | 3220-1212 | 125 | 1 | 1.51 | 350 | 1750 | 8.0 | 15.0 |
| | 1X150FT FUEL MASTER LP350 | 3220-1213 | 150 | 1 | 1.51 | 350 | 1750 | 8.0 | 15.0 |
| | 1XRL FUEL MASTER LP350 | 3220-1210 | 300 | 1 | 1.51 | 350 | 1750 | 8.0 | 15.0 |
| | 2X60FT FUEL MASTER LP350 | 3320-0938 | 60 | 2 | 2.86 | 350 | 1750 | 14.0 | 10.0 |
| | 3/4X100FT FUEL MASTER LP350 | 3220-1207 | 100 | 3/4 | 1.23 | 350 | 1750 | 6.0 | 20.0 |
| | 3/4X125FT FUEL MASTER LP350 | 3220-1208 | 125 | 3/4 | 1.23 | 350 | 1750 | 6.0 | 20.0 |
| | 3/4X150FT FUEL MASTER LP350 | 3220-1209 | 150 | 3/4 | 1.23 | 350 | 1750 | 6.0 | 20.0 |
| | 3/4XRL FUEL MASTER LP350 | 3220-1206 | 350 | 3/4 | 1.23 | 350 | 1750 | 6.0 | 20.0 |
| | 3/8XRL FUEL MASTER LP350 | 3220-1202 | 700 | 3/8 | .74 | 350 | 1750 | 3.0 | 30.0 |
| | 3X60FT FUEL MASTER LP350 | 3320-0934 | 60 | 3 | 3.88 | 350 | 1750 | 24.0 | 10.0 |

NOTE: Not recommended for residential, office buildings or as fuel line hose on compressed natural gas vehicles. Contact Denver Product Application (303) 744–5070 for inspection and assembly testing information.

## FUEL MASTER® DELIVERY

### INDUSTRIAL HOSE

| | |
|---|---|
| RECOMMENDED FOR | Transferring fuel oils, diesel fuel or commercial gasolines in applications at temperatures as low as –40°F (–40°C). Compatible with Bio–Diesel fuels up to B20. Hose remains flexible to –20°F (–29°C). For home and heavy–duty commercial service where an abrasion–resistant and non–marking cover is required. |
| TUBE | Type C (Nitrile). Black. |
| REINFORCEMENT | High tensile synthetic textile cord. |
| COVER | Type C4 (Carboxylated Nitrile). Red. Abrasion–resistant and non–marking. |
| TEMPERATURE RANGE | –40°F to +180°F (–29°C to +82°C) continuous service. |




Meets Flame Resistance Acceptance Designation "MSHA 2G".

| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 1 3/8 X 100 FUEL OIL DEL | 3221-0418 | 100 | 1 3/8 | 1.87 | 200 | 800 | 10.0 | 10.0 |
| | 1 3/8 X 125 FUEL OIL DEL | 3221-0419 | 125 | 1 3/8 | 1.87 | 200 | 800 | 10.0 | 10.0 |
| | 1 1/2X100 FUEL OIL DEL | 3221-0422 | 100 | 1 1/2 | 2.08 | 200 | 800 | 12.0 | 10.0 |
| | 1 1/2X125 FUEL OIL DEL | 3221-0423 | 125 | 1 1/2 | 2.08 | 200 | 800 | 12.0 | 10.0 |
| | 1 1/2X150 FUEL OIL DEL | 3221-0424 | 150 | 1 1/2 | 2.08 | 200 | 800 | 12.0 | 10.0 |
| | 1 1/2X175 FUEL OIL DEL | 3221-0425 | 175 | 1 1/2 | 2.08 | 200 | 800 | 12.0 | 10.0 |
| | 1 1/2X200 FUEL OIL DEL | 3221-0426 | 200 | 1 1/2 | 2.08 | 200 | 800 | 12.0 | 10.0 |
| | 1 1/4X100 FUEL OIL DEL | 3221-0414 | 100 | 1 1/4 | 1.75 | 200 | 800 | 10.0 | 10.0 |
| | 1 1/4X125 FUEL OIL DEL | 3221-0415 | 125 | 1 1/4 | 1.75 | 200 | 800 | 10.0 | 10.0 |
| | 1 1/4X150 FUEL OIL DEL | 3221-0416 | 150 | 1 1/4 | 1.75 | 200 | 800 | 10.0 | 10.0 |
| | 1 1/4X175 FUEL OIL DEL | 3221-0417 | 175 | 1 1/4 | 1.75 | 200 | 800 | 10.0 | 10.0 |
| | 1 3/8X150FT FUEL MASTER DELIVERY 200 | 3221-0420 | 150 | 1 3/8 | 1.87 | 200 | 800 | 10.0 | 10.0 |

## FUEL MASTER® DELIVERY - CONTINUED

### INDUSTRIAL HOSE - CONTINUED

| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 1 3/8X175 FUEL OIL DEL | 3221-0421 | 175 | 1 3/8 | 1.87 | 200 | 800 | 10.0 | 10.0 |
| | 1X100FT FUEL MASTER DELIVERY 200 | 3221-0410 | 100 | 1 | 1.50 | 200 | 800 | 8.0 | 10.0 |
| | 1X125FT FUEL MASTER DELIVERY 200 | 3221-0411 | 125 | 1 | 1.50 | 200 | 800 | 8.0 | 10.0 |
| | 1X150FT FUEL MASTER DELIVERY 200 | 3221-0412 | 150 | 1 | 1.50 | 200 | 800 | 8.0 | 10.0 |
| | 1X175FT FUEL MASTER DELIVERY 200 | 3221-0413 | 175 | 1 | 1.50 | 200 | 800 | 8.0 | 10.0 |

## LPG VAPOR

### INDUSTRIAL HOSE

| | |
|---|---|
| RECOMMENDED FOR | Flexible connector for conveying low–pressure LPG (vapor only) to many types of farm and industrial heating applications; e.g., space heaters. |
| TUBE | Type C (Nitrile). Black. |
| REINFORCEMENT | High tensile synthetic textile cord. |
| COVER | Type A (Polychloroprene). Black. |
| TEMPERATURE RANGE | –30°F to +150°F (–34°C to +66°C) continuous service. |




| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 1/4XRL FUEL MASTER LPG VAPOR 125 | 3220-0456 | 700 | 1/4 | .53 | 125 | 625 | 3.0 | 30.0 |
| | 3/8XRL FUEL MASTER LPG VAPOR 125 | 3220-0461 | 700 | 3/8 | .66 | 125 | 625 | 3.0 | 25.0 |
| | 3/16XRL FUEL MASTER LPG VAPOR 125 | 3220-0451 | 700 | 3/16 | .44 | 125 | 625 | 2.0 | 30.0 |

NOTE: This hose should not be used for liquid LPG or in UL approved appliances such as barbecue grills.

## FUEL MASTER® CURB PUMP

### INDUSTRIAL HOSE

| | |
|---|---|
| RECOMMENDED FOR | Dispensing all types of commercial gasolines or other petroleum–based products, from service station pumps (curb pump). A heavy–duty hardwall hose which does not collapse in reel use or behind the nozzle in heavy–duty service. |
| TUBE | Type C (Nitrile). Black. |
| REINFORCEMENT | Braided, high–tensile steel wire. |
| COVER | Type J (CPE). Black. 5/8" and 3/4" smooth, 1" wrapped. |
| TEMPERATURE RANGE | –40°F to +120°F (–40°C to +49°C) continuous service. |




| Part No. | Description | Product No. | Standard Pack | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | 1XRL FUEL MASTER CURB PUMP 150 | 3624-0003 | 500 | 1 | 1.38 | 150 | 750 | 8.0 | 30.0 |
| | 3/4XRL FUEL MASTER CURB PUMP 150 | 3624-0002 | 500 | 3/4 | 1.13 | 150 | 750 | 6.0 | 30.0 |

## FUEL MASTER® CURB PUMP - CONTINUED

### INDUSTRIAL HOSE - CONTINUED

| Part No. | Description | Product No. | Standard Pack | ⊖ | | | | R | ◯ |
|---|---|---|---|---|---|---|---|---|---|
| | 5/8XRL FUEL MASTER CURB PUMP 150 | 3624-0001 | 500 | 5/8 | 1.00 | 150 | 750 | 6.0 | 30.0 |

## FUEL MASTER® DIESEL CURB PUMP

### INDUSTRIAL HOSE

| | |
|---|---|
| RECOMMENDED FOR | Dispensing of all types of petroleum diesel fuels and Bio–Diesel blends from service station pumps. A heavy–duty hardwall hose which does not collapse in reel use or behind the nozzle in heavy–duty service. |
| TUBE | Type C (Nitrile). Black. |
| REINFORCEMENT | Braided, high–tensile steel wire. |
| COVER | Type J (CPE). Green. Smooth cover. |
| TEMPERATURE RANGE | –40°F to +120°F (–40°C to +49°C) continuous service. |




| Part No. | Description | Product No. | Standard Pack | ⊖ | | | | R | ◯ |
|---|---|---|---|---|---|---|---|---|---|
| | 1XRL FUEL MASTER DIESEL CURB PUMP 150 | 3624-1009 | 500 | 1 | 1.38 | 150 | 750 | 8.0 | 30.0 |
| | 7/8XRL FUEL MASTER DIESEL CURB PUMP 150 | 3624-1008 | 500 | 7/8 | 1.22 | 150 | 750 | 7.0 | 30.0 |

## NOTES

# IN THE SHOP OR IN THE FIELD, GATES HAS A CRIMPER FOR EVERY JOB.

## GC® 16XD™ MINI CRIMPER



- 1” two-wire and 3/4” four-wire capability.
- User-friendly horizontal loading for crimping in the field.
- 80 ton crimp force.
- Unmatched portability and speed with 10,000 psi battery-operated pump.

## MOBILECRIMP® 4-20



- Portable and lightweight – only 78 pounds.
- Powerful enough to crimp up to 1-1/4” I.D. four spiral-wire hose.
- Great for jobs in the field.
- Multiple pump options for maximum flexibility.

## GC® 32TSi™ CRIMPER



- Touch screen simplifies hose and coupling selection.
- Precision crimps without looking up data or adjusting crimper settings.
- After crimp is complete, the crimp O.D. is automatically measured and displayed on screen.
- Controller is updated where wireless internet is available, or via thumb drive.
- All the necessary tools and information reside on-board to crimp, leak-free, factory-quality hydraulic hose assemblies.

## POWER CRIMP® 707



- The most precise, yet simplest crimper made.
- The first crimper with electronic digital readout to indicate crimp diameter setting.
- Crimps low pressure return lines to high pressure spiral hose, from 3/16” to 1-1/4” I.D. four-spiral wire.
- Crimps straight and bent tube couplings plus 45° and 90°. Block style terminations require notched cone.
- Swage capable.

## GC® 96TSi™-3 CRIMPER



- Electronic touch screen control panel for fast input of crimper settings.
- Horizontal front-end feed makes crimping easier and convenient.
- 550 ton force that allows crimping of a wide variety of couplings.
- 2 speed die closure and rapid retract permit fast assembly fabrication.
- Full range die sets that enable production of a wide range of hose assemblies.
- 3" six-wire and 6" industrial.

## SC-32™ CRIMPER



- Compact design to minimize space required.
- High-ton ram force with an integrated pump.
- Pump pre-wired for either 110V or 220V (1 phase) outlets.
- Bottom-loading makes crimping easier.
- Come with all the base plates and spacers required to crimp up to 2" hose.

**For complete crimper specifications, see the following pages.**

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# GC® 16XD™ MINI CRIMPER

Crimping at remote job sites requires a durable yet user-friendly crimper. Weighing only 44 pounds, this crimper can be used anywhere. The Gates Mini Crimper and pump combine the performance and speed of a powered pump with the convenience of a hand pump.



**Features:**

- 1” two-wire and 3/4” 4-wire capability.
- User-friendly horizontal loading for crimping in the field
- 80 ton crimp force
- Unmatched portability and speed with 10,000 psi battery-operated pump

**SPECIFICATIONS**

**Part Number:** 70115
**Product Number:** 7480-7006

## Start-up Kit (Ordered Separately)

**Part Number:** 78733
**Product Number:** 7482-7313

- 1 - Digital Caliper 6” (#78241, 7369-0322)
- 1 - Hose Assembly (#78467, 7482-1017)
- 1 - G95311-0606 6MQFFVH-6FP, quick disconnect
- 1 - G95321-0606 6FQFFVH-6FP, quick disconnect
- 2 - GC16XD Mini Crimper Crimp Data Card (#428-3467, 81000)

## QC Tool (Ordered Separately)

**Part Number:** 78759
**Product Number:** 7482-7304

# GC® 16XD™ Die Selection Table

### For MegaCrimp® (G25) Couplings

| Hose Type | Hose Sizes 1/4” | 3/8” | 1/2” | 5/8” | 3/4” | 1” |
|---|---|---|---|---|---|---|
| M3K | GC16-21 | GC16-22 | GC16-33 | GC16-34 | GC16-35 | GC16-37 |
| M2T | GC16-21 | GC16-22 | GC16-33 | GC16-34 | GC16-35 | GC16-37 |
| G1 | GC16-21 | GC16-22 | GC16-33 | GC16-34 | GC16-35 | GC16-37 |
| G2 | GC16-21 | GC16-22 | GC16-33 | GC16-34 | GC16-35 | GC16-37 |

For other hose and coupling configurations, reference **www.gates.com/ecrimp**

### For GlobalSpiral™ (G20) Couplings

| Hose Type | Hose Sizes 3/8” | 1/2” | 5/8” | 3/4” |
|---|---|---|---|---|
| EFG6K | GC16-33 | GC16-33 | GC16-35L | GC16-35L |
| EFG5K | GC16-33 | GC16-33 | GC16-35L | GC16-35L |
| EFG4K | GC16-33 | GC16-33 | GC16-35L | GC16-35L |

## Die Sets (ordered separately)

| Die Set | GC16-21 | GC16-22 | GC16-33 | GC16-34 | GC16-35 | GC16-35L | GC16-37 |
|---|---|---|---|---|---|---|---|
| Part No. | 78242 | 78243 | 78244 | 78245 | 78246 | 78078 | 78247 |
| Product No. | 7482-7321 | 7482-7322 | 7482-7333 | 7482-7334 | 7482-7335 | 7482-7310 | 7482-7337 |

## Battery Pump

Need to crimp in tight or awkward spaces? Gates new battery-operated pump has a sealed bladder reservoir that prevents contamination and allows the pump to operate in any position. Combined with Gates new GC® 16XD™ Mini Crimper, you can make factory quality assemblies quickly and easily in the most demanding locations.



**Features:**

- Cordless, lightweight design with integrated handle and carrying strap
- 1/2 horsepower motor and two 28V Lithium-Ion Milwaukee M28 batteries
- High-strength fiberglass reinforced composite pump shroud for superior durability
- **Pump can also be used to operate Gates MC4-20 Crimper**

**SPECIFICATIONS**

**Part Number:** 70187
**Product Number:** 7481-0011

# MOBILECRIMP® 4-20 CRIMPER

This lightweight, versatile crimper is powerful enough to crimp up to 1-1/4" four spiral-wire hose. Weighing approximately 57 pounds, this field crimper combines crimping technology with toughness and durability.

## DIGITAL DIAL CONTROL

Just dial in appropriate crimp setting and hold the start button until light comes on and buzzer sounds, then release. Ability to lock-in setting for multiple assemblies. Light and buzzer operate on two "AAA" batteries.

**Part Number:** 77421
**Product Number:** 7480-0051

## POSITIVE STOP CONTROL

No settings necessary since color-coded spacer rings control the crimp. Just hold the start button until the ram extends to a fixed "Stop" for each crimp, then release. Controlled crimp stroke for ease of repeatability.

**Part Number:** 77420
**Product Number:** 7480-0050




| Accessories | Part Number | Product Number |
|---|---|---|
| Crimper-to-Pump Male Quick Disconnect | G95311-0606 | 7252-88315 |
| Crimper-to-Pump Female Quick Disconnect | G95321-0606 | 7252-88305 |

# MobileCrimp® 4-20 Die Selection Table

### For MegaCrimp® (G25) Couplings

| Hose Type | Hose Sizes 1/4" | 3/8" | 1/2" | 5/8" | 3/4" | 1" | 1-1/4" |
|---|---|---|---|---|---|---|---|
| M3K | MC21 or MC31 | MC22 or MC32 | MC33 | MC34 | MC35 | MC37 | — |
| M2T | MC21 or MC31 | MC22 or MC32 | MC33 | MC34 | MC35 | MC37 | MC38† |
| G1 | MC21 or MC31 | MC22 or MC32 | MC33 | MC34 | MC35 | MC37 | MC39 |
| G2 | MC21 or MC31 | MC22 or MC32 | MC33 | MC34 | MC35 | MC37 | MC39 |

For other hose and coupling configurations, reference **www.gates.com/ecrimp** or Gates crimp data manual.
† Must use 20M2T pressure plate 78046 / 7482-1078

### For GlobalSpiral™ (G20) Couplings

| Hose Type | Hose Sizes 3/8" | 1/2" | 5/8" | 3/4" | 1" | 1-1/4" |
|---|---|---|---|---|---|---|
| EFG6K | MC33 | MC33 | MC35 | MC35 | MC37 | — |
| EFG5K | MC33 | MC33 | MC35 | MC35 | MC37 | — |
| EFG4K | MC33 | MC33 | MC35 | MC35 | MC37 | MC39* |

***MGS (G21 series) couplings only.**

## Die Sets (ordered separately)

| Die Set | MC21/MC31 | MC22/MC32 | MC33 | MC34 | MC35 | MC36 | MC37 | MC38 | MC39 |
|---|---|---|---|---|---|---|---|---|---|
| Part No. | 78558/78468 | 78559/78469 | 78470 | 78471 | 78472 | 78473 | 78474 | 78475 | 78476 |
| Product No. | 7482-1220/1131 | 7482-1221/1132 | 7482-1133 | 7482-1134 | 7482-1135 | 7482-1136 | 7482-1137 | 7482-1138 | 7482-1139 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# MOBILECRIMP® 4-20 and GC® 16XD™ POWER SOURCES

**Wide selection of pumps to match all your power needs.**



## HAND PUMP


No power source needed. Economical, convenient and portable for use anywhere. Make factory-quality assemblies in the field to minimize downtime.

**Part Number:** 77821
**Product Number:** 7481-0006
**Pressure Rating:** 10,000 psi
**Weight:** 28 lbs

## SHOP AIR PUMP

Works off standard shop air (90 psi). Economical, convenient and versatile for use wherever 90 psi compressed air is available.

**Part Number:** 77820
**Product Number:** 7481-0002
**Pressure Rating:** 10,000 psi
**Weight:** 12 lbs





## 1/2 HP 115 VOLT AC PUMP

Medium speed. Economical. Recommended for a stationary or mobile application.

**Part Number:** 77441
**Product Number:** 7481-0034
**Pressure Rating:** 10,000 psi
**Weight:** 37 lbs



## BATTERY PUMP

Cordless, lightweight design with integrated handle and carrying strap. 1/2 horsepower motor and two 28V Lithium-Ion Milwaukee M28 batteries. High-strength fiberglass reinforced composite pump shroud for superior durability.

**Part Number:** 70187
**Product Number:** 7481-0011
**Weight:** 24 lbs

## 1-1/2 HP 115 VOLT AC PUMP

High speed. Recommended for stationary applications only.

**Part Number:** 77442
**Product Number:** 7481-0035
**Pressure Rating:** 10,000 psi
**Weight:** 87 lbs





## 1/4 HP 12 VOLT DC PUMP


Mobile operation, runs on standard 12V car/truck battery or a 12V portable battery pack. Ideal for tough jobs in the field.

**Part Number:** 77439
**Product Number:** 7481-0037
**Pressure Rating:** 10,000 psi
**Weight:** 20 lbs

# POWER CRIMP® 707

Gates Power Crimp® 707 is the most reliable, yet simplest crimper made. It was the first crimper with electronic digital readout to indicate gauge setting. The toughest part about using the 707 is pushing a button. It takes just a few seconds to make factory-quality hose assemblies.

Crimps most hydraulic hose from low pressure return lines to extremely high pressure spirals, from 3/16" to 1-1/4" I.D. Crimps straight and bent tube couplings, plus 45° and 90° block types. Can also be adapted for use as a power swager.




### SPECIFICATIONS

**Part Number:** 77700
**Product Number:** 7480-0043
Standard PC707 without die sets wired for 115V (includes die backup ring and a no-notched cone).
**Production Rate:** 100 assemblies per hour (using 1/2" I.D. two-wire straight thread assemblies).

**Dimensions:** 13" wide by 12" deep by 26-1/2" high.
**Weight:** 214 lbs

**PC707 230V Converter Kit**
Converts crimper and pump
**Part Number:** 78760
**Product Number:** 7482-0499

## Power Crimp® 707 Die Selection Table

### For MegaCrimp® (G25) Couplings

| Hose Type | Hose Sizes 1/4" | 3/8" | 1/2" | 5/8" | 3/4" | 1" | 1-1/4" |
|---|---|---|---|---|---|---|---|
| M3K | 721 or 731 | 722 or 732 | 733 | 734 | 735 | 737 | — |
| M2T | 721 or 731 | 722 or 732 | 733 | 734 | 735 | 737 | 720 |
| G1 | 721 or 731 | 722 or 732 | 733 | 734 | 735 | 737 | 739 |
| G2 | 721 or 731 | 722 or 732 | 733 | 734 | 735 | 737 | 739 |

### For GlobalSpiral™ (G20) Couplings

| Hose Type | Hose Sizes 3/8" | 1/2" | 5/8" | 3/4" | 1" | 1-1/4" |
|---|---|---|---|---|---|---|
| EFG6K | 733 | 733 | 735 | 735 | 737 | — |
| EFG5K | 733 | 733 | 735 | 735 | 737 | — |
| EFG4K | 733 | 733 | 735 | 735 | 737 | 739 |

For other hose and coupling configurations, reference **www.gates.com/ecrimp** or Gates crimp data manual.

## Die Sets (ordered separately)

| Die Set | 721/731 | 722/732 | 733 | 734 | 735 | 737* | 720* | 739* |
|---|---|---|---|---|---|---|---|---|
| Part No. | 78943/78931 | 78944/78932 | 78933 | 78934 | 78935 | 78937 | 78920 | 78939 |
| Product No. | 7482-1217/0931 | 7482-1218/0932 | 7482-0933 | 7482-0934 | 7482-0935 | 7482-0937 | 7482-0920 | 7482-0939 |

* Must Use No-Notch Die Cone.

## Power Crimp® 707 Pump

The flows of two fixed displacement pumps are combined to deliver a high volume of oil at low pressure for fast transversion.




### SPECIFICATIONS

**Part Number:** 77810
**Product Number:** 7481-0023
(115V, 30 amp, circuit, 1 hp, 60 cycles)
**Dimensions:** 12" wide by 25" deep by 12" high.
**Weight:** 79 lbs
**Maximum Working Pressure:** 4,900 psi

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# GC® 32TSi™ CRIMPER

There's no room for error when replacing hydraulic hose assemblies. Gates GC® 32TSi™ innovative "smart" crimper leaves nothing to chance. All the necessary tools and information reside on-board to crimp rock-solid, leak-free, factory-quality hose assemblies. Gates GC32TSi crimper features a touch-screen control panel for easy navigation. It links to Gates eCrimp® database for up-to-the-minute crimp specifications and optimal hose/coupling selection. Advanced functionality such as pinch decompression, precision crimp diameter measurement, machined die retention plates with a simple die loading system, and a self-lubricating crimper head assist the operator in building factory-quality assemblies that meet Gates stringent crimping specifications.



## SPECIFICATIONS

**Part Number:** 78827
**Product Number:** 7480-7004
**Dimensions:** 23" wide by 19-1/2" deep by 37" high
**Weight:** 557.4 lbs
**Motor:** 5 hp
**Pump:** 2-stage
**Power Source:** 208-260V, 50-60 hz, 1 phase and 20 amp, (plug is a NEMA L6-20)
**Maximum Crimping Force:** 420 tons
**Rack and Stand sold separately** - can be used with GC®32 and GC®96 crimpers
**Stand: Part Number:** 78829
**Product Number:** 7480-7002
31-3/4" wide by 16-1/2" deep (height adjustable) by 25-1/2" high
**Die Rack: Part Number:** 78830
**Product Number:** 7480-7003

## For GlobalSpiral™ (G20) Couplings

| Hose Type | Hose Sizes 3/8" | 1/2" | 5/8" | 3/4" | 1" | 1-1/4" |
|---|---|---|---|---|---|---|
| EFG6K | 32-33 | 32-33 | 32-35 | 32-35 | 32-37 | 32-310L |
| EFG5K | 32-33 | 32-33 | 32-35 | 32-35 | 32-37 | 32-310L |
| EFG4K | 32-33 | 32-33 | 32-35 | 32-35 | 32-37 | 32-39 |

## For GSP (G22) & GSM (G23, G24) Couplings

| Hose Type | Hose Sizes 1-1/2" | 2" |
|---|---|---|
| EFG6K | 32-311 | 32-314 |
| EFG5K | 32-311 | 32-314 |
| EFG3K | 32-311 | 32-313 |
| G1H | 32-310(L) | 32-313 |
| G2H | 32-310(L) | 32-312 |

## For MegaCrimp® (G25) Couplings

| Hose Type | Hose Sizes 1/4" | 3/8" | 1/2" | 5/8" | 3/4" | 1" | 1-1/4" |
|---|---|---|---|---|---|---|---|
| M3K | 32-21 or 32-31 | 32-22 or 32-32 | 32-33 | 32-34 | 32-35 | 32-37 | — |
| M2T | 32-21 or 32-31 | 32-22 or 32-32 | 32-33 | 32-34 | 32-35 | 32-37 | 32-38 |
| G1 | 32-21 or 32-31 | 32-22 or 32-32 | 32-33 | 32-34 | 32-35 | 32-37 | 32-39 |
| G2 | 32-21 or 32-31 | 32-22 or 32-32 | 32-33 | 32-34 | 32-35 | 32-37 | 32-39 |

## For LifeGuard® Sleeving

| 1/4" | 3/8" | 1/2" |
|---|---|---|
| 32-3234 | 32-3335 | 32-3436 |

| 5/8" | 3/4" | 1" |
|---|---|---|
| 32-3537 | 32-3638 | 32-38311 |

For other hose and coupling configurations, reference **www.gates.com/ecrimp** or Gates crimp data manual.

## Die Sets (ordered separately)

| Die Set | 32-21 | 32-22 | 32-31 | 32-33 | 32-34 | 32-35 | 32-36 |
|---|---|---|---|---|---|---|---|
| Part No. | 78860 | 78861 | 78862 | 78863 | 78864 | 78865 | 78866 |
| Product No. | 7482-7128 | 7482-7129 | 7482-7130 | 7482-7131 | 7482-7132 | 7482-7133 | 7482-7134 |
| **Die Set** | **32-37** | **32-38** | **32-39** | **32-310L** | **32-311** | **32-312A** | **32-313** |
| Part No. | 78867 | 78868 | 78869 | 78870 | 78871 | 78872 | 78873 |
| Product No. | 7482-7135 | 7482-7136 | 7482-7137 | 7482-7138 | 7482-7139 | 7482-7140 | 7482-7141 |
| **Die Set** | **32-314** | **32-40D** | **32-41** | **32-42** | **32-43** | **32-44** | **32-46** |
| Part No. | 78874 | 78875 | 78876 | 78877 | 78878 | 78879 | 78880 |
| Product No. | 7482-7142 | 7482-7143 | 7482-7144 | 7482-7145 | 7482-7146 | 7482-7147 | 7482-7148 |
| **Die Set** | **32-81** | **32-82** | **32-83** | **32-72** | **32-84** | **32-85** | **32-86** |
| Part No. | 78881 | 78882 | 78883 | 78672 | 78884 | 78885 | 78886 |
| Product No. | 7482-7149 | 7482-7150 | 7482-7151 | 7482-7201 | 7482-7152 | 7482-7153 | 7482-7154 |
| **Die Set** | **32-331** | **32-45** | **32-3234** | **32-3335** | **32-3436** | **32-3537** | **32-3638** |
| Part No. | 78888 | 78889 | 78792 | 78790 | 78791 | 78776 | 78777 |
| Product No. | 7482-7156 | 7482-7157 | 7482-1419 | 7482-1420 | 7482-1421 | 7482-1430 | 7482-1431 |
| **Die Set** | **32-38311** | | | | | | |
| Part No. | 78786 | | | | | | |
| Product No. | 7482-1443 | | | | | | |

# GC® 96TSi™-3 CRIMPER

The GC® 96TSi™-3 crimper is capable of crimping 3" six-wire and up to 6" I.D. industrial hose. This crimper allows distributors to make reliable and professional looking assemblies providing more value to the end user. The large crimper head allows industrial hose assemblies to be made with a variety of terminations using crimpable ferrules and sleeves. The GC96TSi crimper has additional versatility since in conjunction with optional spacer dies and GC® 32 dies; it can make Gates hydraulic hose assemblies also.



**Rack and Stand not pictured, sold separately.**

### SPECIFICATIONS

**Part Number:** 78392
**Product Number:** 7480-9003
**Dimensions:** 31" high by 32" wide by 16" deep
**Weight:** 650 lbs
**Power Source:** 208-264V, 45-65 hz, single phase and 20 amp
**Capability:** 1/4"– 3" Hydraulic hose and 1/4"– 6" Industrial hose

### For GlobalSpiral™ (G20) Couplings

| | Hose Sizes | | | | | |
|---|---|---|---|---|---|---|
| **Hose Type** | **3/8"** | **1/2"** | **5/8"** | **3/4"** | **1"** | **1-1/4"** |
| EFG6K | 32-33 | 32-33 | 32-35 | 32-35 | 32-37 | 32-310L |
| EFG5K | 32-33 | 32-33 | 32-35 | 32-35 | 32-37 | 32-310L |
| EFG4K | 32-33 | 32-33 | — | 32-35 | 32-37 | 32-39 |

### For GSP (G22) & GSM (G23, G24) Couplings

| | Hose Sizes | |
|---|---|---|
| **Hose Type** | **1-1/2"** | **2"** |
| EFG6K | 32-311 | — |
| EFG5K | 32-311 | 32-314 |
| EFG3K | 32-311 | 32-313 |
| G1H | 32-310(L) | 32-313 |
| G2H | 32-310(L) | 32-312 |

### For MegaCrimp® (G25) Couplings

| | Hose Sizes | | | | | | |
|---|---|---|---|---|---|---|---|
| **Hose Type** | **1/4"** | **3/8"** | **1/2"** | **5/8"** | **3/4"** | **1"** | **1-1/4"** |
| M3K | 32-21 or 32-31 | 32-22 or 32-32 | 32-33 | 32-34 | 32-35 | 32-37 | — |
| M2T | 32-21 or 32-31 | 32-22 or 32-32 | 32-33 | 32-34 | 32-35 | 32-37 | — |
| G1 | 32-21 or 32-31 | 32-22 or 32-32 | 32-33 | 32-34 | 32-35 | 32-37 | 32-39 |
| G2 | 32-21 or 32-31 | 32-22 or 32-32 | 32-33 | 32-34 | 32-35 | 32-37 | 32-39 |

For other hose and coupling configurations, reference **www.gates.com/ecrimp** or Gates crimp data manual.

### For LifeGuard® Sleeving

| **1/4"** | **3/8"** | **1/2"** |
|---|---|---|
| 32-3234 | 32-3335 | 32-3436 |
| **5/8"** | **3/4"** | **1"** |
| 32-3537 | 32-3638 | 32-38311 |

## Die Sets (ordered separately)

| **Die Set** | **32-21** | **32-22** | **32-31** | **32-33** | **32-34** | **32-35** | **32-36** |
|---|---|---|---|---|---|---|---|
| Part No. | 78860 | 78861 | 78862 | 78863 | 78864 | 78865 | 78866 |
| Product No. | 7482-7128 | 7482-7129 | 7482-7130 | 7482-7131 | 7482-7132 | 7482-7133 | 7482-7134 |
| **Die Set** | **32-37** | **32-38** | **32-39** | **32-310L** | **32-311** | **32-312A** | **32-313** |
| Part No. | 78867 | 78868 | 78869 | 78870 | 78871 | 78872 | 78873 |
| Product No. | 7482-7135 | 7482-7136 | 7482-7137 | 7482-7138 | 7482-7139 | 7482-7140 | 7482-7141 |
| **Die Set** | **32-314** | **32-40D** | **32-41** | **32-42** | **32-43** | **32-44** | **32-46** |
| Part No. | 78874 | 78875 | 78876 | 78877 | 78878 | 78879 | 78880 |
| Product No. | 7482-7142 | 7482-7143 | 7482-7144 | 7482-7145 | 7482-7146 | 7482-7147 | 7482-7148 |
| **Die Set** | **32-81** | **32-82** | **32-83** | **32-72** | **32-84** | **32-85** | **32-86** |
| Part No. | 78881 | 78882 | 78883 | 78672 | 78884 | 78885 | 78886 |
| Product No. | 7482-7149 | 7482-7150 | 7482-7151 | 7482-7201 | 7482-7152 | 7482-7153 | 7482-7154 |
| **Die Set** | **32-331** | **32-45** | **32-3234** | **32-3335** | **32-3436** | **32-3537** | **32-3638** |
| Part No. | 78888 | 78889 | 78792 | 78790 | 78791 | 78776 | 78777 |
| Product No. | 7482-7156 | 7482-7157 | 7482-1419 | 7482-1420 | 7482-1421 | 7482-1430 | 7482-1431 |
| **Die Set** | **32-38311** | | | | | | |
| Part No. | 78786 | | | | | | |
| Product No. | 7482-1443 | | | | | | |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# SC32™ CRIMPER

The Gates SC32™ crimper is a versatile, easy-to-use, economical machine suitable for a hard-working shop environment. It is offered in 110V and 220V single phase versions to match the shop power supply. This rugged crimper is designed for continued use to meet day-to-day shop and counter needs for crimps on hose up to 1-1/4" I.D. with occasional crimps for larger assemblies up to 2", 6-spiral hose.



**Part Number:** 77500
**Product Number:** 7480-0070
Wired for 220V with 2 hp electric pump
**Power Source:** 208-230VAC, 20 amp, single phase, 60 hz
**Part Number:** 77501
**Product Number:** 7480-0071
Wired for 110V with 1 hp electric pump
**Power Source:** 115VAC, 15 amp, 60 hz

**SPECIFICATIONS**
**Dimensions:** 16.5" wide x 32" deep x 29" high
**Max. Rated Working Pressure:** 10,000 psi
**Max. Crimping Force:** 80 tons
**Weight:** 435 lbs

## SC32™ Die Selection Table

### For GlobalSpiral™ (G20) Couplings

| Hose Type | Hose Sizes 3/8" | 1/2" | 5/8" | 3/4" | 1" | 1-1/4" |
|---|---|---|---|---|---|---|
| EFG3K | 733 | 733 | 735 | 735 | 737 | — |
| EFG4K | 733 | 733 | 735 | 735 | 737 | — |
| EFG5K | 733 | 733 | 735 | 735 | 737 | 310L |

### For GSP (G22) & GSM (G23, G24) Couplings

| Hose Type | Hose Sizes 1-1/2" | 2" |
|---|---|---|
| EFG6K | 311 | — |
| EFG5K | 311 | 314 |
| EFG3K | 311 | 313 |
| G1H | 310(L) | 313 |
| G2H | 310(L) | 312 |

### For MegaCrimp® (G25) Couplings

| Hose Type | Hose Sizes 1/4" | 3/8" | 1/2" | 5/8" | 3/4" | 1" | 1-1/4" |
|---|---|---|---|---|---|---|---|
| M3K | 721 or 731 | 722 or 732 | 733 | 734 | 735 | 737 | — |
| M2T | 721 or 731 | 722 or 732 | 733 | 734 | 735 | 737 | 720 |
| G1 | 721 or 731 | 722 or 732 | 733 | 734 | 735 | 737 | 739 |
| G2 | 721 or 731 | 722 or 732 | 733 | 734 | 735 | 737 | 739 |

For other hose and coupling configurations, reference **www.gates.com/ecrimp** or Gates crimp data manual.

## Die Sets (ordered separately)

| Die Set | 721/731 | 722/732 | 733 | 734 | 735 | 737* | 720* | 739* |
|---|---|---|---|---|---|---|---|---|
| Part No. | 78943/78931 | 78944/78932 | 78933 | 78934 | 78935 | 78937 | 78920 | 78939 |
| Product No. | 7482-1217/0931 | 7482-1218/0932 | 7482-0933 | 7482-0934 | 7482-0935 | 7482-0937 | 7482-0920 | 7482-0939 |

| Die Set | SC32-310L | SC32-311 | SC32-312 | SC32-313 | SC32-314 |
|---|---|---|---|---|---|
| Part No. | 78977 | 78978 | 78979 | 78980 | 78981 |
| Product No. | 7482-1710 | 7482-1711 | 7482-1712 | 7482-1713 | 7482-1714 |

* Must Use No-Notch Die Cone.

# POLARSEAL® PORTABLE CRIMPER



**Part Number:** 77716
**Product Number:** 7480-6599

Gates PolarSeal® Portable Crimper is designed for crimping air conditioning assemblies by hand or impact wrench. The PolarSeal Portable Crimper has capability to crimp PolarSeal G45 and G47 couplings, and is intended for use with PolarSeal I and PolarSeal II refrigerant hose. Die included with the crimper have capability to crimp -6, -8, -10, and -12 PolarSeal I and PolarSeal II assemblies.

| Hose | Part Number | Color | Fitting Prefix | Die Number |
|---|---|---|---|---|
| -6 PolarSeal II | 78768 | Red | 6ACB- | 6R |
| -6 PolarSeal I, -8 PolarSeal II | 78656 | Black | 6ACA-, 8ACB- | 6-8R |
| -8 PolarSeal I | 78657 | Blue | 8ACA- | 8 |
| -10 PolarSeal II | 78769 | Almond | 10ACB- | 10R |
| -10 PolarSeal I, -12 PolarSeal II | 78658 | Green | 10ACA, 12ACB | 10-12R |
| -12 PolarSeal I | 78659 | Clear | 12ACA | 12 |

**Features:**

- Portable hand operation, easy to change over from size to size.
- Heavy-duty construction for use with air impact wrenches.
- Crimps two-braid dimension or reduced barrier hose.
- OE-style bubble crimp.
- Quick-change dies, no tools required to change sizes.
- Lightweight for easy handling, less than six pounds.
- Capable of crimping underhood air conditioning applications.
- Includes six color-coded die sets for crimping two-braid barrier hose and reduced barrier hose.
- Removable die holder accommodates complicated shapes.
- Color-coded, urethane encased dies.
- Unit can be bench-mounted.
- Shipped in a custom carrying case with instructions.
- No electrical requirements.
- Locator flag centers ferrule in dies.


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# POLARSEAL® II HOSE PLIERS



**Ratcheting Pliers**



**Straight Jaw Pliers**



**Notched Jaw Pliers**

The PolarSeal® II pliers are used to crimp the clamps on PolarSeal II (G46) couplings. The ratcheting pliers will not release until the crimp is complete guaranteeing a proper seal. The straight jaw pliers are used when there are no obstructions to hinder crimping. The notched jaw pliers are for use in tight quarters. Use the side or the front of the pliers to complete the crimp.

**Ratcheting Pliers**
**Part Number:** 77953
**Product Number:** 7369-5503

**Straight Jaw Pliers**
**Part Number:** 77952
**Product Number:** 7369-5502

**Notched Jaw Pliers**
**Part Number:** 77951
**Product Number:** 7369-5501

# HYDRAULIC HOSE REEL RACK



This sturdy and convenient rack stores three reels of hose.

**Part Number:** 78186
**Product Number:** 7484-0019
**Dimensions:** 28” wide by 30” deep by 72” high

# HYDRAULIC COUPLING CABINET

## Customized to fit all your needs!

Now even more versatile, these easy-to-assemble units are compactly designed to give you years of reliable service. Components are ordered individually by product number for easy customization.

### 1. MobileCrimp® 4-20

Pre-drilled holes in mounting shelf (item #2 below) allows easy mounting of either the Positive Stop or Digital Dial MobileCrimp® 4-20 crimper.

**Safety Hint:**

If the MobileCrimp 4-20 is mounted on top of the cabinet, you **must:**

- Use crimper mounting shelf (item #2 below)
- Bolt shelf and cabinet to wall using pre-drilled holes
- Not use the caster leg set

### 2. Mounting Shelf for MC 4-20 Crimper

**Part Number:** 78193
**Product No.** 7484-0013


### 3. Coupling Cabinet with Four Sliding Shelves (Two Shown)

**Part Number:** 78190
**Product No.** 7484-0010

Shelves slide out for easy access and can hold a combination of ten 3-1/2" wide bin boxes or five 7" wide bin boxes. Unit can be stacked and bolted together as shown in illustration. Each measures 41" wide by 12" deep by 21" high.

**Safety Hint:**

Slide open only one shelf at a time to avoid tipping.




**When assembled, the typical combination of two four-shelf coupling cabinets and stationary leg set as shown measures 41" wide by 12" deep by 48" high.**

### 4. Stationary Legs (Shown)

**Part Number:** 78191
**Product No.** 7484-0011

Allows for precise leveling.

### Heavy-Duty Caster Leg Set (Not Shown)

**Part Number:** 78192
**Product No.** 7484-0012

Set consists of four heavy-duty casters, two of which can be locked.

### 5. Bin Boxes

Order separately in whatever combination best fits your needs. Dividers come with each bin box. Each bin box has slots to allow for maximum utilization.

| Description | Part Number | Product Number |
|---|---|---|
| Ten 3.5" wide bins with 15 dividers | 78194 | 7484-0014 |
| Five 7" wide bins with 9 dividers | 78195 | 7484-0015 |
| Three dividers for 3.5" wide bin box | 78196 | 7484-0016 |
| Three dividers for 7" wide bin box | 78197 | 7484-0017 |
| Sixty dividers for 3.5" wide bin box | 78199 | 7484-0031 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# VERTICAL HYDRAULIC HOSE CABINET




**Part Number:** 78188
**Product Number:** 7484-0022

Rack up sales and get organized at the same time with a new ‘vertical’ hydraulic hose cabinet from Gates.

- Six narrow and two wide slots to stock a variety of hydraulic hose.
- Designed to support one hydraulic coupling cabinet on top for maximum efficiency.
- Optional choice for use as cabinet base with maximum of one four-drawer cabinet.
- Measures 41” wide by 12” deep (top), 36” high.
- Shown with four-drawer cabinet
  Purchase separately as:
  **Part Number:** 78190
  **Product No.:** 7484-0010

# TWO-DRAWER COUPLING CABINET



**Part Number:** 78189
**Product No.** 7484-0021

This two-drawer cabinet is ideal to add nylon air brake tubing couplings to your hydraulic inventory. This cabinet can be stacked and bolted together with your existing hydraulic cabinet. Uses the same bin boxes as listed above. Measures 41” wide by 12” deep by 11” high.

# WORK BENCH




**Part Number:** 78022
**Product Number:** 7484-0020
**Dimensions:** 36” wide by 24” deep by 36” high

This new hydraulic work bench is ideal for holding either the Power Crimp® 707 or MobileCrimp® 4-20 crimpers as well as hydraulic saws. The lower shelf can be used for storage or as shown with the pump. It is made of an angle iron frame construction with a high-density fiberboard top and welded 13-gauge steel lower shelf. All hardware is included to allow for easy assembly in about 10 minutes.

**Note:** Crimpers must be bolted down to the table top.

# HYDRAULIC COUPLING BIN



**Part Number:** 78207
**Product Number:** 7484-0007

The 24-bin cabinet is constructed of heavy gauge steel. Cabinet measures 34" wide by 12" deep by 24" high. Excellent for storing large 1-1/4" to 2" I.D. couplings.

# COUPLING BIN BOXES




**Part Number:** 78208
**Product Number:** 7484-0008

Bin boxes for hydraulic couplings. Corrugated cardboard design gives extra strength. Includes four dividers per box.
**Measures:** 5" wide by 11" deep by 4-1/2" high.

**Part Number:** 78212
**Product Number:** 7484-0009
**Measures:** 7-1/2" wide by 11" deep by 4-1/2" high

# GATES HOSE CUTTER MODEL 1.5" Two-Wire Shop Saw



**Replacement Blade**
**Part Number:** 78003
**Product Number:** 7482-1329

For two-wire braid hose through 1-1/2" I.D.
**Part Number:** 78084
**Product Number:** 7480-6607
**Clean Easy Cuts – Safe Operation**

**FEATURES:**

- Cuts up to 1-1/2" I.D. two-wire braid hose and 1" four-wire spiral hose.
- Designed to operate on standard 20 amp service.
- Reversible 8" scalloped-edge, high-speed steel blade with 5/8" bore can be sharpened.
- Radius hose feed into blade for safety and reduced friction.
- Inner blade guard for safe operation.

**SPECIFICATIONS**
**Power Source:** 1-1/2 hp (2.6 hp peak), 115V, 60 hz, 15 amp motor with power cord and plug.
**Dimensions:** 13" wide by 24" deep by 17" high.
**Weight:** 151 lbs

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# GATES 28VDC PORTABLE HYDRAULIC HOSE SAW



**Part Number:** 78394
**Product Number:** 7480-6610

**FEATURES:**

- Battery power provides unmatched portability. Uses the same Milwaukee M28 battery as the GC® 16XD™ Crimper Battery Pump. Battery sold separately.
- Cuts up to 1”, 4-spiral hose.
- Safety “C” clamp secures saw in cutting position.
- Quick adjusting locator pins make changing hose sizes easy.


**SPECIFICATIONS**

**Dimensions:** 12” wide by 8” deep by 19” high
**Weight:** 16 lbs
**Wheel Type:** Abrasive
**Wheel Diameter:** 6”
**No Load RPM:** 8000
**Arbor:** 7/8”
**Spindle Thread Size:** 5/8”-11”
**Switch Type:** Slide
**Soft Start:** Large Spindle Lock

**Battery Included:** No
**Battery Type:** LI-ION
**Battery Voltage:** 28V
**Battery Capacity:** 3.0AH
**Series:** M28™
**Battery Pack Replacement:** 5AB52

M28™ is a trademark of Milwaukee Tools.

# GATES POWER CUTTER 208



**Caution:** Keep blade sharp. Heat generated by a dull blade can damage steel and flare the hose.

**BLADE SPECIFICATION**
**Blade Dimensions:** 12” by 1/8”
**Scalloped Replacement**
**Part Number:** 78009
**Product Number:** 7482-0983

**Optional Abrasive**
**Part Number:** 78011
**Product Number:** 7482-0426

**Part Number:** 78028
**Product Number:** 7480-6609


**Effortless Straight Cuts Every Time**
- Clear face shield for added safety.
- Powerful high torque, 4.5 horsepower peak motor that makes cutting faster and easier.
- Includes scalloped, 12” blade to dissipate heat, reducing friction for clean, faster cuts up to 1-1/4” I.D.
- Optional abrasive blade for continuous use with 1-1/4” I.D. and larger spiral-wire reinforced hose.
- Safely cuts two and four-wire hose through 2”, six-wire hose through 1-1/4”.
- Reversible blade can be sharpened; removal and installation is easy.
- Cuts small 3/16” I.D. hose and handles the tough job including 2” I.D. spiral-wire hose.*
- Easy to use, front face plate with moveable pins holds hose securely for a clean straight cut.
- Sturdy blade guard shields blade for safety.
- Permanent mounting brackets (included) to attach saw to table.

*Optional abrasive blade preferred for cutting spiral-wire hose, larger than 1-1/4” I.D.

**CUTTER SPECIFICATIONS**
**Shaft/Arbor Hole Diameter:** 1”
**Power Source:** 4.5 hp peak, 115/50/60 hz, 20 amp
**No Load Speed:** 3,500 rpm
**Dimensions:** 22-1/2” wide by 18-1/4” deep by 23-1/2” high
**Weight:** 83.4 lbs

# GATES HOSE CUTTER MODEL 2" Six-Wire Shop Saw

For six-wire spiral and two-wire braid hose through 2” I.D.



**SPECIFICATIONS**
**Dimensions:** 22” wide by 42” deep by 24” high
**Weight:** 195 lbs

**Replacement Blade**
**Part Number:** 78003
**Product Number:** 7482-1329

**Part Number:** 78083
**Product Number:** 7480-6606
**Clean Easy Cuts – Safe Operation**


**FEATURES:**
- Cuts up to 2” I.D. two-wire braid through six-spiral reinforced hose.
- Reversible 10” scalloped-edge, high-speed steel blade with 3/4” bore, can be sharpened.
- Radius hose feed into blade for safety and reduced friction.
- Inner blade guard for safe operation.
- **Includes Coolant Spray System Kit** for reduced heat in high-capacity cutting applications (recommended for multi-braid and spiral reinforced hose). Kit includes reservoir, spray nozzle and mounting hardware.
- **Power cord not included.**

**Power Source:** 3 hp (5.2 hp peak), Single phase, 230V, 60 hz, 20 amp motor

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# GATES HS-1 HAND SWAGER




**Part Number:** 78080
**Product Number:** 7483-1000


Produces top quality assemblies using Gates 1/8” (-2) and 3/16” (-3) thermoplastic hydraulic hose with Gates PCTS couplings and Gates C14 PTFE hose and couplings 3/16 (-4) through 7/8 (-16).

Simply insert the assembly into the swager from the bottom, place dies around the coupling, and pump the handle.

A six-ton jack then goes to work and the swage is completed. Positive dies ensure a correct swage every time. The perfectly swaged assembly is removed and you are ready to repeat the process. Pushers and dies must be ordered separately.

**SPECIFICATIONS**
**Dimensions:** 15” wide by 7” deep by 19-1/2” high
**Weight:** 41 lbs

# HAND-HELD HOSE CUTTER



**Part Number:** 91153
**Product Number:** 7469-0153

Makes clean cuts—no ragged edges. Cuts most non-metal reinforced rubber hose. Excellent for cutting textile-reinforced hose.

**FEATURES:**
- Lightweight with nylon handles.
- Blade closes into handle for safety.
- Cutter and blades packaged individually on shrink-wrapped cards.


**Replacement Blade**
**Part Number:** 91154
**Product Number:** 7469-0154

# SWAGER CONVERSION KIT FOR THE POWER CRIMP® 707

Produces top quality assemblies using Gates 1/8” and 3/16” thermoplastic hydraulic hose with Gates PCTS couplings and Gates C14 PTFE hose and couplings. Easily converts the Power Crimp 707 to a power swager.


| Description | Part Number | Product Number |
|---|---|---|
| Complete Kit | 78081 | 7480-0040 |
| Collar | 78820 | 7482-0429 |
| Die Cone | 78821 | 7482-0430 |
| Adapter | 78824 | 7482-0433 |
| Actuator Rod | 78753 | 7482-0482 |
| 1/2” Spacer Ring | 78184 | 7482-1253 |

Dies and pushers must be ordered separately. See Swage Data Chart in Gates Crimp Data Manual for details.



# C14 HOSE INSERTION DIE HOLDER FOR USE WITH HOSE INSERTION DIES


Required for inserting hose into ferrule on all sizes. Use the fixture (see photo) to mount the Hose Insertion Die Holder onto a bench top to aid in the assembly of Gates C14 hose. Each item listed in the next page must be ordered separately.



**Hose Insertion Die Holder**
**Part Number:** 78518
**Product Number:** 7483-0510


**Hose Insertion Fixture**
**Part Number:** 78517
**Product Number:** 7483-0511

## C14 HOSE INSERTION DIES



Used to guide the hose into the ferrule when used with the Hose Insertion Die Holder. One set required for each hose size. See product numbers listed in Gates Crimp Data and Dies Manual.

## C14 HOSE EXPANDERS




Used to expand the hose and round out the tube after cutting and to insert the stem into the hose. One expander required for each hose size. See product numbers listed in Gates Crimp Data and Dies Manual.

## C14 SWAGE PUSHERS



Specially designed to accommodate Gates C14 couplings. They protect the threads and bottom out on the dies to complete the swage. Use the C14 Swage Data Chart in Gates Crimp Data and Dies Manual to determine the proper pushers.

## C14 SWAGE DIES



Specifically designed to swage Gates C14 hose assemblies. They provide the required swage dimensions to meet full performance. One die set is required for each hose size. See product numbers listed in Gates Crimp Data and Dies Manual.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# PUSHERS AND DIES FOR C14 HOSE AND COUPLINGS

## C14 Swage Pushers

| Description | Part Number | Product Number |
|---|---|---|
| P-C14-4FJSX | 78500 | 7483-0536 |
| P-C14-5FJSX | 78501 | 7483-0537 |
| P-C14-6FJX | 78502 | 7483-0538 |
| P-C14-6FSX | 78503 | 7483-0539 |
| P-C14-8FJSX | 78504 | 7483-0540 |
| P-C14-10FJSX | 78505 | 7483-0541 |
| P-C14-12FJX | 78506 | 7483-0542 |
| P-C14-12FSX | 78507 | 7483-0543 |
| P-C14-16FJSX | 78508 | 7483-0544 |
| P-C14-2MP | 78510 | 7483-0550 |
| P-C14-4MP | 78511 | 7483-0545 |
| P-C14-6MP | 78512 | 7483-0546 |
| P-C14-8MP-8 &10ABC | 78513 | 7483-0547 |
| P-C14-12MP-12ABC | 78514 | 7483-0548 |
| P-C14-16MP | 78515 | 7483-0549 |
| P-C14-4TUBE | 78548 | 7483-0530 |
| P-C14-5TUBE | 78549 | 7483-0531 |
| P-C14-6TUBE | 78550 | 7483-0532 |
| P-C14-8TUBE | 78551 | 7483-0533 |
| P-C14-10TUBE | 78552 | 7483-0534 |
| P-C14-12TUBE | 78553 | 7483-0521 |
| P-C14-12TUBE-JS | 78554 | 7483-0522 |
| P-C14-16TUBE-JS | 78555 | 7483-0580 |
| P-C14-6TBFLX | 78565 | 7483-0552 |
| P-C14-12TBFLX | 78568 | 7483-0553 |
| P-C14-16TBFLX | 78569 | 7483-0554 |

## C14 Hose and Expanders

| Description | Part Number | Product Number |
|---|---|---|
| HE-4C14 | 78530 | 7483-0555 |
| HE-5C14 | 78531 | 7483-0556 |
| HE-6C14 | 78532 | 7483-0557 |
| HE-8C14 | 78533 | 7483-0558 |
| HE-10C14 | 78534 | 7483-0559 |
| HE-12C14 | 78535 | 7483-0560 |
| HE -16C14 | 78536 | 7483-0561 |

## C14 Hose Insertion Dies

| Description | Part Number | Product Number |
|---|---|---|
| HD-4C14 | 78521 | 7483-0503 |
| HD-5C14 | 78522 | 7483-0504 |
| HD-6C14 | 78523 | 7483-0505 |
| HD-8C14 | 78524 | 7483-0506 |
| HD-10C14 | 78525 | 7483-0507 |
| HD-12C14 | 78526 | 7483-0508 |
| HD-16C14 | 78527 | 7483-0509 |

## C14 Swage Dies

| Description | Part Number | Product Number |
|---|---|---|
| SD-4C14 | 78539 | 7483-0513 |
| SD-5C14 | 78540 | 7483-0514 |
| SD-6C14 | 78541 | 7483-0515 |
| SD-8C14 | 78542 | 7483-0516 |
| SD-10C14 | 78543 | 7483-0517 |
| SD-12C14 | 78544 | 7483-0518 |
| SD-16C14 | 78545 | 7483-0519 |

# C14 HOSE CUTTING SHEAR RECOMMENDED FOR C14 PTFE HOSE



**Part Number:** 78006
**Product Number:** 7480-6596

This cutting shear handles Gates C14 PTFE hose up through 1” without requiring pre-taping of the hose. The shear is fast and easy to use and results in a very clean cut.
**Weight:** 23 lbs
**Dimensions:** 9” wide by 14” deep by 15” high. 30” handle.

# MEGACRIMP® COUPLING INSERTION TOOL



**Part Number:** 78017
**Product Number:** 7482-1342

Offers an easy way to confirm the right insertion depth for all Gates wire-braid hydraulic hose. To use, simply insert the hose into its proper slot indicated by dash size, push it all the way in, check for square cut (maximum allowable angle of cut is five degrees), then mark the insertion depth on the hose.

# LOCK-ON TOOL



**Part Number:** 78050
**Product Number:** 7480-0100

This hand-operated coupling machine, made of rugged cast iron and steel construction, eliminates the hard work of manually pushing stems into hose. It comes complete with mandrels for 1/4”, 3/8”, 1/2”, 5/8” and 3/4” I.D. sizes of lock-on couplings.

# HAND-OPERATED HOSE PERFORATOR TOOL



These hose perforators have needle-studded wooden rollers which perforate the covers of non-skive wire braid hose used in high pressure inert gas applications. They are hand-operated so the operator can control the degree of perforation in the hose cover.

**1-1/4” Hose Perforator for 3/16” to 3/4” I.D. Hose**
**Part Number:** 78070
**Product Number:** 7482-6565
**Dimensions:** 2-1/2” O.D. roller by 1-1/4” wide by 8” OAL.
**Weight:** 1 lb

**3” Hose Perforator for 1” to 2” I.D. Hose**
**Part Number:** 78071
**Product Number:** 7482-6566
**Dimensions:** 3-3/4” O.D. roller by 3” wide by 9-1/2” OAL.
**Weight:** 2 lbs

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# MEGACLEAN™ SYSTEM

Used to remove dirt from the inside out with the help of pressurized launchers and compatible nozzles. Gates MegaClean™ foam projectiles sweep through the inside surface of the hose, taking fine particles of loose dirt and other contaminants with them. At 20–30 percent larger than the hose I.D., these projectiles leave nothing behind but a hose that truly is clean from the inside out.

## MegaClean MC-K32 Kit

**Part Number:** MC-K32
**Product Number:** 7467-0001

- MCL-32 Hand Launcher (Including “Rotary” Plug & Coupler)
- MC-GAR-1 Adapter Ring (-4 thru -20)
- LC32 Carrying & Storage Case
- Hose Nozzles GH-04, GH-05, GH-06, GH-08, GH-10, GH-12, GH-16, GH-20, GH-24, GH-32
- JIC Assembly Nozzles GA-04, GA-06, GA-08, GA-10, GA-12, GA-16, GA-20, GA-24, GA-32
- GA-04-FFORX Nozzle
- MC-32 Launcher Stand
- 1 Projectile Catcher Bucket
- 1 Bag of Projectiles Listed in Chart Below




## MegaClean MC-K20 Kit (Hose ¼” – 1¼”)

**Part Number:** MC-K20
**Product Number:** 7467-0002

- MCL-20 Hand Launcher
- Female Quick-Release Coupler
- LC20 Carrying & Storage Case
- GH-04, GH-05, GH-06, GH-08, GH-10, GH-12, GH-16, GH-20 Hose Nozzles
- 1 Projectile Catcher Bucket
- 1 Bag of Projectiles Listed in Chart Below

## MegaClean Projectiles Included in Kits

| Part Number | Product Number | MC-K32 | MC-K20 | Bag Quantity |
|---|---|---|---|---|
| MC-HAP-04-1 | 7467-50005 | X | X | 100 |
| MC-HP-04 | 7467-50025 | X | X | 100 |
| MC-HAP-06 | 7467-50035 | X | X | 100 |
| MC-HP-06 | 7467-50045 | X | X | 100 |
| MC-HAP-08 | 7467-50055 | X | X | 100 |
| MC-HP-08 | 7467-50065 | X | X | 100 |
| MC-HP-08-1 | 7467-50075 | X | X | 50 |
| MC-HP-10 | 7467-50085 | X | X | 50 |
| MC-HP-12 | 7467-50105 | X | X | 50 |
| MC-HP-16 | 7467-50135 | X | X | 40 |
| MC-HP-20 | 7467-50155 | X | X | 30 |
| MC-HP-24 | 7467-50175 | X | | 20 |
| MC-HP-32 | 7467-50195 | X | | 15 |

## How it works:



**Step 1**



**Step 2**

# MegaClean™ System Replacement Projectiles

| Description | Product Number | Part Number |
|---|---|---|
| MegaClean HAP-04-1 Assembly Projectile (100 ea) | 7467-50005 | MC-HAP-04-1 |
| MegaClean HAP-04 Assembly Projectile (100 ea) | 7467-50015 | MC-HAP-04 |
| MegaClean HP-04 Hose Projectile (100 ea) | 7467-50025 | MC-HP-04 |
| MegaClean HAP-06 Assembly Projectile (100 ea) | 7467-50035 | MC-HAP-06 |
| MegaClean HP-06 Hose Projectile (100 ea) | 7467-50045 | MC-HP-06 |
| MegaClean HAP-08 Assembly Projectile (100 ea) | 7467-50055 | MC-HAP-08 |
| MegaClean HP-08 Hose Projectile (100 ea) | 7467-50065 | MC-HP-08 |
| MegaClean HP-08-1 Hose Projectile (50 ea) | 7467-50075 | MC-HP-08-1 |
| MegaClean HP-10 Hose Projectile (50 ea) | 7467-50085 | MC-HP-10 |
| MegaClean HP-10-1 Hose Projectile (50 ea) | 7467-50095 | MC-HP-10-1 |
| MegaClean HP-12 Hose Projectile (50 ea) | 7467-50105 | MC-HP-12 |
| MegaClean HP-12-1 Hose Projectile (40 ea) | 7467-50115 | MC-HP-12-1 |
| MegaClean HP-14 Hose Projectile (40 ea) | 7467-50125 | MC-HP-14 |
| MegaClean HP-16 Hose Projectile (40 ea) | 7467-50135 | MC-HP-16 |
| MegaClean HP-16-1 Hose Projectile (30 ea) | 7467-50145 | MC-HP-16-1 |
| MegaClean HP-20 Hose Projectile (30 ea) | 7467-50155 | MC-HP-20 |
| MegaClean HP-20-1 Hose Projectile (20 ea) | 7467-50165 | MC-HP-20-1 |
| MegaClean HP-24 Hose Projectile (20 ea) | 7467-50175 | MC-HP-24 |
| MegaClean HP-24-1 Hose Projectile (15 ea) | 7467-50185 | MC-HP-24-1 |
| MegaClean HP-32 Hose Projectile (15 ea) | 7467-50195 | MC-HP-32 |
| MegaClean HP-32-1 Hose Projectile (10 ea) | 7467-50205 | MC-HP-32-1 |
| MegaClean HP-40 Hose Projectile (10 ea) | 7467-50215 | MC-HP-40 |
| MegaClean HP-48 Hose Projectile (10 ea) | 7467-50225 | MC-HP-48 |
| MegaClean HP-56 Hose Projectile (10 ea) | 7467-50235 | MC-HP-56 |
| MegaClean HP-64 Hose Projectile (10 ea) | 7467-50245 | MC-HP-64 |

| Description – Bulk Pack | Product Number | Part Number |
|---|---|---|
| MegaClean HAPB-04-1 Assembly Projectile Bulk (10000 ea) | 7467-5000 | MC-HAPB-04-1 |
| MegaClean HAPB-04 Assembly Projectile Bulk (10000 ea) | 7467-5001 | MC-HAPB-04 |
| MegaClean HPB-04 Assembly Projectile Bulk (10000 ea) | 7467-5002 | MC-HPB-04 |
| MegaClean HAPB-06 Assembly Projectile Bulk (10000 ea) | 7467-5003 | MC-HAPB-06 |
| MegaClean HPB-06 Hose Projectile Bulk (10000 ea) | 7467-5004 | MC-HPB-06 |
| MegaClean HAPB-08 Assembly Projectile Bulk (10000 ea) | 7467-5005 | MC-HAPB-08 |
| MegaClean HPB-08 Hose Projectile Bulk (10000 ea) | 7467-5006 | MC-HPB-08 |
| MegaClean HPB-08-1 Hose Projectile Bulk (9000 ea) | 7467-5007 | MC-HPB-08-1 |
| MegaClean HPB-10 Hose Projectile Bulk (7000 ea) | 7467-5008 | MC-HPB-10 |
| MegaClean HPB-10-1 Hose Projectile Bulk (5500 ea) | 7467-5009 | MC-HPB-10-1 |
| MegaClean HPB-12 Hose Projectile Bulk (4000 ea) | 7467-5010 | MC-HPB-12 |
| MegaClean HPB-12-1 Hose Projectile Bulk (3800 ea) | 7467-5011 | MC-HPB-12-1 |
| MegaClean HPB-14 Hose Projectile Bulk (3500 ea) | 7467-5012 | MC-HPB-14 |
| MegaClean HPB-16 Hose Projectile Bulk (2000 ea) | 7467-5013 | MC-HPB-16 |
| MegaClean HPB-16-1 Hose Projectile Bulk (1900 ea) | 7467-5014 | MC-HPB-16-1 |
| MegaClean HPB-20 Hose Projectile Bulk (1500 ea) | 7467-5015 | MC-HPB-20 |
| MegaClean HPB-20-1 Hose Projectile Bulk (1200 ea) | 7467-5016 | MC-HPB-20-1 |
| MegaClean HPB-24 Hose Projectile Bulk (650 ea) | 7467-5017 | MC-HPB-24 |
| MegaClean HPB-24-1 Hose Projectile Bulk (600 ea) | 7467-5018 | MC-HPB-24-1 |
| MegaClean HPB-32 Hose Projectile Bulk (450 ea) | 7467-5019 | MC-HPB-32 |
| MegaClean HPB-32-1 Hose Projectile Bulk (360 ea) | 7467-5020 | MC-HPB-32-1 |




**Step 3**



**Step 4**



**Step 5**



**Step 6**

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Gates Bend-N-Fit™ Tube Bender



**Part Number:** 91025
**Product Number:** 7468-1040


Simply and easily duplicates bent tubes:

- Power Steering
- Air Conditioning
- Transmission Oil Cooler
- Fuel Lines
- Plus many more applications
- See assembly fabrication section for details

Bends SAE tubing as well as metric tubing – without changing any tooling – in the following sizes:
1/4" 5/16" 3/8" 1/2" 6mm-13mm

## Easy One-handed Operation

- Load tubing by pushing in on Tubing Lock Release.
- Pull down on Tubing Lock.
- Load tubing into proper size bending slot.
- Close Tubing Lock until it snaps into place. (Tubing Lock must snap for the tube to be firmly supported and for the tube to bend properly.)
- Close the tube support slide onto the tube.



**Tubing Lock** **Tubing Lock Release**

Top of bender is segmented into 7 1/2° marks. This aids in precision bends. Original tube can be used as a pattern by measuring bends or by holding old tube above bender.



**IMPORTANT:** Be sure the mark on the tube support slide lines up with the zero on the top of the bender. Not lining up with zero will cause notching or creasing of the tube.



- Push handle sliding Tube Support Slide across tube to make your bend.
- Once you've made your first bend, rotate handle out of your way.
- Push in on Tubing Lock Release.
- Pull down on Tubing Lock.
- Remove tubing and reorient for next bend.
- Both the Tube Slide and Tube Lock move completely out of the way. This allows for bends in multiple planes.



# SEVEN EASY STEPS FOR SELECTING THE PROPER HOSE

An effective way to remember hose selection criteria is to remember the word...

**STAMPED**

**S** = Size

**T** = Temperature

**A** = Application

**M** = Material to be conveyed

**P** = Pressure

**E** = Ends or couplings

**D** = Delivery (volume and velocity)

## 1. Hose Size (Dash Numbers)

The inside diameter of the hose must be adequate to keep pressure loss to a minimum and avoid damage to the hose due to heat generation or excessive turbulence. See hose sizing Nomographic Chart.

To determine the replacement hose size, read the layline printed on the side of the original hose. If the original hose layline is painted over or worn off, the original hose must be cut and the inside diameter measured for size.

**NOTE: Before cutting an original hose assembly, measure the overall assembly length and fitting orientation. These measurements will be required to build the replacement assembly.**

The hydraulics industry has adopted a measuring system called Dash Numbers to indicate hose and coupling size. The number which precedes the hose or coupling description is the dash size (see table). This industry standard number denotes hose I.D. in sixteenths of an inch. (The exception to this is the SAE100R5 hose C5CXH, C5C, C5D, C5E, C5M as well as, C14 and AC134a, where dash sizes denote hose I.D. equal to equivalent tube O.D.) See chart to the right. Hose O.D. can be a critical factor when hose routing clamps are used or hose are routed through bulkheads. Check individual hose specification tables for O.D.'s.

| | Hose I.D. | | | |
|---|---|---|---|---|
| | All Except C5 Series, C14 and PolarSeal (true bore) | | C5 Series, C14 and PolarSeal (tube bore) | |
| Dash No. | Inches | Millimeters | Inches | Millimeters |
| -2 | 1/8 | 3.2 | – | – |
| -3 | 3/16 | 4.8 | – | – |
| -4 | 1/4 | 6.4 | 3/16 | 4.8 |
| -5 | 5/16 | 7.9 | 1/4 | 6.4 |
| -6 | 3/8 | 9.5 | 5/16 | 7.9 |
| -8 | 1/2 | 12.7 | 13/32 | 10.3 |
| -10 | 5/8 | 15.9 | 1/2 | 12.7 |
| -12 | 3/4 | 19.0 | 5/8 | 15.9 |
| -14 | 7/8 | 22.2 | – | – |
| -16 | 1 | 25.4 | 7/8 | 22.2 |
| -20 | 1-1/4 | 31.8 | 1-1/8 | 28.6 |
| -24 | 1-1/2 | 38.1 | 1-3/8 | 34.9 |
| -28 | 1-3/4 | 44.5 | – | – |
| -32 | 2 | 50.8 | 1-13/16 | 46.0 |
| -36 | 2-1/4 | 57.6 | – | – |
| -40 | 2-1/2 | 63.5 | 2-3/8 | 60.3 |
| -48 | 3 | 76.2 | – | – |
| -56 | 3-1/2 | 88.9 | – | – |
| -64 | 4 | 101.6 | – | – |
| -72 | 4-1/2 | 115.2 | – | – |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

### 2. Temperature

When selecting a replacement assembly, two areas of temperature must be considered. These are fluid temperature and ambient temperature. The hose selected must be capable of withstanding the minimum and maximum temperature seen by the system. Care must be taken when routing near hot manifolds and in extreme cases a heat shield may be advisable. See the Gates Hydraulic Hose Selection Guide; Hose Specification Pages; and/or the Additional Temperature Limits for Gates Hydraulic Hose Chart for temperature ranges and limits for water, water/oil emulsions and water/glycol solutions.

### 3. Application

Determine where or how the replacement hose or assembly is to be used. Most often only a duplicate of the original hose will have to be made. To fulfill the requirements of the application, additional questions may need to be answered, such as:

- Where Will Hose be Used?
- Fluid and/or Ambient Temperature?
- Hose Construction?
- Equipment Type?
- Fluid Compatibility?
- Thread End Connection Type?
- Working and Surge Pressures?
- Environmental Conditions?
- Permanent or Field Attachable Couplings?
- Suction Application?
- Routing Requirements?
- Thread Type?
- Government and Industry Standards Being Met?
- Unusual Mechanical Loads?
- Minimum Bend Radius?
- Non-Conductive Hose Required?
- Excessive Abrasion?

### 4. Material to be Conveyed

Some applications require specialized oils or chemicals to be conveyed through the system. Hose selection must ensure compatibility of the hose tube, cover, couplings and o-rings with the fluid used. Additional caution must be exercised in hose selection for gaseous applications such as refrigerants and LPG.

**NOTE: All block type couplings contain nitrile o-rings (unless otherwise noted) which must be compatible with the fluids being used.**

### 5. Pressure

Most important in the hose selection process is knowing system pressure, including pressure spikes. Published working pressures must be equal to or greater than the system pressure. Pressure spikes greater than the published working pressure will shorten hose life and must be taken into consideration. Gates **DOES NOT** recommend using hose on applications having pressure spikes greater than published working pressures of the hose.

### 6. Ends of Couplings

Identify end connections using Gates coupling templates and measuring tools or Coupling Identification section. Once thread ends have been identified, consult the appropriate section of the catalog for specific part number selection.

### 7. Delivery (Volume and Velocity)

If the same I.D. of the original hose is used, assume the system is properly sized to efficiently transport fluid. If the system is new or altered, determine the hose I.D. needed to transport required fluid volume flow by using the Nomographic Chart.

The characteristics shown below are for the normal or usual range of these specific stocks. Stocks can be changed somewhat through different compounding to meet the requirements of specialized applications.

Tube and cover stocks may occasionally be upgraded to take advantage of improved materials and technology.

For detailed information on a specific hose tube or cover stock, check the Chemical Resistance Table and also the specific hose page.

| | Polychloroprene | Nitrile | Nylon | CSM | EPDM | CPE | PTFE |
|---|---|---|---|---|---|---|---|
| Flame Resistance | Very Good | Poor | Good | Good | Poor | Good | Good |
| Petroleum Base Oils | Good | Excellent | Good to Excellent | Good | Poor | Very Good | Excellent |
| Diesel Fuel | Fair to Good | Good to Excellent | Good to Excellent | Good | Poor | Good | Excellent |
| Resistance to Gas Permeation | Good | Good | Good To Excellent | Good to Excellent | Fair to Good | Good | Good to Excellent |
| Weather | Good to Excellent | Poor | Excellent | Very Good | Excellent | Good | Excellent |
| Ozone | Good to Excellent | Poor for Tube; Good For Cover | Excellent | Very Good | Outstanding | Good | Excellent |
| Heat | Good | Good | Good | Very Good | Excellent | Excellent | Excellent |
| Low Temperature | Fair to Good | Poor to Fair | Excellent | Poor | Good to Excellent | Good | Excellent |
| Water-Oil Emulsions | Excellent | Excellent | Good to Excellent | Good | Poor | Excellent | Excellent |
| Water/Glycol Emulsions | Excellent | Excellent | Excellent | Excellent | Excellent | Excellent | Excellent |
| Diesters | Poor | Poor | Excellent | Fair | Excellent | Very Good | Excellent |
| Phosphate Esters | Fair (For Cover) | Poor | Excellent | Fair | Very Good | Very Good | Excellent |
| Phosphate Ester Base Emulsions | Fair (For Cover) | Poor | Excellent | Fair | Very Good | Very Good | Excellent |

# COVER ABRASION RESISTANCE

These comparisons are based on test results per ISO 6945 abrasion testing. The table shows the expected number of times of extended cover service life as compared to a standard cover.

| | Modified Nitrile (Standard cover) | Nylon Sleeve | XtraTuff® | MegaTuff® |
|---|---|---|---|---|
| Relative Abrasion Resistance | 1 | 15 X Standard Cover | 25 X Standard Cover | 300 X Standard Cover |

# GATES HYDRAULIC HOSE SELECTION GUIDE

| Standard Industry Specification | Gates Description | Construction (Reinforcement) | Use | Stock | |
|---|---|---|---|---|---|
| | | | | Tube Name | Cover Name |
| Gates Proprietary Design | G8K | 6-spiral, wire | Ultra High Pressure & Impulse Cycle Life, High Temperature, Petroleum Oils | Polychloroprene | Polychloroprene |
| ISO 3862 R15<br>SAE 100R15<br>EN 856<br>4SP/4SH | EFG6K | 4 & 6-spiral, wire | Extremely High Pressure & Impulse Cycle Life, High Temperature, Petroleum Oils, Environmental Fluids | Nitrile | Polychloroprene |
| | EFG6K-MTF | 4 & 6-spiral, wire | Extremely High Abrasion Resistant, Pressure & Impulse Cycle Life, High Temperature, Petroleum Oils, Environmental Fluids | Nitrile | MegaTuff |
| ISO 18752 Grade D<br>ISO 3862 R13<br>SAE 100R13<br>EN 856 4SH/4SP<br>EN 856 R13 | EFG5K | 4 & 6-spiral, wire | Extremely High Pressure & Impulse Cycle Life, High Temperature, Petroleum Oils, Environmental Fluids | Nitrile | Polychloroprene |
| | EFG5K-MTF | 4 & 6-spiral, wire | Extremely High Abrasion Resistant, Pressure & Impulse Cycle Life, High Temperature, Petroleum Oils, Environmental Fluids | Nitrile | MegaTuff |
| ISO 18752<br>SAE J517 100R13 | ID5K | 4-spiral, wire | Extremely High-Pressure, High-Impulse Applications | HNBR | Polychloroprene |
| ISO 18752 Grade D<br>ISO 3862 R12<br>SAE 100R12<br>EN 856 R12 | EFG4K | 4-spiral, wire | Very High Pressure & Impulse Cycle Life, High Temperature, Petroleum Oils, Environmental Fluids | Nitrile | Polychloroprene |
| | EFG4K-MTF | 4-spiral, wire | Extremely High Abrasion Resistant, Very High Pressure & Impulse Cycle Life, High Temperature, Petroleum Oils, Environmental Fluids | Nitrile | MegaTuff |
| | EFG4K-XTF | 4-spiral, wire | High Abrasion Resistant, Pressure & Impulse Cycle Life, High Temperature, Petroleum Oils, Environmental Fluids | Nitrile | XtraTuff Nitrile |
| ISO 18752 Grade D<br>ISO 3862 R12<br>SAE 100R12<br>EN 856 4SP<br>EN 856 R12 | EFG3K | 4-spiral, wire | Very High Pressure & Impulse Cycle Life, High Temperature, Petroleum Oils, Environmental Fluids | Nitrile | Polychloroprene |
| | EFG3K-MTF | 4-spiral, wire | Extremely High Abrasion Resistant, Very High Pressure & Impulse Cycle Life, High Temperature, Petroleum Oils, Environmental Fluids | Nitrile | MegaTuff |
| Gates Proprietary Design | M6K | 2-braid, wire | High Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | Nitrile + PVC |
| Gates Proprietary Design<br>ISO 18752 Grade B | M5K | 2-braid, wire | High Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | Nitrile + PVC and Polychloroprene |
| | M5K-MTF | 2-braid, wire | Extremely High Abrasion Resistant, High Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | MegaTuff |
| | M5K-XTF | 2-braid, wire | High Abrasion Resistant, Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | XtraTuff Nitrile |
| ISO 18752 Grade B<br>ISO 11237 R19<br>SAE 100R19 | M4K | 2-braid, wire | High Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | Nitrile + PVC |
| | M4K-MTF | 2-braid, wire | Extremely High Abrasion Resistant, High Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | MegaTuff |
| | M4K-XTF | 2-braid, wire | High Abrasion Resistant, Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | XtraTuff Nitrile |
| ISO 18752 Grade C<br>ISO 11237 R19<br>SAE 100R19 | M4KH | 2-braid, wire | High Temperature, Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | Polychloroprene |
| | M4KH-MTF | 2-braid, wire | Extremely High Abrasion Resistant, High Temperature, Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | MegaTuff |
| ISO 18752 Grade B<br>ISO 11237 R17<br>SAE 100R17<br>EN 857 1SC | M3K | 1 & 2-braid, wire | High Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | Nitrile + PVC |
| | M3K-MTF | 1 & 2-braid, wire | Extremely High Abrasion Resistant, High Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | MegaTuff |
| | M3K-XTF | 1 & 2-braid, wire | High Abrasion Resistant, Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | XtraTuff Nitrile |
| ISO 18752 Grade C<br>ISO 11237 R17<br>SAE 100R17<br>EN 857 1SC | M3KH | 1 & 2-braid, wire | High Temperature, Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | Polychloroprene |
| | M3KH-MTF | 1 & 2-braid, wire | Extremely High Abrasion Resistant, High Temperature, Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | MegaTuff |
| SAE 100R16<br>SAE 100R2 Performance | MXT | High-tensile steel wire braid | High Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | Nitrile + PVC |
| ISO 11237 2SC R16<br>ISO 1436 2SN R2<br>EN 857 2SC<br>EN 853 2SN<br>SAE 100R16<br>SAE 100R2 | M2T® | 2-braid, wire | High Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | Nitrile + PVC |
| | M2T®-MTF | 2-braid, wire | Ultra High Abrasion Resistant, High Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | MegaTuff |
| | M2T®-XTF | 2-braid, wire | High Abrasion Resistant, Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | XtraTuff Nitrile |
| Exceeds ISO/DIS 1436<br>SAE 100R16<br>EN 857 2SC | CM2TDL-XTF | 2-braid, wire | High Pressure, Impulse Cycle Life & Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | XtraTuff Nitrile |
| ISO 1436 2SN R2<br>SAE 100R2 Type AT<br>EN 853 2SN | G2 | 2-braid, wire | High Pressure, Petroleum Oils & Environmental Fluids | Nitrile | Nitrile + PVC |
| | G2L | 2-braid, wire | High Pressure, Low Temperature, Petroleum Oils & Environmental Fluids | Nitrile | Polychloroprene |
| | G2XH | 2-braid, wire | Extremely High Heat, High Pressure, Petroleum Oils & Environmental Fluids | CPE | CSM |
| ISO 1436 2SN R2<br>SAE 100R2 Type AT<br>EN 853 2SN | G2H | 2-braid, wire | High Pressure, Temperature, Petroleum Oils & Environmental Fluids | Nitrile | CSM |
| | G2H-MTF | 2-braid, wire | High Pressure, Temperature, Petroleum Oils & Environmental Fluids | Nitrile | MegaTuff |
| Gates Proprietary Design | M-XP | 2-braid, wire | High Pressure & Impulse Cycle Life, High Flexibility, Tight Bend Radius, Petroleum Oils, Environmental Fluids | Nitrile | Nitrile + PVC and Polychloroprene |
| IJ100 | J2AT | 2-braid, wire | Industrial Jack Hose Applications | Nitrile | Nitrile + PVC |
| IJ100 | J2AT-MTF | 2-braid, wire | Ultra High Abrasive Industrial Jack Hose Applications | Nitrile | MegaTuff |
| ISO 1436 1SN R1<br>SAE 100R1 Type AT<br>EN 853 1SN | G1 | 1-braid, wire | Medium Pressure, Petroleum Oils & Environmental Fluids | Nitrile | Nitrile + PVC |
| SAE 100R1 Type AT | G1H | 1-braid, wire | High Temperature, Medium Pressure, Petroleum Oils & Environmental Fluids | Nitrile | CSM |
| Gates Proprietary Design<br>SAE 100R1 | RFS | 1-braid, wire | Low Pressure, Powder Fire Suppressant Applications | Nitrile | Nitrile + PVC |

| Standard Industry Specification | Gates Description | Construction (Reinforcement) | Use | Stock | |
|---|---|---|---|---|---|
| | | | | Tube Name | Cover Name |
| SAE 100R3 | G3H | 2-braid, textile | Petroleum Oils, Antifreeze, Water, High Temperature | Nitrile | Polychloroprene |
| SAE 100R6 | GTH | 1-braid, textile | Petroleum Oils, Antifreeze, Water, High Temperature | Nitrile | Polychloroprene |
| SAE 100R6 | GTHX | 1-spiral, textile | Petroleum Oils, Antifreeze, Water, High Temperature | Nitrile | Polychloroprene |
| Gates Proprietary Design | M500 | 1-braid, wire, textile | Pilot Lines, Grease Lines and Pressure Return Lines, 500 psi or Less Pressure Applications | Nitrile | Nitrile + PVC |
| SAE 100R4 | Multi Master | High tensile textile, helical wire | Return & Suction High Temperature | Nitrile | Polychloroprene |
| SAE 100R4 | GMV | 2-spiral, textile, helical wire | Return & Suction High Temperature | Nitrile | Polychloroprene |
| SAE 100R4 | G4H | 2-spiral, textile, helical wire | Return & Suction High Temperature | Nitrile | Polychloroprene |
| SAE 30R2 Type 1 & 2, B20 Biodiesel | RLA | 1-braid, textile | Return & Suction Low Pressure, Biodiesel up to 125°F | Nitrile | Nitrile + PVC |
| Gates Proprietary Design | RLC | 3-braid, textile | Return & Low Pressure | Nitrile | Nitrile + PVC |
| Gates Proprietary Design | MegaTech® LOC | 1-braid, textile | Extremely High Heat, Hot Oil Pressure & Return Lines, High Temperature Rotary Oil/Air, Air Compressor, Petroleum Oils, Transmission Oil Cooler | CPE | Textile |
| SAE 30R2, 30R6, 30R7 and B20 Biodiesel | LOC | 1-braid, textile | Petroleum, Oils, Antifreeze, Water, Air & Biodiesel up to 125°F | Nitrile | Textile |
| Gates Proprietary Design | LOL | 1-braid, textile | Petroleum Oils, Antifreeze, Water & Air | Nitrile | Nitrile + PVC and Polychloroprene (LOLA) |
| SAE J1402, DOT** FMVSS 106-74 | TR500 | 1-braid wire, textile | Petroleum & Synthetic Fluids, Air Brakes | Nitrile | Textile |
| Gates Proprietary Design | MegaTech® G5TB | 2-braid, wire, textile | Extremely High Heat, Hot Oil Pressure & Return Lines, High Temperature Rotary Oil/Air, Air Compressor, Petroleum Oils | CPE | Textile |
| SAE 100R2 Type AT SAE 100R2 Type AT | MegaTech® II | 2-braid, wire, textile | Extremely High Heat, Hot Oil Pressure & Return Lines, High Temperature Rotary Oil/Air, Air Compressor, Petroleum Oils | CPE | Textile |
| Gates Proprietary Design | MegaTech® 3000 | 2-braid, wire, textile | Pressurized Hot Oil Return Lines and Rotary Oil Lines | CPE | Textile |
| SAE J1402 DOT FMVSS 106-74 | MegaTech® 1000 | 1-braid, wire, textile | Extremely High Heat, Hot Oil Pressure & Return Lines, High Temperature Rotary Oil/Air, Air Compressor, Petroleum Oils, Air Brake | CPE | Textile |
| Gates Proprietary Design | MegaTech® 500 | 1-braid, wire, textile | Extremely High Heat, Hot Oil Pressure & Return Lines, High Temperature Rotary Oil/Air, Air Compressor, Petroleum Oils | CPE | Textile |
| Gates Proprietary Design | MegaTech® 250 | 1-braid, wire, textile | Extremely High Heat, Hot Oil Pressure & Return Lines, High Temperature Rotary Oil/Air, Air Compressor, Petroleum Oils, Transmission Oil Cooler | CPE | Textile |
| SAE 100R5, SAE J1402 DOT FMVSS 106-74 Type AII | *C5C | 3-braid, T-W-T | Petroleum Oil, Air Brake, Power Steering | Nitrile | Textile |
| SAE 100R5, SAE J1402 DOT FMVSS 106-74 Type AII | C5C-XH | 1-braid, wire, textile | Extremely High-Temperature Petroleum-Based or Phosphate Ester Fluids | CPE | Textile |
| SAE J1402, DOT FMVSS 106-74 Type AII | C5D | 3-braid, T-W-T | Petroleum & Synthetic Fluids, Air Brakes | CPE | Textile |
| SAE J1527, SAE J1942 ISO 840-A1 | C5M | 1-braid, textile | Marine Fuel & Oil | Nitrile | Nitrile + PVC |
| SAE J1402, DOT FMVSS 106-74 Type A1 | C5E | 3-braid, T-W-T | Air Brake, Power Steering, Lube | Nitrile | Textile |
| **PTFE** | | | | | |
| SAE 100R14 | C14 | 1-braid, stainless steel | High Temperature, Multi Fluid, Non-Conductive | PTFE | Stainless Steel |
| SAE 100R14 | C14CT | 1-braid, stainless steel | High Temperature, Multi Fluid, Conductive | PTFE | Stainless Steel |
| **Thermoplastic** | | | | | |
| SAE 100R7 | TH7 | 1-braid, polyester | Petroleum & Synthetic Fluids | Nylon | Urethane |
| SAE 100R7 | TH7NC | 1-braid, polyester | Non-Conductive | Nylon | Urethane |
| SAE 100R7 | TH7DL | 1-braid, polyester | Petroleum & Synthetic Fluids, Dual Line | Nylon | Urethane |
| SAE 100R7 | TH7NCDL | 1-braid, polyester | Non-Conductive, Dual Line | Nylon | Urethane |
| SAE 100R7 | TH7S | Synthetic fiber | Petroleum & Synthetic Fluids | Polyester | Urethane |
| SAE 100R7 | TH7SNC | Synthetic fiber | Non-Conductive | Polyester | Urethane |
| SAE 100R8 | TH8 | 2-braid, polyester | Petroleum & Synthetic Fluids | Nylon | Urethane |
| SAE 100R8 | TH8NC | 2-braid, polyester | Non-Conductive | Nylon | Urethane |
| SAE 100R18 | TH18 | 1-braid, synthetic fiber | Petroleum & Synthetic Fluids | Nylon | Urethane |
| SAE 100R18 | TH18NC | 2-braid, synthetic fiber | Non-Conductive | Nylon | Urethane |
| **Refrigerant** | | | | | |
| SAE J51 Type A2 Dimensions/Type D Performance, SAE J2064 and J3062 Type C, Class II Performance | PolarSeal® AC134a | Nylon barrier, 2-spiral, polyester | Air Conditioning (R12 and R134a) | Polychloroprene | EPDM |
| SAE J2064, SAE J3062 Type C, Class 1 | PolarSeal® ACC-PSII | Single-braid polyester | Reduced Barrier Construction, Air Conditioning (R12, R13A and R22) | Elastomeric | Elastomeric |

* -4 and -5 sizes have a Polychloroprene tube, **MegaTech1000 sizes -4, 6, -8, -10

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# GATES HYDRAULIC HOSE SELECTION GUIDE - CONTINUED

| | Description | Temp. Range (°F) | Dash Size vs. Rated Working Pressure (psi) | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | -2 | -3 | -4 | -5 | -6 | -8 | -10 | -12 | -16 | -20 | -24 | -28 | -32 | -36 | -40 | -48 | -56 | -64 | -72 |
| Spiral | G8K | -40 +250 | | | | | | | | 8,000 | 8,000 | | | | | | | | | | |
| | EFG6K | -40 +250 | | | | | 6,000 | 6,000 | 6,000 | 6,000 | 6,000 | 6,000 | 6,000 | | 6,000 | | | | | | |
| | EFG6KL | -70 +212 | | | | | | | 6,000 | 6,000 | 6,000 | | | | | | | | | | |
| | EFG5K | -40 +250 | | | | | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | | 5,000 | | 5,000 | | | | |
| | EFG5KL | -70 +212 | | | | | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | | | | | | | | |
| | ID5K | -40 +250 | | | | | | | 5,000 | 5,000 | 5,000 | | | | | | | | | | |
| | EFG4K | -40 +250 | | | | | 4,000 | 4,000 | 4,000 | 4,000 | 4,000 | 4,000 | | | | | | 4,000 | | | |
| | EFG4KL | -70 +212 | | | | | | | | 4,000 | 4,000 | 4,000 | | | | | | | | | |
| | EFG3K | -40 +250 | | | | | | | | | | 3,000 | 3,000 | | 3,000 | | | | | | |
| Constant Pressure Braid | M6K | -40 +212 | | | 6,000 | | | | | | | | | | | | | | | | |
| | M5K | -40 +212 | | | 5,000 | 5,000 | 5,000 | 5,000 | | | | | | | | | | | | | |
| | M4K | -40 +212 | | | 4,000 | 4,000 | 4,000 | 4,000 | 4,000 | 4,000 | 4,000 | | | | | | | | | | |
| | M4KH | -40 +250 | | | 4,000 | | 4,000 | 4,000 | 4,000 | 4,000 | | | | | | | | | | | |
| | M4KL | -70 +212 | | | 4,000 | 4,000 | 4,000 | 4,000 | 4,000 | 4,000 | 4,000 | | | | | | | | | | |
| | M3K | -40 +212 | | 3,250 | 3,250 | 3,250 | 3,250 | 3,250 | 3,250 | 3,250 | 3,250 | | | | | | | | | | |
| | M3KH | -40 +250 | | | 3,250 | 3,250 | 3,250 | 3,250 | 3,250 | 3,250 | 3,250 | | | | | | | | | | |
| Variable Pressure Braid | M-XT | -40 +212 | | | | | 4,800 | 4,000 | 3,625 | 3,125 | 2,400 | | | | | | | | | | |
| | M-XP | -40 +212 | | | 4,000 | | 4,000 | 4,000 | 4,000 | 4,000 | | | | | | | | | | | |
| | M2T® | -40 +212 | | | 6,000 | | 5,000 | 4,300 | 3,800 | 3,500 | 2,500 | 2,300 | 2,000 | | 1,500 | | | | | | |
| | CM2TDL | -40 +212 | | | | | 4,800 | 4,000 | | | | | | | | | | | | | |
| | G2 | -40 +212 | | 6,025 | 5,800 | | 4,800 | 4,000 | 3,625 | 3,100 | 2,400 | | | | | | | | | | |
| | G2H | -40 +275 | | | | | | | | | | 1,825 | 1,300 | | 1,175 | | | | | | |
| | G2XH | -40 +300 | | | 6,000 | | 5,000 | 4,250 | 3,625 | 3,100 | 2,500 | 2,250 | 1,800 | | 1,500 | | | | | | |
| | G2L | -70 +212 | | | 5,800 | | 4,800 | 4,000 | 3,625 | 3,100 | 2,400 | 1,825 | 1,300 | | 1,175 | | | | | | |
| | G1 | -40 +212 | | 3,625 | 3,275 | 3,125 | 2,600 | 2,325 | 1,900 | 1,525 | 1,300 | 925 | 725 | | 600 | | | | | | |
| | G1H | -40 +275 | | | 2,750 | | 2,250 | 2,000 | 1,500 | 1,250 | 1,000 | 925 | 725 | | 600 | | | | | | |
| Specialty | J2AT | -40 +120 | | | 10,000 | | 10,000 | | | | | | | | | | | | | | |
| | Hot Oiler | -40 +300 | | | | | | | | | | | 2,300 | | | | | | | | |
| | RFS | -40 +212 | | 3,000 | 2,750 | | 2,250 | 2,000 | | 1,250 | 1,000 | | | | | | | | | | |
| Transfer | G3H | -40 +275 | | | 1,250 | 1,200 | 1,125 | 1,000 | 900 | 750 | 565 | 375 | 300 | | | | | | | | |
| | GTH | -40 +275 | | 500 | 400 | 400 | | 400 | 350 | 300 | 250 | | | | | | | | | | |
| | GTHX | -40 +275 | | | | | 400 | | | | | | | | | | | | | | |
| | M500 | -40 +212 | | | 500 | | 500 | 500 | 500 | 500 | 500 | | | | | | | | | | |
| Return | Multi Master | -40 +275 | | | | | | | | 350 | 300 | 250 | 150 | | 150 | | 150 | 150 | | 150 | |
| | G4H | -40 +275 | | | | | | | | 300 | 250 | 200 | | | | | | | | | |
| | GMV | -40 +275 | | | | | | | | 350 | 300 | 250 | 160 | | 115 | 90 | 70 | 60 | 55 | 55 | |
| | RLA | -40 +212 | | 250 | 250 | 250 | 250 | 200 | 200 | 200 | 160 | | | | | | | | | | |
| | RLC | -40 +275 | | | | | | | | | 200 | 200 | 200 | 200 | 200 | 150 | 150 | 150 | 150 | | 100 |
| Lock-On | LOC | -40 +250 | | | 300 | 300 | 300 | 300 | 300 | 300 | | | | | | | | | | | |
| | LOL | -40 +212 | | 300 | 300 | 300 | 300 | 300 | 300 | 300 | | | | | | | | | | | |
| Fleet | TR500 | -40 +250 | | | 500 | | 500 | 500 | 500 | 500 | 500 | | | | | | | | | | |
| | MegaTech® II | -40 +300 | | | | | | | | | | 2,250 | 1,500 | | 1,300 | | | | | | |
| | MegaTech® G5TB | -40 +300 | | | 3,000 | | 3,000 | 3,000 | 2,000 | 2,000 | 1,000 | 1,000 | 500 | | 500 | | | | | | |
| | MegaTech® 3000 | -40 +300 | | | 3,000 | | 3,000 | 3,000 | | | | | | | | | | | | | |
| | MegaTech® 1000 | -40 +300 | | | 1,000 | | 1,000 | 1,000 | 1,000 | 1,000 | 1,000 | 1,000 | | | | | | | | | |
| | MegaTech® 500 | -40 +300 | | | | | | | | | | | 500 | | 500 | | 500 | 500 | | | |
| | MegaTech® 250 | -40 +300 | | | 250 | | 250 | 250 | 250 | 250 | 250 | 250 | | | | | | | | | |
| | MegaTech® LOC | -40 +300 | | | 300 | | 300 | 300 | 300 | 300 | 300 | | | | | | | | | | |
| | C5C | -40 +212 | | | 3,000 | 3,000 | 2,250 | 2,000 | 1,750 | 1,500 | 800 | 625 | 500 | | 350 | | 350 | | | | |
| | C5C-XH | -40 +302 | | | 3,000 | 3,000 | 2,250 | 2,000 | 1,750 | 1,500 | 800 | 625 | | | | | | | | | |
| | C5D | -40 +300 * | | | 1,500 | 1,500 | 1,500 | 1,250 | 1,250 | 750 | 400 | | | | | | | | | | |
| | C5M | -4 +212 | | | | 500 | 500 | 500 | 500 | 500 | 500 | | | | | | | | | | |
| | C5E | -40 +300 * | | | 1,500 | 1,500 | 1,500 | 1,250 | 1,250 | 750 | 400 | 300 | | | | | | | | | |
| | PolarSeal® AC134a | -22 +257 | | | | | 500 | 500 | 500 | 500 | | | | | | | | | | | |
| | PolarSeal® ACC-PSII | -22 +257 | | | | | 350 | 350 | 350 | 350 | 350 | | | | | | | | | | |
| PTFE | C14 (Dynamic) | -65 +400 | | | 1,500 | 1,500 | 1,500 | 1,000 | 800 | 800 | 800 | | | | | | | | | | |
| | C14 (Static) | -65 +450 | | | 3,000 | 3,000 | 2,500 | 2,000 | 1,500 | 1,200 | 1,000 | | | | | | | | | | |
| | C14CT (Dynamic) | -65 +400 | | | | | 1,500 | 1,000 | | | | | | | | | | | | | |
| | C14CT (Static) | -65 +450 | | | | | 2,500 | 2,000 | | | | | | | | | | | | | |
| Thermoplastic | TH7 | -65 +200 | 3,000 | 3,000 | 2,750 | 2,500 | 2,250 | 2,000 | | 1,250 | 1,000 | | | | | | | | | | |
| | TH7NC | -65 +200 | 3,000 | 3,000 | 2,750 | 2,500 | 2,250 | 2,000 | | 1,250 | 1,000 | | | | | | | | | | |
| | TH7DL | -65 +200 | | | 2,750 | 2,500 | 2,250 | 2,000 | | | | | | | | | | | | | |
| | TH7NCDL | -65 +200 | | | 2,750 | | 2,250 | 2,000 | | | | | | | | | | | | | |
| | TH7S | -65 +200 | | | 2,750 | 2,500 | 2,250 | 2,000 | | | | | | | | | | | | | |
| | TH8 | -65 +200 | | 5,000 | 5,000 | | 4,000 | 3,500 | | 2,250 | 2,000 | | | | | | | | | | |
| | TH8NC | -65 +200 | | | 5,000 | | 4,000 | 3,500 | | | | | | | | | | | | | |
| | TH18 | -67 +212 | | | 3,000 | 3,000 | 3,000 | 3,000 | 3,000 | | | | | | | | | | | | |
| | TH18NC | -67 +212 | | | 3,000 | 3,000 | 3,000 | 3,000 | 3,000 | | | | | | | | | | | | |

* All purpose fleet application service – 40°F to +300°F (-40°C to +149°C), air to +250°F

**Caution:** Water, water/oil emulsions and water/glycol solutions must be kept below the temperatures listed in the table below, relative to line pressures.

MAXIMUM TEMPERATURE LIMITS FOR WATER,
WATER/OIL EMULSIONS AND WATER/GLYCOL SOLUTIONS

| Hose | Pressure Lines | Return Lines |
|---|---|---|
| G8K, EFG6K, EFG5K, EFG4K, EFG3K, G2, G2L, M2T® , M6K, M5K, M4K, M3K, RFS, RLA, C5C, C5E, LOC, LOL | +200°F (+93°C) | +180°F (+82°C) |
| G2H, G1H, MegaTech® Line, G2XH, C5D, G3H, GTH, G4H, GMV, RLC, TR500, M3KH, M4KH | +225°F (+107°C) | +180°F (+82°C) |

**Caution:** The fluid manufacturer's recommended maximum operating temperature for any given fluid must not be exceeded. If different than the above listed hose temperatures, the lower limit must take precedence. Actual service life at temperatures approaching the recommended limit will depend on the particular application and the fluid being used in the hose. Intermittent (up to 10 percent of operating time) refers to momentary temperature surges. Detrimental effects increase with increased exposure to elevated temperatures.

Do NOT expose hose to maximum temperature and maximum rated working pressure at the same time.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# TYPE APPROVAL AND HOSE SELECTION GUIDE

| Hose Types | DNV-GL | | | ABS | | | USCG | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| | Sizes | | Couplings | Sizes | | Couplings | Sizes | | Couplings | Type |
| | From | To | | From | To | | From | To | | |
| EFG6K | -6 | -32 | GS / GSH / GSM | -6 | -32 | GS (6-20<br>GSM (24-32) | -6 | -32 | GS (6-20)<br>GSM (24,32)<br>S-SS (6, 8, 10) | HF (GS)<br>H (GSM)<br>H S-SS |
| EFG5K | -6 | -32 | GS / GSH / GSM | -10 | -32 | GS (6-20<br>GSM (24-32) | -6 | -32 | GS (6-20)<br>GSM (24,32)<br>S-SS (6, 8, 10) | H GS (6,8)<br>HF GS (10-20)<br>HF GSM (24,32)<br>H (S-SS) |
| EFG4K | -6 | -20 | GS | -6 | -16 | GS | -6 | -16 | GS<br>S-SS (6, 8, 10, 16) | HF (GS)<br>H (S-SS) |
| EFG3K | -20 | -32 | GS / GSP | -20 | -32 | GS | -20 | -20 | GS | HF |
| M6K | -4 | -4 | G | | | | | | | |
| M5K | -4 | -8 | G | | | | -8 | -8 | B-SS | H |
| M4K | -4 | -16 | G & GS | -4 | -12 | G & GS | -4 | -16 | G (4-12)<br>GS (6-16)<br>B-SS (4, 8) | HF (G,GS)<br>H (B-SS) |
| M3K | -4 | -16 | G | -4 | -16 | G | -4 | -16 | G<br>B-SS (10, 12) | HF (G)<br>F (B-SS) |
| M2T | Expected Spring 2015 | | | -4 | -16 | B-SS & G | -4 | -16 | G (4-16)<br>B-SS (4-8, 12, 16) | HF |
| G2XH | | | | | | | -6 | -16 | G | H |
| G2 | -4 | -32 | G (4 - 20)<br>GSP (24 - 32) | -4 | -32 | G (4 - 20)<br>GSP (24 - 32) | -3 | -32 | PC (3), B-SS (4)<br>G (4-20) GSP (24,32) | H |
| G1H | | | | | | | -4 | -16 | G | H (4)<br>HF (6,8,12,16) |
| G1 | -4 | -32 | G (4 - 20)<br>GSP (24 - 32) | -4 | -32 | G (4 - 20)<br>GSP (24 - 32) | -3 | -32 | PC (3)<br>G (4 - 20)<br>GSP (24,32) | H |
| C5CXH | | | | | | | -5 | -20 | C5 (6,10,16,20)<br>C5X (5,8,12) | HF |
| C5M | | | | -5 | -16 | PCSS / C5 | -5 | -16 | C5/C5X | HF |
| GMV (w/ fire sleeve) | GMV Expected Spring 2015 | | | -12 | -64 | GL (12-64)<br>G (12-20) | -12 | -64 | GL (12-32), G (12)<br>G4H (40-64) | H (G)<br>HF (GL)<br>HF (G4H) |
| G4H (w/ fire sleeve) | | | | -12 | -20 | GL | | | | |

NOTE: This chart is subject to change. If the information you need is not shown contact Gates Product Application.

# A SUMMARY OF SAE J1273 SEP 2014

## SCOPE

This summary provides guidelines for safety, selection, routing, fabrication, installation, replacement, maintenance, and storage of hose and hose assemblies. These are the recommended practices for hydraulic hose, but are also appropriate for many other hose and systems.

## SAFETY

Safety should be a paramount concern whenever working with a hydraulic system. The fluids conveyed are often at high temperatures and extremely high pressures which present unique dangers.

Hydraulic fluid injuries are generally very sever and may come in several forms. Fluid injections wounds may occur any time there is a leak in a hydraulic system. Never check for leaks or damage to a hydraulic system by feel, the best case scenario with a fluid injection wound is months of painful treatment to recover, addition risks include amputation and death. Due to the high temperatures any time a user is exposed to hydraulic fluids severe burns may result, this exposure may be a result of an assembly failure or even oil released during maintenance. Additionally there is a danger of fire or explosion if a hose fails around a hot engine or exhaust manifold, or if a static discharge takes place in a fluid spray.

Unconstrained hose may whip on pressurization or in the event of failure and are extremely dangerous. Additionally during the release of pressure on the hydraulic system improperly secured booms or other cylinder supported components may drop suddenly.

A sometimes less recognized risk is that of electrical shock. Any equipment used to work around live electrical lines (such as lifts, etc). Should be equipped with hydraulic hose rated as non-conductive. This is because most hydraulic hose have wire reinforcement and are inherently conductive. Also even when non-conductive hose are used it is important to recognize that hydraulic fluids may also act as conductors.

## HOSE SELECTION

The Gates STAMPED process is the industry accepted standard for hose selection, this process involves determining the following properties:

## SIZE

- Internal diameter requirements will affect fluid velocity and outside diameter may also sometime be concern for routing purposes. When in doubt match existing specifications.

## TEMPERATURE

- The maximum recommended hose temperature should never be exceeded, either in the fluid conveyed or on the exterior of the hose. Similarly special hose are available which will maintain flexibility at very low temperatures, always follow manufacturer guidelines.

## APPLICATION

- Environmental conditions such as ultraviolet light, salt water, air pollutants, temperature, ozone, chemicals, electricity, abrasion and paint application will all negatively impact hose assembly life.
- Static Discharge can become an issue when non-polar liquids or mixtures including non-polar liquids are conveyed in non-conductive hose. A static charge will build and on discharge perforate the hose tube, to avoid this use conductive tube products when conveying non-polar, or mixtures of non-polar, liquids.
- Electrical Conductivity of hydraulic hose or conveyed fluids is an issue with equipment used to work around electrical lines. If hydraulic equipment is to be used around electrical lines, always use hydraulic hose rated as non-conductive.
- The cleanliness requirements of a final hose assembly will be determined by the system it is to be applied too. Always follow the equipment manufacturer's recommended cleanliness standard.
- Be sure to select products which will meet any regulatory standards required in the application. Examples of these standards would include: SAE, USCG, EN/DIN, ABS, etc.
- Never place hose in a position where they are pulled on. Hose are designed to hold pressure and convey fluids, exposing them to axial loads will cause premature failure.
- Any special or unusual applications should always be approved by the hose manufacturer, otherwise additional independent testing may be required.

## MATERIALS

- Permeation, or effusion, is the movement of a substance through the hose tube walls which may degrade the hose tube, cause cover blistering, or other undesired effects, and must be considered especially when conveying compressed gasses.
- Be sure to select a hose which is compatible and approved by the manufacturer for the fluid conveyed. Concentration, pressure, temperature and other factors may impact the compatibility of the hose and fluid.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## PRESSURE

- The maximum working pressure of a hose assembly is the lowest working pressure of any component of the assembly.
- Hose should be sized with a working pressure equal to or above the maximum pressure encountered in a system. High frequency electronic transducers will be necessary to determine the maximum surge, or impulse, pressure in a system.
- If a hose assembly will be exposed to suction, be sure it is rated to hold the maximum suction and pressure in that portion of the system.
- Any time a hose assembly is to be exposed to external pressures, which may exceed the internal hose pressures, be sure to consult the hose manufacturer for recommendations.

## ENDS

- Always use manufacturer approved couplings for hose assemblies. Be sure to select the appropriate end termination for a system working pressure and other requirements such as vibration resistance.

## DELIVERY

- Always follow manufacturer recommendations for maximum fluid velocity within a hose. Excessive fluid velocity may cause excessive pressure loss, heat generation, hose movement or whipping, system noise, and hammer effects.

## HOSE ROUTING

Proper attention to good hose routing and application practices will ensure reliable function of hose assemblies. The following is a short list of factors to consider when routing hose.

- Vibration: Consider vibration requirements when selecting hose and predicting service life. Clamps, dampers, and other mechanisms may be necessary to reduce vibration.
- Cover protection: Protect the hose cover from abrasion, erosion, snagging, and cutting. Special abrasion-resistant hose and hose guards are available for additional protection. Route the hose to reduce abrasion from hose rubbing other hose or objects that may abrade it.
- External Physical Abuse: Route hose to avoid tensile (pulling) loads, side loads, flattening, thread damage, kinking, damage to sealing surfaces, abrasion and twisting.
- Swivel Adapters: Swivel-type fittings or adapters do not transfer torque to hose while being tightened. Use these as needed to prevent twisting during installation.
- Live Swivels: If two components in the system are rotating in relation to each other, live swivels may be necessary. These connectors reduce the torque transmitted to the hose.
- Slings and Clamps: Use slings and clamps to support heavy or long hose and to keep it away from moving parts. Use clamps that prevent hose movement that will cause abrasion. Care shall be taken to prevent the sling clamp from abraiding the hose. Avoid over tightening of slings or clamps.
- MBR: Routing during assembly and use at less than minimum bend radius may reduce hose life. Sharp bending at the hose/fitting juncture may result in leaking, hose rupturing, or the hose assembly blowing apart. A minimum straight length of 1.5 times the hose's outside diameter shall be allowed between the hose fitting and the point at which the bend starts.
- Elbows and Adapters: Use elbows or adapters to relieve hose strain due to routing.
- Lengths: Unnecessarily long hose can increase pressure drop and affect system performance. When pressurized, hose that is too short may pull loose from its fittings, or stress the hose fitting connections, causing premature metallic or seal failures.
- Motion Absorbtion: Provide adequate hose length to distribute movement and prevent bends smaller than the minimum bend radius.
- Hose Movement and Bending (multi plane bending): Hose allows relative motion between system components. Analyze this motion when designing hose systems. The number of cycles per day may significantly affect hose life. Also avoid multiple planes of motion and twisting motion.
- Hose and machine tolerances: Design hose to allow for changes in length due to machine motion and tolerances.
- Hose length change due to pressure: Design hose to accommodate length changes from changing pressures.
- Do not cross or clamp together high- and low-pressure hose. The difference in length changes could wear the hose covers.

## HOSE ASSEMBLY FABRICATION

- Component inspection: Before creating an assembly be sure to inspect all components to be sure they are the correct product, cut correctly, and do not have any visually identifiable defects.
- Couplings (compatibility): Hose fitting components from one manufacturer are not usually compatible with fitting components supplied by another manufacturer. Never mix and match hose and couplings from different manufacturers, unless approved by both parties.

- Hose assembly equipment (crimpers): Hose and fittings from one manufacturer should not generally be assembled with the equipment of another manufacturer.
- Safety Equipment: During fabrication, use proper safety equipment, including eye protection, respiratory protection, and adequate ventilation.
- Reuse of Hose and Fittings: Damaged hose and fittings shall not be used.
  - Never reuse: Field-attachable fittings that have blown or pulled off hose
  - Never reuse: Any part of hose fittings that were permanently crimped or swaged to hose
  - Never reuse: Hose that has been in service
- Cleanliness: Hose assemblies may be contaminated during fabrication. Clean hose to specified cleanliness levels.
- Temperature: The fabrication of hose assemblies should be performed at an ambient temperature over 0°C.
- Assembly inspection: After assembly, hose assemblies shall be inspected for visible defects and interior obstructions.
- Marking: Hose assemblies shall be marked in accordance with any relevant standards.

## HOSE ASSEMBLY INSTALLATION AND REPLACEMENT

- Before installation inspect the hose assembly for:
  - Hose length and routing for compliance with original design
  - Correct style, size, length, and visible nonconformities
  - Coupling sealing surfaces for burrs, nicks, or other damage
- Handling during installation: Handle hose with care during installation. Kinking hose, or bending at less than minimum bend radius may reduce hose life. Avoid sharp bending at the hose/fitting juncture. Before and during installation, hose assemblies should be at a temperature above 0°C.
- Twist angle and orientation: To avoid twisting, which shortens hose life, the hose layline can be used as a reference. Twisting can also be avoided through the use of two wrenches during the installation of swivel connectors.

Securement and protection: Install necessary restraints and protective devices. Determine that such devices do not create additional stress or wear points.

Assembly Torque: Always follow the manufacturer recommended coupling installation practices, and torque or flats values. Improper installation may result in a leaking connection.

System Checkouts: In hydraulic or other liquid systems, eliminate all air entrapment after completing the installation. Follow manufacturers' instructions to test the system for possible malfunctions and leaks.

## MAINTENANCE INSPECTION

As part of regular equipment maintenance, hose assemblies should always be checked for deterioration.

Frequency: Evaluate factors such as the nature and severity of the application, past history, and manufacturers' information to establish the frequency of inspections.

Visual Inspection: Only visually inspect for leaks. NEVER attempt to feel a leak, which could cause a fluid injection wound. Look for leaks, weeping, hose cracking, deformation, hardening or softening, rust, noise, smells, and any other defect which indicates a hose assembly may require replacement.

## HOSE STORAGE

Age control: Store hose in a manner that facilitates age control and first-in, first-out usage based on manufacturing date on hose or hose assembly. Any hose or assembly in storage for more than two years should be visually inspected and proof pressure tested.

Storage Conditions will greatly affect hose shelf life, always store hose in the manufacturers' original packaging. Avoid high temperatures, ozone, solvents and their vapors, corrosive (acid or basic) liquids and fumes, rodents, extremes in humidity, ultraviolet light, insects, radiation, strong, electro-magnetic fields, molds, and fungi.

Basic Testing for Usability: Flex the hose to the minimum bend radius and compare it with new hose. After flexing, examine the cover and tube for cracks. If any appear, no matter how small, reject the hose.

If the hose is wire reinforced, and the hose is unusually stiff, or a cracking sound is heard during flexing, check for corrosion by cutting away a section of the cover from a sample. Corrosion would be another reason for rejection.

If doubt still persists, contact hose assembler to conduct proof-pressure tests or any other tests needed to verify hose quality.

## REFERENCES

All of the material presented here may be explored in more detail by obtaining the original standards from the appropriate
regulatory agency.

## SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE J343 Test and Test Procedures for SAE 100R Series Hydraulic Hose and Hose Assemblies
SAE J514 Hydraulic Tube Fittings
SAE J517 Hydraulic Hose

## INTERNATIONAL STANDARDS ORGANIZATION (ISO)

ISO 3457 Earth moving machinery—Guards and shields—Definitions and specifications
ISO 2230 Rubber products—Guidelines for storage
ISO 8331 Rubber and plastics hose and hose assemblies—Guide to selection, storage, use and maintenance

# DOT FMVSS 106-74

## MOTOR VEHICLE SAFETY STANDARD FOR BRAKE HOSE

Gates has received an increasing number of inquiries about the Department of Transportation (DOT) regulation FMVSS-106 regarding air brake hose. The requirements of the standard were issued by the National Highway Traffic Safety Administration and are published in the Federal Register, 49 Code of Federal Regulations, Part 571 MVSS 106 Brake Hose.

**NOTE: Anyone making brake assemblies must be registered with the Department of Transportation.**

### WHAT IS FMVSS-106?

The standard is written with specifics on labeling, performance tests, tests procedures, and registration. It is not a standard for design specifications for motor vehicle brake hose, brake hose assemblies, or brake hose end fittings. The Standard No. 106 will ensure that each user of brake hose will be supplied only the highest quality of hose. DOT will conduct random performance testing in accordance with the test procedures to ensure that the hose, couplings, and assemblies meet FMVSS 106.

"The purpose of the standard is to reduce deaths and injuries occurring as a result of brake system failure from pressure or vacuum loss due to hose or hose assembly rupture."
The regulations will apply to all over-the-road vehicles including trailers and motorcycles. Off–the-road vehicles will not be regulated if they are designed to operate on those other than public roads.

### BASIC PROVISIONS OF FMVSS-106.

1. Three types of brake hose are covered (hydraulic, air, and vacuum brake) together with couplings and hose assemblies. At this point, we will only focus on air brake hose and assemblies.
2. Performance level for brake hose is established instead of design specifications.
3. Permanent as well as reusable fittings are permissible with air brake hose. Inside and outside diameters standards for air brake hose intended for use with field attachable couplings have been established. These hose are identified as Type I and Type II.

### GATES CUSTOMER/ASSEMBLER WITH REGARD TO FMVSS-106.

1. Test (dimensional and pressure) each assembly or per customer's requirements before it is packaged and delivered to the customer.
2. Two of every 100 air brake hose assemblies produced or per customer's requirements are subjected to hydrostatic pressure testing and tensile strength (destructive) testing.

### LABELING OF AIR BRAKE HOSE.

Any customer crimping air brake assemblies must be registered with the National Traffic Safety Administration (NHTSA).

**THE NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION (NHTSA) REQUIRES:**

1. Product DOT CERTIFICATION. (Gates Corporation responsibility. The Gates logo is our DOT registration.)
2. Registration of the assembler. (Customer/ Distributor responsibility.)*
3. Permanent assembly identification. (Customer/ Distributor responsibility.) Refer to Gates frosted air brake hose labels below.

* For customers needing to apply for Brake Hose Manufacturer's Identification or Symbol, please follow the link to the manufacturers portal at http://vpic.nhtsa.dot.gov/mfrportal/ and complete the appropriate form found in the dropdown menu. Domestic Brake hose manufacturers are required to complete the (49 CFR Part 566 form).

## FROSTED AIR BRAKE HOSE LABELS

**Product Number: 7484-0023**
**Part Number: 78214**

To assist you in complying with the NHTSA requirement for identifying brake hose assemblies, Gates now offers mylar hose labels.

- Self-adhesive
- 1" wide by 3-3/4" long, with a 1-1/2" by 1" white area on one end for printed information
- Format suitable for typewriters, computer printers or hand writing
- Accepts 9-10 typed characters per row, 4 or 5 on a row
- Wrap-around label resists damage from elements

**LABEL APPLICATION PROCEDURE:**

1. Print appropriate information on label.
2. Wrap tag around hose assembly, printed end first.
3. Cover printed end with clear mylar tail of label.


Comes in 500 labels per pack.





## Overall Assembly Length – C1 – C2 = Hose Cut Length

The "C" length for each coupling is listed in the catalog, as shown below.





For the Gates Assembly 6M3K-8FJX-8MP-12.5

12.5" – 1.38" – 1.42" = 9.7" (Cut Hose Length)

| Descr. | Prod. No. | | | C | |
|---|---|---|---|---|---|
| | | r | m | " | mm |
| 6G-8MP | 7100-10095 | 3 | 4.0 | 1.42 | 36.1 |

| Descr. | Prod. No. | | | C | |
|---|---|---|---|---|---|
| | | r | m | " | mm |
| 6GE-8FJX | 7100-10955 | 3 | 3.1 | 1.38 | 35.1 |





To meet SAE quality requirements: the final assembly must meet the dimensional requirements shown in the table on the right; the hose cut must be within 5° of perpendicular, on 1" hose this is less than 3/32"; and coupling orientation must be within 2° of specification, orientation which is off as little as one percent can half the life of a hose assembly.

| Assembly OAL (in) | Tolerance (in) |
|---|---|
| ≤ 12 | ±0.125 |
| 12 < L ≤ 18 | ±0.1875 |
| 18 < L ≤ 36 | ±0.25 |
| > 36 | + 1%* |
| *to the nearest 0.125 inches | |

Assembly length tolerance (SAE J517)

Best practice to achieve these requirements is to begin by dry fitting all components of the assembly, then measure from one end of a coupling to the opposite end of the cut hose, crimp the coupling and measure the change in length. This will give a good estimate of change in hose length due to the crimping process, and allow for compensation. The use of witness marks to verify orientation and coupling insertion depth is also encouraged.

When measuring a hose assembly, the point at which the ends of the assembly are measured will depend on the style and construction of the couplings. A summary of measurement points is shown below. More detailed information is available in the tech note "Overall Length of Hose Assemblies."





Coupling termination measurement points, from left to right: D) flange, E) straight male, F) US spec (SAE, JIC, NPSM), G) International spec (DIN, BSP, GAZ)., H) FFOR and I) bent (elbow) couplings

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

When you order hydraulic assemblies, be sure the following information is included as shown in the illustrations below:

1. Quantity of assemblies required.
2. Hose catalog description (dash size and type).
3. First coupling dash size and end style.
4. Second coupling dash size and end style.
5. Offset angle or orientation of couplings must be specified if both couplings contain bent tube ends.
6. Assembly overall length.

## Example:




## CAUTION:

**Rated working pressure** of the application should always determine selection of hose. Used up to the recommended **rated working pressure**, the hose will provide normal service life before replacement is required.

When new, the hose described in this catalog will meet or exceed the **minimum burst pressure** listed in the hose specification tables. However—as with any hose in the industry—after the hose has been impulsed for a length of time, **minimum burst pressure** will decrease from the figure shown in the specification tables.

Temperature ranges specified for specific hose refer to recommended temperature limits of fluids being conveyed or ambient temperatures. Exceeding these limits will cause degradation of material compounds and reduce hose service life.



## Coupling A Information

☐ Male ☐ Female

Angle ____° Drop: ☐S ☐M ☐L ☐XL

or Drop Length_____ (mm)

| | Thread |
|---|---|
| ☐ JIC (37° Flare) | _____ |
| ☐ NPTF | _____ |
| ☐ O-Ring Boss | _____ |
| ☐ Flat-Face O-Ring (ORFS) | _____ |
| ☐ Code 61 | _____ |
| ☐ Code 62 | _____ |
| ☐ BSPP | _____ |
| ☐ DIN (Light/Heavy) | _____ |
| ☐ Other | _____ |

## Hose Type

Gates _____ I.D. _____

or

SAE 100R _____

**Dash Size:**

☐ 2 ☐ 3 ☐ 4 ☐ 5 ☐ 6

☐ 8 ☐ 10 ☐ 12 ☐ 16 ☐ 20

☐ 24 ☐ 32 ☐ 40 ☐ 48 ☐ 56

☐ 64

**Temperature** _____°

**Working Pressure (psi):**

☐ 100 ☐ 101-250

☐ 250-499 ☐ 500-1000

☐ 1001-2999 ☐ 3000-3999

☐ 4000-5999 ☐ 6000

**Application**

☐ Return Line ☐ Pressure Line

☐ Intake Line ☐ High Pressure Line

☐ Special Fluid _____

## Coupling B Information

☐ Male ☐ Female


Angle ____° Drop: ☐S ☐M ☐L ☐XL

or Drop Length_____ (mm)

| | Thread |
|---|---|
| ☐ JIC (37° Flare) | _____ |
| ☐ NPTF | _____ |
| ☐ O-Ring Boss | _____ |
| ☐ Flat-Face O-Ring (ORFS) | _____ |
| ☐ Code 61 | _____ |
| ☐ Code 62 | _____ |
| ☐ BSPP | _____ |
| ☐ DIN (Light/Heavy) | _____ |
| ☐ Other | _____ |

**Overall Length** _____ ☐ In. ☐ mm

**Coupling Orientation:**_____ °




Measure from centerline of flanged head to centerline of flanged head for length of assembly.

Offset angle is measured with far coupling vertically downward.

Orientation angle is measured clockwise.


## HOSE GUARDS

| | Full Length | Partial Length | From End of Coupling |
|---|---|---|---|
| **LifeGuard® Sleeve**  | ☐ | _____ | _____ |
| **Wire Spring**  | ☐ | _____ | _____ |
| **Flat Armor Spring**  | ☐ | _____ | _____ |
| **Nylon Sleeve**  | ☐ | _____ | _____ |
| **Plastic Coil Sleeve**  | ☐ | _____ | _____ |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

Proper hose installation is essential for satisfactory performance. If hose length is excessive, the appearance of the installation will be unsatisfactory and unnecessary cost of equipment will be involved. If hose assemblies are too short to permit adequate flexing and changes in length due to expansion or contraction, hose service life will be reduced.


The following diagrams show proper hose installations which provide maximum performance and cost savings. Consider these examples in determining length of a specific assembly.




When hose installation is straight, allow enough slack in hose line to provide for length changes which will occur when pressure is applied.





Adequate hose length is necessary to distribute movement on flexing applications and to avoid abrasion.





Avoid twisting of hose lines bent in two planes by clamping hose at change of plane.





Reduce number of pipe thread joints by using hydraulic adapters instead of pipe fittings.





When radius is below the required minimum, use an angle adapter to avoid sharp bends.





Use proper angle adapters to avoid tight bend in hose.





Prevent twisting and distortion by bending hose in same plane as the motion of the port to which hose is connected.





Route hose directly by using 45° and/or 90° adapter and fittings. Avoid excessive hose length to improve appearance.





**Note:** To allow for length changes when hose is pressurized, do not clamp at bends so that curves will absorb changes. Do not clamp high and low pressure lines together.





High ambient temperatures shorten hose life, so make sure hose is kept away from hot parts. If this is not possible, insulate hose.





To avoid hose collapse and flow restriction, keep hose bend radius as large as possible. Refer to hose specification tables for minimum bend radius.




When installing hose, make sure it is not twisted. Pressure applied to a twisted hose can result in hose failure or loosening of connections.




Elbows and adapters should be used to relieve strain on the assembly, and to provide neater installations which will be more accessible for inspection and maintenance.




Run hose in the installation so that it avoids rubbing and abrasion. Often, clamps are required to support long hose runs or to keep hose away from moving parts. Use clamps of the correct size. A clamp too large allows hose to move inside the clamp and causes abrasion.

## Hydraulic Flareless Assembly Procedure (per SAE J514 6.1.3 and 6.1.4)

1. Bottom the tube in the coupling, and tighten the nut until the ferrule just grips the tube. With a little experience, the technician can determine this point by feel. If the couplings are bench assembled, the gripping action can be determined by rotating the tube by hand as the nut is drawn down. When the tube can no longer be turned by hand, the ferrule has started to grip the tube.
2. After the ferrule grips the tube, tighten the nut one full turn. This may vary slightly with different tubing materials, but for general practice, it is a good rule for the technician to follow.

# GATES FIELD ATTACHABLE COUPLING INSTALLATION

1. Cut the hose end square with fine-tooth hacksaw or cut-off saw, the cut must be within 5° of perpendicular.

2. At a minimum be sure to blow out the hose to remove any rubber or metal dust, if higher levels of cleanliness are required utilize the MegaClean system or see the “Hose Assembly Cleanliness” tech note.

3. Be sure to thoroughly oil the stem and the inside of the hose. This is critical to ensure that the ferrule and stem are easily placed onto the hose, without removing tube or cover material.



4. Secure the ferrule in a vise or adjustable wrench, then using a clockwise motion, thread the hose into the ferrule until it bottoms out on the inside shoulder of the ferrule. Once fully inserted, using a counter-clockwise motion, turn the hose back one half turn.



5. With the hose and ferrule secured, thread the stem into the hose and ferrule in a clockwise motion until the stem hex contacts the ferrule.



6. Finally clean the assembly to ensure that the desired cleanliness levels are achieved. Follow the same procedure as in step 2.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

**1.** Determine LifeGuard® sleeve length using the following guidelines:

Sleeve length should exceed the length of free hose (distance between clamps that hold sleeve on) by the following amount:

**LifeGuard Sleeve Length = Free Hose Length (in) x 1.05**


All the decimals are rounded **up** to a full inch

**For example:** 11 ¾" free hose length x 1.05 = 12.34" ~ 13" LifeGuard sleeve length

**Note:** A minimum of ¾"of sleeve must extend beyond the clamps to properly clamp the sleeve. Sleeve cannot extend over the hex part of the fitting.


**2.** A hot knife is recommended to cut the sleeve as it will seal the ends as it cuts and keep the sleeving from unraveling. Gates also sells a guide table which keeps the sleeving in the correct, slightly open position to help simplify this process. Failure to use the guide table with the hot knife could result in both edges of the sleeve being melted together, which in turn makes hose insertion impossible.

If a hot knife is not available, cut sleeve with sharp scissors, and seal the edges of the sleeve to prevent unraveling and to strengthen it. Use flame torch to seal the inside white lining to the black outer sheath. Make sure sleeve end is spread apart before sealing ends with flame.





**3.** Before inserting the stems and crimping, verify whether the LifeGuard sleeve and collars can be installed after the couplings are crimped or must be installed prior to crimping the couplings.
a. If the collars will fit over at least one of the couplings and also clear the backup hex nut, then the sleeve and collars can be assembled after the hose assembly is completely crimped.
b. If the collars will not freely clear the termination and backup hex of at least one of the stems, then the sleeve and collars must be slid over the hose before crimping. In certain cases it may be desirable to do this anyway, even if the collars will fit. (An example would be when an assembly that uses long drop 90° couplings at both ends.)

**4.** The LifeGuard line-of-sight sleeve consists of two sleeves woven one inside the other. When inserting the hose, it is critical that the hose is positioned inside the white inner sleeve. Be careful not to snag the inside lining of the sleeve while inserting hose. If hose does not glide in easily, use hose insertion tool.




**5.** The aluminum collars must be free of burrs, sharp edges, gash marks and surface cracks/indentations. Embossing of these collars is permissible. The crimp O.D. for the aluminum collars depends on the hose type and ferrule used. Look up the proper crimp O.D. in eCrimp® (http://www.gates.com/ecrimp). The collars are listed numerically by product number. Match the collar product number to the hose type and ferrule product number being used. The collar crimp O.D. is listed in the table, directly to the right of the ferrule product number for each combination.




**Note:** Use PC707 LifeGuard die plate when making assemblies.

**Note:** The crimp O.D. tolerance for all aluminum collars used to hold LifeGuard line-of-sight nylon sleeving on hose assemblies is ±.005".
**WARNING:** Extra care must be taken when aligning the back-up hex of the coupling with the crimp dies during crimping of the LifeGuard assembly. Improperly positioned back-up hex can damage the die face.

**6.** Install proper die sets by first positioning the die plate in such manner as to let the notches rest against the back locator pins on the PC707 crimper. Then install the recommended die set taking extra care that the two die pins fit inside the two holes in the die plate.

**7.** Dial in crimp setting and crimp sleeve onto one end of the hose assembly.

**8.** To take the slack out of the sleeve, roll or twist the hose. This will take-up the excess in the sleeve, and help with crimping the other end of the assembly.

**9.** Pull back any remaining excess of the sleeve. Hold it in place and crimp the other end of the assembly.

**10.** LifeGuard crimp collars require specialized dies for their installation, since the final form of the collar is very different from a standard crimp. When crimping LifeGuard with the GC® 32 crimper, use eCrimp to determine the appropriate die and setting based on the hose and coupling to which it is to be attached. Once the die has been selected, care must be taken to ensure the die fingers are installed correctly. When using the LifeGuard die set, the fingers are properly aligned when the colored stripe forms a straight line across the die.



**GC® 32**

**11.** Your LifeGuard assembly is now ready to go.



## END CONFIGURATION SELECTION

It is important to keep in mind that the hose assembly (coupling and hose) is only one component of the system. In choosing the correct end terminations for the couplings attached to the hose, formal design standards and sound engineering judgement should be used.

In the absence of formal design standards, consider the following factors in choosing the proper end termination:


- Pressure
- Impulse frequency, amplitude and wave form
- Vibration
- Corrosion
- Dissimilar metals (galvanic corrosion)
- Maintenance procedures and frequency
- Installation reliability
- Connection's risk in the system
- Exposure to the elements
- Operator's and/or bystander's exposure to the connection
- Installation, operation and service activities and practices that affect safety

If there are any questions as to what end fittings should be used, Gates recommends that you consult your field sales representative or the Gates Hose and Connector Product Application Group for assistance.

### Stem and Ferrule Selection

Choosing the proper stem and ferrule termination to be used in the assembly. Check the Gates Crimp Data Manual to ensure proper hose assembly components and crimp specifications.

Gates also offers eCrimp® , an online crimp database that can be accessed at **www.gates.com/ecrimp.**





After determining the proper coupling components, refer to the Table of Contents in this catalog to find the proper coupling section. The ferrules are at the end of each coupling section.

### Stem Selection

Different hose may require different coupling styles. To make your selection, determine the correct stem to be used. There are two functional ends of the stem to consider:

1. the hose end for hose attachment;
2. the thread end for port attachment.




References to the coupling type(s) recommended for a specific hose are listed on the individual hose data pages; for example, EFG5K hose specifies GS couplings.

The thread end of a coupling (or adapter) can be identified by comparing the coupling being replaced or by measuring the port or thread end to which it is to be attached.

See thread end identification nomenclature.

### Plating corrosion resistance - time to red rust


| | |
|---|---|
| SAE Minimum Standard | |
| >3X SAE | Gates TuffCoat® |
| 6X SAE | TuffCoat® Xtreme™ |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# COUPLING AND ADAPTER END STYLE NOMENCLATURE

Gates couplings feature a meaningful description by combining end-style codes shown below that make thread end identification fast and easy. Always refer to Gates Crimp Data Manual when selecting hose and coupling combinations.

In the following example, the Gates description 12GS-12FJX90L identifies a GlobalSpiral™ Female JIC Swivel 90° Bend Long Drop coupling for -12 (3/4") hose size and -12 (3/4") stem size.




| Code | Description |
|---|---|
| A | Adapterless |
| AB | Air Brake |
| API | API Unions |
| B | Brass |
| BBDS | British Bonded Seal |
| BJ | Banjo |
| BKHD | Bulkhead |
| BL | Block |
| BS | Bite Sleeve |
| BSPP | British Standard Pipe Parallel |
| BSPT | British Standard Pipe Tapered |
| C | Caterpillar Flange |
| CC | Clamping Collar |
| DH | DIN Heavy |
| DL | DIN Light |
| F | Female |
| FABX | Female Air Brake Swivel |
| FBFFOR | Female British Flat-Face O-Ring |
| FBO | Female Braze-on Stem |
| FWO | Female Weldon |
| FF | Flat-Face |
| FFGX | Female French GAZ Swivel (Female Kobelco) |
| FFN | Female Flareless Nut |
| FOR | Flat-Face O-Ring |
| FFS | Female Flareless Sleeve |
| FG | Female Grease Thread |
| FKX | Female Komatsu Style Swivel |
| FL | Code 61 O-Ring Flange |
| FLC | Caterpillar Style O-Ring Flange |
| FLH | Code 62 O-Ring Flange Heavy |
| FLOS | Flange O-Ring Special |
| FT | Female SAE Tube |
| HLE | Hose Length Extender |
| HLEC | Hose Length Extender (Caterpillar) |
| HM | Hose Mender |
| HU | Hammer Union |
| I | Inverted Flare |
| J | JIC (37° Flare) |
| JIS | Japanese Industrial Standard |
| K | Komatsu Style (Japanese 30° Seat) |

| Code | Description |
|---|---|
| LH | Long Hex |
| LN | Lock Nut |
| M | Male |
| MB | Male Boss |
| MBAX | Male Boss Adapterless Swivel |
| MBDS | Metric Bonded Seal |
| MFA | Male Flareless Assembly (Ermeto) |
| MFG | Male French GAZ |
| MKB | Metric Kobelco |
| MM | Metric Male |
| MN | Metric Nut |
| MPG | Male Special Grease Fitting |
| MPLN | Male Pipe Long Nose |
| MLSP | Metric Light Stand Pipe |
| MSP | Metric Stand Pipe |
| NASP | North American Stand Pipe |
| OR | O-Ring |
| P | Pipe Thread (NPTF or NPSM) |
| PL | Press Lok® |
| PT | Port |
| PWX | Pressure Washer Swivel |
| QLH | Quick-Lok® High |
| QLL | Quick-Lok® Low |
| R | Field Attachable |
| S | SAE (45° Flare) |
| SP | Special |
| SS | Stainless Steel |
| TS | Tube Sleeve |
| TSN | Tube Sleeve Nut |
| X | Swivel |
| Z | Parker Triple Thread |
| 22 | 22-1/2° Bent Tube Angle |
| 30 | 30° Bent Tube Angle |
| 45 | 45° Bent Tube Angle |
| 60 | 60° Bent Tube Angle |
| 67 | 67-1/2° Bent Tube Angle |
| 90 | 90° Bent Tube Angle |
| 110 | 110° Bent Tube Angle |
| 135 | 135° Bent Tube Angle |

# THREAD END DASH SIZES, DESCRIPTIONS AND DIMENSIONS

### Coupling Dash Size and End Style

Coupling dash size is a shorthand method of denoting the size of a particular end fitting (see Thread Chart).

EXAMPLE: 12MP denotes a 3/4" male pipe thread end fitting. The corresponding thread description for a 3/4" pipe thread is 3/4 -14 NPTF solid male.

EXAMPLE: 12FJX denotes a 3/4" female JIC swivel (37° seat) end fitting. The corresponding thread description for a 3/4" JIC thread is 1-1/16 – 12 JIC 37° flare swivel female.

EXAMPLE: 12FL denotes a 3/4" SAE standard pressure (Code 61) flange fitting. This is the standard fitting description for a 3/4" SAE standard pressure flange.

### Termination Drop Lengths

Bent tube couplings carry a suffix designation that specifies the degree of bend and the length of the drop.

For example, a 12FJX90S is a female JIC swivel with a 90 degree bend. The "S" designates an SAE J516 short drop length. The short and long drops are specified in SAE J516. Flat-face and metric couplings meet ISO-12151-1 drop length specifications. Medium drops are not specified and can vary from manufacturer to manufacturer.

**S –** Short Drop

**M –** Medium Drop

**L –** Long Drop

**XL –** Extra Long Drop

Special, non-industry standard drop lengths are designated with a numerical suffix instead of the S, M, L code. For example, a **12FJX90-075** designates a 75mm drop.

### JIC 37 Degree per SAE J516 and ISO 12151-5

| Hose Size | Short Drop (mm) | Medium Drop (mm) | Long Drop (mm) |
|---|---|---|---|
| -4 | 21 | 32 | 46 |
| -5 | 21 | 32 | 46 |
| -6 | 23 | 38 | 54 |
| -8 | 29 | 41 | 64 |
| -10 | 32 | 47 | 70 |
| -12 | 48 | 58 | 96 |
| -16 | 56 | 71 | 114 |
| -20 | 64 | 78 | 129 |
| -24 | 69 | 86 | 141 |
| -32 | 88 | 140 | 222 |

### Flange Code 61 or 62 per SAE J516 and ISO 12151-3

| Hose Size | Short Drop (mm) | Medium Drop (mm) | Long Drop (mm) |
|---|---|---|---|
| -8 | - | 40 | 99 |
| -12 | - | 58 | 133 |
| -16 | 61 | 70 | 154 |
| -20 | 68 | 90 | 189 |
| -24 | 81 | 104 | 220 |
| -32 | 120 | 138 | 275 |
| -40 | 118 | - | - |
| -48 | 141 | - | - |

### Thread End Catalog Descriptions

Gates coupling ends shown on the following pages are accepted as industry standards. See detailed catalog listings for availability of specific hose/coupling combinations, detailed descriptions, thread end configurations such as swivels, bent tubes and special ends.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

When identifying hydraulic couplings, it is important to identify the type of seal made. There are three major types of coupling interfaces used in hydraulics today: Thread Interface, O-Rings and Mated Angle or Mechanical Joint. These three interfaces have developed differently in different parts of the world. In the following pages, country of origin and the coupling styles found in each country are identified. Brief descriptions and dimensional data help identify your particular coupling style.

## Identifying couplings is as easy as 1-2-3!

### 1. Determine Seal Type.

- Thread Interference
- O-Ring
- Mated Angle or Mechanical Joint
- Mated Angle with O-Ring

**Thread Interference.** A characteristic of this thread is that the male is thinner at the front than it is at the back. As the male is threaded into the female, the edges of the thread distort by flattening out. This distortion creates the seal.

**O-Ring.** The o-ring on the male being compressed against the corresponding female makes this seal. This type of seal is excellent for high-pressure applications. The threads pull the fitting against the port, trap the o-ring and flatten it to form a tight seal.

**Mated Angle or Mechanical Joint.** Different angles are used to create the seal. The seal takes place where the two angles meet and are wedged into one another. These can be cut with the angle either being inverted or standard. Standard seat couplings have the nose angle of the male on the outer surface of the coupling. Inverted seat couplings contain the nose angle of the male on the inside bore of the coupling.


**Mated Angle with O-Ring.** These couplings are a hybrid, which use both the mated angle and the o-ring to make the seal.

### 2. Visual Identification.

Thread Interference. These are the easiest because the only factor here is whether the termination is male or female. Couplings that use this seal are:

**TAPERED THREAD**


**National Pipe Tapered**




**NPTF**
**Solid Male (MP)**

**NPTF or NPSF**
**Solid Female (FP)**

**British Standard Pipe Tapered**





**BSPT Male (MBSPT)**

**BSPT Female**

**O-Ring.** Two determinations are needed:
**A.** O-Ring Location – Flange Groove, Outside, or on the Nose Seat
**B.** Coupling Termination – Male or Female

O-Ring Location


**Flange Groove**
**O-Ring Flange - SAEJ1518**




**Flange Head**
**(FL/FLH, FLC)**


**4-Bolt Split Flange**

**Outside**
**O-Ring Boss**




**Male (MB, MBX,**

**Female Port (FB)**




**Male (MFFOR)**

**Female (FFORX)**


## 2. Visual Identification - Continued

**Mated Angle or Mechanical Joint.** Determine:


**A.** Nose Seat – Standard or Inverted
**B.** Seat Angle (See Measuring Seat Angles)
**C.** Coupling Termination

### Standard Nose Seat

**JIC 37° Flare**





**JIC 37° Male (MJ, MJLN)**





**JIC 37° Flare Swivel Female (FJX)**

**37° Seat Angle**

**SAE 45° Flare**





**SAE 45° Flare Male (MS)**





**SAE 45° Flare Swivel Female (FSX)**

**45° Seat Angle**

**Japanese Industrial Standard & Komatsu**




**Male (MJIS, MK)**





**Female (FJIS, FKX)**

**30° Seat Angle**

### Inverted Nose Seats


**North American or Metric Stand Pipe & Male Flareless Assembly**



**Male Fitt Body** | **Bite Sleeve** | **Nut** | **Standpipe Fitting (NASP, MSP, MFA)**

**24° Seat Angle**


**National Pipe Straight Mechanical**




**NPTF Solid Male (MP)** | **NPSM Swivel Female (FPX)**

**30° Seat Angle**

**SAE Inverted Flare**




**SAE Inverted Flare Swivel Male (MIX)** | **SAE Inverted Flare Solid Female**


**45° Seat Angle**

**Mated Angle with O-Ring.** Determine:


**A.** O-Ring Location
**B.** Nose Seat
**C.** Seat Angle (See Measuring Seat Angles)
**D.** Coupling Termination

### Inside O-Ring Location with Inverted Nose Seat

**British Standard Pipe Parallel**





**BSPP Male (MBSPP)**





**BSPOR Female (FBSPORX)**

**30° Cone Seat**

**DIN 24° Cone**




**Male 24° Cone, DIN 2353 (MDL/MDH)**




**Female 24° Cone with O-Ring (FDLORX/FDHORX)**


**24° Cone Seat**

For a wall poster representation of this information, order literature form number 428-7125.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

**Measuring Seat Angles**


Using the seat gauge, determine the angle of the seat, as illustrated. When the centerline of the seat gauge extends parallel with the projected longitudinal axis of the coupling, then the angles of the gauge and seat match.





**NOTE:** Thread binding will occur when different thread configurations are used. DO NOT mix thread configurations.

## 3. Measure Threads.

Because some couplings have very similar characteristics, the only way to determine the correct identification is by measuring the thread. Follow the procedure below when measuring coupling threads:




With the caliper measure the thread diameter of the largest point. (Outside Diameter (O.D.) of male threads—Inside Diameter (I.D.) of female threads.)




Using the thread gauge, determine the number of threads per inch. Comparison of gauge and coupling threads against a lighted background will ensure an accurate reading.

Match the measurements taken above against those in the following tables that appear to be similar to the coupling under consideration.

**Gates provides many useful tools to assist you in identifying the right coupling!**

## HYDRAULIC COUPLING TEMPLATES



**Automotive Number:** 428-7108
**Industrial Number:** 39549

These templates provide a fast and easy way to measure North American threads, International threads, flange ends, seat angles (37° and 45°) and hose I.D.

## STAINLESS STEEL DIGITAL CALIPER



**Part Number:** 78241
**Product Number:** 7369-0322

Caliper features an easy-to-read LCD screen clearly displaying the crimp diameter digitally. Capable of four-way measurement: inside, outside, depth and step. Constructed of hardened stainless steel and comes in a handy, protective carrying case.

## INTERNATIONAL THREAD IDENTIFICATION KIT



**Part Number:** 70264
**Product Number:** 7369-0015

Attractive carrying case suitable for counter display and field sales calls. Contains male and female metric and British gauge for identifying thread size. Also includes pocket thread I.D. kit.

## NORTH AMERICAN THREAD IDENTIFICATION KIT



**Part Number:** 70270
**Product Number:** 7369-0016

Attractive carrying case suitable for counter display and field sales calls. Contains 45 anodized gauges, male and female, for identifying pipe and UN/UNF 2A/2B threads. Also includes pocket thread ID kit.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# POCKET THREAD IDENTIFICATION KIT



**Part Number:** 86583
**Product Number:** 7369-4318

To properly identify the correct replacement couplings, the measuring tools shown here should be used.

**Contents:**
Calipers
Seat Gauges (English)
Seat Gauges (Metric)
Thread Gauges
Thread I.D. Guide

# THREAD CHART

| DASH SIZE | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 10 | 12 | 14 | 16 | 20 | 24 | 32 | 40 | 48 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **NPTF Pipe Thread** | 1/8–27 | | 1/4–18 | | 3/8–18 | | 1/2–14 | | 3/4–14 | | 1–11 1/2 | 1 1/4–11 1/2 | 1 1/2–11 1/2 | 2–11 1/2 | 2 1/2–8 | 3–8 |
| **NPSM Swivel Thread** | 1/8–27 | | 1/4–18 | | 3/8–18 | | 1/2–14 | | 3/4–14 | | 1–11 1/2 | 1 1/4–11 1/2 | 1 1/2–11 1/2 | 2–11 1/2 | | |
| **JIC 37° Flare Thread** | 5/16–24 | 3/8–24 | 7/16–20 | 1/2–20 | 9/16–18 | | 3/4–16 | 7/8–14 | 1 1/16–12 | 1 3/16–12 | 1 5/16–12 | 1 5/8–12 | 1 7/8–12 | 2 1/2–12 | 3–12 | 3 1/2–12 |
| **SAE 45° Flare Thread** | 5/16–24 | 3/8–24 | 7/16–20 | 1/2–20 | 5/8–18 | 11/16–16 | 3/4–16 | 7/8–14 | 1 1/16–14 | | | | | | | |
| **SAE O-Ring Thread** | 5/16–24 | 3/8–24 | 7/16–20 | 1/2–20 | 9/16–18 | | 3/4–16 | 7/8–14 | 1 1/16–12 | 1 3/16–12 | 1 5/16–12 | 1 5/8–12 | 1 7/8–12 | 2 1/2–12 | | |
| **Flat-Face Thread** | | | 9/16–18 | | 11/16–16 | | 13/16–16 | 1–14 | 1 3/16–12 | | 1 7/16–12 | 1 11/16–12 | 2–12 | | | |
| **Inverted Flare Thread** | 5/16-28 | 3/8–24 | 7/16–24 | 1/2–20 | 5/8–18 | 11/16–18 | 3/4–18 | 7/8–18 | 1 1/16-16 | | | | | | | |
| **Compression Thread** | 5/16–24 | 3/8–24 | 7/16–24 | 1/2–24 | 9/16–24 | 5/8–24 | 11/16–20 | 13/16–18 | 1–18 | | | | | | | |
| **Code 61 Flange Head O.D.** | | | | | | | 1.19 | 1.335 | 1.50 | | 1.75 | 2.00 | 2.38 | 2.81 | 3.31 | 4.00 |
| **Code 62 Flange Head O.D.** | | | | | | | 1.25 | | 1.62 | | 1.88 | 2.12 | 2.50 | 3.12 | | |
| **BSPP Thread** | 1/8-28 | | 1/4-19 | | 3/8-19 | | 1/2–14 | 5/8–14 | 3/4–14 | | 1–11 | 1 1/4–11 | 1 1/2–11 | 2–11 | | |
| **BSPT Thread** | 1/8-28 | | 1/4-19 | | 3/8-19 | | 1/2–14 | 5/8–14 | 3/4–14 | | 1–11 | 1 1/4–11 | 1 1/2–11 | 2–11 | | |
| **Japanese Pipe Tapered Thread** | 1/8-28 | | 1/4-19 | | 3/8-19 | | 1/2–14 | 5/8–14 | 3/4–14 | | 1–11 | 1 1/4–11 | 1 1/2–11 | 2–11 | | |
| **Japanese Flare Thread** | 1/8-28 | | 1/4-19 | | 3/8-19 | | 1/2–14 | 5/8–14 | 3/4–14 | | 1–11 | 1 1/4–11 | 1 1/2–11 | 2–11 | | |
| **Copper/Nylon Air Brake Thread** | | | 7/16–24 | | 17/32–24 | | 11/16–20 | 13/16–18 | 1–18 | | | | | | | |

| METRIC (mm) | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 24 | 26 | 30 | 33 | 36 | 42 | 45 | 52 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **MDL** | | | M12X1.5 | M14X1.5 | M16X1.5 | M18X1.5 | M20X1.5 | M22X1.5 | | M26X1.5 | M30X2.0 | | M36X2.0 | | M45X2.0 | M52X2.0 |
| **MDH** | | | | | M16X1.5 | M18X1.5 | M20X1.5 | M22X1.5 | M24X1.5 | | M30X2.0 | | M36X2.0 | M42X2.0 | | M52X2.0 |
| **Komatsu** | | | | | | M18X1.5 | | M22X1.5 | M24X1.5 | | M30X1.5 | M33X1.5 | M36X1.5 | M42X1.5 | | |
| **GAZ** | | | | | | | M20X1.5 | | M24X1.5 | | M30X1.5 | | M36X1.5 | | M45X1.5 | M52X1.5 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

This section lists the origin and coupling style found in each country. Brief descriptions and dimensional data follows each coupling style.

There are five coupling systems generally used for hydraulic connections today.

They are identified geographically or by country as:

**North American**
**British**
**French**
**German**
**Japanese**

# NORTH AMERICAN THREAD TYPES

## Iron Pipe Thread Abbreviations

**N** National
**P** Pipe
**S** Straight Thread
**T** Tapered Thread
**F** Fuels
**M** Mechanical Joint

## NPTF

National Pipe Tapered thread for Fuel is a dryseal thread. It is used for both male and female ends. The NPTF male will mate with the NPTF, NPSF, or NPSM female.

The NPTF male has tapered threads and a 30° inverted seat. The NPTF female has tapered threads and no seat. The seal takes place by deformation of the threads. The NPSM female has straight threads and a 30° inverted seat. The seal takes place on the 30° seat.

The NPTF connector is similar to, but not interchangeable with, the BSPT connector. The thread pitch is different in most sizes. Also, the thread angle is 60° instead of the 55° angle found on BSPT threads.

## NPSF


National Pipe Straight thread for Fuels is sometimes used for female ends and properly mates with the NPTF male end. However, SAE recommends the NPTF thread in preference to the NPSF for female ends.

## NPSM

National Pipe Straight thread for Mechanical Joint is used on the female swivel nut of iron pipe swivel adapters. The leak-resistant joint is not made by the sealing fit of threads, but by a tapered seat in the coupling end.

| Dash Size | Nominal Size (in) | No. Threads per Inch | Female Thread I.D. (in) | Male Thread O.D. (in) | Max. Torque Recommendation for Dry NPTF* (ft-lb) |
|---|---|---|---|---|---|
| -2 | 1/8 | 27 | 23/64 | 13/32 | 20 |
| -4 | 1/4 | 18 | 15/32 | 35/64 | 25 |
| -6 | 3/8 | 18 | 19/32 | 43/64 | 35 |
| -8 | 1/2 | 14 | 3/4 | 27/32 | 45 |
| -12 | 3/4 | 14 | 61/64 | 1-1/16 | 55 |
| -16 | 1 | 11-1/2 | 1-13/64 | 1-5/16 | 65 |
| -20 | 1-1/4 | 11-1/2 | 1-17/32 | 1-43/64 | 80 |
| -24 | 1-1/2 | 11-1/2 | 1-25/32 | 1-29/32 | 95 |
| -32 | 2 | 11-1/2 | 2-1/4 | 2-3/8 | 120 |

### NPT Pipe Thread




**NPTF Solid Male (MP, MPLN)** | NPTF or NPSF Solid Female (FP) | NPSM Swivel Female (FPX)

***NOTES:**

1. Torque values can vary considerably depending on thread condition. Use only enough torque to achieve adequate sealing.
2. With female straight or parallel pipe threads (NPSM), maximum values are 50 percent of those listed in the table.
3. If thread sealant is used, maximum values shown should be decreased by 25 percent.

# NORTH AMERICAN THREAD TYPES – Continued

## *JIC (37° Flare)


The Society of Automotive Engineers (SAE) specifies a 37° angle flare or seat be used with high pressure hydraulic tubing. These are commonly called JIC couplings.

The JIC 37° flare male will mate with a JIC female only.*
The JIC male has straight threads and a 37° flare seat.
The JIC female has straight threads and a 37° flare seat.
The seal is made on the 37° flare seat.

Some sizes have the same threads as the SAE 45° flare. Carefully measure the seat angle to differentiate.

***Note:** Some C5, C5E and Lock-On couplings may have dual machined seats (both 37° and 45° seats).

**JIC 37° Flare**




**JIC 37° Male (MJ)** | **JIC 37° Flare Female (FJX)**

| Dash Size | Nominal Size (in) | Thread Size | Female Thread | Male Thread | Steel Torque Recommendation (ft-lb) | | Steel Torque Recommendation (N·m) | |
|---|---|---|---|---|---|---|---|---|
| | | | I.D. (in) | O.D. (in) | Assembly Torque* +25%-0 ft-lb | Assembly Torque Max. ft-lb | Assembly Torque* +25%-0 N·m | Assembly Torque Max. N·m |
| -2 | 1/8 | 5/16 - 24 | 17/64 | 5/16 | - | - | - | - |
| -3 | 3/16 | 3/8 - 24 | 21/64 | 3/8 | - | - | - | - |
| -4 | 1/4 | 7/16 - 20 | 25/64 | 7/16 | 11 | 14 | 15 | 19 |
| -5 | 5/16 | 1/2 - 20 | 29/64 | 1/2 | 14 | 18 | 19 | 24 |
| -6 | 3/8 | 9/16 - 18 | 1/2 | 9/16 | 18 | 22 | 24 | 30 |
| -8 | 1/2 | 3/4 - 16 | 11/16 | 3/4 | 36 | 45 | 49 | 61 |
| -10 | 5/8 | 7/8 - 14 | 13/16 | 7/8 | 57 | 71 | 77 | 96 |
| -12 | 3/4 | 1-1/16 - 12 | 31/32 | 1-1/16 | 79 | 99 | 107 | 134 |
| -14 | 7/8 | 1-3/16 - 12 | 1-7/64 | 1-3/16 | - | - | - | - |
| -16 | 1 | 1-5/16 - 12 | 1-15/64 | 1-5/16 | 108 | 135 | 147 | 184 |
| -20 | 1-1/4 | 1-5/8 - 12 | 1-35/64 | 1-5/8 | 127 | 158 | 172 | 215 |
| -24 | 1-1/2 | 1-7/8 - 12 | 1-51/64 | 1-7/8 | 158 | 198 | 215 | 269 |
| -32 | 2 | 2-1/2 - 12 | 2-27/64 | 2-1/2 | 245 | 306 | 332 | 415 |

* Values from SAE J2593 FEB2015

**Over torque of hydraulic couplings can damage mating surfaces and is a leading cause of premature leaks.**

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# NORTH AMERICAN THREAD TYPES – Continued

## *SAE (45° Flare)


A term usually applied to fittings having a 45° angle flare or seat. Soft copper tubing is generally used in such applications as it is easily flared to the 45° angle. These are for low-pressure applications—such as for fuel lines and refrigerant lines.

The SAE 45° flare male will mate with an SAE 45° flare female only or a dual seat JIC/SAE 45°.*


The SAE male has straight threads and a 45° flare seat. The SAE female has straight threads and a 45° flare seat. The seal is made on the 45° flare seat.
Some sizes have the same threads as the JIC 37° flare. Carefully measure the seat angle to differentiate.

***Note:** Some C5, C5E and Lock-On couplings may have dual machined seats (both 37° and 45° seats).

**SAE 45° Flare**




**SAE 45° Flare Male (MS)**




**SAE 45° Flare Swivel Female (FSX)**

| Dash Size | Nominal Size (in) | Thread Size | Female Thread | Male Thread | Steel Torque Recommendation (ft-lb) | | Steel Torque Recommendation (N·m) | |
|---|---|---|---|---|---|---|---|---|
| | | | I.D. (in) | O.D. (in) | Assembly Torque* +25%-0 ft-lb | Assembly Torque Max. ft-lb | Assembly Torque* +25%-0 N·m | Assembly Torque Max. N·m |
| -2 | 1/8 | 5/16 - 24 | 17/64 | 5/16 | - | - | - | - |
| -3 | 3/16 | 3/8 - 24 | 21/64 | 3/8 | - | - | - | - |
| -4 | 1/4 | 7/16 - 20 | 25/64 | 7/16 | 11 | 14 | 15 | 19 |
| -5 | 5/16 | 1/2 - 20 | 29/64 | 1/2 | 14 | 18 | 19 | 24 |
| -6 | 3/8 | 9/16 - 18 | 1/2 | 9/16 | 18 | 22 | 24 | 30 |
| -8 | 1/2 | 3/4 - 16 | 11/16 | 3/4 | 36 | 45 | 49 | 61 |
| -10 | 5/8 | 7/8 - 14 | 13/16 | 7/8 | 57 | 71 | 77 | 96 |
| -12 | 3/4 | 1-1/16 - 12 | 31/32 | 1-1/16 | 79 | 99 | 107 | 134 |

* Values from SAE J2593 FEB2015

| Dash Size | Nominal Size (in) | Thread Size | Female Thread | Male Thread |
|---|---|---|---|---|
| | | | I.D. (in) | O.D. (in) |
| -6 | 3/8 | 11/16 – 18 | 5/8 | 11/16 |

# NORTH AMERICAN THREAD TYPES – Continued


## O-Ring Boss

The o-ring boss male will mate with an o-ring boss female only. The female is generally found on ports.

The male has straight threads, a sealing face and an o-ring. The female has straight threads and a sealing face.

The seal is made at the o-ring on the male and the sealing face on the female.

### SAE Straight Thread O-Ring Boss




**O-Ring Boss Male (MB, MBX)** **O-Ring Boss Female Port (FB)**

| Dash Size | Nominal Size (in) | Thread Size | Female Thread | Male Thread | O-Ring | |
|---|---|---|---|---|---|---|
| | | | I.D. (in) | O.D. (in) | I.D. (in) | DESCR |
| -2 | 1/8 | 5/16 – 24 | 17/64 | 5/16 | 0.239 | – |
| -3 | 3/16 | 3/8 – 24 | 21/64 | 3/8 | 0.301 | 30R |
| -4 | 1/4 | 7/16 – 20 | 25/64 | 7/16 | 0.351 | 40R |
| -5 | 5/16 | 1/2 – 20 | 29/64 | 1/2 | 0.414 | 50R |
| -6 | 3/8 | 9/16 – 18 | 1/2 | 9/16 | 0.468 | 60R |
| -8 | 1/2 | 3/4 – 16 | 11/16 | 3/4 | 0.644 | 80R |
| -10 | 5/8 | 7/8 – 14 | 13/16 | 7/8 | 0.755 | 100R |
| -12 | 3/4 | 1-1/16 – 12 | 31/32 | 1-1/16 | 0.924 | 120R |
| -14 | 7/8 | 1-3/16 – 12 | 1-7/64 | 1-3/16 | 1.048 | 140R |
| -16 | 1 | 1-5/16 – 12 | 1-15/64 | 1-5/16 | 1.171 | 160R |
| -20 | 1-1/4 | 1-5/8 – 12 | 1-35/64 | 1-5/8 | 1.475 | 200R |
| -24 | 1-1/2 | 1-7/8 – 12 | 1-51/64 | 1-7/8 | 1.720 | – |
| -32 | 2 | 2-1/2 – 12 | 2-27/64 | 2-1/2 | 2.337 | – |

### O-Ring Boss Light-Duty - SAE J1926-3

| Dash Size | Assembly Torque* +25%-0 ft-lb | Assembly Torque Max. ft-lb | Assembly Torque* +25%-0 N·m | Assembly Torque Max. N·m |
|---|---|---|---|---|
| -2 | 6 | 7 | 8 | 10 |
| -3 | 7 | 9 | 10 | 13 |
| -4 | 13 | 17 | 18 | 23 |
| -5 | 18 | 23 | 25 | 31 |
| -6 | 22 | 28 | 30 | 38 |
| -8 | 37 | 46 | 50 | 63 |
| -10 | 44 | 55 | 60 | 75 |
| -12 | 70 | 88 | 95 | 119 |
| -14 | 92 | 115 | 125 | 156 |
| -16 | 111 | 138 | 150 | 188 |
| -20 | 147 | 184 | 200 | 250 |
| -24 | 155 | 193 | 210 | 263 |
| -32 | 221 | 276 | 300 | 375 |
| -40 | 221 | 276 | 300 | 375 |
| -48 | 258 | 322 | 350 | 438 |
| -64 | 258 | 322 | 350 | 438 |

* Values from SAE J2593 FEB2015

### O-Ring Boss Heavy-Duty - SAE J1926-2

| Dash Size | Assembly Torque* +25%-0 ft-lb | Assembly Torque Max. ft-lb | Assembly Torque* +25%-0 N·m | Assembly Torque Max. N·m |
|---|---|---|---|---|
| -3 | 7 | 9 | 10 | 13 |
| -4 | 15 | 18 | 20 | 25 |
| -5 | 18 | 23 | 25 | 31 |
| -6 | 26 | 32 | 35 | 44 |
| -8 | 52 | 64 | 70 | 88 |
| -10 | 74 | 92 | 100 | 125 |
| -12 | 125 | 157 | 170 | 213 |
| -14 | 158 | 198 | 215 | 269 |
| -16 | 199 | 249 | 270 | 338 |
| -20 | 210 | 263 | 285 | 356 |
| -24 | 273 | 341 | 370 | 463 |
| -32 | 398 | 497 | 540 | 675 |
| -40 | 398 | 497 | 540 | 675 |
| -48 | 472 | 590 | 640 | 800 |

* Values from SAE J2593 FEB2015


# NORTH AMERICAN THREAD TYPES – Continued

## O-Ring Flange—SAE J518


The SAE Code 61 and Code 62 4-bolt split flange is used worldwide, usually as a connection on pumps and motors. There are three exceptions.

1. The -10 size, which is common outside of North America, is not an SAE standard size (generally found on Komatsu equipment). All Komatsu flanges are the same as SAE code 61 except for the -10 size.
2. Caterpillar flanges, which are the same flange O.D. as SAE Code 62, have a thicker flange head ("C" dimension in Table).
3. Poclain flanges, which are completely different from SAE flanges.

### SAE Code 61 and Code 62




**Flange Head (FL/ FLH, FLC)**




**4-Bolt Split Flange Bolt Hose Dimensions**

### Code 61 Inch Screw - SAE J518-1

| Dash Size | Assembly Torque* +10%-0 ft-lb | Assembly Torque Max. ft-lb | Assembly Torque* +10%-0 N·m | Assembly Torque Max. N·m |
|---|---|---|---|---|
| -8 | 24 | 29 | 32 | 40 |
| -12 | 44 | 55 | 60 | 75 |
| -16 | 44 | 55 | 60 | 75 |
| -20 | 68 | 85 | 92 | 115 |
| -24 | 111 | 138 | 150 | 188 |
| -32 | 111 | 138 | 150 | 188 |
| -40 | 111 | 138 | 150 | 188 |
| -48 | 217 | 272 | 295 | 369 |
| -56 | 217 | 272 | 295 | 369 |
| -64 | 217 | 272 | 295 | 369 |
| -80 | 217 | 272 | 295 | 369 |

* Values from SAE J2593 FEB2015

### Code 61 Metric Screw - SAE J518-1

| Dash Size | Assembly Torque* +10%-0 ft-lb | Assembly Torque Max. ft-lb | Assembly Torque* +10%-0 N·m | Assembly Torque Max. N·m |
|---|---|---|---|---|
| -8 | 24 | 29 | 32 | 40 |
| -12 | 52 | 64 | 70 | 88 |
| -16 | 52 | 64 | 70 | 88 |
| -20 | 52 | 64 | 70 | 88 |
| -24 | 96 | 120 | 130 | 163 |
| -32 | 96 | 120 | 130 | 163 |
| -40 | 96 | 120 | 130 | 163 |
| -48 | 217 | 272 | 295 | 369 |
| -56 | 217 | 272 | 295 | 369 |
| -64 | 217 | 272 | 295 | 369 |
| -80 | 217 | 272 | 295 | 369 |

* Values from SAE J2593 FEB2015

### Code 62 Inch Screw - SAE J518-2

| Dash Size | Assembly Torque* +10%-0 ft-lb | Assembly Torque Max. ft-lb | Assembly Torque* +10%-0 N·m | Assembly Torque Max. N·m |
|---|---|---|---|---|
| -8 | 24 | 29 | 32 | 40 |
| -12 | 44 | 55 | 60 | 75 |
| -16 | 68 | 85 | 92 | 115 |
| -20 | 111 | 138 | 150 | 188 |
| -24 | 217 | 272 | 295 | 369 |
| -32 | 332 | 415 | 450 | 563 |

* Values from SAE J2593 FEB2015

### Code 62 Metric Screw - SAE J518-2

| Dash Size | Assembly Torque* +10%-0 ft-lb | Assembly Torque Max. ft-lb | Assembly Torque* +10%-0 N·m | Assembly Torque Max. N·m |
|---|---|---|---|---|
| -8 | 24 | 29 | 32 | 40 |
| -12 | 52 | 64 | 70 | 88 |
| -16 | 96 | 120 | 130 | 163 |
| -20 | 96 | 120 | 130 | 163 |
| -24 | 217 | 272 | 295 | 369 |
| -32 | 405 | 507 | 550 | 688 |

* Values from SAE J2593 FEB2015

### Caterpillar Code 62 (FLC)

| Dash Size | Flange O.D. (in) | A (in) | B (in) | C (in) |
|---|---|---|---|---|
| -12 | 1.625 | .938 | 2.000 | .560 |
| -16 | 1.875 | 1.094 | 2.250 | .560 |
| -20 | 2.125 | 1.250 | 2.625 | .560 |
| -24 | 2.500 | 1.438 | 3.125 | .560 |
| -32 | 3.125 | 1.750 | 3.812 | .560 |

# NORTH AMERICAN THREAD TYPES – Continued


## O-Ring Face Seal (ORFS)—SAE J1453

A seal is made when the o-ring in the male contacts the flat face on the female. Couplings are intended for hydraulic systems where elastomeric seals are acceptable to overcome leakage and leak resistance is crucial.

The solid male o-ring face seal fitting will mate with a swivel female o-ring face seal SAE J1453 fitting only.

An o-ring rests in the o-ring groove in the male.

**O-Ring Face Seal**




**Male Flat-Face O-Ring (MFFOR)** **Female Flat-Face O-Ring Swivel (FFORX)**

| Dash Size | Nominal Size (in) | Thread Size | Female Thread I.D. (in) | Male Thread O.D. (in) | Assembly Torque* +25%-0 ft-lb | Assembly Torque Max. ft-lb | Assembly Torque* +25%-0 N·m | Assembly Torque Max. N·m | O-Ring Size |
|---|---|---|---|---|---|---|---|---|---|
| -4 | 1/4 | 9/16 - 18 | 1/2 | 9/16 | 18 | 23 | 25 | 31 | -011 |
| -6 | 3/8 | 11/16 - 16 | 5/8 | 11/16 | 29 | 37 | 40 | 50 | -012 |
| -8 | 1/2 | 13/16 - 16 | 3/4 | 13/16 | 41 | 51 | 55 | 69 | -014 |
| -10 | 5/8 | 1 - 14 | 15/16 | 1 | 44 | 55 | 60 | 75 | -016 |
| -12 | 3/4 | 1-3/16 - 12 | 1-1/8 | 1-3/16 | 66 | 83 | 90 | 113 | -018 |
| -16 | 1 | 1-7/16 - 12 | 1-11/32 | 1-7/16 | 92 | 115 | 125 | 156 | -021 |
| -20 | 1-1/4 | 1-11/16 - 12 | 1-19/32 | 1-11/16 | 125 | 157 | 170 | 213 | -025 |
| -24 | 1-1/2 | 2 - 12 | 1-29/32 | 2 | 147 | 184 | 200 | 250 | -029 |
| -32 | 2 | 2-1/2 - 12 | - | - | 376 | 470 | 510 | 638 | - |

* Values from SAE J2593 FEB2015

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# NORTH AMERICAN THREAD TYPES – Continued

## Flareless Tube

The flareless solid male will mate with a female flareless nut and compression sleeve only.

The male has straight threads and a 24° seat. The female has straight threads and has a compression sleeve for a sealing surface. The seal is made between the compression sleeve and the 24° seat on the male, and between the compression sleeve and the tubing on the female.

**Flareless Tube**





**Solid Male (MFA)** **Female Nut**

| Dash Size | Tube Size (in) | Nominal Size (in) | Thread Size | Female Thread I.D. (in) | Male Thread O.D. (in) |
|---|---|---|---|---|---|
| -2 | 1/8 | 5/16 | 5/16 – 24 | 17/64 | 5/16 |
| -3 | 3/16 | 3/8 | 3/8 – 24 | 21/64 | 3/8 |
| -4 | 1/4 | 7/16 | 7/16 – 20 | 25/64 | 7/16 |
| -5 | 5/16 | 1/2 | 1/2 – 20 | 29/64 | 1/2 |
| -6 | 3/8 | 9/16 | 9/16 – 18 | 1/2 | 9/16 |
| -8 | 1/2 | 3/4 | 3/4 – 16 | 11/16 | 3/4 |
| -10 | 5/8 | 7/8 | 7/8 – 14 | 13/16 | 7/8 |
| -12 | 3/4 | 1-1/16 | 1-1/16 – 12 | 31/32 | 1-1/16 |
| -14 | 7/8 | 1-3/16 | 1-3/16 – 12 | 1-7/64 | 1-3/16 |
| -16 | 1 | 1-5/16 | 1-5/16 – 12 | 1-15/64 | 1-5/16 |
| -20 | 1-1/4 | 1-5/8 | 1-5/8 – 12 | 1-35/64 | 1-5/8 |
| -24 | 1-1/2 | 1-7/8 | 1-7/8 – 12 | 1-51/64 | 1-7/8 |
| -32 | 2 | 2-1/2 | 2-1/2 – 12 | 2-27/64 | 2-1/2 |

## North American Stand Pipe (NASP)

A stand pipe assembly is comprised of three components attached to a male fitting. The components are a Stand Pipe Tube, Bite Sleeve and Nut. The Nut is placed over the Stand Pipe, followed by the Bite Sleeve (see illustration below). The Bite Sleeve and Stand Pipe are selected on the basis of tube O.D. required.

**North American Stand Pipe**



**Male Fitting Body** **Bite Sleeve** **Nut** **Standpipe Fitting (NASP)**


| Dash Size | Tube O.D. (in) | Tube Length (in) |
|---|---|---|
| -4 | 1/4 | 0.88 |
| -6 | 3/8 | 0.88 |
| -8 | 1/2 | 1.00 |
| -12 | 3/4 | 1.16 |
| -16 | 1 | 1.12 |

## SAE Inverted Flare

The SAE 45° inverted flare male will mate with an SAE 42° inverted flare female only.

The male has straight threads and a 45° inverted flare. The female has straight threads and a 42° inverted flare. The seal is made on the 45° flare seat on the male and the 42° flare seat on the female.

**SAE Inverted Flare**




**SAE Inverted Flare Swivel Male (MIX)** **SAE Inverted Flare Solid Female**

| Dash Size | Nominal Size (in) | Thread Size | Female Thread I.D. (in) | Male Thread O.D. (in) |
|---|---|---|---|---|
| -2 | 1/8 | 5/16 – 28 | 9/32 | 5/16 |
| -3 | 3/16 | 3/8 – 24 | 21/64 | 3/8 |
| -4 | 1/4 | 7/16 – 24 | 25/64 | 7/16 |
| -5 | 5/16 | 1/2 – 20 | 29/64 | 1/2 |
| -6 | 3/8 | 5/8 – 18 | 37/64 | 5/8 |
| -7 | 7/16 | 11/16 – 18 | 5/8 | 11/16 |
| -8 | 1/2 | 3/4 – 18 | 45/64 | 3/4 |
| -10 | 5/8 | 7/8 – 18 | 13/16 | 7/8 |
| -12 | 3/4 | 1-1/16 – 16 | 1 | 1-1/16 |


# NORTH AMERICAN THREAD TYPES – Continued

## Air Brake Fittings


Female air brake swivels are designed to work exclusively with a male air brake adapter. Federal law requires only this combination to be used on air brake lines from the valve to the air brake diaphragm chamber.

The male has straight threads and an inverted seat. The female has straight threads and a corresponding inverted flare. The seal is made on the flare seats of both the male and female.

| Dash Size | Thread Size | Female Thread I.D. (in) | Male Thread O.D. (in) |
|---|---|---|---|
| -6 | 3/4 – 20 | 23/32 | 3/4 |
| -8 | 7/8 – 20 | 27/32 | 7/8 |





**Male Air Brake**




**Female Air Brake Swivel**


## Grease Fittings

### Special Male Grease Fitting




**1/8–27 Pipe Thread**


### Special Female Grease Fitting





**1/2–27 Tapered Thread**

## Parker Triple Thread Flare Fittings

### Parker Triple Thread Flare Fittings




**Swivel Female (FZX)**




**Solid Male (MZ)**

| Dash Size | Nominal Size (in) | Thread Size | Female Thread I.D. (in) | Male Thread O.D. (in) |
|---|---|---|---|---|
| -16 | 1-5/16 | 1-5/16 – 14 | 1-1/4 | 1-5/16 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Foreign Thread Types

## Identifying Foreign Couplings

If you can identify the country of origin of the equipment you are working with, it is easy to identify the coupling style. Simply find the appropriate country in the following pages and locate the particular coupling in the table that follows.

# Foreign Thread Types – British

It is a common misconception that all foreign threads are metric. This is not always the case. There are two common thread forms: Metric and Whitworth (BSP). The country of origin and the proper nomenclature for each is listed below.

## British Standard Pipe Parallel


Popular couplings have British Standard Pipe (BSP) threads, also known as Whitworth threads. These can be parallel threads (BSPP) with a 30° inverted flare or tapered threads (BSPT), with a 30° inverted flare. Port connections are usually made with BSPP threads and a soft metal cutting ring for sealing. The BSPP (parallel) male will mate with a BSPOR (parallel) female or a female port.

The BSPP male has straight threads and a 30° seat. The BSPOR female has straight threads, a 30° seat, and o-ring. The female port has straight threads and a spotface. The seal on the port is made with an o-ring or soft metal washer on the male.


The BSPP (parallel) connector is similar to, but not interchangeable with, the NPSM connector. The thread pitch is different in most sizes, and the thread angle is 55° instead of the 60° angle found on NPSM threads.

| Dash Size | Nominal Size (in) | Thread Size | Female Parallel Thread | Male Parallel Thread | Torque Recommendation (ft-lb) | |
|---|---|---|---|---|---|---|
| | | | I.D. (in) | O.D. (in) | Min. | Max. |
| -2 | 1/8 | 1/8 – 28 | 11/32 | 3/8 | 7 | 9 |
| -4 | 1/4 | 1/4 – 19 | 15/32 | 17/32 | 11 | 18 |
| -6 | 3/8 | 3/8 – 19 | 19/32 | 21/32 | 19 | 28 |
| -8 | 1/2 | 1/2 – 14 | 3/4 | 13/16 | 30 | 36 |
| -10 | 5/8 | 5/8 – 14 | 13/16 | 29/32 | 37 | 44 |
| -12 | 3/4 | 3/4 – 14 | 31/32 | 1-1/32 | 50 | 60 |
| -16 | 1 | 1 – 11 | 1-7/32 | 1-11/32 | 79 | 95 |
| -20 | 1-1/4 | 1-1/4 – 11 | 1-17/32 | 1-21/32 | 127 | 152 |
| -24 | 1-1/2 | 1-1/2 – 11 | 1-25/32 | 1-7/8 | 167 | 190 |
| -32 | 2 | 2 – 11 | 2-7/32 | 2-11/32 | 262 | 314 |


### British Standard Pipe Parallel (BSPOR)




**BSPP Male (MBSPP)**




**BSPOR Female (FBSPORX)**





**BSPOR Female Port**

## British Flat-Face Seal


A seal is made when the o-ring in the male contacts the flat face on the female. These couplings are intended for hydraulic systems where elastomeric seals are acceptable to overcome leakage and leak resistance is crucial.

The solid male British o-ring face seal fitting will mate with a swivel female British o-ring face seal fitting only. An o-ring rests in the o-ring groove in the male.

| Dash Size | Nominal Size (in) | Thread Size | Female Parallel Thread | Male Parallel Thread | Torque Recommendation (ft-lb) | |
|---|---|---|---|---|---|---|
| | | | I.D. (in) | O.D. (in) | Min. | Max. |
| -6 | 3/8 | 3/8-19 | 19/32 | 21/32 | 18 | 20 |
| -8 | 1/2 | 1/2-14 | 3/4 | 13/16 | 32 | 40 |
| -10 | 5/8 | 5/8 - 14 | – | – | – | – |
| -12 | 3/4 | 3/4-14 | 31/32 | 1 1/32 | 65 | 80 |
| -16 | 1 | 1 - 11 | – | – | – | – |




**Male British Flat-Face (MBFF)**




**Female British Flat-Face (FBFF)**

# Foreign Thread Types – British – Continued

## British Standard Pipe Tapered


The BSPT (tapered) male will mate with a BSPT (tapered) female, or a BSPOR (parallel) female.

The BSPT male has tapered threads. When mating with either the BSPT (tapered) female or the BSPOR (parallel) female port, the seal is made on the threads.


The BSPT connector is similar to, but not interchangeable with, the NPTF connector. The thread pitch is different in most cases, and the thread angle is 55° instead of the 60° angle found on NPTF threads.

| Dash Size | Nominal Size (in) | Thread Size | Female Tapered Thread | Male Tapered Thread | Torque Recommendation (ft-lb) | |
|---|---|---|---|---|---|---|
| | | | I.D. (in) | O.D. (in) | Min. | Max. |
| -2 | 1/8 | 1/8 – 28 | 11/32 | 3/8 | 7 | 9 |
| -4 | 1/4 | 1/4 – 19 | 15/32 | 17/32 | 11 | 18 |
| -6 | 3/8 | 3/8 – 19 | 19/32 | 21/32 | 19 | 28 |
| -8 | 1/2 | 1/2 – 14 | 3/4 | 13/16 | 30 | 36 |
| -10 | 5/8 | 5/8 – 14 | 13/16 | 29/32 | 37 | 44 |
| -12 | 3/4 | 3/4 – 14 | 31/32 | 1-1/32 | 50 | 60 |
| -16 | 1 | 1 – 11 | 1-7/32 | 1-11/32 | 79 | 95 |
| -20 | 1-1/4 | 1-1/4 – 11 | 1-17/32 | 1-21/32 | 127 | 152 |
| -24 | 1-1/2 | 1-1/2 – 11 | 1-25/32 | 1-7/8 | 167 | 190 |
| -32 | 2 | 2 – 11 | 2-7/32 | 2-11/32 | 262 | 314 |

### British Standard Pipe Tapered (BSPT)




**BSPT Male (MBSPT)**




**BSPT Female**

# Foreign Thread Types – French

Popular couplings are French GAZ. These have a 24° seat and metric threads. These are similar to German DIN couplings, but the threads are different in some sizes. Although both are metric threads, the French use fine threads in all sizes and German DIN couplings use coarse threads in larger sizes. Most port connections are flange connections. French flanges are different than SAE—they have a lip that protrudes from the flange face. These are called Poclain-style flanges.

## GAZ 24°


The French Metric (GAZ) male will mate with the female 24° cone or the female tube fitting.

The male has a 24° seat and straight metric threads. The female has a 24° seat or a tubing sleeve and straight metric threads and is interchangeable with female Kobelco.


When measuring the flare angle with the seat angle gauge, use the 12° gauge. The seat angle gauge measures the angle from the connector centerline.

| Metric Thread Size | Female Thread I.D. (mm) | Male Thread O.D. (mm) | Tube O.D. (mm) |
|---|---|---|---|
| M20x1.5 | 18.5 | 20.0 | 13.25 |
| M24x1.5 | 22.5 | 24.0 | 16.75 |
| M30x1.5 | 28.5 | 30.0 | 21.25 |
| M36x1.5 | 34.5 | 36.0 | 26.75 |
| M45x1.5 | 43.5 | 45.0 | 33.50 |
| M52x1.5 | 50.5 | 52.0 | 42.25 |


### French Metric (GAZ)




**Male 24° Cone**




**Female 24° Cone**




**Female Tube Fitting**

# Foreign Thread Types – French – Continued


## GAZ Poclain 24° Flange

The Poclain (French GAZ) 24° high pressure flange is usually found on Poclain equipment.

The male flange will mate with a female flange or port. The seal is made on the 24° seat.

| Nominal Size (in) | A (in) | B (in) | C (in) | D (in) | E (in) | F (in) |
|---|---|---|---|---|---|---|
| 1/2 | 1.57 | .72 | 2.20 | 1.89 | .55 | .35 |
| 5/8 | 1.57 | .72 | 2.20 | 1.89 | .55 | .35 |
| 3/4 | 2.00 | .94 | 2.75 | 2.38 | .71 | .43 |

**Poclain (French GAZ)**




**Male Flange** **Female Flange** **Flange Clamp**

# Foreign Thread Types – German DIN (Deutsche Industrial Norme)

Popular couplings are German DIN (Deutsche Industrial Norme). A coupling referred to as “metric” usually means a DIN coupling.

## DIN 24° Cone


The DIN 24° cone male will mate with any of the females shown.

The male has a 24° seat, straight metric threads, and a recessed counterbore which matches the tube O.D. of the coupling used with it. The mating female is a 24° cone with o-ring, a metric tube fitting or a universal 24° and 60° cone. There is a light and heavy series DIN coupling. Proper identification is made by measuring both the thread size and the tube O.D. (The heavy series has a smaller tube O.D. but a thicker wall section than the light.)

When measuring the flare angle with the seat angle gauge, use the 12° gauge. The seat angle gauge measures the angle from the connector centerline.

| Metric Thread Size | Female Thread | Male Thread | Tube O.D. | | Torque Recommendation (ft-lb) | |
|---|---|---|---|---|---|---|
| | I.D. (mm) | O.D. (mm) | Light Series (mm) | Heavy Series (mm) | Min. | Max. |
| M12x1.5 | 10.5 | 12.0 | 6 | — | 7 | 15 |
| M14x1.5 | 12.5 | 14.0 | 8 | — | 15 | 26 |
| M16x1.5 | 14.5 | 16.0 | 10 | 8 | 18 | 30 |
| M18x1.5 | 16.5 | 18.0 | 12 | 10 | 22 | 33 |
| M20x1.5 | 18.5 | 20.0 | 14 | 12 | 26 | 37 |
| M22x1.5 | 20.5 | 22.0 | 15 | 14 | 30 | 52 |
| M24x1.5 | 22.5 | 24.0 | — | 16 | 30 | 52 |
| M26x1.5 | 24.5 | 26.0 | 18 | — | 44 | 74 |
| M30x2.0 | 28.0 | 30.0 | 22 | 20 | 59 | 89 |
| M36x2.0 | 34.0 | 36.0 | 28 | 25 | 74 | 111 |
| M42x2.0 | 40.0 | 42.0 | — | 30 | 74 | 162 |
| M45x2.0 | 43.0 | 45.0 | 35 | — | 133 | 184 |
| M52x2.0 | 50.0 | 52.0 | 42 | 38 | 148 | 221 |

**DIN 24° Male and Mating Females**




**Male 24° Cone, DIN 2353 (MDL/MDH)** **Female 24° Cone with O-Ring (FDLORX/FDHORX)** **Female Universal 24° and 60° Cone (FDLX/FDHX)**

# Foreign Thread Types – German DIN – Continued

## DIN 60° Cone


The DIN 60° cone male will mate with the female universal 24° or 60° cone connector only.

The male has a 60° seat and straight metric threads. The female has a 24° and 60° universal seat and straight metric threads.


When measuring the flare angle with the seat angle gauge, use the 30° gauge. The seat angle gauge measures the angle from the connector centerline.

| Metric Thread Size | Female Thread | Male Thread | Tube O.D. | Torque Recommendation (ft-lb) | |
|---|---|---|---|---|---|
| | I.D. (mm) | O.D. (mm) | (mm) | Min. | Max. |
| M14x1.5 | 12.5 | 14.0 | 8 | 15 | 26 |
| M16x1.5 | 14.5 | 16.0 | 10 | 18 | 30 |
| M18x1.5 | 16.5 | 18.0 | 12 | 22 | 33 |
| M22x1.5 | 20.5 | 22.0 | 15 | 30 | 52 |
| M26x1.5 | 24.5 | 26.0 | 18 | 44 | 74 |
| M30x1.5 | 28.5 | 30.0 | 22 | 59 | 59 |
| M38x1.5 | 36.5 | 38.0 | 28 | 74 | 111 |
| M45x1.5 | 43.5 | 45.0 | 35 | 133 | 184 |
| M52x2.0 | 50.5 | 52.0 | 42 | 148 | 221 |

### DIN 60° Male and Mating Female




**Male 60° Cone, DIN 6711**




**Female Universal 24° and 60° Cone**

# Foreign Thread Types – German DIN – Continued

## DIN 3852 Couplings Type A & B (Parallel Threads)


The male DIN 3852 Type A & B couplings will mate with the female DIN coupling shown below. Gates offers this thread as an adapter.

The male and female type A & B couplings have straight threads. The seal occurs when the ring seal (Type A) or the face seal (Type B) mates with the face of the female port.


There are two series of DIN 3852 Type A & B couplings, the light (L) and the heavy (S) series.

**Note:** Commonly used threads on male metric adapters.

### DIN 3852 Couplings Type A & B (Parallel Threads)




**Male Type A** **Male Type B**




**Female Types A & B**

| Series | Tube O.D. (mm) | Metric Thread Parallel | | | | | | | | Whitworth Thread Parallel | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | Female | | | Male | | | | | Female (BSPOR) | | | Male (BSPP) | | | |
| | | Thread Size | Thread I.D. (mm) | A (mm) | B (mm) | Thread O.D. (mm) | A (mm) | B (mm) | C (mm) | Thread Size | Thread I.D. (in) | A (mm) | B (mm) | Thread O.D. (in) | A (mm) | B (mm) | C (mm) |
| L Light | 6 | 10x1.0 | 8.5 | 15 | 1.0 | 10 | 14 | 1.5 | 8 | 1/8-28 | 11/32 | 15 | 1.0 | 3/8 | 14 | 1.5 | 8 |
| | 8 | 12x1.5 | 10.5 | 18 | 1.5 | 12 | 17 | 2.0 | 12 | 1/4-19 | 15/32 | 19 | 1.5 | 1/2 | 17 | 2.0 | 12 |
| | 10 | 14x1.5 | 12.5 | 20 | 1.5 | 14 | 19 | 2.0 | 12 | 1/4-19 | 15/32 | 19 | 1.5 | 1/2 | 19 | 2.0 | 12 |
| | 12 | 16x1.5 | 14.5 | 22 | 1.5 | 16 | 21 | 2.5 | 12 | 3/8-19 | 19/32 | 23 | 2.0 | 21/32 | 21 | 2.5 | 12 |
| | 15 | 18x1.5 | 16.5 | 24 | 2.0 | 18 | 23 | 2.5 | 12 | 1/2-14 | 3/4 | 27 | 2.5 | 13/16 | 23 | 2.5 | 12 |
| | 18 | 22x1.5 | 20.5 | 28 | 2.5 | 22 | 27 | 3.0 | 14 | 1/2-14 | 3/4 | 27 | 2.5 | 13/16 | 27 | 3.0 | 14 |
| | 22 | 26x1.5 | 24.5 | 32 | 2.5 | 26 | 31 | 3.0 | 16 | 3/4-14 | 31/32 | 33 | 2.5 | 1-1/32 | 31 | 3.0 | 16 |
| | 28 | 33x2.0 | 31.5 | 40 | 2.5 | 33 | 39 | 3.0 | 18 | 1-11 | 1-7/32 | 40 | 2.5 | 1-5/16 | 39 | 3.0 | 18 |
| | 35 | 42x2.0 | 40.5 | 50 | 2.5 | 42 | 49 | 3.0 | 20 | 1-1/4-11 | 1-17/32 | 50 | 2.5 | 1-21/32 | 49 | 3.0 | 20 |
| | 42 | 48x2.0 | 46.5 | 56 | 2.5 | 48 | 55 | 3.0 | 22 | 1-1/2-11 | 1-25/32 | 56 | 2.5 | 1-7/8 | 55 | 3.0 | 22 |
| S Heavy | 6 | 12x1.5 | 10.5 | 18 | 1.5 | 12 | 17 | 2.0 | 12 | 1/4-19 | 15/32 | 19 | 1.5 | 1/2 | 17 | 2.0 | 12 |
| | 8 | 14x1.5 | 12.5 | 20 | 1.5 | 14 | 19 | 2.0 | 12 | 1/4-19 | 15/32 | 19 | 1.5 | 1/2 | 19 | 2.0 | 12 |
| | 10 | 16x1.5 | 14.5 | 22 | 1.5 | 16 | 21 | 2.5 | 12 | 3/8-19 | 19/32 | 23 | 2.0 | 21/32 | 21 | 2.5 | 12 |
| | 12 | 18x1.5 | 16.5 | 24 | 2.0 | 18 | 23 | 2.5 | 12 | 3/8-19 | 19/32 | 23 | 2.0 | 21/32 | 23 | 2.5 | 12 |
| | 14 | 20x1.5 | 18.5 | 26 | 2.0 | 20 | 25 | 3.0 | 14 | 1/2-14 | 3/4 | 27 | 2.5 | 13/16 | 25 | 3.0 | 14 |
| | 16 | 22x1.5 | 20.5 | 28 | 2.5 | 22 | 27 | 3.0 | 14 | 1/2-14 | 3/4 | 27 | 2.5 | 13/16 | 27 | 3.0 | 14 |
| | 20 | 27x2.0 | 25.5 | 33 | 2.5 | 27 | 32 | 3.0 | 16 | 3/4-14 | 31/32 | 33 | 2.5 | 1-1/32 | 32 | 3.0 | 16 |
| | 25 | 33x2.0 | 31.5 | 40 | 2.5 | 33 | 39 | 3.0 | 18 | 1-11 | 1-7/32 | 40 | 2.5 | 1-5/16 | 39 | 3.0 | 18 |
| | 30 | 42x2.0 | 40.5 | 50 | 2.5 | 42 | 49 | 3.0 | 20 | 1-1/4-11 | 1-17/32 | 50 | 2.5 | 1-21/32 | 49 | 3.0 | 20 |
| | 38 | 48x2.0 | 46.5 | 56 | 2.5 | 48 | 55 | 3.0 | 22 | 1-1/2-11 | 1-25/32 | 56 | 2.5 | 1-7/8 | 55 | 3.0 | 22 |


# Foreign Thread Types – German DIN – Continued

## DIN 3852 Type C Metric and Whitworth Tapered (BSPT) Thread Connectors

The DIN 3852 Type C couplings are available with either metric or Whitworth British thread. The male will mate only with the female as shown.

The male and female couplings have tapered threads. The seal takes place on the threads. There are three series of DIN 3852 Type C Couplings: extra light (LL), light (L) and heavy (S).

### DIN 3852 Type C Metric and Whitworth Tapered Thread Connectors





**Male** **Female**

| Series | Tube O.D. (mm) | Metric Tapered Threads | | | | | | Whitworth Tapered Threads | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Thread Size | Female | | Male | | | Thread Size | Female | | Male | | |
| | | | Thread I.D. (mm) | A (mm) | Thread O.D. (mm) | A (mm) | B (mm) | | Thread I.D. (in) | A (mm) | Thread O.D. (in) | A (mm) | B (mm) |
| LL Extra Light | 4 | 8x1.0 | 6.5 | 5.5 | 8 | 8.40 | 8 | 1/8-28 | 11/32 | 5.5 | 1/8 | .392 | 8 |
| | 5 | 8x1.0 | 6.5 | 5.5 | 8 | 8.40 | 8 | 1/8-28 | 11/32 | 5.5 | 1/8 | .392 | 8 |
| | 6 | 10x1.0 | 8.5 | 5.5 | 10 | 10.40 | 8 | 1/8-28 | 11/32 | 5.5 | 1/8 | .392 | 8 |
| | 8 | 10x1.0 | 8.5 | 5.5 | 10 | 10.40 | 8 | 1/8-28 | 11/32 | 5.5 | 1/8 | .392 | 8 |
| L Light | 6 | 10x1.0 | 8.5 | 5.5 | 10 | 10.40 | 8 | 1/8-28 | 11/32 | 5.5 | 1/8 | .392 | 8 |
| | 8 | 12x1.5 | 10.5 | 8.5 | 12 | 12.53 | 12 | 1/4-19 | 15/32 | 8.5 | 1/4 | .532 | 12 |
| | 10 | 14x1.5 | 12.5 | 8.5 | 14 | 14.53 | 12 | 1/4-19 | 15/32 | 8.5 | 1/4 | .532 | 12 |
| | 12 | 16x1.5 | 14.5 | 8.5 | 16 | 16.53 | 12 | 3/8-19 | 19/32 | 8.5 | 3/8 | .670 | 12 |
| | 15 | 18x1.5 | 16.5 | 8.5 | 18 | 18.53 | 12 | 1/2-14 | 3/4 | 8.5 | 1/2 | .839 | 14 |
| | 18 | 22x1.5 | 20.5 | 10.5 | 22 | 22.65 | 14 | 1/2-14 | 3/4 | 10.5 | 1/2 | .839 | 14 |
| S Heavy | 6 | 12x1.5 | 10.5 | 8.5 | 12 | 12.53 | 12 | 1/4-19 | 15/32 | 8.5 | 1/4 | .532 | 12 |
| | 8 | 14x1.5 | 12.5 | 8.5 | 14 | 14.53 | 12 | 1/4-19 | 15/32 | 8.5 | 1/4 | .532 | 12 |
| | 10 | 16x1.5 | 14.5 | 8.5 | 16 | 16.53 | 12 | 3/8-19 | 19/32 | 8.5 | 3/8 | .670 | 12 |
| | 12 | 18x1.5 | 16.5 | 8.5 | 18 | 18.53 | 12 | 3/8-19 | 19/32 | 8.5 | 3/8 | .670 | 12 |
| | 14 | 20x1.5 | 18.5 | 10.5 | 20 | 20.65 | 14 | 1/2-14 | 3/4 | 10.5 | 1/2 | .839 | 14 |
| | 16 | 22x1.5 | 20.5 | 10.5 | 22 | 22.65 | 14 | 1/2-14 | 3/4 | 10.5 | 1/2 | .839 | 14 |

## Metric Stand Pipe Assembly

A metric stand pipe assembly is comprised of three components attached to a male fitting. The components are: a Stand Pipe Tube, Bite Sleeve and Metric Nut. The nut is placed over the Stand Pipe, followed by the Bite Sleeve (see illustration below). For DIN light assemblies, a DIN light metric nut is used. For DIN heavy assemblies, a DIN heavy metric nut is used. The Bite Sleeve and Stand Pipe are selected on the basis of tube O.D.

### Metric Standpipe Assembly



**DIN 2353 Male Fitting Body (MDL)** **Bite Sleeve** **Nut** **Standpipe Fitting (MSP)**

| Metric Stand Pipe DIN Tube O.D. (mm) | Bite Sleeve DIN Tube O.D. (mm) | Metric Nut Thread |
|---|---|---|
| | | Light |
| 6 | 6 | M12x1.5 |
| 8 | 8 | M14x1.5 |
| 10 | 10 | M16x1.5 |
| 12 | 12 | M18x1.5 |
| 15 | 15 | M22x1.5 |
| 18 | 18 | M26x1.5 |
| 22 | 22 | M30x2.0 |
| 28 | 28 | M36x2.0 |
| 35 | 35 | M45x2.0 |
| 42 | 42 | M52x2.0 |

# Foreign Thread Types – Japanese

There are two popular types of coupling styles in Japan, Japanese Industrial Standard and Komatsu. These couplings look similar to Male JIC and Female JIC Swivel couplings. However there are two major differences: The threads are BSP and the seat angle is only 30° instead of 37° for JIC.

1. **Japanese Industrial Standard.** Most Japanese equipment uses this type of coupling with a 30° seat and British Standard Pipe Parallel threads. They are not interchangeable with British couplings, since the flare is not inverted.
2. **Komatsu.** All Komatsu equipment uses couplings with a 30° seat and metric fine threads. All flanges are Code 61 or Code 62, except -10 which utilizes a special Komatsu-style flange that does not conform to SAE standard sizing.


## Japanese 30° Flare Parallel Threads

The Japanese 30° flare male connector will mate with a Japanese 30° flare female only.

The male and female have straight threads and a 30° seat. The seal is made on the 30° seat.

The threads on the Japanese 30° flare connector conform to JIS B 0202, which are the same as the BSPOR threads. Both the British and Japanese connectors have a 30° seat, but they are not interchangeable because the British seat is inverted.

**Japanese 30° Flare**




**Male (MJIS)** **Female (FJISX)**

| Dash Size | Nominal Size (in) | Thread Size | Female Thread I.D. (in) | Male Thread O.D. (in) |
|---|---|---|---|---|
| -2 | 1/8 | 1/8 – 28 | 11/32 | 3/8 |
| -4 | 1/4 | 1/4 – 19 | 7/16 | 17/32 |
| -6 | 3/8 | 3/8 – 19 | 19/32 | 21/32 |
| -8 | 1/2 | 1/2 – 14 | 3/4 | 13/16 |
| -10 | 5/8 | 5/8 – 14 | 13/16 | 29/32 |
| -12 | 3/4 | 3/4 – 14 | 15/16 | 1-1/32 |
| -16 | 1 | 1 – 11 | 1-13/16 | 1-15/16 |
| -20 | 1-1/4 | 1-1/4 – 11 | 1-17/32 | 1-21/32 |
| -24 | 1-1/2 | 1-1/2 – 11 | 1-25/32 | 1-7/8 |
| -32 | 2 | 2 – 11 | 2-7/32 | 2-11/32 |


## Japanese Tapered Pipe Thread

The Japanese tapered pipe thread connector is identical to and fully interchangeable with the BSPT (tapered) connector. The Japanese connector does not have a 30° flare and will not mate with the BSPOR female.

The threads conform to JIS B 0203, which are the same as BSPT threads.

The seal on the Japanese tapered pipe thread connector is made on the threads.

**Japanese Tapered Pipe Thread**




**Male (MBSPT)** **Female (FBSPT)**

| Dash Size | Nominal Size (in) | Thread Size | Female Tapered Thread I.D. (in) | Male Tapered Thread O.D. (in) |
|---|---|---|---|---|
| -2 | 1/8 | 1/8 – 28 | 11/32 | 3/8 |
| -4 | 1/4 | 1/4 – 19 | 7/16 | 17/32 |
| -6 | 3/8 | 3/8 – 19 | 19/32 | 21/32 |
| -8 | 1/2 | 1/2 – 14 | 3/4 | 13/16 |
| -12 | 3/4 | 3/4 – 14 | 15/16 | 1-1/32 |
| -16 | 1 | 1 – 11 | 1-13/16 | 1-15/16 |
| -20 | 1-1/4 | 1-1/4 – 11 | 1-17/32 | 1-21/32 |
| -24 | 1-1/2 | 1-1/2 – 11 | 1-25/32 | 1-7/8 |
| -32 | 2 | 2 – 11 | 2-7/32 | 1-11/32 |
| -32 | 2 | 2 – 11 | 2-7/32 | 2-11/32 |

# Foreign Thread Types – Japanese – Continued


## Komatsu Style 30° Flare Parallel Threads

The Komatsu style 30° flare parallel thread connector is identical to the Japanese 30° flare parallel thread connector except for the threads. The Komatsu style connector uses metric fine threads which conform to JIS B 0207. Gates identifies these as Komatsu-style by marking the hex nuts with two small notches.

The Komatsu style connector seals on the 30° flare.

| Dash Size | Nominal Size (in) | Nominal Size (mm) | Thread Size | Female Thread I.D. (mm) | Male Thread (O.D.) (mm) |
|---|---|---|---|---|---|
| -4 | 1/4 | 6.4 | M14x1.5 | 12.5 | 14 |
| -6 | 3/8 | 9.5 | M18x1.5 | 16.5 | 18 |
| -8 | 1/2 | 12.7 | M22x1.5 | 20.5 | 22 |
| -10 | 5/8 | 15.9 | M24x1.5 | 22.5 | 24 |
| -12 | 3/4 | 19.1 | M30x1.5 | 28.5 | 30 |
| -16 | 1 | 25.4 | M33x1.5 | 31.5 | 33 |
| -20 | 1-1/4 | 31.8 | M36x1.5 | 34.5 | 36 |
| -24 | 1-1/2 | 38.1 | M42x1.5 | 40.5 | 42 |

### Komatsu Style 30° Flare




**Female (FKX)** **Male (MK)**


## Komatsu Style Flange Fitting

The Komatsu style flange fitting is nearly identical to and fully interchangeable with the SAE Code 61 flange fitting. In all sizes the o-ring dimensions are different. When replacing a Komatsu style flange with an SAE style flange, an SAE style o-ring must always be used.

| Dash Size | Nominal Size (in) | Nominal Size (mm) | Flange O.D. (in) | A (in) | B (in) |
|---|---|---|---|---|---|
| -8 | 1/2 | 12.7 | 1.188 | .728 | .984 |
| -10* | 5/8 | 15.9 | 1.345 | .728 | 1.102 |
| -12 | 3/4 | 19.1 | 1.500 | .846 | 1.220 |
| -16 | 1 | 25.4 | 1.750 | 1.122 | 1.496 |
| -20 | 1-1/4 | 31.8 | 2.000 | 1.358 | 1.732 |
| -24 | 1-1/2 | 38.1 | 2.375 | 1.750 | 2.125 |
| -32 | 2 | 50.8 | 2.812 | 2.225 | 2.559 |

*(-10 is a non-SAE size flange)

### Komatsu Style Flange Fitting





**Flange (FL)** **Flange Head**

## Metric Kobelco

These are similar to the German DIN 24° cone, but the DIN style uses courser threads. Therefore, the Kobelco and German DIN are not interchangeable for female Kobelco (see French GAZ 24° swivel).

| Dash Size | Metric Thread Size | Female Thread I.D. (mm) | Male Thread O.D. (mm) |
|---|---|---|---|
| -22 | M30X1.5 | 28 | 30 |
| -28 | M36X1.5 | 34 | 36 |
| -35 | M45X1.5 | 43 | 45 |




**Male 24° Cone (MKB)**

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# GATES GLOBAL PART NUMBERING SYSTEM

Gates couplings feature a meaningful part number that makes coupling identification fast and easy. Always refer to Gates Crimp Data Manual when selecting hose and coupling combinations.

In the following example, the Global Part Number G25100-0808 identifies a MegaCrimp® Male Pipe (MP) coupling with -8 (1/2") stem size and -8 (1/2") thread size.

**G25100-0808**

- G25100 — Series Stem Style (see below)
- 08 — Thread Configuration (see following pages)
- 08 — Stem Size
- 08 — Thread Size

## Series Stem Styles:

**G17**- Stainless Steel Braid Couplings
**G18**- Stainless Steel Spiral Couplings
**G19**- G8K Couplings

**G20**- GlobalSpiral™ Couplings
**G21**- GlobalSpiral™ One Piece Couplings For MC4-20 Crimper
**G22**- GlobalSpiral™ Plus (GSP)
**G23**- GlobalSpiral™ Max (GSM) Pressure Couplings (-32)
**G24**- GlobalSpiral™ Max (GSM) Pressure Couplings (-24)
**G25**- MegaCrimp® Couplings
**G27**- Field Attachable Type T for G1 Hose (1 Wire)
**G28**- Field Attachable Type T for G2 Hose (2 Wire)

**G33**- Air Brake Couplings For Rubber Hose
**G34**- Field Attachable for C5CXH, C5C, C5D & C5M Hose
**G35**- Field Attachable for C5E Hose
**G36** - Brass Lock-On Field Attachable Couplings for LOC & LOL Hose
**G37**- Single Bead
**G38**- Barbed Stem

**G40**- C14 Couplings
**G43**- GL Couplings
**G44**- GLX® Couplings
**G45**- PolarSeal® Couplings (ACA)
**G46**- PolarSeal® II Couplings (ACC)
**G47**- PolarSeal® II Couplings (ACB)

**G50**- Power Steering Couplings
**G51**- PCTS Thermoplastic Couplings

## Other Non-Stem Series Styles:

**G52**- Gates OE-Style Clamp Collars

**G60**- SAE to SAE Adapters
**G62**- British to SAE Adapters
**G63**- Metric Conversion Adapters
**G64**- International to International Adapters
**G65**- Japanese Conversion Adapters

**G73**- Ermeto Adapters

**G80**- Hose Bend Restrictors
**G81**- Hose Guards
**G82**- Plated Flat Armor Spring Guards
**G83**- Plated Wire Spring Guards
**G89**- C14 Assembly

**G93**- Live Swivel
**G94**- Quick Disconnect Couplers
**G95**- Quick Disconnect Couplers
**G96**- Ball Valves

# Thread Configurations for Stem Styles

These three-digit numbers identify the various coupling thread configurations

| | | |
|---|---|---|
| **100**- | MP | Male Pipe (NPTF - 30° Cone Seat) |
| **101**- | MPLN | Male Pipe Long Nose |
| **102**- | MPAPI | API Line Pipe Connection |
| **103**- | MPLH | Male Pipe (NPTF - 30° Cone Seat) - Long Hex |
| **105**- | MPX | Male Pipe Swivel (NPTF - Without 30° Cone Seat) |
| **106**- | MPX90 | Male Pipe Swivel - 90° Block (NPTF - Without 30° Cone Seat) |
| **107**- | MPX90L | Male Pipe Swivel - 90° Long Block (NPTF - Without 30° Cone Seat) |
| **110**- | FP | Female Pipe (NPTF - Without 30° Cone Seat) |
| **111**- | FPX | Female Pipe Swivel (NPSM - 30° Cone Seat) |
| **120**- | MB | Male O-Ring Boss |
| **121**- | MBX | Male O-Ring Boss Swivel |
| **122**- | MBX45BL | Male O-Ring Boss Swivel - 45° Block |
| **123**- | MBX90BL | Male O-Ring Boss Swivel - 90° Block |
| **124**- | MBX90BLL | Male O-Ring Boss Swivel - 90° Block Long |
| **126**- | MBX45 | Male O-Ring Boss Swivel - 45° Bent Tube |
| **128**- | MBX90 | Male O-Ring Boss Swivel - 90° Bent Tube |
| **134**- | MBAX90M | Male O-Ring Boss Adapterless Swivel - 90° Bent Tube - Medium |
| **140**- | FMX | Female MegaSeal Swivel |
| **145**- | FMX45 | Female MegaSeal Swivel - 45° Bent Tube |
| **149**- | FMX90S | Female MegaSeal Swivel - 90° Bent Tube - Short |
| **150**- | FMX90 | Female MegaSeal Swivel - 90° Bent Tube |
| **151**- | FMX90L | Female MegaSeal Swivel - 90° Bent Tube - Long |
| **165**- | MJ | Male JIC 37° Flare |
| **170**- | FJX | Female JIC 37° Flare Swivel |
| **171**- | FJXL | Female JIC 37° Flare Swivel - Long |
| **172**- | FJX30 | Female JIC 37° Flare Swivel - 30° Bent Tube |
| **174**- | FJX45S | Female JIC 37° Flare Swivel - 45° Bent Tube - Short |
| **175**- | FJX45 | Female JIC 37° Flare Swivel - 45° Bent Tube |
| **176**- | FJX45L | Female JIC 37° Flare Swivel - 45° Bent Tube - Long |
| **177**- | FJX60 | Female JIC 37° Flare Swivel - 60° Bent Tube |
| **179**- | FJX90S | Female JIC 37° Flare Swivel - 90° Bent Tube - Short |
| **180**- | FJX90M | Female JIC 37° Flare Swivel - 90° Bent Tube - Medium |
| **181**- | FJX90L | Female JIC 37° Flare Swivel - 90° Bent Tube - Long |
| **182**- | FJX90XL | Female JIC 37° Flare Swivel - 90° Bent Tube - Extra Long |
| **183**- | FJX90 | Female JIC 37° Flare Swivel - 90° Bent Tube |
| **187**- | FJX90BLK | Female JIC 37° Flare Swivel - 90° Block |
| **195**- | MS | Male SAE 45° Flare |
| **196**- | MS45 | Male SAE 45° Flare - 45° Bent Tube |
| **197**- | MS90 | Male SAE 45° Flare - 90° Bent Tube |
| **200**- | FSX | Female SAE 45° Flare Swivel |
| **202**- | FSX45 | Female SAE 45° Flare Swivel - 45° Bent Tube |
| **204**- | FSX90S | Female SAE 45° Flare Swivel - 90° Bent Tube - Short |
| **205**- | FSX90 | Female SAE 45° Flare Swivel - 90° Bent Tube |
| **206**- | FSX90L | Female SAE 45° Flare Swivel - 90° Bent Tube - Long |
| **210**- | FJSX | Dual Seat Female JIC 37°/SAE 45° Flare Swivel |
| **211**- | FJSX45 | Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 45° Bent Tube |
| **212**- | FJSX90 | Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 90° Bent Tube |
| **213**- | FJSX90L | Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 90° Bent Tube - Long |
| **225**- | MFFOR | Male Flat-Face O-Ring |
| **226**- | MFFORBKHDLN | Male Flat-Face O-Ring Bulk Head Long Nose |
| **228**- | MFFORBKHD | Male Flat-Face O-Ring Bulk Head |
| **230**- | FFORX | Female Flat-Face O-Ring Swivel |
| **232**- | FFORX22 | Female Flat-Face O-Ring Swivel - 22 1/2° Bent Tube |
| **233**- | FFORX30 | Female Flat-Face O-Ring Swivel - 30° Bent Tube |
| **234**- | FFORX45S | Female Flat-Face O-Ring Swivel - 45° Bent Tube - Short |
| **235**- | FFORX45 | Female Flat-Face O-Ring Swivel - 45° Bent Tube |
| **238**- | FFORX67 | Female Flat-Face O-Ring Swivel - 67 1/2° Bent Tube |
| **239**- | FFORX90S | Female Flat-Face O-Ring Swivel - 90° Bent Tube - Short |
| **240**- | FFORX90M | Female Flat-Face O-Ring Swivel - 90° Bent Tube - Medium |
| **241**- | FFORX90L | Female Flat-Face O-Ring Swivel - 90° Bent Tube - Long |
| **248**- | FFORX135 | Female Flat-Face O-Ring Swivel - 135° Bent Tube |
| **300**- | FL | Code 61 O-Ring Flange |
| **301**- | FLL | Code 61 O-Ring Flange Long Neck |
| **302**- | FL22M | Code 61 O-Ring Flange - 22 1/2° Bent Tube - Medium |
| **304**- | FL30 | Code 61 O-Ring Flange - 30° Bent Tube |
| **306**- | FL45S | Code 61 O-Ring Flange - 45° Bent Tube - Short |
| **307**- | FL45 | Code 61 O-Ring Flange - 45° Bent Tube |
| **308**- | FL60S | Code 61 O-Ring Flange - 60° Bent Tube - Short |
| **309**- | FL60M | Code 61 O-Ring Flange - 60° Bent Tube - Medium |
| **311**- | FL67 | Code 61 O-Ring Flange - 67 1/2° Bent Tube |
| **313**- | FL90XS | Code 61 O-Ring Flange - 90° Bent Tube - Extra Short |
| **314**- | FL90S | Code 61 O-Ring Flange - 90° Bent Tube - Short |
| **315**- | FL90M | Code 61 O-Ring Flange - 90° Bent Tube - Medium |
| **316**- | FL90L | Code 61 O-Ring Flange - 90° Bent Tube - Long |
| **317**- | FL90XL | Code 61 O-Ring Flange - 90° Bent Tube - Extra Long |
| **318**- | FL90XXL | Code 61 O-Ring Flange - 90° Bent Tube - Extra Extra Long |
| **319**- | FL90 | Code 61 O-Ring Flange - 90° Bent Tube (Non-ISO) |
| **323**- | FL100 | Code 61 O-Ring Flange - 100° Bent Tube |
| **325**- | FL110 | Code 61 O-Ring Flange - 110° Bent Tube |
| **327**- | FL120 | Code 61 O-Ring Flange - 120° Bent Tube |
| **329**- | FL125 | Code 61 O-Ring Flange - 125° Bent Tube |
| **331**- | FL135 | Code 61 O-Ring Flange - 135° Bent Tube |
| **333**- | FLCF | Code 61 Captive O-Ring Flange |
| **334**- | FLCF45 | Code 61 Captive O-Ring Flange - 45° Bent Tube |
| **335**- | FLCF90 | Code 61 Captive O-Ring Flange - 90° Bent Tube |
| **342**- | RFL90S | Special Flange - 90° |
| **350**- | FLH | Code 62 O-Ring Flange Heavy |
| **352**- | FLH22 | Code 62 O-Ring Flange Heavy - 22 1/2° Bent Tube |
| **353**- | FLH20 | Code 62 O-Ring Flange Heavy - 22° Bent Tube |
| **354**- | FLH30 | Code 62 O-Ring Flange Heavy - 30° Bent Tube |
| **355**- | FLH30 | Code 62 O-Ring Flange Heavy - 30° Bent Tube (Non-Std.) |
| **357**- | FLH45 | Code 62 O-Ring Flange Heavy - 45° Bent Tube |
| **359**- | FLH60 | Code 62 O-Ring Flange Heavy - 60° Bent Tube |
| **360**- | FLH67 | Code 62 O-Ring Flange Heavy - 67 1/2° Bent Tube |
| **364**- | FLH90S | Code 62 O-Ring Flange Heavy - 90° Bent Tube - Short |
| **365**- | FLH90M | Code 62 O-Ring Flange Heavy - 90° Bent Tube - Medium |
| **366**- | FLH90L | Code 62 O-Ring Flange Heavy - 90° Bent Tube - Long |
| **367**- | FLH90XL | Code 62 O-Ring Flange Heavy - 90° Bent Tube - Extra Long (Non-ISO) |
| **369**- | FLH110 | Code 62 O-Ring Flange Heavy -110° Bent Tube |
| **370**- | FLFF | Code 61 Flange Without O-Ring Groove |
| **374**- | FLHCF | Code 62 O-Ring Flange Heavy with Captive Flange |
| **376**- | FLHCF45 | Code 62 O-Ring Flange Heavy with Captive Flange - 45° Bent Tube |
| **380**- | FLHCF90 | Code 62 O-Ring Flange Heavy with Captive Flange - 90° Bent Tube |
| **386**- | FLHCFM | Code 62 O-Ring Flange Heavy Captive Flange Metric Bolts |
| **400**- | FLC | Caterpillar Style O-Ring Flange |
| **401**- | FLCL | Caterpillar Style O-Ring Flange - Long |
| **402**- | FLC22 | Caterpillar Style O-Ring Flange - 22 1/2° Bent Tube |
| **404**- | FLC30 | Caterpillar Style O-Ring Flange - 30° Bent Tube |
| **407**- | FLC45 | Caterpillar Style O-Ring Flange - 45° Bent Tube |
| **408**- | FLC45 | Caterpillar Style O-Ring Flange - 45° Bent Tube |
| **409**- | FLC60 | Caterpillar Style O-Ring Flange - 60° Bent Tube |
| **410**- | FLC67 | Caterpillar Style O-Ring Flange - 67 1/2° Bent Tube |
| **415**- | FLC90 | Caterpillar Style O-Ring Flange - 90° Bent Tube |
| **416**- | FLC90L | Caterpillar Style O-Ring Flange - 90° Bent Tube - Long |
| **420**- | FPFL | Female French GAZ (Poclain) 24° High Pressure Flange |
| **460**- | ABC | Air Brake Compression |
| **461**- | STA | Straight Tube Assembly |
| **462**- | STA-ABC | Straight Tube Assembly (STA) and One Air Brake Compression (ABC) |
| **480**- | MPFL | Male French GAZ (Poclain) 24° High Pressure Flange |
| **482**- | MPFL90 | Male French GAZ (Poclain) 24° High Pressure Flange - 90° Bent Tube |
| **500**- | MIX | SAE Male Inverted Swivel |
| **502**- | MIX45 | SAE Male Inverted Swivel - 45° Bent Tube |
| **504**- | MIX90 | SAE Male Inverted Swivel - 90° Bent Tube |
| **510**- | MFA | SAE Male Flareless Assembly |
| **511**- | MFA90 | Male SAE Flareless Assembly - 90° Block |
| **520**- | NASP | North American Stand Pipe |
| **527**- | FBO | Female Braze-On Stems |
| **534**- | HLEC | Hose Length Extender - Caterpillar |
| **535**- | HLE | Hose Length Extender |
| **536**- | HLE45 | Hose Length Extender - 45° Bent Tube |
| **537**- | HLE90 | Hose Length Extender - 90° Bent Tube |
| **538**- | HLESG | Hose Length Extender with Sight Glass |
| **539**- | HLET | Hose Length Extender - Tee |
| **540**- | FABX | Female Air Brake Swivel |
| **541**- | HLE180 | Hose Length Extender - 180° Bent Tube |
| **542**- | HLEY | Y Splicer |
| **543**- | TBFLX | Two-Bolt Flange Swivel |

# Thread Configurations for Stem Styles – Continued

**561**- FG Female Grease
**562**- FZX Female Parker Triple Thread Flare
**563**- PWX Pressure Wash Swivel
**564**- BJ US Banjo
**570**- VIC Victaulic Nipple
**576**- FTON134SP45 Female O-Ring with R134 Service Port - 45° Bent Tube
**577**- FTON12SP45 Female O-Ring with R12 Service Port - 45° Bent Tube
**578**- MTON180 Male O-Ring - 180° Bent Tube
**580**- MTON134SP Male SAE Tube O-Ring Nut Swivel with R134a Service Port
**582**- MTON134SP90 Male SAE Tube O-Ring Nut Swivel with R134a Service Port - 90° Bent Tube
**583**- MTON Male SAE Tube O-Ring Nut Swivel
**584**- MTON45 Male SAE Tube O-Ring Nut - 45° Bent Tube
**585**- MTON90 Male SAE Tube O-Ring Nut - 90° Bent Tube
**586**- FTONR12SP Female SAE Tube O-Ring Nut Swivel with R12 Service Port
**587**- FTONR12SP90 Female SAE Tube O-Ring Nut Swivel with R12 Service - 90° Bent Tube
**588**- FTON134SP Female SAE Tube O-Ring Nut Swivel with R134a Service Port
**589**- FTON134SP90 Female SAE Tube O-Ring Nut Swivel with R134a Service Port - 90° Bent Tube
**590**- FTON Female SAE Tube O-Ring Nut Swivel
**591**- FTON45 Female SAE Tube O-Ring Nut Swivel - 45° Bent Tube
**592**- FTON90 Female SAE Tube O-Ring Nut Swivel - 90° Bent Tube
**593**- FTOMN Female SAE Tube O-Ring Metric Nut Swivel
**594**- FTOMN45 Female SAE Tube O-Ring Metric Nut Swivel - 45° Bent Tube
**595**- FTOMN90 Female SAE Tube O-Ring Metric Nut Swivel - 90° Bent Tube
**596**- FTON90BL Female SAE Tube O-Ring Nut Swivel - 90° Block
**597**- MIO Male Inverted O-Ring
**598**- MIO45 Male Inverted O-Ring - 45° Bent Tube
**599**- MIO90 Male Inverted O-Ring - 90° Bent Tube
**600**- MIOBKHD Male Inverted O-Ring Bulkhead
**602**- MIOBKHD90 Male Inverted O-Ring Bulkhead - 90° Bent Tube
**604**- FTDON Female SAE Tube Dual O-Ring Nut
**605**- FTDON45 Female SAE Tube Dual O-Ring Nut - 45° Bent Tube
**606**- FTDON90 Female SAE Tube Dual O-Ring Nut - 90° Bent Tube
**607**- FTDOMN Female SAE Tube Dual O-Ring Metric Nut
**608**- FTDOMN45 Female SAE Tube Dual O-Ring Metric Nut - 45° Bent Tube
**609**- FTDOMN90 Female SAE Tube Dual O-Ring Metric Nut - 90° Bent Tube
**610**- FTON180 Female SAE Tube O-Ring Nut - 180° Bent Tube
**611**- MIO134SP Male Inverted O-Ring with R134a Service Port
**613**- MIO134SP90 Male Inverted O-Ring with R134a Service Port - 90° Bent Tube
**614**- TORSP Universal Tee O-Ring Splicer English Threads
**615**- MDL Male DIN 24° Cone - Light Series
**645**- FDLORX Female DIN 24° Cone Swivel - Light Series with O-Ring
**650**- FDLORX45 Female DIN 24° Cone Swivel - Light Series with O-Ring - 45° Bent Tube
**655**- FDLORX90 Female DIN 24° Cone Swivel - Light Series with O-Ring - 90° Bent Tube
**675**- MFG Male French GAZ
**680**- FFGX Female French GAZ Swivel (Female Kobelco)
**688**- FTON134SPH Female SAE Tube O-Ring Nut Swivel with R134a High Pressure Service Port
**690**- FFGX90 Female French GAZ Swivel - 90° Bent Tube (Female Kobelco)
**691**- FFGX90S Female French GAZ Swivel - 90° Bent Tube - Short (Female Kobelco)
**715**- MDH Male DIN 24° Cone - Heavy Series
**720**- FDHORX Female DIN 24° Cone Swivel - Heavy Series with O-Ring
**725**- FDHORX45 Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 45° Bent Tube
**730**- FDHORX90 Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 90° Bent Tube
**735**- MKB Male Kobelco (Male French GAZ)
**750**- MSP Metric Light Stand Pipe
**770**- DBJ International Thread Metric 7642 DIN Banjo
**795**- MBSPT Male British Standard Pipe Tapered/Japanese Tapered Thread
**810**- MBSPP Male British Standard Pipe Parallel
**830**- FBSPX Female British Standard Parallel Pipe O-Ring Swivel
**830**- FBSPORX Female British Standard Parallel Pipe O-Ring Swivel
**831**- FBSPORX45 Female British Standard Parallel Pipe O-Ring Swivel - 45° Bent Tube
**832**- FBSPORX90 Female British Standard Parallel Pipe O-Ring Swivel - 90° Bent Tube
**845**- FBSPORX90BL Female British Standard Parallel Pipe O-Ring Swivel - 90° Block
**850**- BSPBJ International Thread British Std Pipe Banjo
**855**- FBFFX Female British Flat-Face Swivel
**857**- FLSHCF ISO 6164 4-Bolt Heavy Captive Flange
**860**- XXSBW GSM Butt Weld
**910**- FKX Female Komatsu Style Japanese Metric Swivel
**911**- FKX45 Female Komatsu Style Japanese Metric Swivel - 45° Bent Tube
**913**- FKX90 Female Komatsu Style Japanese Metric Swivel - 90° Bent Tube
**930**- FJISX Female Japanese Industrial Standard Swivel
**932**- FJISPX Female Japanese Inverted Flare Parallel Threads
**934**- FJISX90S Female Japanese Industrial Standard Swivel - 90° Bent Tube
**935**- MMFA Male Metric Flareless Assembly
**947**- FSLTORSP Female (Ford) Spring Lock Tee O-Ring Splicer
**948**- FSLSP Female (Ford) Spring Lock Liquid Line Splicer
**949**- MSL45 Male (Ford) Spring Lock - 45° Bent Tube
**950**- MSL Male (Ford) Spring Lock
**951**- MSL90 Male (Ford) Spring Lock - 90° Bent Tube
**952**- FSL Female (Ford) Spring Lock
**953**- FSL90 Female (Ford) Spring Lock - 90° Bent Tube
**954**- R12SP Hose Splicer with R12 Thread Service Port
**955**- FSL45 Female (Ford) Spring Lock - 45° Bent Tube
**956**- R134SP Hose Splicer with R134a Service Port
**957**- R134SP-RL Female Rotalok with R134a Service Port - 90° Block
**958**- CFTON90 Compressor Female SAE Tube O-Ring Nut Swivel - 90° Bent Tube
**959**- CFTON90BL Compressor Female SAE Tube O-Ring Nut Swivel - 90° Block
**960**- CFTON134SP90BL Compressor Female Tube O-Ring Nut with 134a Service Port - 90° Block
**961**- CBSR12SP90 Compressor Block - Single w/Switch or Service Port - 90° Bent Tube
**962**- CBSRR12SP90 Compressor Block - Single Reverse w/Switch or Service Port - 90° Bent Tube
**963**- FTOMN90134SPH Metric Female O-Ring (FOR) with Switch or Service Port - 90° Bent Tube
**964**- FTOMN90SPL Metric Female O-Ring (FOR) with Switch or Service Port - 90° Bent Tube
**965**- MIOM Metric Male Insert O-Ring (MIO)
**970**- MQLH Male Quick-Lok® High
**971**- MQLH45S Male Quick-Lok® High - 45° Bent Tube - Short
**972**- MQLH90S Male Quick-Lok® High - 90° Bent Tube - Short
**973**- MQLH90L Male Quick-Lok® High - 90° Bent Tube - Long
**974**- FQLH-MB Female Quick-Lok® High to Male O-Ring Boss Adapter
**976**- FQLH-FJ Female Quick-Lok® High to Female JIC 37 Flare
**978**- FQLH-FFORX Female Quick-Lok® High to Female Flat-Face
**980**- MQLL Male Quick-Lok® Low
**981**- MQLL45 Male Quick-Lok® Low - 45° Bent Tube
**982**- MQLL90 Male Quick-Lok® Low - 90° Bent Tube
**983**- MQLL90M Male Quick-Lok® Low - 90° Bent Tube - Medium
**984**- MQLL90L Male Quick-Lok® Low - 90° Bent Tube - Long
**995**- B1F Non-Skive Ferrule - Stainless Steel Braid
**995**- CLAMP Clamp Assemblies
**995**- G8K1F G8K Ferrule for G8K Spiral Hose
**995**- GS1F GS Ferrule for Wire Braid Hose
**995**- GS1F-4 GS Ferrule for 4-Spiral Hose
**995**- GS1F-6 GS Ferrule for 6-Spiral Hose
**995**- GSP1F-2 GSP Ferrule for Wire Braid Hose
**995**- GSP1F-4 GSP Ferrule for 4-Spiral Hose
**995**- S1F Non-Skive Ferrules - Stainless Steel Spiral
**995**- S2F Skive Ferrules - Stainless Steel Spiral
**997**- GSID1F GS Ferrule for ID5K Hose

# Air Brake

In the following example, the Global Part Number G33100-0808 identifies a Air Brake Male Pipe (MP) coupling with -8 (1/2") tube size and -8 (1/2") thread size.

**G 33** — **Series Stem Style** (see below)

**1 00** — **Thread Configuration** (see below)

**-**

**0 8** — **Stem Size** (1/2")

**0 8** — **Thread Size** (1/2")

## Series Stem Styles:

### Air Brake

**G33**—Air Brake Fittings for Rubber Hose

### Brass Stemed Fittings

**G36** -Brass Lock-On Field Attachable
**G37** -Single Bead
**G38** -Barb Stem

## THREAD CONFIGURATIONS

These three-digit numbers identify the various coupling thread configurations

### Air Brake – G33

**021** — MP-ATDV Air Tank Drain Valve
**022** — MP-AV Air Vent
**027** — MP-CV One Way Check Valve
**030** — MAB-MP Male Air Brake to Male Pipe Adapter
**031** — GH Gladhand
**032** — GH-SEAL Gladhand Seal
**050** — TS-ABR Sleeve
**060** — TSN-ABR Nut
**061** — SGN-ABR Spring Guard Nut
**100** — ABR-MP Air Brake to Male Pipe with Nut and Sleeve
**110** — ABRSG-MP Air Brake to Male Pipe with Spring Guard
**111** — ABRI-MP Air Brake to Male Pipe without Nut and Sleeve
**112** — SGABR Air Brake Spring Guard
**150** — ABR-FABX Air Brake to Female Air Brake Swivel
**151** — ABR-FABX-MPA Air Brake to Female Air Brake Swivel with Adapter
**300** — FP-FPBKHD Female Pipe to Female Pipe Bulkhead
**301** — FP-FPBKHDS Female Pipe to Female Pipe Bulkhead
**302** — MP-FPBKHDL Male Pipe to Female Pipe Bulkhead
**303** — MP-FPBKHD Male Pipe to Female Pipe Bulkhead
**400** — ABR-ABR Air Brake Union
**610** — MP-MS90-TV Truck Valve 90° - Male SAE 45° Flare to Male Pipe Run
**612** — MS-MP90-TV Truck Valve 90° - Male SAE 45° to Male Pipe Branch
**620** — SB-MP90-TV Truck Valve 90° - Single Bead to Male Pipe Run
**622** — SB-MP90-TVP Truck Valve 90° - Barbed to Male Pipe Branch with Pin Handle
**630** — FP-MP90-TV Truck Valve 90° - Male Pipe to Female Pipe Branch
**650** — FP-FP-FPWTV Truck Valve - 3-Way
**655** — FP-FP-FPWTV Truck Valve - 4-Way
**656** — FP-FP-FPWTV-L Truck Valve - 4-Way
**701** — MFA-MFASC Shut-Off Cock - Copper Tubing Ind. Compression to Copper Tubing Ind. Compression Run
**705** — MFA-MPSC Shut-Off Cock - Copper Tubing Industrial Compression to Male Pipe Run
**710** — MP-FPSC Shut-Off Cock - Male Pipe to Female Pipe Run
**715** — FP-FPSC Shut-Off Cock - Female Pipe to Female Pipe Run
**720** — MS-MPSC Shut-Off Cock - Male SAE 45° Flare to Male Pipe Run
**730** — MS-MSSC Shut-Off Cock - Male SAE 45° Flare to Male SAE 45° Flare Run
**801** — MP-ADC Air Shut-Off Cock - Male Pipe to Bibb Nose
**805** — FP-MPADC Air Drain Cock - Male Pipe to Female Pipe
**823** — BN-MPDC90 Drain Cock 90° - Single Bead to Male Pipe - Long
**830** — MP-ISDC Drain Cock - Male Pipe Internal Seat - Bibb Nose - Long
**831** — MP-ESDC Drain Cock - Male Pipe to Tube External Seat - Long
**832** — MP-ADCBN Air Shut-off Cock - Male Pipe - Bibb Nose with Key Handle
**850** — ATNKV Air Tank Valve
**901** — MFA-MFANV Needle Valve - Copper Tubing Ind. Compression to Copper Tubing Ind. Compression Run
**905** — MFA-MP90NV Needle Valve 90° - Copper Tubing Industrial Compression to Male Pipe
**910** — MFA-MPNV Needle Valve - Copper Tubing Industrial Compression to Male Pipe
**915** — MP-MPNV Needle Valve - Male Pipe to Male Pipe
**920** — MP-FPNV Needle Valve - Male Pipe to Female Pipe
**930** — FP-FPNV Needle Valve - Female Pipe to Female Pipe

# Air Brake – Continued

## Air Brake – G33 — Continued

**940** — MS-MPNV Needle Valve - Male SAE 45° Flare to Male Pipe
**945** — MS-MP90NV Needle Valve 90° - Male SAE 45° Flare to Male Pipe
**950** — MS-MSNV Needle Valve - Male SAE 45° Flare to Male SAE 45° Flare

## Brass Stemed Fittings – G36

**100** — LOC-RMP Male Pipe with Cone Seat
**105** — LOC-RMPX Male Pipe Swivel without Cone Seat
**106** — LOC-RMP90 Male Pipe 90° Block with Cone Seat
**110** — LOC-RFP Female Pipe without Cone Seat
**111** — LOC-RFPX Female Pipe Swivel with Cone Seat
**165** — LOC-RMJ Male JIC 37° Flare
**170** — LOC-RFJX Female JIC 37° Flare Swivel
**195** — LOC-RMS Male SAE 45° Flare
**200** — LOC-RFSX Female SAE 45° Flare Swivel
**210** — LOC-RFJSX Dual Seat Female JIC 37°/SAE 45° Flare Swivel
**500** — LOC-RMIX Male SAE Inverted Flare Swivel
**508** — LOC-RFI Female SAE Inverted Flare
**520** — LOC-RFT North American Stand Pipe
**520** — LOC-RSP North American Stand Pipe
**535** — LOC-RHM Hose Length Extenders
**795** — LOC-MBSPT Male British Standard Pipe Tapered

## Brass Stemed Fittings – G37

**100** — SB-RMP Male Pipe with Cone Seat
**103** — SB-MSC Male Straight Thread Connector
**106** — SB-RMP90 Male Pipe 90° Block Cone Seat
**195** — SB-RMS Male SAE 45° Flare Connector
**500** — SB-RMIX Male SAE Inverted Flare Swivel
**503** — SB-RMIX45 Male SAE Inverted Flare Swivel - 45°
**504** — SB-RMIX90 Male SAE Inverted Flare Swivel - 90°
**508** — SB-RFI Female SAE Inverted Flare

## Brass Stemed Fittings – G38


**100** — BS-MP Male Pipe NPTF with Cone Seat
**110** — BS-FP Female Pipe NPTF

# Adapters

In the following example, the Global Part Number G60110-0808 identifies a Male Pipe NPTF (MP) to Male Pipe NPTF (MP) adapter with -8 (1/2") pipe thread and -8 (1/2") pipe thread size. Meets SAE100R2 working pressures except where noted.

**SERIES STEM STYLES:**

**G60** - SAE to SAE **G62** - British to SAE **G63** - Metric to SAE **G64** - International to International **G65** - Japanese Conversion **G73** - Ermento




## THREAD CONFIGURATIONS

These three-digit numbers identify the various coupling thread configurations

| | |
|---|---|
| **60050** - FFN | Female Flareless Nut |
| **60051** - FFS | Female Flareless Sleeve |
| **60102** - MP-PLUG | Male Pipe NPTF Plug |
| **60110** - MP-MP | Male Pipe NPTF to Male Pipe NPTF |
| **60115** - MP-MP90 | Male Pipe NPTF to Male Pipe NPTF - 90° |
| **60130** - MP-FPS | Male Pipe NPTF to Female Pipe NPTF Reducer Bushing - Short |
| **60132** - MP-FPL | Male Pipe NPTF to Female Pipe NPTF Increasing Bushing - Long |
| **60134** - FP-MP45 | Female Pipe NPTF to Male Pipe NPTF - 45° |
| **60136** - MP-FP90 | Male Pipe NPTF to Female Pipe NPTF - 90° |
| **60140** - MP-FPX | Male Pipe NPTF to Female Pipe Swivel NPSM |
| **60142** - MP-FPX45 | Male Pipe NPTF to Female Pipe Swivel NPSM - 45° |
| **60144** - MP-FPX90 | Male Pipe NPTF to Female Pipe Swivel NPSM - 90° |
| **60152** - FP-FP | Female Pipe NPTF to Female Pipe NPTF |
| **60156** - FP-FP90 | Female Pipe NPTF to Female Pipe NPTF - 90° |
| **60160** - FP-FPX | Female Pipe NPTF to Female Pipe Swivel NPSM |
| **60162** - FP-FPX45 | Female Pipe NPTF to Female Pipe Swivel NPSM - 45° |
| **60164** - FP-FPX90 | Female Pipe NPTF to Female Pipe Swivel NPSM - 90° |
| **60181** - FP-FP-FP | Female Pipe NPTF - Tee |
| **60183** - FP-FP-MP | Female Pipe NPTF on Run to Male Pipe NPTF - Tee |
| **60184** - FPX-FPX-FPX | Female Pipe Swivel NPSM - Tee |
| **60186** - FPX-FPX-MP | Female Pipe Swivel NPSM on Run to Male Pipe NPTF - Tee |
| **60248** - O-RING | O-Rings for Straight Thread Boss Fittings |
| **60250** - MB-PLUG | Male O-Ring Boss Plug |
| **60265** - MB-MP | Male O-Ring Boss to Male Pipe NPTF |
| **60275** - MB-FP | Male O-Ring Boss to Female Pipe NPTF |
| **60285** - MB-FPX | Male O-Ring Boss to Female Pipe Swivel NPSM |
| **60287** - MB-FPX45 | Male O-Ring Boss to Female Pipe Swivel NPSM - 45° |
| **60289** - MB-FPX90 | Male O-Ring Boss to Female Pipe Swivel NPSM - 90° |
| **60291** - FB-MP | Female O-Ring Boss to Male Pipe NPTF |
| **60301** - MB-MJ | Male O-Ring Boss to Male JIC 37° Flare |
| **60308** - MB-MJ45 | Male O-Ring Boss to Male JIC 37° Flare - 45° |
| **60312** - MB-MJ90 | Male O-Ring Boss to Male JIC 37° Flare - 90° |
| **60320** - MB-FJX | Male O-Ring Boss to Female JIC 37° Flare Swivel |
| **60350** - MJ-MJ-MB | Male JIC 37° Flare on Run to Male O-Ring Boss - Tee |
| **60352** - MB-MJ-MJ | Male O-Ring Boss to Male JIC 37° Flare to Male JIC 37° Flare - Tee |
| **60394** - TS | Tube Sleeve |
| **60395** - TSN | Tube Sleeve Nut |
| **60399** - LN | Locknuts for Bulkhead Fittings |
| **60401** - FJ-CAP | Female JIC 37° Flare Cap |
| **60402** - MJ-PLUG | Male JIC 37° Flare Plug |
| **60405** - MJ-FBO | Male JIC 37° Flare to Female Braze - On |
| **60410** - MJ-MJ | Male JIC 37° Flare to Male JIC 37° Flare |
| **60417** - MJ-MJ90 | Male JIC 37° Flare to Male JIC 37° Flare - 90° |
| **60420** - MJ-FJ | Male JIC 37° Flare to Female JIC 37° Flare |
| **60422** - MJ-FJX90 | Male JIC 37° Flare to Female JIC 37° Flare Swivel - 90° |
| **60424** - MJ-FJX45 | Male JIC 37° Flare to Female JIC 37° Flare Swivel - 45° |
| **60445** - MJ-BKHD | Male JIC 37° Flare to Male JIC 37° Flare Bulkhead |
| **60446** - MJ-BKHD45 | Male JIC 37° Flare to Male JIC 37° Flare Bulkhead - 45° |
| **60447** - MJ-BKHD90 | Male JIC 37° Flare to Male JIC 37° Flare Bulkhead - 90° |
| **60469** - MJ-MJ-MJ | Male JIC 37° Flare Tee |
| **60470** - MJ-MJ-FJX | Male JIC 37° Flare on Run to Female JIC 37° Flare Swivel - Tee |
| **60471** - MJ-MJ-BKHD | Male JIC 37° Flare on Run to Male JIC 37° Flare Bulkhead - Tee |
| **60472** - MJ-BKHD-MJ | Male JIC 37° Flare to Male JIC 37° Flare Bulkhead to Male JIC 37° Flare - Tee |
| **60473** - MJ-FJX-MJ | Male JIC 37° Flare to Female JIC 37° Flare Swivel to Male JIC 37° Flare - Tee |
| **60490** - MJ-MP | Male JIC 37° Flare to Male Pipe NPTF |
| **60497** - MJ-MP45 | Male JIC 37° Flare to Male Pipe NPTF - 45° |
| **60499** - MJ-MP90 | Male JIC 37° Flare to Male Pipe NPTF - 90° |
| **60510** - MJ-FP | Male JIC 37° Flare to Female Pipe NPTF |
| **60514** - MJ-FP90 | Male JIC 37° Flare to Female Pipe NPTF - 90° |
| **60520** - FJX-MP | Female JIC 37° Flare Swivel to Male Pipe NPTF |
| **60524** - FJX-MP90 | Female JIC 37° Flare Swivel to Male Pipe NPTF - 90° |
| **60530** - FJX-FP | Female JIC 37° Flare Swivel to Female Pipe NPTF |
| **60541** - MJBKHD-MP | Male JIC 37° Flare Bulkhead to Male Pipe NPTF |
| **60551** - MJ-MJ-MP | Male JIC 37° Flare on Run to Male Pipe NPTF - Tee |
| **60698** - O-RING FF | O-Rings for Flat-Face Fittings |

# Adapters – Continued

**60701** - FFOR-CAP Female Flat-Face O-Ring Cap
**60702** - MFFOR-PLUG Male Flat-Face O-Ring Plug
**60705** - MFFOR-MFFOR Male Flat-Face O-Ring to Male Flat-Face O-Ring
**60712** - MFFOR-MFFOR90 Male Flat-Face O-Ring to Male Flat-Face O-Ring - 90°
**60724** - MFFOR-FFORX90 Male Flat-Face O-Ring to Female Flat-Face Swivel - 90°
**60740** - MFFOR-MFFOR-MFFOR Male Flat-Face O-Ring Tee
**60742** - MFFOR-MFFOR-FFORX Male Flat-Face O-Ring on Run to Female Flat-Face Swivel- Tee
**60744** - MFFOR-FFORX-MFFOR Male Flat-Face O-Ring to Female Flat- Face O-Ring to Male Flat-Face O-Ring - Tee
**60770** - MFFOR-MP Male Flat-Face O-Ring to Male Pipe NPTF
**60785** - MFFOR-FJX Male Flat-Face O-Ring to Female JIC 37° Flare Swivel
**60800** - MFFOR-MB Male Flat-Face O-Ring to Male O-Ring Boss
**60805** - MFFOR-MB45 Male Flat-Face O-Ring to Male O-Ring Boss - 45°
**60810** - MFFOR-MB90 Male Flat-Face O-Ring to Male O-Ring Boss - 90°
**60811** - MFFOR-MB90L Male Flat-Face O-Ring to Male O-Ring Boss - 90° Long Drop
**60820** - MFFOR-MFFOR-MB Male Flat-Face O-Ring on Run to Male O-Ring Boss - Tee
**60821** - MFFOR-MB-MFFOR Male Flat-Face O-Ring to Male O-Ring Boss to Male Flat-Face O-Ring - Tee
**60880** - FFORX-MJ Female Flat-Face Swivel to Male JIC 37° Flare
**60897** - FL-CAP Code 61 Flange Cap
**60898** - FLANGE O-RING O-Rings for Code 61, Code 62, and Caterpillar-Style Flange Fittings
**60899** - CFHS Flange Half Sets (Code 61 - SAE J518)
**60900** - FL-MJ Code 61 O-Ring Flange to Male JIC 37° Flare
**60901** - FL4K-MJ / FL5K-MJ Code 61 O-Ring Flange to Male JIC 37° Flare - High Pressure
**60905** - FL-MJ45 Code 61 O-Ring Flange to Male JIC 37° Flare - 45°
**60906** - FL4K-MJ45 / FL5K-MJ45 Code 61 O-Ring Flange to Male JIC 37° Flare - 45° - High Pressure
**60910** - FL-MJ90 Code 61 O-Ring Flange to Male JIC 37° Flare - 90°
**60911** - FL4K-MJ90/ FL5K-MJ90 Code 61 O-Ring Flange to Male JIC 37° Flare - 90° - High Pressure
**60915** - FL4K-MFFOR/ FL5K-MFFOR Code 61 O-Ring Flange to Male Flat-Face O-Ring - High Pressure
**60920** - FL4K-MFFOR45/ FL5K-MFFOR45 Code 61 O-Ring Flange to Male Flat-Face O-Ring 45° - High Pressure
**60925** - FL4K-MFFOR90/ FL5K-MFFOR90 Code 61 O-Ring Flange to Male Flat-Face O-Ring 90° - High Pressure
**60927** - FLH-CAP Code 62 Flange Cap
**60929** - FHHS Flange Half Sets (Code 62 - SAE J518)
**60930** - FLH6K-MJ Code 62 O-Ring Flange Heavy to Male JIC 37° Flare - (6,000 psi)
**60935** - FLH6K-MJ45 Code 62 O-Ring Flange Heavy to Male JIC 37° Flare 45° -(6,000 psi)
**60940** - FLH6K-MJ90 Code 62 O-Ring Flange Heavy to Male JIC 37° Flare 90° -(6,000 psi)
**60945** - FLH6K-MFFOR Code 62 O-Ring Flange Heavy to Male Flat-Face O Ring - (6,000 psi)
**60950** - FLH6K-MFFOR45 Code 62 O-Ring Flange Heavy to Male Flat-Face O-Ring 45° - (6,000 psi)
**60955** - FLH6K-MFFOR90 Code 62 O-Ring Flange Heavy to Male Flat-Face O-Ring 90° - (6,000 psi)
**60959** - CATFHS Caterpillar-Style Flange Half Sets
**62150** - MBSPT-MJ Male British Standard Pipe Tapered Thread to Male JIC 37° Flare
**62153** - MBSPT-MJ45 Male British Standard Pipe Tapered Thread to Male JIC 37° Flare - 45°
**62155** - MBSPT-MJ90 Male British Standard Pipe Tapered Thread to Male JIC 37° Flare - 90°
**62200** - MBSPP-MP Male British Standard Pipe Parallel to Male Pipe NPTF
**62220** - MBSPP-FP Male British Standard Pipe Parallel to Female Pipe NPTF
**62300** - MBSPP-MJ Male British Standard Pipe Parallel to Male JIC 37° Flare
**62305** - MBSPP-MJ45 Male British Standard Pipe Parallel to Male JIC 37° Flare - 45°
**62310** - MBSPP-MJ90 Male British Standard Pipe Parallel to Male JIC 37° Flare - 90°
**62320** - MBSPP-FJX Male British Standard Pipe Parallel to Female JIC 37° Flare Swivel
**62450** - MBSPPOR-MJ Male British Standard Pipe Parallel with O-Ring to Male JIC 37° Flare
**62460** - MBSPPOR-MJ90 Male British Standard Pipe Parallel with O-Ring to Male JIC 37° Flare - 90°
**62470** - MBSPPOR-MFFOR Male British Standard Pipe Parallel with O-Ring to Male Flat-Face O-Ring
**62471** - MBSPPOR-MFFORL Male British Standard Pipe Parallel with O-Ring to Male Flat-Face O-Ring - Long
**62473** - MBSPPOR-MFFOR45 Male British Standard Pipe Parallel with O-Ring to Male Flat-Face O-Ring - 45°
**62475** - MBSPPOR-MFFOR90 Male British Standard Pipe Parallel with O-Ring to Male Flat-Face O-Ring - 90°
**62500** - FBSPP-MP Female British Standard Pipe Parallel to Male Pipe NPTF
**62520** - FBSPP-FP Female British Standard Pipe Parallel to Female Pipe NPTF
**62550** - FBSPP-MJ Female British Standard Pipe Parallel to Male JIC 37° Flare
**62605** - FBSPPX-MP90 Female British Standard Pipe Parallel Swivel to Male Pipe NPTF - 90°
**62650** - FBSPPX-MJ Female British Standard Pipe Parallel Swivel to Male JIC 37° Flare
**62660** - FBSPPX-FJX Female British Standard Pipe Parallel Swivel to Female JIC 37° Flare Swivel
**62801** - FBFFOR-MJ Female British Flat-Face O-Ring to Male JIC 37° Flare
**63099** - MMOR-PLUG Male Metric O-Ring Plug
**63120** - MM-FP Male Metric with O-Ring to Female Pipe NPTF
**63150** - MM-MJ Male Metric with O-Ring to Male JIC 37° Flare
**63160** - MM-MJ90 Male Metric with O-Ring to Male JIC 37° Flare - 90°
**63350** - MDL-MJ Male DIN 24° Cone - Light Series to Male JIC 37° Flare
**63450** - FDLX-MJ Female DIN 24° Cone Swivel - Light Series to Male JIC 37° Flare
**63650** - MDH-MJ Male DIN 24° Cone - Heavy Series to Male JIC 37° Flare
**63750** - FDHX-MJ Female DIN 24° Cone Swivel - Heavy Series to Male JIC 37° Flare
**63980** - MKB-PLUG Male Kobelco Plug
**63990** - MKB-MJ Male Kobelco to Male JIC 37° Flare
**64075** - BBDS British Bonded Seal
**64094** - MBSPOR-PLUG Male British Standard Pipe Parallel with O-Ring Plug
**64095** - O-RING FBSPP O-Rings for British Standard Parallel Pipe (BSPP Couplings)
**64097** - FBSPP-CAP Female British Standard Pipe Parallel Cap

# Adapters – Continued

**64098** - MBSPT-PLUG Male British Standard Pipe Tapered Thread Plug
**64099** - MBSPP-PLUG Male British Standard Pipe Parallel Plug
**64350** - MBSPP-FBSPPX Male British Standard Pipe Parallel to Female British Standard Pipe Parallel Swivel
**64775** - MBDS Metric Bonded Seal
**64780** - O-RING DIN L O-Rings for DIN Light Series (MegaCrimp® and GlobalSpiral™ Couplings)
**64781** - O-RING DIN H O-Rings for DIN Heavy Series (PC, PCM, PCS Couplings)
**64790** - MM-PLUG Male Metric Plug
**64792** - MDL-PLUG Male DIN 24° Cone - Light Series Plug
**64793** - FDL-CAP Female DIN 24° Cone - Light Series Cap
**64794** - MDH-PLUG Male DIN 24° Cone - Heavy Series Plug
**64795** - FDH-CAP Female DIN 24° Cone - Heavy Series Cap
**65097** - FJIS-CAP Female Japanese Industrial Standard Cap
**65099** - MJIS-PLUG Male Japanese Industrial Standard Plug
**65100** - FJIS-MJ Female Japanese Industrial Standard to Male JIC 37° Flare
**65597** - FK-CAP Female Komatsu Cap
**65599** - MK-PLUG Male Komatsu Plug
**65600** - FK-MJ Female Komatsu to Male JIC 37° Flare
**65700** - MK-MK Male Komatsu to Male Komatsu
**65750** - MK-MJ Male Komatsu to Male JIC 37° Flare
**65800** - MK-FK90 Male Komatsu to Female Komatsu - 90°
**65950** - MK-FK-MK Male Komatsu to Female Komatsu to Male Komatsu - Tee
**73050** - ERBS Bite Sleeve
**73060** - ERTSN Tube Sleeve Nut
**73100** - ERT-MP Ermeto to Male Pipe
**73104** - ERT-MP90 Ermeto to Male Pipe - 90°
**73400** - ERT-ERT Ermeto to Ermeto

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Quick Disconnect Couplers

Gates Quick Disconnect couplers feature a meaningful part number that makes coupling identification fast and easy. Always refer to Gates Cross Reference Charts when selecting a quick disconnect coupler for a competitive interchange.

**G94021-0808 D**

| Coupling Series | Body Style | Thread Style | Nominal Coupling Size | Thread Size | Letter Optional |
|---|---|---|---|---|---|
| (see below) | (see right) | (see right) | | | (Double Acting Sleeve) |

### BODY STYLE IDENTIFICATION

0 Assembly
1 Male Tip (Nipple)
2 Female Coupler
3 Repair Kit
5 O-Ring
6 Backup Ring
8 Dust Plug
9 Dust Cap

### THREAD STYLE

0 Not Applicable
1 Female Pipe
2 Female O-Ring Boss
3 Bulkhead Mounts
4 Female British Parallel Pipe

### MISCELLANEOUS

D Double-Acting Sleeve
P Connect-Under-Pressure Option

## COUPLING SERIES INDENTIFICATION

**G940 Series (Agriculture Standard-Ball Valve)**

| | | | |
|---|---|---|---|
| **G94** | - 011 | MQBA-FP | Male Ball Valve to Female Pipe |
| **G94** | - 012 | MQBA-FB | Male Ball Valve to Female O-Ring Boss |
| **G94** | - 021 | FQBA-FP | Female Ball Valve To Female Pipe |
| **G94** | - 021 | FQBADA-FP | Female Ball Valve To Female Pipe |
| **G94** | - 022 | FQBA-FB | Female Ball Valve To Female O-Ring Boss |
| **G94** | - 025 | QDAOR | O-Ring |

**G940 and G941 Series (Agricultural)**

| | | | |
|---|---|---|---|
| **G94** | - 080 | QDADP | QD Dust Plug |
| **G94** | - 090 | QDADC | QD Dust Cap |

**G941 Series (Agriculture Standard-Poppet Valve)**

| | | | |
|---|---|---|---|
| **G94** | - 111 | MQPA-FP | Male Poppet Valve to Female Pipe |
| **G94** | - 121 | FQPA-FP | Female Poppet Valve to Female Pipe |

**G942 Series (John Deere Old Style)**

| | | | |
|---|---|---|---|
| **G94** | - 211 | MQBAJD-FP | Male Ball Valve to Female Pipe |
| **G94** | - 212 | MQBAJD-FB | Male Ball Valve to Female O-Ring Boss |
| **G94** | - 221 | FQBAJD-FP | Female Ball Valve to Female Pipe |

**G943 Series (International Harvester Old Style)**

| | | | |
|---|---|---|---|
| **G94** | - 311 | MQBAIHC-FP | Male Tip - Ball Valve to Female Pipe |

**G944 Series (J.I. Case Old Style)**

| | | | |
|---|---|---|---|
| **G94** | - 411 | MQBAJIC-FP | Male Tip - Ball Valve to Female Pipe |

**G945 Series (Industrial ISO 7241-1 - Series B)**

| | | | |
|---|---|---|---|
| **G94** | - 511 | MQPI-FP | Male Poppet Valve to Female Pipe |
| **G94** | - 521 | FQPI-FP | Female Poppet Valve to Female Pipe |
| **G94** | - 525 | QDIOR | O-Ring |
| **G94** | - 526 | QDIBR | Backup Ring |
| **G94** | - 581 | QDIDP/C | QD Plug - Cap Combinations |

**G949 Series (Flush Face - HTMA)**

| | | | |
|---|---|---|---|
| **G94** | - 911 | MQFF-FP | Male Flush Face Valve to Female Pipe |
| **G94** | - 912 | MQFF-FB | Male Flush Face Valve to Female O-Ring Boss |
| **G94** | - 913 | MQFF-BKHD | Male Flush Face Valve to JIC 37° Flare Bulkhead |
| **G94** | - 915 | MQFF-FBPP | Male Flush Face Valve to Female British Pipe Parallel |
| **G94** | - 921 | FQFF-FP | Female Flush Face Valve to Female Pipe |
| **G94** | - 922 | FQFF-FB | Female Flush Face Valve to Female O-Ring Boss |
| **G94** | - 923 | FQFF-BKHD | Female Flush Face to JIC 37° Flare Bulkhead |
| **G94** | - 925 | FQFF-FBPP | Female Flush Face Valve to Female British Pipe Parallel |
| **G94** | - 980 | QDFFDP | Dust Plug |
| **G94** | - 981 | QDFFDP/C | Dust Plug/Cap Combination |
| **G94** | - 990 | QDFFDC | Dust Cap |

**G950 Series (Flush Face - High Pressure)**

| | | | |
|---|---|---|---|
| **G95** | - 011 | MQFFH-FP | Male Flush Face Valve |
| **G95** | - 021 | FQFFH-FP | Female Flush Face Valve |
| **G95** | - 080 | QDFFHDP | QD Dust Plug |
| **G95** | - 081 | QDFFHDP/C | QD Plug - Cap Combination |
| **G95** | - 090 | QDFFHDC | QD Dust Cap |

**G951 Series (Wing Nut)**

| | | | |
|---|---|---|---|
| **G95** | - 111 | MQW-FP | Male (Brass) - Less Flange |
| **G95** | - 121 | FQW-FP | Female (Brass) - Wing Nut (Cast Iron) |
| **G95** | - 180 | QWDP | Dust Plug |
| **G95** | - 190 | QWDC | Dust Cap |

**G952 Series (High Pressure Wing Nut)**

| | | | |
|---|---|---|---|
| **G95** | - 211 | MQWH-FP | Male Acme Flat Threads to Female Pipe |
| **G95** | - 221 | FQWH-FP | Female Wing Nut to Female Pipe |
| **G95** | - 280 | QWHDP | Dust Plug |
| **G95** | - 290 | QWHDC | Dust Cap |

**G953 Series (Very High Pressure)**

| | | | |
|---|---|---|---|
| **G95** | - 311 | MQFFVH-FP | Male Poppet Valve to Female Pipe |
| **G95** | - 321 | FQFFVH-FP | Female Screw to Connect to Female Pipe |

**G956 Series (Industrial ISO 7241 - Series A)**

| | | | |
|---|---|---|---|
| **G95** | - 611 | MQP-FP | Male Poppet Valve to Female Pipe |
| **G95** | - 621 | FQP-FP | Female Poppet Valve to Female Pipe |
| **G95** | - 625 | QDOR | O-Ring |
| **G95** | - 626 | QDBR | Backup Ring |
| **G95** | - 680 | QDDP | QD Dust Plug |
| **G95** | - 681 | QDDP/C | QD Plug - Cap Combination |
| **G95** | - 690 | QDDC | QD Dust Cap |

**G959 Series (Agriculture QD Adapters)**

| | | | |
|---|---|---|---|
| **G95** | - 961 | MJD-FISO | John Deere Old Style to ISO Style |
| **G95** | - 962 | MISO-FJD | ISO Style to John Deere Old Style |
| **G95** | - 963 | MIHC-FJD | Int'l Harvester to John Deere Old Style |
| **G95** | - 964 | MIHC-FISO | Int'l Harvester Old Style to ISO Style |
| **G95** | - 965 | MISO-FIHC | ISO Style to Int'l Harvester Old Style |
| **G95** | - 966 | MISO-FJDDSO | ISO Style to John Deere Old Style - (Double Shutoff) |
| **G95** | - 967 | MISO-FIHCDSO | ISO Style to Int'l Harvester Old Style - (Double Shutoff) |

# High Pressure Ball Valves

Gates Ball Valves feature a meaningful part number that makes coupling identification fast and easy.

**G96210-0808**

| Coupling Series (Ball Valve, see below) | Body Style | Thread Style | Thread Size | Thread Size |
|---|---|---|---|---|

## BODY AND THREAD INDENTIFICATION

| | | |
|---|---|---|
| **110** | FP-FPBV | Female Pipe NPTF |
| **115** | FB-FBBV | Female O-Ring Boss |
| **120** | FP-FPBV | Female Pipe NPTF |
| **210** | FP-FP-FPBV | Female Pipe NPTF |
| **211** | FP-FP-FPBV | Female Pipe NPTF |
| **300** | FL-FLBV | Code 61 O-Ring Flange |
| **310** | FL-FLBV | Code 61 O-Ring Flange |
| **350** | FLH-FLHBV | Code 62 O-Ring Flange |
| **355** | FLH-FLHBV | Code 62 O-Ring Flange |

# High Pressure Live Swivels

Gates Live Swivels feature a meaningful part number that makes coupling identification fast and easy.

**G93510-0808**

| Live Swivel | Body Style | Thread Style | Thread Size | Thread Size |
|---|---|---|---|---|


## BODY AND THREAD INDENTIFICATION


| | | |
|---|---|---|
| **340** | MP-FP-LX90 | Male Pipe to Female Pipe - 90° |
| **345** | BSPP-BSPP-LX | Male BSPP to Male BSPP |
| **410** | MJ-MJ-LX | Male JIC to Male JIC |
| **415** | MJ-MJ-LX90 | Male JIC to Male JIC - 90° |
| **420** | MJ-MJ-LX90S | Male JIC to Male JIC - 90° |
| **450** | MJ-FJ/FB-LX | Male JIC to Female JIC/Boss |
| **455** | MJ-FB-LX90 | Male JIC to Female Boss - 90° |
| **460** | MB-FJ/FB-LX90S | Male Boss to Female JIC/Boss - 90° |
| **500** | JIC SWIVEL SEAL KIT | JIC Seal Kit |
| **510** | MJ-FP-LX | Male JIC to Female Pipe |
| **520** | MB-FP-LX90S | Male Boss to Female Pipe - 90° |
| **530** | MB-MJ-LX90S | Male Boss to Male JIC - 90° |
| **600** | ORS LIVE SWIVEL SEAL KIT | ORS Seal Kit |
| **700** | ORS/BSPP LIVE SWVL SEAL KIT | ORS/BSPP Seal Kit |
| **724** | MFFOR-FFORX-LX | Male ORFS to Female ORFS |
| **742** | MFFOR-MFFOR-LX | Male ORFS to Male ORFS |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# GlobalSpiral™ (GS) Couplings


## For EFG6K, EFG5K, EFG4K, EFG3K, and more Hose



GS-FBFFX



GS-FBSPORX



GS-FBSPORX45



GS-FBSPORX90



GS-FBSPORX90BL



GS-FDHORX



GS-FDHORX45



GS-FDHORX90



GS-FDLORX



GS-FDLORX45



GS-FDLORX90



GS-FFGX



GS-FFGX90



GS-FFORX



GS-FFORX22
GS-FFORX30



GS-FFORX45



GS-FFORX90



GS-FFORX135



GS-FJISX



GS-FJX



GS-FJX30



GS-FJX45



GS-FJX60



GS-FJX90



GS-FKX



GS-FL
GS-FLK



GS-FL22



GS-FL30



GS-FL45
GS-FLK45



GS-FL60



GS-FL67



GS-FL90
GS-FLK90



GS-FL100



GS-FL110



GS-FL135


GS-FLC


GS-FLC22



GS-FLC30



GS-FLC45



GS-FLC60


# GlobalSpiral™ (GS) Couplings


## For EFG6K, EFG5K, EFG4K, EFG3K and more Hose-Continued



GS-FLC67



GS-FLC90



GS-FLH



GS-FLH22



GS-FLH30



GS-FLH45



GS-FLH60



GS-FLH67



GS-FLH90



GS-FLH110



GS-FLL



GS-FMX



GS-FMX45



GS-FMX90



GS-FPFL



GS-HLE



GS-HLE45



GS-HLE90



GS-HLEC



GS-MB



GS-MBSPP



GS-MDH



GS-MDL



GS-MFG



GS-MFFOR



GS-MJ



GS-MKB


GS-MP



GS-MPFL


GS-MPFL90


GS-MPLH


GS1F-1
GS1F-2



GS1F-4
GSID1F-4



GS1F-6


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# GlobalSpiral™ (GS) Couplings


## One-Piece Couplings for Use with MobileCrimp® Crimpers for EFG6K, EFG5K, EFG4K, EFG3K and more Hose



MGS-FBSPORX



MGS-FDHORX



MGS-FJX



MGS-FJX90



MGS-FFORX



MGS-FFORX90



MGS-FL



MGS-FL45


MGS-FL90


MGS-FLH



MGS-MDH



MGS-MJ



MGS-MP


# MegaCrimp® Couplings


## For High and Medium Pressure Hose



FQLH-FFORX



FQLH-FJ



FQLH-MB



G-BJ



G-BSPBJ
G-DBJ



G-FABX



G-FBFFX



G-FBSPORX



G-FBSPORX45



G-FBSPORX90



G-FBSPORX90BL



G-FDHORX



G-FDHORX45



G-FDHORX90



G-FDLORX


G-FDLORX45


G-FDLORX90



G-FFGX



G-FFORX



G-FFORX30


# MegaCrimp® Couplings – Continued


## For High And Medium Pressure Hose-Continued



G-FFORX45



G-FFORX67



G-FFORX90



G-FG



G-FJISX



G-FJISPX



G-FJX



G-FJX30



G-FJX45



G-FJX90



G-FJX90BLK



G-FKX



G-FKX45



G-FKX90



G-FL
G-FLK



G-FL22



G-FL30



G-FL45
G-FLK45



G-FL60



G-FL67



G-FL90
G-FLK90



G-FP



G-FPX



G-FSX



G-FSX45



G-FSX90



G-FZX



G-HLE



G-MB



G-MBSPP



G-MBSPT



G-MBX



G-MBX45



G-MBX45BL



G-MBX90


G-MBX90BL


G-MBAX90


G-MDH



G-MDL



G-MFA


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# MegaCrimp® Couplings – Continued


## For High And Medium Pressure Hose-Continued



G-MFFOR



G-MFFORBKHDLN



G-MIX



G-MIX45



G-MIX90



G-MJ



G-MP



G-MPLN



G-MPX



G-MPX90



G-MS



G-MSP



G-MQLH



G-MQLH45



G-MQLH90


G-MQLL


G-MQLL45


G-MQLL90


G-NASP


G-PWX

# CHEMICAL RESISTANCE RATINGS FOR GATES HOSE POLYMERS, COUPLINGS AND ADAPTER MATERIALS

The Chemical Resistance Table lists the relative resistance of hose and coupling materials to more common chemicals. These ratings do not cover all possible variations of all factors, such as temperature, concentration, degradation or fluid contamination, etc. Testing under actual conditions is the best way to ensure chemical compatibility for critical applications.

**For specific information, contact Gates Hose/ Connector Product Application, Denver, Colorado 303-744-5070.**

## Rating Scale

| | |
|---|---|
| "1" | Excellent resistance |
| "2" | Good resistance |
| "X" | Not recommended |
| "—" | Testing recommended |

**HOW TO USE THE CHEMICAL RESISTANCE TABLE**

1. Chemicals are listed alphabetically.
2. Find the hose, coupling and adapter material type that has a resistance rating of "1" or "2" (See Rating Scale).
3. Find hose with compatible polymer(s) in the Gates Hydraulic Hose Selection Guide.
4. Look for compatible couplings for the selected hose by following the hose page references in the Selection Guide.

**NOTE:** O-rings used with couplings also must be considered for chemical compatibility with the fluid to be conveyed. This includes couplings containing internal o-rings; for example, MPX (Male Pipe Swivel). Gates standard o-ring is made of Nitrile. If o-rings other than Nitrile are required, contact Gates Hose/Connector Product Application.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# CHEMICAL RESISTANCE TABLE

Rating Scale:
1 Excellent
2 Good resistance
X Not recommended
– Testing recommended
[ ] Cover stock rating only; Rating for tube stock "X"
* Use Gates fuel hose or contact Denver Product Application Department

| Chemical Name | Gates Hose Polymers: Polychloroprene | Nitrile, HNBR, or XTF | Nitrile + PVC | CPE | CSM | Urethane | PTFE | Nylon | MegaTuff | Couplings & Adapters: Carbon Steel | Stainless Steel 304 | Stainless Steel 316 | Aluminum | Brass |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **A** | | | | | | | | | | | | | | |
| Absorption Oil | 2 | 1 | 2 | 1 | 2 | - | 1 | 1 | 2 | - | - | - | - | 1 |
| Acetaldehyde | X | X | X | - | X | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 | 1 |
| Acetamide | 1 | 2 | - | - | - | X | 1 | - | 1 | - | - | - | - | - |
| Acetic Acid, 5-20% | 2 | X | 2 | 1 | 2 | X | 1 | 1 | 1 | X | 2 | 2 | 2 | X |
| Acetic Acid, 25% | 2 | X | 2 | 1 | 2 | - | 1 | X | 1 | X | 2 | 2 | 2 | X |
| Acetic Acid, 30% | 2 | X | - | 1 | - | - | 1 | 2 | 1 | X | 2 | 1 | 2 | X |
| Acetic Acid, 50% | 2 | X | 2 | 1 | - | - | 1 | 2 | 1 | X | 2 | 2 | 2 | X |
| Acetic Acid, 50% Boiling | X | X | - | - | - | - | 1 | X | - | X | X | 2 | - | - |
| Acetic Acid, 80% | X | X | - | - | - | - | 1 | X | 1 | X | 2 | 2 | 2 | X |
| Acetic Acid, 80% Boiling | X | X | - | - | - | - | 1 | X | - | X | X | 2 | X | X |
| Acetic Acid, 100% | X | X | - | - | - | - | 1 | X | X | X | X | 2 | 2 | X |
| Acetic Acid, 100% Boiling | X | X | - | - | - | X | 1 | X | X | X | X | 2 | - | X |
| Acetic Acid, 100% (Hot) Vapors | 2 | 2 | - | - | - | - | - | X | X | X | X | 2 | 2 | X |
| Acetic Acid, Air Free | - | - | - | - | - | - | 1 | - | - | X | X | X | - | X |
| Acetic Acid, Anhydride | X | X | X | 1 | 2 | - | 1 | X | X | X | 2 | 2 | 2 | X |
| Acetic Acid, Areated | - | - | - | - | - | - | 1 | - | - | X | X | X | - | X |
| Acetic Acid, Crude | X | X | - | - | - | - | 1 | 1 | - | X | 2 | 1 | 2 | X |
| Acetic Acid, Glacial | X | X | X | 1 | X | X | 1 | X | X | X | 2 | 2 | 2 | - |
| Acetone (Dimethylketone) | X | X | X | 1 | X | X | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Acetonitrile (Methyl Cyanide) | 2 | X | 2 | 1 | 2 | - | - | - | 2 | - | - | - | - | - |
| Acetylene | 2 | 2 | 1 | 1 | - | - | 1 | 1 | X | 1 | 1 | 1 | 1 | 2 |
| Acrylonitrile (Vinyl Cyanide) | X | X | X | 1 | X | - | - | - | 2 | 1 | 1 | 1 | 2 | 1 |
| Aero Lubriplate | 1 | 1 | - | - | - | - | - | - | - | 1 | 1 | 1 | 1 | - |
| Aero-Safe 2300 | X | X | - | - | - | X | - | - | - | 1 | 1 | 1 | 1 | 1 |
| Aeroshell Type 1A, 1AC, 4 | 2 | 1 | - | - | - | 1 | - | - | - | - | - | - | - | - |
| Aeroshell 7AGrease | 2 | 1 | - | - | - | X | - | - | - | 1 | 1 | 1 | 1 | - |
| Aeroshell 17 Grease | 2 | 1 | - | - | - | X | - | - | - | 1 | 1 | 1 | 1 | - |
| Aeroshell 750 | X | 2 | - | - | - | X | - | - | - | 1 | 1 | 1 | 1 | - |
| Air, Ambient | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Air, 150°F | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Air, 180°F | 2 | 2 | 2 | 1 | 2 | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Air, 200°F | X | X | X | 1 | X | 2 | 1 | 2 | 1 | 1 | 1 | 1 | 1 | 1 |
| Aircraft Hyd. Oil AA | - | 1 | - | - | - | - | - | - | - | 1 | 1 | 1 | 1 | 1 |
| Alcohol | 1 | 1 | - | - | - | - | 1 | - | 1 | 1 | 1 | 1 | 1 | 1 |
| Alcohol, Amyl | 2 | 2 | - | - | - | - | 1 | 1 | 2 | - | 2 | 1 | 2 | - |
| Alcohol, Benzyl | X | X | - | 1 | 2 | 2 | 1 | - | 1 | 1 | 1 | 1 | - | - |
| Alcohol, Butyl | 2 | X | 2 | - | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Alcohol, Denatured | 1 | 1 | - | - | 1 | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Alcohol, Diacetone | - | X | - | - | 2 | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Alcohol, Ethyl (Ethanol) | 1 | 1 | 1 | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 |
| Alcohol, Furfural | 2 | X | X | 1 | 2 | - | 1 | - | 2 | 2 | 1 | 1 | 1 | 1 |
| Alcohol, Hexyl (Hexanol) | 2 | 1 | - | - | X | - | 1 | - | - | 1 | 1 | 1 | 1 | 2 |
| Alcohol, Isobutyl | 2 | 2 | - | - | 1 | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 |
| Alcohol, Isopropyl (Isopropanol) | 2 | 2 | 2 | - | 2 | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 |
| Alcohol, Methyl (100%) (Methanol) | 1 | 1 | 1 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 |
| Alcohol, Methyl (6%) | 1 | 1 | 1 | - | 1 | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 |
| Alcohol, Octyl | 2 | 2 | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | - |
| Alcohol, Propyl | 1 | 1 | - | - | - | - | 1 | X | 1 | 2 | 1 | 1 | 1 | 1 |
| Alkazene | X | X | X | - | X | X | - | - | - | 1 | 1 | - | - | - |
| Aluminum Chloride | 1 | 1 | 1 | 1 | 1 | 2 | 1 | X | X | X | 2 | 2 | X | X |
| Aluminum Fluoride | 1 | 1 | 1 | 1 | 1 | 2 | 1 | X | - | X | 2 | 2 | 2 | X |
| Aluminum Hydroxide | 1 | 1 | 1 | 1 | 1 | - | 1 | 1 | 1 | - | 1 | 1 | - | 1 |
| Aluminum Hydroxide, Saturated | 1 | 1 | - | - | - | - | 1 | 1 | 1 | - | 1 | 1 | - | - |
| Aluminum Nitrate | 1 | 1 | 1 | 1 | 1 | 2 | 1 | - | 1 | X | 1 | 1 | 2 | - |
| Aluminum Sulfate | 1 | 1 | 1 | 1 | 1 | X | 1 | 1 | - | X | X | 2 | X | X |
| Alums (Ammonium or Potassium) | 1 | 1 | 1 | 1 | 1 | - | 1 | - | 1 | X | 2 | 2 | X | X |
| Ammonia, Aqueous | 1 | 2 | 1 | - | 1 | - | 1 | 1 | 1 | - | 1 | 1 | - | X |
| Ammonium Carbonate | 2 | X | - | - | - | - | - | - | - | 1 | 1 | 1 | - | - |

Rating Scale:
1 Excellent
2 Good resistance
X Not recommended
– Testing recommended
[ ] Cover stock rating only; Rating for tube stock "X"
* Use Gates fuel hose or contact Denver Product Application Department

| Chemical Name | Gates Hose Polymers: Polychloroprene | Nitrile, HNBR, or XTF | Nitrile + PVC | CPE | CSM | Urethane | PTFE | Nylon | MegaTuff | Couplings & Adapters: Carbon Steel | Stainless Steel 304 | Stainless Steel 316 | Aluminum | Brass |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Ammonium Chloride, 1% | X | 2 | 1 | 1 | 1 | 1 | 1 | 1 | - | X | 2 | 2 | X | X |
| Ammonium Chloride, 10% Boiling | X | X | - | - | - | - | 1 | X | - | X | 2 | 2 | X | X |
| Ammonium Chloride, 28% Boiling | X | X | - | - | - | - | 1 | X | - | X | 2 | 2 | X | X |
| Ammonium Chloride, 50% Boiling | X | X | - | - | - | - | 1 | X | - | X | 2 | 2 | X | X |
| Ammonium Hydroxide | 2 | 2 | 2 | 1 | 1 | X | 1 | 1 | 1 | 2 | 1 | 1 | - | X |
| Ammonium Hydroxide, 3 Molar | 1 | X | - | - | - | 2 | 1 | - | 1 | X | 2 | 2 | X | X |
| Ammonium Hydroxide, Concentrated | 1 | X | - | 1 | - | X | 1 | 1 | 1 | X | 2 | 2 | X | X |
| Ammonium Metaphosphate | 2 | 2 | 2 | - | 2 | - | 1 | - | - | 1 | 1 | 1 | X | - |
| Ammonium Nitrate, Fertilizer | 1 | 2 | 1 | 1 | 1 | 1 | 1 | X | - | 1 | 1 | 1 | 2 | X |
| Ammonium Nitrite | 1 | 1 | - | - | - | - | - | 1 | - | 2 | 1 | 1 | X | - |
| Ammonium Persulfate | X | X | X | 1 | - | X | - | X | - | X | 2 | 2 | X | X |
| Ammonium Persulfate, 5% | 1 | X | - | - | - | - | - | X | - | X | 2 | 2 | X | X |
| Ammonium Persulfate, 10% | 1 | X | - | - | - | X | - | X | | X | 2 | 2 | X | X |
| Ammonium Phosphate (Mono, Di, Tri, Basic) | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | - | X | 2 | 2 | X | - |
| Ammonium Sulfate | 1 | 2 | 1 | 1 | 1 | 1 | 1 | X | - | X | X | 2 | X | X |
| Ammonium Thiocyanate | 1 | 1 | - | 1 | 1 | - | 1 | - | - | 1 | 1 | 1 | - | - |
| Amyl Acetate | X | X | X | 2 | X | 2 | 1 | 1 | 1 | X | 1 | 1 | X | 2 |
| Amyl Alcohol | 2 | 2 | 2 | 1 | - | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Amyl Borate | 2 | 2 | 2 | - | - | - | - | - | 2 | - | - | - | - | - |
| Amyl Chloride | X | - | X | 2 | X | - | 1 | 2 | - | - | 1 | 1 | - | - |
| Amyl Chloronaphthalene | X | X | X | - | X | - | 1 | - | 2 | - | 1 | 1 | - | - |
| Amyl Naphthalene | X | X | X | - | X | - | 1 | - | 2 | - | 1 | 1 | - | - |
| Amyl Phenol | - | - | - | - | - | - | 1 | - | - | - | 1 | 1 | - | - |
| AN-0-3 Grade M | 1 | 1 | - | - | - | - | - | - | - | - | - | - | - | - |
| AN-0-6 | 1 | 1 | - | - | - | - | - | - | - | - | - | - | - | - |
| AN-0-366 | 1 | 1 | - | - | - | - | - | - | - | - | - | - | - | - |
| Anderol, L-774 (Diester) | X | 2 | - | - | - | - | 1 | X | - | - | - | - | - | - |
| Anderol, L-826 (Diester) | X | 2 | - | - | - | - | 1 | X | - | - | - | - | - | - |
| Anderol, L-829 (Diester) | X | 2 | - | - | - | - | 1 | X | - | - | - | - | - | - |
| ANG-25 (Glyceral Ester) | 2 | 2 | - | - | - | - | 1 | 2 | - | - | - | - | - | - |
| ANG-25 (Diester Base, TG749) | X | 2 | - | - | - | - | 1 | X | - | 1 | 1 | 1 | 1 | - |
| Aniline | X | X | X | 2 | X | X | 1 | 2 | - | 2 | 1 | 1 | X | X |
| Aniline Dyes | X | X | - | 2 | - | - | 1 | X | X | 2 | 1 | 1 | 2 | X |
| Aniline Hydrochloride | X | X | - | 2 | - | - | 1 | - | - | X | 1 | 1 | - | - |
| Animal Gelatin | 1 | 1 | - | 1 | - | - | 1 | - | - | - | 1 | 1 | - | - |
| Animal Fats | 2 | 1 | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | X |
| Animal Oil (Lard Oil) | 2 | 1 | - | 1 | - | - | 1 | - | 1 | 1 | 1 | 1 | 1 | - |
| Antifreeze, Alcohol Base | 2 | 2 | 2 | 2 | 2 | - | 1 | - | 1 | 1 | 1 | 1 | 1 | - |
| Antifreeze, Glycol Base | 2 | 1 | 1 | 1 | 1 | - | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 |
| Antimony Chloride, 50% | - | 1 | - | - | - | - | 1 | X | 2 | X | X | X | - | - |
| AN-VV-0-366B Hydraulic Fluid | 1 | - | - | - | - | - | - | 2 | 1 | - | - | - | - | - |
| Aqua Regia (Concentrated) | X | X | X | 2 | X | X | 1 | X | - | X | X | X | X | - |
| Arco A.T.F. Dexron | - | 1 | - | - | - | - | - | - | X | - | - | - | - | - |
| Arco C2, 100 | - | 1 | - | - | - | - | - | - | - | - | - | - | - | - |
| Aromatic Fuel 30%, Mil. | - | - | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Aromatic Fuel 50% | X | 2 | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Aromatic Hydrocarbons | X | X | - | - | X | 2 | 1 | - | - | 2 | 1 | 2 | 2 | 2 |
| Arsenic Acid | - | - | - | 1 | - | - | 1 | - | 2 | 2 | - | 1 | 2 | - |
| Askarel, Transformer Oil | X | X | X | - | X | - | 1 | - | 1 | 1 | 1 | 1 | - | 1 |
| Asphalt, Under 180°F | 2 | 2 | 2 | X | X | 1 | 1 | - | 2 | 1 | 1 | 1 | - | 2 |
| Asphalt, Cut Back | X | 2 | 2 | - | X | 1 | 1 | 1 | X | 1 | 1 | 1 | 2 | 2 |
| Asphalt, Topping | 1 | X | - | - | - | - | 1 | - | X | 1 | 1 | 1 | - | - |
| ASTM Oil No. 1 | 1 | 1 | 1 | 1 | 1 | 2 | 1 | 1 | X | 1 | 1 | 1 | 1 | 1 |
| ASTM Oil No. 2 | 2 | 2 | 1 | - | 2 | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| ASTM Oil No. 3 | X | 1 | X | X | X | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| ASTM Oil No. 4 | X | 2 | - | - | - | - | 1 | - | 1 | 1 | 1 | 1 | 1 | - |

Rating Scale:
1 Excellent
2 Good resistance
X Not recommended
– Testing recommended
[ ] Cover stock rating only; Rating for tube stock "X"
* Use Gates fuel hose or contact Denver Product Application Department

| Chemical Name | Gates Hose Polymers: Polychloroprene | Nitrile, HNBR, or XTF | Nitrile + PVC | CPE | CSM | Urethane | PTFE | Nylon | MegaTuff | Couplings & Adapters: Carbon Steel | Stainless Steel 304 | Stainless Steel 316 | Aluminum | Brass |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| ASTM Reference Fuel A | [2] | 1 | [1] | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| ASTM Reference Fuel B | [2] | 1 | [2] | 2 | X | - | 1 | - | 1 | 1 | 1 | 1 | 1 | 1 |
| ASTM Reference Fuel C | X | 2 | X | 2 | X | - | 1 | - | 1 | 1 | 1 | 1 | - | 1 |
| ATL-857 | X | 2 | - | - | - | - | - | - | 2 | - | - | - | - | - |
| Atlantic Dominion F | 2 | 1 | - | - | - | - | - | - | - | - | - | - | - | - |
| Aurex 903R (Mobil) | 2 | 1 | - | - | - | - | - | - | - | - | - | - | - | - |
| Automatic Brake Fluid | 2 | X | - | - | - | - | 1 | - | 1 | 1 | 1 | 1 | 1 | - |
| Automatic Transmission Fluid - ATF | 2 | 1 | - | 1 | - | - | 1 | - | 1 | 1 | 1 | 1 | 1 | - |
| Aviation Gasoline, Mil. | - | 2 | - | - | - | - | - | - | - | 1 | 1 | 1 | 1 | - |
| **B** | | | | | | | | | | | | | | |
| Baltic Types 100, 150, 200, 300, 500 | - | 1 | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Banvel, Concentrated (Ag Spray) | - | - | - | - | - | - | 1 | 1 | - | - | - | 1 | - | - |
| Bardol B | X | X | X | - | X | - | 1 | - | - | 1 | 1 | 1 | - | - |
| Barium Carbonate | 1 | 1 | 1 | 1 | 1 | - | 1 | 1 | - | 2 | 1 | 1 | X | 1 |
| Barium Chloride | X | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | X | 2 | 2 | X | 2 |
| Barium Chloride, 5% | X | 1 | - | - | - | - | 1 | X | 1 | 2 | 1 | 1 | X | - |
| Barium Chloride, Aqueous Solution (Hot) | X | 1 | - | - | - | - | 1 | X | - | 2 | 2 | 2 | X | - |
| Barium Hydroxide | 1 | 1 | 1 | 1 | 1 | X | 1 | 1 | 1 | X | 1 | 1 | X | X |
| Barium Sulfate | 1 | 1 | - | 1 | 2 | - | 1 | 1 | 1 | 2 | 1 | 1 | 2 | 2 |
| Barium Sulfate, Aqueous Solution (Hot) | X | - | - | - | - | - | 1 | X | 1 | 2 | 1 | 1 | 2 | - |
| Barium Sulfide | 2 | 1 | 1 | 1 | 1 | - | 1 | 2 | 1 | X | 1 | 1 | X | X |
| Bayol D | - | 1 | - | - | - | - | - | - | - | - | - | - | - | - |
| Bayol 35 | - | 1 | - | - | - | - | - | - | - | - | - | - | - | - |
| Beet Sugar Liquors | X | 1 | 1 | 1 | 1 | X | 1 | - | 1 | 2 | 2 | 2 | 2 | X |
| Bellows 80-20 Hydraulic Oil | - | 1 | - | - | - | 2 | 1 | - | - | - | - | - | - | - |
| Benzaldehyde | X | X | X | 2 | X | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Benzene, Benzol | X | X | X | X | X | 2 | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 |
| Benzene Sulfonic Acid | X | - | - | - | - | - | 1 | - | 1 | X | - | 2 | X | - |
| Benzine, Petroleum Ether | X | 2 | X | 1 | - | 2 | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Benzoic Acid 21°C (70°F) | X | X | X | 1 | - | - | 1 | - | 1 | 1 | 1 | 1 | 1 | 1 |
| Benzol | X | X | X | X | - | - | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 |
| Benzyl Alcohol | X | X | - | 1 | - | - | 1 | X | 1 | 1 | 1 | 1 | 1 | - |
| Benzyl Benzoate | - | - | - | - | - | - | 1 | - | - | 1 | 1 | 1 | - | - |
| Benzyl Chloride | X | X | X | X | - | - | 1 | 2 | 2 | 1 | - | - | - | - |
| Bismuth Carbonate | X | - | - | - | - | - | 1 | - | - | 1 | 1 | 1 | - | - |
| Black Point 77 | - | 1 | - | - | - | - | - | - | - | - | - | - | - | - |
| Black Sulfate Liquor | 2 | 2 | 2 | 2 | 2 | - | 1 | 1 | 1 | 1 | 1 | 1 | - | 1 |
| Blast Furnace Gas | X | X | X | - | X | X | 1 | - | - | 1 | 1 | 1 | 2 | 1 |
| Borax, Sodium Borate | X | 2 | 2 | 1 | 1 | 1 | 1 | X | - | 2 | 1 | 1 | X | 2 |
| Bordeaux Mixture | 2 | 2 | 2 | - | - | 1 | 1 | 1 | 1 | X | - | 1 | 1 | X |
| Boric Acid | 1 | 1 | 1 | - | 1 | 1 | 1 | X | 1 | X | 2 | 2 | 1 | X |
| Boron Fuels, HEF | X | X | - | - | - | - | - | - | - | - | - | - | - | - |
| Brake Fluid, Petroleum Base | 2 | 1 | 2 | 1 | X | - | 1 | - | - | 1 | 1 | 1 | - | 1 |
| Brake Fluid, Synthetic Base | X | X | X | 1 | X | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Bray GG - 130 | X | 2 | - | - | - | - | - | - | - | - | - | - | - | - |
| Brayco 719-r (VV-H-910) | 2 | X | - | - | - | - | - | - | - | - | - | - | - | - |
| Brayco 885 (MIL-L-6085A) | X | 2 | - | - | - | - | - | - | - | - | - | - | - | - |
| Brayco 910 | 2 | 2 | - | - | - | - | - | - | - | - | - | - | - | - |
| Brine | 1 | 1 | 1 | 1 | - | - | 1 | 1 | 1 | 2 | 1 | 1 | - | 2 |
| Brom-113 | X | 2 | - | - | - | - | - | - | - | - | - | - | - | - |
| Brom-114 | 2 | 2 | - | - | - | - | - | - | - | - | - | - | - | - |
| Bromine, Dry | X | X | X | - | - | - | X | - | - | X | X | X | - | X |
| Bunker Oil | X | 2 | 2 | - | X | 2 | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 |
| Butadiene | X | 2 | - | - | - | - | 1 | 1 | - | - | 1 | 1 | - | 1 |
| Butane | X | X | X | - | X | X | 1 | X | - | 1 | 1 | 1 | - | 1 |
| Butter Oil | 2 | - | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Butyric Acid | X | - | - | 1 | - | - | 1 | X | 1 | X | 1 | 1 | - | 2 |
| Butyl Acetate | X | X | X | 2 | X | - | 1 | - | 2 | 2 | 1 | 1 | 1 | 1 |
| Butyl Alcohol | 1 | 1 | 1 | 1 | - | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Butyl Amine | - | - | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Butyl Carbitol | 2 | 2 | - | 1 | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Butyl Mercaptan | - | - | - | - | - | - | 1 | - | - | - | 1 | 1 | 1 | - |
| Butyl Stearate | X | 2 | 2 | 2 | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Butyraldehyde | X | X | - | 2 | - | - | 1 | - | - | - | - | - | - | 1 |
| **C** | | | | | | | | | | | | | | |
| Calcium Acetate | X | X | X | 1 | X | - | 1 | - | - | 2 | 2 | 2 | X | 1 |
| Calcium Arsenate | - | - | - | - | - | 1 | 1 | 1 | - | - | - | - | - | - |
| Calcium Bisulfate | 1 | 1 | 2 | 1 | 1 | - | 1 | - | - | - | 2 | 1 | - | X |
| Calcium Bisulfide | 1 | 1 | 2 | 1 | 1 | 1 | 1 | - | - | - | 2 | 2 | X | X |
| Calcium Bisulfite | 1 | 1 | 1 | 1 | 1 | - | 1 | 1 | - | X | 1 | 1 | 1 | X |
| Calcium Carbonate | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | 2 | 1 | 1 | X | 1 |
| Calcium Chlorate | 1 | 1 | 1 | - | 1 | - | 1 | - | - | 2 | 2 | 1 | 1 | - |
| Calcium Chloride | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | X | 2 | 1 | X | - |
| Calcium Hydroxide | 1 | 2 | 2 | 1 | 1 | X | 1 | - | X | X | X | 1 | - | 2 |
| Calcium Hydroxide, 10% Boiling | - | 2 | - | - | - | - | 1 | X | X | 2 | 1 | 1 | X | X |
| Calcium Hydroxide, 20% Boiling | - | - | - | - | - | - | 1 | X | X | - | 1 | 1 | X | X |
| Calcium Hydroxide, 50% Boiling | - | - | - | - | - | - | 1 | X | X | - | X | 2 | X | X |
| Calcium Hypochlorite, 5% (Under 100°F) | X | 2 | X | 1 | 2 | - | 1 | X | X | X | X | 2 | X | X |
| Calcium Hypochlorite, 15% (Under 100°F) | X | - | X | 1 | 2 | - | 1 | X | X | - | X | 2 | X | X |
| Calcium Nitrate | 1 | 1 | 1 | 1 | 1 | - | 1 | 1 | - | X | 2 | 2 | X | 1 |
| Calcium Silicate | - | 2 | - | 1 | 2 | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Calcium Sulfate | 1 | 1 | 1 | 1 | 1 | - | 1 | - | - | 2 | 1 | 1 | 2 | 1 |
| Calcium Sulfide | 1 | 2 | - | 1 | - | - | 1 | 2 | - | 2 | 1 | 1 | 2 | – |
| Caliche Liquors | 1 | 2 | - | 1 | 1 | 1 | 1 | - | - | 1 | 1 | 1 | - | - |
| Cane Sugar Liquors | 1 | 1 | 2 | 1 | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 2 |
| Carbolic Acid, Phenol | X | X | X | 1 | X | X | 1 | X | - | X | 1 | 1 | 2 | X |
| Carbon Dioxide, Dry | 2 | 1 | 1 | 1 | 1 | 1 | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Carbon Dioxide, Wet | 2 | 1 | 1 | 1 | 1 | - | 1 | - | 1 | 1 | 1 | 1 | 1 | 1 |
| Carbon Disulfide | X | X | - | 2 | X | 2 | 1 | 1 | 1 | 2 | 1 | 1 | 2 | X |
| Carbon Monoxide, Under 150°F (Hot) | 2 | 2 | 2 | 1 | 1 | - | 1 | 2 | 1 | 1 | 1 | 1 | 1 | 1 |
| Carbon Tetrachloride, 5%-10% | - | - | - | - | - | - | 1 | - | X | - | X | - | - | - |
| Carbon Tetrachloride, Pure | X | X | X | 2 | X | X | 1 | X | X | X | X | 2 | 2 | 2 |
| Carbonic Acid | 1 | 1 | 1 | 1 | 1 | X | 1 | - | 1 | X | 1 | 1 | 2 | X |
| Castor Oil | 2 | 2 | 2 | 1 | 2 | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Caustic Soda, 20% | 2 | X | X | 1 | 1 | X | 1 | 2 | - | 2 | 1 | 1 | X | X |
| Caustic Soda, 50% | 2 | X | X | 1 | 1 | X | 1 | 2 | - | 2 | 1 | 1 | X | X |
| Cellosolve Acetate, Under 100°F | X | X | X | 2 | X | - | 1 | - | - | 2 | 2 | 2 | 1 | – |
| Cellosolve, Butyl, Under 100°F | X | X | X | - | X | - | 1 | - | - | 2 | 2 | 2 | 2 | – |
| Cellosolve, Union Carbide, Under 100°F | X | X | - | - | - | - | 1 | - | - | 2 | 2 | 2 | 2 | - |
| Cellugard, Cellugard 200 | 1 | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Cellulube 90, 150, 220, 300, 550 | X | X | X | - | X | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Cellulube 1000, 220A, ST220, A60 | X | X | X | - | X | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Cellutherm 2505A | X | 2 | - | - | - | - | - | - | - | - | - | - | - | - |
| Chevron Fr-10,13,20.8 | - | - | - | - | - | - | 1 | - | - | 1 | 1 | 1 | - | 1 |
| Chlordane | X | X | X | - | X | - | 1 | 1 | - | - | - | - | - | - |
| Chlorinate Paraffin & Petroleum Oil | - | - | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Chlorine Gas, Dry | NO HOSE AVAILABLE | | | | | | | | | 2 | X | X | - | 2 |
| Chlorine Gas, Wet | NO HOSE AVAILABLE | | | | | | | | | X | X | X | X | X |
| Chlorine Trifluoride | X | X | - | - | - | - | - | - | - | 1 | 1 | 1 | 1 | - |

**Nitrile 150°F or less, no constant contact.

# CHEMICAL RESISTANCE TABLE – CONTINUED

Rating Scale:
1 Excellent
2 Good resistance
X Not recommended
– Testing recommended
[ ] Cover stock rating only; Rating for tube stock "X"
* Use Gates fuel hose or contact Denver Product Application Department

| Chemical Name | Gates Hose Polymers: Polychloroprene | Nitrile, HNBR, or XTF | Nitrile + PVC | CPE | CSM | Urethane | PTFE | Nylon | MegaTuff | Couplings & Adapters: Carbon Steel | Stainless Steel 304 | Stainless Steel 316 | Aluminum | Brass |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Chlorine Water, 3% Chlorine | X | X | X | - | - | - | 1 | - | 1 | - | X | X | - | - |
| Chlorine Water, 25% Chlorine | X | X | X | - | 2 | 2 | 1 | 2 | - | - | X | X | - | - |
| Chloroacetic Acid (Under 100°F) | X | X | X | - | 2 | - | 1 | X | X | X | X | X | - | 2 |
| Chlorobenzene | X | X | X | X | X | - | 1 | X | - | 2 | 2 | 2 | X | 1 |
| Chlorobromo Methane | X | X | X | - | X | - | 1 | - | X | 2 | 2 | 2 | X | 1 |
| Chloroform | X | X | X | X | X | - | 1 | X | 2 | 2 | 1 | 1 | X | 1 |
| O-Chloronaphthalene | X | X | X | - | - | - | 1 | 2 | - | 1 | 1 | 1 | - | 1 |
| Chlorosulfonic Acid | 2 | X | X | X | - | - | 1 | X | X | 1 | - | - | - | - |
| Chlorotoluene | X | X | X | X | X | X | 1 | - | - | 1 | 1 | 1 | X | 1 |
| Chlorox, Bleach | 2 | 2 | - | 1 | 2 | - | 1 | 1 | 1 | X | X | 2 | X | X |
| Chromic Acid, 5% | X | X | - | - | - | - | 1 | X | 1 | X | X | 2 | X | X |
| Chromic Acid, 10% | X | X | X | 1 | 2 | X | 1 | X | 1 | X | X | 2 | X | X |
| Chromic Acid, 25% | X | X | X | 1 | 2 | X | 1 | X | 1 | X | X | 2 | X | X |
| Chromic Acid, 50% | X | X | X | 1 | 2 | X | 1 | X | 1 | X | X | 2 | 1 | X |
| Chromic Acid, 100% | - | - | - | - | - | X | 1 | - | 2 | X | X | 2 | - | X |
| Circo Light Process Oil | 1 | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Citgo FR Fluids | - | X | - | X | - | 2 | 1 | - | - | 1 | 1 | 1 | - | 1 |
| Citgo Glycol FR-20XD | - | 1 | - | - | - | 2 | 1 | - | - | 1 | 1 | 1 | - | 1 |
| Citgo Sentry (Under 100°F) | 2 | 2 | 1 | - | X | 2 | 1 | - | - | 1 | 1 | 1 | - | 1 |
| Citgo Tractor Hydraulic Fluid | - | 1 | - | - | - | 2 | 1 | - | - | 1 | 1 | 1 | - | 1 |
| Citric Acid, 5% | - | 2 | - | - | - | - | 1 | 1 | 1 | X | 1 | 1 | 1 | X |
| Citric Acid, 5% @150°F | - | 2 | - | - | - | - | 1 | X | 1 | X | X | 1 | 2 | X |
| Citric Acid, 15% | 1 | 2 | - | - | - | - | 1 | 1 | 1 | X | X | 1 | - | 1 |
| Citric Acid, 15% Boiling | 1 | 2 | - | - | - | - | 1 | X | - | X | 2 | 1 | X | X |
| Citric Acid, Concentrated Boiling | 1 | X | 1 | - | 1 | 2 | 1 | X | - | X | X | 1 | X | X |
| Coal Gas | 1 | X | - | 1 | - | 1 | 1 | - | - | - | - | - | - | - |
| Coal Tars | X | 2 | X | 2 | 2 | - | 1 | X | - | 1 | 1 | 1 | 1 | 1 |
| Cod Liver Oil | 1 | 1 | 1 | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Coke Oven Gas (Under 100°F) | X | 2 | X | - | 2 | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Condor 1000, 1002, 1004, 1006, 1008 | - | 2 | - | - | - | - | - | - | - | - | - | - | - | - |
| Condor 1008, 1010, 1012, 1014, 1016 | - | 2 | - | - | - | - | - | - | - | - | - | - | - | - |
| Convelex 10 | X | X | - | - | - | - | - | - | - | - | - | - | - | - |
| Copper Arsenate, Cupric Arsenate | - | - | - | - | 2 | - | 1 | - | - | 1 | 1 | 1 | - | - |
| Copper Chloride, 1% | 1 | 1 | - | - | - | - | 1 | X | - | X | X | 1 | - | X |
| Copper Chloride, 5% | 1 | 1 | - | - | - | - | 1 | X | - | X | X | 1 | - | - |
| Copper Chloride, Cupric Chloride | 2 | 2 | 2 | 2 | 2 | 1 | 1 | 2 | - | X | X | 1 | - | X |
| Copper Cyanide, Cupric Cyanide | 2 | 2 | 2 | - | 2 | - | 1 | X | - | 1 | 1 | 1 | - | X |
| Copper Nitrate, 1% & 5% | 1 | 1 | - | - | - | - | 1 | 1 | - | X | 1 | 1 | X | X |
| Copper Nitrate, Cupric Nitrate | 1 | 1 | 1 | 1 | 1 | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Copper Sulfate, Cupric Sulfate | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | X | 1 | 1 | X | X |
| Copper Sulfate, 10% | 1 | 1 | - | - | - | - | 1 | - | - | X | 2 | 2 | X | - |
| Copper Sulfate, 50% | 1 | 1 | - | - | - | - | 1 | - | - | - | 2 | 2 | - | - |
| Corn Oil | X | 2 | 2 | 2 | X | X | 1 | - | - | 1 | 1 | 1 | - | 1 |
| Corn Syrup | 2 | 2 | - | 2 | - | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Cottonseed Oil | 2 | 2 | 1 | 2 | 2 | X | 1 | 2 | - | 1 | 1 | 1 | 1 | 1 |
| Creosote, Wood Or Coal Tar (Under 100F) | X | 2 | X | - | X | X | 1 | X | X | 2 | 1 | 1 | 1 | X |
| Cresol, Cresylic Acid (Under 100°F) | X | X | X | 1 | X | - | 1 | X | - | 2 | 1 | 1 | 2 | - |
| Cyesylic Acid | X | X | - | - | - | - | 1 | X | - | 1 | 1 | 1 | 1 | – |
| Crude Petroleum Oil (Under 100°F) | X | X | 2 | 2 | 2 | 2 | 1 | - | - | X | X | 2 | 1 | - |
| Cutting Oil, Water Soluble | X | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | - | 1 |
| Cutting Oil, Sulfur Base | X | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |

Rating Scale:
1 Excellent
2 Good resistance
X Not recommended
– Testing recommended
[ ] Cover stock rating only; Rating for tube stock "X"
* Use Gates fuel hose or contact Denver Product Application Department

| Chemical Name | Gates Hose Polymers: Polychloroprene | Nitrile, HNBR, or XTF | Nitrile + PVC | CPE | CSM | Urethane | PTFE | Nylon | MegaTuff | Couplings & Adapters: Carbon Steel | Stainless Steel 304 | Stainless Steel 316 | Aluminum | Brass |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Cutting Oil | 2 | 1 | 2 | 1 | X | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Cyclohexane | X | 2 | - | 1 | X | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Cyclohexanone | X | X | X | 2 | X | 1 | 1 | 1 | - | - | 1 | 1 | 2 | - |
| Cymene | X | X | X | X | X | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| **D** | | | | | | | | | | | | | | |
| Dasco FR150, FR200, FR200B, FR310 | - | 1 | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Dasco IFR | - | 1 | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| DC200, DC510, DC550, DC560 | - | 1 | - | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 |
| Decalin | X | 2 | - | 2 | X | - | 1 | 1 | 2 | - | - | - | - | 1 |
| Dectol R&O Oils | X | 1 | - | - | - | 2 | - | - | - | - | - | - | - | - |
| Denatured Alcohol | 1 | 1 | 1 | 1 | - | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Developing Fluids, Photo | 1 | 1 | - | 1 | - | - | - | - | - | X | X | 2 | - | - |
| Developing Solutions, Hypos | 2 | - | - | 1 | 2 | - | 1 | - | - | - | 1 | 1 | - | - |
| Diacetone | X | X | X | 1 | X | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Diacetone Alcohol | - | X | - | 1 | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Dibenzel Ether | X | X | - | 2 | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Dibutyl Ether | X | X | - | 1 | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Dibutyl Phthalate (Under 120°F) | X | X | X | 2 | X | 2 | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Dibutyl Sebacate | X | X | X | 2 | - | - | 1 | - | - | - | - | - | - | 1 |
| Dichlorobenzene | X | X | X | X | X | X | 1 | 1 | - | - | 1 | 1 | - | 1 |
| Dichloroethane | X | X | X | X | - | - | 1 | X | 2 | - | X | X | X | X |
| Diesel Oil, Fuel ASTM #2 | [2] | 1 | [2] | 2 | X | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Diester Lubricant MIL-l-7808 | X | 2 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Diester Synthetic Lubricants | X | 2 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Diethylamine (Under 120°F) | 2 | 2 | - | 2 | X | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Diethylene Glycol | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Diethy Ether | X | X | - | 1 | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Diethyl Phthalate | - | X | - | 2 | - | - | 1 | - | - | - | 1 | 1 | - | 1 |
| Diethyl Sebacate | X | X | X | 2 | - | - | 1 | - | - | - | 1 | 1 | - | 1 |
| Diisobutylene | X | 2 | - | 1 | X | - | 1 | - | - | 2 | 1 | 1 | 2 | 1 |
| Diisobutyl Ketone | X | X | X | 2 | X | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Diisopropyl Ketone | X | X | X | 2 | X | - | 1 | 1 | - | - | 1 | 1 | - | 1 |
| Dimethyl Aniline | X | X | X | 2 | X | - | 1 | - | - | - | - | - | - | 1 |
| Dimethyl Formamide (Under 120°F) | X | X | X | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Dimethyl Phthalate | X | X | X | 1 | X | - | 1 | - | - | - | - | - | - | 1 |
| Dioctyl Phthalate | X | X | X | 2 | X | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Dioctyl Sebacate | X | X | X | X | X | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Dioxane | X | X | X | 2 | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Dipentene | X | X | - | 2 | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Dirco Oils | - | 1 | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Dispersing Oil #10 | X | X | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Dowtherm A | X | X | X | 2 | X | X | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Dowtherm E | X | X | - | 2 | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| DP47, 200 Flow - DOW | - | 1 | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Duro FR-HD | - | 1 | - | - | - | X | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Duro Oils | - | 1 | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| **E** | | | | | | | | | | | | | | |
| Elco 28-EPLubricant | X | 1 | - | - | - | - | - | - | - | 1 | 1 | 1 | 1 | - |
| Enamels | - | - | - | - | - | - | 1 | 1 | - | - | - | - | - | 1 |
| Energol HL68 | - | 1 | - | - | - | - | - | - | - | 1 | 1 | 1 | 1 | 1 |
| Energol HLPC 68 | - | 1 | - | - | - | - | - | - | - | 1 | 1 | 1 | 1 | 1 |
| EPHydraulic Oils, Chevron | - | 1 | - | - | - | - | - | - | - | 1 | 1 | 1 | 1 | 1 |
| Epichlorohydrin (Under 120°F) | X | X | - | - | - | - | 1 | - | - | 1 | 2 | 1 | 1 | - |
| Esam-6 Fluid | 2 | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Ethanol | 1 | 1 | - | 1 | - | X | 1 | 1 | 1 | X | 1 | 1 | - | 1 |
| Ethanolamine, Aminoethanol | 2 | 2 | - | 1 | X | X | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Ethers (Under 120°F) | X | 2 | X | 1 | 2 | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |

**Nitrile 150°F or less, no constant contact.

Rating Scale:
1 Excellent
2 Good resistance
X Not recommended
– Testing recommended
[ ] Cover stock rating only; Rating for tube stock "X"
* Use Gates fuel hose or contact Denver Product Application Department

| Chemical Name | Gates Hose Polymers: Polychloroprene | Nitrile, HNBR, or XTF | Nitrile + PVC | CPE | CSM | Urethane | PTFE | Nylon | MegaTuff | Couplings & Adapters: Carbon Steel | Stainless Steel 304 | Stainless Steel 316 | Aluminum | Brass |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Ethyl Acetate | X | X | X | 2 | X | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 2 |
| Ethyl Acetoacetate | X | X | X | 1 | X | X | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Ethyl Acrylate | X | X | X | 2 | X | X | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Ethyl Alcohol | 1 | 1 | 1 | 1 | - | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 |
| Ethyl Amine, Monoethylamine | X | X | X | 1 | X | X | 1 | - | - | 2 | 1 | 1 | 2 | 1 |
| Ethyl Benzene | X | X | X | 2 | X | 1 | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Ethyl Bromide, Di | X | X | X | 2 | X | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Ethyl Butyrate | X | X | X | - | - | - | 1 | - | - | - | 1 | 1 | 1 | - |
| Ethyl Cellulose | - | - | - | 1 | - | - | 1 | - | - | 1 | 1 | 1 | - | 1 |
| Ethyl Chloride | X | X | X | - | - | X | 1 | - | 2 | 2 | 1 | 1 | 1 | 2 |
| Ethyl Ether | | X | X | X | - | - | 1 | - | X | 2 | 1 | 1 | 1 | 1 |
| Ethyl Mercaptan | X | X | X | - | X | X | 1 | - | - | 2 | - | - | - | - |
| Ethyl Oxalate | X | X | - | 1 | X | X | 1 | - | - | - | - | - | - | - |
| Ethyl Pentachlorobenzene | - | X | - | X | - | 1 | 1 | - | - | 2 | 1 | 1 | - | 1 |
| Ethyl Silicate | 1 | 1 | 1 | 1 | - | 1 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Ethylene Chloride | X | X | X | X | - | 1 | 1 | X | - | - | 1 | 1 | - | 2 |
| Ethylene Chlorohydrin, Under 100°F | X | X | X | - | - | X | 1 | X | - | 1 | 1 | 2 | X | - |
| Ethylene Diamine (Under 100°F) | 2 | 2 | 2 | 1 | X | X | 1 | - | - | - | - | - | - | 1 |
| Ethylene Dichloride | X | X | X | X | - | 1 | 1 | X | - | - | 1 | 1 | X | 2 |
| Ethylene Glycol | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 1 | 1 | 1 | 1 |
| **F** | | | | | | | | | | | | | | |
| Factovis 52 | - | 1 | - | - | - | - | - | - | - | 1 | 1 | 1 | 1 | 1 |
| Fatty Acids | 2 | 2 | 2 | 2 | X | 1 | 1 | 1 | 2 | 2 | 1 | 1 | 1 | 2 |
| Ferric Chloride | - | - | - | 1 | 2 | - | 1 | 1 | - | X | X | X | X | X |
| Ferric Chloride, 1% | 1 | 1 | - | - | - | - | 1 | 1 | - | X | 2 | 2 | X | X |
| Ferric Chloride, 1% Boiling | - | 2 | - | - | - | - | 1 | 1 | - | X | X | X | X | X |
| Ferric Chloride, 5% Still | 2 | 1 | - | - | - | - | 1 | 1 | - | X | X | X | X | X |
| Ferric Chloride, 5% Agitated or Aerated | 2 | 2 | - | - | - | - | 1 | 1 | - | X | X | X | X | X |
| Ferric Chloride, 10% | 2 | 1 | - | - | - | - | 1 | 1 | - | X | X | X | X | X |
| Ferric Sulfate | 2 | 2 | 2 | 1 | 2 | - | 1 | 1 | 1 | X | 1 | 1 | X | X |
| Ferrous Chloride | 1 | 1 | - | 1 | 2 | - | 1 | - | - | X | 1 | 2 | - | 2 |
| Ferrous Nitrate | 2 | 2 | 2 | - | 2 | - | 1 | - | - | - | 1 | 1 | - | - |
| Ferrous Sulfate, Copper Gas | 2 | 2 | 2 | 1 | 2 | - | 1 | - | 1 | X | 1 | 1 | 1 | 2 |
| Ferrous Sulfate, 10% | 1 | 1 | - | - | - | - | 1 | 1 | 1 | X | 2 | 2 | X | - |
| Ferrous Sulfate, Saturated | 1 | - | - | - | - | - | 1 | 1 | 1 | - | 2 | 2 | X | - |
| Fire Resistant Hydraulic Fluid, Texaco | - | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Firtec 290, MF | - | - | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Fixing Solution, Photo | 2 | - | - | - | 2 | - | 1 | - | - | - | 1 | 1 | - | - |
| Fluoboric Acid | 1 | 1 | - | 1 | - | - | 1 | - | 1 | 1 | - | 1 | X | - |
| Fluoboric Acid, 65% | 2 | - | - | 1 | 2 | X | 1 | - | 1 | - | 1 | 1 | - | - |
| Fluosilicic Acid | 2 | 1 | - | - | - | - | 1 | - | 1 | X | X | X | X | 1 |
| Fluosilicic Acid, 50% | 2 | X | X | 1 | 2 | X | 1 | X | 1 | - | - | - | 1 | - |
| Formaldehyde | 1 | X | - | 1 | - | - | 1 | 2 | - | 1 | 1 | 1 | 1 | X |
| Formaldehyde, 37% | 2 | 2 | - | 1 | 2 | 2 | 1 | - | 1 | - | 1 | 1 | 1 | 1 |
| Formaldehyde, Hot | - | - | - | - | - | - | 1 | 1 | - | X | 2 | 1 | 2 | 1 |
| Formic Acid (Under 120°F) | 1 | X | 1 | 1 | 2 | X | 1 | 2 | 1 | X | 2 | 1 | 1 | 2 |
| Formic Acid, Dilute Hot | 1 | X | - | 1 | - | - | 1 | X | - | X | 2 | 1 | 2 | X |
| Freon 12 (Under 100°F) Use Freon Hose Only | | | | | | | | | 2 | 1 | 1 | 1 | 1 | |
| Freon 114 Use Freon Hose Only | | | | | | | | | 1 | 1 | 1 | 1 | - | |
| Fruit Juices | | | | | | - | - | 1 | 1 | - | X | 1 | 1 | - | - |
| Fuel Oil | [2] | 1 | [1] | 1 | X | 2 | 1 | 1 | 1 | 2 | 2 | 2 | 1 | 2 |
| Fumaric Acid | 2 | X | - | - | - | X | 1 | - | 1 | 1 | 1 | 1 | - | - |
| Furan, Furfuran | X | X | X | 1 | - | - | 1 | - | 1 | 1 | 1 | 1 | 1 | 1 |
| Furan Resin | X | X | - | - | - | - | 1 | - | - | - | - | 1 | - | - |
| Furfural Alcohol, Ant Oil | 2 | X | X | 1 | 2 | - | 1 | 1 | 2 | 2 | 1 | 1 | 1 | 1 |

**Nitrile 150°F or less, no constant contact.

| Chemical Name | Gates Hose Polymers: Polychloroprene | Nitrile, HNBR, or XTF | Nitrile + PVC | CPE | CSM | Urethane | PTFE | Nylon | MegaTuff | Couplings & Adapters: Carbon Steel | Stainless Steel 304 | Stainless Steel 316 | Aluminum | Brass |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Fusel Oil, Grain Oil | X | X | - | - | - | - | 1 | - | 1 | - | - | - | - | - |
| Fyrguard 150, 200 | - | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Fyrquel A60, 90, 100, 150, 220, 300, 500 | X | X | - | - | - | - | 1 | - | - | 1 | - | - | 1 | - |
| Fyrquel 1000, 15R&O, 220R&O, 550R&O | X | X | - | - | - | - | 1 | - | - | 1 | - | - | 1 | - |
| **G** | | | | | | | | | | | | | | |
| Gallic Acid (Under 100°F) | X | X | X | 1 | - | X | 1 | 2 | 1 | X | 1 | 1 | X | - |
| Gas, Natural | - | - | - | X | - | - | 1 | - | - | 1 | 1 | 1 | - | 2 |
| Gasohol | 2 | * | * | - | X | - | 1 | - | 1 | 2 | 1 | 1 | 1 | 1 |
| Gasoline, Aviation | X | - | 2 | - | - | - | 1 | - | 1 | - | 1 | 1 | 1 | 1 |
| Gasoline, Meter | X | * | - | - | - | - | 1 | X | 1 | 1 | 1 | 1 | 1 | X |
| Gasoline, Premium | [2] | * | * | - | X | X | 1 | - | 1 | 2 | 1 | 1 | 1 | 1 |
| Gasoline, Sour | X | X | - | - | - | - | 1 | - | - | 2 | 1 | 1 | X | - |
| Gasoline, Standard | [1] | * | * | 2 | X | X | 1 | - | 1 | 2 | 1 | 1 | 1 | 1 |
| Gasoline, Unleaded Under 50% Aromatics | X | * | X | - | X | X | 1 | - | 1 | 2 | 1 | 1 | 1 | 1 |
| Gelatin | 1 | 1 | - | - | - | - | 1 | 1 | - | X | 1 | 1 | 1 | - |
| Glauber's Salt | 2 | X | - | - | - | - | 1 | - | - | 1 | 1 | 1 | - | - |
| Glucose | 1 | 1 | 1 | - | 1 | 1 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Glue (Under 120°F) | 2 | 2 | 2 | - | 1 | 1 | 1 | 2 | - | 2 | 1 | 1 | 2 | X |
| Glycerine, Glycerol | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | 2 | 1 | 1 | 1 | 2 |
| Glycol FR Fluids | - | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Glycols (Under 120°F) | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 2 | 1 | 1 | 1 | 1 |
| Grease, Ester Base | - | - | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Grease, Petroleum Base | 2 | 1 | 2 | - | 2 | 1 | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 |
| Grease, Silicone Base | - | - | - | - | - | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Green Sulfate Liquor, Under 100°F | 2 | 2 | 1 | 2 | 1 | - | 1 | - | 1 | 1 | 1 | 1 | - | - |
| Gulf FR Fluid G-200 | - | 1 | - | - | - | X | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Gulf FR Fluid P37, P40, P43, P45, P47 | - | X | - | - | - | X | 1 | - | - | - | - | - | - | - |
| **H** | | | | | | | | | | | | | | |
| Halowax Oil | X | X | X | - | X | - | 1 | - | 1 | - | - | - | - | - |
| Heptachlor, In Petroleum | - | 2 | X | - | - | - | 1 | - | - | - | - | - | - | - |
| Heptane (Under 100°F) | [2] | 1 | [2] | 1 | X | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| N-Hexaldehyde | 2 | X | 2 | - | - | - | 1 | - | 1 | 1 | 1 | 1 | 1 | 1 |
| Hexane (Under 120°F) | [2] | 1 | [2] | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Hexene | [2] | 2 | - | 1 | - | - | 1 | - | 1 | 1 | 1 | 1 | - | 1 |
| Hexyl Alcohol | 1 | 2 | 1 | 1 | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 2 |
| High Viscosity Lubricant, U4 | 2 | 1 | - | - | - | - | 1 | - | - | - | - | - | - | - |
| High Viscosity Lubricant, H2 | 2 | 1 | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Hilo MS #1 | X | X | - | - | - | - | - | - | - | - | - | - | - | - |
| Houghto-Safe 1010,1055 (Phos. Ester) | X | X | X | 1 | X | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Houghto-Safe 1115, 1120, 1130 (Phos. Ester) | X | X | X | 1 | X | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Houghto-Safe 271, 416, 520, 616 (Water/Glycol) | 2 | 1 | 1 | - | - | 2 | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Houghto-Safe 620, 625, 640, 525 (Water/Glycol) | 1 | 1 | 1 | - | - | 2 | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Houghto-Safe 5046, 5046W (Water/Oil Emulsion) | 2 | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Hy-Chock Oil | - | 1 | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | - | - |
| Hydrafluid 760, Texaco and Houghton | - | 1 | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | - | 1 |
| Hydrafluid AZR&O, A, B, AA, C | - | 1 | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | - | 1 |
| Hydrasol A | - | 1 | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | - | - |
| Hydraulic Fluid, Phosphate Ester Base | X | X | X | 1 | - | X | 1 | 1 | - | 1 | 1 | 1 | - | - |

# CHEMICAL RESISTANCE TABLE – CONTINUED

Rating Scale:
1 Excellent
2 Good resistance
X Not recommended
– Testing recommended
[ ] Cover stock rating only; Rating for tube stock "X"
* Use Gates fuel hose or contact Denver Product Application Department

| Chemical Name | Gates Hose Polymers: Polychloroprene | Nitrile, HNBR, or XTF | Nitrile + PVC | CPE | CSM | Urethane | PTFE | Nylon | MegaTuff | Couplings & Adapters: Carbon Steel | Stainless Steel 304 | Stainless Steel 316 | Aluminum | Brass |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Hydraulic Fluid, Std. Petroleum Oils | 2 | 1 | 2 | 1 | 2 | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Hydraulic Fluid, Water Glycol Base | 1 | 1 | 1 | - | - | 1 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Hydraulic Fluid HF - 18, HF - 20 | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Hydraulic Fluid HF - 31 | - | - | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Hydraulic Oils, Petroleum | 2 | 1 | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Hydraulic Oils, Synthetic | - | X | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Hydraulic Safety Fluid 200 & 300, Texaco | - | 1 | - | - | - | 1 | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Hydrazine | X | X | X | - | - | 2 | 1 | - | - | - | - | - | - | - |
| Hydro-Drive Oil, Houghton | - | 1 | - | - | - | 2 | 1 | - | - | - | - | - | - | - |
| Hydrobromic Acid | X | X | - | - | - | - | 1 | X | 1 | 1 | 1 | 1 | X | - |
| Hydrobromic Acid, 37% | X | X | X | 1 | 2 | X | 1 | X | 1 | 1 | 1 | 1 | X | - |
| Hydrochloric Acid | 2 | X | - | - | - | - | 1 | X | 1 | X | X | X | X | X |
| Hydrochloric Acid, 3 Molar | 2 | X | - | - | - | - | 1 | X | 1 | X | X | X | X | X |
| Hydrochloric Acid, Concentrated | X | X | - | - | - | - | 1 | X | 1 | X | X | X | X | X |
| Hydrochloric Acid, 15% | X | X | X | 1 | 2 | X | 1 | X | 1 | X | X | X | X | X |
| Hydrochloric Acid, 37% | X | - | X | 1 | 2 | X | 1 | X | 1 | X | X | X | X | X |
| Hydrocyanic Acid, 20% Under 100°F | X | X | X | - | 2 | X | 1 | 1 | 1 | X | 1 | 1 | 1 | X |
| Hydrocyanic Acid, 98% | - | - | - | - | - | - | 1 | - | 1 | - | - | - | - | - |
| Hydrofluoric Acid, 10% | 2 | 2 | X | 1 | 1 | X | 1 | X | 1 | X | X | X | X | X |
| Hydrofluoric Acid, 20% (Under 120°F) | 2 | X | X | 1 | 2 | X | 1 | X | 1 | X | X | X | X | X |
| Hydrofluoric Acid, 48% (Under 120°F) | 2 | X | X | 1 | 2 | X | 1 | X | 1 | X | X | X | X | X |
| Hydrofluoric Acid, 70% | - | X | X | - | 2 | X | 1 | X | X | X | X | X | X | X |
| Hydrofluoric Acid, Concentrated | X | X | X | 1 | 2 | X | 1 | X | X | X | X | X | X | X |
| Hydrofluoric Acid, Anhydrous | - | X | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Hydrofluosilicic | X | X | X | X | - | - | 1 | X | 1 | X | X | X | X | 1 |
| Hydrogen | 1 | 1 | - | 1 | - | - | 1 | - | X | X | X | X | 1 | - |
| Hydrogen Chloride Gas | - | - | - | 1 | - | - | 1 | - | - | - | 1 | 1 | - | - |
| Hydrogen Cyanide Gas | - | - | - | - | - | - | - | - | - | - | - | - | 1 | - |
| Hydrogen Fluoride (Under 100°F) | - | X | - | - | - | - | 1 | - | - | 2 | 2 | 1 | - | - |
| Hydrogen Peroxide, Dilute | 1 | 2 | - | - | - | - | 1 | 1 | 1 | 1 | - | 1 | - | X |
| Hydrogen Peroxide, 10% | X | 1 | X | 1 | 2 | X | 1 | X | 1 | X | 2 | 1 | 1 | X |
| Hydrogen Peroxide, 30% | X | 2 | X | 1 | 2 | X | 1 | X | 1 | X | 2 | 1 | 1 | X |
| Hydrogen Peroxide, 70% | X | X | X | 1 | - | X | 1 | X | 1 | X | 2 | 1 | 1 | X |
| Hydrogen Peroxide, 90% | X | X | - | - | - | - | 1 | - | 1 | X | 2 | 1 | - | X |
| Hydrogen Sulfide | 2 | X | - | - | - | - | 1 | 1 | X | 2 | 2 | 1 | - | X |
| Hydrogen Sulfide Aqueous Solution | 2 | X | - | - | - | - | 1 | - | - | X | - | - | X | - |
| Hydrogen Sulfide, Gas | - | - | - | - | - | - | - | - | X | - | - | - | - | - |
| Hydrolube, Water Glycol | 2 | 1 | - | - | - | X | 1 | - | 1 | 1 | 1 | 1 | - | 1 |
| Hydrolubric Oil, Houghton | - | 2 | - | - | - | 2 | 1 | 1 | - | - | - | - | - | - |
| Hydroquinone | X | - | - | - | X | - | 1 | - | - | - | 1 | 1 | 2 | - |
| Hykil No.6 (33%); Water (67%) | - | 2 | - | - | - | - | 1 | - | - | 1 | - | - | - | - |
| Hypochlorous Acid (Under 120°F) | X | X | X | - | 2 | - | 1 | 1 | 1 | 2 | 2 | 2 | X | - |
| Hypoid Grease (Parapoid 10-C) | - | 1 | - | - | - | - | 1 | - | - | - | - | - | - | - |
| **I** | | | | | | | | | | | | | | |
| Imol, Imol S150, S220, S300, S500 | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | - |
| Industron 53 | - | 1 | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Ink (Printers) | 1 | 1 | - | - | - | - | 1 | 1 | - | 2 | 2 | 1 | - | 2 |
| Ink Oil | - | 2 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | - | 1 |
| Insulating Oil (Transformer) | 2 | 1 | 2 | - | X | - | 1 | - | - | 1 | 1 | 1 | - | 1 |
| Isobutyl Alcohol | 2 | 2 | 2 | 1 | - | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 |
| Iodine (Under 100°F) | X | X | - | 1 | 2 | X | 1 | 1 | - | 2 | 2 | 2 | X | - |
| Iodine, In Alcohol | 2 | - | - | - | - | X | 1 | - | 1 | - | - | - | X | - |
| Iodine Pentafluoride | X | X | - | - | - | - | 1 | - | - | X | 2 | 2 | X | - |
| Isooctane | 1 | 1 | 2 | 2 | 1 | 2 | 1 | 1 | - | 1 | 1 | 1 | 2 | 1 |
| Isooctyl Thioglucolate | - | - | - | - | - | - | 1 | 1 | - | - | - | - | - | - |
| Isobutane - WET | X | X | - | - | - | X | 1 | X | - | X | 1 | 1 | 2 | 1 |
| Isopropyl Acetate | X | X | X | - | X | 2 | 1 | 1 | 1 | 2 | 2 | 1 | X | 1 |
| Isopropyl Alcohol (Isopropanol) | 2 | 2 | 2 | 1 | 2 | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 |
| Isopropyl Ether | X | X | X | - | - | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| **J** | | | | | | | | | | | | | | |
| Fuel JP-3 (Under 100°F) | [2] | 1 | [2] | - | X | 2 | 1 | 1 | - | 1 | 1 | 1 | 2 | 1 |
| Jet Fuel JP-4 (Under 100°F) | [X] | 1 | [2] | - | X | - | 1 | 1 | - | 1 | 1 | 1 | 2 | 1 |
| Jet Fuel JP-5 | X | 1 | X | - | X | - | 1 | 1 | - | 2 | 1 | 1 | 2 | 1 |
| Jet Fuel JP-6 | X | 1 | X | - | X | - | 1 | 1 | - | 2 | 1 | 1 | 2 | 1 |
| Jet Fuel JP-x | 2 | 1 | X | - | X | - | 1 | 1 | - | 2 | 1 | 1 | 2 | 1 |
| **K** | | | | | | | | | | | | | | |
| Kerosene | X | 1 | [2] | 1 | X | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Ketchup | 1 | 1 | - | - | - | - | 1 | 1 | - | - | 1 | 1 | - | - |
| Ketones | X | X | X | - | X | X | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 1 |
| **L** | | | | | | | | | | | | | | |
| Lacquer Solvents | X | X | X | - | X | 2 | 1 | 1 | 1 | X | 2 | 1 | 1 | 1 |
| Lacquers | X | X | X | - | X | - | 1 | 1 | - | X | X | 1 | 1 | 1 |
| Lactic Acid | 1 | X | X | - | 1 | X | 1 | - | 1 | X | 2 | 1 | X | 2 |
| Lactic Acid (5%) | 2 | 1 | - | - | - | - | 1 | 1 | 1 | X | 2 | 1 | 1 | X |
| Lactic Acid (5% Boiling) | X | X | - | - | - | - | 1 | - | - | X | 2 | 1 | 2 | X |
| Lactic Acid (10% Boiling) | X | X | - | - | - | - | 1 | - | - | X | 2 | 1 | X | X |
| Lactol | 2 | 2 | 2 | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Lard | 2 | 1 | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | X |
| Lasso (Ag Spray) | - | - | - | - | - | - | 1 | 1 | - | - | 1 | 1 | - | - |
| Latex | 1 | 1 | - | - | X | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Lead Acetate | X | X | - | 1 | 2 | 1 | 1 | - | - | 2 | 2 | 2 | X | 1 |
| Lead Arsenate | 2 | 2 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | - | - |
| Lead Nitrate | 2 | 2 | - | - | 1 | 1 | 1 | - | 1 | 1 | 2 | 2 | - | - |
| Lead Sulfate | 1 | 1 | - | 1 | 2 | - | 1 | - | - | 1 | 1 | 1 | - | - |
| Lead, Tetraethyl (Under 100°F) | X | 2 | X | - | X | - | 1 | 2 | - | - | - | - | - | - |
| Lead, Tetramethyl | X | 2 | X | - | X | 1 | 1 | - | - | - | - | - | - | - |
| Lecithin | 2 | X | - | - | - | - | 1 | - | - | - | 1 | 1 | - | - |
| Ligroin (Petroleum Ether, Under 120°F) | X | 1 | - | - | X | - | 1 | - | - | 2 | 1 | 1 | X | - |
| Lime (Chlorinated, Free Chlorine 20%) | - | 1 | - | 1 | - | 1 | - | - | 1 | - | - | 2 | - | - |
| Lime Bleach (Under 100°F) | X | 2 | X | - | X | - | - | - | - | X | 2 | 1 | - | - |
| Lime Sulphur | 1 | X | - | - | - | - | 2 | 1 | 1 | 2 | 1 | 1 | X | X |
| Lime Sulfur (Under 135°F) | 1 | X | X | - | 2 | - | 2 | 1 | 1 | 2 | 1 | 1 | X | X |
| Lindane (Ag Spray) | - | - | - | - | - | - | 1 | 1 | - | - | 1 | 1 | - | - |
| Linoleic Acid | X | 2 | X | - | - | - | 1 | - | 1 | X | 2 | 1 | 1 | - |
| Linseed Oil | X | 1 | - | - | - | - | 1 | 1 | X | 1 | 1 | 1 | 2 | 2 |
| Linseed Oil (Boiled) | 2 | 2 | 1 | 1 | 1 | 1 | 1 | - | - | 2 | 1 | 1 | 1 | 2 |
| Lubricating Oil (SAE 10, 20, 30, 40, 50) | 2 | 2 | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Lubricating Oils (Diester, Under 135°F) | X | 2 | X | - | - | X | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| **M** | | | | | | | | | | | | | | |
| Machine Oil (Under 135°F) | 1 | 1 | 2 | - | 2 | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Magnesium Carbonate | 1 | 1 | 1 | - | 1 | 1 | 1 | - | - | 2 | 2 | 2 | 1 | - |
| Magnesium Chloride | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | X | 2 | 1 | X | 2 |
| Magnesium Hydroxide | 2 | 2 | 2 | 1 | 1 | X | 1 | - | - | 1 | 1 | 1 | X | X |
| Magnesium Nitrate | 2 | 2 | 2 | - | 1 | - | 1 | - | - | 2 | 2 | 2 | X | 1 |

**Nitrile 150°F or less, no constant contact.

Rating Scale:
1 Excellent
2 Good resistance
X Not recommended
– Testing recommended
[ ] Cover stock rating only; Rating for tube stock "X"
* Use Gates fuel hose or contact Denver Product Application Department

| Chemical Name | Gates Hose Polymers: Polychloroprene | Nitrile, HNBR, or XTF | Nitrile + PVC | CPE | CSM | Urethane | PTFE | Nylon | MegaTuff | Couplings & Adapters: Carbon Steel | Stainless Steel 304 | Stainless Steel 316 | Aluminum | Brass |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Magnesium Sulfate | 2 | 2 | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 2 | 2 | 2 | 2 |
| Malathion (Ag Spray Dilute) | - | 2 | - | - | - | - | 1 | 1 | 1 | 1 | 1 | 1 | - | 1 |
| Maleic Acid | 2 | X | - | - | - | - | 1 | - | 1 | 2 | 2 | 1 | - | - |
| Malic Acid | - | - | - | - | - | - | 1 | - | 1 | 2 | 2 | 1 | - | - |
| Manganese Salts | - | 1 | 1 | - | 1 | - | 1 | - | - | - | - | - | - | - |
| Maxmul (Penzoil Hydraulic Fluid) | 2 | 1 | 2 | - | - | - | 1 | - | - | 1 | - | 1 | - | - |
| Mercuric Chloride | 1 | 2 | 2 | 1 | 1 | 2 | 1 | X | - | X | 1 | 1 | X | X |
| Mercuric Cyanide | 1 | 2 | 2 | - | 1 | - | - | - | - | 2 | 2 | 2 | X | - |
| Mercurous Nitrate (Under 120°F) | 1 | 2 | 2 | - | 1 | - | 1 | - | 1 | 1 | 1 | 1 | X | - |
| Mercury | 1 | 2 | 2 | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 | 1 | X | X |
| Mesityl Oxide | X | X | X | 2 | X | X | 1 | - | 1 | 1 | 1 | 1 | 1 | 1 |
| Methane | 2 | 1 | - | - | - | - | 1 | - | - | - | 1 | 1 | - | - |
| Methoxychlor (Insecticide) | - | - | - | - | - | - | 1 | X | - | 1 | 1 | 1 | - | - |
| Methyl Acetate | X | X | X | 1 | X | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Methyl Acrylate | X | X | X | - | X | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Methyl Alcohol | 1 | 1 | 1 | 1 | - | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 |
| Methyl Amine (25% Aqueous Solution) | 2 | X | - | - | - | - | 1 | - | 1 | 1 | 1 | 1 | 1 | - |
| Methyl Amine (60%) | 2 | 2 | - | - | - | - | 1 | 2 | 1 | 1 | 1 | 1 | 1 | 2 |
| Methyl Amine (99%) | X | X | - | - | - | - | 1 | - | 1 | 1 | 1 | 1 | 1 | X |
| Methyl Bromide | X | X | X | - | X | X | 1 | 1 | - | 1 | 1 | 1 | X | 1 |
| Methyl Butyl Ketone (MBK) | X | X | X | 2 | X | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Methyl Cellosolve (Under 100°F) | 2 | X | - | 1 | X | - | 1 | - | - | 2 | 2 | 2 | 2 | 1 |
| Methyl Chloride | X | X | X | X | X | - | 1 | 1 | - | 1 | 1 | 1 | - | 1 |
| Methyl Ethyl Ketone (MEK) | X | X | X | 2 | X | X | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 1 |
| Methyl Formate | 2 | X | X | - | X | - | 1 | - | - | 2 | 1 | 1 | 1 | 1 |
| Methyl Isobutyl Ketone (MIBK, 100°F) | X | X | X | 2 | X | X | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Methyl Isopropyl Ketone | X | X | X | 2 | X | X | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Methyl Methacrylate | X | X | X | 2 | 2 | - | 1 | - | - | 2 | 2 | 2 | - | - |
| Methyl Salicylate | 2 | 2 | 2 | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Methyl Sulfate (Dimethyl, Under 100°F) | X | X | X | - | X | 1 | 1 | 1 | - | 1 | 1 | 1 | - | - |
| Methylene Chloride | X | X | X | X | X | - | 1 | X | 2 | 1 | 1 | 1 | X | 1 |
| Methylene Dichloride | X | X | X | - | - | - | 1 | 1 | - | 1 | 1 | 1 | X | 1 |
| Mineral Oil (Under 120°F) | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 1 |
| Mineral Spirits | - | 1 | 2 | - | X | - | 1 | - | - | 1 | 1 | 1 | 2 | 1 |
| Mobile Therm 603 | - | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Molasses (Under 120°F) | 2 | 2 | 2 | - | 1 | 1 | 1 | - | - | 2 | 1 | 1 | 2 | X |
| Monochlorobenzene | X | X | X | X | X | X | 1 | - | - | 1 | 1 | 1 | X | 1 |
| Monoethanolamine | X | 2 | - | 1 | X | - | 1 | - | 1 | 1 | 1 | 1 | 2 | 1 |
| Morpholine (Pure Additive) | - | - | - | - | - | - | 1 | - | - | - | 1 | 1 | - | - |
| Motor Oils (Under 135°F) | 2 | 1 | 2 | 1 | 2 | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Mould Oil | - | - | - | - | - | - | 1 | - | * | 1 | 1 | 1 | - | - |
| Muriatic Acid (Hydrochloric) | X | X | X | 1 | 2 | X | 1 | X | 1 | X | X | X | X | X |
| Mustard | 1 | 2 | 1 | - | 1 | - | 1 | - | - | X | 1 | 1 | 2 | - |
| **N** | | | | | | | | | | | | | | |
| Naphtha (Low Aromatic Content) | X | 2 | X | 1 | X | - | 1 | 1 | - | 2 | 1 | 1 | 1 | 1 |
| Naphthalene (Tar Camphor) | X | X | X | 1 | X | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Naphthalene | X | X | X | - | X | - | 1 | - | - | 1 | 1 | 1 | - | 1 |
| Naphthenic Acid | - | 2 | - | - | - | - | 1 | - | - | - | 2 | 1 | - | - |
| Natural Gas | - | - | - | - | - | - | 1 | - | X | 1 | 1 | 1 | - | 2 |
| Nickel Acetate solution (in water or alcohol) | - | - | - | - | - | - | 1 | - | 1 | 1 | 1 | 1 | 1 | 1 |
| Nickel Chloride | 2 | 2 | 2 | 1 | 2 | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Nickel Nitrate | 2 | 2 | 2 | 1 | 2 | - | 1 | 1 | - | 2 | 2 | 2 | X | - |
| Nickel Plating Solution | - | 2 | - | - | 2 | X | 1 | - | - | - | 1 | 1 | - | - |
| Nickel Salts | 2 | - | 1 | - | - | - | 1 | - | - | - | - | - | - | - |
| Nicotine Salts | - | - | - | - | - | 1 | 1 | - | - | 1 | X | 2 | - | - |
| Nitric Acid | X | X | - | - | - | - | 1 | - | - | X | 1 | 1 | - | X |
| Nitric Acid, 3 Molar | X | X | - | - | - | - | 1 | - | 1 | X | 1 | 1 | - | X |
| Nitric Acid, Concentrated (Boiling) | X | X | - | - | - | - | 1 | X | X | X | 2 | 2 | X | X |
| Nitric Acid, Inhibited Red Fuming (IRFNA) | X | X | - | - | - | - | 1 | - | X | X | 1 | 1 | 1 | X |
| Nitric Acid, Red Fuming (RNFA) | X | X | X | - | X | X | 1 | X | X | X | 2 | 2 | 2 | X |
| Nitric Acid, 5% To 10% | X | X | X | 1 | 2 | X | 1 | X | 1 | X | 2 | 2 | 1 | X |
| Nitric Acid, 20% | X | X | X | 1 | 2 | X | 1 | X | 1 | X | 2 | 2 | X | X |
| Nitric Acid, 50% (Boiling) | X | X | X | X | X | X | 1 | X | X | X | 2 | 2 | X | X |
| Nitric Acid, 65% (Boiling) | X | X | X | X | X | X | 1 | X | X | X | 2 | 2 | X | X |
| Nitric Acid & Hydrochloric Acid | - | X | - | - | - | - | 1 | - | X | X | X | X | X | – |
| Nitrobenzene (Under 100°F) | X | X | X | 2 | X | X | 1 | 2 | - | 1 | 1 | 1 | 1 | 1 |
| Nitroethane | X | X | X | 1 | 2 | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Nitrogen | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 | X | 1 | 1 | 1 | 1 | 1 |
| Nitrogen Oxide Up To 50% (Under 100°F) | 1 | 1 | 2 | 1 | 1 | - | 1 | 1 | - | 1 | 1 | 1 | - | X |
| Nitromethane | X | X | X | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Nitropropane | X | X | X | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Nyvac 20 (WG), 30 (WG) | - | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Nyvac FR Fluid | - | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Nyvac FR200 Fluid | - | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| N-Octane | X | 2 | - | 1 | X | - | - | - | - | 1 | 1 | 1 | - | 1 |
| **O** | | | | | | | | | | | | | | |
| Octyl Alcohol | 2 | 2 | 2 | 1 | - | - | 1 | 1 | - | 1 | 1 | 1 | - | 2 |
| Oils, Crude | X | 2 | - | - | - | - | 1 | - | - | 1 | - | - | - | - |
| Oil (SAE, Under 100°F) | 1 | 1 | 1 | 1 | 2 | 1 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Oleic Acid (Under 120°F) | 2 | 2 | 2 | 1 | 2 | 1 | 1 | - | 2 | 2 | 2 | 1 | 1 | 2 |
| Oleum | X | X | X | X | X | - | 1 | X | X | - | - | 1 | - | - |
| Olive Oil | X | 2 | 2 | 2 | X | - | 1 | - | 1 | 2 | 1 | 1 | 1 | 2 |
| OS 45 Type III (OS45) | 1 | 2 | - | - | - | - | 1 | - | - | - | - | - | - | - |
| OS 45 Type IV (OS45-1) | 1 | 2 | - | - | - | - | 1 | - | - | - | - | - | - | - |
| OS 70 | 1 | 2 | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Oxalic Acid (5%, Hot And Cold) | 2 | 2 | - | - | - | - | 1 | 2 | - | X | 2 | 1 | 1 | X |
| Oxalic Acid (10%) | 2 | 2 | - | - | - | - | 1 | 2 | 1 | X | 2 | 1 | 1 | X |
| Oxalic Acid (10% Boiling) | X | X | - | - | - | - | 1 | - | - | X | X | X | X | X |
| Oxalic Acid | X | X | X | 1 | 2 | X | 1 | X | - | X | 2 | 1 | 2 | X |
| Oxygen, Gaseous | - | - | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Ozone (Dry) | 2 | X | 2 | 1 | 2 | 1 | 1 | 2 | 2 | 1 | 1 | 1 | 1 | 1 |
| Ozone (Wet) | - | X | - | - | - | - | 1 | - | 2 | X | 2 | 1 | 2 | - |
| **P** | | | | | | | | | | | | | | |
| Paint | X | - | - | - | X | X | 1 | 2 | 1 | - | 1 | 1 | 1 | 1 |
| Paint Solvents (Oil Base) | X | X | - | - | X | X | 1 | 2 | - | - | 1 | 1 | 1 | 1 |
| Paints (Oil Base) | - | 1 | - | - | 1 | - | 1 | 1 | - | - | - | - | - | - |
| Paint Thinner, Duco | 2 | 1 | - | - | - | - | 1 | 1 | - | 2 | 2 | 1 | 2 | X |
| Palmetic Acid | 2 | 2 | 2 | 1 | X | 1 | 1 | 1 | 1 | 2 | 2 | 1 | 1 | X |
| Palm Oil | 2 | 1 | 2 | - | 2 | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Paraffin (Petroleum) | 2 | 1 | 2 | 1 | X | - | 1 | 1 | 1 | 2 | 1 | 1 | 1 | 1 |
| Paraformaldehyde | 2 | 2 | 2 | - | 2 | 2 | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Peanut Oil (Less Than 100°F) | 2 | 1 | 2 | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Pentasol | 2 | 2 | 2 | - | 2 | - | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 |
| Perchloric Acid | X | X | - | - | 2 | X | 1 | X | 1 | X | 2 | 1 | X | - |
| Perchloroethylene (Tetrachloroethylene) | X | X | X | 2 | X | - | 1 | 2 | 1 | 1 | 1 | 1 | X | X |
| Petroleum Ether | X | 2 | - | 1 | - | - | 1 | - | - | 2 | 1 | 1 | - | 1 |
| Petroleum Oil (Crude) | 2 | 1 | - | - | - | - | 1 | - | 1 | - | - | - | - | - |
| Petroleum Oil (Below 250°F) | 2 | 1 | - | - | - | - | 1 | - | X | - | - | - | - | - |

**Nitrile 150°F or less, no constant contact.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# CHEMICAL RESISTANCE TABLE – CONTINUED

Rating Scale:
1 Excellent
2 Good resistance
X Not recommended
– Testing recommended
[ ] Cover stock rating only; Rating for tube stock "X"
* Use Gates fuel hose or contact Denver Product Application Department

| Chemical Name | Gates Hose Polymers: Polychloroprene | Nitrile, HNBR, or XTF | Nitrile + PVC | CPE | CSM | Urethane | PTFE | Nylon | MegaTuff | Couplings & Adapters: Carbon Steel | Stainless Steel 304 | Stainless Steel 316 | Aluminum | Brass |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Petroleum Oil (Above 250°F) | X | X | - | - | - | - | 1 | - | X | - | - | - | - | - |
| Petroleum Oils (Under 100°F) | 2 | 1 | 2 | - | 2 | 2 | 1 | - | 1 | 1 | 1 | 1 | 1 | 1 |
| Petroleum Oils (Refined) | 2 | 1 | 2 | - | 2 | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Petroleum Oils (Sour) | 2 | 2 | - | - | X | 2 | 1 | - | 1 | 2 | 1 | 1 | 1 | X |
| Phenol (Carbolic Acid) | X | X | X | 1 | X | X | 1 | X | - | 2 | 1 | 1 | 1 | X |
| Phenol (70/30 Water) | X | X | - | - | - | - | 1 | - | - | - | 1 | 1 | 1 | - |
| Phenol (85/15 Water) | X | X | - | - | - | - | 1 | - | - | - | 1 | 1 | 1 | - |
| Phorone (Diisopropylidene Acetone) | X | X | - | - | X | X | 1 | - | - | 1 | 1 | 1 | - | 1 |
| Phosphate Esters (Concentrated) | X | X | - | X | X | X | 1 | 2 | 1 | - | - | - | - | - |
| Phosphate Esters (3 Molar) | X | X | - | 2 | 2 | X | 1 | 2 | 1 | - | - | - | - | - |
| Phosphate Esters (Dilute) | X | X | - | 1 | 1 | X | 1 | 2 | 1 | - | - | - | - | - |
| Phosphoric Acid | 2 | 2 | - | - | - | - | 1 | - | 1 | - | - | 2 | - | - |
| Phosphoric Acid (3 Molar) | X | X | - | - | - | - | 1 | - | 1 | - | - | - | - | - |
| Phosphoric Acid (Concentrated) | X | X | - | - | - | - | 1 | - | 2 | - | - | - | - | - |
| Phosphoric Acid (1%) | 2 | - | - | - | - | - | 1 | - | 1 | - | 1 | 1 | - | X |
| Phosphoric Acid (5%) | 2 | X | - | - | - | - | 1 | - | 1 | - | 1 | 1 | - | X |
| Phosphoric Acid (10%) | 2 | X | - | - | - | - | 1 | - | 1 | X | - | 1 | X | X |
| Phosphoric Acid (10% Hot) | 2 | X | - | - | - | - | 1 | - | - | X | - | 1 | X | X |
| Phosphoric Acid (50%) | 2 | 2 | 2 | 1 | 1 | X | 1 | X | 1 | X | 2 | 1 | X | 2 |
| Phosphoric Acid (50% Hot) | 2 | X | - | - | - | - | 1 | - | - | X | X | 2 | X | X |
| Phosphoric Acid (85%) | 2 | X | - | 1 | 1 | X | 1 | X | 1 | X | 2 | 2 | X | X |
| Phosphoric Acid (85% Hot) | 2 | X | - | - | - | - | 1 | - | - | X | X | X | X | X |
| Phosphoric Acid (Aerated) | - | - | - | - | - | - | 1 | - | - | X | - | 2 | - | - |
| Phosphoric Acid Air Free | - | - | - | - | - | - | 1 | - | 1 | X | - | - | X | - |
| Photographic Developers | 1 | 1 | - | - | - | - | 1 | - | - | X | 1 | 1 | - | - |
| Photographic, Emulsions | - | - | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Photographic, Fixing Solutions | 2 | - | - | - | 2 | - | 1 | - | - | - | 1 | 1 | - | - |
| Phthalic Acid | - | - | - | - | - | - | - | - | - | 2 | 2 | 1 | 2 | - |
| Picric Acid (Water Solution 100°F) | 2 | 2 | 2 | - | 2 | - | 1 | X | 2 | X | 1 | 1 | X | X |
| Pinene | X | 2 | - | 2 | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Pine Oil | X | 2 | - | 2 | X | - | 1 | 1 | - | 1 | 1 | 1 | 1 | - |
| Piperazine Hydrochloride Solution (34%) | - | 2 | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Pitch | 2 | 1 | - | - | 2 | 2 | 1 | 1 | X | - | - | - | - | - |
| Plating Solutions (Chrome) | X | X | - | - | - | X | 1 | X | - | - | X | X | - | - |
| Plating Solutions (Other) | - | 1 | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Polyester Resin | - | - | - | - | - | - | - | 2 | - | - | - | - | - | - |
| Polyurethane Foam (Under 125°F) | - | - | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Potassium Acetate | 2 | 2 | - | 1 | 2 | X | 1 | - | - | 2 | 1 | 1 | X | - |
| Potassium Bicarbonate | 1 | 1 | - | - | 1 | - | 1 | 1 | - | 1 | 2 | 2 | 1 | - |
| Potassium Bisulfite | - | 1 | - | - | - | - | 1 | 1 | - | - | - | - | - | - |
| Potassium Bromate | - | - | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Potassium Bromide | 1 | 1 | - | - | 1 | 2 | 1 | 1 | - | X | X | 2 | X | - |
| Potassium Carbonate (Potash) | 1 | 1 | 1 | 1 | 1 | 2 | 1 | 1 | - | 2 | 1 | 1 | X | X |
| Potassium Chlorate | 1 | 1 | - | - | - | 2 | 1 | 1 | - | 2 | 2 | 2 | 2 | - |
| Potassium Chloride (1% To 5%) | 1 | 1 | - | 1 | - | 2 | 1 | 1 | 1 | 1 | 2 | 2 | X | X |
| Potassium Chloride (Boiling) | - | - | - | - | - | - | 1 | - | X | - | 2 | 2 | - | X |
| Potassium Cyanide | 1 | 1 | - | 1 | - | - | 1 | 1 | - | 2 | 1 | 1 | X | X |
| Potassium Dichromate | 1 | 1 | - | 1 | - | - | 1 | 2 | - | 1 | 2 | 2 | 2 | - |
| Potassium Ferrocyanide | - | - | - | - | - | - | 1 | - | - | 2 | 1 | 1 | 2 | - |
| Potassium Fluoride | - | - | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Potassium Hydroxide | 2 | 2 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | - | - |
| Potassium Hydroxide (5%) | 1 | 1 | - | - | - | - | 1 | 1 | 1 | 2 | 2 | 2 | X | X |
| Potassium Hydroxide (27% Boiling) | - | - | - | - | - | - | 1 | - | X | 2 | 2 | 1 | X | X |

**Nitrile 150°F or less, no constant contact.

| Chemical Name | Gates Hose Polymers: Polychloroprene | Nitrile, HNBR, or XTF | Nitrile + PVC | CPE | CSM | Urethane | PTFE | Nylon | MegaTuff | Couplings & Adapters: Carbon Steel | Stainless Steel 304 | Stainless Steel 316 | Aluminum | Brass |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Potassium Hydroxide (30%, Caustic Potash) | - | - | - | 1 | - | - | 1 | - | - | - | - | - | - | - |
| Potassium Hydroxide (50% Boiling) | - | - | - | - | - | - | 1 | - | X | 2 | 2 | 2 | X | X |
| Potassium Hydroxide (70%) | - | 1 | - | - | - | - | 1 | - | - | - | - | - | X | X |
| Potassium Hydroxide (70% Hot) | - | - | - | - | - | - | 1 | - | X | X | - | - | X | X |
| Potassium Iodide | 1 | 1 | - | - | 1 | - | 1 | 1 | - | 1 | 2 | 2 | - | - |
| Potassium Nitrate | 1 | 1 | - | 1 | - | 1 | 1 | 1 | - | 1 | 1 | 2 | 2 | 2 |
| Potassium Nitrate (1% To 5%) | 1 | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 2 |
| Potassium Permanganate | 1 | 2 | - | - | - | - | 1 | 2 | - | 1 | 2 | 2 | 2 | - |
| Potassium Permanganate (5%) | 1 | 1 | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | - |
| Potassium Persulfate | - | - | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Potassium Phosphate | 1 | - | - | - | 1 | - | 1 | - | - | X | 2 | 2 | X | - |
| Potassium Sulfate | 1 | 1 | - | 1 | - | 1 | 1 | 1 | - | 1 | 2 | 2 | 1 | - |
| Potassium Sulfate - 1% & 5% | 1 | 1 | - | - | - | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | X |
| Potassium Sulfide | 1 | 1 | - | - | - | - | 1 | - | - | 2 | 2 | 2 | - | - |
| Potassium Sulfite | 1 | 1 | - | 1 | - | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Potassium Thiosulfate | 1 | - | - | - | 1 | - | 1 | - | - | - | - | - | - | - |
| Primatol A, S, P (Ag Spray) | - | - | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Propane Gas | X | X | - | - | - | X | 1 | - | X | 1 | 1 | 1 | - | 1 |
| Propionic Acid | X | X | - | - | - | - | 1 | - | 1 | 1 | - | 2 | 2 | - |
| Propyl Acetate | X | X | - | 2 | - | - | 1 | - | 1 | 1 | - | - | - | - |
| Propyl Alcohol | 1 | 1 | 2 | 1 | - | X | 1 | 1 | 1 | 1 | 1 | 1 | - | 2 |
| Propylene (Liquid Or Gas, Ambient) | X | X | - | 1 | - | - | 1 | 2 | - | 1 | 1 | 1 | 1 | - |
| Propylene Dichloride | - | - | - | - | - | - | 1 | - | - | 1 | 2 | 1 | X | - |
| Propylene Glycol | 1 | 1 | - | 1 | 1 | 1 | 1 | 2 | 1 | 1 | 1 | 1 | - | - |
| Propylene Oxide | X | X | - | - | - | - | - | - | - | 2 | 1 | 1 | 2 | - |
| Purina Insecticide | X | X | - | - | - | - | 1 | 2 | - | 1 | 1 | 1 | 1 | 2 |
| Puropale RX Oils | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Pyranol, Transformer Oil | 2 | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Pydraul | X | X | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Pydraul 10E, 29E-LT, 30E, 60, 65E, 115E | X | X | - | 2 | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Pydraul 135 | - | X | - | 2 | - | - | 1 | 2 | - | 1 | 1 | 1 | - | - |
| Pydraul 150 | X | X | X | 2 | X | 2 | 1 | 2 | - | 1 | 1 | 1 | 1 | 1 |
| Pydraul 280 | X | X | X | 2 | X | 2 | 1 | 2 | - | 1 | 1 | 1 | - | - |
| Pydraul 312 | X | X | X | 2 | - | 2 | 1 | 1 | - | 1 | 1 | 1 | - | - |
| Pydraul 50E | - | - | - | 2 | - | 2 | 1 | 1 | - | 1 | 1 | 1 | - | - |
| Pydraul 540 | X | X | X | 2 | X | X | 1 | X | - | 1 | 1 | 1 | - | - |
| Pydraul 625 | X | X | X | 2 | X | 2 | 1 | 2 | - | 1 | 1 | 1 | - | - |
| Pydraul A-200 | X | X | X | 2 | X | X | 1 | 2 | - | 1 | 1 | 1 | - | - |
| Pydraul F-9 | X | X | X | 2 | X | 2 | 1 | 1 | - | 1 | 1 | 1 | - | - |
| Pyridine (50%) | X | X | - | - | X | 1 | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| Pyrogard 160, 230, 630 | - | - | - | - | - | - | 1 | - | - | 1 | 1 | 1 | - | - |
| Pyrogard 51, 53, 55 | - | X | - | - | - | - | 1 | - | - | 1 | 1 | 1 | - | - |
| Pyrogard C, D | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| **Q** | | | | | | | | | | | | | | |
| Quench Oil | 2 | 2 | - | - | - | - | 1 | - | - | - | 1 | 1 | 1 | - |
| Quintolubric 822 | 2 | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | 1 |
| **R** | | | | | | | | | | | | | | |
| Ramrod (Ag Spray) | - | - | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Rando Oils | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Rape Seed Oil | 2 | X | - | - | X | - | 1 | 2 | 1 | 1 | 1 | 1 | 1 | 1 |
| Red Oil (Comm. Oleic Acid, MIL-H-5606) | 2 | 2 | 2 | 1 | 2 | - | 1 | 1 | 2 | 2 | 2 | 1 | 1 | 2 |
| Refined Wax (Petroleum) | 2 | 1 | 2 | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | - | 1 |
| Regal Oils R&O | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Richfield Weed Killer | X | 2 | - | - | X | - | 1 | - | - | - | - | - | - | - |

Rating Scale:
1 Excellent
2 Good resistance
X Not recommended
– Testing recommended
[ ] Cover stock rating only; Rating for tube stock "X"
* Use Gates fuel hose or contact Denver Product Application Department

| Chemical Name | Gates Hose Polymers: Polychloroprene | Nitrile, HNBR, or XTF | Nitrile + PVC | CPE | CSM | Urethane | PTFE | Nylon | MegaTuff | Couplings & Adapters: Carbon Steel | Stainless Steel 304 | Stainless Steel 316 | Aluminum | Brass |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Round Up | 2 | 2 | - | - | - | - | 1 | 1 | - | 2 | 1 | 1 | 1 | 1 |
| RSC Futerra | - | - | 1 | - | - | - | - | - | - | - | - | - | - | - |
| RSC Envirologic 146 | - | - | 1 | - | - | - | - | - | - | - | - | - | - | - |
| Rubilene Oils | - | 1 | - | - | - | 2 | 1 | 1 | - | - | - | - | - | - |
| **S** | | | | | | | | | | | | | | |
| Salicylic Acid | 1 | X | - | - | - | - | 1 | 1 | 1 | 1 | 1 | 1 | 2 | - |
| Salt Water (Sea Water) | 2 | 2 | 2 | - | 2 | 1 | 1 | 1 | - | 2 | 1 | 1 | X | 2 |
| Santosafe W-G15, W-G20, W-G30 | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Santo Safe 300 | X | X | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Sevin | - | - | - | - | - | - | 1 | 1 | - | - | - | - | - | - |
| Sewage | 2 | 2 | 2 | 1 | 2 | - | 1 | 1 | 1 | X | 1 | 1 | 2 | 1 |
| SFR Fluid B (Shell) | - | X | - | - | - | - | 1 | - | - | - | - | - | - | - |
| SFR Fluid C (Shell) | - | X | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Shellac | 2 | 1 | - | - | - | - | 1 | 1 | X | 1 | 1 | 1 | 1 | - |
| Shellac (Bleached) | 2 | 1 | - | - | - | - | 1 | 1 | X | 1 | 1 | 1 | 1 | 2 |
| Shellac (Orange) | 2 | 1 | - | - | - | - | 1 | 1 | X | 1 | 1 | 1 | 1 | 2 |
| Silicone Greases | 2 | 2 | 2 | - | 2 | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Silicone Oils | 2 | 2 | 2 | - | 2 | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Silver Cyanide | 1 | - | - | - | - | - | 1 | - | - | 1 | 1 | 1 | X | - |
| Silver Nitrate | 1 | 1 | 1 | 1 | 1 | - | 1 | 1 | - | 2 | 1 | 1 | 1 | 2 |
| Skydrol 500A& 7000 | X | X | X | 2 | X | - | 1 | 1 | - | 1 | 1 | 1 | 1 | - |
| Soap Oil | X | X | - | - | X | - | 1 | - | 2 | 1 | 1 | 1 | - | - |
| Soap Solutions | 2 | 1 | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Soda Ash (Sodium Carbonate) | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | 1 | 1 | 1 | X | 2 |
| Soda Water | - | - | - | - | - | 1 | 1 | 1 | - | - | - | - | - | - |
| Sodium Acetate | X | X | X | 1 | X | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Sodium Benzoate | - | - | - | - | - | 1 | 1 | - | - | - | - | - | - | - |
| Sodium Bicarbonate | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | 2 | 1 | 1 | 2 | 2 |
| Sodium Bisulfate (Niter Cake) | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | X | 2 | 1 | X | X |
| Sodium Bisulfite | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | 2 | 1 | 1 | 2 | - |
| Sodium Borate | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | 1 | 1 | 1 | - | - |
| Sodium Carbonate | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | 2 | 2 | 2 | X | 2 |
| Sodium Chlorate | 2 | 1 | - | - | 1 | 1 | 1 | 1 | - | 2 | 2 | 2 | X | - |
| Sodium Chloride | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 2 | 1 | X | X |
| Sodium Chloride - 2% | 1 | 1 | - | - | - | - | 1 | 1 | 1 | 2 | 2 | 1 | X | X |
| Sodium Chloride - 5% | 1 | 1 | - | - | - | - | 1 | 1 | 1 | - | 2 | 1 | X | X |
| Sodium Chloride - 5% @ 150°F | 1 | 1 | - | - | - | - | 1 | 1 | 1 | - | 2 | 1 | - | X |
| Sodium Chloride Saturated | 1 | 1 | - | - | - | - | 1 | 1 | 1 | - | 1 | 1 | X | - |
| Sodium Chloride Saturated (Boiling) | - | - | - | - | - | - | 1 | - | X | - | 2 | 1 | X | - |
| Sodium Chloride Slurry | - | - | - | - | - | - | 1 | - | 1 | - | - | - | - | - |
| Sodium Cyanide | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | 2 | 1 | 1 | X | X |
| Sodium Dichromate | 2 | 1 | - | 1 | 2 | 1 | 1 | 1 | - | - | - | - | - | - |
| Sodium Ferricyanide | - | - | - | - | - | - | 1 | - | - | 2 | 2 | 2 | - | - |
| Sodium Ferrocyanide | - | - | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Sodium Fluoride | - | 1 | - | - | - | - | 1 | - | 1 | 2 | 2 | 2 | - | - |
| Sodium Fluoride (5%) | - | 1 | - | - | - | - | 1 | 1 | 1 | 2 | 2 | 2 | - | - |
| Sodium Fluoride (70%) | - | - | - | - | - | - | 1 | - | 1 | - | - | 2 | - | - |
| Sodium Hydrosulfide | 1 | X | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Sodium Hydrosulfite | - | - | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Sodium Hydroxide | 2 | 2 | - | - | - | - | 1 | - | - | 2 | - | - | - | X |
| Sodium Hydroxide (3 Molar) | 2 | 2 | - | - | - | - | 1 | - | 1 | - | - | - | - | X |
| Sodium Hydroxide (10%) | - | - | - | 1 | - | - | 1 | - | 1 | - | - | - | - | - |
| Sodium Hydroxide (20% Cold) | 1 | 2 | - | - | - | - | 1 | 1 | 1 | 1 | 1 | 1 | X | X |
| Sodium Hydroxide (20% Hot) | 1 | X | - | - | - | - | 1 | - | - | 2 | 1 | 1 | X | X |
| Sodium Hydroxide (40%) | 1 | 2 | 2 | 1 | 1 | - | 1 | 2 | 1 | 2 | 1 | 1 | X | X |
| Sodium Hydroxide (50% Cold) | 2 | X | X | 1 | 1 | - | 1 | 2 | 1 | 2 | 2 | 2 | X | X |
| Sodium Hydroxide (50% Hot) | - | - | - | 1 | 2 | - | 1 | X | - | X | 2 | 2 | X | X |
| Sodium Hydroxide (60%) | 2 | X | X | 1 | 2 | - | 1 | X | 2 | X | 2 | 2 | X | X |

**Nitrile 150°F or less, no constant contact.

Rating Scale:
1 Excellent
2 Good resistance
X Not recommended
– Testing recommended
[ ] Cover stock rating only; Rating for tube stock "X"
* Use Gates fuel hose or contact Denver Product Application Department

| Chemical Name | Gates Hose Polymers: Polychloroprene | Nitrile, HNBR, or XTF | Nitrile + PVC | CPE | CSM | Urethane | PTFE | Nylon | MegaTuff | Couplings & Adapters: Carbon Steel | Stainless Steel 304 | Stainless Steel 316 | Aluminum | Brass |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Sodium Hydroxide (70% Cold) | 1 | 2 | - | - | - | - | 1 | - | 2 | - | - | 2 | X | X |
| Sodium Hydroxide (70% Hot) | - | - | - | - | - | - | 1 | - | X | - | - | - | - | - |
| Sodium Hydroxide (80% Hot) | 1 | X | - | - | - | - | 1 | - | X | X | X | X | X | X |
| Sodium Hypochlorite | 1 | X | - | - | - | - | 1 | - | 1 | X | X | X | X | - |
| Sodium Hypochlorite, 5% | - | X | X | 1 | 1 | X | 1 | 1 | 1 | X | X | 2 | X | X |
| Sodium Hypochlorite, 20% | X | X | X | 1 | 1 | X | 1 | 2 | 1 | X | X | 2 | X | X |
| Sodium Hyposulfate | X | - | - | - | - | - | 1 | - | - | X | 1 | 1 | X | - |
| Sodium Metaphosphate | 2 | 2 | 2 | 1 | 2 | - | 1 | 1 | - | X | 1 | 1 | 1 | X |
| Sodium Nitrate | X | X | - | 1 | 2 | 1 | 1 | 1 | - | 1 | 2 | 2 | 2 | 2 |
| Sodium Perborate | X | X | - | - | X | - | 1 | 2 | - | X | 1 | 1 | 1 | X |
| Sodium Peroxide (Sodium Dioxide) | 1 | 2 | 1 | 2 | 1 | - | 1 | X | 2 | X | 1 | 1 | 1 | X |
| Sodium Phosphate | X | 1 | - | 1 | - | 1 | 1 | 1 | - | 2 | 1 | 1 | X | X |
| Sodium Phosphate (Mono) | 1 | 1 | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Sodium Phosphate (Dibasic) | 2 | 1 | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Sodium Phosphate (Tribasic) | 2 | 1 | - | - | - | - | 1 | - | - | 2 | 2 | 2 | - | - |
| Sodium Silicate | 1 | 1 | - | 1 | 1 | 2 | 1 | 1 | - | 1 | 1 | 1 | - | 1 |
| Sodium Silicate (Hot) | 1 | 1 | - | - | - | - | 1 | - | - | 2 | 2 | 2 | X | X |
| Sodium Sulfate | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 | - | 2 | 1 | 1 | - | 2 |
| Sodium Sulfide | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 | - | X | X | 2 | X | X |
| Soium Sulfide, Saturated | 1 | 1 | - | - | - | - | 1 | 1 | - | 2 | 2 | 1 | X | X |
| Sodium Sulfite | 2 | 2 | 2 | 1 | 2 | 1 | 1 | 2 | - | 1 | 1 | 1 | - | X |
| Sodium Sulfite, 5% | 1 | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Sodium Sulfite, 10% @ 150°F | 1 | 1 | - | - | - | - | 1 | - | - | 2 | 2 | 2 | 2 | - |
| Sodium Thiosulfate (HPO, An tich ior) | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | X | 1 | 1 | 2 | X |
| Sodium Tripolyphosphate (STPP) | - | - | - | - | - | - | 1 | - | - | - | 1 | 1 | X | X |
| Solnus Oils | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Sour Crude Oil | - | - | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Soybean Oil | 2 | 2 | 2 | - | 2 | - | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - |
| Spent Acid | - | - | - | - | 2 | - | 1 | - | 2 | - | 1 | 1 | - | - |
| Stannic Chloride | X | 2 | 2 | 1 | X | - | 1 | X | - | X | X | X | X | X |
| Stannic Chloride, 50% | X | 1 | - | - | - | - | 1 | - | - | X | X | X | X | - |
| Stannous Chloride (Under 150°F) | 1 | 1 | - | 1 | 1 | - | 1 | X | - | - | X | 2 | X | - |
| Stannous Chloride, 15% | 1 | 1 | - | - | - | - | 1 | - | - | X | X | - | X | - |
| Starch | 2 | 2 | - | - | 1 | 1 | 1 | 1 | - | X | 1 | 1 | 1 | - |
| Steam | USE STEAM HOSE | | | | | | | | | 1 | 1 | 1 | - | 2 |
| Stearic Acid | 2 | 2 | 2 | 1 | 2 | 1 | 1 | 1 | 1 | X | 2 | 1 | X | X |
| Stearin | - | - | - | - | - | 1 | 1 | 2 | - | - | - | - | - | - |
| Stoddard Solvent | 2 | 2 | X | 1 | - | X | 1 | 1 | - | 2 | 1 | 1 | 1 | 1 |
| Styrene (Vinyl Benzene) | X | X | - | - | - | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Styrene (Monomer) | - | X | - | 2 | - | - | 1 | 2 | - | 2 | X | 2 | X | 2 |
| Sucrose Solutions | 1 | 1 | 1 | - | 1 | - | 1 | - | - | 1 | 1 | 1 | - | - |
| Sulfamic Acid (10%, Under 170°F) | - | - | - | 1 | 2 | - | 1 | - | 1 | - | - | - | - | - |
| Sulfate Black Liquor | 1 | 1 | - | - | - | - | 1 | 1 | - | 2 | 2 | 2 | X | - |
| Sulfate Green Liquor | 1 | 1 | - | - | - | - | 1 | 1 | - | 2 | 2 | 2 | X | - |
| Sulfur | - | - | - | - | - | - | - | - | X | - | - | - | - | - |
| Sulfur (Molten) | X | X | - | - | - | - | - | - | X | - | - | - | - | - |
| Sulfur Chloride | X | X | X | - | 2 | - | 1 | 2 | - | X | X | 2 | X | X |
| Sulfur Dioxide (Moist) | 2 | X | - | - | 2 | - | 1 | 1 | 1 | - | 2 | 1 | 1 | X |
| Sulfur Dioxide (Dry) | X | X | X | - | 2 | - | 1 | X | 1 | 2 | 1 | 1 | 1 | 1 |
| Sulfur Dioxide (Liquid) | 2 | X | - | - | 2 | - | 1 | - | - | - | - | - | - | - |
| Sulfur Hexaflouride (Gas) | 1 | 2 | - | - | 2 | - | 1 | X | - | - | - | - | - | - |
| Sulfur Trioxide (Dry) | X | X | X | X | X | - | 1 | 1 | - | 2 | 2 | 2 | 2 | X |
| Sulfuric Acid, 85% | X | X | - | - | - | - | 1 | - | 1 | X | 2 | 1 | X | - |
| Sulfuric Acid, 3 Molar | X | X | - | - | - | - | 1 | - | 1 | - | - | - | - | - |

# CHEMICAL RESISTANCE TABLE – CONTINUED

Rating Scale:
1 Excellent
2 Good resistance
X Not recommended
– Testing recommended
[ ] Cover stock rating only; Rating for tube stock "X"
* Use Gates fuel hose or contact Denver Product Application Department

| Chemical Name | Gates Hose Polymers: Polychloroprene | Nitrile, HNBR, or XTF | Nitrile + PVC | CPE | CSM | Urethane | PTFE | Nylon | MegaTuff | Couplings & Adapters: Carbon Steel | Stainless Steel 304 | Stainless Steel 316 | Aluminum | Brass |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Sulfuric Acid, Aerated, No Velocity | - | - | - | - | - | - | 1 | - | 1 | 2 | 2 | 2 | X | - |
| Sulfuric Acid, Air Free No Velocity | - | - | - | - | - | - | 1 | - | 1 | X | X | 2 | X | - |
| Sulfuric Acid, Concentrated | X | X | - | - | - | - | 1 | - | 1 | - | 1 | 1 | - | - |
| Sulfuric Acid, Fuming, Oleum | X | - | - | - | - | - | 1 | - | 1 | 2 | 1 | 1 | 2 | - |
| Sulfuric Acid (10%) | 1 | 2 | 2 | 1 | 1 | - | 1 | X | X | - | X | X | 2 | X |
| Sulfuric Acid (30%) | 1 | - | - | 1 | 1 | - | 1 | X | 1 | X | X | 2 | X | X |
| Sulfuric Acid (50%) | 2 | X | X | 1 | 1 | - | 1 | X | 1 | X | X | 2 | X | X |
| Sulfuric Acid (75%) | X | X | X | - | 2 | - | 1 | X | 1 | X | X | 2 | X | X |
| Sulfuric Acid (93%) | X | X | X | - | X | - | 1 | X | 1 | 2 | X | 2 | X | X |
| Sulfuric Acid (98%) | X | X | X | X | X | - | 1 | X | 1 | 2 | X | 2 | X | X |
| Sulfurous Acid | 2 | 2 | - | - | - | - | 1 | X | 1 | X | X | 2 | 2 | - |
| Sulfurous Acid (10%) | - | X | - | 1 | 1 | - | 1 | - | 1 | - | X | 2 | 1 | X |
| Sulfurous Acid (75%) | X | X | X | 1 | 1 | - | 1 | X | 1 | X | X | 2 | X | X |
| Sun R&O Oils | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Sunsafe (Fire Resist. Hydr. Fluid) | 2 | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | - |
| Suntac HPOils | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | - | 1 | 1 | - |
| Suntac WR Oils | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | - | 1 | 1 | - |
| Sunvis Oils 700, 800, 900 | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | - | - |
| Super Hydraulic Oils (Conoco) | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | - |
| Sutan Plus, Herbicide | X | X | X | 1 | - | - | - | 1 | - | 1 | 1 | 1 | 1 | - |
| Sutazine Plus, Herbicide | X | X | - | 1 | - | - | - | 1 | - | X | 1 | 1 | 1 | - |
| Synthetic Oil (Citgo) | - | - | - | - | - | 2 | - | 1 | - | 1 | 1 | 1 | - | - |
| Syrup | 2 | 1 | 2 | - | - | - | 1 | 1 | - | - | 1 | 1 | 1 | - |
| **T** | | | | | | | | | | | | | | |
| Tall Oil (Under 150°F) | 2 | 2 | 2 | - | X | - | 1 | - | - | 2 | X | 2 | X | - |
| Tallow | 2 | 2 | 2 | - | - | - | 1 | 1 | - | 2 | 2 | 2 | 1 | 2 |
| Tannic Acid (10%) | 2 | X | - | 1 | 2 | - | 1 | X | 1 | 2 | 1 | 1 | 2 | X |
| Tar And Tar Oil | 2 | - | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 2 |
| Tar (Bituminous, Under 100°F) | 2 | 2 | 2 | X | - | - | 1 | - | 1 | 1 | 1 | 1 | 1 | 2 |
| Tartaric Acid | 2 | 2 | 2 | 1 | 1 | - | 1 | 1 | 1 | X | 2 | 2 | 2 | X |
| Tellus Oils | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Tenol Oils | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | - | - |
| Tergitol | - | - | - | - | - | - | 1 | - | - | 2 | 1 | 1 | - | 2 |
| Terpineol | X | 2 | - | 1 | 2 | - | 1 | 2 | - | - | - | - | - | - |
| Terresstic | - | 1 | - | - | - | - | - | 1 | - | 1 | 1 | 1 | - | - |
| Tetraethyl Lead | 2 | 2 | - | - | - | - | 1 | 2 | - | - | - | - | - | - |
| Tetraethyl Lead Blend | X | 2 | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Tetrahydrofuran (THF) | X | X | - | - | X | 2 | 1 | 1 | - | 2 | - | - | - | - |
| Tetralin | X | X | - | - | X | - | 1 | 2 | - | 1 | 1 | 1 | 1 | - |
| Thiopen | X | X | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Titanium Tetrachloride | X | X | X | - | - | - | 1 | - | - | 1 | 2 | 2 | X | X |
| Toluene (Toluol) | X | X | X | X | X | - | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 |
| Toluene Diisocyanate (Under 150°F) | X | - | - | - | - | - | 1 | - | 1 | 1 | 1 | 1 | - | - |
| Transformer Oil (Askarel Types) | X | X | X | 1 | X | - | 1 | - | 2 | 1 | 1 | 1 | 1 | - |
| Transformer Oil (Petroleum Type) | 2 | 1 | 2 | 1 | X | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Transmission Fluid, Type A | 2 | 1 | 2 | 1 | 2 | - | 1 | 2 | - | 1 | 1 | 1 | 1 | 1 |
| Tributoxyethyl Phosphate | X | X | X | X | X | - | 1 | 2 | X | 1 | - | - | X | - |
| Tributyl Phosphate | X | X | X | 2 | X | - | 1 | - | X | 1 | - | - | X | - |
| Trichloroethylene | X | X | X | 2 | X | - | 1 | 2 | X | X | 2 | 1 | X | 1 |
| Trichloromonofluoroethane (Freon 17) | Use Freon Hose | | | | | | | | | 1 | 1 | 1 | X | - |
| Trichlorotrifluoroethane (Freon 113) | Use Freon Hose | | | | | | | | | 1 | 1 | 1 | X | - |
| Tricresyl Phosphate | X | X | X | 1 | X | - | 1 | 1 | X | 1 | 2 | 2 | X | - |

**Nitrile 150°F or less, no constant contact.


Rating Scale:
1 Excellent
2 Good resistance
X Not recommended
– Testing recommended
[ ] Cover stock rating only; Rating for tube stock "X"
* Use Gates fuel hose or contact Denver Product Application Department

| Chemical Name | Gates Hose Polymers: Polychloroprene | Nitrile, HNBR, or XTF | Nitrile + PVC | CPE | CSM | Urethane | PTFE | Nylon | MegaTuff | Couplings & Adapters: Carbon Steel | Stainless Steel 304 | Stainless Steel 316 | Aluminum | Brass |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Triethanolamine (TEA) | 2 | 2 | - | 1 | 2 | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Tripolyphosphate (STPP) | X | 1 | - | - | - | - | 1 | - | - | - | 2 | 1 | X | - |
| Tung Oil | 2 | 2 | - | - | 2 | - | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Turpentine | X | 2 | - | 2 | X | 1 | 1 | 1 | 1 | X | 1 | 1 | 1 | 2 |
| Type I Fuel (MIL-S-3136) ASTM Fuel A | 2 | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Type II Fuel (MIL-S-3136) | X | 2 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Type III Fuel (MIL-3136) ASTM Fuel B | X | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| **U** | | | | | | | | | | | | | | |
| Ucon Hydrolube Types 150CP, 200CP | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Ucon Hydrolube Types 275CP, 300CP, 550CP | - | - | - | - | - | - | 1 | - | - | - | - | - | - | - |
| Ucon M1 | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Union ATF Dexron | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | - | - |
| Union ATF Type F | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Union C-2 Fluid | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | - | - |
| Union C-POil | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Union Hydraulic Oil AW | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Union Hydraulic Tractor Fluid | - | 1 | - | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Urea Solution | 1 | 2 | - | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | - |
| **V** | | | | | | | | | | | | | | |
| Varnish | X | X | X | - | X | - | 1 | 1 | - | 2 | 1 | 1 | 1 | 2 |
| Vegetable Oils | 2 | 1 | 2 | 1 | - | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 |
| Vegetable Oil (Hot) | - | - | - | - | - | - | 1 | 1 | - | 2 | 2 | 2 | 1 | 2 |
| Versilube | 1 | 1 | - | - | - | - | 1 | - | - | 1 | 1 | 1 | 1 | - |
| Versilube F-50, F-44 | 2 | 2 | 2 | - | 2 | 2 | 1 | 1 | - | 1 | 1 | 1 | 1 | 1 |
| Vinegar | 2 | X | X | 2 | X | - | 1 | 1 | - | X | 2 | 1 | X | X |
| Vinyl Acetate | X | X | X | 1 | X | - | 1 | - | X | 2 | 1 | 2 | 1 | 2 |
| Vinyl Chloride (Chloroethylene, Monomer) | X | X | X | X | X | - | 1 | - | - | 2 | 1 | 1 | 2 | X |
| Vitrea Oils | X | X | X | - | - | 2 | 1 | 1 | - | 1 | 1 | 1 | - | - |
| **W** | | | | | | | | | | | | | | |
| Water | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 1 | 1 | 1 | 1 |
| Water, Acid Mine | 2 | X | - | - | - | - | 1 | 1 | - | X | 2 | 2 | X | X |
| Water, Brine | 2 | 2 | - | - | 1 | 1 | 1 | 1 | - | X | 2 | 2 | - | - |
| Water Deionized, (Demineralized) | - | - | - | - | - | - | 1 | - | 1 | - | - | - | - | - |
| Water, Distilled | 2 | 1 | - | - | 1 | 1 | 1 | 1 | 1 | X | 1 | 1 | 1 | 1 |
| Water, Fresh | 1 | 1 | - | - | - | - | 1 | 1 | 1 | X | 1 | 1 | 1 | X |
| Water In Oil Emulsions | - | - | - | - | - | 2 | 1 | 1 | - | - | - | - | - | - |
| Water, Potable (FDA Tube Only) | Use FDAHose Only | | | | | | | | | - | - | - | | - |
| Water, Salt | 2 | 1 | - | - | - | - | 1 | 1 | - | X | 2 | 2 | X | X |
| White & Bagley No. 2190 Cutting Oil | 2 | 1 | - | - | - | - | 1 | - | - | - | - | - | -. | - |
| Wines | 2 | 1 | 1 | 1 | 1 | - | 1 | 1 | - | 2 | 2 | 2 | 1 | - |
| Wood Oil | 2 | 1 | - | 1 | 2 | 1 | 1 | 1 | - | 1 | 1 | 1 | 1 | - |
| **X** | | | | | | | | | | | | | | |
| Xylene | X | 1 | - | X | - | 2 | 1 | X | 2 | 2 | 2 | 2 | - | - |
| **Z** | | | | | | | | | | | | | | |
| Zeric | - | 1 | - | - | - | 2 | 1 | 2 | 1 | - | - | - | - | - |
| Zinc Acetate | 2 | X | - | - | X | - | 1 | 2 | 1 | 1 | 1 | 1 | 1 | 1 |
| Zinc Chloride Solutions | 1 | 1 | 1 | 1 | 1 | - | 1 | 1 | 1 | X | 2 | 1 | X | X |
| Zinc Chromate | - | - | - | 1 | 1 | - | 1 | - | 1 | - | 1 | 1 | - | - |
| Zinc Hydrate | - | - | - | - | - | 2 | 1 | - | - | - | - | - | - | - |
| Zinc Sulfate Solutions | 2 | 2 | 2 | 1 | 2 | - | 1 | 2 | 1 | X | 2 | 1 | X | X |

# FLOW CAPACITY OF HOSE ASSEMBLIES AT RECOMMENDED FLOW VELOCITIES

Example: A loader burned up a 75 LPM (19.8 GPM) pump, the only available replacement is a 25 GPM model. Can the 25 mm (1 in) output line be kept, or will the additional flow exceed the recommended velocity range? If the output line was 20 mm (0.75 in), should it be replaced?

Solution: Draw a straight line starting at 25 GPM on the flow rate axis, passing through the 1 inch mark on the hose diameter axis, all the way to the velocity axis.
A 25 mm (1 in) line will have a velocity of ~10 ft/s, well within the recommended range. A 20 mm (0.75 in) line will have a velocity of ~18 ft/s, so should be increased in size.




| | |
|---|---|
| Based on Formula: | V = 0.3209 x Q / A |
| Where: | V = Fluid velocity in {ft/s} |
| | Q = Fluid flow rate in {GPM} |
| | A = Hose internal cross sectional area in {in²} = D² x ▾ / 4 |
| | D = Hose internal diameter in {in} |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# PROPERTIES OF C14 PTFE TUBE

| | | |
|---|---|---|
| Tensile Strength, 73°F (23°C) | | 1500-3000 psi |
| Elongation, 73°F (23°C) | | 100-200% |
| Stiffness, 73°F (23°C) | | 60,000 psi |
| Impact Strength | @70°F (21°C) | 2.0 lbf-ft/in |
| | @73°F (23°C) | 3.5 lbf-ft/in |
| | @170°F (77°C) | 6.0 lbf-ft/in |
| Hardness, Durometer | | D55-D70 Shore D |
| Compressive Stress at | | |
| 1% Deformation | @73°F (23°C) | 600 psi |
| 1% Offset | @73°F (23°C) | 1000 psi |
| Deformation Under Load, 24 Hrs. @ 122°F (50°C) | | |
| 1200 Lb./Sq. In. | | 4-8% |
| 2000 Lb./Sq. In. | | 25% |
| Heat-Distortion Temperature @66 Lb./Sq. In. | | 250°F (121°C) |
| Coefficient of Linear Thermal Expansion per °F; 77-140°F (25-60°C) | | $5.5 \times 10^{-5}$ |
| Thermal Conductivity 0.18 In. | | 1.7 BTU/hr/sq ft/°F/in |
| Specific Heat | | 0.25 BTU/lb/°F |
| Water Absorption | | 0.0% |
| Flammability | | Nonflammable |
| Specific Gravity | | 2.1-2.3 |

Most applications of PTFE hose do not require the use of a conductive inner tube. Under certain applications, the potential for Static Discharge must be considered. Be aware that static electricity can be a hazard. Under those conditions where static discharge can occur, the use of conductive Gates C14CT hose is recommended. The following should serve to increase your knowledge and understanding of this phenomenon and how to avoid its occurrence:

When two different materials contact each other, electrons from one material can move across its boundary and associate with the other. These electrons align themselves with the material contacted. If the two materials are good conductors of electricity, the positive and negative electrons flow back and forth between them, keeping them in balance. If one or both are insulators, the flow will not occur. A charge will then build up on the surface of one of the materials. When the charge exceeds the electric strength of the material, electric breakdown results.

In applying this to PTFE hose, we have to consider fluids and gases that are poor conductors of electricity and the flow rates of those fluids and gases. In order for a liquid or gas to be a poor electrical conductor, it will generally satisfy one or both of the following conditions:

1. Be nonpolar; that is, an imbalance between protons and electrons, and/or
2. Contain a nonmixable component or a suspended solid; such as water in kerosene.

So when a liquid contacts a PTFE tube that isn't a good conductor (white PTFE innercore), the result is phase separation and the electric charge starts to build. The rate at which static electricity builds up now becomes a function of the fluid flow rate. When the electric strength of the PTFE tube is exceeded, the electric charge will puncture the tube wall and ground itself on the stainless steel braid of the hose.

In hydraulics, high pressures generally mean high velocities. Historically, fluids were filtered upstream of the hose using metallic filter elements. The metallic element helped to ground the charge. But, today, most filtration is done with paper-type and glass-fiber filter elements that have a tendency to inject an electrostatic charge into the fluid they are filtering.

**Steam and fuels are two specific areas of concern. No hose in this catalog can or should be used in steam applications. Contact Gates Product Application for proper hose recommendation.**

Fuels (i.e. gasoline and white spirits, hydrazine, benzene, diesel oils, etc.) are, for the most part, "nonconductive" liquids. These fluids usually are transferred at fairly low velocities, but there still is a potential for an electrostatic discharge due to external factors, such as humidity and, to some extent, temperature. You should take all of these factors into account even at fluid velocities at or below 1 meter per second.

When using PTFE hose, you can offset the potential hazard of electrostatic discharge by using a conductive Gates C14CT hose. Carbon is added to the PTFE inner tube wall during manufacture. The carbon layer directs the electrostatic charge down the inner diameter of the hose to the metal end fittings. This prevents the charge from building up on the inner tube wall.

So, it's important to examine any application where nonconductive fluids are used and any of the above conditions exist. This section is not meant to cover all conditions or situations when they involve fuels, steam or other media which may cause electrostatic buildup or potential discharge. If you need help on any individual application, contact Hose/Connector Product Application, Denver.

Following is a list of some of the chemicals that meet at least one of the criteria necessary to create electrostatic discharge:

- Cyclohexane
- Decalin
- Diacetone
- Dibutyl Ether
- Dibutyl Phthalate
- Dibutyl Sebacate
- Dimethyl Phthalate
- Dioctyl Phthalate
- Dipentene
- Fuel Oil
- Gasoline
- Hexane
- Hexene
- Hydrazine
- Kerosene
- Lacquers
- Lacquer Solvents
- Naphtha
- Naphthalene
- Octane
- Paint
- Petroleum
- Pinene
- Silicone Oils
- Skydrol 500 & 700
- Steam
- Toluene
- Transformer Oil
- Turpentine
- Varnish
- Versilube

**General Industry Practice has identified the above fluids as requiring a conductive hose—Gates C14CT.**

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## WHAT IS EFFUSION?

It is the process where chemical molecules move through the PTFE wall and escape from a hose or hose assembly. It is sometimes called permeation. The rate at which effusion occurs depends upon temperature, pressure, wall thickness and the hose material.

The fact that effusion occurs isn't the problem. This process will happen with most all media in most hose material.

**The basic issues are:**

1. At what rate will effusion occur?
2. How hazardous are the media?
3. In what kind of environment does effusion take place; closed room, outside, etc.?

## GENERAL MEDIA CONCERNS REGARDING THE POTENTIAL EFFECTS OF EFFUSION:

- Media where corrosion is not of concern, but effusion may displace the air we breathe, thus becoming a hazard to personnel.

  Some of the chemicals in this category are:

  - Carbon Dioxide
  - Nitrogen
  - Steam
  - Oxygen
  - Helium
  - Neon
  - Argon
  - Xenon
  - Krypton

- Media that can effuse in their "vapor phase"; i.e., their boiling point is below approximately +125°F (+52°C) at atmospheric pressure. These media can form chemicals that can corrode the braid and/or cause injury to personnel.

  **Some of these include:**

  - Acetaldehyde (Flammable, Toxic)
  - Benzene (Flammable, Toxic)
  - Liquid Butane (Flammable)
  - Carbon Disulfide (Flammable, Toxic)
  - Diethyl Ether (Flammable, Narcotic)
  - Ethyl Mercaptan (Flammable, Toxic)
  - Hydrochloric Acid (Corrosive, Toxic)
  - Lacquer Solvents (Flammable)
  - Methyl Bromide (Flammable, Toxic, Corrosive)
  - Methylene Chloride (Toxic)
  - Methyl Formate (Flammable, toxic)
  - Liquid Propane (Flammable)
  - Sulphur Trioxide (Corrosive, toxic)
  - Liquid Chlorine (Corrosive, toxic)

- Media with the potential to effuse and cause corrosion of the braid reinforcement and fitting materials. These chemicals are all gases while at atmospheric pressure and a temperature of +56°F (+13°C) or lower.

  **Some of these chemicals are:**

  - Acetylene (Flammable)
  - Butadiene (Flammable)
  - Butane Gas (Flammable)
  - Carbon Monoxide (Toxic, Flammable)
  - Chlorine (Toxic, Corrosive)
  - Chlorine Trifluoride (Toxic, Corrosive)
  - Ethyl Chloride (Toxic, Corrosive)
  - Hydrogen (Flammable)
  - Hydrogen Chloride (Corrosive, Toxic)
  - Hydrogen Sulfide (Flammable, Toxic)
  - Hydrocyanic Acid (Flammable, Toxic)
  - Hydrogen Cyanide (Flammable, Toxic)
  - Coke Oven Gas (Flammable, Toxic)
  - Natural Gas (Flammable, Toxic)
  - Propane Gas (Flammable)
  - Sulfur Dioxide (Corrosive)
  - Vinyl Chloride Monomer (Toxic, Corrosive)

It is important that hose assemblies used in these applications are installed in well-vented areas to avoid potential problems for personnel and/or equipment.

## WHAT IS PRESSURE DROP?

Friction is defined as the resistance an object encounters in moving over another. Solids, liquids, and gasses all exhibit friction in their motion. In hose and piping systems the result of this friction is pressure drop and heat generation that may be accurately estimated with engineering models.

## WHY DOES PRESSURE DROP MATTER?

If there is excessive pressure drop in a system pumps, will have to work harder, use more energy, and the working fluid will increase in temperature. Depending on the source of the additional pressure loss it could: raise the whole system pressure, increasing wear and introducing potentially dangers over pressure conditions; render some tools or equipment functions inoperable, because of inadequate operation pressure; or create damaging cavitation and loss of net positive suction head (NPSH).

## WHAT AFFECTS PRESSURE DROP?

The factors which contribute pressure loss may be broken down into two general categories: mechanical components and fluid properties. Mechanical components such as valves, flow meters, quick disconnects, adapters, couplings, tubing, hose, etc., all contribute to pressure loss. The amount of pressure loss in mechanical components is impacted by criteria such as cross sectional area, internal surface roughness, length, bends, and geometric complexity. Fluid properties such as density, viscosity, heat capacity and bulk modulus will also contribute to pressure loss. Fluid properties are impacted by temperature, pressure, contamination, air entrainment, and time.

While all of these components contribute to pressure loss, fluid velocity has the most impact. Fluid velocity is a direct product of flow rate and cross sectional area.

## WHAT CAN BE DONE TO REDUCE PRESSURE DROP?

- Check system pressure drop when non-identical replacement parts are required or there is ongoing system problems.
- Use straight adapters and bent couplings whenever possible.
- Replace worn parts and old fluids.
- Lower the fluid velocity.

## HOW CAN I CALCULATE PRESSURE DROP FOR A HOSE ASSEMBLY?

With some basic system information reliable pressure drop approximations may be readily calculated. First determine the applicable mechanical components and fluid for the analysis (doing 1 hose assembly at a time is recommended), then enter those values into the Gates online pressure drop calculator. Hose assembly information: Inside Diameter, Length, Couplings, Adapters

**Fluid information:** Density, Viscosity, and Heat Capacity (these may be estimated with fluid type and temperature)

**Go to https://www.gates.com/resources/calculators/fluid-flow-pressure-calculator to calculate the pressure loss from the system information.**

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# FAHRENHEIT-CELSIUS CONVERSION

Locate the temperature to be converted in the center column. This number can be in Celsius or Fahrenheit. The equivalent converted temperature for Centigrade/Celsius is listed in the left column and the equivalent converted temperature for Fahrenheit is located in the right column.

| C | F\C | F |
|---|---|---|
| -68 | -90 | -130 |
| -62 | -80 | -112 |
| -57 | -70 | -94 |
| -51 | -60 | -76 |
| -46 | -50 | -58 |
| -40 | -40 | -40 |
| -34 | -30 | -22 |
| -29 | -20 | -4 |
| -23 | -10 | 14 |
| -17.8 | 0 | 32 |
| -17.2 | 1 | 33.8 |
| -16.7 | 2 | 35.6 |
| -16.1 | 3 | 37.4 |
| -15.6 | 4 | 39.2 |
| -15.0 | 5 | 41.0 |
| -14.4 | 6 | 42.8 |
| -13.9 | 7 | 44.6 |
| -13.3 | 8 | 46.4 |
| -12.8 | 9 | 48.2 |
| -12.2 | 10 | 50.0 |
| -11.7 | 11 | 51.8 |
| -11.1 | 12 | 53.6 |
| -10.6 | 13 | 55.4 |
| -10.0 | 14 | 57.2 |
| -9.4 | 15 | 59.0 |
| -8.9 | 16 | 60.8 |
| -8.3 | 17 | 62.6 |
| -7.8 | 18 | 64.4 |
| -7.2 | 19 | 66.2 |
| -6.7 | 20 | 68.0 |
| -6.1 | 21 | 69.8 |
| -5.6 | 22 | 71.6 |
| -5.0 | 23 | 73.4 |
| -4.4 | 24 | 75.2 |
| -3.9 | 25 | 77.0 |
| -3.3 | 26 | 78.8 |
| -2.8 | 27 | 80.6 |
| -2.2 | 28 | 82.4 |
| -1.7 | 29 | 84.2 |
| -1.1 | 30 | 86.0 |
| -.6 | 31 | 87.8 |
| 0 | 32 | 89.6 |
| .6 | 33 | 91.4 |
| 1.1 | 34 | 93.2 |
| 1.7 | 35 | 95.0 |
| 2.2 | 36 | 96.8 |
| 2.8 | 37 | 98.6 |
| 3.3 | 38 | 100.4 |
| 3.9 | 39 | 102.2 |
| 4.4 | 40 | 104.0 |

| C | F\C | F |
|---|---|---|
| 5.0 | 41 | 105.8 |
| 5.6 | 42 | 107.6 |
| 6.1 | 43 | 109.4 |
| 6.7 | 44 | 111.2 |
| 7.2 | 45 | 113.0 |
| 7.8 | 46 | 114.8 |
| 8.3 | 47 | 116.6 |
| 8.9 | 48 | 118.4 |
| 9.4 | 49 | 120.2 |
| 10.0 | 50 | 122.0 |
| 10.6 | 51 | 123.8 |
| 11.1 | 52 | 125.6 |
| 11.7 | 53 | 127.4 |
| 12.2 | 54 | 129.2 |
| 12.8 | 55 | 131.0 |
| 13.3 | 56 | 132.8 |
| 13.9 | 57 | 134.6 |
| 14.4 | 58 | 136.4 |
| 15.0 | 59 | 138.2 |
| 15.6 | 60 | 140.0 |
| 16.1 | 61 | 141.8 |
| 16.7 | 62 | 143.6 |
| 17.2 | 63 | 145.4 |
| 17.8 | 64 | 147.2 |
| 18.3 | 65 | 149.0 |
| 18.9 | 66 | 150.8 |
| 19.4 | 67 | 152.6 |
| 20.0 | 68 | 154.4 |
| 20.6 | 69 | 156.2 |
| 21.1 | 70 | 158.0 |
| 21.7 | 71 | 159.8 |
| 22.2 | 72 | 161.6 |
| 22.8 | 73 | 163.4 |
| 23.3 | 74 | 165.2 |
| 23.9 | 75 | 167.0 |
| 24.4 | 76 | 168.8 |
| 25.0 | 77 | 170.6 |
| 25.6 | 78 | 172.4 |
| 26.1 | 79 | 174.2 |
| 26.7 | 80 | 176.0 |
| 27.2 | 81 | 177.8 |
| 27.8 | 82 | 179.6 |
| 28.3 | 83 | 181.6 |
| 28.9 | 84 | 183.2 |
| 29.4 | 85 | 185.0 |
| 30.0 | 86 | 186.8 |
| 30.6 | 87 | 188.6 |
| 31.1 | 88 | 190.4 |
| 31.7 | 89 | 192.2 |
| 32.2 | 90 | 194.0 |
| 32.8 | 91 | 195.8 |

| C | F\C | F |
|---|---|---|
| 33.3 | 92 | 197.6 |
| 33.9 | 93 | 199.4 |
| 34.4 | 94 | 201.2 |
| 35.0 | 95 | 203.0 |
| 35.6 | 96 | 204.8 |
| 36.1 | 97 | 206.6 |
| 36.7 | 98 | 208.4 |
| 37.2 | 99 | 210.2 |
| 37.8 | 100 | 212.0 |
| 43 | 110 | 230 |
| 49 | 120 | 248 |
| 54 | 130 | 266 |
| 60 | 140 | 284 |
| 66 | 150 | 302 |
| 71 | 160 | 320 |
| 77 | 170 | 338 |
| 82 | 180 | 356 |
| 88 | 190 | 374 |
| 93 | 200 | 392 |
| 99 | 210 | 410 |
| 100 | 212 | 413.6 |
| 104 | 220 | 428 |
| 110 | 230 | 446 |
| 116 | 240 | 464 |
| 121 | 250 | 482 |
| 127 | 260 | 500 |
| 132 | 270 | 518 |
| 138 | 280 | 536 |
| 143 | 290 | 554 |
| 149 | 300 | 572 |
| 154 | 310 | 590 |
| 160 | 320 | 608 |
| 166 | 330 | 626 |
| 170 | 338 | 640 |
| 171 | 340 | 644 |
| 177 | 350 | 662 |
| 182 | 360 | 680 |
| 186 | 366 | 691 |
| 188 | 370 | 698 |
| 193 | 380 | 716 |
| 198 | 388 | 730 |
| 199 | 390 | 734 |
| 204 | 400 | 752 |
| 208 | 406 | 763 |
| 210 | 410 | 770 |
| 216 | 420 | 788 |
| 221 | 430 | 806 |
| 227 | 440 | 824 |
| 232 | 450 | 842 |

# PRESSURE CONVERSIONS

## Metric to PSI
**(1 kPa = .145 psi)**

| Kilo Pascals (kPa) | Mega Pascals (MPa) | Bar (Bar) | Pounds per Square Inch (psi) |
|---|---|---|---|
| 100 | 0.1 | 1 | 14.5 |
| 200 | 0.2 | 2 | 29.0 |
| 300 | 0.3 | 3 | 43.5 |
| 400 | 0.4 | 4 | 58.0 |
| 500 | 0.5 | 5 | 72.5 |
| 600 | 0.6 | 6 | 87.0 |
| 700 | 0.7 | 7 | 101.5 |
| 800 | 0.8 | 8 | 116.0 |
| 900 | 0.9 | 9 | 130.5 |
| 1,000 | 1.0 | 10 | 145.0 |
| 2,000 | 2.0 | 20 | 290.1 |
| 3,000 | 3.0 | 30 | 435.1 |
| 4,000 | 4.0 | 40 | 580.2 |
| 5,000 | 5.0 | 50 | 725.2 |
| 6,000 | 6.0 | 60 | 870.2 |
| 7,000 | 7.0 | 70 | 1,015.3 |
| 8,000 | 8.0 | 80 | 1,160.3 |
| 9,000 | 9.0 | 90 | 1,305.3 |
| 10,000 | 10 | 100 | 1,450 |
| 20,000 | 20 | 200 | 2,901 |
| 30,000 | 30 | 300 | 4,351 |
| 40,000 | 40 | 400 | 5,802 |
| 50,000 | 50 | 500 | 7,252 |
| 60,000 | 60 | 600 | 8,702 |
| 70,000 | 70 | 700 | 10,153 |
| 80,000 | 80 | 800 | 11,603 |
| 90,000 | 90 | 900 | 13,053 |
| 100,000 | 100 | 1000 | 14,504 |
| 200,000 | 200 | 2000 | 29,008 |
| 300,000 | 300 | 3000 | 43,511 |

## PSI to Metric
**(1 psi = 6.89 kPa)**

| Pounds per Square Inch (psi) | Kilo Pascals (kPa) | Mega Pascals (MPa) | Bar (Bar) |
|---|---|---|---|
| 10 | 68.9 | 0.07 | 0.7 |
| 20 | 137.9 | 0.14 | 1.4 |
| 30 | 206.8 | 0.21 | 2.1 |
| 40 | 275.8 | 0.28 | 2.8 |
| 50 | 344.7 | 0.34 | 3.4 |
| 60 | 413.7 | 0.41 | 4.1 |
| 70 | 482.6 | 0.48 | 4.8 |
| 80 | 551.6 | 0.55 | 5.5 |
| 90 | 620.5 | 0.62 | 6.2 |
| 100 | 689 | 0.7 | 6.9 |
| 200 | 1,379 | 1.4 | 13.8 |
| 300 | 2,068 | 2.1 | 20.7 |
| 400 | 2,758 | 2.8 | 27.6 |
| 500 | 3,447 | 3.4 | 34.5 |
| 600 | 4,137 | 4.1 | 41.4 |
| 700 | 4,826 | 4.8 | 48.3 |
| 800 | 5,516 | 5.5 | 55.2 |
| 900 | 6,205 | 6.2 | 62.1 |
| 1,000 | 6,895 | 6.9 | 68.9 |
| 2,000 | 13,790 | 13.8 | 137.9 |
| 3,000 | 20,684 | 20.7 | 206.8 |
| 4,000 | 27,579 | 27.6 | 275.8 |
| 5,000 | 34,474 | 34.5 | 344.7 |
| 6,000 | 41,369 | 41.4 | 413.7 |
| 7,000 | 48,263 | 48.3 | 482.6 |
| 8,000 | 55,158 | 55.2 | 551.6 |
| 9,000 | 62,053 | 62.1 | 620.5 |
| 10,000 | 68,948 | 68.9 | 689 |
| 20,000 | 137,895 | 137.9 | 1,379 |
| 30,000 | 206,843 | 206.8 | 2,068 |
| 40,000 | 275,790 | 275.8 | 2,758 |

## EXAMPLES


**(A) Convert 3,429 psi to the equivalent pressure in Bar.**

| | | | | |
|---|---|---|---|---|
| | 3,000 psi | = | 206.8 | Bar |
| + | 400 psi | = | 27.6 | Bar |
| + | 20 psi | = | 1.4 | Bar |
| + | 9 psi | = | .62 | Bar |
| | 3429 psi | = | 236.42 | Bar |

**(B) Convert 3,429 psi to the equivalent pressure in MPa.**

| | | | | |
|---|---|---|---|---|
| | 3,000 psi | = | 20.680 | MPa |
| + | 400 psi | = | 2.760 | MPa |
| + | 20 psi | = | .140 | MPa |
| + | 9 psi | = | .062 | MPa |
| | 3,429 psi | = | 23.642 | MPa |

# FAHRENHEIT-CELSIUS CONVERSION



# DECIMAL AND MILLIMETER FRACTION EQUIVALENTS

| Inches | | |
|---|---|---|
| Fractions | Decimals | Millimeters |
| 1/64 | .015625 | .397 |
| 1/32 | .03125 | .794 |
| 3/64 | .046875 | 1.191 |
| 1/16 | .0625 | 1.588 |
| 5/64 | .078125 | 1.984 |
| 3/32 | .09375 | 2.381 |
| 7/64 | .109375 | 2.778 |
| 1/8 | .125 | 3.175 |
| 9/64 | .140625 | 3.572 |
| 5/32 | .15625 | 3.969 |
| 11/64 | .171875 | 4.366 |
| 3/16 | .1875 | 4.763 |
| 13/64 | .203125 | 5.159 |
| 7/32 | .21875 | 5.556 |
| 15/64 | .234375 | 5.953 |
| 1/4 | .250 | 6.350 |
| 17/64 | .265625 | 6.747 |
| 9/32 | .28125 | 7.144 |
| 19/64 | .296875 | 7.541 |
| 5/16 | .3125 | 7.938 |

| Inches | | |
|---|---|---|
| Fractions | Decimals | Millimeters |
| 23/64 | .359375 | 9.128 |
| 3/8 | .375 | 9.525 |
| 25/64 | .390625 | 9.922 |
| 13/32 | .40625 | 10.319 |
| 27/64 | .421875 | 10.716 |
| 7/16 | .4375 | 11.113 |
| 29/64 | .453125 | 11.509 |
| 15/32 | .46875 | 11.906 |
| 31/64 | .484375 | 12.303 |
| 1/2 | .500 | 12.700 |
| 33/64 | .515625 | 13.097 |
| 17/32 | .53125 | 13.494 |
| 35/64 | .546875 | 13.891 |
| 9/16 | .5625 | 14.288 |
| 37/64 | .578125 | 14.684 |
| 19/32 | .59375 | 15.081 |
| 39/64 | .609375 | 15.478 |
| 5/8 | .625 | 15.875 |
| 41/64 | .640625 | 16.272 |
| 21/32 | .65625 | 16.669 |

| Inches | | |
|---|---|---|
| Fractions | Decimals | Millimeters |
| 11/16 | .6875 | 17.463 |
| 45/64 | .703125 | 17.859 |
| 23/32 | .71875 | 18.256 |
| 47/64 | .734375 | 18.653 |
| 3/4 | .750 | 19.050 |
| 49/64 | .765625 | 19.447 |
| 25/32 | .78125 | 19.844 |
| 51/64 | .796875 | 20.241 |
| 13/16 | .8125 | 20.638 |
| 53/64 | .828125 | 21.034 |
| 27/32 | .84375 | 21.431 |
| 55/64 | .859375 | 21.828 |
| 7/8 | .875 | 22.225 |
| 57/64 | .890625 | 22.622 |
| 29/32 | .90625 | 23.019 |
| 59/64 | .921875 | 23.416 |
| 15/16 | .9375 | 23.813 |
| 61/64 | .953125 | 24.209 |
| 31/32 | .96875 | 24.606 |
| 63/64 | .984375 | 25.003 |
| 1 | 1.000 | 25.400 |

# METRIC (SI) — U.S. UNITS FOR FLUID POWER USE

(The following conversions are based on information taken from ASTM, American Society for Testing and Materials, Handbook E380-72.)

| Quantity | Customary U.S. Unit | SI Unit | Conversion from U.S. to SI Units | Conversion from SI to U.S. Units |
|---|---|---|---|---|
| Area | Square Inch (in2) | Square Metre (m2) | (in2) x (6.4516 x 10 -4 ) = (m2) | (m2) x 1550.003 = (in2) |
| Force | Pound ($lb_f$) | Newton (N) | (lbf) x 4.4482 = (N) | (N) x (2.2481 x10-1) = ($lb_f$) |
| Frequency | Cycles/Second (cps) | Hertz ($H_z$) | 1 (cps) = 1($H_z$) | 1(Hz) = 1(cps) |
| Length | Inch (in) | Metre (m) | (in) x (2.540 x 10-2 ) = (m) | (m) x 39.370 = (in) |
| Mass | Pound ($lb_m$) | Kilogram (kg) | (lbm) x .4536 = (kg) | (kg) x 2.2046 = ($lb_m$) |
| Power | Electric Horsepower (HP) | Watt (W) | (HP) x (7.460 x 102 ) = (W) | (W) x (1.3405 x 10-3 ) = (HP) |
| | Pounds/Sq In (psi) | Newtons/Sq Metre (N/m2) | (psi) x (6.8948 x 103) = (N/m2) | (N/m2) x (1.4504 x 10-4) = (psi) |
| Pressure | | | (Non-Preferred Conversions) | |
| | (psi) | Mega Pascal (MPa) | (psi)/145 = MPa | (MPa) x 145 = (psi) |
| | (psi) | Bar (Bar) | psi/14.5 = Bar | (Bar) x (1.4504 x 101) = (psi) |
| | (Bar) | (N/m2) | (Bar) x 100,000 = (N/m2) | (N/m2) x (1.00 x 10-5) = (Bar) |
| Temperature | Degrees Fahrenheit (°F) | Degrees Celsius (°C) | (°Celsius) = 0.556(°F-32) | (1.8°C) + 32 = °F |
| Torque | Pound-Inch ($lb_f$-in) | Newton-Metres (N-m) | ($lb_f$-in) x (1.1298 x 10-1) = (N-m) | (N-m) x 8.8507 = ($lb_f$-in) |
| | US Gallon (Gal) | Cubic Metre (m3) | (Gal) x (3.7854 x 10-3) = (m3) | (m3) x (2.6417 x 102) = (Gal) |
| Volume | | | (Non-Preferred Conversions) | |
| | | Litre (l) | (Gal) x 3.7854 = (l) | (l) x (2.6417 x 10-1) = (Gal) |
| Work | Foot-Pound (ft-$lb_f$) | Joule (J) | (ft-$lb_f$) x 1.3558 = (J) | (J) x (7.3756 x 10-1) = (ft-$lb_f$) |

1. Determine the correct torque value for your coupling using the manufacturers' recommendations. The minimum torque values are adequate for sealing in most applications; never exceed the maximum torque recommendations. Only use manufacturer specified torque values; do not use SAE recommendations.
2. Calculated the correct torque wrench setting. Wrench Setting = Desired Torque * L / LA (see Figure 1)
3. Ensure that the seal face and threads are clean and in good condition. O-rings should be lubricated with light oil, but threads should be completely dry unless making a tapered pipe thread connection (interference seal).
4. If the assembly has a male connector on one end, install the male connector first.
5. Hand tighten the connection by bringing seal face in contact and rotating the nut by hand until it stops, approximately 0.3-1 ft-lb.
6. Mark the coupling nut and backup hex with a line for flats method of torque verification.
7. Apply a wrench to the backup hex to prevent the coupling and hose from moving while tightening the nut with a torque wrench. Failure to retain the backup hex during installation can cause hose twisting and will result in additional clamp load force that can cause seal face damage.
8. While keeping the backup hex secure apply the torque wrench to the fitting nut and pull until the proper torque is achieved. The coupling nut must be in motion when the final torque is achieved, otherwise the nut must be loosened and retightened until the torque is attained while the nut is in motion.
9. If a torque wrench cannot fit into the coupling area or if it is unavailable, flats method may be used to ensure that JIC couplings are properly tightened, as shown in figure 2. Checking flats is also a good method of ensuring that critical connections have been properly tightened.





**Figure 1 -** Torque wrench adjustment when using a crowfoot wrench. Torque Wrench Setting = Desired Torque * L / LA





**Figure 2 -** Flats method of verifying coupling torque.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## JIC, SAE 45°, ORFS, O-RING BOSS, GATES ADAPTERLESS, & MEGASEAL®

| Dash Size | JIC 37°, SAE 45° & MegaSeal (Steel) | | JIC 37°, SAE 45° & MegaSeal (Brass) | | Flat Face O-Ring Seal (Steel) | | SAE O-Ring Boss (Steel) & Gates Adapterless ≤ 4000 PSI | | SAE O-Ring Boss (Steel) & Gates Adapterless > 4000 PSI | |
|---|---|---|---|---|---|---|---|---|---|---|
| 1/16 inch | lb-ft | | lb-ft | | lb-ft | | lb-ft | | lb-ft | |
| | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max |
| -3 | 8 | 10 | 5 | 7 | | | 7 | 9 | 7 | 9 |
| -4 | 11 | 14 | 7 | 9 | 18 | 23 | 13 | 17 | 15 | 18 |
| -5 | 14 | 18 | 9 | 11 | 22 | 28 | 18 | 23 | 18 | 23 |
| -6 | 18 | 22 | 11 | 14 | 29 | 37 | 22 | 28 | 26 | 32 |
| -8 | 36 | 45 | 23 | 29 | 41 | 51 | 37 | 46 | 52 | 64 |
| -10 | 57 | 71 | 37 | 46 | 44 | 55 | 44 | 55 | 74 | 92 |
| -12 | 79 | 99 | 51 | 64 | 66 | 83 | 70 | 88 | 125 | 157 |
| -14 | 94 | 117 | 61 | 76 | | | 92 | 115 | 158 | 198 |
| -16 | 108 | 135 | 70 | 88 | 92 | 115 | 111 | 138 | 199 | 249 |
| -20 | 127 | 158 | 82 | 103 | 125 | 157 | 147 | 184 | 210 | 263 |
| -24 | 158 | 198 | 103 | 129 | 147 | 184 | 155 | 193 | 273 | 341 |
| -32 | 245 | 306 | 159 | 199 | 376 | 470 | 221 | 276 | 398 | 497 |

## DIN 24/60 & INVERTED CONE

| Size | | Torque | |
|---|---|---|---|
| mm | | lb-ft | |
| Light Tube O.D. | Heavy Tube O.D. | Min | Max |
| 6 | | 7 | 15 |
| 8 | | 15 | 26 |
| 10 | 8 | 18 | 30 |
| 12 | 10 | 22 | 33 |
| 14 | 12 | 26 | 37 |
| 15 | 14 | 30 | 52 |
| | 16 | 30 | 52 |
| 18 | | 44 | 74 |
| 22 | 20 | 59 | 89 |
| 28 | 25 | 74 | 111 |
| | 30 | 74 | 162 |
| 35 | | 133 | 184 |
| 42 | 38 | 148 | 221 |


## BSP 30° & JIS

| Dash Size | Torque | |
|---|---|---|
| 1/16 inch | lb-ft | |
| | Min | Max |
| -2 | 7 | 9 |
| -4 | 11 | 18 |
| -6 | 19 | 28 |
| -8 | 30 | 36 |
| -10 | 37 | 44 |
| -12 | 50 | 60 |
| -16 | 79 | 95 |
| -20 | 127 | 152 |
| -24 | 167 | 190 |
| -32 | 262 | 314 |

## 4-BOLT FLANGES

| Dash Size | Bolt Size | Torque |
|---|---|---|
| 1/16 inch | inch | lb-ft |
| -8 | 0.31 | 24 |
| -12 | 0.38 | 44 |
| -16 | 0.44 | 44 |
| -20 | 0.5 | 68 |
| -24 | 0.63 | 111 |
| -32 | 0.75 | 111 |

Note:
1. Align faces and finger tighten bolts before applying final torque in a pattern. The seal faces must be parallel with even bolt tension to seal properly.
2. Torque values apply to bolts which are plated or coated in light engine oil.
3. Before assembly lubricate o-ring with light oil (SAE 10W or 20W).




## SAE MALE FLARELESS ASSEMBLY (MFA)

After hand tight (when the sleeve bites the tube) rotate nut one full turn (eight flats).

## NPTF

| Dash Size | Max Torque |
|---|---|
| 1/16 inch | lb-ft |
| -2 | 20 |
| -4 | 25 |
| -6 | 35 |
| -8 | 45 |
| -12 | 55 |
| -16 | 65 |
| -20 | 80 |
| -24 | 95 |
| -32 | 120 |

Note:
1. The torque values obtained from tightening pipe threads can vary considerably depending on thread condition. Adequate sealing can occur at values much lower than the maximum values listed above. Only enough torque to achieve adequate sealing should be used.
2. When using a male tapered pipe thread with a female straight or parallel pipe thread, maximum values are 50% of those listed in the table.
3. If thread sealant is used, maximum values shown should be decreased by 25%.

## FLATS METHOD VALUES

| Termination Type | Dash Size | Flats |
|---|---|---|
| | 1/16 in | |
| JIS | -4 | 0.5 – 1.5 |
| JIC | -4 | 1.5 – 1.75 |
| JIC | -6 | 1.0 – 1.5 |
| JIC | -8 | 1.5 – 1.75 |
| JIC | -10 | 1.0 – 1.5 |
| JIC | -12 | 1.0 – 1.5 |
| JIC | -16 | .75 – 1.0 |
| JIC | -20 | .75 – 1.0 |
| JIC | -24 | .75 – 1.0 |
| JIC | -32 | .75 – 1.0 |

Note:
1. Seal faces must be in contact and the fitting fully hand tightened before marking flats.
2. Flats method is most accurate for the first assembly cycle, for multiple disassembly/assembly cycles torque values are more reliable.
3. Tightening two flats or more is analogous to severe over torque and may damage seal faces.

| Conversion | Formula |
|---|---|
| lbf-ft to N-m | [lbf-ft]*1.3558 = [N-m] |
| lbf-ft to lb-in | [lbf-ft]*12 = [lb-in] |
| N-m to lb-in | [N-m]*8.8508 = [lb-in] |

# HYDRAULIC HOSE FOR G8K COUPLINGS




**The Gates eCrimp program** is a web based utility which allows users and distributors of Gates hydraulic and industrial hose products to find and print the most up to date crimp specifications with nothing more than an internet browser.

This program can be used to find crimp data for all Gates crimpers. Custom result may be printed by selecting the crimper, hose and coupling. Optionally results may also be limited by die set and working pressure.

The eCrimp web application can be directly accessed from a web browser by entering http://eCrimp.Gates.com for the website.


**The eCrimp mobile app** is available for download for the iPhone and iPad from the App Store.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Caterpillar Style O-Ring Flange


Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings)




| Part No. | Descr. | Prod. No. | ⟷ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G19400-1212 | 12G8K-12FLC | 7347-80215 | 3/4 | 19.1 | 1.62 | 41.2 | 5.93 | 150.6 | 2.95 | 75.0 | .56 | 14.2 |
| G19400-1616 | 16G8K-16FLC | 7347-80015 | 1 | 25.4 | 1.87 | 47.5 | 5.64 | 143.3 | 2.96 | 75.2 | .56 | 14.2 |

# Caterpillar Style O-Ring Flange - 45° Bent Tube


Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings)




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G19407-1212 | 12G8K-12FLC45-034 | 7347-80225 | 3/4 | 19.1 | 1.62 | 41.2 | 1.35 | 34.3 | 6.65 | 168.9 | 3.68 | 93.5 | .56 | 14.2 |
| G19407-1616 | 16G8K-16FLC45-050 | 7347-80025 | 1 | 25.4 | 1.87 | 47.5 | 1.97 | 50.0 | 7.76 | 197.1 | 5.08 | 129.0 | .56 | 14.2 |


# Caterpillar Style O-Ring Flange - 90° Bent Tube

Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings)




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G19415-1212 | 12G8K-12FLC90-070 | 7347-80235 | 3/4 | 19.1 | 1.62 | 41.2 | 2.76 | 70.1 | 6.18 | 157.0 | 3.22 | 81.8 | .56 | 14.2 |
| G19415-1616 | 16G8K-16FLC90-093 | 7347-80055 | 1 | 25.4 | 1.87 | 47.5 | 3.66 | 93.0 | 6.46 | 164.1 | 3.79 | 96.3 | .56 | 14.2 |
| G19416-1616 | 16G8K-16FLC90-117 | 7347-80045 | 1 | 25.4 | 1.87 | 47.5 | 4.61 | 117.1 | 6.46 | 164.1 | 3.79 | 96.3 | .56 | 14.2 |

# G8K Ferrule for G8K Spiral Hose




| Part No. | Descr. | Prod. No. | ⟷ | | L | |
|---|---|---|---|---|---|---|
| | | | " | mm | " | mm |
| G19995-0012 | 12G8K1F | 7347-80205 | 3/4 | 19.1 | 2.56 | 65.0 |
| G19995-0016 | 16G8K1F | 7347-80065 | 1 | 25.4 | 2.60 | 66.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# HYDRAULIC HOSE FOR GLOBALSPIRAL™ COUPLINGS




Also available with MegaTuff® cover




Also available with MegaTuff® cover







Also available with MegaTuff® and XtraTuff® cover




Also available with MegaTuff® and XtraTuff® cover




Also available with MegaTuff® and XtraTuff® cover







Also available with MegaTuff® cover










Also available with MegaTuff® and XtraTuff® cover




Also available with MegaTuff® and XtraTuff® cover







Also available with MegaTuff® cover

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# HYDRAULIC HOSE FOR GLOBALSPIRAL™ COUPLINGS - CONTINUED




Also available with MegaTuff® and XtraTuff® cover













Also available with MegaTuff® cover



















Also available with MegaTuff® and XtraTuff® cover







For GlobalSpiral™ Plus Couplings




For GlobalSpiral™ Plus Couplings

# HYDRAULIC HOSE FOR GLOBALSPIRAL™ COUPLINGS - CONTINUED




For GlobalSpiral™ Plus Couplings







For GlobalSpiral™ Plus Couplings




Also available with MegaTuff® cover. For GlobalSpiral™ Plus Couplings




**The Gates eCrimp program** is a web based utility which allows users and distributors of Gates hydraulic and industrial hose products to find and print the most up to date crimp specifications with nothing more than an internet browser.

This program can be used to find crimp data for all Gates crimpers. Custom result may be printed by selecting the crimper, hose and coupling. Optionally results may also be limited by die set and working pressure.


The eCrimp web application can be directly accessed from a web browser by entering http://eCrimp.Gates.com for the website.


**The eCrimp mobile app** is available for download for the iPhone and iPad from the App Store.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Male Pipe (NPTF - 30° Cone Seat)





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G20100-0606 | 6GS-6MP | 7347-20145 | 3/8 | 9.5 | 3/8–18 | 11/16 | 2.72 | 69.1 | 1.31 | 33.3 |
| G20100-0608 | 6GS-8MP | 7347-20155 | 3/8 | 9.5 | 1/2–14 | 7/8 | 2.87 | 72.9 | 1.46 | 37.1 |
| G20100-0808 | 8GS-8MP | 7347-20245 | 1/2 | 12.7 | 1/2–14 | 7/8 | 2.91 | 73.9 | 1.43 | 36.3 |
| G20100-0812 | 8GS-12MP | 7347-20265 | 1/2 | 12.7 | 3/4–14 | 1 1/16 | 3.03 | 77.0 | 1.56 | 39.6 |
| G20100-1008 | 10GS-8MP | 7347-20335 | 5/8 | 15.9 | 1/2–14 | 15/16 | 3.35 | 85.1 | 1.34 | 34.0 |
| G20100-1012 | 10GS-12MP | 7347-20355 | 5/8 | 15.9 | 3/4–14 | 1 1/8 | 3.58 | 90.9 | 1.60 | 40.6 |
| G20100-1208 | 12GS-8MP | 7347-20425 | 3/4 | 19.1 | 1/2–14 | 1 1/16 | 3.54 | 89.9 | 1.54 | 39.1 |
| G20100-1212 | 12GS-12MP | 7347-20445 | 3/4 | 19.1 | 3/4–14 | 1 1/16 | 3.54 | 89.9 | 1.54 | 39.1 |
| G20100-1216 | 12GS-16MP | 7347-20465 | 3/4 | 19.1 | 1–11 1/2 | 1 3/8 | 3.82 | 97.0 | 1.81 | 46.0 |
| G20100-1612 | 16GS-12MP | 7347-20535 | 1 | 25.4 | 3/4–14 | 1 3/8 | 3.98 | 101.1 | 1.74 | 44.2 |
| G20100-1616 | 16GS-16MP | 7347-20555 | 1 | 25.4 | 1–11 1/2 | 1 3/8 | 4.17 | 105.9 | 1.94 | 49.3 |
| G20100-1620 | 16GS-20MP | 7347-20565 | 1 | 25.4 | 1 1/4–11 1/2 | 1 3/4 | 4.29 | 109.0 | 2.06 | 52.3 |
| G20100-2020 | 20GS-20MP | 7347-20645 | 1 1/4 | 31.8 | 1 1/4–11 1/2 | 1 3/4 | 5.00 | 127.0 | 2.20 | 55.9 |


# API Line Pipe Connection





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G20102-2020 | 20GS-20API-LP | 7347-76955 | 1 1/4 | 31.8 | 1 1/4–11 1/2 | 1 3/4 | 5.51 | 140.0 | 2.70 | 68.6 |

# Male Pipe (NPTF - 30° Cone Seat) - Long Hex









| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | mm | " | mm |
| G20103-1616 | 16GS-16MPLH | 7347-76545 | 1 | 25.4 | 1–11 1/2 | | 1 3/8 | 5.16 | 131.1 | 2.92 | 74.2 |

# Male O-Ring Boss

SAE J1926/2 ISO 11926–2 Heavy Duty (S Series) Stud End.








| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | mm | " | mm |
| G20120-0606 | 6GS-6MB | 7347-21145 | 3/8 | 9.5 | 9/16–18 | | 11/16 | 2.56 | 65.0 | 1.15 | 29.2 |
| G20120-0808 | 8GS-8MB | 7347-21245 | 1/2 | 12.7 | 3/4–16 | | 7/8 | 2.76 | 70.1 | 1.26 | 32.0 |
| G20120-0810 | 8GS-10MB | 7347-21255 | 1/2 | 12.7 | 7/8–14 | | 1 | 2.83 | 71.9 | 1.34 | 34.0 |
| G20120-1010 | 10GS-10MB | 7347-21345 | 5/8 | 15.9 | 7/8–14 | | 1 | 3.46 | 87.9 | 1.48 | 37.6 |
| G20120-1012 | 10GS-12MB | 7347-21355 | 5/8 | 15.9 | 1 1/16–12 | | 1 1/4 | 3.46 | 87.9 | 1.48 | 37.6 |
| G20120-1212 | 12GS-12MB | 7347-21445 | 3/4 | 19.1 | 1 1/16–12 | | 1 1/4 | 3.66 | 93.0 | 1.65 | 41.9 |
| G20120-1216 | 12GS-16MB | 7347-21465 | 3/4 | 19.1 | 1 5/16–12 | | 1 1/2 | 3.54 | 89.9 | 1.54 | 39.1 |
| G20120-1612 | 16GS-12MB | 7347-21535 | 1 | 25.4 | 1 1/16–12 | | 1 3/8 | 3.98 | 101.1 | 1.74 | 44.2 |
| G20120-1616 | 16GS-16MB | 7347-21555 | 1 | 25.4 | 1 5/16–12 | | 1 1/2 | 3.86 | 98.1 | 1.62 | 41.2 |
| G20120-1620 | 16GS-20MB | 7347-21565 | 1 | 25.4 | 1 5/8–12 | | 1 7/8 | 4.53 | 115.1 | 1.62 | 41.2 |
| G20120-2020 | 20GS-20MB | 7347-21645 | 1 1/4 | 31.8 | 1 5/8–12 | | 1 7/8 | 4.53 | 115.1 | 1.73 | 43.9 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female MegaSeal® Swivel


Gates High Performance Replacement for Female JIC Fittings – Connects to Standard Male JIC Termination.




| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G20140-1212 | 12GS-12FMX | 7347-69445 | 3/4 | 19.1 | 1 1/16–12 | 1 1/8 | 1 1/4 | 4.02 | 102.1 | 2.02 | 51.3 |
| G20140-1216 | 12GS-16FMX | 7347-69465 | 3/4 | 19.1 | 1 5/16–12 | 1 1/8 | 1 1/2 | 4.06 | 103.1 | 2.06 | 52.3 |
| G20140-1616 | 16GS-16FMX | 7347-69555 | 1 | 25.4 | 1 5/16–12 | 1 1/2 | 1 1/2 | 4.37 | 111.0 | 2.15 | 54.6 |
| G20140-2020 | 20GS-20FMX | 7347-69645 | 1 1/4 | 31.8 | 1 5/8–12 | 1 7/8 | 2 | 5.36 | 136.1 | 2.56 | 65.0 |

# Female MegaSeal® Swivel - 45° Bent Tube


Gates High Performance Replacement for Female JIC Fittings – Connects to Standard Male JIC Termination.




| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G20145-1212 | 12GS-12FMX45-032 | 7347-73275 | 3/4 | 19.1 | 1 1/16–12 | 1 1/4 | 1.26 | 32.0 | 5.08 | 129.0 | 3.07 | 78.0 |
| G20145-1616 | 16GS-16FMX45-038 | 7347-70555 | 1 | 25.4 | 1 5/16–12 | 1 1/2 | 1.50 | 38.1 | 6.26 | 159.0 | 4.04 | 102.6 |
| G20145-2020 | 20GS-20FMX45-041 | 7347-70645 | 1 1/4 | 31.8 | 1 5/8–12 | 2 | 1.61 | 40.9 | 7.47 | 189.7 | 4.67 | 118.6 |


# Female MegaSeal® Swivel - 90° Bent Tube


Gates High Performance Replacement for Female JIC Fittings – Connects to Standard Male JIC Termination.




| Part No. | Descr. | Prod. No. | ⊖ | | ⫼ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G20149-1212 | 12GS-12FMX90-048 | 7347-71445 | 3/4 | 19.1 | 1 1/16–12 | 1 1/4 | 1.89 | 48.0 | 4.72 | 119.9 | 2.72 | 69.1 |
| G20150-1212 | 12GS-12FMX90-058 | 7347-71395 | 3/4 | 19.1 | 1 1/16–12 | 1 1/4 | 2.28 | 57.9 | 4.72 | 119.9 | 2.72 | 69.1 |
| G20151-1212 | 12GS-12FMX90-096 | 7347-71405 | 3/4 | 19.1 | 1 1/16–12 | 1 1/4 | 3.78 | 96.0 | 4.72 | 119.9 | 2.72 | 69.1 |
| G20150-1216 | 12GS-16FMX90-056 | 7347-71465 | 3/4 | 19.1 | 1 5/16–12 | 1 1/2 | 2.20 | 55.9 | 5.39 | 136.9 | 3.39 | 86.1 |
| G20149-1616 | 16GS-16FMX90-056 | 7347-71555 | 1 | 25.4 | 1 5/16–12 | 1 1/2 | 2.20 | 55.9 | 5.67 | 144.0 | 3.45 | 87.6 |
| G20150-1616 | 16GS-16FMX90-071 | 7347-71505 | 1 | 25.4 | 1 5/16–12 | 1 1/2 | 2.80 | 71.1 | 5.67 | 144.0 | 3.45 | 87.6 |

# Male JIC 37° Flare









| Part No. | Descr. | Prod. No. | ⊖ | | ⫼ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G20165-0606 | 6GS-6MJ | 7347-22145 | 3/8 | 9.5 | 9/16–18 | 11/16 | 2.60 | 66.0 | 1.19 | 30.2 |
| G20165-0608 | 6GS-8MJ | 7347-22155 | 3/8 | 9.5 | 3/4–16 | 13/16 | 2.76 | 70.1 | 1.35 | 34.3 |
| G20165-0610 | 6GS-10MJ | 7347-22165 | 3/8 | 9.5 | 7/8–14 | 15/16 | 3.03 | 77.0 | 1.62 | 41.2 |
| G20165-0808 | 8GS-8MJ | 7347-22245 | 1/2 | 12.7 | 3/4–16 | 13/16 | 2.83 | 71.9 | 1.36 | 34.5 |
| G20165-0810 | 8GS-10MJ | 7347-22255 | 1/2 | 12.7 | 7/8–14 | 7/8 | 2.95 | 74.9 | 1.48 | 37.6 |
| G20165-1010 | 10GS-10MJ | 7347-22345 | 5/8 | 15.9 | 7/8–14 | 15/16 | 3.62 | 92.0 | 1.64 | 41.7 |
| G20165-1012 | 10GS-12MJ | 7347-22355 | 5/8 | 15.9 | 1 1/16–12 | 1 1/16 | 3.70 | 94.0 | 1.72 | 43.7 |
| G20165-1212 | 12GS-12MJ | 7347-22445 | 3/4 | 19.1 | 1 1/16–12 | 1 1/8 | 3.66 | 93.0 | 1.65 | 41.9 |
| G20165-1214 | 12GS-14MJ | 7347-22455 | 3/4 | 19.1 | 1 3/16–12 | 1 1/4 | 3.70 | 94.0 | 1.69 | 42.9 |
| G20165-1216 | 12GS-16MJ | 7347-22465 | 3/4 | 19.1 | 1 5/16–12 | 1 5/16 | 3.78 | 96.0 | 1.77 | 45.0 |
| G20165-1616 | 16GS-16MJ | 7347-22555 | 1 | 25.4 | 1 5/16–12 | 1 3/8 | 4.09 | 103.9 | 1.86 | 47.2 |
| G20165-1620 | 16GS-20MJ | 7347-22585 | 1 | 25.4 | 1 5/8–12 | 1 3/4 | 4.27 | 108.5 | 2.04 | 51.8 |
| G20165-2020 | 20GS-20MJ | 7347-22645 | 1 1/4 | 31.8 | 1 5/8–12 | 1 3/4 | 4.92 | 125.0 | 2.12 | 53.9 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female JIC 37° Flare Swivel









| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G20170-0606 | 6GS-6FJX | 7347-24145 | 3/8 | 9.5 | 9/16–18 | 3/4 | 3/4 | 2.72 | 69.1 | 1.31 | 33.3 |
| G20170-0608 | 6GS-8FJX | 7347-24155 | 3/8 | 9.5 | 3/4–16 | 3/4 | 7/8 | 2.80 | 71.1 | 1.39 | 35.3 |
| G20170-0808 | 8GS-8FJX | 7347-24245 | 1/2 | 12.7 | 3/4–16 | 7/8 | 7/8 | 2.83 | 71.9 | 1.36 | 34.5 |
| G20170-0810 | 8GS-10FJX | 7347-24255 | 1/2 | 12.7 | 7/8–14 | 7/8 | 1 1/16 | 2.99 | 76.0 | 1.51 | 38.4 |
| G20170-0812 | 8GS-12FJX | 7347-24265 | 1/2 | 12.7 | 1 1/16–12 | 7/8 | 1 1/4 | 3.03 | 77.0 | 1.56 | 39.6 |
| G20170-1010 | 10GS-10FJXMM | 7347-82175 | 5/8 | 15.9 | 7/8–14 | 1 | 1 1/16 | 3.68 | 93.5 | 1.70 | 43.2 |
| G20170-1012 | 10GS-12FJX | 7347-24355 | 5/8 | 15.9 | 1 1/16–12 | 1 | 1 1/4 | 3.74 | 95.0 | 1.76 | 44.7 |
| G20170-1210 | 12GS-10FJX | 7347-24435 | 3/4 | 19.1 | 7/8–14 | 1 1/16 | 1 1/8 | 3.87 | 98.3 | 1.87 | 47.5 |
| G20170-1212 | 12GS-12FJX | 7347-24445 | 3/4 | 19.1 | 1 1/16–12 | 1 | 1 1/4 | 3.87 | 98.3 | 1.86 | 47.2 |
| G20170-1214 | 12GS-14FJX | 7347-24455 | 3/4 | 19.1 | 1 3/16–12 | 1 1/8 | 1 3/8 | 4.06 | 103.1 | 2.06 | 52.3 |
| G20170-1216 | 12GS-16FJX | 7347-24465 | 3/4 | 19.1 | 1 5/16–12 | 1 1/4 | 1 1/2 | 4.02 | 102.1 | 2.01 | 51.1 |
| G20170-1612 | 16GS-12FJX | 7347-24535 | 1 | 25.4 | 1 1/16–12 | 1 3/8 | 1 3/8 | 4.25 | 108.0 | 2.00 | 50.8 |
| G20170-1614 | 16GS-14FJX | 7347-24545 | 1 | 25.4 | 1 3/16–12 | 1 3/8 | 1 1/2 | 4.25 | 108.0 | 2.01 | 51.1 |
| G20170-1616 | 16GS-16FJX | 7347-24555 | 1 | 25.4 | 1 5/16–12 | 1 1/2 | 1 1/2 | 4.30 | 109.2 | 2.07 | 52.6 |
| G20170-1620 | 16GS-20FJX | 7347-24565 | 1 | 25.4 | 1 5/8–12 | 1 1/2 | 2 | 4.53 | 115.1 | 2.31 | 58.7 |
| G20170-2016 | 20GS-16FJX | 7347-24635 | 1 1/4 | 31.8 | 1 5/16–12 | 1 3/4 | 1 5/8 | 5.08 | 129.0 | 2.28 | 57.9 |
| G20170-2020 | 20GS-20FJX | 7347-24645 | 1 1/4 | 31.8 | 1 5/8–12 | 1 7/8 | 2 | 5.29 | 134.4 | 2.56 | 65.0 |
| G20170-2024 | 20GS-24FJX | 7347-24655 | 1 1/4 | 31.8 | 1 7/8–12 | 1 7/8 | 2 3/8 | 5.39 | 136.9 | 2.59 | 65.8 |

# Female JIC 37° Flare Swivel - 30° Bent Tube


S, M and L Drops per ISO Final Draft International Standard 12151–S.





| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G20172-1616 | 16GS-16FJX30M | 7347-73055 | 1 | 25.4 | 1 5/16–12 | 1 1/2 | 1.06 | 26.9 | 6.02 | 152.9 | 3.80 | 96.5 |


# Female JIC 37° Flare Swivel - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | mm | " | mm | " | mm |
| G20174-0606 | 6GS-6FJX45S | 7347-25145 | 3/8 | 9.5 | 9/16–18 | 3/4 | .43 | 11.0 | 3.23 | 82.0 | 1.82 | 46.2 |
| G20174-0608 | 6GS-8FJX45S | 7347-25155 | 3/8 | 9.5 | 3/4–16 | 7/8 | .59 | 15.0 | 3.66 | 93.0 | 2.25 | 57.2 |
| G20174-0808 | 8GS-8FJX45S | 7347-25245 | 1/2 | 12.7 | 3/4–16 | 7/8 | .59 | 15.0 | 3.70 | 94.0 | 2.22 | 56.4 |
| G20174-0810 | 8GS-10FJX45S | 7347-25255 | 1/2 | 12.7 | 7/8–14 | 1 1/16 | .63 | 16.0 | 3.58 | 90.9 | 2.11 | 53.6 |
| G20175-1010 | 10GS-10FJXMM45-018 | 7347-83275 | 5/8 | 15.9 | 7/8–14 | 1 1/16 | .71 | 18.0 | 4.45 | 113.0 | 2.48 | 63.0 |
| G20174-1012 | 10GS-12FJX45S | 7347-25355 | 5/8 | 15.9 | 1 1/16–12 | 1 1/4 | .83 | 21.1 | 4.80 | 121.9 | 2.82 | 71.6 |
| G20174-1212 | 12GS-12FJX45S | 7347-25445 | 3/4 | 19.1 | 1 1/16–12 | 1 1/4 | .83 | 21.1 | 5.12 | 130.1 | 3.11 | 79.0 |
| G20174-1216 | 12GS-16FJX45S | 7347-25465 | 3/4 | 19.1 | 1 5/16–12 | 1 1/2 | .94 | 23.9 | 5.39 | 136.9 | 3.39 | 86.1 |
| G20174-1616 | 16GS-16FJX45S | 7347-25555 | 1 | 25.4 | 1 5/16–12 | 1 1/2 | .94 | 23.9 | 5.98 | 151.9 | 3.77 | 95.8 |
| G20175-1616 | 16GS-16FJX45M | 7347-26555 | 1 | 25.4 | 1 5/16–12 | 1 1/2 | 1.50 | 38.1 | 6.30 | 160.0 | 4.07 | 103.4 |
| G20174-1620 | 16GS-20FJX45S | 7347-25565 | 1 | 25.4 | 1 5/8–12 | 2 | .98 | 24.9 | 6.46 | 164.1 | 4.23 | 107.4 |
| G20175-2020 | 20GS-20FJX45-038 | 7347-76175 | 1 1/4 | 31.8 | 1 5/8–12 | 2 | 1.50 | 38.1 | 7.09 | 180.1 | 4.29 | 109.0 |

# Female JIC 37° Flare Swivel - 60° Bent Tube









| Part No. | Descr. | Prod. No. | ⟷ | | ||| H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | mm | " | mm | " | mm |
| G20177-1212 | 12GS-12FJX60-043 | 7347-76795 | 3/4 | 19.1 | 1 1/16–12 | 1 1/4 | 1.69 | 42.9 | 5.59 | 142.0 | 3.58 | 90.9 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female JIC 37° Flare Swivel - 90° Bent Tube









| Part No. | Descr. | Prod. No. | ⟷ | | ≡ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G20179-0606 | 6GS-6FJX90S | 7347-27145 | 3/8 | 9.5 | 9/16–18 | 3/4 | .91 | 23.1 | 3.11 | 79.0 | 1.70 | 43.2 |
| G20180-0606 | 6GS-6FJXMM90M | 7347-84045 | 3/8 | 9.5 | 9/16–18 | 3/4 | 1.50 | 38.1 | 3.11 | 79.0 | 1.70 | 43.2 |
| G20181-0606 | 6GS-6FJX90L | 7347-29145 | 3/8 | 9.5 | 9/16–18 | 3/4 | 2.13 | 54.1 | 3.39 | 86.1 | 1.98 | 50.3 |
| G20180-0608 | 6GS-8FJX90M | 7347-28155 | 3/8 | 9.5 | 3/4–16 | 7/8 | 1.61 | 40.9 | 3.58 | 90.9 | 2.17 | 55.1 |
| G20182-0608 | 6GS-8FJX90-083 | 7347-76785 | 3/8 | 9.5 | 3/4–16 | 7/8 | 3.27 | 83.1 | 3.58 | 90.9 | 2.17 | 55.1 |
| G20179-0808 | 8GS-8FJX90S | 7347-27245 | 1/2 | 12.7 | 3/4–16 | 7/8 | 1.14 | 29.0 | 3.39 | 86.1 | 1.91 | 48.5 |
| G20180-0808 | 8GS-8FJX90M | 7347-28245 | 1/2 | 12.7 | 3/4–16 | 7/8 | 1.61 | 40.9 | 3.62 | 92.0 | 2.15 | 54.6 |
| G20181-0808 | 8GS-8FJX90L | 7347-29245 | 1/2 | 12.7 | 3/4–16 | 7/8 | 2.52 | 64.0 | 3.62 | 92.0 | 2.15 | 54.6 |
| G20182-0808 | 8GS-8FJX90XL | 7347-73065 | 1/2 | 12.7 | 3/4–16 | 7/8 | 4.06 | 103.1 | 3.62 | 92.0 | 2.15 | 54.6 |
| G20179-0810 | 8GS-10FJX90S | 7347-27255 | 1/2 | 12.7 | 7/8–14 | 1 1/16 | 1.26 | 32.0 | 3.62 | 92.0 | 2.15 | 54.6 |
| G20180-0810 | 8GS-10FJX90M | 7347-28165 | 1/2 | 12.7 | 7/8–14 | 1 1/16 | 1.85 | 47.0 | 3.50 | 88.9 | 2.01 | 51.1 |
| G20181-0810 | 8GS-10FJX90L | 7347-29255 | 1/2 | 12.7 | 7/8–14 | 1 1/16 | 3.27 | 83.1 | 3.74 | 95.0 | 2.26 | 57.4 |
| G20179-0812 | 8GS-12FJX90S | 7347-27265 | 1/2 | 12.7 | 1 1/16–12 | 1 1/4 | 1.89 | 48.0 | 4.37 | 111.0 | 2.89 | 73.4 |
| G20179-1010 | 10GS-10FJXMM90-036 | 7347-84275 | 5/8 | 15.9 | 7/8–14 | 1 1/16 | 1.42 | 36.1 | 4.37 | 111.0 | 2.40 | 61.0 |
| G20180-1010 | 10GS-10FJXMM90M | 7347-84285 | 5/8 | 15.9 | 7/8–14 | 1 1/16 | 1.85 | 47.0 | 4.21 | 106.9 | 2.23 | 56.6 |
| G20180-1012 | 10GS-12FJX90M | 7347-28355 | 5/8 | 15.9 | 1 1/16–12 | 1 1/4 | 2.28 | 57.9 | 4.76 | 120.9 | 2.78 | 70.6 |
| G20179-1212 | 12GS-12FJX90S | 7347-27445 | 3/4 | 19.1 | 1 1/16–12 | 1 1/4 | 1.89 | 48.0 | 4.45 | 113.0 | 2.68 | 68.1 |
| G20180-1212 | 12GS-12FJX90M | 7347-28445 | 3/4 | 19.1 | 1 1/16–12 | 1 1/4 | 2.28 | 57.9 | 4.45 | 113.0 | 2.44 | 62.0 |
| G20181-1212 | 12GS-12FJX90L | 7347-29445 | 3/4 | 19.1 | 1 1/16–12 | 1 1/4 | 3.78 | 96.0 | 4.45 | 113.0 | 2.44 | 62.0 |
| G20180-1214 | 12GS-14FJX90-060 | 7347-28455 | 3/4 | 19.1 | 1 3/16–12 | 1 3/8 | 2.36 | 59.9 | 5.55 | 141.0 | 3.54 | 89.9 |
| G20179-1216 | 12GS-16FJX90S | 7347-27465 | 3/4 | 19.1 | 1 5/16–12 | 1 1/2 | 2.20 | 55.9 | 5.31 | 134.9 | 3.31 | 84.1 |
| G20180-1216 | 12GS-16FJX90M | 7347-28465 | 3/4 | 19.1 | 1 5/16–12 | 1 1/2 | 2.80 | 71.1 | 5.31 | 134.9 | 3.31 | 84.1 |
| G20181-1216 | 12GS-16FJX90L | 7347-29465 | 3/4 | 19.1 | 1 5/16–12 | 1 1/2 | 4.49 | 114.1 | 5.32 | 135.1 | 3.31 | 84.1 |
| G20179-1616 | 16GS-16FJX90S | 7347-27555 | 1 | 25.4 | 1 5/16–12 | 1 1/2 | 2.20 | 55.9 | 5.67 | 144.0 | 3.45 | 87.6 |
| G20180-1616 | 16GS-16FJX90M | 7347-28555 | 1 | 25.4 | 1 5/16–12 | 1 1/2 | 2.80 | 71.1 | 5.67 | 144.0 | 3.45 | 87.6 |
| G20181-1616 | 16GS-16FJX90L | 7347-29555 | 1 | 25.4 | 1 5/16–12 | 1 1/2 | 4.33 | 110.0 | 5.67 | 144.0 | 3.45 | 87.6 |
| G20181-1620 | 16GS-20FJX90L | 7347-29565 | 1 | 25.4 | 1 5/8–12 | 2 | 5.08 | 129.0 | 6.06 | 153.9 | 3.84 | 97.5 |
| G20179-2020 | 20GS-20FJX90S | 7347-27645 | 1 1/4 | 31.8 | 1 5/8–12 | 2 | 2.52 | 64.0 | 6.85 | 174.0 | 4.05 | 102.9 |
| G20180-2020 | 20GS-20FJX90M | 7347-28645 | 1 1/4 | 31.8 | 1 5/8–12 | 2 | 3.07 | 78.0 | 6.85 | 174.0 | 4.05 | 102.9 |
| G20181-2020 | 20GS-20FJX90L | 7347-29645 | 1 1/4 | 31.8 | 1 5/8–12 | 2 | 5.08 | 129.0 | 6.85 | 174.0 | 4.05 | 102.9 |
| G20180-2024 | 20GS-24FJX90M | 7347-28655 | 1 1/4 | 31.8 | 1 7/8–12 | 2 3/8 | 3.39 | 86.1 | 7.32 | 185.9 | 4.52 | 114.8 |

# Male Flat-Face O-Ring

Includes Peroxide–cured O–Ring.
Metric Hex per ISO Draft International Standard 12151–1.
Utilizes SAE J1453 Captive O–Ring Groove for Improved O–Ring Retention.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G20225-0606 | 6GS-6MFFOR | 7347-23865 | 3/8 | 9.5 | 11/16–16 | | 19 | 2.52 | 64.0 | 1.11 | 28.2 |
| G20225-0808 | 8GS-8MFFOR | 7347-23825 | 1/2 | 12.7 | 13/16–16 | | 22 | 2.68 | 68.1 | 1.20 | 30.5 |
| G20225-0810 | 8GS-10MFFOR | 7347-23895 | 1/2 | 12.7 | 1–14 | | 27 | 2.91 | 73.9 | 1.44 | 36.6 |
| G20225-1010 | 10GS-10MFFOR | 7347-23875 | 5/8 | 15.9 | 1–14 | | 27 | 3.42 | 86.9 | 1.44 | 36.6 |
| G20225-1012 | 10GS-12MFFOR | 7347-23885 | 5/8 | 15.9 | 1 3/16–12 | | 32 | 3.50 | 88.9 | 1.52 | 38.6 |
| G20225-1212 | 12GS-12MFFOR | 7347-23835 | 3/4 | 19.1 | 1 3/16–12 | | 32 | 3.50 | 88.9 | 1.50 | 38.1 |
| G20225-1216 | 12GS-16MFFOR | 7347-23845 | 3/4 | 19.1 | 1 7/16–12 | | 41 | 3.74 | 95.0 | 1.73 | 43.9 |
| G20225-1616 | 16GS-16MFFOR | 7347-23815 | 1 | 25.4 | 1 7/16–12 | | 41 | 4.02 | 102.1 | 1.78 | 45.2 |
| G20225-1620 | 16GS-20MFFOR | 7347-23925 | 1 | 25.4 | 1 11/16–12 | | 50 | 4.17 | 106.0 | 1.78 | 45.2 |
| G20225-2020 | 20GS-20MFFOR | 7347-23855 | 1 1/4 | 31.8 | 1 11/16–12 | | 50 | 4.72 | 119.9 | 1.93 | 49.0 |

# Female Flat-Face O-Ring Swivel

Metric Hex per ISO Draft International Standard 12151–1.
SAE J1453 O–Ring Face Seal.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | mm | " | mm | " | mm |
| G20230-0606 | 6GS-6FFORX | 7347-30145 | 3/8 | 9.5 | 11/16–16 | | 22 | 22 | 2.72 | 69.1 | 1.31 | 33.3 |
| G20230-0608 | 6GS-8FFORX | 7347-30155 | 3/8 | 9.5 | 13/16–16 | | 22 | 24 | 2.83 | 71.9 | 1.43 | 36.3 |
| G20230-0808 | 8GS-8FFORX | 7347-30245 | 1/2 | 12.7 | 13/16–16 | | 24 | 24 | 2.87 | 72.9 | 1.40 | 35.6 |
| G20230-0810 | 8GS-10FFORX | 7347-30255 | 1/2 | 12.7 | 1–14 | | 24 | 30 | 3.07 | 78.0 | 1.59 | 40.4 |
| G20230-0812 | 8GS-12FFORX | 7347-30265 | 1/2 | 12.7 | 1 3/16–12 | | 24 | 36 | 3.11 | 79.0 | 1.63 | 41.4 |
| G20230-1010 | 10GS-10FFORX | 7347-30345 | 5/8 | 15.9 | 1–14 | | 30 | 30 | 3.70 | 94.0 | 1.72 | 43.7 |
| G20230-1012 | 10GS-12FFORX | 7347-30355 | 5/8 | 15.9 | 1 3/16–12 | | 30 | 36 | 3.74 | 95.0 | 1.76 | 44.7 |
| G20230-1210 | 12GS-10FFORX | 7347-30435 | 3/4 | 19.1 | 1–14 | | 32 | 30 | 3.82 | 97.0 | 1.81 | 46.0 |
| G20230-1212 | 12GS-12FFORX | 7347-30445 | 3/4 | 19.1 | 1 3/16–12 | | 32 | 36 | 1.95 | 49.5 | 1.89 | 48.1 |
| G20230-1216 | 12GS-16FFORX | 7347-30465 | 3/4 | 19.1 | 1 7/16–12 | | 32 | 41 | 4.06 | 103.1 | 2.05 | 52.1 |
| G20230-1220 | 12GS-20FFORX | 7347-30475 | 3/4 | 19.1 | 1 11/16–12 | | 32 | 50 | 3.91 | 99.3 | 1.90 | 48.3 |
| G20230-1612 | 16GS-12FFORX | 7347-30535 | 1 | 25.4 | 1 3/16–12 | | 36 | 36 | 5.15 | 130.8 | 2.92 | 74.2 |
| G20230-1616 | 16GS-16FFORX | 7347-30555 | 1 | 25.4 | 1 7/16–12 | | 41 | 41 | 4.36 | 110.7 | 2.14 | 54.4 |
| G20230-1620 | 16GS-20FFORX | 7347-30565 | 1 | 25.4 | 1 11/16–12 | | 41 | 50 | 4.36 | 110.7 | 2.14 | 54.4 |

## Female Flat-Face O-Ring Swivel - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G20230-2020 | 20GS-20FFORX | 7347-30645 | 1 1/4 | 31.8 | 1 11/16–12 | 50 | 50 | 5.04 | 128.0 | 2.24 | 56.9 |
| G20230-2024 | 20GS-24FFORX | 7347-30655 | 1 1/4 | 31.8 | 2–12 | 50 | 60 | 5.12 | 130.1 | 2.32 | 58.9 |


## Female Flat-Face O-Ring Swivel - 22 1/2° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20232-1616 | 16GS-16FFORX22-011 | 7347-78615 | 1 | 25.4 | 1 7/16–12 | 41 | .43 | 11.0 | 5.87 | 149.1 | 3.68 | 93.5 |

## Female Flat-Face O-Ring Swivel - 30° Bent Tube









| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20233-1616 | 16GS-16FFORX30-14 | 7347-76345 | 1 | 25.4 | 1 7/16–12 | 41 | .55 | 14.0 | 5.87 | 149.1 | 3.64 | 92.5 |

# Female Flat-Face O-Ring Swivel - 45° Bent Tube

Metric Hex per ISO Draft International Standard 12151–1.
SAE J1453 O–Ring Face Seal.









| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20234-0606 | 6GS-6FFORX45S | 7347-31145 | 3/8 | 9.5 | 11/16–16 | 22 | .43 | 11.0 | 3.23 | 82.0 | 1.82 | 46.2 |
| G20234-0608 | 6GS-8FFORX45S | 7347-31155 | 3/8 | 9.5 | 13/16–16 | 24 | .59 | 15.0 | 3.66 | 93.0 | 2.25 | 57.2 |
| G20234-0808 | 8GS-8FFORX45S | 7347-31245 | 1/2 | 12.7 | 13/16–16 | 24 | .59 | 15.0 | 3.70 | 94.0 | 2.22 | 56.4 |
| G20234-0810 | 8GS-10FFORX45S | 7347-31255 | 1/2 | 12.7 | 1–14 | 24 | .63 | 16.0 | 3.90 | 99.1 | 2.42 | 61.5 |
| G20234-0812 | 8GS-12FFORX45S | 7347-31265 | 1/2 | 12.7 | 1 3/16–12 | 24 | .83 | 21.1 | 4.53 | 115.1 | 3.05 | 77.5 |
| G20234-1010 | 10GS-10FFORX45S | 7347-31345 | 5/8 | 15.9 | 1–14 | 30 | .63 | 16.0 | 4.37 | 111.0 | 2.39 | 60.7 |
| G20234-1212 | 12GS-12FFORX45S | 7347-31445 | 3/4 | 19.1 | 1 3/16–12 | 36 | .83 | 21.1 | 4.92 | 125.0 | 2.91 | 73.9 |
| G20234-1216 | 12GS-16FFORX45S | 7347-31465 | 3/4 | 19.1 | 1 7/16–12 | 24 | .94 | 23.9 | 5.39 | 136.9 | 3.39 | 86.1 |
| G20234-1616 | 16GS-16FFORX45S | 7347-31555 | 1 | 25.4 | 1 7/16–12 | 24 | .94 | 23.9 | 5.67 | 144.0 | 3.46 | 87.9 |
| G20234-1620 | 16GS-20FFORX45S | 7347-31565 | 1 | 25.4 | 1 11/16–12 | 50 | .98 | 24.9 | 6.46 | 164.1 | 4.24 | 107.7 |
| G20234-2020 | 20GS-20FFORX45-032 | 7347-76045 | 1 1/4 | 31.8 | 1 11/16–12 | 50 | 1.26 | 32.0 | 7.09 | 180.1 | 4.29 | 109.0 |

# Female Flat-Face O-Ring Swivel - 90° Bent Tube

Metric Hex per ISO Draft International Standard 12151–1.
SAE J1453 O–Ring Face Seal.





| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20239-0606 | 6GS-6FFORX90S | 7347-32145 | 3/8 | 9.5 | 11/16–16 | 22 | .91 | 23.1 | 3.07 | 78.0 | 1.66 | 42.2 |
| G20241-0606 | 6GS-6FFORX90L | 7347-34145 | 3/8 | 9.5 | 11/16–16 | 22 | 2.13 | 54.1 | 3.35 | 85.1 | 1.94 | 49.3 |
| G20240-0608 | 6GS-8FFORX90M | 7347-33155 | 3/8 | 9.5 | 13/16–16 | 24 | 1.61 | 40.9 | 3.35 | 85.1 | 1.94 | 49.3 |
| G20239-0808 | 8GS-8FFORX90S | 7347-32245 | 1/2 | 12.7 | 13/16–16 | 24 | 1.14 | 29.0 | 3.39 | 86.1 | 1.91 | 48.5 |
| G20240-0808 | 8GS-8FFORX90M | 7347-33245 | 1/2 | 12.7 | 13/16–16 | 24 | 1.61 | 40.9 | 3.39 | 86.1 | 1.91 | 48.5 |
| G20241-0808 | 8GS-8FFORX90-083 | 7347-73845 | 1/2 | 12.7 | 13/16–16 | 24 | 3.27 | 83.1 | 3.39 | 86.1 | 1.91 | 48.5 |
| G20239-0810 | 8GS-10FFORX90S | 7347-32255 | 1/2 | 12.7 | 1–14 | 30 | 1.26 | 32.0 | 3.98 | 101.1 | 2.50 | 63.5 |
| G20240-0810 | 8GS-10FFORX90M | 7347-33255 | 1/2 | 12.7 | 1–14 | 30 | 1.85 | 47.0 | 3.98 | 101.1 | 2.50 | 63.5 |
| G20241-0810 | 8GS-10FFORX90L | 7347-34255 | 1/2 | 12.7 | 1–14 | 30 | 2.76 | 70.1 | 3.98 | 101.1 | 2.50 | 63.5 |
| G20239-0812 | 8GS-12FFORX90S | 7347-32265 | 1/2 | 12.7 | 1 3/16–12 | 36 | 1.89 | 48.0 | 4.21 | 106.9 | 2.74 | 69.6 |
| G20239-1010 | 10GS-10FFORX90S | 7347-32345 | 5/8 | 15.9 | 1–14 | 30 | 1.26 | 32.0 | 4.20 | 106.7 | 2.22 | 56.4 |
| G20240-1010 | 10GS-10FFORX90M | 7347-33345 | 5/8 | 15.9 | 1–14 | 30 | 1.85 | 47.0 | 4.21 | 106.9 | 2.20 | 55.9 |
| G20241-1010 | 10GS-10FFORX90L | 7347-34345 | 5/8 | 15.9 | 1–14 | 30 | 2.76 | 70.1 | 4.45 | 113.0 | 2.44 | 62.0 |


## Female Flat-Face O-Ring Swivel - 90° Bent Tube - Continued

| Part No. | Descr. | Prod. No. | ⟷ | | ≋ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20239-1012 | 10GS-12FFORX90S | 7347-32355 | 5/8 | 15.9 | 1 3/16–12 | 36 | 1.26 | 32.0 | 4.21 | 106.9 | 2.74 | 69.6 |
| G20239-1210 | 12GS-10FFORX90S | 7347-32435 | 3/4 | 19.1 | 1–14 | 30 | 1.26 | 32.0 | 4.37 | 111.0 | 2.36 | 59.9 |
| G20239-1212 | 12GS-12FFORX90S | 7347-32445 | 3/4 | 19.1 | 1 3/16–12 | 36 | 1.89 | 48.0 | 5.04 | 128.0 | 3.03 | 77.0 |
| G20240-1212 | 12GS-12FFORX90M | 7347-33445 | 3/4 | 19.1 | 1 3/16–12 | 36 | 2.28 | 57.9 | 5.04 | 128.0 | 3.03 | 77.0 |
| G20241-1212 | 12GS-12FFORX90L | 7347-34445 | 3/4 | 19.1 | 1 3/16–12 | 36 | 3.78 | 96.0 | 5.04 | 128.0 | 3.03 | 77.0 |
| G20239-1216 | 12GS-16FFORX90S | 7347-32465 | 3/4 | 19.1 | 1 7/16–12 | 41 | 2.20 | 55.9 | 5.39 | 136.9 | 3.39 | 86.1 |
| G20240-1216 | 12GS-16FFORX90M | 7347-33465 | 3/4 | 19.1 | 1 7/16–12 | 41 | 2.80 | 71.1 | 5.39 | 136.9 | 3.39 | 86.1 |
| G20241-1216 | 12GS-16FFORX90L | 7347-34465 | 3/4 | 19.1 | 1 7/16–12 | 41 | 4.49 | 114.1 | 5.39 | 136.9 | 3.39 | 86.1 |
| G20239-1616 | 16GS-16FFORX90S | 7347-32555 | 1 | 25.4 | 1 7/16–12 | 41 | 2.20 | 55.9 | 5.67 | 144.0 | 3.45 | 87.6 |
| G20240-1616 | 16GS-16FFORX90M | 7347-33555 | 1 | 25.4 | 1 7/16–12 | 41 | 2.80 | 71.1 | 5.67 | 144.0 | 3.45 | 87.6 |
| G20241-1616 | 16GS-16FFORX90L | 7347-34555 | 1 | 25.4 | 1 7/16–12 | 41 | 4.49 | 114.1 | 5.67 | 144.0 | 3.45 | 87.6 |
| G20239-1620 | 16GS-20FFORX90S | 7347-32565 | 1 | 25.4 | 1 11/16–12 | 50 | 2.52 | 64.0 | 6.06 | 153.9 | 3.84 | 97.5 |
| G20240-1620 | 16GS-20FFORX90M | 7347-33565 | 1 | 25.4 | 1 11/16–12 | 50 | 3.07 | 78.0 | 6.05 | 153.7 | 3.83 | 97.3 |
| G20241-1620 | 16GS-20FFORX90L | 7347-34565 | 1 | 25.4 | 1 11/16–12 | 50 | 5.08 | 129.0 | 6.05 | 153.7 | 3.83 | 97.3 |
| G20239-2020 | 20GS-20FFORX90S | 7347-32645 | 1 1/4 | 31.8 | 1 11/16–12 | 50 | 2.52 | 64.0 | 6.77 | 172.0 | 3.97 | 100.8 |
| G20240-2020 | 20GS-20FFORX90M | 7347-33645 | 1 1/4 | 31.8 | 1 11/16–12 | 50 | 3.07 | 78.0 | 6.77 | 172.0 | 3.97 | 100.8 |
| G20241-2020 | 20GS-20FFORX90L | 7347-34645 | 1 1/4 | 31.8 | 1 11/16–12 | 50 | 5.08 | 129.0 | 6.77 | 172.0 | 3.97 | 100.8 |
| G20239-2024 | 20GS-24FFORX90-064 | 7347-76985 | 1 1/4 | 31.8 | 2–12 | 60 | 2.52 | 64.0 | 6.77 | 172.0 | 3.97 | 100.8 |

## Female Flat-Face O-Ring Swivel - 135° Bent Tube

Metric Hex per ISO Draft International Standard 12151–1.
SAE J1453 O–Ring Face Seal.





| Part No. | Descr. | Prod. No. | ⟷ | | ≋ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20248-1216 | 12GS-16FFORX135 | 7347-73795 | 3/4 | 19.1 | 1 7/16–12 | 24 | 2.99 | 76.0 | 3.39 | 86.1 | 1.48 | 37.6 |

# Code 61 O-Ring Flange


–8FL, –12FL, –16FL Max. W.P. 5,000 psi; –20FL Max. W.P. 4,000 psi.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20300-0608 | 6GS-8FL | 7347-41155 | 3/8 | 9.5 | 1.19 | 30.2 | 3.54 | 89.9 | 2.13 | 54.1 | .27 | 6.9 |
| G20300-0808 | 8GS-8FL | 7347-41245 | 1/2 | 12.7 | 1.19 | 30.2 | 3.66 | 93.0 | 2.19 | 55.6 | .27 | 6.9 |
| G20300-0812 | 8GS-12FL | 7347-41265 | 1/2 | 12.7 | 1.50 | 38.1 | 3.86 | 98.1 | 2.38 | 60.5 | .27 | 6.9 |
| G20300-0816 | 8GS-16FL | 7347-41285 | 1/2 | 12.7 | 1.75 | 44.5 | 2.84 | 72.1 | 1.37 | 34.8 | .32 | 8.1 |
| G20300-1012 | 10GS-12FL | 7347-41355 | 5/8 | 15.9 | 1.50 | 38.1 | 4.29 | 109.0 | 2.31 | 58.7 | .27 | 6.9 |
| G20300-1208 | 12GS-8FL | 7347-41425 | 3/4 | 19.1 | 1.19 | 30.2 | 4.41 | 112.0 | 2.40 | 61.0 | .27 | 6.9 |
| G20300-1212 | 12GS-12FL | 7347-41445 | 3/4 | 19.1 | 1.50 | 38.1 | 4.37 | 111.0 | 2.36 | 59.9 | .27 | 6.9 |
| G20300-1216 | 12GS-16FL | 7347-41465 | 3/4 | 19.1 | 1.75 | 44.5 | 4.37 | 111.0 | 2.36 | 59.9 | .32 | 8.1 |
| G20300-1220 | 12GS-20FL | 7347-41475 | 3/4 | 19.1 | 2.00 | 50.8 | 4.37 | 111.0 | 2.36 | 59.9 | .32 | 8.1 |
| G20300-1612 | 16GS-12FL | 7347-41535 | 1 | 25.4 | 1.50 | 38.1 | 4.65 | 118.1 | 2.40 | 61.0 | .27 | 6.9 |
| G20300-1616 | 16GS-16FL | 7347-41555 | 1 | 25.4 | 1.75 | 44.5 | 4.92 | 125.0 | 2.70 | 68.6 | .32 | 8.1 |
| G20300-1620 | 16GS-20FL | 7347-41565 | 1 | 25.4 | 2.00 | 50.8 | 4.92 | 125.0 | 2.69 | 68.3 | .32 | 8.1 |
| G20300-1624 | 16GS-24FL | 7347-41575 | 1 | 25.4 | 2.38 | 60.5 | 4.92 | 125.0 | 1.90 | 48.3 | .32 | 8.1 |
| G20300-2016 | 20GS-16FL | 7347-41635 | 1 1/4 | 31.8 | 1.75 | 44.5 | 5.35 | 135.9 | 2.55 | 64.8 | .32 | 8.1 |
| G20300-2020 | 20GS-20FL | 7347-41645 | 1 1/4 | 31.8 | 2.00 | 50.8 | 5.75 | 146.1 | 2.95 | 74.9 | .32 | 8.1 |
| G20300-2024 | 20GS-24FL | 7347-41655 | 1 1/4 | 31.8 | 2.38 | 60.5 | 6.30 | 160.0 | 3.50 | 88.9 | .32 | 8.1 |
| G20300-2032 | 20GS-32FL | 7347-41665 | 1 1/4 | 31.8 | 2.81 | 71.4 | 5.71 | 145.0 | 2.91 | 73.9 | .38 | 9.7 |

# Code 61 Komatsu Style O-Ring Flange

See Accessories for O–Rings.





| Part No. | Descr. | Prod. No. | ⟷ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20300-0810 | 8GS-10FLK | 7347-55255 | 1/2 | 12.7 | 1.35 | 34.3 | 3.21 | 81.5 | 1.74 | 44.2 | .27 | 6.9 |
| G20300-1010 | 10GS-10FLK | 7347-73335 | 5/8 | 15.9 | 1.35 | 34.3 | 4.49 | 114.1 | 2.51 | 63.8 | .27 | 6.9 |
| G20300-1210 | 12GS-10FLK | 7347-73375 | 3/4 | 19.1 | 1.35 | 34.3 | 4.33 | 110.0 | 2.32 | 58.9 | .27 | 6.9 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Code 61 O-Ring Flange Long Neck


–8FL, –12FL, –16FL Max. W.P. 5,000 psi; –20FL Max. W.P. 4,000 psi.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⊖ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20301-1212 | 12GS-12FLL | 7347-41455 | 3/4 | 19.1 | 1.50 | 38.1 | 5.20 | 132.1 | 3.19 | 81.0 | .27 | 6.9 |
| G20301-1616 | 16GS-16FLL | 7347-41545 | 1 | 25.4 | 1.75 | 44.5 | 5.63 | 143.0 | 3.41 | 86.6 | .32 | 8.1 |
| G20301-2020 | 20GS-20FLL | 7347-41675 | 1 1/4 | 31.8 | 2.00 | 50.8 | 6.26 | 159.0 | 3.46 | 87.9 | .32 | 8.1 |

# Code 61 O-Ring Flange - 22 1/2° Bent Tube


–8FL, –12FL, –16FL Max. W.P. 5,000 psi; –20FL Max. W.P. 4,000 psi.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20302-0808 | 8GS-8FL22M | 7347-42245 | 1/2 | 12.7 | 1.19 | 30.2 | .35 | 8.9 | 3.78 | 96.0 | 2.30 | 58.4 | .27 | 6.9 |
| G20302-1212 | 12GS-12FL22M | 7347-42445 | 3/4 | 19.1 | 1.50 | 38.1 | .43 | 11.0 | 5.16 | 131.1 | 3.15 | 80.0 | .27 | 6.9 |
| G20302-1216 | 12GS-16FL22M | 7347-42465 | 3/4 | 19.1 | 1.75 | 44.5 | .55 | 14.0 | 5.24 | 133.1 | 3.23 | 82.0 | .32 | 8.1 |
| G20302-1616 | 16GS-16FL22M | 7347-42555 | 1 | 25.4 | 1.75 | 44.5 | .55 | 14.0 | 6.10 | 154.9 | 3.87 | 98.3 | .32 | 8.1 |
| G20302-1620 | 16GS-20FL22M | 7347-42565 | 1 | 25.4 | 2.00 | 50.8 | .59 | 15.0 | 6.61 | 167.9 | 4.37 | 111.0 | .32 | 8.1 |
| G20302-2020 | 20GS-20FL22M | 7347-42645 | 1 1/4 | 31.8 | 2.00 | 50.8 | .59 | 15.0 | 7.01 | 178.1 | 4.21 | 106.9 | .32 | 8.1 |
| G20302-2024 | 20GS-24FL22M | 7347-42655 | 1 1/4 | 31.8 | 2.38 | 60.5 | .71 | 18.0 | 7.32 | 185.9 | 4.52 | 114.8 | .32 | 8.1 |

# Code 61 O-Ring Flange - 30° Bent Tube


–8FL, –12FL, –16FL Max. W.P. 5,000 psi; –20FL Max. W.P. 4,000 psi.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20304-0812 | 8GS-12FL30M | 7347-43265 | 1/2 | 12.7 | 1.50 | 38.1 | .63 | 16.0 | 3.94 | 100.1 | 2.46 | 62.5 | .27 | 6.9 |
| G20304-1212 | 12GS-12FL30M | 7347-43445 | 3/4 | 19.1 | 1.50 | 38.1 | .63 | 16.0 | 5.08 | 129.0 | 3.07 | 78.0 | .27 | 6.9 |
| G20304-1216 | 12GS-16FL30M | 7347-43465 | 3/4 | 19.1 | 1.75 | 44.5 | .75 | 19.1 | 4.76 | 120.9 | 2.76 | 70.1 | .32 | 8.1 |
| G20304-1616 | 16GS-16FL30M | 7347-43555 | 1 | 25.4 | 1.75 | 44.5 | .75 | 19.1 | 6.02 | 152.9 | 3.80 | 96.5 | .32 | 8.1 |
| G20304-1620 | 16GS-20FL30M | 7347-43565 | 1 | 25.4 | 2.00 | 50.8 | .87 | 22.1 | 6.54 | 166.1 | 4.29 | 109.0 | .32 | 8.1 |
| G20304-2020 | 20GS-20FL30M | 7347-43645 | 1 1/4 | 31.8 | 2.00 | 50.8 | .87 | 22.1 | 6.93 | 176.0 | 4.13 | 104.9 | .32 | 8.1 |
| G20304-2024 | 20GS-24FL30M | 7347-43655 | 1 1/4 | 31.8 | 2.38 | 60.5 | 1.18 | 30.0 | 7.17 | 182.1 | 4.37 | 111.0 | .32 | 8.1 |

# Code 61 O-Ring Flange - 45° Bent Tube


–8FL, –12FL, –16FL Max. W.P. 5,000 psi; –20FL Max. W.P. 4,000 psi.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20307-0608 | 6GS-8FL45M | 7347-44155 | 3/8 | 9.5 | 1.19 | 30.2 | .75 | 19.1 | 3.66 | 93.0 | 2.25 | 57.2 | .27 | 6.9 |
| G20307-0808 | 8GS-8FL45M | 7347-44245 | 1/2 | 12.7 | 1.19 | 30.2 | .75 | 19.1 | 3.70 | 94.0 | 2.22 | 56.4 | .27 | 6.9 |
| G20307-0812 | 8GS-12FL45M | 7347-44265 | 1/2 | 12.7 | 1.50 | 38.1 | 1.02 | 25.9 | 3.98 | 101.1 | 2.50 | 63.5 | .27 | 6.9 |
| G20307-1012 | 10GS-12FL45M | 7347-44355 | 5/8 | 15.9 | 1.50 | 38.1 | 1.02 | 25.9 | 5.00 | 127.0 | 3.02 | 76.7 | .27 | 6.9 |
| G20307-1212 | 12GS-12FL45M | 7347-44445 | 3/4 | 19.1 | 1.50 | 38.1 | 1.02 | 25.9 | 4.88 | 124.0 | 2.87 | 72.9 | .27 | 6.9 |
| G20306-1216 | 12GS-16FL45S | 7347-73135 | 3/4 | 19.1 | 1.75 | 44.5 | 1.10 | 27.9 | 4.96 | 126.0 | 2.95 | 74.9 | .32 | 8.1 |
| G20307-1616 | 16GS-16FL45M | 7347-44555 | 1 | 25.4 | 1.75 | 44.5 | 1.26 | 32.0 | 5.79 | 147.1 | 3.57 | 90.7 | .32 | 8.1 |
| G20307-1620 | 16GS-20FL45M | 7347-44565 | 1 | 25.4 | 2.00 | 50.8 | 1.50 | 38.1 | 6.22 | 158.0 | 3.97 | 100.8 | .32 | 8.1 |
| G20307-2016 | 20GS-16FL45M | 7347-44635 | 1 1/4 | 31.8 | 1.75 | 44.5 | 1.26 | 32.0 | 6.42 | 163.1 | 3.62 | 92.0 | .32 | 8.1 |
| G20306-2020 | 20GS-20FL45S | 7347-73565 | 1 1/4 | 31.8 | 2.00 | 50.8 | 1.26 | 32.0 | 6.69 | 169.9 | 3.89 | 98.8 | .32 | 8.1 |
| G20306-2024 | 20GS-24FL45S | 7347-73575 | 1 1/4 | 31.8 | 2.38 | 60.5 | 1.50 | 38.1 | 6.93 | 176.0 | 4.13 | 104.9 | .32 | 8.1 |

# Code 61 Komatsu Style O-Ring Flange - 45° Bent Tube


See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20307-1010 | 10GS-10FLK45-026 | 7347-73365 | 5/8 | 15.9 | 1.35 | 34.3 | 1.02 | 25.9 | 4.76 | 120.9 | 2.78 | 70.6 | .27 | 6.9 |

# Code 61 O-Ring Flange - 60° Bent Tube


–8FL, –12FL, –16FL Max. W.P. 5,000 psi; –20FL Max. W.P. 4,000 psi.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20309-0808 | 8GS-8FL60M | 7347-45245 | 1/2 | 12.7 | 1.19 | 30.2 | 1.06 | 26.9 | 4.09 | 103.9 | 2.62 | 66.6 | .27 | 6.9 |
| G20309-1212 | 12GS-12FL60M | 7347-45445 | 3/4 | 19.1 | 1.50 | 38.1 | 1.46 | 37.1 | 5.39 | 136.9 | 3.39 | 86.1 | .27 | 6.9 |
| G20309-1216 | 12GS-16FL60M | 7347-45465 | 3/4 | 19.1 | 1.75 | 44.5 | 1.73 | 43.9 | 5.35 | 135.9 | 3.35 | 85.1 | .32 | 8.1 |
| G20309-1616 | 16GS-16FL60M | 7347-45555 | 1 | 25.4 | 1.75 | 44.5 | 1.73 | 43.9 | 6.18 | 157.0 | 3.97 | 100.8 | .32 | 8.1 |
| G20309-1620 | 16GS-20FL60M | 7347-45565 | 1 | 25.4 | 2.00 | 50.8 | 2.17 | 55.1 | 6.18 | 157.0 | 3.94 | 100.1 | .32 | 8.1 |
| G20309-2020 | 20GS-20FL60M | 7347-45645 | 1 1/4 | 31.8 | 2.00 | 50.8 | 2.17 | 55.1 | 7.36 | 186.9 | 4.56 | 115.8 | .32 | 8.1 |
| G20309-2024 | 20GS-24FL60M | 7347-45655 | 1 1/4 | 31.8 | 2.38 | 60.5 | 2.52 | 64.0 | 7.68 | 195.1 | 4.88 | 124.0 | .32 | 8.1 |

# Code 61 O-Ring Flange - 67 1/2° Bent Tube


–8FL, –12FL, –16FL Max. W.P. 5,000 psi; –20FL Max. W.P. 4,000 psi.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20311-0812 | 8GS-12FL67-032 | 7347-78025 | 1/2 | 12.7 | 1.50 | 38.1 | 1.26 | 32.0 | 3.70 | 94.0 | 2.21 | 56.1 | .27 | 6.9 |
| G20311-1212 | 12GS-12FL67M | 7347-46445 | 3/4 | 19.1 | 1.50 | 38.1 | 1.65 | 41.9 | 5.20 | 132.1 | 3.19 | 81.0 | .27 | 6.9 |
| G20311-1216 | 12GS-16FL67M | 7347-46465 | 3/4 | 19.1 | 1.75 | 44.5 | 2.01 | 51.1 | 5.08 | 129.0 | 3.07 | 78.0 | .32 | 8.1 |
| G20311-1616 | 16GS-16FL67M | 7347-46555 | 1 | 25.4 | 1.75 | 44.5 | 2.01 | 51.1 | 5.94 | 150.9 | 3.71 | 94.2 | .32 | 8.1 |
| G20311-1620 | 16GS-20FL67M | 7347-46565 | 1 | 25.4 | 2.00 | 50.8 | 2.52 | 64.0 | 5.83 | 148.1 | 3.59 | 91.2 | .32 | 8.1 |
| G20311-2020 | 20GS-20FL67M | 7347-46645 | 1 1/4 | 31.8 | 2.00 | 50.8 | 2.52 | 64.0 | 7.01 | 178.1 | 4.21 | 106.9 | .32 | 8.1 |
| G20311-2024 | 20GS-24FL67S | 7347-76605 | 1 1/4 | 31.8 | 2.38 | 60.5 | 2.01 | 51.1 | 6.46 | 164.1 | 3.66 | 93.0 | .32 | 8.1 |

# Code 61 O-Ring Flange - 90° Bent Tube

–8FL, –12FL, –16FL Max. W.P. 5,000 psi; –20FL Max. W.P. 4,000 psi.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20315-0608 | 6GS-8FL90M | 7347-74155 | 3/8 | 9.5 | 1.19 | 30.2 | 1.57 | 39.9 | 3.43 | 87.1 | 2.02 | 51.3 | .27 | 6.9 |
| G20315-0808 | 8GS-8FL90M | 7347-74245 | 1/2 | 12.7 | 1.19 | 30.2 | 1.57 | 39.9 | 3.46 | 87.9 | 1.99 | 50.6 | .27 | 6.9 |
| G20316-0808 | 8GS-8FL90L | 7347-73815 | 1/2 | 12.7 | 1.19 | 30.2 | 3.27 | 83.1 | 3.46 | 87.9 | 1.99 | 50.6 | .27 | 6.9 |
| G20315-0812 | 8GS-12FL90M | 7347-74265 | 1/2 | 12.7 | 1.50 | 38.1 | 2.28 | 57.9 | 3.46 | 87.9 | 1.98 | 50.3 | .27 | 6.9 |
| G20315-1012 | 10GS-12FL90M | 7347-74355 | 5/8 | 15.9 | 1.50 | 38.1 | 2.28 | 57.9 | 4.33 | 110.0 | 2.35 | 59.7 | .27 | 6.9 |
| G20314-1208 | 12GS-8FL90-050 | 7347-76035 | 3/4 | 19.1 | 1.19 | 30.2 | 1.97 | 50.0 | 4.80 | 121.9 | 2.80 | 71.1 | .27 | 6.9 |
| G20315-1212 | 12GS-12FL90M | 7347-74445 | 3/4 | 19.1 | 1.50 | 38.1 | 2.28 | 57.9 | 4.41 | 112.0 | 2.40 | 61.0 | .27 | 6.9 |
| G20317-1212 | 12GS-12FL90-100 | 7347-73905 | 3/4 | 19.1 | 1.50 | 38.1 | 3.94 | 100.1 | 4.41 | 112.0 | 2.40 | 61.0 | .27 | 6.9 |

## Code 61 O-Ring Flange - 90° Bent Tube - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20318-1212 | 12GS-12FL90-125 | 7347-73985 | 3/4 | 19.1 | 1.50 | 38.1 | 4.92 | 125.0 | 4.80 | 121.9 | 2.80 | 71.1 | .27 | 6.9 |
| G20314-1216 | 12GS-16FL90S | 7347-73915 | 3/4 | 19.1 | 1.75 | 44.5 | 2.40 | 61.0 | 4.41 | 112.0 | 2.40 | 61.0 | .32 | 8.1 |
| G20315-1216 | 12GS-16FL90M | 7347-73925 | 3/4 | 19.1 | 1.75 | 44.5 | 2.76 | 70.1 | 4.41 | 112.0 | 2.40 | 61.0 | .32 | 8.1 |
| G20316-1216 | 12GS-16FL90-080 | 7347-76805 | 3/4 | 19.1 | 1.75 | 44.5 | 3.15 | 80.0 | 5.04 | 128.0 | 3.03 | 77.0 | .32 | 8.1 |
| G20319-1216 | 12GS-16FL90-178 | 7347-79025 | 3/4 | 19.1 | 1.75 | 44.5 | 7.01 | 178.1 | 4.41 | 112.0 | 2.38 | 60.5 | .32 | 8.1 |
| G20314-1220 | 12GS-20FL90-054 | 7347-73995 | 3/4 | 19.1 | 2.00 | 50.8 | 2.13 | 54.1 | 5.16 | 131.1 | 3.15 | 80.0 | .32 | 8.1 |
| G20317-1220 | 12GS-20FL90-125 | 7347-78375 | 3/4 | 19.1 | 2.00 | 50.8 | 4.92 | 125.0 | 4.76 | 120.9 | 2.76 | 70.1 | .32 | 8.1 |
| G20315-1612 | 16GS-12FL90M | 7347-74535 | 1 | 25.4 | 1.50 | 38.1 | 2.28 | 57.9 | 5.31 | 134.9 | 5.08 | 129.0 | .27 | 6.9 |
| G20316-1612 | 16GS-12FL90 | 7347-73255 | 1 | 25.4 | 1.50 | 38.1 | 3.15 | 80.0 | 5.31 | 134.9 | 3.10 | 78.7 | .27 | 6.9 |
| G20314-1616 | 16GS-16FL90S | 7347-47555 | 1 | 25.4 | 1.75 | 44.5 | 2.40 | 61.0 | 5.31 | 134.9 | 3.09 | 78.5 | .32 | 8.1 |
| G20315-1616 | 16GS-16FL90M | 7347-74555 | 1 | 25.4 | 1.75 | 44.5 | 2.76 | 70.1 | 5.31 | 134.9 | 3.09 | 78.5 | .32 | 8.1 |
| G20317-1616 | 16GS-16FL90-120 | 7347-73165 | 1 | 25.4 | 1.75 | 44.5 | 4.72 | 119.9 | 5.28 | 134.1 | 3.04 | 77.2 | .32 | 8.1 |
| G20318-1616 | 16GS-16FL90-150 | 7347-78705 | 1 | 25.4 | 1.75 | 44.5 | 5.91 | 150.1 | 5.67 | 144.0 | 3.44 | 87.4 | .32 | 8.1 |
| G20319-1616 | 16GS-16FL90-210 | 7347-78875 | 1 | 25.4 | 1.75 | 44.5 | 8.27 | 210.1 | 5.28 | 134.1 | 3.02 | 76.7 | .32 | 8.1 |
| G20314-1620 | 16GS-20FL90S | 7347-47565 | 1 | 25.4 | 2.00 | 50.8 | 2.68 | 68.1 | 5.28 | 134.1 | 3.02 | 76.7 | .32 | 8.1 |
| G20315-1620 | 16GS-20FL90M | 7347-74565 | 1 | 25.4 | 2.00 | 50.8 | 3.54 | 89.9 | 5.28 | 134.1 | 2.99 | 76.0 | .32 | 8.1 |
| G20317-1620 | 16GS-20FL90-120 | 7347-76495 | 1 | 25.4 | 2.00 | 50.8 | 4.72 | 119.9 | 5.28 | 134.1 | 3.04 | 77.2 | .32 | 8.1 |
| G20313-1624 | 16GS-24FL90-060 | 7347-73975 | 1 | 25.4 | 2.38 | 60.5 | 2.36 | 59.9 | 5.71 | 145.0 | 3.47 | 88.1 | .32 | 8.1 |
| G20314-1624 | 16GS-24FL90S | 7347-47575 | 1 | 25.4 | 2.38 | 60.5 | 3.19 | 81.0 | 5.28 | 134.1 | 3.04 | 77.2 | .32 | 8.1 |
| G20315-2016 | 20GS-16FL90M | 7347-74635 | 1 1/4 | 31.8 | 1.75 | 44.5 | 2.76 | 70.1 | 6.30 | 160.0 | 3.50 | 88.9 | .32 | 8.1 |
| G20316-2016 | 20GS-16FL90-215 | 7347-78885 | 1 1/4 | 31.8 | 1.75 | 44.5 | 8.46 | 214.9 | 6.30 | 160.0 | 3.50 | 88.9 | .32 | 8.1 |
| G20314-2020 | 20GS-20FL90S | 7347-47645 | 1 1/4 | 31.8 | 2.00 | 50.8 | 2.68 | 68.1 | 6.50 | 165.1 | 3.70 | 94.0 | .32 | 8.1 |
| G20315-2020 | 20GS-20FL90M | 7347-74645 | 1 1/4 | 31.8 | 2.00 | 50.8 | 3.54 | 89.9 | 6.50 | 165.1 | 3.70 | 94.0 | .32 | 8.1 |
| G20317-2020 | 20GS-20FL90-168 | 7347-76105 | 1 1/4 | 31.8 | 2.00 | 50.8 | 6.61 | 167.9 | 6.54 | 166.1 | 3.74 | 95.0 | .32 | 8.1 |
| G20314-2024 | 20GS-24FL90S | 7347-47655 | 1 1/4 | 31.8 | 2.38 | 60.5 | 3.19 | 81.0 | 6.50 | 165.1 | 3.70 | 94.0 | .32 | 8.1 |
| G20315-2024 | 20GS-24FL90-118 | 7347-76085 | 1 1/4 | 31.8 | 2.38 | 60.5 | 4.65 | 118.1 | 6.50 | 165.1 | 3.70 | 94.0 | .32 | 8.1 |

## Code 61 Komatsu Style O-Ring Flange - 90° Bent Tube


See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20315-1010 | 10GS-10FLK90-055 | 7347-73355 | 5/8 | 15.9 | 1.35 | 34.3 | 2.17 | 55.1 | 4.33 | 110.0 | 2.35 | 59.7 | .27 | 6.9 |
| G20315-1210 | 12GS-10FLK90-055 | 7347-73695 | 3/4 | 19.1 | 1.35 | 34.3 | 2.17 | 55.1 | 4.65 | 118.1 | 2.64 | 67.1 | .27 | 6.9 |

# Code 61 O-Ring Flange - 100° Bent Tube


–8FL, –12FL, –16FL Max. W.P. 5,000 psi; –20FL Max. W.P. 4,000 psi.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20323-1216 | 12GS-16FL100-059 | 7347-78055 | 3/4 | 19.1 | 1.75 | 44.5 | 2.32 | 58.9 | 4.93 | 125.2 | 2.92 | 74.2 | .32 | 8.1 |

# Code 61 O-Ring Flange - 110° Bent Tube

–8FL, –12FL, –16FL Max. W.P. 5,000 psi; –20FL Max. W.P. 4,000 psi.
See Accessories for O–Rings.





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20325-1212 | 12GS-12FL110-064 | 7347-76025 | 3/4 | 19.1 | 1.50 | 38.1 | 2.52 | 64.0 | 5.16 | 131.1 | 3.15 | 80.0 | .27 | 6.9 |
| G20325-1616 | 16GS-16FL110-073 | 7347-73005 | 1 | 25.4 | 1.75 | 44.5 | 2.87 | 72.9 | 5.83 | 148.1 | 3.61 | 91.7 | .32 | 8.1 |
| G20325-1620 | 16GS-20FL110-073 | 7347-76455 | 1 | 25.4 | 2.00 | 50.8 | 2.87 | 72.9 | 4.65 | 118.1 | 2.41 | 61.2 | .32 | 8.1 |
| G20325-2020 | 20GS-20FL110-080 | 7347-76115 | 1 1/4 | 31.8 | 2.00 | 50.8 | 3.15 | 80.0 | 7.13 | 181.1 | 4.33 | 110.0 | .32 | 8.1 |
| G20325-2024 | 20GS-24FL110-080 | 7347-76125 | 1 1/4 | 31.8 | 2.38 | 60.5 | 3.15 | 80.0 | 7.13 | 181.1 | 4.33 | 110.0 | .32 | 8.1 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Code 61 O-Ring Flange - 135° Bent Tube


–8FL, –12FL, –16FL Max. W.P. 5,000 psi; –20FL Max. W.P. 4,000 psi.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20331-1212 | 12GS-12FL135-070 | 7347-76825 | 3/4 | 19.1 | 1.50 | 38.1 | 2.76 | 70.1 | 3.82 | 97.0 | 1.81 | 46.0 | .27 | 6.9 |

# Code 62 O-Ring Flange Heavy


All FLH sizes Maximum Working Pressure 6,000 PSI.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⊖ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20350-0808 | 8GS-8FLH | 7347-48245 | 1/2 | 12.7 | 1.25 | 31.8 | 3.66 | 93.0 | 2.19 | 55.6 | .31 | 7.9 |
| G20350-0812 | 8GS-12FLH | 7347-48265 | 1/2 | 12.7 | 1.63 | 41.4 | 3.66 | 93.0 | 2.19 | 55.6 | .35 | 8.9 |
| G20350-1008 | 10GS-8FLH | 7347-48335 | 5/8 | 15.9 | 1.25 | 31.8 | 4.29 | 109.0 | 2.31 | 58.7 | .31 | 7.9 |
| G20350-1012 | 10GS-12FLH | 7347-48355 | 5/8 | 15.9 | 1.63 | 41.4 | 4.29 | 109.0 | 2.31 | 58.7 | .35 | 8.9 |
| G20350-1212 | 12GS-12FLH | 7347-48445 | 3/4 | 19.1 | 1.63 | 41.4 | 4.49 | 114.1 | 2.48 | 63.0 | .35 | 8.9 |
| G20350-1216 | 12GS-16FLH | 7347-48465 | 3/4 | 19.1 | 1.88 | 47.8 | 4.49 | 114.1 | 2.48 | 63.0 | .38 | 9.7 |
| G20350-1612 | 16GS-12FLH | 7347-48535 | 1 | 25.4 | 1.63 | 41.4 | 5.08 | 129.0 | 2.86 | 72.6 | .35 | 8.9 |
| G20350-1616 | 16GS-16FLH | 7347-48555 | 1 | 25.4 | 1.88 | 47.8 | 4.92 | 125.0 | 2.70 | 68.6 | .38 | 9.7 |
| G20350-1620 | 16GS-20FLH | 7347-48565 | 1 | 25.4 | 2.13 | 54.1 | 4.92 | 125.0 | 2.69 | 68.3 | .41 | 10.4 |
| G20350-2016 | 20GS-16FLH | 7347-48635 | 1 1/4 | 31.8 | 1.88 | 47.8 | 6.42 | 163.1 | 3.62 | 92.0 | .38 | 9.7 |
| G20350-2020 | 20GS-20FLH | 7347-48645 | 1 1/4 | 31.8 | 2.13 | 54.1 | 5.75 | 146.1 | 2.95 | 74.9 | .41 | 10.4 |
| G20350-2024 | 20GS-24FLH | 7347-48655 | 1 1/4 | 31.8 | 2.50 | 63.5 | 6.30 | 160.0 | 3.50 | 88.9 | .50 | 12.7 |

# Code 62 O-Ring Flange Heavy - 22 1/2° Bent Tube


All FLH sizes Maximum Working Pressure 6,000 PSI.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20352-1216 | 12GS-16FLH22M | 7347-49465 | 3/4 | 19.1 | 1.88 | 47.8 | .55 | 14.0 | 5.43 | 137.9 | 3.43 | 87.1 | .38 | 9.7 |
| G20352-1616 | 16GS-16FLH22M | 7347-49555 | 1 | 25.4 | 1.88 | 47.8 | .55 | 14.0 | 6.10 | 154.9 | 3.88 | 98.6 | .38 | 9.7 |
| G20352-1620 | 16GS-20FLH22M | 7347-49565 | 1 | 25.4 | 2.13 | 54.1 | .59 | 15.0 | 6.61 | 167.9 | 4.52 | 114.8 | .41 | 10.4 |
| G20352-2020 | 20GS-20FLH22M | 7347-49645 | 1 1/4 | 31.8 | 2.13 | 54.1 | .59 | 15.0 | 7.32 | 185.9 | 4.52 | 114.8 | .41 | 10.4 |
| G20352-2024 | 20GS-24FLH22M | 7347-49655 | 1 1/4 | 31.8 | 2.50 | 63.5 | .71 | 18.0 | 7.40 | 188.0 | 4.60 | 116.8 | .50 | 12.7 |

# Code 62 O-Ring Flange Heavy - 30° Bent Tube


All FLH sizes Maximum Working Pressure 6,000 PSI.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20354-1212 | 12GS-12FLH30M | 7347-50445 | 3/4 | 19.1 | 1.63 | 41.4 | .63 | 16.0 | 5.08 | 129.0 | 3.07 | 78.0 | .35 | 8.9 |
| G20354-1216 | 12GS-16FLH30M | 7347-50465 | 3/4 | 19.1 | 1.88 | 47.8 | .75 | 19.1 | 5.08 | 129.0 | 3.07 | 78.0 | .38 | 9.7 |
| G20354-1616 | 16GS-16FLH30M | 7347-50555 | 1 | 25.4 | 1.88 | 47.8 | .75 | 19.1 | 6.02 | 152.9 | 3.80 | 96.5 | .38 | 9.7 |
| G20354-1620 | 16GS-20FLH30M | 7347-50565 | 1 | 25.4 | 2.13 | 54.1 | 1.50 | 38.1 | 6.22 | 158.0 | 3.98 | 101.1 | .41 | 10.4 |
| G20354-2020 | 20GS-20FLH30M | 7347-50645 | 1 1/4 | 31.8 | 2.13 | 54.1 | .87 | 22.1 | 7.24 | 183.9 | 4.44 | 112.8 | .41 | 10.4 |
| G20354-2024 | 20GS-24FLH30M | 7347-50655 | 1 1/4 | 31.8 | 2.50 | 63.5 | 1.18 | 30.0 | 7.24 | 183.9 | 4.44 | 112.8 | .50 | 12.7 |

# Code 62 O-Ring Flange Heavy - 45° Bent Tube


All FLH sizes Maximum Working Pressure 6,000 PSI.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20357-0808 | 8GS-8FLH45M | 7347-51245 | 1/2 | 12.7 | 1.25 | 31.8 | .75 | 19.1 | 3.70 | 94.0 | 2.22 | 56.4 | .31 | 7.9 |
| G20357-0812 | 8GS-12FLH45M | 7347-51265 | 1/2 | 12.7 | 1.63 | 41.4 | 1.02 | 25.9 | 3.98 | 101.1 | 2.50 | 63.5 | .35 | 8.9 |
| G20357-1012 | 10GS-12FLH45M | 7347-51355 | 5/8 | 15.9 | 1.63 | 41.4 | 1.02 | 25.9 | 5.00 | 127.0 | 3.02 | 76.7 | .35 | 8.9 |
| G20357-1208 | 12GS-8FLH45M | 7347-51425 | 3/4 | 19.1 | 1.25 | 31.8 | .75 | 19.1 | 4.56 | 115.8 | 2.55 | 64.8 | .31 | 7.9 |
| G20357-1212 | 12GS-12FLH45M | 7347-51445 | 3/4 | 19.1 | 1.63 | 41.4 | 1.02 | 25.9 | 4.88 | 124.0 | 2.87 | 72.9 | .35 | 8.9 |
| G20357-1216 | 12GS-16FLH45M | 7347-51465 | 3/4 | 19.1 | 1.88 | 47.8 | 1.26 | 32.0 | 5.12 | 130.1 | 3.11 | 79.0 | .38 | 9.7 |
| G20357-1612 | 16GS-12FLH45M | 7347-51535 | 1 | 25.4 | 1.63 | 41.4 | 1.02 | 25.9 | 5.55 | 141.0 | 3.33 | 84.6 | .35 | 8.9 |
| G20357-1616 | 16GS-16FLH45M | 7347-51555 | 1 | 25.4 | 1.88 | 47.8 | 1.26 | 32.0 | 5.79 | 147.1 | 3.57 | 90.7 | .38 | 9.7 |
| G20357-1620 | 16GS-20FLH45M | 7347-51565 | 1 | 25.4 | 2.13 | 54.1 | 1.50 | 38.1 | 6.22 | 158.0 | 3.98 | 101.1 | .41 | 10.4 |
| G20357-2016 | 20GS-16FLH45M | 7347-51635 | 1 1/4 | 31.8 | 1.88 | 47.8 | 1.26 | 32.0 | 6.73 | 170.9 | 3.93 | 99.8 | .38 | 9.7 |
| G20357-2020 | 20GS-20FLH45M | 7347-51645 | 1 1/4 | 31.8 | 2.13 | 54.1 | 1.50 | 38.1 | 6.93 | 176.0 | 4.13 | 104.9 | .41 | 10.4 |
| G20357-2024 | 20GS-24FLH45M | 7347-51655 | 1 1/4 | 31.8 | 2.50 | 63.5 | 1.73 | 43.9 | 6.93 | 176.0 | 4.13 | 104.9 | .50 | 12.7 |

# Code 62 O-Ring Flange Heavy - 60° Bent Tube


All FLH sizes Maximum Working Pressure 6,000 PSI.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20359-1212 | 12GS-12FLH60M | 7347-52445 | 3/4 | 19.1 | 1.63 | 41.4 | 1.46 | 37.1 | 5.39 | 136.9 | 3.39 | 86.1 | .35 | 8.9 |
| G20359-1216 | 12GS-16FLH60M | 7347-52465 | 3/4 | 19.1 | 1.88 | 47.8 | 1.73 | 43.9 | 5.35 | 135.9 | 3.35 | 85.1 | .38 | 9.7 |
| G20359-1616 | 16GS-16FLH60M | 7347-52555 | 1 | 25.4 | 1.88 | 47.8 | 1.73 | 43.9 | 6.18 | 157.0 | 3.96 | 100.6 | .38 | 9.7 |
| G20359-2020 | 20GS-20FLH60M | 7347-52645 | 1 1/4 | 31.8 | 2.13 | 54.1 | 2.17 | 55.1 | 7.32 | 185.9 | 4.52 | 114.8 | .41 | 10.4 |
| G20359-2024 | 20GS-24FLH60M | 7347-52655 | 1 1/4 | 31.8 | 2.50 | 63.5 | 2.52 | 64.0 | 7.64 | 194.1 | 4.84 | 122.9 | .50 | 12.7 |

# Code 62 O-Ring Flange Heavy - 67 1/2° Bent Tube


All FLH sizes Maximum Working Pressure 6,000 PSI.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20360-1616 | 16GS-16FLH67M | 7347-53555 | 1 | 25.4 | 1.88 | 47.8 | 2.01 | 51.1 | 5.94 | 150.9 | 3.72 | 94.5 | .38 | 9.7 |

# Code 62 O-Ring Flange Heavy - 90° Bent Tube

All FLH sizes Maximum Working Pressure 6,000 PSI.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20365-0808 | 8GS-8FLH90M | 7347-75245 | 1/2 | 12.7 | 1.25 | 31.8 | 1.57 | 39.9 | 3.46 | 87.9 | 1.99 | 50.6 | .31 | 7.9 |
| G20366-0808 | 8GS-8FLH90-080 | 7347-73825 | 1/2 | 12.7 | 1.25 | 31.8 | 3.15 | 80.0 | 3.46 | 87.9 | 1.99 | 50.6 | .31 | 7.9 |
| G20365-0812 | 8GS-12FLH90M | 7347-75265 | 1/2 | 12.7 | 1.63 | 41.4 | 2.28 | 57.9 | 3.46 | 87.9 | 1.99 | 50.6 | .35 | 8.9 |
| G20365-1008 | 10GS-8FLH90M | 7347-75335 | 5/8 | 15.9 | 1.25 | 31.8 | 1.57 | 39.9 | 4.45 | 113.0 | 2.47 | 62.7 | .31 | 7.9 |
| G20365-1012 | 10GS-12FLH90M | 7347-75355 | 5/8 | 15.9 | 1.63 | 41.4 | 2.28 | 57.9 | 4.33 | 110.0 | 2.35 | 59.7 | .35 | 8.9 |
| G20365-1212 | 12GS-12FLH90M | 7347-75445 | 3/4 | 19.1 | 1.63 | 41.4 | 2.28 | 57.9 | 4.41 | 112.0 | 2.40 | 61.0 | .35 | 8.9 |
| G20366-1212 | 12GS-12FLH90-100 | 7347-73835 | 3/4 | 19.1 | 1.63 | 41.4 | 3.94 | 100.1 | 4.41 | 112.0 | 2.40 | 61.0 | .35 | 8.9 |
| G20367-1212 | 12GS-12FLH90-122 | 7347-76415 | 3/4 | 19.1 | 1.63 | 41.4 | 4.80 | 121.9 | 4.80 | 121.9 | 2.80 | 71.1 | .35 | 8.9 |
| G20364-1216 | 12GS-16FLH90S | 7347-54465 | 3/4 | 19.1 | 1.88 | 47.8 | 2.40 | 61.0 | 4.41 | 112.0 | 2.40 | 61.0 | .38 | 9.7 |
| G20365-1216 | 12GS-16FLH90M | 7347-73935 | 3/4 | 19.1 | 1.88 | 47.8 | 2.76 | 70.1 | 4.41 | 112.0 | 2.40 | 61.0 | .38 | 9.7 |
| G20367-1216 | 12GS-16FLH90-140 | 7347-76715 | 3/4 | 19.1 | 1.88 | 47.8 | 5.51 | 140.0 | 4.57 | 116.1 | 2.56 | 65.0 | .38 | 9.7 |
| G20365-1220 | 12GS-20FLH90M | 7347-75475 | 3/4 | 19.1 | 2.13 | 54.1 | 3.54 | 89.9 | 4.80 | 121.9 | 2.80 | 71.1 | .41 | 10.4 |
| G20365-1612 | 16GS-12FLH90M | 7347-54535 | 1 | 25.4 | 1.63 | 41.4 | 2.28 | 57.9 | 5.31 | 134.9 | 3.09 | 78.5 | .35 | 8.9 |
| G20364-1616 | 16GS-16FLH90S | 7347-54555 | 1 | 25.4 | 1.88 | 47.8 | 2.40 | 61.0 | 5.31 | 134.9 | 3.09 | 78.5 | .38 | 9.7 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Code 62 O-Ring Flange Heavy - 90° Bent Tube - Continued

| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20365-1616 | 16GS-16FLH90M | 7347-75555 | 1 | 25.4 | 1.88 | 47.8 | 2.76 | 70.1 | 5.31 | 134.9 | 3.09 | 78.5 | .38 | 9.7 |
| G20366-1616 | 16GS-16FLH90-120 | 7347-73015 | 1 | 25.4 | 1.88 | 47.8 | 4.72 | 119.9 | 5.28 | 134.1 | 3.04 | 77.2 | .38 | 9.7 |
| G20367-1616 | 16GS-16FLH90-090 | 7347-78105 | 1 | 25.4 | 1.88 | 47.8 | 3.54 | 89.9 | 5.52 | 140.2 | 3.28 | 83.3 | .38 | 9.7 |
| G20364-1620 | 16GS-20FLH90S | 7347-54565 | 1 | 25.4 | 2.13 | 54.1 | 2.68 | 68.1 | 5.28 | 134.1 | 3.02 | 76.7 | .41 | 10.4 |
| G20365-1620 | 16GS-20FLH90M | 7347-75565 | 1 | 25.4 | 2.13 | 54.1 | 3.54 | 89.9 | 5.28 | 134.1 | 3.02 | 76.7 | .41 | 10.4 |
| G20364-1624 | 16GS-24FLH90S | 7347-54575 | 1 | 25.4 | 2.50 | 63.5 | 3.19 | 81.0 | 5.28 | 134.1 | 3.04 | 77.2 | .50 | 12.7 |
| G20364-2016 | 20GS-16FLH90S | 7347-54635 | 1 1/4 | 31.8 | 1.88 | 47.8 | 2.40 | 61.0 | 6.30 | 160.0 | 3.50 | 88.9 | .38 | 9.7 |
| G20365-2016 | 20GS-16FLH90M | 7347-75635 | 1 1/4 | 31.8 | 1.88 | 47.8 | 2.76 | 70.1 | 6.30 | 160.0 | 3.50 | 88.9 | .38 | 9.7 |
| G20366-2016 | 20GS-16FLH90-100 | 7347-76185 | 1 1/4 | 31.8 | 1.88 | 47.8 | 3.94 | 100.1 | 6.30 | 160.0 | 3.50 | 88.9 | .38 | 9.7 |
| G20364-2020 | 20GS-20FLH90-076 | 7347-73635 | 1 1/4 | 31.8 | 2.13 | 54.1 | 2.99 | 76.0 | 6.50 | 165.1 | 3.70 | 94.0 | .41 | 10.4 |
| G20365-2020 | 20GS-20FLH90M | 7347-75645 | 1 1/4 | 31.8 | 2.13 | 54.1 | 3.54 | 89.9 | 6.50 | 165.1 | 3.70 | 94.0 | .41 | 10.4 |
| G20366-2020 | 20GS-20FLH90-120 | 7347-76135 | 1 1/4 | 31.8 | 2.13 | 54.1 | 4.72 | 119.9 | 6.50 | 165.1 | 3.70 | 94.0 | .41 | 10.4 |
| G20367-2020 | 20GS-20FLH90-152 | 7347-76485 | 1 1/4 | 31.8 | 2.13 | 54.1 | 5.98 | 151.9 | 6.50 | 165.1 | 3.70 | 94.0 | .41 | 10.4 |
| G20364-2024 | 20GS-24FLH90S | 7347-54655 | 1 1/4 | 31.8 | 2.50 | 63.5 | 3.19 | 81.0 | 6.50 | 165.1 | 3.70 | 94.0 | .50 | 12.7 |

## Code 62 O-Ring Flange Heavy - 110° Bent Tube


All FLH sizes Maximum Working Pressure 6,000 PSI.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20369-1212 | 12GS-12FLH110-064 | 7347-78525 | 3/4 | 19.1 | 1.63 | 41.4 | 2.76 | 70.1 | 3.82 | 97.0 | 1.81 | 46.0 | .35 | 8.9 |

# Caterpillar Style O-Ring Flange


NOTE: These FLC flanges are designed with a thicker flange head. The .56" flange dimension is frequently found on Caterpillar equipment. These flanges let the user utilize the existing Caterpillar flange halves or new Gates Caterpillar flange halves. At the user's option, standard Code 62 flanges and halves can be used in place of Caterpillar flanges and halves. The standard Code 62 flange head thickness ranges between .305" and .495". Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings).




| Part No. | Descr. | Prod. No. | ⟷ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20400-1212 | 12GS-12FLC | 7347-62445 | 3/4 | 19.1 | 1.63 | 41.4 | 5.71 | 145.0 | 3.70 | 94.0 | .56 | 14.2 |
| G20400-1216 | 12GS-16FLC | 7347-62465 | 3/4 | 19.1 | 1.88 | 47.8 | 5.71 | 145.0 | 3.70 | 94.0 | .56 | 14.2 |
| G20400-1616 | 16GS-16FLC | 7347-62555 | 1 | 25.4 | 1.88 | 47.8 | 6.10 | 154.9 | 3.87 | 98.3 | .56 | 14.2 |
| G20400-1620 | 16GS-20FLC | 7347-62565 | 1 | 25.4 | 2.13 | 54.1 | 6.10 | 154.9 | 3.87 | 98.3 | .56 | 14.2 |
| G20400-2020 | 20GS-20FLC | 7347-62645 | 1 1/4 | 31.8 | 2.13 | 54.1 | 7.36 | 186.9 | 4.56 | 115.8 | .56 | 14.2 |
| G20400-2024 | 20GS-24FLC | 7347-62655 | 1 1/4 | 31.8 | 2.50 | 63.5 | 7.36 | 186.9 | 4.56 | 115.8 | .56 | 14.2 |

# Caterpillar Style O-Ring Flange - 22 1/2° Bent Tube

NOTE: These FLC flanges are designed with a thicker flange head. The .56" flange dimension is frequently found on Caterpillar equipment. These flanges let the user utilize the existing Caterpillar flange halves or new Gates Caterpillar flange halves. At the user's option, standard Code 62 flanges and halves can be used in place of Caterpillar flanges and halves. The standard Code 62 flange head thickness ranges between .305" and .495". Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings).





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20402-1212 | 12GS-12FLC22-016 | 7347-63445 | 3/4 | 19.1 | 1.63 | 41.4 | .63 | 16.0 | 5.63 | 143.0 | 3.62 | 92.0 | .56 | 14.2 |
| G20402-1616 | 16GS-16FLC22-017 | 7347-63555 | 1 | 25.4 | 1.88 | 47.8 | .67 | 17.0 | 6.02 | 152.9 | 3.78 | 96.0 | .56 | 14.2 |
| G20402-1620 | 16GS-20FLC22-017 | 7347-63565 | 1 | 25.4 | 2.13 | 54.1 | .67 | 17.0 | 6.02 | 152.9 | 3.78 | 96.0 | .56 | 14.2 |
| G20402-2020 | 20GS-20FLC22-017 | 7347-63645 | 1 1/4 | 31.8 | 2.13 | 54.1 | .67 | 17.0 | 7.28 | 184.9 | 4.48 | 113.8 | .56 | 14.2 |
| G20402-2024 | 20GS-24FLC22-017 | 7347-63655 | 1 1/4 | 31.8 | 2.50 | 63.5 | .67 | 17.0 | 7.28 | 184.9 | 4.48 | 113.8 | .56 | 14.2 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Caterpillar Style O-Ring Flange - 30° Bent Tube


NOTE: These FLC flanges are designed with a thicker flange head. The .56" flange dimension is frequently found on Caterpillar equipment. These flanges let the user utilize the existing Caterpillar flange halves or new Gates Caterpillar flange halves. At the user's option, standard Code 62 flanges and halves can be used in place of Caterpillar flanges and halves. The standard Code 62 flange head thickness ranges between .305" and .495". Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings).




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20404-1212 | 12GS-12FLC30-022 | 7347-64445 | 3/4 | 19.1 | 1.63 | 41.4 | .87 | 22.1 | 5.51 | 140.0 | 3.50 | 88.9 | .56 | 14.2 |
| G20404-1216 | 12GS-16FLC30-022 | 7347-64465 | 3/4 | 19.1 | 1.88 | 47.8 | .87 | 22.1 | 5.55 | 141.0 | 3.54 | 89.9 | .56 | 14.2 |
| G20404-1616 | 16GS-16FLC30-023 | 7347-64555 | 1 | 25.4 | 1.88 | 47.8 | .91 | 23.1 | 5.94 | 150.9 | 3.69 | 93.7 | .56 | 14.2 |
| G20404-1620 | 16GS-20FLC30-023 | 7347-64565 | 1 | 25.4 | 2.13 | 54.1 | .91 | 23.1 | 5.94 | 150.9 | 3.69 | 93.7 | .56 | 14.2 |
| G20404-2020 | 20GS-20FLC30-024 | 7347-64645 | 1 1/4 | 31.8 | 2.13 | 54.1 | .94 | 23.9 | 7.20 | 182.9 | 4.41 | 112.0 | .56 | 14.2 |
| G20404-2024 | 20GS-24FLC30-024 | 7347-64655 | 1 1/4 | 31.8 | 2.50 | 63.5 | .94 | 23.9 | 7.20 | 182.9 | 4.41 | 112.0 | .56 | 14.2 |

# Caterpillar Style O-Ring Flange - 45° Bent Tube


NOTE: These FLC flanges are designed with a thicker flange head. The .56" flange dimension is frequently found on Caterpillar equipment. These flanges let the user utilize the existing Caterpillar flange halves or new Gates Caterpillar flange halves. At the user's option, standard Code 62 flanges and halves can be used in place of Caterpillar flanges and halves. The standard Code 62 flange head thickness ranges between .305" and .495". Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings).




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20407-1212 | 12GS-12FLC45-035 | 7347-65445 | 3/4 | 19.1 | 1.63 | 41.4 | 1.38 | 35.1 | 5.24 | 133.1 | 3.23 | 82.0 | .56 | 14.2 |
| G20408-1212 | 12GS-12FLC45-066 | 7347-76425 | 3/4 | 19.1 | 1.63 | 41.4 | 2.60 | 66.0 | 6.50 | 165.1 | 4.49 | 114.1 | .56 | 14.2 |
| G20407-1216 | 12GS-16FLC45-035 | 7347-65465 | 3/4 | 19.1 | 1.88 | 47.8 | 1.38 | 35.1 | 5.24 | 133.1 | 3.23 | 82.0 | .56 | 14.2 |
| G20407-1616 | 16GS-16FLC45-037 | 7347-65555 | 1 | 25.4 | 1.88 | 47.8 | 1.46 | 37.1 | 5.63 | 143.0 | 3.40 | 86.4 | .56 | 14.2 |
| G20407-1620 | 16GS-20FLC45-037 | 7347-65565 | 1 | 25.4 | 2.13 | 54.1 | 1.46 | 37.1 | 5.63 | 143.0 | 3.40 | 86.4 | .56 | 14.2 |
| G20407-2020 | 20GS-20FLC45-037 | 7347-65645 | 1 1/4 | 31.8 | 2.13 | 54.1 | 1.46 | 37.1 | 6.93 | 176.0 | 4.13 | 104.9 | .56 | 14.2 |
| G20407-2024 | 20GS-24FLC45-037 | 7347-65655 | 1 1/4 | 31.8 | 2.50 | 63.5 | 1.46 | 37.1 | 6.93 | 176.0 | 4.13 | 104.9 | .56 | 14.2 |

# Caterpillar Style O-Ring Flange - 60° Bent Tube


NOTE: These FLC flanges are designed with a thicker flange head. The .56" flange dimension is frequently found on Caterpillar equipment. These flanges let the user utilize the existing Caterpillar flange halves or new Gates Caterpillar flange halves. At the user's option, standard Code 62 flanges and halves can be used in place of Caterpillar flanges and halves. The standard Code 62 flange head thickness ranges between .305" and .495". Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings).




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20409-1216 | 12GS-16FLC60-048 | 7347-66465 | 3/4 | 19.1 | 1.88 | 47.8 | 1.89 | 48.0 | 5.75 | 146.1 | 3.74 | 95.0 | .56 | 14.2 |
| G20409-1616 | 16GS-16FLC60-050 | 7347-66555 | 1 | 25.4 | 1.88 | 47.8 | 1.97 | 50.0 | 6.42 | 163.1 | 4.17 | 105.9 | .56 | 14.2 |
| G20409-1620 | 16GS-20FLC60-050 | 7347-66565 | 1 | 25.4 | 2.13 | 54.1 | 1.97 | 50.0 | 6.42 | 163.1 | 4.17 | 105.9 | .56 | 14.2 |
| G20409-2020 | 20GS-20FLC60-052 | 7347-66645 | 1 1/4 | 31.8 | 2.13 | 54.1 | 2.05 | 52.1 | 7.80 | 198.1 | 5.00 | 127.0 | .56 | 14.2 |
| G20409-2024 | 20GS-24FLC60-052 | 7347-66655 | 1 1/4 | 31.8 | 2.50 | 63.5 | 2.05 | 52.1 | 7.80 | 198.1 | 5.00 | 127.0 | .56 | 14.2 |

# Caterpillar Style O-Ring Flange - 67 1/2° Bent Tube

NOTE: These FLC flanges are designed with a thicker flange head. The .56" flange dimension is frequently found on Caterpillar equipment. These flanges let the user utilize the existing Caterpillar flange halves or new Gates Caterpillar flange halves. At the user's option, standard Code 62 flanges and halves can be used in place of Caterpillar flanges and halves. The standard Code 62 flange head thickness ranges between .305" and .495". Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings).





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20410-1616 | 16GS-16FLC67-057 | 7347-67555 | 1 | 25.4 | 1.88 | 47.8 | 2.24 | 56.9 | 6.14 | 156.0 | 3.90 | 99.1 | .56 | 14.2 |
| G20410-1620 | 16GS-20FLC67-057 | 7347-67565 | 1 | 25.4 | 2.13 | 54.1 | 2.24 | 56.9 | 6.14 | 156.0 | 3.90 | 99.1 | .56 | 14.2 |
| G20410-2020 | 20GS-20FLC67-059 | 7347-67645 | 1 1/4 | 31.8 | 2.13 | 54.1 | 2.32 | 58.9 | 7.52 | 191.0 | 4.72 | 119.9 | .56 | 14.2 |
| G20410-2024 | 20GS-24FLC67-059 | 7347-67655 | 1 1/4 | 31.8 | 2.50 | 63.5 | 2.32 | 58.9 | 7.52 | 191.0 | 4.72 | 119.9 | .56 | 14.2 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Caterpillar Style O-Ring Flange - 90° Bent Tube


NOTE: These FLC flanges are designed with a thicker flange head. The .56" flange dimension is frequently found on Caterpillar equipment. These flanges let the user utilize the existing Caterpillar flange halves or new Gates Caterpillar flange halves. At the user's option, standard Code 62 flanges and halves can be used in place of Caterpillar flanges and halves. The standard Code 62 flange head thickness ranges between .305" and .495". Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings).




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20415-1212 | 12GS-12FLC90-068 | 7347-73945 | 3/4 | 19.1 | 1.63 | 41.4 | 2.68 | 68.1 | 4.92 | 125.0 | 2.91 | 73.9 | .56 | 14.2 |
| G20416-1212 | 12GS-12FLC90-128 | 7347-76015 | 3/4 | 19.1 | 1.63 | 41.4 | 5.04 | 128.0 | 4.61 | 117.1 | 2.60 | 66.0 | .56 | 14.2 |
| G20415-1216 | 12GS-16FLC90-068 | 7347-73955 | 3/4 | 19.1 | 1.88 | 47.8 | 2.68 | 68.1 | 4.61 | 117.1 | 2.60 | 66.0 | .56 | 14.2 |
| G20415-1616 | 16GS-16FLC90-074 | 7347-68555 | 1 | 25.4 | 1.88 | 47.8 | 2.91 | 73.9 | 5.16 | 131.1 | 2.92 | 74.2 | .56 | 14.2 |
| G20416-1616 | 16GS-16FLC90-132 | 7347-73035 | 1 | 25.4 | 1.88 | 47.8 | 5.20 | 132.1 | 5.16 | 131.1 | 2.92 | 74.2 | .56 | 14.2 |
| G20415-1620 | 16GS-20FLC90-074 | 7347-68565 | 1 | 25.4 | 2.13 | 54.1 | 2.91 | 73.9 | 5.16 | 131.1 | 2.92 | 74.2 | .56 | 14.2 |
| G20416-1620 | 16GS-20FLC90-132 | 7347-68585 | 1 | 25.4 | 2.13 | 54.1 | 5.19 | 131.8 | 5.15 | 130.8 | 2.92 | 74.2 | .56 | 14.2 |
| G20415-2020 | 20GS-20FLC90-077 | 7347-68645 | 1 1/4 | 31.8 | 2.13 | 54.1 | 3.03 | 77.0 | 6.54 | 166.1 | 3.74 | 95.0 | .56 | 14.2 |
| G20416-2020 | 20GS-20FLC90-150 | 7347-68685 | 1 1/4 | 31.8 | 2.13 | 54.1 | 5.90 | 149.9 | 9.48 | 240.8 | 6.70 | 170.2 | .56 | 14.2 |
| G20415-2024 | 20GS-24FLC90-077 | 7347-68655 | 1 1/4 | 31.8 | 2.50 | 63.5 | 3.03 | 77.0 | 6.54 | 166.1 | 3.74 | 95.0 | .56 | 14.2 |
| G20416-2024 | 20GS-24FLC90-150 | 7347-68815 | 1 1/4 | 31.8 | 2.13 | 54.1 | 5.91 | 150.1 | 6.54 | 166.1 | 3.74 | 95.0 | .56 | 14.2 |


# Female French GAZ (Poclain) 24° High Pressure Flange





| Part No. | Descr. | Prod. No. | ⟷ | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G20420-0817 | 8GS-17FPFL | 7347-93215 | 1/2 | 12.7 | 2.72 | 69.1 | 1.24 | 31.5 | .56 | 14.2 |
| G20420-1021 | 10GS-21FPFL | 7347-92995 | 5/8 | 15.9 | 3.35 | 85.1 | 1.37 | 34.8 | .56 | 14.2 |
| G20420-1227 | 12GS-27FPFL | 7347-93065 | 3/4 | 19.1 | 3.58 | 90.9 | 1.57 | 39.9 | .56 | 14.2 |
| G20420-1634 | 16GS-34FPFL | 7347-93165 | 1 | 25.4 | 4.02 | 102.1 | 1.78 | 45.2 | .56 | 14.2 |
| G20420-2042 | 20GS-42FPFL | 7347-93465 | 1 1/4 | 31.8 | 5.24 | 133.1 | 2.44 | 62.0 | .56 | 14.2 |

# Male French GAZ (Poclain) 24° High Pressure Flange





| Part No. | Descr. | Prod. No. | ⊖ | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G20480-0817 | 8GS-17MPFL | 7347-93225 | 1/2 | 12.7 | 3.11 | 79.0 | 1.63 | 41.4 | .56 | 14.2 |
| G20480-1021 | 10GS-21MPFL | 7347-93005 | 5/8 | 15.9 | 3.27 | 83.1 | 1.29 | 32.8 | .56 | 14.2 |
| G20480-1227 | 12GS-27MPFL | 7347-93085 | 3/4 | 19.1 | 4.02 | 102.1 | 2.01 | 51.1 | .56 | 14.2 |
| G20480-1634 | 16GS-34MPFL | 7347-93185 | 1 | 25.4 | 4.51 | 114.6 | 2.27 | 57.7 | .56 | 14.2 |
| G20480-2042 | 20GS-42MPFL | 7347-93475 | 1 1/4 | 31.8 | 6.77 | 172.0 | 3.96 | 100.6 | .56 | 14.2 |

# Male French GAZ (Poclain) 24° High Pressure Flange - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20482-1021 | 10GS-21MPFL90 | 7347-93045 | 5/8 | 15.9 | 2.27 | 57.7 | 3.62 | 92.0 | 1.64 | 41.7 | .56 | 14.2 |
| G20482-2042 | 20GS-42MPFL90 | 7347-93485 | 1 1/4 | 31.8 | 3.51 | 89.2 | 5.90 | 149.9 | 3.09 | 78.5 | .56 | 14.2 |

# Hose Length Extender Caterpillar





| Part No. | Descr. | Prod. No. | ⊖ | | L | | C | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G20534-1212 | 12GS-12HLEC | 7347-76405 | 3/4 | 19.1 | 6.42 | 163.1 | 2.40 | 61.0 |
| G20534-1616 | 16GS-16HLEC | 7347-76395 | 1 | 25.4 | 7.09 | 180.1 | 2.61 | 66.3 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Hose Length Extender





| Part No. | Descr. | Prod. No. | ⊖ | | L | | C | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G20535-0808 | 8GS-8HLE | 7347-73265 | 1/2 | 12.7 | 3.70 | 94.0 | .75 | 19.1 |
| G20535-1212 | 12GS-12HLE | 7347-76815 | 3/4 | 19.1 | 4.80 | 121.9 | .78 | 19.8 |
| G20535-1616 | 16GS-16HLE | 7347-76625 | 1 | 25.4 | 5.43 | 137.9 | .98 | 24.9 |
| G20535-2020 | 20GS-20HLE | 7347-78585 | 1 1/4 | 31.8 | 6.77 | 172.0 | 1.17 | 29.7 |

## Hose Length Extender - 45° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | L | | C | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G20536-2020 | 20GS-20HLE45-103 | 7347-78895 | 1 1/4 | 31.8 | 9.80 | 248.9 | 6.19 | 157.2 |


# Hose Length Extender - 90° Bent Tube





| Part No. | Descr. | Prod. No. | ⟷ | | L | | C | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G20537-0808 | 8GS-8HLE90-086 | 7347-73195 | 1/2 | 12.7 | 3.39 | 86.1 | 1.91 | 48.5 |
| G20537-1212 | 12GS-12HLE90 | 7347-73965 | 3/4 | 19.1 | 4.39 | 111.5 | 2.38 | 60.5 |
| G20537-1616 | 16GS-16HLE90-127 | 7347-73705 | 1 | 25.4 | 5.00 | 127.0 | 2.76 | 70.1 |
| G20537-2020 | 20GS-20HLE90-155 | 7347-76705 | 1 1/4 | 31.8 | 6.10 | 154.9 | 3.30 | 83.8 |

# Male DIN 24° Cone - Light Series

Do not use at a pressure above DIN Light ratings.
Nut Hex per ISO Draft International Standards 12151–2.





| Part No. | Descr. | Prod. No. | ⟷ | | ⫼ | H1 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | mm |
| G20615-0612 | 6GS-12MDL | 7347-93445 | 3/8 | 9.5 | M18X1.5 | 22 | 2.51 | 63.8 | 1.10 | 27.9 | 12.0 |
| G20615-0815 | 8GS-15MDL | 7347-90625 | 1/2 | 12.7 | M22X1.5 | 24 | 2.48 | 63.0 | 1.00 | 25.4 | 15.0 |
| G20615-1222 | 12GS-22MDL | 7347-93565 | 3/4 | 19.1 | M30X2.0 | 32 | 3.13 | 79.5 | 1.12 | 28.5 | 22.0 |
| G20615-1628 | 16GS-28MDL | 7347-91495 | 1 | 25.4 | M36X2.0 | 41 | 3.54 | 89.9 | 1.31 | 33.3 | 28.0 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female DIN 24° Cone Swivel - Light Series with O-Ring

Do not use at a pressure above DIN Light ratings.
Nut Hex per ISO Draft International Standards 12151–2.









| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H2 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | mm |
| G20645-0612 | 6GS-12FDLORX | 7347-92815 | 3/8 | 9.5 | M18X1.5 | 22 | 2.87 | 72.9 | 1.46 | 37.1 | 12.0 |
| G20645-0815 | 8GS-15FDLORX | 7347-90595 | 1/2 | 12.7 | M22X1.5 | 22 | 2.87 | 72.9 | 1.40 | 35.6 | 15.0 |
| G20645-1018 | 10GS-18FDLORX | 7347-92105 | 5/8 | 15.9 | M26X1.5 | 32 | 3.61 | 91.7 | 1.63 | 41.4 | 18.0 |
| G20645-1222 | 12GS-22FDLORX | 7347-92125 | 3/4 | 19.1 | M30X2.0 | 36 | 3.82 | 97.0 | 1.81 | 46.0 | 22.0 |
| G20645-1228 | 12GS-28FDLORX | 7347-92165 | 3/4 | 19.1 | M36X2.0 | 41 | 3.90 | 99.1 | 1.89 | 48.1 | 28.0 |
| G20645-1628 | 16GS-28FDLORX | 7347-90795 | 1 | 25.4 | M36X2.0 | 41 | 4.13 | 104.9 | 1.91 | 48.5 | 28.0 |
| G20645-2035 | 20GS-35FDLORX | 7347-94135 | 1 1/4 | 31.8 | M45X2.0 | 50 | 5.21 | 132.3 | 2.41 | 61.2 | 35.0 |

# Female DIN 24° Cone Swivel - Light Series with O-Ring - 45° Bent Tube

Do not use at a pressure above DIN Light ratings.
Nut Hex per ISO Draft International Standards 12151–2.









| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | mm |
| G20650-0815 | 8GS-15FDLORX45 | 7347-90605 | 1/2 | 12.7 | M22X1.5 | 27 | .79 | 20.1 | 3.72 | 94.5 | 2.25 | 57.2 | 15.0 |
| G20650-1222 | 12GS-22FDLORX45 | 7347-92525 | 3/4 | 19.1 | M30X2.0 | 36 | 1.17 | 29.7 | 5.35 | 135.9 | 3.34 | 84.8 | 22.0 |
| G20650-1628 | 16GS-28FDLORX45 | 7347-91525 | 1 | 25.4 | M36X2.0 | 41 | 1.21 | 30.7 | 6.12 | 155.5 | 3.90 | 99.1 | 28.0 |

# Female DIN 24° Cone Swivel - Light Series with O-Ring - 90° Bent Tube


Do not use at a pressure above DIN Light ratings.
Nut Hex per ISO Draft International Standards 12151–2.




| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | mm |
| G20655-0612 | 6GS-12FDLORX90 | 7347-92455 | 3/8 | 9.5 | M18X1.5 | 22 | 1.45 | 36.8 | 3.07 | 78.0 | 1.66 | 42.2 | 12.0 |
| G20655-0815 | 8GS-15FDLORX90 | 7347-90615 | 1/2 | 12.7 | M22X1.5 | 27 | 1.65 | 41.9 | 3.46 | 87.9 | 1.98 | 50.3 | 15.0 |
| G20655-1018 | 10GS-18FDLORX90 | 7347-92515 | 5/8 | 15.9 | M26X1.5 | 32 | 2.03 | 51.6 | 4.47 | 113.5 | 2.49 | 63.3 | 18.0 |
| G20655-1222 | 12GS-22FDLORX90M | 7347-92135 | 3/4 | 19.1 | M30X2.0 | 36 | 2.44 | 62.0 | 4.86 | 123.4 | 2.86 | 72.6 | 22.0 |
| G20655-1628 | 16GS-28FDLORX90M | 7347-90765 | 1 | 25.4 | M36X2.0 | 41 | 2.76 | 70.1 | 5.82 | 147.8 | 2.71 | 68.8 | 28.0 |

# Male French GAZ






| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G20675-0817 | 8GS-17MFG | 7347-90655 | 1/2 | 12.7 | M24X1.5 | 26 | 2.61 | 66.3 | 1.14 | 29.0 |
| G20675-1221 | 12GS-21MFG | 7347-94075 | 3/4 | 19.1 | M30X1.5 | 32 | 3.23 | 82.0 | 1.22 | 31.0 |
| G20675-1227 | 12GS-27MFG | 7347-93055 | 3/4 | 19.1 | M36X1.5 | 42 | 3.33 | 84.6 | 1.32 | 33.5 |
| G20675-1634 | 16GS-34MFG | 7347-93155 | 1 | 25.4 | M45X1.5 | 50 | 3.70 | 94.0 | 1.46 | 37.1 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Female French GAZ Swivel (Female Kobelco)





| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H2 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | mm |
| G20680-0817 | 8GS-17FFGX | 7347-90665 | 1/2 | 12.7 | M24X1.5 | 30 | 2.68 | 68.1 | 1.20 | 30.5 | 16.8 |
| G20680-1021 | 10GS-21FFGX | 7347-93025 | 5/8 | 15.9 | M30X1.5 | 36 | 3.44 | 87.4 | 1.44 | 36.6 | 21.3 |
| G20680-1221 | 12GS-21FFGX | 7347-94715 | 3/4 | 19.1 | M30X1.5 | 36 | 3.27 | 83.1 | 1.29 | 32.8 | 21.3 |
| G20680-1227 | 12GS-27FFGX | 7347-93075 | 3/4 | 19.1 | M36X1.5 | 41 | 3.41 | 86.6 | 1.40 | 35.6 | 26.6 |
| G20680-1627 | 16GS-27FFGX | 7347-94725 | 1 | 25.4 | M36X1.5 | 41 | 3.41 | 86.6 | 1.40 | 35.6 | 26.6 |
| G20680-1634 | 16GS-34FFGX | 7347-93175 | 1 | 25.4 | M45X1.5 | 55 | 3.76 | 95.5 | 1.54 | 39.1 | 33.5 |


## Female French GAZ Swivel - 90° Bent Tube (Female Kobelco)





| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G20690-1021 | 10GS-21FFGX90 | 7347-93035 | 5/8 | 15.9 | M30X1.5 | 36 | 1.77 | 45.0 | 3.62 | 92.0 | 1.64 | 41.7 |
| G20690-1221 | 12GS-21FFGX90 | 7347-94735 | 3/4 | 19.1 | M30X1.5 | 36 | 2.00 | 50.8 | 4.91 | 124.7 | 2.90 | 73.7 |
| G20691-1227 | 12GS5K-27FFGX90-060 | 7347-78645 | 3/4 | 19.1 | M36X1.5 | 41 | 2.36 | 59.9 | 4.91 | 124.7 | 2.90 | 73.7 |
| G20690-1627 | 16GS-27FFGX90 | 7347-94745 | 1 | 25.4 | M36X1.5 | 41 | 2.64 | 67.1 | 5.94 | 150.9 | 3.72 | 94.5 |
| G20691-1634 | 16GS5K-34FFGX90-065 | 7347-78655 | 1 | 25.4 | M45X1.5 | 55 | 2.56 | 65.0 | 5.67 | 144.0 | 3.45 | 87.6 |

# Male DIN 24° Cone - Heavy Series









| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | mm |
| G20715-0612 | 6GS-12MDH | 7347-01785 | 3/8 | 9.5 | M20X1.5 | 22 | 2.51 | 63.8 | 1.10 | 27.9 | 12.0 |
| G20715-0614 | 6GS-14MDH | 7347-92675 | 3/8 | 9.5 | M22X1.5 | 24 | 2.59 | 65.8 | 1.18 | 30.0 | 14.0 |
| G20715-0816 | 8GS-16MDH | 7347-91325 | 1/2 | 12.7 | M24X1.5 | 27 | 1.17 | 29.7 | 1.18 | 30.0 | 16.0 |
| G20715-1020 | 10GS-20MDH | 7347-92695 | 5/8 | 15.9 | M30X2.0 | 32 | 3.35 | 85.1 | 1.37 | 34.8 | 20.0 |
| G20715-1220 | 12GS-20MDH | 7347-92255 | 3/4 | 19.1 | M30X2.0 | 32 | 3.35 | 85.1 | 1.34 | 34.0 | 20.0 |
| G20715-1225 | 12GS-25MDH | 7347-92265 | 3/4 | 19.1 | M36X2.0 | 41 | 3.50 | 88.9 | 1.50 | 38.1 | 25.0 |
| G20715-1230 | 12GS-30MDH | 7347-93765 | 3/4 | 19.1 | M42X2.0 | 46 | 3.90 | 99.1 | 1.06 | 26.9 | 30.0 |
| G20715-1625 | 16GS-25MDH | 7347-91505 | 1 | 25.4 | M36X2.0 | 41 | 3.82 | 97.0 | 1.58 | 40.1 | 25.0 |
| G20715-1630 | 16GS-30MDH | 7347-91515 | 1 | 25.4 | M42X2.0 | 46 | 3.90 | 99.1 | 1.66 | 42.2 | 30.0 |
| G20715-2038 | 20GS-38MDH | 7347-93295 | 1 1/4 | 31.8 | M52X2.0 | 55 | 4.84 | 122.9 | 2.04 | 51.8 | 38.0 |

# Female DIN 24° Cone Swivel - Heavy Series with O-Ring

Nut Hex per ISO Draft International Standards 12151–2.









| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H2 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | mm |
| G20720-0610 | 6GS-10FDHORX | 7347-92635 | 3/8 | 9.5 | M18X1.5 | 22 | 3.24 | 82.3 | 1.41 | 35.8 | 10.0 |
| G20720-0612 | 6GS-12FDHORX | 7347-92645 | 3/8 | 9.5 | M20X1.5 | 24 | 2.87 | 72.9 | 1.46 | 37.1 | 12.0 |
| G20720-0614 | 6GS-14FDHORX | 7347-92085 | 3/8 | 9.5 | M22X1.5 | 27 | 2.97 | 75.4 | 1.56 | 39.6 | 14.0 |
| G20720-0812 | 8GS-12FDHORX | 7347-95195 | 1/2 | 12.7 | M20X1.5 | 24 | 2.87 | 72.9 | 1.53 | 38.9 | 12.0 |
| G20720-0814 | 8GS-14FDHORX | 7347-92095 | 1/2 | 12.7 | M22X1.5 | 27 | 3.01 | 76.5 | 1.53 | 38.9 | 14.0 |
| G20720-0816 | 8GS-16FDHORX | 7347-91335 | 1/2 | 12.7 | M24X1.5 | 30 | 3.11 | 79.0 | 1.63 | 41.4 | 16.0 |
| G20720-0820 | 8GS-20FDHORX | 7347-92715 | 1/2 | 12.7 | M30X2.0 | 36 | 3.11 | 79.0 | 1.96 | 49.9 | 20.0 |
| G20720-1020 | 10GS-20FDHORX | 7347-92115 | 5/8 | 15.9 | M30X2.0 | 36 | 3.94 | 100.1 | 1.96 | 49.9 | 20.0 |
| G20720-1025 | 10GS-25FDHORX | 7347-93425 | 5/8 | 15.9 | M36X2.0 | 46 | 4.09 | 103.9 | 2.11 | 53.6 | 25.0 |
| G20720-1220 | 12GS-20FDHORX | 7347-92145 | 3/4 | 19.1 | M30X2.0 | 36 | 4.06 | 103.1 | 2.05 | 52.1 | 20.0 |
| G20720-1225 | 12GS-25FDHORX | 7347-92155 | 3/4 | 19.1 | M36X2.0 | 46 | 4.23 | 107.4 | 2.22 | 56.4 | 25.0 |
| G20720-1625 | 16GS-25FDHORX | 7347-91535 | 1 | 25.4 | M36X2.0 | 46 | 4.57 | 116.1 | 2.35 | 59.7 | 25.0 |
| G20720-1630 | 16GS-30FDHORX | 7347-90805 | 1 | 25.4 | M42X2.0 | 50 | 4.65 | 118.1 | 2.43 | 61.7 | 30.0 |
| G20720-1638 | 16GS-38FDHORX | 7347-94225 | 1 | 25.4 | M52X2.0 | 60 | 4.40 | 111.8 | 2.17 | 55.1 | 38.0 |
| G20720-2038 | 20GS-38FDHORX | 7347-93305 | 1 1/4 | 31.8 | M52X2.0 | 60 | 5.71 | 145.0 | 2.91 | 73.9 | 38.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 45° Bent Tube

Nut Hex per ISO Draft International Standards 12151–2.









| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | mm |
| G20725-0612 | 6GS-12FDHORX45 | 7347-92425 | 3/8 | 9.5 | M20X1.5 | 24 | 2.87 | 72.9 | 2.97 | 75.4 | 1.41 | 35.8 | 12.0 |
| G20725-0614 | 6GS-14FDHORX45 | 7347-92465 | 3/8 | 9.5 | M22X1.5 | 27 | 2.97 | 75.4 | 3.31 | 84.1 | 1.46 | 37.1 | 14.0 |
| G20725-0816 | 8GS-16FDHORX45 | 7347-91345 | 1/2 | 12.7 | M24X1.5 | 30 | .85 | 21.6 | 3.70 | 94.0 | 2.23 | 56.6 | 16.0 |
| G20725-1020 | 10GS-20FDHORX45 | 7347-92325 | 5/8 | 15.9 | M30X2.0 | 36 | .98 | 24.9 | 4.79 | 121.7 | 2.81 | 71.4 | 20.0 |
| G20725-1220 | 12GS-20FDHORX45 | 7347-93285 | 3/4 | 19.1 | M30X2.0 | 36 | 1.17 | 29.7 | 6.33 | 160.8 | 4.33 | 110.0 | 20.0 |
| G20725-1225 | 12GS-25FDHORX45M | 7347-92175 | 3/4 | 19.1 | M36X2.0 | 46 | 1.23 | 31.2 | 5.31 | 134.9 | 3.40 | 86.4 | 25.0 |
| G20725-1625 | 16GS-25FDHORX45M | 7347-91545 | 1 | 25.4 | M36X2.0 | 46 | 1.38 | 35.1 | 3.90 | 99.1 | 1.66 | 42.2 | 25.0 |
| G20725-1630 | 16GS-30FDHORX45 | 7347-91565 | 1 | 25.4 | M42X2.0 | 50 | 1.38 | 35.1 | 6.29 | 159.8 | 4.07 | 103.4 | 30.0 |
| G20725-2038 | 20GS-38FDHORX45M | 7347-93415 | 1 1/4 | 31.8 | M52X2.0 | 60 | 1.67 | 42.4 | 7.72 | 196.1 | 4.92 | 125.0 | 38.0 |

# Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 90° Bent Tube

Nut Hex per ISO Draft International Standards 12151–2.









| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | mm |
| G20730-0612 | 6GS-12FDHORX90 | 7347-92435 | 3/8 | 9.5 | M20X1.5 | 24 | 1.45 | 36.8 | 3.07 | 78.0 | 1.46 | 37.1 | 12.0 |
| G20730-0614 | 6GS-14FDHORX90 | 7347-92475 | 3/8 | 9.5 | M22X1.5 | 27 | 1.57 | 39.9 | 3.07 | 78.0 | 1.66 | 42.2 | 14.0 |
| G20730-0816 | 8GS-16FDHORX90M | 7347-91485 | 1/2 | 12.7 | M24X1.5 | 30 | 1.73 | 43.9 | 3.39 | 86.1 | 1.91 | 48.5 | 16.0 |
| G20730-1020 | 10GS-20FDHORX90M | 7347-92335 | 5/8 | 15.9 | M30X2.0 | 36 | 2.01 | 51.1 | 4.43 | 112.5 | 2.45 | 62.2 | 20.0 |
| G20730-1220 | 12GS-20FDHORX90 | 7347-92185 | 3/4 | 19.1 | M30X2.0 | 36 | 2.44 | 62.0 | 4.86 | 123.4 | 2.85 | 72.4 | 20.0 |
| G20730-1225 | 12GS-25FDHORX90M | 7347-92195 | 3/4 | 19.1 | M36X2.0 | 46 | 2.52 | 64.0 | 4.86 | 123.4 | 2.85 | 72.4 | 25.0 |
| G20730-1625 | 16GS-25FDHORX90 | 7347-91555 | 1 | 25.4 | M36X2.0 | 46 | 2.99 | 76.0 | 5.94 | 150.9 | 3.72 | 94.5 | 25.0 |
| G20730-1630 | 16GS-30FDHORX90M | 7347-90775 | 1 | 25.4 | M42X2.0 | 50 | 2.99 | 76.0 | 5.81 | 147.6 | 3.59 | 91.2 | 30.0 |

## Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 90° Bent Tube - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | mm | " | mm | " | mm | " | mm | mm |
| G20730-2038 | 20GS-38FDHORX90M | 7347-93315 | 1 1/4 | 31.8 | M52X2.0 | 60 | 3.43 | 87.1 | 7.11 | 180.6 | 4.31 | 109.5 | 38.0 |


## Male Kobelco (Male French GAZ)





| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | mm | " | mm | " | mm |
| G20735-1222 | 12GS-22MKB | 7347-73665 | 3/4 | 19.1 | M30X1.5 | 36 | 3.35 | 85.1 | 1.34 | 34.0 |
| G20735-1228 | 12GS-28MKB | 7347-73675 | 3/4 | 19.1 | M36X1.5 | 41 | 3.62 | 92.0 | 1.61 | 40.9 |
| G20735-1628 | 16GS-28MKB | 7347-73095 | 1 | 25.4 | M36X1.5 | 50 | 3.98 | 101.1 | 1.74 | 44.2 |
| G20735-1635 | 16GS-35MKB | 7347-73025 | 1 | 25.4 | M45X1.5 | 50 | 3.74 | 95.0 | 1.50 | 38.1 |

## Male British Standard Pipe Parallel









| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | mm | " | mm | " | mm |
| G20810-0606 | 6GS-6MBSPP | 7347-01775 | 3/8 | 9.5 | 3/8–19 | 22 | 2.48 | 63.0 | 1.07 | 27.2 |
| G20810-0808 | 8GS-8MBSPP | 7347-91365 | 1/2 | 12.7 | 1/2–14 | 27 | 2.66 | 67.6 | 1.81 | 46.0 |
| G20810-1010 | 10GS-10MBSPP | 7347-92615 | 5/8 | 15.9 | 5/8–14 | 30 | 2.66 | 67.6 | 1.18 | 30.0 |
| G20810-1012 | 10GS-12MBSPP | 7347-92625 | 5/8 | 15.9 | 3/4–14 | 32 | 3.35 | 85.1 | 1.37 | 34.8 |
| G20810-1212 | 12GS-12MBSPP | 7347-92205 | 3/4 | 19.1 | 3/4–14 | 32 | 3.35 | 85.1 | 1.37 | 34.8 |
| G20810-1616 | 16GS-16MBSPP | 7347-90825 | 1 | 25.4 | 1–11 | 41 | 3.86 | 98.1 | 1.62 | 41.2 |
| G20810-2020 | 20GS-20MBSPP | 7347-93365 | 1 1/4 | 31.8 | 1 1/4–11 | 50 | 4.65 | 118.1 | 1.85 | 47.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female British Standard Parallel Pipe O-Ring Swivel









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G20830-0606 | 6GS-6FBSPORX | 7347-92235 | 3/8 | 9.5 | 3/8–19 | 22 | 2.34 | 59.4 | .93 | 23.6 | |
| G20830-0608 | 6GS-8FBSPORX | 7347-92705 | 3/8 | 9.5 | 1/2–14 | 27 | 2.40 | 61.0 | .93 | 23.6 | |
| G20830-0808 | 8GS-8FBSPORX | 7347-91405 | 1/2 | 12.7 | 1/2–14 | 27 | 2.40 | 61.0 | .93 | 23.6 | |
| G20830-1010 | 10GS-10FBSPORX | 7347-92405 | 5/8 | 15.9 | 5/8–14 | 30 | 3.35 | 85.1 | 1.18 | 30.0 | |
| G20830-1012 | 10GS-12FBSPORX | 7347-93965 | 5/8 | 15.9 | 3/4–14 | 30 | 3.35 | 85.1 | 1.37 | 34.8 | |
| G20830-1212 | 12GS-12FBSPORX | 7347-93995 | 3/4 | 19.1 | 3/4–14 | 32 | 3.41 | 86.6 | 1.40 | 35.6 | |
| G20830-1216 | 12GS-16FBSPORX | 7347-92585 | 3/4 | 19.1 | 1–11 | 41 | 3.74 | 95.0 | 1.40 | 35.6 | |
| G20830-1616 | 16GS-16FBSPORX | 7347-90815 | 1 | 25.4 | 1–11 | 41 | 3.74 | 95.0 | 1.52 | 38.6 | |
| G20830-1620 | 16GS-20FBSPORX | 7347-94195 | 1 | 25.4 | 1 1/4–11 | 50 | 3.27 | 83.1 | 1.03 | 26.2 | |
| G20830-2020 | 20GS-20FBSPORX | 7347-93375 | 1 1/4 | 31.8 | 1 1/4–11 | 50 | 4.59 | 116.6 | 1.79 | 45.5 | |

# Female British Standard Parallel Pipe O-Ring Swivel - 45° Bent Tube

S, M and L Drops and Hex per ISO Working Draft 12151–6.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm | " | mm |
| G20831-0606 | 6GS-6FBSPORX45 | 7347-92345 | 3/8 | 9.5 | 3/8–19 | 22 | .61 | 15.5 | 3.27 | 83.1 | 1.86 | 47.2 | |
| G20831-0808 | 8GS-8FBSPORX45M | 7347-91415 | 1/2 | 12.7 | 1/2–14 | 27 | .67 | 17.0 | 3.60 | 91.4 | 2.13 | 54.1 | |
| G20831-1010 | 10GS-10FBSPORX45 | 7347-92285 | 5/8 | 15.9 | 5/8–14 | 30 | 1.04 | 26.4 | 4.20 | 106.7 | 2.25 | 57.2 | |
| G20831-1212 | 12GS-12FBSPORX45 | 7347-94005 | 3/4 | 19.1 | 3/4–14 | 32 | 1.11 | 28.3 | 5.22 | 132.6 | 3.21 | 81.6 | |
| G20831-1616 | 16GS-16FBSPORX45M | 7347-92275 | 1 | 25.4 | 1–11 | 41 | 1.22 | 31.0 | 6.12 | 155.5 | 3.90 | 99.1 | |
| G20831-2020 | 20GS-20FBSPORX45M | 7347-93395 | 1 1/4 | 31.8 | 1 1/4–11 | 50 | 1.48 | 37.6 | 7.52 | 191.0 | 4.72 | 119.9 | |

# Female British Standard Parallel Pipe O-Ring Swivel - 90° Bent Tube


S, M and L Drops and Hex per ISO Working Draft 12151–6.





| Part No. | Descr. | Prod. No. | ⊖ | | Thread | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm | " | mm |
| G20832-0606 | 6GS-6FBSPORX90 | 7347-92355 | 3/8 | 9.5 | 3/8–19 | | 22 | 1.26 | 32.0 | 3.07 | 78.0 | 1.66 | 42.2 |
| G20832-0808 | 8GS-8FBSPORX90M | 7347-91425 | 1/2 | 12.7 | 1/2–14 | | 27 | 1.48 | 37.6 | 3.46 | 87.9 | 1.99 | 50.6 |
| G20832-1010 | 10GS-10FBSPORX90 | 7347-92295 | 5/8 | 15.9 | 5/8–14 | | 30 | 1.90 | 48.3 | 4.70 | 119.4 | 2.45 | 62.2 |
| G20832-1212 | 12GS-12FBSPORX90 | 7347-94015 | 3/4 | 19.1 | 3/4–14 | | 30 | 2.36 | 60.0 | 4.90 | 124.2 | 2.88 | 73.2 |
| G20832-1616 | 16GS-16FBSPORX90 | 7347-90785 | 1 | 25.4 | 1–11 | | 41 | 2.76 | 70.1 | 5.81 | 147.6 | 3.59 | 91.2 |
| G20832-2020 | 20GS-20FBSPORX90M | 7347-93405 | 1 1/4 | 31.8 | 1 1/4–11 | | 50 | 3.15 | 80.0 | 7.11 | 180.6 | 4.31 | 109.5 |

# Female British Standard Parallel Pipe O-Ring Swivel - 90° Block








| Part No. | Descr. | Prod. No. | ⊖ | | Thread | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm | " | mm |
| G20845-1212 | 12GS-12FBSPORX90BL | 7347-93955 | 3/4 | 19.1 | 3/4–14 | | 32 | 1.53 | 38.9 | 3.07 | 78.0 | 1.06 | 26.9 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Female British Flat-Face Swivel





| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G20855-1616 | 16GS-16FBFFX | 7347-78915 | 1 | 25.4 | 1–11 | 41 | 3.78 | 96.0 | 1.56 | 39.6 |

## Female Komatsu Style Japanese Metric Swivel


These female swivels have been marked with two small notches on the hex to identify them as the Komatsu style.





| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G20910-0808 | 8GS-8FKX | 7347-35245 | 1/2 | 12.7 | M22X1.5 | 27 | 27 | 2.93 | 74.4 | 1.46 | 37.1 |
| G20910-1010 | 10GS-10FKX | 7347-35345 | 5/8 | 15.9 | M24X1.5 | 30 | 32 | 3.74 | 95.0 | 1.76 | 44.7 |
| G20910-1212 | 12GS-12FKX | 7347-35445 | 3/4 | 19.1 | M30X1.5 | 32 | 36 | 4.00 | 101.6 | 2.00 | 50.8 |
| G20910-1616 | 16GS-16FKX | 7347-35555 | 1 | 25.4 | M33X1.5 | 41 | 41 | 4.51 | 114.6 | 2.29 | 58.2 |

## Female Japanese Industrial Standard 30° Flare Swivel





| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G20930-1212 | 12GS-12FJISX | 7347-76195 | 3/4 | 19.1 | 3/4–14 | 32 | 36 | 3.87 | 98.3 | 1.86 | 47.2 |
| G20930-1616 | 16GS-16FJISX | 7347-76005 | 1 | 25.4 | 1–11 | 41 | 41 | 4.25 | 108.0 | 2.03 | 51.6 |

## Female Japanese Industrial Standard 30° Flare Swivel - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G20930-2020 | 20GS-20FJISX | 7347-76235 | 1 1/4 | 31.8 | 1 1/4–11 | 27 | 50 | 5.35 | 135.9 | 2.56 | 65.0 |


## GS Ferrule for Wire Braid Hose

Consult eCrimp for wire braid types and sizes.




| Part No. | Descr. | Prod. No. | ⊖ | | L | | ⊙ | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G20995-0106 | 6GS1F-1 | 7347-02875 | 3/8 | 9.5 | 1.20 | 30.5 | .96 | 24.4 |
| G20995-0206 | 6GS1F-2 | 7347-02945 | 3/8 | 9.5 | 1.20 | 30.5 | 1.06 | 26.9 |
| G20995-0208 | 8GS1F-2 | 7347-02955 | 1/2 | 12.7 | 1.47 | 37.3 | 1.15 | 29.2 |
| G20995-0210 | 10GS1F-2 | 7347-02965 | 5/8 | 15.9 | 1.40 | 35.6 | 1.33 | 33.8 |
| G20995-0212 | 12GS1F-2 | 7347-02975 | 3/4 | 19.1 | 1.73 | 44.0 | 1.57 | 39.9 |
| G20995-0216 | 16GS1F-2 | 7347-02985 | 1 | 25.4 | 2.06 | 52.3 | 1.94 | 49.3 |
| G20995-0220 | 20GS1F-2 | 7347-02995 | 1 1/4 | 31.8 | 2.41 | 61.2 | 2.37 | 60.2 |

## GS Ferrule for 4-Spiral Hose





| Part No. | Descr. | Prod. No. | ⊖ | | L | | ⊙ | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G20995-0406 | 6GS1F-4 | 7347-03105 | 3/8 | 9.5 | 1.43 | 36.3 | 1.25 | 31.8 |
| G20995-0408 | 8GS1F-4 | 7347-03115 | 1/2 | 12.7 | 1.44 | 36.9 | 1.35 | 34.3 |
| G20995-0410 | 10GS1F-4 | 7347-03125 | 5/8 | 15.9 | 1.88 | 47.8 | 1.64 | 41.7 |
| G20995-0412 | 12GS1F-4 | 7347-03135 | 3/4 | 19.1 | 2.00 | 50.8 | 1.80 | 45.7 |
| G20995-0416 | 16GS1F-4 | 7347-03145 | 1 | 25.4 | 2.22 | 56.4 | 2.07 | 52.6 |
| G20995-0420 | 20GS1F-4 | 7347-03155 | 1 1/4 | 31.8 | 2.67 | 67.8 | 2.42 | 61.5 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## GS Ferrule for 6-Spiral Hose




| Part No. | Descr. | Prod. No. | ⊖ | | L | | ⌀ | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G20995-0620 | 20GS1F-6 | 7347-02905 | 1 1/4 | 31.8 | 2.87 | 72.9 | 2.67 | 67.8 |


## GS Ferrule for ID5K Hose





| Part No. | Descr. | Prod. No. | ⊖ | | L | | ⌀ | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G20997-0408 | 8GSID1F-4 | 7347-85915 | 1/2 | 12.7 | 1.46 | 37.0 | 1.21 | 30.7 |
| G20997-0410 | 10GSID1F-4 | 7347-85925 | 5/8 | 15.9 | 1.81 | 46.0 | 1.43 | 36.3 |
| G20997-0412 | 12GSID1F-4 | 7347-85935 | 3/4 | 19.1 | 2.01 | 51.1 | 1.59 | 40.4 |
| G20997-0416 | 16GSID1F-4 | 7347-85945 | 1 | 25.4 | 2.01 | 51.1 | 1.92 | 48.8 |

## 1 1/4" Special One-Piece Couplings - Male Pipe (NPTF - 30° Cone Seat)

MGS Couplings for use with MC4–20 Crimper Only.









| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G21100-2020 | 20MGS-20MP | 7347-86005 | 1 1/4 | 31.8 | 1 1/4–11 1/2 | 1 3/4 | 5.00 | 127.0 | 2.20 | 55.9 |

# 1 1/4" Special One-Piece Couplings - Male JIC 37° Flare

MGS Couplings for use with MC4–20 Crimper Only.









| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G21165-2020 | 20MGS-20MJ | 7347-86015 | 1 1/4 | 31.8 | 1 5/8–12 | 1 3/4 | 4.92 | 125.0 | 2.12 | 53.9 |

# 1 1/4" Special One-Piece Couplings - Female JIC 37° Flare Swivel

MGS Couplings for use with MC4–20 Crimper Only.





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G21170-2020 | 20MGS-20FJX | 7347-86025 | 1 1/4 | 31.8 | 1 5/8–12 | 1 7/8 | 2 | 5.35 | 135.9 | 2.56 | 65.0 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# 1 1/4" Special One-Piece Couplings - Female JIC 37° Flare Swivel - 90° Bent Tube

MGS Couplings for use with MC4–20 Crimper Only.





| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G21180-2020 | 20MGS-20FJX90M-078 | 7347-86035 | 1 1/4 | 31.8 | 1 5/8–12 | 2 | 3.07 | 78.0 | 6.85 | 174.0 | 4.05 | 102.9 |

# 1 1/4" Special One-Piece Couplings - Female Flat-Face O-Ring Swivel


MGS Couplings for use with MC4–20 Crimper Only.





| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G21230-2020 | 20MGS-20FFORX | 7347-86045 | 1 1/4 | 31.8 | 1 11/16–12 | 50 | 50 | 5.04 | 128.0 | 2.24 | 56.9 |

# 1 1/4" Special One-Piece Couplings - Female Flat-Face O-Ring Swivel - 90° Bent Tube

MGS Couplings for use with MC4–20 Crimper Only.





| Part No. | Descr. | Prod. No. | ⊖ | | Thread I.D. | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G21240-2020 | 20MGS-20FFORX90M | 7347-86055 | 1 1/4 | 31.8 | 1 11/16–12 | 50 | 3.07 | 78.0 | 6.77 | 172.0 | 3.97 | 100.8 |

# 1 1/4" Special One-Piece Couplings - Code 61 O-Ring Flange

MGS Couplings for use with MC4–20 Crimper Only.





| Part No. | Descr. | Prod. No. | ⊖ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G21300-2020 | 20MGS-20FL | 7347-86065 | 1 1/4 | 31.8 | 2.00 | 50.8 | 5.75 | 146.1 | 2.95 | 74.9 | .32 | 8.1 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# 1 1/4" Special One-Piece Couplings - Code 61 O-Ring Flange - 45° Bent Tube


MGS Couplings for use with MC4–20 Crimper Only.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G21307-2020 | 20MGS-20FL45S-032 | 7347-86075 | 1 1/4 | 31.8 | 2.00 | 50.8 | 1.26 | 32.0 | 6.69 | 169.9 | 3.89 | 98.8 | .32 | 8.1 |

# 1 1/4" Special One-Piece Couplings - Code 61 O-Ring Flange - 90° Bent Tube


MGS Couplings for use with MC4–20 Crimper Only.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G21315-2020 | 20MGS-20FL90M-090 | 7347-86085 | 1 1/4 | 31.8 | 2.00 | 50.8 | 3.54 | 89.9 | 6.54 | 166.1 | 3.74 | 95.0 | .32 | 8.1 |

# 1 1/4" Special One-Piece Couplings - Code 62 O-Ring Flange


MGS Couplings for use with MC4–20 Crimper Only.





| Part No. | Descr. | Prod. No. | ⊖ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G21350-2020 | 20MGS-20FLH | 7347-86135 | 1 1/4 | 31.8 | 2.13 | 54.1 | 5.75 | 146.1 | 2.95 | 74.9 | .41 | 10.4 |

# 1 1/4" Special One-Piece Couplings - Male DIN 24° Cone - Heavy Series

MGS Couplings for use with MC4–20 Crimper Only.








Male 24° Cone

| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | mm | " | mm | " | mm |
| G21715-2038 | 20MGS-38MDH | 7347-86115 | 1 1/4 | 31.8 | M52X2.0 | | 55 | 4.84 | 122.9 | 2.04 | 51.8 |

# 1 1/4" Special One-Piece Couplings - Female DIN 24° Cone Swivel - Heavy Series with O-Ring

MGS Couplings for use with MC4–20 Crimper Only.





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | mm | " | mm | " | mm |
| G21720-2038 | 20MGS-38FDHORX | 7347-86095 | 1 1/4 | 31.8 | M52X2.0 | | 60 | 5.71 | 145.0 | 2.91 | 73.9 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# 1 1/4" Special One-Piece Couplings - Female British Standard Pipe Parallel O-Ring Swivel


MGS Couplings for use with MC4–20 Crimper Only.




| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G21830-2020 | 20MGS-20FBSPORX | 7347-86105 | 1 1/4 | 31.8 | 1 1/4–11 | 60 | 4.59 | 116.6 | 1.79 | 45.5 |


## Male Pipe (NPTF - 30° Cone Seat)





| Part No. | Descr. | Prod. No. | ⊖ | | ⦚ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G22100-2424 | 24GSP-24MP | 7347-20725 | 1 1/2 | 38.1 | 1 1/2–11 1/2 | 2 | 5.24 | 133.1 | 2.34 | 59.4 |
| G22100-3232 | 32GSP-32MP | 7347-20795 | 2 | 50.8 | 2–11 1/2 | 2.50 | 6.05 | 153.7 | 2.43 | 61.7 |


## API Line Pipe Connection





| Part No. | Descr. | Prod. No. | ⊖ | | ⦚ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G22102-2424 | 24GSP-24API-LP | 7347-85665 | 1 1/2 | 38.1 | 1 1/2–11 1/2 | 2 | 5.45 | 138.4 | 2.65 | 67.3 |
| G22102-3232 | 32GSP-32MPAPI | 7347-85415 | 2 | 50.8 | 2–11 1/2 | 2.50 | 7.90 | 200.7 | 4.28 | 108.7 |

## Male Pipe (NPTF - 30° Cone Seat) - Long Hex









| Part No. | Descr. | Prod. No. | ⊖ | | ⦚ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G22103-2424 | 24GSP-24MPLH | 7347-20745 | 1 1/2 | 38.1 | 1 1/2–11 1/2 | 2 | 6.29 | 159.8 | 3.40 | 86.4 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male JIC 37° Flare





| Part No. | Descr. | Prod. No. | ⊖ | | ≡ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G22165-2420 | 24GSP-20MJ | 7347-81455 | 1 1/2 | 38.1 | 1 5/8–12 | 1.97 | 5.00 | 127.0 | 2.10 | 53.3 |
| G22165-2424 | 24GSP-24MJ | 7347-81465 | 1 1/2 | 38.1 | 1 7/8–12 | 1.97 | 5.12 | 130.1 | 2.22 | 56.4 |
| G22165-3232 | 32GSP-32MJ | 7347-81535 | 2 | 50.8 | 2 1/2–12 | 2.56 | 6.34 | 161.0 | 2.72 | 69.1 |


## Female JIC 37° Flare Swivel





| Part No. | Descr. | Prod. No. | ⊖ | | ≡ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G22170-2424 | 24GSP-24FJX | 7347-82455 | 1 1/2 | 38.1 | 1 7/8–12 | 1.97 | 2.36 | 5.64 | 143.3 | 2.74 | 69.6 |
| G22170-2432 | 24GSP-32FJX | 7347-82465 | 1 1/2 | 38.1 | 2 1/2–12 | 2.56 | 2.98 | 6.88 | 174.8 | 3.17 | 80.5 |
| G22170-3232 | 32GSP-32FJX | 7347-82525 | 2 | 50.8 | 2 1/2–12 | 2.56 | 2.95 | 6.80 | 172.7 | 3.17 | 80.5 |


## Female JIC 37° Flare Swivel - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | ≡ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G22175-2424 | 24GSP-24FJX45-050 | 7347-83735 | 1 1/2 | 38.1 | 1 7/8–12 | 2 1/3 | 1.97 | 50.0 | 9.17 | 232.9 | 6.28 | 159.5 |

# Female JIC 37° Flare Swivel - 90° Bent Tube









| Part No. | Descr. | Prod. No. | ⊖ | | ≡ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G22179-2424 | 24GSP-24FJX90-089 | 7347-84745 | 1 1/2 | 38.1 | 1 7/8–12 | 2 1/3 | 3.50 | 88.9 | 8.35 | 212.1 | 5.45 | 138.4 |
| G22180-2424 | 24GSP-24FJX90-118 | 7347-84755 | 1 1/2 | 38.1 | 1 7/8–12 | 2 1/3 | 4.65 | 118.1 | 7.46 | 189.5 | 4.56 | 115.8 |
| G22180-3232 | 32GSP-32FJX90M | 7347-84785 | 2 | 50.8 | 2 1/2–12 | 3 | 5.51 | 140.0 | 10.71 | 272.0 | 7.07 | 179.6 |

# Male Flat-Face O-Ring

Includes Peroxide–cured O–Ring.
Metric Hex per ISO Draft International Standard 12151–1.
Utilizes SAE J1453 Captive O–Ring Groove for Improved O–Ring Retention.









| Part No. | Descr. | Prod. No. | ⊖ | | ≡ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G22225-2424 | 24GSP-24MFFOR | 7347-23905 | 1 1/2 | 38.1 | 2–12 | 55 | 5.12 | 130.1 | 2.22 | 56.4 |

# Female Flat-Face O-Ring Swivel

Metric Hex per ISO Draft International Standard 12151–1.
SAE J1453 O–Ring Face Seal.








| Part No. | Descr. | Prod. No. | ⊖ | | ≡ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G22230-2424 | 24GSP-24FFORX | 7347-30725 | 1 1/2 | 38.1 | 2–12 | 55 | 2 1/4 | 5.17 | 131.3 | 2.37 | 60.2 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female Flat-Face O-Ring Swivel - 45° Bent Tube


Metric Hex per ISO Draft International Standard 12151–1.
SAE J1453 O–Ring Face Seal.




| Part No. | Descr. | Prod. No. | ⟷ | | ≋ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22235-2424 | 24GSP-24FFORX45-036 | 7347-31725 | 1 1/2 | 38.1 | 2–12 | 2 1/4 | 2.70 | 68.6 | 7.61 | 193.3 | 4.81 | 122.2 |

# Female Flat-Face O-Ring Swivel - 90° Bent Tube


Metric Hex per ISO Draft International Standard 12151–1.
SAE J1453 O–Ring Face Seal.




| Part No. | Descr. | Prod. No. | ⟷ | | ≋ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22240-2424 | 24GSP-24FFORX90M | 7347-33725 | 1 1/2 | 38.1 | 2–12 | 2 1/4 | 3.41 | 86.6 | 7.61 | 193.3 | 4.81 | 122.2 |
| G22241-2424 | 24GSP-24FFORX90L | 7347-34725 | 1 1/2 | 38.1 | 2–12 | 2 1/4 | 5.54 | 140.7 | 7.61 | 193.3 | 4.81 | 122.2 |

# Code 61 O-Ring Flange


–24FL Max. W.P. 3,000 psi; –32FL Max. W.P. 3,000 psi.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22300-2420 | 24GSP-20FL | 7347-41715 | 1 1/2 | 38.1 | 2.00 | 50.8 | 5.74 | 145.8 | 2.85 | 72.4 | .32 | 8.1 |
| G22300-2424 | 24GSP-24FL | 7347-41725 | 1 1/2 | 38.1 | 2.38 | 60.5 | 6.02 | 152.9 | 3.12 | 79.3 | .32 | 8.1 |
| G22300-2432 | 24GSP-32FL | 7347-41735 | 1 1/2 | 38.1 | 2.81 | 71.4 | 5.79 | 147.1 | 2.99 | 76.0 | .38 | 9.7 |
| G22300-3224 | 32GSP-24FL | 7347-41785 | 2 | 50.8 | 2.38 | 60.5 | 6.53 | 165.9 | 2.49 | 63.3 | .32 | 8.1 |
| G22300-3232 | 32GSP-32FL | 7347-41795 | 2 | 50.8 | 2.81 | 71.4 | 6.27 | 159.3 | 2.65 | 67.3 | .38 | 9.7 |
| G22300-3240 | 32GSP-40FL | 7347-41805 | 2 | 50.8 | 3.31 | 84.1 | 8.52 | 216.4 | 2.99 | 76.0 | .38 | 9.7 |

# Code 61 O-Ring Flange - 22 1/2° Bent Tube

–24FL Max. W.P. 3,000 psi; –32FL Max. W.P. 3,000 psi.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22302-2424 | 24GSP-24FL22M | 7347-42725 | 1 1/2 | 38.1 | 2.38 | 60.5 | .71 | 18.0 | 8.31 | 211.0 | 5.41 | 137.4 | .32 | 8.1 |
| G22302-2432 | 24GSP-32FL22M | 7347-42735 | 1 1/2 | 38.1 | 2.81 | 71.4 | .87 | 22.1 | 8.43 | 214.1 | 5.52 | 140.2 | .38 | 9.7 |
| G22302-3232 | 32GSP-32FL22M | 7347-42795 | 2 | 50.8 | 2.81 | 71.4 | .97 | 24.6 | 10.83 | 275.1 | 7.22 | 183.4 | .38 | 9.7 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Code 61 O-Ring Flange - 30° Bent Tube


–24FL Max. W.P. 3,000 psi; –32FL Max. W.P. 3,000 psi.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22304-2424 | 24GSP-24FL30S | 7347-43725 | 1 1/2 | 38.1 | 2.38 | 60.5 | .98 | 24.9 | 8.23 | 209.0 | 5.31 | 134.9 | .32 | 8.1 |
| G22304-2432 | 24GSP-32FL30M | 7347-43735 | 1 1/2 | 38.1 | 2.81 | 71.4 | 1.26 | 32.0 | 8.27 | 210.1 | 5.39 | 136.9 | .38 | 9.7 |
| G22304-3232 | 32GSP-32FL30M | 7347-43795 | 2 | 50.8 | 2.81 | 71.4 | 1.25 | 31.8 | 10.70 | 271.8 | 7.10 | 180.3 | .38 | 9.7 |

# Code 61 O-Ring Flange - 45° Bent Tube


–24FL Max. W.P. 3,000 psi; –32FL Max. W.P. 3,000 psi.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22306-2420 | 24GSP-20FL45S | 7347-44715 | 1 1/2 | 38.1 | 2.00 | 50.8 | 1.26 | 32.0 | 7.09 | 180.1 | 4.49 | 114.1 | .32 | 8.1 |
| G22306-2424 | 24GSP-24FL45S | 7347-44725 | 1 1/2 | 38.1 | 2.38 | 60.5 | 1.50 | 38.1 | 7.95 | 201.9 | 5.05 | 128.3 | .32 | 8.1 |
| G22306-2432 | 24GSP-32FL45S | 7347-44735 | 1 1/2 | 38.1 | 2.81 | 71.4 | 2.05 | 52.1 | 7.87 | 199.9 | 4.97 | 126.2 | .38 | 9.7 |
| G22306-3224 | 32GSP-24FL45S | 7347-44785 | 2 | 50.8 | 2.38 | 60.5 | 1.50 | 38.1 | 8.10 | 205.8 | 4.48 | 113.8 | .32 | 8.1 |
| G22307-3232 | 32GSP-32FL45-066 | 7347-44805 | 2 | 50.8 | 2.81 | 71.4 | 2.60 | 66.0 | 10.12 | 257.1 | 6.50 | 165.1 | .38 | 9.7 |

# Code 61 O-Ring Flange - 60° Bent Tube


–24FL Max. W.P. 3,000 psi; –32FL Max. W.P. 3,000 psi.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22308-2424 | 24GSP-24FL60S | 7347-45725 | 1 1/2 | 38.1 | 2.38 | 60.5 | 2.08 | 52.8 | 9.09 | 230.9 | 6.20 | 157.5 | .32 | 8.1 |
| G22309-2432 | 24GSP-32FL60S | 7347-45735 | 1 1/2 | 38.1 | 2.81 | 71.4 | 2.95 | 74.9 | 9.21 | 233.9 | 6.30 | 160.0 | .38 | 9.7 |
| G22309-3232 | 32GSP-32FL60S | 7347-45805 | 2 | 50.8 | 2.81 | 71.4 | 2.95 | 74.9 | 10.20 | 259.1 | 6.56 | 166.6 | .38 | 9.7 |

# Code 61 O-Ring Flange - 67 1/2° Bent Tube


–24FL Max. W.P. 3,000 psi; –32FL Max. W.P. 3,000 psi.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22311-2424 | 24GSP-24FL67S | 7347-46725 | 1 1/2 | 38.1 | 2.38 | 60.5 | 2.40 | 61.0 | 8.90 | 226.1 | 5.90 | 149.9 | .32 | 8.1 |
| G22311-2432 | 24GSP-32FL67S | 7347-46735 | 1 1/2 | 38.1 | 2.81 | 71.4 | 3.33 | 84.6 | 10.20 | 259.1 | 5.90 | 149.9 | .38 | 9.7 |
| G22311-3232 | 32GSP-32FL67S | 7347-46795 | 2 | 50.8 | 2.81 | 71.4 | 3.84 | 97.5 | 10.20 | 259.1 | 6.56 | 166.6 | .38 | 9.7 |

# Code 61 O-Ring Flange - 90° Bent Tube


–24FL Max. W.P. 3,000 psi; –32FL Max. W.P. 3,000 psi.
S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22314-2420 | 24GSP-20FL90S | 7347-47715 | 1 1/2 | 38.1 | 2.00 | 50.8 | 2.68 | 68.1 | 6.81 | 173.0 | 3.92 | 99.6 | .32 | 8.1 |
| G22314-2424 | 24GSP-24FL90S | 7347-47725 | 1 1/2 | 38.1 | 2.38 | 60.5 | 3.19 | 81.0 | 7.24 | 183.9 | 4.33 | 110.0 | .32 | 8.1 |
| G22315-2424 | 24GSP-24FL90M | 7347-74725 | 1 1/2 | 38.1 | 2.38 | 60.5 | 4.09 | 103.9 | 6.89 | 175.0 | 4.01 | 101.9 | .32 | 8.1 |
| G22316-2424 | 24GSP-24FL90-148 | 7347-85625 | 1 1/2 | 38.1 | 2.38 | 60.5 | 5.83 | 148.1 | 6.89 | 175.0 | 4.01 | 101.9 | .32 | 8.1 |
| G22314-2432 | 24GSP-32FL90S | 7347-47735 | 1 1/2 | 38.1 | 2.81 | 71.4 | 4.72 | 119.9 | 6.90 | 175.3 | 4.01 | 101.9 | .38 | 9.7 |
| G22315-2432 | 24GSP-32FL90-080 | 7347-47745 | 1 1/2 | 38.1 | 2.81 | 71.4 | 3.15 | 80.0 | 6.99 | 177.6 | 4.01 | 101.9 | .38 | 9.7 |
| G22316-2432 | 24GSP-32FL90-170 | 7347-85435 | 1 1/2 | 38.1 | 2.81 | 71.4 | 6.69 | 169.9 | 6.88 | 174.8 | 3.99 | 101.4 | .38 | 9.7 |
| G22314-3224 | 32GSP-24FL90S | 7347-47785 | 2 | 50.8 | 2.38 | 60.5 | 3.19 | 81.0 | 7.76 | 197.1 | 4.13 | 104.9 | .32 | 8.1 |
| G22314-3232 | 32GSP-32FL90-114 | 7347-47805 | 2 | 50.8 | 2.81 | 71.4 | 4.49 | 114.1 | 8.74 | 222.0 | 5.12 | 130.1 | .38 | 9.7 |
| G22315-3232 | 32GSP-32FL90-165 | 7347-85425 | 2 | 50.8 | 2.81 | 71.4 | 6.50 | 165.1 | 9.69 | 246.1 | 6.06 | 153.9 | .38 | 9.7 |
| G22316-3232 | 32GSP-32FL90-200 | 7347-85455 | 2 | 50.8 | 2.81 | 71.4 | 7.97 | 202.4 | 8.74 | 222.0 | 5.13 | 130.3 | .38 | 9.7 |
| G22315-3240 | 32GSP-40FL90-110 | 7347-74805 | 2 | 50.8 | 3.31 | 84.1 | 4.38 | 111.3 | 8.52 | 216.4 | 4.98 | 126.5 | .38 | 9.7 |

# Code 61 O-Ring Flange - 110° Bent Tube


–24FL Max. W.P. 3,000 psi; –32FL Max. W.P. 3,000 psi.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22325-2424 | 24GSP-24FL110-094 | 7347-85635 | 1 1/2 | 38.1 | 2.38 | 60.5 | 3.70 | 94.0 | 7.95 | 201.9 | 5.07 | 128.8 | .32 | 8.1 |
| G22325-3232 | 32GSP-32FL110-140 | 7347-85465 | 2 | 50.8 | 2.81 | 71.4 | 5.51 | 140.0 | 9.80 | 248.9 | 6.40 | 162.6 | .38 | 9.7 |

# Code 61 O-Ring Flange - 120° Bent Tube


–24FL Max. W.P. 3,000 psi; –32FL Max. W.P. 3,000 psi.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22327-2424 | 24GSP-24FL120-119 | 7347-85645 | 1 1/2 | 38.1 | 2.38 | 60.5 | 4.69 | 119.1 | 7.20 | 182.9 | 4.31 | 109.5 | .32 | 8.1 |

# Code 61 O-Ring Flange - 125° Bent Tube

–24FL Max. W.P. 3,000 psi; –32FL Max. W.P. 3,000 psi.
See Accessories for O–Rings.





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22329-3232 | 32GSP-32FL125-150 | 7347-85475 | 2 | 50.8 | 2.81 | 71.4 | 3.90 | 99.1 | 8.30 | 210.8 | 4.70 | 119.4 | .38 | 9.7 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Code 62 O-Ring Flange Heavy


See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22350-2424 | 24GSP-24FLH | 7347-48725 | 1 1/2 | 38.1 | 2.50 | 63.5 | 6.57 | 166.9 | 3.68 | 93.5 | .50 | 12.7 |
| G22350-2432 | 24GSP-32FLH | 7347-48735 | 1 1/2 | 38.1 | 3.13 | 79.5 | 6.57 | 166.9 | 3.68 | 93.5 | .50 | 12.7 |
| G22350-3232 | 32GSP-32FLH | 7347-48795 | 2 | 50.8 | 3.13 | 79.5 | 7.09 | 180.1 | 3.46 | 87.9 | .50 | 12.7 |

# Code 62 O-Ring Flange Heavy - 45° Bent Tube


S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22357-2424 | 24GSP-24FLH45M | 7347-51725 | 1 1/2 | 38.1 | 2.50 | 63.5 | 1.73 | 43.9 | 7.56 | 192.0 | 4.65 | 118.1 | .50 | 12.7 |
| G22357-2432 | 24GSP-32FLH45S | 7347-51735 | 1 1/2 | 38.1 | 3.13 | 79.5 | 2.05 | 52.1 | 7.87 | 199.9 | 4.98 | 126.5 | .50 | 12.7 |
| G22357-3232 | 32GSP-32FLH45-066 | 7347-51805 | 2 | 50.8 | 3.13 | 79.5 | 2.60 | 66.0 | 10.67 | 271.0 | 7.06 | 179.3 | .50 | 12.7 |


# Code 62 O-Ring Flange Heavy - 90° Bent Tube

S, M and L Drops per ISO Final Draft International Standard 12151–3.
See Accessories for O–Rings.





| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22365-2424 | 24GSP-24FLH90-094 | 7347-79105 | 1 1/2 | 38.1 | 2.50 | 63.5 | 3.70 | 94.0 | 6.91 | 175.5 | 4.01 | 101.9 | .50 | 12.7 |
| G22364-2432 | 24GSP-32FLH90S | 7347-54735 | 1 1/2 | 38.1 | 3.13 | 79.5 | 4.72 | 119.9 | 6.96 | 176.8 | 4.06 | 103.1 | .50 | 12.7 |
| G22365-3232 | 32GSP-32FLH90M | 7347-75795 | 2 | 50.8 | 3.13 | 79.5 | 5.40 | 137.2 | 8.72 | 221.5 | 5.09 | 129.3 | .50 | 12.7 |

# Code 61 Flange without O-Ring Groove




| Part No. | Descr. | Prod. No. | ⊖ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22370-2424 | 24GSP-24FLFF | 7347-85655 | 1 1/2 | 38.1 | 2.38 | 60.5 | 6.02 | 152.9 | 3.12 | 79.3 | .32 | 8.1 |

# Hose Length Extender





| Part No. | Descr. | Prod. No. | ⊖ | | L | | C | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G22535-2424 | 24GSP-24HLE | 7347-85445 | 1 1/2 | 38.1 | 7.33 | 186.2 | 1.53 | 38.9 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Hose Length Extender - Continued


| Part No. | Descr. | Prod. No. | ⊖ | | L | | C | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G22535-3232 | 32GSP-32HLE | 7347-79335 | 2 | 50.8 | 8.76 | 222.5 | 1.52 | 38.6 |


## Hose Length Extender - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | L | | C | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G22537-2424 | 24GSP-24HLE90-182 | 7347-85525 | 1 1/2 | 38.1 | 7.17 | 182.0 | 4.27 | 108.4 |


## Male DIN 24° Cone - Light Series





| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H1 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | mm |
| G22615-2442 | 24GSP-42MDL | 7347-95015 | 1 1/2 | 38.1 | M52X2.0 | 55 | 4.72 | 119.9 | 1.83 | 46.5 | 42.0 |


## Female DIN 24° Cone Swivel - Light Series with O-Ring





| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | mm |
| G22645-2442 | 24GSP-42FDLORX | 7347-94955 | 1 1/2 | 38.1 | M52X2.0 | 60 | 5.34 | 133.5 | 2.44 | 62.0 | 42.0 |
| G22645-3242 | 32GSP-42FDLORX | 7347-95005 | 2 | 50.8 | M52X2.0 | 60 | 5.71 | 145.0 | 2.09 | 53.1 | 42.0 |


## Female DIN 24° Cone Swivel - Light Series with O-Ring - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | mm |
| G22650-2442 | 24GSP-42FDLORX45 | 7347-95095 | 1 1/2 | 38.1 | M52X2.0 | 60 | 1.73 | 43.9 | 8.22 | 208.8 | 5.32 | 135.1 | 42.0 |

## Female DIN 24° Cone Swivel - Light Series with O-Ring - 90° Bent Tube









| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | mm |
| G22655-2442 | 24GSP-42FDLORX90 | 7347-94965 | 1 1/2 | 38.1 | M52X2.0 | 60 | 3.62 | 92.0 | 7.66 | 194.6 | 4.76 | 120.9 | 42.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Female DIN 24° Cone Swivel - Heavy Series with O-Ring





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm | mm |
| G22720-2438 | 24GSP-38FDHORX | 7347-95065 | 1 1/2 | 38.1 | M52X2.0 | 60 | 5.91 | 150.1 | 3.00 | 76.2 | 38.0 |


## Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 90° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm | " | mm | mm |
| G22730-2438 | 24GSP-38FDHORX90 | 7347-95085 | 1 1/2 | 38.1 | M52X2.0 | 60 | 3.62 | 91.9 | 7.66 | 194.6 | 4.76 | 120.9 | 38.0 |


## Male British Standard Pipe Tapered




| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G22795-2424 | 24GSP-24MBSPT | 7347-95235 | 1 1/2 | 38.1 | 1 1/2–11 | 55 | 5.12 | 130.1 | 2.22 | 56.4 | |

# Female British Standard Parallel Pipe O-Ring Swivel









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | | | " | mm | " | mm |
| G22830-2424 | 24GSP-24FBSPORX | 7347-95025 | 1 1/2 | 38.1 | 1 1/2–11 | 55 | 4.92 | 125.0 | 2.01 | 51.1 | | |
| G22830-3232 | 32GSP-32FBSPORX | 7347-95105 | 2 | 50.8 | 2–11 | 70 | 5.98 | 151.9 | 2.36 | 59.9 | | |

# Female British Standard Parallel Pipe O-Ring Swivel - 45° Bent Tube

S, M and L Drops and Hex per ISO Working Draft 12151–6.





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | | " | mm | " | mm | " | mm |
| G22831-2424 | 24GSP-24FBSPORX45 | 7347-95035 | 1 1/2 | 38.1 | 1 1/2–11 | 55 | 1.96 | 49.8 | 8.44 | 214.4 | 5.54 | 140.7 | |
| G22831-3232 | 32GSP-32FBSPORX45 | 7347-95115 | 2 | 50.8 | 2–11 | 70 | 2.45 | 62.2 | 10.87 | 276.1 | 7.24 | 183.9 | |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female British Standard Parallel Pipe O-Ring Swivel - 90° Bent Tube

S, M and L Drops and Hex per ISO Working Draft 12151–6.









| Part No. | Descr. | Prod. No. | ⊖ | | ⦀ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G22832-2424 | 24GSP-24FBSPORX90 | 7347-95045 | 1 1/2 | 38.1 | 1 1/2–11 | 55 | 3.93 | 99.8 | 7.66 | 194.6 | 4.75 | 120.7 |
| G22832-3232 | 32GSP-32FBSPORX90 | 7347-95125 | 2 | 50.8 | 2–11 | 70 | 5.08 | 129.0 | 10.02 | 254.5 | 6.40 | 162.6 |

# Female Komatsu Style Japanese Metric Swivel


These female swivels have been marked with two small notches on the hex to identify them as the Komatsu style.




| Part No. | Descr. | Prod. No. | ⊖ | | ⦀ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G22910-2424 | 24GSP-24FKX | 7347-35725 | 1 1/2 | 38.1 | M42X1.5 | 49 | 59 | 5.81 | 147.6 | 2.92 | 74.2 |


# Female Japanese Industrial Standard 30° Flare Swivel





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | mm | mm | " | mm | " | mm |
| G22930-2424 | 24GSP-24FJISX | 7347-79345 | 1 1/2 | 38.1 | 1 1/2–11 | | 54 | 54 | 5.61 | 142.5 | 2.72 | 69.1 |

# GSP Ferrule for Wire Braid Hose




| Part No. | Descr. | Prod. No. | ⟷ | | L | | ↕ | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G22995-0224 | 24GSP1F-2 | 7347-03165 | 1 1/2 | 38.1 | 2.98 | 75.7 | 2.76 | 70.1 |
| G22995-0232 | 32GSP1F-2 | 7347-03185 | 2 | 50.8 | 3.54 | 89.9 | 3.29 | 83.6 |

# GSP Ferrule for 4-Spiral Hose






| Part No. | Descr. | Prod. No. | ⟷ | | L | | ↕ | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G22995-0424 | 24GSP1F-4 | 7347-03175 | 1 1/2 | 38.1 | 3.01 | 76.5 | 2.83 | 71.9 |
| G22995-0432 | 32GSP1F-4 | 7347-03195 | 2 | 50.8 | 3.58 | 90.9 | 3.35 | 85.1 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male Pipe (NPTF - 30° Cone Seat)





| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G24100-2424 | 24GSM-24MP | 7341-02585 | 1 1/2 | 38.1 | 1 1/2–11 1/2 | 2 | 6.51 | 165.4 | 2.77 | 70.4 |
| G23100-3232 | 32GSM-32MP | 7341-20405 | 2 | 50.8 | 2–11 1/2 | 2.75 | 7.54 | 191.6 | 3.05 | 77.6 |


## API Line Pipe Connection




| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G24102-2424 | 24GSM-24API-LP | 7341-02735 | 1 1/2 | 38.1 | 1 1/2–11 | 2 | 5.76 | 146.3 | 2.23 | 56.6 |
| G23102-3232 | 32GSM-32API-LP | 7341-20305 | 2 | 50.8 | 2 | 2.75 | 9.39 | 238.4 | 4.90 | 124.4 |
| G24102-4040 | 40GSM-40API-LP | 7341-20675 | 2 1/2 | 63.5 | 2 1/2 | — | 12.40 | 316.0 | 5.47 | 138.9 |
| G24102-4848 | 48GSM-48API-LP | 7341-20715 | 3 | 76.2 | 3 | — | 14.10 | 359.0 | 6.38 | 162.0 |


## Male JIC 37° Flare





| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G24165-2424 | 24GSM-24MJ | 7341-02555 | 1 1/2 | 38.1 | 1 7/8–12 | 1.97 | 6.39 | 162.3 | 2.65 | 67.3 |
| G23165-3232 | 32GSM-32MJ | 7341-20465 | 2 | 50.8 | 2 1/2–12 | 2.56 | 7.72 | 196.1 | 3.23 | 82.1 |


## Female JIC 37° Flare Swivel





| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G24170-2424 | 24GSM-24FJX | 7341-02525 | 1 1/2 | 38.1 | 1 7/8–12 | 2.17 | 2.36 | 6.78 | 172.2 | 3.04 | 77.2 |
| G23170-3232 | 32GSM-32FJX | 7341-20455 | 2 | 50.8 | 2 1/2–12 | 2.76 | 2.95 | 8.07 | 205.1 | 3.59 | 91.1 |

## Female JIC 37° Flare Swivel - 45° Bent Tube




| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | | " | mm | " | mm | " | mm |
| G24174-2424 | 24GSM-24FJX45-034 | 7341-02535 | 1 1/2 | 38.1 | 1 7/8–12 | 60 | 1.34 | 34.0 | 8.90 | 226.1 | 5.15 | 130.8 |

## Female JIC 37° Flare Swivel - 90° Bent Tube






| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24180-2424 | 24GSM-24FJX90M | 7341-02545 | 1 1/2 | 38.1 | 1 7/8–12 | 60 | 3.39 | 86.1 | 8.96 | 227.6 | 7.18 | 182.4 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Female Flat-Face Swivel





| Part No. | Descr. | Prod. No. | ⊖ | | ≀≀≀ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G24230-2424 | 24GSM4K-24FFORX | 7341-02445 | 1 1/2 | 38.1 | 2–12 | 2.17 | 2.36 | 6.47 | 164.3 | 2.73 | 69.3 |
| G23230-3232 | 32GSM-32FFORX | 7341-20485 | 2 | 50.8 | 2 1/2–12 | 2.76 | 2.95 | 7.60 | 193.0 | 3.07 | 79.0 |

## Female Flat-Face Swivel - 45° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | ≀≀≀ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24234-2424 | 24GSM4K-24FFORX45-038 | 7341-02455 | 1 1/2 | 38.1 | 2–12 | 60 | 1.50 | 38.1 | 9.31 | 236.6 | 5.56 | 141.1 |


## Female Flat-Face Swivel - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | ≀≀≀ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G24240-2424 | 24GSM4K-24FFORX90M | 7341-02475 | 1 1/2 | 38.1 | 2–12 | 2.50 | 3.41 | 86.6 | 8.48 | 215.4 | 3.69 | 93.7 |


# Code 61 O-Ring Flange

–24FL and –32FL Max. W.P. 3,000 psi; –40FL Max. W.P. 2,500 psi.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24300-2424 | 24GSM-24FL | 7341-01905 | 1 1/2 | 38.1 | 2.38 | 60.5 | 7.09 | 180.1 | 3.35 | 85.1 | .32 | 8.1 |
| G24300-2432 | 24GSM-32FL | 7341-01915 | 1 1/2 | 38.1 | 2.81 | 71.4 | 7.40 | 188.0 | 3.66 | 93.0 | .38 | 9.7 |
| G23300-3232 | 32GSM-32FL | 7341-20255 | 2 | 50.8 | 2.81 | 71.4 | 9.90 | 251.4 | 5.41 | 137.4 | .38 | 9.7 |
| G24300-4040 | 40GSM-40FL | 7341-20905 | 2 1/2 | 63.5 | 3.31 | 84.1 | 11.81 | 300.0 | 4.80 | 122.9 | .38 | 9.7 |

# Code 61 O-Ring Flange - 30° Bent Tube





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24304-2424 | 24GSM-24FL30M | 7341-01925 | 1 1/2 | 38.1 | 2.38 | 60.5 | 1.77 | 45.0 | 8.52 | 216.4 | 5.00 | 127.0 | .32 | 8.1 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Code 61 O-Ring Flange - 45° Bent Tube


Maximum working pressure 3,000 psi.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24307-2424 | 24GSM-24FL45M | 7341-01945 | 1 1/2 | 38.1 | 2.38 | 60.5 | 1.73 | 43.9 | 9.05 | 229.9 | 5.31 | 134.9 | .32 | 8.1 |
| G24306-2432 | 24GSM-32FL45S | 7341-01955 | 1 1/2 | 38.1 | 2.81 | 71.4 | 2.05 | 52.1 | 9.13 | 231.9 | 5.34 | 136.6 | .38 | 9.7 |
| G23307-3232 | 32GSM-32FL45M | 7341-20265 | 2 | 50.8 | 2.81 | 71.4 | 2.20 | 56.0 | 11.30 | 288.0 | 6.83 | 173.6 | .38 | 9.7 |

# Code 61 O-Ring Flange - 60° Bent Tube


Maximum working pressure 3,000 psi.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24309-2424 | 24GSM-24FL60M | 7341-01965 | 1 1/2 | 38.1 | 2.38 | 60.5 | 2.52 | 64.0 | 9.50 | 241.3 | 5.75 | 146.1 | .32 | 8.1 |


# Code 61 O-Ring Flange - 90° Bent Tube

Maximum working pressure 3,000 psi.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24314-2424 | 24GSM-24FL90S | 7341-01985 | 1 1/2 | 38.1 | 2.38 | 60.5 | 3.19 | 81.0 | 8.46 | 214.9 | 4.72 | 119.9 | .32 | 8.1 |
| G23314-3232 | 32GSM-32FL90-130 | 7341-20275 | 2 | 50.8 | 2.81 | 71.4 | 5.12 | 130.0 | 10.43 | 265.0 | 5.93 | 150.5 | .38 | 9.7 |


# Code 62 O-Ring Flange Heavy




| Part No. | Descr. | Prod. No. | ⟷ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24350-2420 | 24GSM-20FLH | 7341-02245 | 1 1/2 | 38.1 | 2.13 | 54.1 | 7.87 | 199.9 | 4.13 | 104.9 | .41 | 10.4 |
| G24350-2424 | 24GSM-24FLH | 7341-02255 | 1 1/2 | 38.1 | 2.50 | 63.5 | 7.87 | 199.9 | 4.13 | 104.9 | .50 | 12.7 |
| G24350-2432 | 24GSM-32FLH | 7341-02265 | 1 1/2 | 38.1 | 3.13 | 79.5 | 7.87 | 199.9 | 4.13 | 104.9 | .50 | 12.7 |
| G23350-3224 | 32GSM-24FLH | 7341-20095 | 2 | 50.8 | 2.50 | 63.5 | 9.06 | 230.0 | 4.57 | 116.0 | .50 | 12.7 |
| G23350-3232 | 32GSM-32FLH | 7341-20005 | 2 | 50.8 | 3.13 | 79.5 | 9.90 | 251.4 | 5.41 | 137.4 | .50 | 12.7 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Code 62 O-Ring Flange Heavy - 22° Bent Tube





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24352-2424 | 24GSM-24FLH22M | 7341-02275 | 1 1/2 | 38.1 | 2.50 | 63.5 | .70 | 17.9 | 9.56 | 242.8 | 5.84 | 148.4 | .50 | 12.7 |
| G24353-2424 | 24GSM-24FLH20-024 | 7341-02395 | 1 1/2 | 38.1 | 2.50 | 63.5 | .94 | 23.9 | 9.56 | 242.8 | 5.81 | 147.6 | .50 | 12.7 |

## Code 62 O-Ring Flange Heavy - 30° Bent Tube




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24354-2424 | 24GSM-24FLH30M | 7341-02295 | 1 1/2 | 38.1 | 2.50 | 63.5 | 3.54 | 89.9 | 9.45 | 240.0 | 5.70 | 144.8 | .50 | 12.7 |
| G24355-2424 | 24GSM-24FLH30-28 | 7341-02305 | 1 1/2 | 38.1 | 2.50 | 63.5 | 1.10 | 27.9 | 8.86 | 225.0 | 5.12 | 130.0 | .50 | 12.7 |
| G23354-3232 | 32GSM-32FLH30-040 | 7341-20065 | 2 | 50.8 | 3.13 | 79.5 | 1.57 | 40.0 | 12.17 | 309.0 | 7.66 | 194.6 | .50 | 12.7 |

## Code 62 O-Ring Flange Heavy - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24357-2424 | 24GSM-24FLH45M | 7341-02315 | 1 1/2 | 38.1 | 2.50 | 63.5 | 1.73 | 43.9 | 9.13 | 231.9 | 5.39 | 136.9 | .50 | 12.7 |
| G24357-2432 | 24GSM-32FLH45M | 7341-02325 | 1 1/2 | 38.1 | 3.13 | 79.5 | 2.20 | 55.9 | 9.48 | 240.8 | 5.74 | 146.0 | .50 | 12.7 |

## Code 62 O-Ring Flange Heavy - 45° Bent Tube - Continued


| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G23357-3232 | 32GSM-32FLH45-063 | 7341-20055 | 2 | 50.8 | 3.13 | 79.5 | 2.48 | 63.0 | 11.69 | 297.0 | 6.00 | 152.5 | .50 | 12.7 |

## Code 62 O-Ring Flange Heavy - 60° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24359-2424 | 24GSM-24FLH60M | 7341-02335 | 1 1/2 | 38.1 | 2.50 | 63.5 | 2.50 | 63.5 | 9.25 | 235.0 | 6.23 | 158.2 | .50 | 12.7 |
| G23359-3232 | 32GSM-32FLH60M | 7341-20075 | 2 | 50.8 | 3.13 | 79.5 | 3.27 | 83.1 | 12.28 | 311.9 | 7.77 | 197.4 | .50 | 12.7 |

## Code 62 O-Ring Flange Heavy - 90° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24365-2424 | 24GSM-24FLH90-094 | 7341-02355 | 1 1/2 | 38.1 | 2.50 | 63.5 | 3.70 | 94.0 | 8.73 | 221.7 | 4.68 | 118.9 | .50 | 12.7 |
| G24366-2424 | 24GSM-24FLH90-150 | 7341-02375 | 1 1/2 | 38.1 | 2.50 | 63.5 | 5.90 | 149.9 | 8.42 | 213.9 | 4.68 | 118.9 | .50 | 12.7 |
| G24365-2432 | 24GSM-32FLH90S | 7341-02365 | 1 1/2 | 38.1 | 3.13 | 79.5 | 4.72 | 119.9 | 8.42 | 213.9 | 4.68 | 118.9 | .50 | 12.7 |
| G23364-3232 | 32GSM-32FLH90S | 7341-20085 | 2 | 50.8 | 3.13 | 79.5 | 4.72 | 120.0 | 10.41 | 264.0 | 5.91 | 150.0 | .50 | 12.7 |
| G23365-3232 | 32GSM-32FLH90M | 7341-20045 | 2 | 50.8 | 3.13 | 79.5 | 5.43 | 138.0 | 10.41 | 264.0 | 5.91 | 150.0 | .50 | 12.7 |
| G23366-3232 | 32GSM-32FLH90-159 | 7341-20035 | 2 | 50.8 | 3.13 | 79.5 | 6.26 | 159.0 | 10.41 | 264.0 | 5.92 | 150.4 | .50 | 12.7 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Code 62 O-Ring Flange Heavy with Captive Flange





| Part No. | Descr. | Prod. No. | ⟷ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24374-2424 | 24GSM-24FLHCFM | 7341-02805 | 1 1/2 | 38.1 | 2.50 | 63.5 | 7.87 | 200.0 | 4.13 | 105.0 | .50 | 2.5 |
| G23374-3232 | 32GSM-32FLHCFM | 7341-20135 | 2 | 50.8 | 3.13 | 79.5 | 9.90 | 251.4 | 5.41 | 137.4 | .50 | 3.1 |

## Code 62 O-Ring Flange Heavy with Captive Flange - 45° Bent Tube




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24376-2424 | 24GSM-24FLHCFM45M | 7341-02815 | 1 1/2 | 38.1 | 2.50 | 63.5 | 1.73 | 44.0 | 9.13 | 232.0 | 5.39 | 137.0 | .50 | 2.5 |
| G23376-3232 | 32GSM-32FLHCFM45-063 | 7341-20145 | 2 | 50.8 | 3.13 | 79.5 | 2.48 | 63.0 | 11.69 | 297.0 | 7.18 | 182.5 | .50 | 3.1 |

## Code 62 O-Ring Flange Heavy with Captive Flange - 90° Bent Tube





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24380-2424 | 24GSM-24FLHCFM90-094 | 7341-02825 | 1 1/2 | 38.1 | 2.50 | 63.5 | 3.70 | 94.0 | 8.43 | 214.0 | 4.69 | 119.0 | .50 | 2.5 |

## Code 62 O-Ring Flange Heavy with Captive Flange - 90° Bent Tube - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G23380-3232 | 32GSM-32FLHCFM90-120 | 7341-20155 | 2 | 50.8 | 3.13 | 79.5 | 4.72 | 120.0 | 10.39 | 264.0 | 5.91 | 150.0 | .50 | 3.1 |


## Code 62 O-Ring Flange Heavy Captive Flange Metric Bolts




| Part No. | Descr. | Prod. No. | ⊖ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24386-4040 | 40GSM-40FLHCFM | 7341-20655 | 2 1/2 | 63.5 | 5.91 | 150.0 | 15.00 | 380.0 | 7.95 | 202.0 | 1.89 | 48.0 |
| G24386-4848 | 48GSM-48FLHCFM | 7341-20695 | 3 | 76.2 | 8.27 | 210.0 | 17.30 | 440.0 | 9.57 | 243.0 | 2.28 | 58.0 |

## Caterpillar Style O-Ring Flange

NOTE: These FLC flanges are designed with a thicker flange head. The .56" flange dimension is frequently found on Caterpillar equipment. These flanges let the user utilize the existing Caterpillar flange halves or new Gates Caterpillar flange halves. At the user's option, standard Code 62 flanges and halves can be used in place of Caterpillar flanges and halves. The standard Code 62 flange head thickness ranges between .305" and .495". Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings).





| Part No. | Descr. | Prod. No. | ⊖ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24400-2424 | 24GSM-24FLC | 7341-02055 | 1 1/2 | 38.1 | 2.50 | 63.5 | 7.44 | 189.0 | 3.71 | 94.2 | .56 | 14.2 |
| G24401-2424 | 24GSM-24FLCL | 7341-02175 | 1 1/2 | 38.1 | 2.50 | 63.5 | 9.37 | 238.0 | 5.64 | 143.3 | .56 | 14.2 |
| G24400-2432 | 24GSM-32FLC | 7341-02065 | 1 1/2 | 38.1 | 3.13 | 79.5 | 7.87 | 199.9 | 4.13 | 104.9 | .56 | 14.2 |
| G23400-3232 | 32GSM-32FLC | 7341-20205 | 2 | 50.8 | 3.13 | 79.5 | 8.97 | 227.7 | 4.48 | 113.8 | .56 | 14.2 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Caterpillar Style O-Ring Flange - 22° Bent Tube


NOTE: These FLC flanges are designed with a thicker flange head. The .56" flange dimension is frequently found on Caterpillar equipment. These flanges let the user utilize the existing Caterpillar flange halves or new Gates Caterpillar flange halves. At the user's option, standard Code 62 flanges and halves can be used in place of Caterpillar flanges and halves. The standard Code 62 flange head thickness ranges between .305" and .495". Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings).




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24402-2424 | 24GSM-24FLC22-017 | 7341-02075 | 1 1/2 | 38.1 | 2.50 | 63.5 | .66 | 16.8 | 9.29 | 236.0 | 5.57 | 141.5 | .56 | 14.2 |
| G24402-2432 | 24GSM-32FLC22-022 | 7341-02085 | 1 1/2 | 38.1 | 3.13 | 79.5 | .87 | 22.1 | 7.87 | 261.0 | 4.13 | 104.9 | .56 | 14.2 |

# Caterpillar Style O-Ring Flange - 30° Bent Tube


NOTE: These FLC flanges are designed with a thicker flange head. The .56" flange dimension is frequently found on Caterpillar equipment. These flanges let the user utilize the existing Caterpillar flange halves or new Gates Caterpillar flange halves. At the user's option, standard Code 62 flanges and halves can be used in place of Caterpillar flanges and halves. The standard Code 62 flange head thickness ranges between .305" and .495". Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings).




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24404-2424 | 24GSM-24FLC30-023 | 7341-02095 | 1 1/2 | 38.1 | 2.50 | 63.5 | .90 | 22.9 | 9.25 | 235.0 | 5.49 | 139.5 | .56 | 14.2 |
| G24404-2432 | 24GSM-32FLC30-035 | 7341-02105 | 1 1/2 | 38.1 | 3.13 | 79.5 | 1.37 | 34.8 | 10.11 | 257.0 | 6.36 | 161.6 | .56 | 14.2 |
| G23404-3232 | 32GSM-32FLC30-035 | 7341-20245 | 2 | 50.8 | 3.13 | 79.5 | 1.38 | 35.0 | 11.85 | 301.2 | 7.37 | 187.2 | .56 | 14.2 |

# Caterpillar Style O-Ring Flange - 45° Bent Tube


NOTE: These FLC flanges are designed with a thicker flange head. The .56" flange dimension is frequently found on Caterpillar equipment. These flanges let the user utilize the existing Caterpillar flange halves or new Gates Caterpillar flange halves. At the user's option, standard Code 62 flanges and halves can be used in place of Caterpillar flanges and halves. The standard Code 62 flange head thickness ranges between .305" and .495". Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings).




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24407-2424 | 24GSM-24FLC45-039 | 7341-02115 | 1 1/2 | 38.1 | 2.50 | 63.5 | 1.54 | 39.1 | 8.94 | 227.1 | 5.20 | 132.1 | .56 | 14.2 |
| G24407-2432 | 24GSM-32FLC45-059 | 7341-02125 | 1 1/2 | 38.1 | 3.13 | 79.5 | 2.32 | 58.9 | 9.60 | 244.0 | 5.86 | 149.0 | .56 | 14.2 |
| G23407-3232 | 32GSM-32FLC45-064 | 7341-20215 | 2 | 50.8 | 3.13 | 79.5 | 2.52 | 64.0 | 11.32 | 287.5 | 6.83 | 173.5 | .56 | 14.2 |

# Caterpillar Style O-Ring Flange - 60° Bent Tube

NOTE: These FLC flanges are designed with a thicker flange head. The .56" flange dimension is frequently found on Caterpillar equipment. These flanges let the user utilize the existing Caterpillar flange halves or new Gates Caterpillar flange halves. At the user's option, standard Code 62 flanges and halves can be used in place of Caterpillar flanges and halves. The standard Code 62 flange head thickness ranges between .305" and .495". Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings).





| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24409-2424 | 24GSM-24FLC60-055 | 7341-02135 | 1 1/2 | 38.1 | 2.50 | 63.5 | 2.17 | 55.1 | 9.91 | 251.7 | 6.17 | 156.7 | .56 | 14.2 |
| G24409-2432 | 24GSM-32FLC60-087 | 7341-02145 | 1 1/2 | 38.1 | 3.13 | 79.5 | 3.42 | 86.9 | 11.69 | 297.0 | 7.94 | 201.9 | .56 | 14.2 |
| G23409-3232 | 32GSM-32FLC60-083 | 7341-20225 | 2 | 50.8 | 3.13 | 79.5 | 3.27 | 83.1 | 12.69 | 322.3 | 8.17 | 207.5 | .56 | 14.2 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Caterpillar Style O-Ring Flange - 90° Bent Tube

NOTE: These FLC flanges are designed with a thicker flange head. The .56" flange dimension is frequently found on Caterpillar equipment. These flanges let the user utilize the existing Caterpillar flange halves or new Gates Caterpillar flange halves. At the user's option, standard Code 62 flanges and halves can be used in place of Caterpillar flanges and halves. The standard Code 62 flange head thickness ranges between .305" and .495". Compatible with Code 62 O–Ring. See Accessories for recommended O–Rings. (Do Not use "D" shaped O–Rings).





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24415-2424 | 24GSM-24FLC90-087 | 7341-02155 | 1 1/2 | 38.1 | 2.50 | 63.5 | 3.43 | 87.1 | 8.43 | 214.1 | 4.70 | 119.4 | .56 | 14.2 |
| G24415-2432 | 24GSM-32FLC90-140 | 7341-02165 | 1 1/2 | 38.1 | 3.13 | 79.5 | 5.51 | 140.0 | 8.85 | 225.0 | 5.11 | 129.9 | .56 | 14.2 |
| G23415-3232 | 32GSM-32FLC90-130 | 7341-20235 | 2 | 50.8 | 3.13 | 79.5 | 5.12 | 130.0 | 10.41 | 264.5 | 5.93 | 150.5 | .56 | 14.2 |

# Hose Length Extender





| Part No. | Descr. | Prod. No. | ⟷ | | L | | C | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G23534-3232 | 32GSM-32HLE | 7341-20475 | 2 | 50.8 | 11.11 | 282.0 | 2.14 | 54.4 |
| G24534-4040 | 40GSM-40HLE | 7341-20735 | 2 1/2 | 63.5 | 16.70 | 424.0 | 2.68 | 68.0 |
| G24535-4848 | 48GSM-48HLE | 7341-20745 | 3 | 76.2 | 18.40 | 468.0 | 2.91 | 73.9 |

## Hose Length Extender for Caterpillar with Clamping Area





| Part No. | Descr. | Prod. No. | ⊖ | | L | | C | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G24534-2424 | 24GSM-24HLEC | 7341-02645 | 1 1/2 | 38.1 | 10.66 | 270.8 | 3.18 | 80.8 |

## Female DIN 24° Cone Swivel - Heavy Series with O-Ring




| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | mm |
| G24720-2438 | 24GSM-38FDHORX | 7341-07055 | 1 1/2 | 38.1 | M52X2.0 | 60 | 7.09 | 180.1 | 3.35 | 85.1 | 38.0 |

## Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | mm |
| G24725-2438 | 24GSM-38FDHORX45 | 7341-07065 | 1 1/2 | 38.1 | M52X2.0 | 60 | 1.74 | 44.2 | 9.33 | 237.0 | 5.59 | 142.0 | 38.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 90° Bent Tube





| Part No. | Descr. | Prod. No. | ⟷ | | | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | mm |
| G24730-2438 | 24GSM-38FDHORX90 | 7341-07075 | 1 1/2 | 38.1 | M52X2.0 | 60 | 3.62 | 92.0 | 8.76 | 222.5 | 5.02 | 127.5 | 38.0 |

## Male British Standard Pipe Parallel





| Part No. | Descr. | Prod. No. | ⟷ | | | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G24810-2424 | 24GSM-24MBSPP | 7341-07025 | 1 1/2 | 38.1 | 1 1/2–11 | 55 | 6.41 | 162.8 | 2.67 | 67.8 |
| G23810-3232 | 32GSM-32MBSPP | 7341-20585 | 2 | 50.8 | 2–11 | 70 | 7.40 | 188.0 | 2.91 | 74.0 |

## Female British Standard Parallel Pipe O-Ring Swivel





| Part No. | Descr. | Prod. No. | ⟷ | | | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G24830-2424 | 24GSM-24FBSPORX | 7341-07015 | 1 1/2 | 38.1 | 1 1/2–11 | 55 | 6.06 | 153.9 | 2.32 | 58.9 |
| G23830-3232 | 32GSM-32FBSPORX | 7341-20555 | 2 | 50.8 | 2–11 | 70 | 7.24 | 183.9 | 2.76 | 70.0 |

# Female British Standard Parallel Pipe O-Ring Swivel - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24831-2424 | 24GSM-24FBSPORX45 | 7341-07035 | 1 1/2 | 38.1 | 1 1/2–11 | 55 | 1.96 | 49.8 | 9.56 | 242.8 | 5.81 | 147.6 |
| G23831-3232 | 32GSM-32FBSPORX45 | 7341-20565 | 2 | 50.8 | 2–11 | 70 | 2.95 | 75.0 | 12.11 | 307.6 | 7.62 | 193.6 |

# Female British Standard Parallel Pipe O-Ring Swivel - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24832-2424 | 24GSM-24FBSPORX90 | 7341-07045 | 1 1/2 | 38.1 | 1 1/2–11 | 55 | 3.94 | 100.1 | 8.76 | 222.5 | 5.02 | 127.5 |
| G23832-3232 | 32GSM-32FBSPORX90 | 7341-20575 | 2 | 50.8 | 2–11 | 70 | 5.91 | 150.1 | 10.89 | 276.5 | 6.40 | 162.5 |


# ISO 6164 4-bolt Square Heavy Captive Flange




| Part No. | Descr. | Prod. No. | ⊖ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G24857-4063 | 40GSM-63FLSHCF | 7341-20665 | 2 1/2 | 63.5 | 5.91 | 150.0 | 15.00 | 380.0 | 7.95 | 202.0 | 2.05 | 52.0 |
| G24857-4880 | 48GSM-80FLSHCF | 7341-20705 | 3 | 76.2 | 7.09 | 180.0 | 17.30 | 440.0 | 9.57 | 243.0 | 2.76 | 70.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# GSM Butt Weld




| Part No. | Descr. | Prod. No. | ⊖ | | M | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G24860-4040 | 40GSM-40XXSBW | 7341-20685 | 2 1/2 | 63.5 | 1.77 | 45.0 | 9.65 | 245.1 | 2.64 | 67.1 |
| G24860-4848 | 48GSM-48XXSBW | 7341-20725 | 3 | 76.2 | 2.28 | 58.0 | 10.70 | 272.0 | 2.95 | 75.0 |

# HYDRAULIC HOSE FOR STAINLESS STEEL SPIRAL COUPLINGS




Also available with MegaTuff® cover




Also available with MegaTuff® cover




Also available with MegaTuff® and XtraTuff® cover




Also available with MegaTuff® and XtraTuff® cover




Also available with MegaTuff® and XtraTuff® cover




**The Gates eCrimp program** is a web based utility which allows users and distributors of Gates hydraulic and industrial hose products to find and print the most up to date crimp specifications with nothing more than an internet browser.

This program can be used to find crimp data for all Gates crimpers. Custom result may be printed by selecting the crimper, hose and coupling. Optionally results may also be limited by die set and working pressure.


The eCrimp web application can be directly accessed from a web browser by entering http://eCrimp.Gates.com for the website.


**The eCrimp mobile app** is available for download for the iPhone and iPad from the App Store.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male Pipe (NPTF - 30° Cone Seat)





| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm | " | mm |
| G18100-0606 | 6S-6MP-SS | 7362-00285 | 3/8 | 9.5 | 3/8–18 | .68 | 17.3 | 2.24 | 56.9 | 1.22 | 31.0 |
| G18100-0808 | 8S-8MP-SS | 7362-00305 | 1/2 | 12.7 | 1/2–14 | .87 | 22.2 | 1.22 | 31.0 | 1.43 | 36.3 |
| G18100-1212 | 12S-12MP-SS | 7362-00335 | 3/4 | 19.1 | 3/4–14 | 1.06 | 27 | 3.54 | 90.0 | 1.54 | 39.0 |
| G18100-1616 | 16S-16MP-SS | 7362-00365 | 1 | 25.4 | 1–11 1/2 | 1.37 | 34.8 | 4.17 | 106.0 | 1.94 | 49.2 |
| G18100-2020 | 20S-20MP-SS | 7362-00395 | 1 1/4 | 31.8 | 1 1/4–11 1/2 | 1.81 | 46 | 4.94 | 125.5 | 2.19 | 55.6 |

## API Line Pipe Connection




| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | L | | C | |
|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm |
| G18102-2424 | 24S-24MPAPI-SS | 7362-00455 | 1 1/2 | 38.1 | 1 1/2–11 1/2 | 6.26 | 159.0 | 2.74 | 69.5 |

## Female JIC 37° Flare Swivel





| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | | H2 | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm | " | mm | " | mm |
| G18170-0606 | 6S-6FJX-SS | 7362-01245 | 3/8 | 9.5 | 9/16–18 | .69 | 17.5 | .75 | 19.1 | 2.23 | 56.6 | 1.21 | 30.8 |

## Female JIC 37° Flare Swivel - Continued


| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | | H2 | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm | " | mm | " | mm |
| G18170-0808 | 8S-8FJSX-SS | 7362-01275 | 1/2 | 12.7 | 3/4–16 | .88 | 22.4 | .88 | 22.4 | 2.84 | 72.1 | 1.36 | 34.5 |
| G18170-1010 | 10S-10FJX-SS | 7362-01295 | 5/8 | 15.9 | 7/8–14 | .94 | 23.9 | 1.06 | 26.9 | 3.61 | 91.6 | 1.63 | 41.3 |
| G18170-1212 | 12S-12FJX-SS | 7362-01325 | 3/4 | 19.1 | 1 1/16–12 | 1.06 | 26.9 | 1.25 | 31.8 | 3.91 | 99.3 | 1.99 | 50.6 |
| G18170-1616 | 16S-16FJX-SS | 7362-01385 | 1 | 25.4 | 1 5/16–12 | 1.38 | 35.1 | 1.50 | 38.1 | 4.35 | 110.4 | 2.11 | 53.6 |
| G18170-2020 | 20S-20FJX-SS | 7362-01415 | 1 1/4 | 31.8 | 1 5/8–12 | 1.88 | 47.6 | 2 | 50.8 | 5.11 | 129.9 | 2.36 | 66.0 |
| G18170-2424 | 24S-24FJX-SS | 7362-01445 | 1 1/2 | 38.1 | 1 7/8–12 | 2 | 50.8 | 2.25 | 57.2 | 6.00 | 152.5 | 2.48 | 63.0 |
| G18170-3232 | 32S-32FJX-SS | 7362-01475 | 2 | 50.8 | 2 1/2–12 | 2.63 | 66.7 | 3 | 76.2 | 6.68 | 169.6 | 2.85 | 72.4 |

## Female Flat-Face O-Ring Swivel Metric Hex




| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | | H2 | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm | " | mm | " | mm |
| G18230-0606 | 6S-6FFORX-SS | 7362-03265 | 3/8 | 9.5 | 11/16–16 | .75 | 19 | .87 | 22 | 2.65 | 67.5 | 1.26 | 32.0 |
| G18230-0808 | 8S-8FFORX-SS | 7362-03275 | 1/2 | 12.7 | 13/16–16 | .91 | 23 | .94 | 24 | 2.91 | 74.0 | 1.43 | 36.4 |
| G18230-1010 | 10S-10FFORX-SS | 7362-03295 | 5/8 | 15.9 | 1–14 | 1.06 | 27 | 1.18 | 30 | 3.68 | 93.5 | 1.70 | 43.2 |
| G18230-1212 | 12S-12FFORX-SS | 7362-03315 | 3/4 | 19.1 | 1 3/16–12 | 1.18 | 30 | 1.41 | 36 | 3.70 | 94.0 | 1.69 | 43.0 |
| G18230-1616 | 16S-16FFORX-SS | 7362-03335 | 1 | 25.4 | 1 7/16–12 | 1.42 | 36 | 1.61 | 41 | 4.47 | 113.5 | 2.23 | 113.5 |
| G18230-2020 | 20S-20FFORX-SS | 7362-03355 | 1 1/4 | 31.8 | 1 11/16–12 | 1.81 | 46 | 1.96 | 50 | 5.27 | 134.0 | 2.53 | 64.2 |
| G18230-2424 | 24S-24FFORX-SS | 7362-03375 | 1 1/2 | 38.1 | 2–12 | 1.97 | 50 | 2.36 | 60 | 6.06 | 154.0 | 2.54 | 64.5 |


## Code 61 O-Ring Flange




| Part No. | Descr. | Prod. No. | ⊖ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G18300-1212 | 12S-12FL-SS | 7362-04375 | 3/4 | 19.1 | 1.50 | 38.1 | 4.33 | 110.0 | 2.32 | 59.0 | .27 | 6.9 |
| G18300-1616 | 16S-16FL-SS | 7362-04405 | 1 | 25.4 | 1.75 | 44.5 | 4.80 | 122.0 | 2.57 | 65.2 | .32 | 8.1 |
| G18300-2020 | 20S-20FL-SS | 7362-04435 | 1 1/4 | 31.8 | 2.00 | 50.8 | 5.43 | 138.0 | 2.69 | 68.2 | .32 | 8.1 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Code 62 O-Ring Flange Heavy





| Part No. | Descr. | Prod. No. | ⊖ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G18350-1212 | 12S-12FLH-SS | 7362-04105 | 3/4 | 19.1 | 1.63 | 41.4 | 4.48 | 113.8 | 2.48 | 63.0 | .35 | 8.9 |
| G18350-1616 | 16S-16FLH-SS | 7362-04135 | 1 | 25.4 | 1.88 | 47.8 | 4.92 | 125.0 | 2.68 | 68.1 | .38 | 9.7 |
| G18350-2020 | 20S-20FLH-SS | 7362-04155 | 1 1/4 | 31.8 | 2.13 | 54.1 | 5.75 | 146.1 | 3.00 | 76.2 | .41 | 10.4 |
| G18350-2424 | 24S-24FLH-SS | 7362-04165 | 1 1/2 | 38.1 | 2.50 | 63.5 | 7.14 | 181.6 | 3.62 | 92.1 | .41 | 10.4 |
| G18350-3232 | 32S-32FLH-SS | 7362-04195 | 2 | 50.8 | 3.13 | 79.5 | 7.24 | 183.9 | 3.42 | 86.9 | .50 | 12.7 |

## Female DIN 24° Cone Swivel - Heavy Series with O-Ring





| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | mm |
| G18720-1630 | 16S-30FDHORX-SS | 7362-92055 | 1 | 25.4 | M42X2.0 | 50 | 4.33 | 110.0 | 2.09 | 53.1 | 30.0 |

# Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⟷ | | ||| H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm | " | mm | mm |
| G18730-1630 | 16S-30FDHORX90-SS | 7362-93055 | 1 | 25.4 | M42X2.0 | 50 | 2.76 | 70.0 | 5.50 | 139.7 | 3.26 | 82.8 | 30.0 |

# Non-Skive Ferrules





| Part No. | Descr. | Prod. No. | ⟷ | | L | |
|---|---|---|---|---|---|---|
| | | | " | mm | " | mm |
| G18995-0210 | 10S1F-2SS | 7362-51755 | 5/8 | 15.9 | 1.40 | 35.6 |
| G18995-0212 | 12S1F-2SS | 7362-51585 | 3/4 | 19.1 | 1.73 | 44.0 |
| G18995-0216 | 16S1F-2SS | 7362-51595 | 1 | 25.4 | 2.06 | 52.2 |
| G18995-0406 | 6S1F-4SS | 7362-51445 | 3/8 | 9.5 | 1.10 | 28.0 |
| G18995-0408 | 8S1F-4SS | 7362-51345 | 1/2 | 12.7 | 1.50 | 38.1 |
| G18995-0410 | 10S1F-4SS | 7362-51485 | 5/8 | 15.9 | 1.88 | 47.8 |
| G18995-0412 | 12S1F-4SS | 7362-51495 | 3/4 | 19.1 | 2.00 | 50.8 |
| G18995-0416 | 16S1F-4SS | 7362-51525 | 1 | 25.4 | 2.22 | 56.4 |
| G18995-0420 | 20S1F-4SS | 7362-51535 | 1 1/4 | 31.8 | 2.67 | 67.8 |
| G18995-0620 | 20S1F-6SS | 7362-51625 | 1 1/4 | 31.8 | 2.87 | 72.9 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Skive Ferrules




| Part No. | Descr. | Prod. No. | ⟷ | | L | |
|---|---|---|---|---|---|---|
| | | | " | mm | " | mm |
| G18995-0624 | 24S2F-6SS | 7362-51655 | 1 1/2 | 38.1 | 3.53 | 89.7 |
| G18995-0632 | 32S2F-6SS | 7362-51685 | 2 | 50.8 | 3.68 | 93.5 |

# HYDRAULIC HOSE FOR MEGACRIMP® COUPLINGS













Also available with MegaTuff® cover




























EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# HYDRAULIC HOSE FOR MEGACRIMP® COUPLINGS - CONTINUED







Also available with MegaTuff® cover










Also available with MegaTuff® cover




Also available with MegaTuff® and XtraTuff® cover




Also available with MegaTuff® and XtraTuff® cover




Also available with MegaTuff® and XtraTuff® cover




Also available with MegaTuff® and XtraTuff® cover







Also available with MegaTuff® cover







Also available with MegaTuff® and XtraTuff® cover



# HYDRAULIC HOSE FOR MEGACRIMP® COUPLINGS - CONTINUED











































EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# HYDRAULIC HOSE FOR MEGACRIMP® COUPLINGS - CONTINUED





**The Gates eCrimp program** is a web based utility which allows users and distributors of Gates hydraulic and industrial hose products to find and print the most up to date crimp specifications with nothing more than an internet browser.


This program can be used to find crimp data for all Gates crimpers. Custom result may be printed by selecting the crimper, hose and coupling. Optionally results may also be limited by die set and working pressure.

The eCrimp web application can be directly accessed from a web browser by entering http://eCrimp.Gates.com for the website.

**The eCrimp mobile app** is available for download for the iPhone and iPad from the App Store.

# Male Pipe (NPTF - 30° Cone Seat)









| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G25100-0402 | 4G-2MP | 7100-10025 | 1/4 | 6.4 | 1/8–27 | 1/2 | 1.96 | 49.8 | .94 | 23.9 |
| G25100-0404 | 4G-4MP | 7100-10035 | 1/4 | 6.4 | 1/4–18 | 9/16 | 2.17 | 55.0 | 1.14 | 29.0 |
| G25100-0406 | 4G-6MP | 7100-10045 | 1/4 | 6.4 | 3/8–18 | 11/16 | 2.17 | 55.0 | 1.14 | 29.0 |
| G25100-0408 | 4G-8MP | 7100-10055 | 1/4 | 6.4 | 1/2–14 | 7/8 | 2.44 | 62.0 | 1.41 | 35.8 |
| G25100-0504 | 5G-4MP | 7100-00065 | 5/16 | 7.9 | 1/4–18 | 5/8 | 2.28 | 58.0 | 1.18 | 30.0 |
| G25100-0506 | 5G-6MP | 7100-10065 | 5/16 | 7.9 | 3/8–18 | 11/16 | 2.32 | 59.0 | 1.22 | 31.0 |
| G25100-0604 | 6G-4MP | 7100-10075 | 3/8 | 9.5 | 1/4–18 | 5/8 | 2.32 | 58.9 | 1.22 | 31.0 |
| G25100-0606 | 6G-6MP | 7100-10085 | 3/8 | 9.5 | 3/8–18 | 11/16 | 2.32 | 58.9 | 1.22 | 31.0 |
| G25100-0608 | 6G-8MP | 7100-10095 | 3/8 | 9.5 | 1/2–14 | 7/8 | 2.51 | 63.8 | 1.42 | 36.1 |
| G25100-0804 | 8G-4MP | 7100-10105 | 1/2 | 12.7 | 1/4–18 | 13/16 | 2.72 | 69.0 | 1.24 | 31.5 |
| G25100-0806 | 8G-6MP | 7100-00105 | 1/2 | 12.7 | 3/8–18 | 13/16 | 2.72 | 69.0 | 1.24 | 31.5 |
| G25100-0808 | 8G-8MP | 7100-00115 | 1/2 | 12.7 | 1/2–14 | 7/8 | 2.87 | 73.0 | 1.40 | 35.5 |
| G25100-0812 | 8G-12MP | 7100-00125 | 1/2 | 12.7 | 3/4–14 | 1 1/16 | 2.95 | 74.9 | 1.47 | 37.3 |
| G25100-1008 | 10G-8MP | 7100-00225 | 5/8 | 15.9 | 1/2–14 | 15/16 | 2.95 | 75.0 | 1.48 | 37.5 |
| G25100-1012 | 10G-12MP | 7100-00235 | 5/8 | 15.9 | 3/4–14 | 1 1/16 | 2.95 | 75.0 | 1.48 | 37.5 |
| G25100-1208 | 12G-8MP | 7100-00155 | 3/4 | 19.1 | 1/2–14 | 1 1/16 | 3.46 | 87.9 | 1.45 | 36.8 |
| G25100-1212 | 12G-12MP | 7100-00165 | 3/4 | 19.1 | 3/4–14 | 1 1/16 | 3.46 | 87.9 | 1.45 | 36.8 |
| G25100-1216 | 12G-16MP | 7100-00175 | 3/4 | 19.1 | 1–11 1/2 | 1 3/8 | 3.77 | 95.8 | 1.77 | 45.0 |
| G25100-1612 | 16G-12MP | 7100-00195 | 1 | 25.4 | 3/4–14 | 1 3/8 | 3.93 | 99.8 | 1.70 | 43.2 |
| G25100-1616 | 16G-16MP | 7100-00205 | 1 | 25.4 | 1–11 1/2 | 1 3/8 | 4.11 | 104.4 | 1.87 | 47.5 |
| G25100-2020 | 20G-20MP | 7100-00215 | 1 1/4 | 31.8 | 1 1/4–11 1/2 | 1 3/4 | 4.44 | 112.8 | 2.12 | 53.8 |

# Male Pipe Long Nose

For use with J2AT Jack Hose and special high–pressure applications.





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G25101-0404 | 4G-4MPLN | 7100-16615 | 1/4 | 6.4 | 1/4–18 | 9/16 | 2.56 | 65.0 | 1.54 | 39.0 |
| G25101-0406 | 4G-6MPLN | 7100-16625 | 1/4 | 6.4 | 3/8–18 | 11/16 | 2.56 | 65.0 | 1.54 | 39.0 |
| G25101-0604 | 6G-4MPLN | 7100-16645 | 3/8 | 9.5 | 1/4–18 | 5/8 | 2.72 | 69.0 | 1.62 | 41.1 |
| G25101-0606 | 6G-6MPLN | 7100-16635 | 3/8 | 9.5 | 3/8–18 | 11/16 | 2.72 | 69.0 | 1.62 | 41.1 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Pipe Swivel (NPTF - without 30° Cone Seat)

NOT TO BE USED AS A LIVE SWIVEL.









| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | " | mm | " | mm |
| G25105-0402 | 4G-2MPX | 7100-10245 | 1/4 | 6.4 | 1/8–27 | 1/2 | 1/2 | 2.39 | 60.7 | 1.37 | 34.8 |
| G25105-0404 | 4G-4MPX | 7100-10255 | 1/4 | 6.4 | 1/4–18 | 1/2 | 11/16 | 2.61 | 66.3 | 1.58 | 40.1 |
| G25105-0406 | 4G-6MPX | 7100-10265 | 1/4 | 6.4 | 3/8–18 | 5/8 | 7/8 | 2.73 | 69.3 | 1.71 | 43.4 |
| G25105-0408 | 4G-8MPX | 7100-10275 | 1/4 | 6.4 | 1/2–14 | 3/4 | 1 | 2.97 | 75.4 | 1.94 | 49.4 |
| G25105-0604 | 6G-4MPX | 7100-10285 | 3/8 | 9.5 | 1/4–18 | 5/8 | 7/8 | 2.87 | 72.8 | 1.77 | 44.9 |
| G25105-0606 | 6G-6MPX | 7100-10295 | 3/8 | 9.5 | 3/8–18 | 5/8 | 7/8 | 2.81 | 71.4 | 1.71 | 43.4 |
| G25105-0608 | 6G-8MPX | 7100-10305 | 3/8 | 9.5 | 1/2–14 | 3/4 | 1 | 3.04 | 77.2 | 1.94 | 49.3 |
| G25105-0806 | 8G-6MPX | 7100-00315 | 1/2 | 12.7 | 3/8–18 | 13/16 | 7/8 | 3.22 | 81.8 | 1.75 | 44.5 |
| G25105-0808 | 8G-8MPX | 7100-00325 | 1/2 | 12.7 | 1/2–14 | 13/16 | 1 | 3.42 | 86.9 | 1.94 | 49.3 |
| G25105-1012 | 10G-12MPX | 7100-00335 | 5/8 | 15.9 | 3/4–14 | 1 1/16 | 1 5/16 | 3.48 | 88.4 | 2.01 | 51.1 |
| G25105-1208 | 12G-8MPX | 7100-00345 | 3/4 | 19.1 | 1/2–14 | 1 1/16 | 1 | 3.97 | 100.8 | 1.96 | 49.8 |
| G25105-1212 | 12G-12MPX | 7100-00355 | 3/4 | 19.1 | 3/4–14 | 1 1/16 | 1 5/16 | 4.01 | 101.9 | 2.00 | 50.8 |
| G25105-1616 | 16G-16MPX | 7100-00365 | 1 | 25.4 | 1–11 1/2 | 1 3/8 | 1 5/8 | 4.73 | 120.1 | 2.49 | 63.2 |

# Male Pipe Swivel - 90° Block (NPTF - without 30° Cone Seat)

NOT TO BE USED AS A LIVE SWIVEL.









| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | " | mm | " | mm | " | mm |
| G25106-0402 | 4G-2MPX90 | 7100-10365 | 1/4 | 6.4 | 1/8–27 | 11/16 | 1/2 | 1.20 | 30.5 | 1.75 | 44.5 | .72 | 18.3 |
| G25106-0404 | 4G-4MPX90 | 7100-10375 | 1/4 | 6.4 | 1/4–18 | 11/16 | 11/16 | 1.62 | 41.1 | 1.75 | 44.5 | .72 | 18.3 |
| G25106-0406 | 4G-6MPX90 | 7100-10385 | 1/4 | 6.4 | 3/8–18 | 11/16 | 7/8 | 1.73 | 43.9 | 1.82 | 46.2 | .79 | 20.1 |
| G25106-0604 | 6G-4MPX90 | 7100-10395 | 3/8 | 9.5 | 1/4–18 | 3/4 | 11/16 | 1.65 | 41.9 | 1.96 | 49.7 | .85 | 21.6 |
| G25106-0606 | 6G-6MPX90 | 7100-10405 | 3/8 | 9.5 | 3/8–18 | 3/4 | 7/8 | 1.76 | 44.7 | 1.96 | 49.7 | .85 | 21.6 |
| G25106-0608 | 6G-8MPX90 | 7100-10415 | 3/8 | 9.5 | 1/2–14 | 3/4 | 1 | 1.93 | 49.1 | 1.96 | 49.7 | .85 | 21.6 |
| G25106-0806 | 8G-6MPX90 | 7100-07135 | 1/2 | 12.7 | 3/8–18 | — | 7/8 | 1.88 | 47.8 | 2.55 | 64.7 | 1.07 | 27.2 |
| G25106-0808 | 8G-8MPX90 | 7100-00425 | 1/2 | 12.7 | 1/2–14 | — | 1 | 2.05 | 52.1 | 2.55 | 64.7 | 1.07 | 27.2 |
| G25106-1212 | 12G-12MPX90 | 7100-00435 | 3/4 | 19.1 | 3/4–14 | — | 1 5/16 | 2.30 | 58.4 | 3.17 | 80.5 | 1.16 | 29.5 |

# Male Pipe Swivel - 90° Long Block (NPTF - without 30° Cone Seat)


NOT TO BE USED AS A LIVE SWIVEL.
These couplings have a longer reach (L dimension) to accommodate the OmniCrimp 21 crimper.








| Part No. | Descr. | Prod. No. | ⟷ | | ≋ | H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm | " | mm |
| G25107-0608 | 6G-8MPX90L | 7100-00445 | 3/8 | 9.5 | 1/2–14 | 3/4 | 1 | 1.93 | 49.0 | 3.40 | 86.4 | 1.94 | 49.3 |
| G25107-0808 | 8G-8MPX90L | 7100-00455 | 1/2 | 12.7 | 1/2–14 | 1 | 1 | 2.06 | 52.3 | 3.27 | 83.1 | 1.80 | 45.7 |
| G25107-1212 | 12G-12MPX90L | 7100-00475 | 3/4 | 19.1 | 3/4–14 | 1 3/8 | 1 5/16 | 2.30 | 58.4 | 3.93 | 99.7 | 1.92 | 48.7 |

# Female Pipe (NPTF - without 30° Cone Seat)




H1






| Part No. | Descr. | Prod. No. | ⟷ | | ≋ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G25110-0402 | 4G-2FP | 7100-10485 | 1/4 | 6.4 | 1/8–27 | 9/16 | 1.74 | 44.2 | .72 | 18.3 |
| G25110-0404 | 4G-4FP | 7100-10495 | 1/4 | 6.4 | 1/4–18 | 11/16 | 1.98 | 50.3 | .96 | 24.4 |
| G25110-0406 | 4G-6FP | 7100-10505 | 1/4 | 6.4 | 3/8–18 | 13/16 | 1.98 | 50.3 | .96 | 24.4 |
| G25110-0604 | 6G-4FP | 7100-10515 | 3/8 | 9.5 | 1/4–18 | 11/16 | 2.00 | 50.8 | .90 | 22.9 |
| G25110-0606 | 6G-6FP | 7100-10525 | 3/8 | 9.5 | 3/8–18 | 13/16 | 2.06 | 52.3 | .96 | 24.4 |
| G25110-0608 | 6G-8FP | 7100-10535 | 3/8 | 9.5 | 1/2–14 | 1 | 2.24 | 56.9 | 1.14 | 29.0 |
| G25110-0806 | 8G-6FP | 7100-00545 | 1/2 | 12.7 | 3/8–18 | 13/16 | 2.46 | 62.5 | .98 | 24.9 |
| G25110-0808 | 8G-8FP | 7100-00555 | 1/2 | 12.7 | 1/2–14 | 1 | 2.63 | 66.8 | 1.16 | 29.5 |
| G25110-1212 | 12G-12FP | 7100-00565 | 3/4 | 19.1 | 3/4–14 | 1 1/4 | 3.22 | 81.8 | 1.22 | 31.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female Pipe Swivel (NPSM - 30° Cone Seat)









| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | " | mm | " | mm |
| G25111-0404 | 4G-4FPX | 7100-10575 | 1/4 | 6.4 | 1/4–18 | 1/2 | — | 11/16 | 2.24 | 56.9 | 1.21 | 30.7 |
| G25111-0606 | 6G-6FPX | 7100-10585 | 3/8 | 9.5 | 3/8–18 | 5/8 | — | 7/8 | 2.48 | 63.0 | 1.38 | 35.1 |
| G25111-0608 | 6G-8FPX | 7100-10595 | 3/8 | 9.5 | 1/2–14 | 13/16 | — | 1 | 2.55 | 64.8 | 1.45 | 36.8 |
| G25111-0808 | 8G-8FPX | 7100-00595 | 1/2 | 12.7 | 1/2–14 | 13/16 | — | 1 | 2.88 | 73.2 | 1.41 | 35.8 |
| G25111-1212 | 12G-12FPX | 7100-00605 | 3/4 | 19.1 | 3/4–14 | — | 27 | 1 1/4 | 3.71 | 94.2 | 1.70 | 43.2 |
| G25111-1616 | 16G-16FPX | 7100-00615 | 1 | 25.4 | 1–11 1/2 | 1 3/8 | — | 1 1/2 | 4.10 | 104.1 | 1.87 | 47.5 |
| G25111-2020 | 20G-20FPX | 7100-00625 | 1 1/4 | 31.8 | 1 1/4–11 1/2 | 1 3/4 | — | 1 7/8 | 4.67 | 118.6 | 2.26 | 57.4 |

# Male O-Ring Boss

SAE J1926/3 ISO 11926–3 Light–Duty (L Series) Stud End.





| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G25120-0404 | 4G-4MB | 7100-12205 | 1/4 | 6.4 | 7/16–20 | 9/16 | 1.99 | 50.5 | .96 | 24.5 |
| G25120-0405 | 4G-5MB | 7100-12215 | 1/4 | 6.4 | 1/2–20 | 5/8 | 1.99 | 50.5 | .96 | 24.5 |
| G25120-0406 | 4G-6MB | 7100-12225 | 1/4 | 6.4 | 9/16–18 | 11/16 | 2.05 | 52.0 | 1.02 | 26.0 |
| G25120-0605 | 6G-5MB | 7100-12285 | 3/8 | 9.5 | 1/2–20 | 5/8 | 2.05 | 52.0 | .95 | 24.1 |
| G25120-0606 | 6G-6MB | 7100-13235 | 3/8 | 9.5 | 9/16–18 | 11/16 | 2.20 | 56.0 | 1.11 | 28.1 |
| G25120-0608 | 6G-8MB | 7100-13245 | 3/8 | 9.5 | 3/4–16 | 7/8 | 2.28 | 58.0 | 1.19 | 30.1 |
| G25120-0610 | 6G-10MB | 7100-12255 | 3/8 | 9.5 | 7/8–14 | 1 | 2.22 | 56.5 | 1.13 | 28.6 |
| G25120-0612 | 6G-12MB | 7100-12265 | 3/8 | 9.5 | 1 1/16–12 | 1 1/4 | 2.42 | 61.5 | 1.32 | 33.6 |
| G25120-0808 | 8G-8MB | 7100-13275 | 1/2 | 12.7 | 3/4–16 | 7/8 | 2.64 | 67.0 | 1.16 | 29.5 |
| G25120-0810 | 8G-10MB | 7100-13285 | 1/2 | 12.7 | 7/8–14 | 1 | 2.68 | 68.0 | 1.20 | 30.5 |
| G25120-0812 | 8G-12MB | 7100-13295 | 1/2 | 12.7 | 1 1/16–12 | 1 1/4 | 2.91 | 74.0 | 1.44 | 36.5 |
| G25120-1008 | 10G-8MB | 7100-02305 | 5/8 | 15.9 | 3/4–16 | 15/16 | 2.83 | 72.0 | 1.36 | 34.5 |
| G25120-1010 | 10G-10MB | 7100-13315 | 5/8 | 15.9 | 7/8–14 | 1 | 2.83 | 72.0 | 1.36 | 34.5 |
| G25120-1012 | 10G-12MB | 7100-13325 | 5/8 | 15.9 | 1 1/16–12 | 1 1/4 | 2.99 | 76.0 | 1.52 | 38.5 |
| G25120-1210 | 12G-10MB | 7100-02265 | 3/4 | 19.1 | 7/8–14 | 1 | 3.23 | 82.1 | 1.22 | 31.1 |
| G25120-1212 | 12G-12MB | 7100-02335 | 3/4 | 19.1 | 1 1/16–12 | 1 1/4 | 3.33 | 84.5 | 1.32 | 33.5 |
| G25120-1214 | 12G-14MB | 7100-02345 | 3/4 | 19.1 | 1 3/16–12 | 1 3/8 | 3.31 | 84.0 | 1.30 | 33.0 |
| G25120-1216 | 12G-16MB | 7100-02355 | 3/4 | 19.1 | 1 5/16–12 | 1 1/2 | 3.44 | 87.5 | 1.44 | 36.5 |
| G25120-1614 | 16G-14MB | 7100-02365 | 1 | 25.4 | 1 3/16–12 | 1 3/8 | 3.78 | 96.0 | 1.54 | 39.2 |
| G25120-1616 | 16G-16MB | 7100-02375 | 1 | 25.4 | 1 5/16–12 | 1 1/2 | 3.84 | 97.5 | 1.60 | 40.7 |
| G25120-1620 | 16G-20MB | 7100-02255 | 1 | 25.4 | 1 5/8–12 | 1 7/8 | 3.74 | 95.0 | 1.50 | 38.2 |


## Male O-Ring Boss - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G25120-2020 | 20G-20MB | 7100-02385 | 1 1/4 | 31.8 | 1 5/8–12 | 1 7/8 | 3.90 | 99.0 | 1.57 | 40.0 |

## Male O-Ring Boss Swivel

NOT TO BE USED AS A LIVE SWIVEL.
NOTE: Internal O–Rings rated at +250°F (+121°C).
SAE J1926/3 ISO 11926–3 Light–Duty (L Series) Stud End.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G25121-0404 | 4G-4MBX | 7209-40015 | 1/4 | 6.4 | 7/16–20 | 19 | 3.21 | 81.5 | 2.19 | 55.5 |
| G25121-0406 | 4G-6MBX | 7209-40025 | 1/4 | 6.4 | 9/16–18 | 19 | 3.21 | 81.5 | 2.19 | 55.5 |
| G25121-0606 | 6G-6MBX | 7209-40045 | 3/8 | 9.5 | 9/16–18 | 22 | 3.33 | 84.5 | 2.23 | 56.6 |
| G25121-0608 | 6G-8MBX | 7209-40055 | 3/8 | 9.5 | 3/4–16 | 23 | 3.33 | 84.5 | 2.23 | 56.6 |
| G25121-0610 | 6G-10MBX | 7209-40065 | 3/8 | 9.5 | 7/8–14 | 27 | 3.21 | 81.5 | 2.11 | 53.6 |
| G25121-0808 | 8G-8MBX | 7209-40085 | 1/2 | 12.7 | 3/4–16 | 23 | 3.78 | 96.0 | 2.30 | 58.5 |
| G25121-0810 | 8G-10MBX | 7209-40095 | 1/2 | 12.7 | 7/8–14 | 27 | 3.84 | 97.5 | 2.36 | 60.0 |
| G25121-1010 | 10G-10MBX | 7209-40115 | 5/8 | 15.9 | 7/8–14 | 32 | 3.88 | 98.5 | 2.40 | 61.0 |
| G25121-1212 | 12G-12MBX | 7209-40145 | 3/4 | 19.1 | 1 1/16–12 | 32 | 4.55 | 115.5 | 2.54 | 64.5 |

## Male O-Ring Boss Swivel - 45° Block

NOT TO BE USED AS A LIVE SWIVEL.
NOTE: Internal O–Rings rated at +250°F (+121°C).
SAE J1926/3 ISO 11926–3 Light–Duty (L Series) Stud End.




| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G25122-0606 | 6G-6MBX45BL | 7100-12475 | 3/8 | 9.5 | 9/16–18 | 7/8 | 1.09 | 27.8 | 3.11 | 79.0 | 2.01 | 51.0 |
| G25122-0608 | 6G-8MBX45BL | 7100-12485 | 3/8 | 9.5 | 3/4–16 | 1 | 1.06 | 26.9 | 3.07 | 78.1 | 1.98 | 50.2 |
| G25122-0808 | 8G-8MBX45BL | 7100-02495 | 1/2 | 12.7 | 3/4–16 | 1 | 1.12 | 28.4 | 3.04 | 77.2 | 1.56 | 39.7 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male O-Ring Boss Swivel - 45° Block - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | Thread | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G25122-0810 | 8G-10MBX45BL | 7100-02505 | 1/2 | 12.7 | 7/8–14 | 1 | 1.16 | 29.5 | 3.08 | 78.3 | 1.61 | 40.8 |

## Male O-Ring Boss Swivel - 90° Block

NOT TO BE USED AS A LIVE SWIVEL.
NOTE: Internal O–Rings rated at +250°F (+121°C).
SAE J1926/3 ISO 11926–3 Light–Duty (L Series) Stud End.









| Part No. | Descr. | Prod. No. | ⊖ | | Thread | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G25123-0405 | 4G-5MBX90BL | 7100-12555 | 1/4 | 6.4 | 1/2–20 | 11/16 | 1.57 | 40.0 | 1.75 | 44.5 | .80 | 20.2 |
| G25123-0406 | 4G-6MBX90BL | 7100-12515 | 1/4 | 6.4 | 9/16–18 | 7/8 | 1.65 | 41.8 | 1.82 | 46.2 | .80 | 20.2 |
| G25123-0606 | 6G-6MBX90BL | 7100-12525 | 3/8 | 9.5 | 9/16–18 | 7/8 | 1.67 | 42.5 | 2.41 | 61.2 | .86 | 21.8 |
| G25123-0608 | 6G-8MBX90BL | 7100-12535 | 3/8 | 9.5 | 3/4–16 | 1 | 1.63 | 41.3 | 2.41 | 61.2 | .86 | 21.8 |
| G25123-0610 | 6G-10MBX90BL | 7100-12545 | 3/8 | 9.5 | 7/8–14 | 1 | 1.69 | 42.8 | 1.95 | 49.6 | .85 | 21.7 |
| G25123-0808 | 8G-8MBX90BL | 7100-02555 | 1/2 | 12.7 | 3/4–16 | 1 | 1.75 | 44.5 | 2.55 | 64.8 | 1.07 | 27.2 |
| G25124-0808 | 8G-8MBX90BLL | 7100-02705 | 1/2 | 12.7 | 3/4–16 | 1 | 1.75 | 44.4 | 3.27 | 83.1 | 1.80 | 45.6 |
| G25123-0810 | 8G-10MBX90BL | 7100-02565 | 1/2 | 12.7 | 7/8–14 | 1 | 1.81 | 46.0 | 2.55 | 64.7 | 1.07 | 27.2 |
| G25124-0810 | 8G-10MBX90BLL | 7100-02715 | 1/2 | 12.7 | 7/8–14 | 1 | 1.81 | 46.0 | 3.27 | 83.1 | 1.80 | 45.6 |
| G25123-0812 | 8G-12MBX90BL | 7100-02575 | 1/2 | 12.7 | 1 1/16–12 | 1 5/16 | 2.09 | 53.1 | 2.52 | 64.1 | 1.07 | 27.2 |
| G25124-0812 | 8G-12MBX90BLL | 7100-02725 | 1/2 | 12.7 | 1 1/16–12 | 1 5/16 | 2.09 | 53.1 | 3.76 | 95.5 | 2.28 | 58.0 |
| G25123-1010 | 10G-10MBX90BL | 7100-02585 | 5/8 | 15.9 | 7/8–14 | 1 | 1.81 | 46.0 | 2.40 | 61.0 | .93 | 23.6 |
| G25124-1010 | 10G-10MBX90BLL | 7100-02735 | 5/8 | 15.9 | 7/8–14 | 1 | 1.81 | 46.0 | 3.15 | 79.9 | 1.67 | 42.4 |
| G25123-1212 | 12G-12MBX90BL | 7100-02595 | 3/4 | 19.1 | 1 1/16–12 | 1 5/16 | 2.39 | 60.7 | 3.18 | 80.8 | 1.17 | 29.7 |
| G25124-1212 | 12G-12MBX90BLL | 7100-02755 | 3/4 | 19.1 | 1 1/16–12 | 1 5/16 | 2.28 | 57.9 | 3.94 | 100.0 | 1.93 | 49.0 |

# Male O-Ring Boss Swivel - 45° Bent Tube

NOT TO BE USED AS A LIVE SWIVEL.
NOTE: Internal O–Rings rated at +250°F (+121°C).
SAE J1926/3 ISO 11926–3 Light–Duty (L Series) Stud End.









| Part No. | Descr. | Prod. No. | ⟷ | | ≡ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25126-0606 | 6G-6MBX45 | 7209-40225 | 3/8 | 9.5 | 9/16–18 | 22 | 1.52 | 38.7 | 3.65 | 92.6 | 2.54 | 64.6 |
| G25126-0608 | 6G-8MBX45 | 7209-40235 | 3/8 | 9.5 | 3/4–16 | 24 | 1.52 | 38.7 | 3.65 | 92.6 | 2.54 | 64.6 |
| G25126-0808 | 8G-8MBX45 | 7209-40255 | 1/2 | 12.7 | 3/4–16 | 24 | 1.64 | 41.7 | 4.24 | 107.7 | 2.77 | 70.3 |
| G25126-0810 | 8G-10MBX45 | 7209-40265 | 1/2 | 12.7 | 7/8–14 | 27 | 1.69 | 42.8 | 4.28 | 108.8 | 2.81 | 71.3 |

# Male O-Ring Boss Swivel - 90° Bent Tube

NOT TO BE USED AS A LIVE SWIVEL.
NOTE: Internal O–Rings rated at +250°F (+121°C).
SAE J1926/3 ISO 11926–3 Light–Duty (L Series) Stud End.









| Part No. | Descr. | Prod. No. | ⟷ | | ≡ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G25128-0406 | 4G-6MBX90 | 7209-40425 | 1/4 | 6.4 | 9/16–18 | 7/8 | 2.36 | 60.0 | 2.19 | 55.6 | 1.17 | 29.6 |
| G25128-0606 | 6G-6MBX90 | 7209-40455 | 3/8 | 9.5 | 9/16–18 | 7/8 | 2.48 | 63.1 | 2.47 | 62.8 | 1.37 | 34.8 |
| G25128-0608 | 6G-8MBX90 | 7209-40475 | 3/8 | 9.5 | 3/4–16 | 1 | 2.48 | 63.1 | 2.47 | 62.8 | 1.37 | 34.8 |
| G25128-0610 | 6G-10MBX90 | 7209-40485 | 3/8 | 9.5 | 7/8–14 | 1 | 2.37 | 60.1 | 2.47 | 62.8 | 1.37 | 34.8 |
| G25128-0808 | 8G-8MBX90 | 7209-40505 | 1/2 | 12.7 | 3/4–16 | 1 | 2.76 | 70.1 | 3.16 | 80.3 | 1.69 | 42.9 |
| G25128-0810 | 8G-10MBX90 | 7209-40525 | 1/2 | 12.7 | 7/8–14 | 1 | 2.82 | 71.6 | 3.16 | 80.3 | 1.69 | 42.9 |
| G25128-0812 | 8G-12MBX90 | 7209-40545 | 1/2 | 12.7 | 1 1/16–12 | 1 1/4 | 2.90 | 73.6 | 3.16 | 80.3 | 1.69 | 42.9 |
| G25128-1010 | 10G-10MBX90 | 7209-40585 | 5/8 | 15.9 | 7/8–14 | 1 5/16 | 3.14 | 79.8 | 3.55 | 90.1 | 2.07 | 52.6 |
| G25128-1012 | 10G-12MBX90 | 7209-40605 | 5/8 | 15.9 | 1 1/16–12 | 1 | 3.18 | 80.8 | 3.55 | 90.1 | 2.07 | 52.6 |
| G25128-1212 | 12G-12MBX90 | 7209-40645 | 3/4 | 19.1 | 1 1/16–12 | 1 5/16 | 3.42 | 86.8 | 4.33 | 110.1 | 2.33 | 59.1 |

# Male O-Ring Boss Adapterless Swivel - 90° Bent Tube


NOTE: Internal O–Rings rated at +250°F (+121°C).





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | mm | " | mm | " | mm | " | mm |
| G25134-0404 | 4G-4MBAX90M | 7100-18615 | 1/4 | 6.4 | 7/16–20 | 17 | 17 | 2.95 | 74.9 | 2.42 | 61.5 | 1.38 | 35.1 |
| G25134-0606 | 6G-6MBAX90M | 7100-18715 | 3/8 | 9.5 | 9/16–18 | 22 | 22 | 3.27 | 83.1 | 2.76 | 70.1 | 1.66 | 42.2 |
| G25134-0808 | 8G-8MBAX90M | 7100-18765 | 1/2 | 12.7 | 3/4–16 | 24 | 24 | 3.82 | 97.0 | 3.44 | 87.4 | 1.97 | 50.0 |
| G25134-1010 | 10G-10MBAX90M | 7100-18815 | 5/8 | 15.9 | 7/8–14 | 30 | 30 | 4.33 | 110.0 | 3.76 | 95.5 | 2.28 | 57.9 |
| G25134-1212 | 12G-12MBAX90M | 7100-18865 | 3/4 | 19.1 | 1 1/16–12 | 36 | 36 | 4.80 | 122.0 | 4.49 | 114.1 | 2.48 | 63.0 |

# Male JIC 37° Flare









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G25165-0404 | 4G-4MJ | 7103-36045 | 1/4 | 6.4 | 7/16–20 | 14 | 2.19 | 55.5 | 1.16 | 29.5 |
| G25165-0405 | 4G-5MJ | 7103-36055 | 1/4 | 6.4 | 1/2–20 | 14 | 2.19 | 55.5 | 1.16 | 29.5 |
| G25165-0406 | 4G-6MJ | 7103-36065 | 1/4 | 6.4 | 9/16–18 | 17 | 2.22 | 56.5 | 1.20 | 30.5 |
| G25165-0505 | 5G-5MJ | 7103-36105 | 5/16 | 7.9 | 1/2–20 | 17 | 2.26 | 57.5 | 1.16 | 29.5 |
| G25165-0506 | 5G-6MJ | 7103-36115 | 5/16 | 7.9 | 9/16–18 | 17 | 2.26 | 57.5 | 1.16 | 29.5 |
| G25165-0606 | 6G-6MJ | 7103-36155 | 3/8 | 9.5 | 9/16–18 | 17 | 2.30 | 58.5 | 1.20 | 30.6 |
| G25165-0608 | 6G-8MJ | 7103-36165 | 3/8 | 9.5 | 3/4–16 | 19 | 2.48 | 63.0 | 1.38 | 35.1 |
| G25165-0610 | 6G-10MJ | 7103-36175 | 3/8 | 9.5 | 7/8–14 | 24 | 2.64 | 67.0 | 1.54 | 39.1 |
| G25165-0808 | 8G-8MJ | 7103-36215 | 1/2 | 12.7 | 3/4–16 | 22 | 2.81 | 71.5 | 1.34 | 34.0 |
| G25165-0810 | 8G-10MJ | 7103-36225 | 1/2 | 12.7 | 7/8–14 | 24 | 2.91 | 74.0 | 1.44 | 36.5 |
| G25165-0812 | 8G-12MJ | 7103-36235 | 1/2 | 12.7 | 1 1/16–12 | 27 | 3.19 | 81.0 | 1.71 | 43.5 |
| G25165-1008 | 10G-8MJ | 7103-36265 | 5/8 | 15.9 | 3/4–16 | 27 | 2.93 | 74.5 | 1.46 | 37.0 |
| G25165-1010 | 10G-10MJ | 7103-36275 | 5/8 | 15.9 | 7/8–14 | 27 | 3.03 | 77.0 | 1.56 | 39.5 |
| G25165-1012 | 10G-12MJ | 7103-36285 | 5/8 | 15.9 | 1 1/16–12 | 27 | 3.19 | 81.0 | 1.71 | 43.5 |
| G25165-1210 | 12G-10MJ | 7103-36315 | 3/4 | 19.1 | 7/8–14 | 27 | 3.68 | 93.5 | 1.67 | 42.5 |
| G25165-1212 | 12G-12MJ | 7103-36325 | 3/4 | 19.1 | 1 1/16–12 | 27 | 3.72 | 94.5 | 1.71 | 43.5 |

## Male JIC 37° Flare - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | ≋ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G25165-1214 | 12G-14MJ | 7103-36335 | 3/4 | 19.1 | 1 3/16–12 | 32 | 3.76 | 95.5 | 1.75 | 44.5 |
| G25165-1216 | 12G-16MJ | 7103-36345 | 3/4 | 19.1 | 1 5/16–12 | 36 | 3.78 | 96.0 | 1.77 | 45.0 |
| G25165-1614 | 16G-14MJ | 7103-36375 | 1 | 25.4 | 1 3/16–12 | 36 | 4.09 | 104.0 | 1.86 | 47.2 |
| G25165-1616 | 16G-16MJ | 7103-36385 | 1 | 25.4 | 1 5/16–12 | 36 | 4.11 | 104.5 | 1.88 | 47.7 |
| G25165-1620 | 16G-20MJ | 7103-36395 | 1 | 25.4 | 1 5/8–12 | 46 | 4.29 | 109.0 | 2.06 | 52.2 |
| G25165-2020 | 20G-20MJ | 7103-36435 | 1 1/4 | 31.8 | 1 5/8–12 | 46 | 4.43 | 112.5 | 2.11 | 53.5 |
| G25165-2024 | 20G-24MJ | 7103-36445 | 1 1/4 | 31.8 | 1 7/8–12 | 50 | 4.43 | 112.5 | 2.11 | 53.5 |

## Female JIC 37° Flare Swivel









| Part No. | Descr. | Prod. No. | ⊖ | | ≋ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G25170-0404 | 4G-4FJX | 7103-08045 | 1/4 | 6.4 | 7/16–20 | 15 | 14 | 2.20 | 55.9 | 1.18 | 29.9 |
| G25170-0405 | 4G-5FJX | 7103-08055 | 1/4 | 6.4 | 1/2–20 | 15 | 17 | 2.30 | 58.3 | 1.27 | 32.3 |
| G25170-0406 | 4G-6FJX | 7103-08065 | 1/4 | 6.4 | 9/16–18 | 15 | 19 | 2.35 | 59.6 | 1.32 | 33.6 |
| G25170-0505 | 5G-5FJX | 7103-09095 | 5/16 | 7.9 | 1/2–20 | 17 | 17 | 2.44 | 62.1 | 1.34 | 34.1 |
| G25170-0506 | 5G-6FJX | 7103-09105 | 5/16 | 7.9 | 9/16–18 | 17 | 19 | 2.50 | 63.6 | 1.40 | 35.6 |
| G25170-0604 | 6G-4FJXSP | 7103-10125 | 3/8 | 9.5 | 7/16–20 | 17 | 14 | 2.30 | 58.4 | 1.20 | 30.5 |
| G25171-0604 | 6G-4FJX | 7103-09135 | 3/8 | 9.5 | 7/16–20 | 15.9 | 14 | 2.94 | 74.7 | 1.84 | 46.8 |
| G25170-0605 | 6G-5FJXSP | 7103-10135 | 3/8 | 9.5 | 1/2–20 | 17 | 17 | 2.27 | 57.7 | 1.17 | 29.8 |
| G25171-0605 | 6G-5FJX | 7103-09125 | 3/8 | 9.5 | 1/2–20 | 17 | 17 | 2.96 | 75.2 | 1.86 | 47.3 |
| G25170-0606 | 6G-6FJX | 7103-08145 | 3/8 | 9.5 | 9/16–18 | 18 | 19 | 2.42 | 61.5 | 1.29 | 32.7 |
| G25170-0608 | 6G-8FJX | 7103-08155 | 3/8 | 9.5 | 3/4–16 | 18 | 24 | 2.63 | 66.7 | 1.49 | 37.9 |
| G25170-0610 | 6G-10FJX | 7103-08165 | 3/8 | 9.5 | 7/8–14 | 18 | 27 | 2.76 | 70.0 | 1.62 | 41.2 |
| G25170-0612 | 6G-12FJX | 7103-09175 | 3/8 | 9.5 | 1 1/16–12 | 17 | 32 | 2.91 | 74.0 | 1.81 | 46.0 |
| G25170-0806 | 8G-6FJXSP | 7103-10195 | 1/2 | 12.7 | 9/16–18 | 22 | 19 | 2.67 | 67.8 | 1.19 | 30.3 |
| G25171-0806 | 8G-6FJX | 7103-09195 | 1/2 | 12.7 | 9/16–18 | 22 | 19 | 3.81 | 96.7 | 2.33 | 59.2 |
| G25170-0808 | 8G-8FJX | 7103-08205 | 1/2 | 12.7 | 3/4–16 | 22 | 24 | 2.88 | 73.2 | 1.50 | 38.0 |
| G25170-0810 | 8G-10FJX | 7103-08215 | 1/2 | 12.7 | 7/8–14 | 22 | 27 | 3.01 | 76.5 | 1.63 | 41.3 |
| G25170-0812 | 8G-12FJX | 7103-08225 | 1/2 | 12.7 | 1 1/16–12 | 22 | 32 | 3.06 | 77.7 | 1.67 | 42.5 |
| G25170-0816 | 8G-16FJX | 7103-09235 | 1/2 | 12.7 | 1 5/16–12 | 22 | 41 | 3.52 | 89.3 | 2.04 | 51.8 |
| G25170-1008 | 10G-8FJXSP | 7103-10255 | 5/8 | 15.9 | 3/4–16 | 24 | 24 | 2.90 | 73.6 | 1.42 | 36.1 |
| G25171-1008 | 10G-8FJX | 7103-09255 | 5/8 | 15.9 | 3/4–16 | 24 | 24 | 4.06 | 103.0 | 2.58 | 65.5 |
| G25170-1010 | 10G-10FJX | 7103-08265 | 5/8 | 15.9 | 7/8–14 | 24 | 27 | 3.14 | 79.7 | 1.66 | 42.2 |
| G25170-1012 | 10G-12FJX | 7103-08275 | 5/8 | 15.9 | 1 1/16–12 | 24 | 32 | 3.20 | 81.4 | 1.73 | 43.9 |
| G25170-1014 | 10G-14FJX | 7103-08285 | 5/8 | 15.9 | 1 3/16–12 | 24 | 36 | 3.39 | 86.1 | 1.91 | 48.6 |
| G25170-1208 | 12G-8FJX | 7103-10305 | 3/4 | 19.1 | 3/4–16 | 27 | 24 | 3.51 | 89.1 | 1.50 | 38.1 |
| G25170-1210 | 12G-10FJXSP | 7103-10315 | 3/4 | 19.1 | 7/8–14 | 27 | 27 | 3.51 | 89.2 | 1.50 | 38.2 |
| G25171-1210 | 12G-10FJX | 7103-09315 | 3/4 | 19.1 | 7/8–14 | 27 | 27 | 4.80 | 122.0 | 2.80 | 71.0 |
| G25170-1212 | 12G-12FJX | 7103-08325 | 3/4 | 19.1 | 1 1/16–12 | 30 | 32 | 3.74 | 95.0 | 1.73 | 44.0 |
| G25170-1214 | 12G-14FJX | 7103-08335 | 3/4 | 19.1 | 1 3/16–12 | 30 | 36 | 3.81 | 96.9 | 1.81 | 45.9 |
| G25170-1216 | 12G-16FJX | 7103-08345 | 3/4 | 19.1 | 1 5/16–12 | 30 | 41 | 3.85 | 97.9 | 1.85 | 46.9 |

## Female JIC 37° Flare Swivel - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | mm | " | mm | " | mm |
| G25170-1612 | 16G-12FJXSP | 7103-10375 | 1 | 25.4 | 1 1/16–12 | 36 | 32 | 4.02 | 102.0 | 1.78 | 45.2 |
| G25171-1612 | 16G-12FJX | 7103-09375 | 1 | 25.4 | 1 1/16–12 | 36 | 32 | 5.87 | 149.1 | 3.64 | 92.4 |
| G25170-1614 | 16G-14FJXSP | 7103-10385 | 1 | 25.4 | 1 3/16–12 | 36 | 36 | 4.02 | 102.1 | 1.78 | 45.3 |
| G25171-1614 | 16G-14FJX | 7103-09385 | 1 | 25.4 | 1 3/16–12 | 36 | 36 | 6.31 | 160.4 | 4.08 | 103.6 |
| G25170-1616 | 16G-16FJX | 7103-08395 | 1 | 25.4 | 1 5/16–12 | 36 | 41 | 4.24 | 107.8 | 2.01 | 51.0 |
| G25170-1620 | 16G-20FJX | 7103-08405 | 1 | 25.4 | 1 5/8–12 | 36 | 50 | 4.54 | 115.3 | 2.30 | 58.5 |
| G25170-2020 | 20G-20FJX | 7103-08435 | 1 1/4 | 31.8 | 1 5/8–12 | 41 | 50 | 4.42 | 112.3 | 2.10 | 53.3 |
| G25170-2024 | 20G-24FJX | 7103-08445 | 1 1/4 | 31.8 | 1 7/8–12 | 41 | 60 | 4.86 | 123.4 | 2.14 | 64.4 |


## Female JIC 37° Flare Swivel - 30° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm | " | mm |
| G25172-1012 | 10G-12FJX30-018 | 7103-57005 | 5/8 | 15.9 | 1 1/16–12 | 32 | .71 | 18.0 | 4.43 | 112.4 | 2.95 | 74.9 |
| G25172-1210 | 12G-10FJX30-018 | 7103-59005 | 3/4 | 19.1 | 7/8–14 | 27 | .71 | 18.0 | 4.45 | 113.0 | 2.44 | 62.0 |

## Female JIC 37° Flare Swivel - 45° Bent Tube









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm | " | mm |
| G25175-0404 | 4G-4FJX45S | 7103-46055 | 1/4 | 6.4 | 7/16–20 | 14 | .39 | 10.0 | 2.74 | 69.7 | 1.72 | 43.7 |
| G25175-0405 | 4G-5FJX45-011 | 7103-46075 | 1/4 | 6.4 | 1/2–20 | 17 | .43 | 11.0 | 2.59 | 65.8 | 1.56 | 39.7 |
| G25175-0406 | 4G-6FJX45S | 7103-46135 | 1/4 | 6.4 | 9/16–18 | 19 | .43 | 11.0 | 2.69 | 68.3 | 1.67 | 42.3 |
| G25175-0505 | 5G-5FJX45-011 | 7103-46175 | 5/16 | 7.9 | 1/2–20 | 17 | .43 | 11.0 | 2.69 | 68.3 | 1.59 | 40.3 |
| G25175-0506 | 5G-6FJX45S | 7103-46195 | 5/16 | 7.9 | 9/16–18 | 19 | .43 | 11.0 | 2.85 | 72.4 | 1.75 | 44.4 |
| G25175-0604 | 6G-4FJX45S | 7103-46215 | 3/8 | 9.5 | 7/16–20 | 14 | .39 | 10.0 | 2.86 | 72.7 | 1.76 | 44.8 |
| G25175-0606 | 6G-6FJX45S | 7103-46235 | 3/8 | 9.5 | 9/16–18 | 19 | .43 | 11.0 | 3.05 | 77.5 | 1.95 | 49.6 |
| G25175-0608 | 6G-8FJX45S | 7103-46255 | 3/8 | 9.5 | 3/4–16 | 24 | .59 | 15.0 | 3.51 | 89.1 | 2.41 | 61.2 |
| G25174-0808 | 8G-8FJX45S | 7103-46295 | 1/2 | 12.7 | 3/4–16 | 24 | .59 | 15.0 | 3.42 | 86.9 | 1.95 | 49.5 |
| G25175-0810 | 8G-10FJX45S | 7103-46315 | 1/2 | 12.7 | 7/8–14 | 27 | .63 | 16.0 | 3.81 | 96.8 | 2.34 | 59.4 |

## Female JIC 37° Flare Swivel - 45° Bent Tube - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25175-1010 | 10G-10FJX45S | 7103-46355 | 5/8 | 15.9 | 7/8–14 | 27 | .63 | 16.0 | 3.80 | 96.4 | 2.32 | 59.0 |
| G25175-1012 | 10G-12FJX45S | 7103-46375 | 5/8 | 15.9 | 1 1/16–12 | 32 | .83 | 21.0 | 4.57 | 116.0 | 3.09 | 78.5 |
| G25175-1210 | 12G-10FJX45S | 7103-46415 | 3/4 | 19.1 | 7/8–14 | 27 | .75 | 19.1 | 4.58 | 116.3 | 2.57 | 65.3 |
| G25175-1212 | 12G-12FJX45S | 7103-46425 | 3/4 | 19.1 | 1 1/16–12 | 32 | .83 | 21.0 | 5.09 | 129.2 | 3.08 | 78.2 |
| G25175-1216 | 12G-16FJX45S | 7103-46455 | 3/4 | 19.1 | 1 5/16–12 | 41 | .94 | 24.0 | 5.24 | 133.1 | 3.23 | 82.1 |
| G25174-1612 | 16G-12FJX45S | 7103-46495 | 1 | 25.4 | 1 1/16–12 | 32 | .83 | 21.0 | 5.48 | 139.2 | 3.24 | 82.4 |
| G25175-1616 | 16G-16FJX45S | 7103-46505 | 1 | 25.4 | 1 5/16–12 | 41 | .94 | 24.0 | 5.68 | 144.3 | 3.44 | 87.5 |
| G25175-2020 | 20G-20FJX45-035 | 7103-46605 | 1 1/4 | 31.8 | 1 5/8–12 | 50 | 1.38 | 35.0 | 6.65 | 169.0 | 4.33 | 110.0 |

## Female JIC 37° Flare Swivel - 90° Bent Tube









| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25179-0404 | 4G-4FJX90S | 7103-47045 | 1/4 | 6.4 | 7/16–20 | 14 | .83 | 21.0 | 2.48 | 63.1 | 1.46 | 37.1 |
| G25180-0404 | 4G-4FJX90M | 7103-47055 | 1/4 | 6.4 | 7/16–20 | 14 | 1.26 | 32.0 | 2.48 | 63.1 | 1.46 | 37.1 |
| G25181-0404 | 4G-4FJX90L | 7103-47065 | 1/4 | 6.4 | 7/16–20 | 14 | 1.81 | 46.0 | 2.48 | 63.1 | 1.46 | 37.1 |
| G25179-0405 | 4G-5FJX90-023 | 7103-47075 | 1/4 | 6.4 | 1/2–20 | 17 | .91 | 23.0 | 2.45 | 62.2 | 1.43 | 36.2 |
| G25180-0405 | 4G-5FJX90M | 7103-47095 | 1/4 | 6.4 | 1/2–20 | 17 | 1.26 | 32.0 | 2.25 | 57.2 | 1.23 | 31.2 |
| G25181-0405 | 4G-5FJX90L | 7103-47105 | 1/4 | 6.4 | 1/2–20 | 17 | 1.81 | 46.0 | 2.25 | 57.2 | 1.23 | 31.2 |
| G25179-0406 | 4G-6FJX90S | 7103-47125 | 1/4 | 6.4 | 9/16–18 | 19 | .91 | 23.0 | 2.80 | 71.2 | 1.78 | 45.1 |
| G25180-0406 | 4G-6FJX90M | 7103-47135 | 1/4 | 6.4 | 9/16–18 | 19 | 1.50 | 38.0 | 2.56 | 64.9 | 1.53 | 38.9 |
| G25181-0406 | 4G-6FJX90L | 7103-47145 | 1/4 | 6.4 | 9/16–18 | 19 | 2.13 | 54.0 | 2.73 | 69.3 | 1.70 | 43.2 |
| G25179-0506 | 5G-6FJX90S | 7103-47165 | 5/16 | 7.9 | 9/16–18 | 19 | .91 | 23.0 | 2.96 | 75.2 | 1.86 | 47.2 |
| G25180-0506 | 5G-6FJX90M | 7103-47175 | 5/16 | 7.9 | 9/16–18 | 19 | 1.50 | 38.0 | 2.99 | 76.0 | 1.89 | 48.0 |
| G25179-0604 | 6G-4FJX90S | 7103-47195 | 3/8 | 9.5 | 7/16–20 | 14 | .83 | 21.0 | 2.60 | 66.1 | 1.50 | 38.2 |
| G25181-0604 | 6G-4FJX90L | 7103-47635 | 3/8 | 9.5 | 7/16–20 | 14 | 1.81 | 46.0 | 2.37 | 60.2 | 1.27 | 32.3 |
| G25179-0606 | 6G-6FJX90S | 7103-47205 | 3/8 | 9.5 | 9/16–18 | 19 | .91 | 23.0 | 3.09 | 78.6 | 1.99 | 50.7 |
| G25180-0606 | 6G-6FJX90M | 7103-47215 | 3/8 | 9.5 | 9/16–18 | 19 | 1.50 | 38.0 | 3.01 | 76.5 | 1.91 | 48.5 |
| G25181-0606 | 6G-6FJX90L | 7103-47225 | 3/8 | 9.5 | 9/16–18 | 19 | 2.13 | 54.0 | 2.78 | 70.6 | 1.68 | 42.7 |
| G25179-0608 | 6G-8FJX90S | 7103-47245 | 3/8 | 9.5 | 3/4–16 | 24 | 1.14 | 29.0 | 3.18 | 80.7 | 2.08 | 52.8 |
| G25180-0608 | 6G-8FJX90M | 7103-47255 | 3/8 | 9.5 | 3/4–16 | 24 | 1.61 | 41.0 | 3.31 | 84.1 | 2.21 | 56.2 |
| G25181-0608 | 6G-8FJX90L | 7103-47265 | 3/8 | 9.5 | 3/4–16 | 24 | 2.52 | 64.0 | 3.33 | 84.5 | 2.23 | 56.6 |
| G25180-0610 | 6G-10FJX90M | 7103-47235 | 3/8 | 9.5 | 7/8–14 | 27 | 1.85 | 47.0 | 3.25 | 82.5 | 2.15 | 54.6 |
| G25179-0806 | 8G-6FJX90S | 7103-47275 | 1/2 | 12.7 | 9/16–18 | 19 | .91 | 23.1 | 3.53 | 89.7 | 2.05 | 52.1 |
| G25179-0808 | 8G-8FJX90S | 7103-47285 | 1/2 | 12.7 | 3/4–16 | 24 | 1.14 | 29.0 | 3.19 | 81.0 | 1.71 | 43.6 |
| G25180-0808 | 8G-8FJX90M | 7103-47295 | 1/2 | 12.7 | 3/4–16 | 24 | 1.61 | 41.0 | 3.04 | 77.3 | 1.30 | 32.9 |
| G25181-0808 | 8G-8FJX90L | 7103-47305 | 1/2 | 12.7 | 3/4–16 | 24 | 2.52 | 64.0 | 3.04 | 77.3 | 1.57 | 39.9 |
| G25179-0810 | 8G-10FJX90S | 7103-47325 | 1/2 | 12.7 | 7/8–14 | 27 | 1.26 | 32.0 | 3.67 | 93.3 | 2.20 | 55.8 |
| G25180-0810 | 8G-10FJX90M | 7103-47335 | 1/2 | 12.7 | 7/8–14 | 27 | 1.85 | 47.0 | 3.67 | 93.3 | 2.20 | 55.8 |
| G25181-0810 | 8G-10FJX90L | 7103-47345 | 1/2 | 12.7 | 7/8–14 | 27 | 2.76 | 70.0 | 3.67 | 93.3 | 2.20 | 55.8 |
| G25183-0810 | 8G-10FJX90-089 | 7103-47655 | 1/2 | 12.7 | 7/8–14 | 27 | 3.50 | 89.0 | 3.65 | 92.8 | 2.18 | 55.3 |
| G25179-0812 | 8G-12FJX90S | 7103-47355 | 1/2 | 12.7 | 1 1/16–12 | 32 | 1.89 | 48.0 | 4.28 | 108.7 | 2.80 | 71.1 |

## Female JIC 37° Flare Swivel - 90° Bent Tube - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25179-1010 | 10G-10FJX90-036 | 7103-47675 | 5/8 | 15.9 | 7/8–14 | 27 | 1.42 | 36.0 | 3.50 | 89.0 | 2.03 | 51.5 |
| G25180-1010 | 10G-10FJX90M | 7103-47375 | 5/8 | 15.9 | 7/8–14 | 27 | 1.85 | 47.0 | 3.68 | 93.4 | 2.20 | 55.9 |
| G25181-1010 | 10G-10FJX90L | 7103-47385 | 5/8 | 15.9 | 7/8–14 | 27 | 2.76 | 70.0 | 3.38 | 85.9 | 1.91 | 48.4 |
| G25179-1012 | 10G-12FJX90S | 7103-47405 | 5/8 | 15.9 | 1 1/16–12 | 32 | 1.89 | 48.0 | 4.22 | 107.3 | 2.75 | 69.8 |
| G25180-1012 | 10G-12FJX90M | 7103-47415 | 5/8 | 15.9 | 1 1/16–12 | 32 | 2.28 | 58.0 | 4.03 | 102.3 | 1.80 | 45.8 |
| G25181-1012 | 10G-12FJX90L | 7103-47425 | 5/8 | 15.9 | 1 1/16–12 | 32 | 3.78 | 96.0 | 4.56 | 115.7 | 3.08 | 78.2 |
| G25180-1210 | 12G-10FJX90M | 7103-47435 | 3/4 | 19.1 | 7/8–14 | 27 | 1.85 | 47.0 | 4.49 | 114.1 | 2.48 | 63.1 |
| G25179-1212 | 12G-12FJX90S | 7103-47445 | 3/4 | 19.1 | 1 1/16–12 | 32 | 1.89 | 48.0 | 4.82 | 122.4 | 2.81 | 71.4 |
| G25180-1212 | 12G-12FJX90M | 7103-47455 | 3/4 | 19.1 | 1 1/16–12 | 32 | 2.28 | 58.0 | 4.82 | 122.4 | 2.81 | 71.4 |
| G25181-1212 | 12G-12FJX90L | 7103-47465 | 3/4 | 19.1 | 1 1/16–12 | 32 | 3.78 | 96.0 | 4.82 | 122.4 | 2.81 | 71.4 |
| G25179-1214 | 12G-14FJX90-054 | 7103-47615 | 3/4 | 19.1 | 1 3/16–12 | 36 | 2.13 | 54.0 | 4.88 | 124.0 | 2.87 | 73.0 |
| G25181-1214 | 12G-14FJX90-100 | 7103-47625 | 3/4 | 19.1 | 1 3/16–12 | 36 | 3.94 | 100.0 | 4.23 | 107.4 | 2.22 | 56.4 |
| G25179-1216 | 12G-16FJX90S | 7103-47475 | 3/4 | 19.1 | 1 5/16–12 | 41 | 2.20 | 56.0 | 5.22 | 132.7 | 3.22 | 81.7 |
| G25180-1216 | 12G-16FJX90M | 7103-47515 | 3/4 | 19.1 | 1 5/16–12 | 41 | 2.80 | 71.0 | 4.78 | 121.3 | 2.77 | 70.3 |
| G25179-1616 | 16G-16FJX90S | 7103-47485 | 1 | 25.4 | 1 5/16–12 | 41 | 2.20 | 56.0 | 5.73 | 145.6 | 3.50 | 88.8 |
| G25180-1616 | 16G-16FJX90M | 7103-47495 | 1 | 25.4 | 1 5/16–12 | 41 | 2.80 | 71.0 | 4.73 | 120.2 | 2.50 | 63.4 |
| G25181-1616 | 16G-16FJX90L | 7103-47505 | 1 | 25.4 | 1 5/16–12 | 41 | 4.49 | 114.0 | 4.74 | 120.3 | 2.50 | 63.5 |
| G25179-1620 | 16G-20FJX90S | 7103-47535 | 1 | 25.4 | 1 5/8–12 | 50 | 2.52 | 64.0 | 6.18 | 157.0 | 3.94 | 100.2 |
| G25180-2020 | 20G-20FJX90M | 7103-47575 | 1 1/4 | 31.8 | 1 5/8–12 | 50 | 3.07 | 78.0 | 6.26 | 159.0 | 3.94 | 100.1 |
| G25181-2020 | 20G-20FJX90L | 7103-47585 | 1 1/4 | 31.8 | 1 5/8–12 | 50 | 5.08 | 129.0 | 6.22 | 158.0 | 3.90 | 99.0 |
| G25183-2020 | 20G-20FJX90-089 | 7103-47595 | 1 1/4 | 31.8 | 1 5/8–12 | 50 | 3.50 | 89.0 | 6.22 | 157.8 | 3.89 | 98.8 |


## Female JIC 37° Flare Swivel - 90° Block





| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G25187-1216 | 12G-16FJX90BLK | 7103-59015 | 3/4 | 19.1 | 1 5/16–12 | 1 3/8 | 2.09 | 53.2 | 4.53 | 115.0 | 1.73 | 44.0 |


# Male SAE 45° Flare





| Part No. | Descr. | Prod. No. | ⊖ | | ≋ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G25195-0404 | 4G-4MS | 7100-11815 | 1/4 | 6.4 | 7/16–20 | 1/2 | 2.50 | 63.5 | 1.08 | 27.5 |
| G25195-0405 | 4G-5MS | 7100-11825 | 1/4 | 6.4 | 1/2–20 | 1/2 | 2.16 | 54.8 | 1.13 | 28.8 |
| G25195-0606 | 6G-6MS | 7100-11835 | 3/8 | 9.5 | 5/8–18 | 5/8 | 2.38 | 60.5 | 1.28 | 32.6 |
| G25195-0608 | 6G-8MS | 7100-11845 | 3/8 | 9.5 | 3/4–16 | 13/16 | 2.42 | 61.4 | 1.31 | 33.4 |
| G25195-0808 | 8G-8MS | 7100-01855 | 1/2 | 12.7 | 3/4–16 | 13/16 | 2.89 | 73.5 | 1.42 | 36.0 |
| G25195-0810 | 8G-10MS | 7100-01865 | 1/2 | 12.7 | 7/8–14 | 7/8 | 3.03 | 77.0 | 1.56 | 39.5 |
| G25195-1212 | 12G-12MS | 7100-01875 | 3/4 | 19.1 | 1 1/16–14 | 1 1/16 | 3.78 | 96.0 | 1.77 | 45.0 |

# Female SAE 45° Flare Swivel









| Part No. | Descr. | Prod. No. | ⊖ | | ≋ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G25200-0404 | 4G-4FSX | 7100-11885 | 1/4 | 6.4 | 7/16–20 | 1/2 | 9/16 | 2.24 | 57.0 | 1.22 | 31.0 |
| G25200-0405 | 4G-5FSX | 7100-11895 | 1/4 | 6.4 | 1/2–20 | 1/2 | 11/16 | 2.21 | 56.2 | 1.19 | 30.2 |
| G25200-0406 | 4G-6FSX | 7100-11905 | 1/4 | 6.4 | 5/8–18 | 5/8 | 3/4 | 2.31 | 58.7 | 1.28 | 32.6 |
| G25200-0506 | 5G-6FSX | 7100-11935 | 5/16 | 7.9 | 5/8–18 | 5/8 | 3/4 | 2.44 | 62.1 | 1.34 | 34.1 |
| G25200-0606 | 6G-6FSX | 7100-11915 | 3/8 | 9.5 | 5/8–18 | 5/8 | 3/4 | 2.44 | 62.1 | 1.35 | 34.2 |
| G25200-0608 | 6G-8FSX | 7100-11925 | 3/8 | 9.5 | 3/4–16 | 11/16 | 7/8 | 2.48 | 63.1 | 1.38 | 35.1 |
| G25200-0808 | 8G-8FSX | 7100-01935 | 1/2 | 12.7 | 3/4–16 | 13/16 | 7/8 | 2.82 | 71.6 | 1.34 | 34.1 |
| G25200-0810 | 8G-10FSX | 7100-01945 | 1/2 | 12.7 | 7/8–14 | 13/16 | 1 1/16 | 2.99 | 75.9 | 1.51 | 38.4 |
| G25200-1212 | 12G-12FSX | 7100-01955 | 3/4 | 19.1 | 1 1/16–14 | 1 1/16 | 1 1/4 | 3.68 | 93.5 | 1.67 | 42.5 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Female SAE 45° Flare Swivel - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G25202-0404 | 4G-4FSX45 | 7100-11965 | 1/4 | 6.4 | 7/16–20 | 1 9/16 | .33 | 8.4 | 2.34 | 59.5 | 1.32 | 33.5 |
| G25202-0405 | 4G-5FSX45-009 | 7100-01965 | 1/4 | 6.4 | 1/2–20 | 5/8 | .36 | 9.1 | 2.63 | 66.9 | 1.61 | 40.9 |
| G25202-0606 | 6G-6FSX45 | 7100-11995 | 3/8 | 9.5 | 5/8–18 | 3/4 | .39 | 10.0 | 2.74 | 69.5 | 1.64 | 41.6 |
| G25202-0608 | 6G-8FSX45-014 | 7100-02035 | 3/8 | 9.5 | 3/4–16 | 7/8 | .55 | 14.0 | 3.46 | 87.8 | 2.36 | 59.9 |
| G25202-0808 | 8G-8FSX45 | 7100-02015 | 1/2 | 12.7 | 3/4–16 | 7/8 | .55 | 14.0 | 3.31 | 84.0 | 1.83 | 46.5 |
| G25202-0810 | 8G-10FSX45-016 | 7100-02055 | 1/2 | 12.7 | 7/8–14 | 1 | .63 | 16.0 | 3.67 | 93.1 | 2.19 | 55.6 |
| G25202-1212 | 12G-12FSX45 | 7100-02045 | 3/4 | 19.1 | 1 1/16–14 | 1 1/4 | .78 | 19.8 | 4.37 | 111.0 | 2.36 | 60.0 |

# Female SAE 45° Flare Swivel - 90° Bent Tube









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G25205-0404 | 4G-4FSX90 | 7100-12055 | 1/4 | 6.4 | 7/16–20 | 9/16 | 1.24 | 31.5 | 2.05 | 52.0 | 1.02 | 26.0 |
| G25205-0405 | 4G-5FSX90-046 | 7100-01985 | 1/4 | 6.4 | 1/2–20 | 5/8 | 1.80 | 45.7 | 2.47 | 62.8 | 1.45 | 36.8 |
| G25204-0506 | 5G-6FSX90-022 | 7100-02005 | 5/16 | 7.9 | 5/8–18 | 3/4 | .85 | 21.6 | 2.77 | 70.4 | 1.67 | 42.4 |
| G25205-0606 | 6G-6FSX90 | 7100-12105 | 3/8 | 9.5 | 5/8–18 | 3/4 | 1.52 | 38.5 | 2.36 | 60.0 | 1.26 | 32.1 |
| G25206-0606 | 6G-6FSX90-055 | 7100-01995 | 3/8 | 9.5 | 5/8–18 | 3/4 | 2.18 | 55.4 | 2.83 | 71.8 | 1.73 | 43.9 |
| G25205-0608 | 6G-8FSX90 | 7100-02125 | 3/8 | 9.5 | 3/4–16 | 7/8 | 1.75 | 44.5 | 2.50 | 63.5 | 1.40 | 35.6 |
| G25205-0808 | 8G-8FSX90 | 7100-02135 | 1/2 | 12.7 | 3/4–16 | 7/8 | 1.75 | 44.5 | 2.93 | 74.5 | 1.46 | 37.0 |
| G25204-0810 | 8G-10FSX90-031 | 7100-02065 | 1/2 | 12.7 | 7/8–14 | 1 | 1.23 | 31.2 | 3.29 | 83.5 | 1.81 | 46.0 |
| G25205-1212 | 12G-12FSX90 | 7100-02185 | 3/4 | 19.1 | 1 1/16–14 | 1 1/4 | 2.78 | 70.6 | 3.94 | 100.0 | 1.93 | 49.0 |

# Male Flat-Face O-Ring


SAE J1453 Captive O–Ring Groove for Improved O–Ring Retention.





| Part No. | Descr. | Prod. No. | ⊖ | | ⦚ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G25225-0404 | 4G-4MFFOR | 7104-16045 | 1/4 | 6.4 | 9/16–18 | 17 | 2.07 | 52.5 | 1.04 | 26.5 |
| G25225-0406 | 4G-6MFFOR | 7104-16055 | 1/4 | 6.4 | 11/16–16 | 19 | 2.13 | 54.0 | 1.10 | 28.0 |
| G25225-0506 | 5G-6MFFOR | 7104-16065 | 5/16 | 7.9 | 11/16–16 | 19 | 2.20 | 56.0 | 1.10 | 28.0 |
| G25225-0606 | 6G-6MFFOR | 7104-16075 | 3/8 | 9.5 | 11/16–16 | 19 | 2.20 | 56.0 | 1.11 | 28.1 |
| G25225-0608 | 6G-8MFFOR | 7104-16085 | 3/8 | 9.5 | 13/16–16 | 22 | 2.32 | 59.0 | 1.22 | 31.1 |
| G25225-0610 | 6G-10MFFOR | 7104-16095 | 3/8 | 9.5 | 1–14 | 27 | 2.52 | 64.0 | 1.42 | 36.1 |
| G25225-0808 | 8G-8MFFOR | 7104-16115 | 1/2 | 12.7 | 13/16–16 | 22 | 2.69 | 68.2 | 1.21 | 30.7 |
| G25225-0810 | 8G-10MFFOR | 7104-16125 | 1/2 | 12.7 | 1–14 | 27 | 2.87 | 73.0 | 1.40 | 35.5 |
| G25225-0812 | 8G-12MFFOR | 7104-16135 | 1/2 | 12.7 | 1 3/16–12 | 32 | 3.01 | 76.5 | 1.54 | 39.0 |
| G25225-1010 | 10G-10MFFOR | 7104-16155 | 5/8 | 15.9 | 1–14 | 27 | 2.87 | 73.0 | 1.40 | 35.5 |
| G25225-1012 | 10G-12MFFOR | 7104-16165 | 5/8 | 15.9 | 1 3/16–12 | 32 | 3.03 | 77.0 | 1.56 | 39.5 |
| G25225-1212 | 12G-12MFFOR | 7104-16185 | 3/4 | 19.1 | 1 3/16–12 | 32 | 3.54 | 90.0 | 1.54 | 39.0 |
| G25225-1216 | 12G-16MFFOR | 7104-16195 | 3/4 | 19.1 | 1 7/16–12 | 41 | 3.74 | 95.0 | 1.73 | 44.0 |
| G25225-1616 | 16G-16MFFOR | 7104-16215 | 1 | 25.4 | 1 7/16–12 | 41 | 4.02 | 102.0 | 1.78 | 45.2 |
| G25225-1620 | 16G-20MFFOR | 7104-16225 | 1 | 25.4 | 1 11/16–12 | 46 | 4.13 | 105.0 | 1.90 | 48.2 |
| G25225-2020 | 20G-20MFFOR | 7104-16245 | 1 1/4 | 31.8 | 1 11/16–12 | 46 | 4.29 | 109.0 | 1.97 | 50.0 |

# Male Flat-Face O-Ring Bulk Head Long Nose









| Part No. | Descr. | Prod. No. | ⊖ | | ⦚ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G25226-0606 | 6G-6MFFORBKHDLN | 7104-17075 | 3/8 | 9.5 | 11/16–16 | 27 | 27 | 3.07 | 78.1 | 1.98 | 50.2 |
| G25226-0808 | 8G-8MFFORBKHDLN | 7104-17115 | 1/2 | 12.7 | 13/16–16 | 30 | 30 | 3.55 | 90.2 | 2.07 | 52.7 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Male Flat-Face O-Ring Bulk Head





| Part No. | Descr. | Prod. No. | ⟷ | | ≡ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G25228-0404 | 4G-4MFFORBKHD | 7104-17295 | 1/4 | 6.4 | 9/16–18 | 22 | 22 | 2.80 | 71.1 | 1.78 | 45.2 |
| G25228-0606 | 6G-6MFFORBKHD | 7104-17325 | 3/8 | 9.5 | 11/16–16 | 27 | 27 | 3.07 | 78.1 | 1.98 | 50.3 |


# Female Flat-Face O-Ring Swivel





| Part No. | Descr. | Prod. No. | ⟷ | | ≡ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G25230-0404 | 4G-4FFORX | 7104-18045 | 1/4 | 6.4 | 9/16–18 | 15 | 17 | 2.07 | 52.7 | 1.05 | 26.7 |
| G25230-0406 | 4G-6FFORX | 7104-18055 | 1/4 | 6.4 | 11/16–16 | 15 | 22 | 2.01 | 51.1 | .99 | 25.1 |
| G25230-0408 | 4G-8FFORX | 7104-18075 | 1/4 | 6.4 | 13/16–16 | 15 | 24 | 1.99 | 50.5 | .96 | 24.5 |
| G25230-0506 | 5G-6FFORX | 7104-19505 | 5/16 | 7.9 | 11/16–16 | 17 | 22 | 2.42 | 61.5 | 1.32 | 33.5 |
| G25230-0604 | 6G-4FFORX | 7104-19085 | 3/8 | 9.5 | 9/16–18 | 17 | 17 | 3.08 | 78.3 | 1.98 | 50.3 |
| G25230-0606 | 6G-6FFORX | 7104-18095 | 3/8 | 9.5 | 11/16–16 | 18 | 22 | 2.27 | 57.7 | 1.14 | 28.9 |
| G25230-0608 | 6G-8FFORX | 7104-18105 | 3/8 | 9.5 | 13/16–16 | 18 | 24 | 2.26 | 57.4 | 1.13 | 28.6 |
| G25230-0610 | 6G-10FFORX | 7104-18115 | 3/8 | 9.5 | 1–14 | 18 | 30 | 2.15 | 54.7 | 1.02 | 25.9 |
| G25230-0806 | 8G-6FFORX | 7104-19145 | 1/2 | 12.7 | 11/16–16 | 22 | 22 | 3.78 | 95.9 | 2.30 | 58.4 |
| G25230-0808 | 8G-8FFORX | 7104-18155 | 1/2 | 12.7 | 13/16–16 | 22 | 24 | 2.62 | 66.5 | 1.23 | 31.3 |
| G25230-0810 | 8G-10FFORX | 7104-18165 | 1/2 | 12.7 | 1–14 | 22 | 30 | 2.76 | 70.0 | 1.37 | 34.8 |
| G25230-0812 | 8G-12FFORX | 7104-18175 | 1/2 | 12.7 | 1 3/16–12 | 22 | 36 | 2.81 | 71.5 | 1.43 | 36.3 |
| G25230-1008 | 10G-8FFORX | 7104-19195 | 5/8 | 15.9 | 13/16–16 | 24 | 24 | 3.83 | 97.2 | 2.35 | 59.7 |
| G25230-1010 | 10G-10FFORX | 7104-18205 | 5/8 | 15.9 | 1–14 | 24 | 30 | 2.99 | 76.0 | 1.52 | 38.5 |
| G25230-1012 | 10G-12FFORX | 7104-18215 | 5/8 | 15.9 | 1 3/16–12 | 24 | 36 | 3.03 | 77.0 | 1.56 | 39.5 |
| G25230-1210 | 12G-10FFORX | 7104-19245 | 3/4 | 19.1 | 1–14 | 30 | 30 | 3.74 | 95.1 | 1.74 | 44.1 |
| G25230-1212 | 12G-12FFORX | 7104-18255 | 3/4 | 19.1 | 1 3/16–12 | 30 | 36 | 3.65 | 92.8 | 1.65 | 41.8 |
| G25230-1216 | 12G-16FFORX | 7104-18265 | 3/4 | 19.1 | 1 7/16–12 | 30 | 41 | 3.48 | 88.3 | 1.47 | 37.3 |
| G25230-1612 | 16G-12FFORX | 7104-19295 | 1 | 25.4 | 1 3/16–12 | 36 | 36 | 5.58 | 141.8 | 3.35 | 85.0 |
| G25230-1616 | 16G-16FFORX | 7104-18305 | 1 | 25.4 | 1 7/16–12 | 36 | 41 | 4.09 | 104.0 | 1.86 | 47.2 |
| G25230-1620 | 16G-20FFORX | 7104-18315 | 1 | 25.4 | 1 11/16–12 | 36 | 50 | 4.06 | 103.0 | 1.82 | 46.2 |
| G25230-2020 | 20G-20FFORX | 7104-18355 | 1 1/4 | 31.8 | 1 11/16–12 | 41 | 50 | 4.29 | 109.0 | 1.97 | 50.0 |
| G25230-2024 | 20G-24FFORX | 7104-18385 | 1 1/4 | 31.8 | 2–12 | 41 | 60 | 4.09 | 104.0 | 1.77 | 45.0 |


# Female Flat-Face O-Ring Swivel - 30° Bent Tube





| Part No. | Descr. | Prod. No. | ⟷ | | ⦚ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25233-0810 | 8G-10FFORX30-010 | 7104-07025 | 1/2 | 12.7 | 1–14 | 30 | .38 | 9.7 | 3.65 | 92.7 | 2.18 | 55.3 |

# Female Flat-Face O-Ring Swivel - 45° Bent Tube









| Part No. | Descr. | Prod. No. | ⟷ | | ⦚ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25235-0404 | 4G-4FFORX45S | 7104-22045 | 1/4 | 6.4 | 9/16–18 | 17 | .39 | 10.0 | 2.57 | 65.2 | 1.54 | 39.2 |
| G25235-0406 | 4G-6FFORX45S | 7104-22055 | 1/4 | 6.4 | 11/16–16 | 22 | .43 | 11.0 | 2.70 | 68.5 | 1.67 | 42.5 |
| G25235-0506 | 5G-6FFORX45S | 7104-22335 | 5/16 | 7.9 | 11/16–16 | 22 | .43 | 11.0 | 2.73 | 69.4 | 1.63 | 41.4 |
| G25235-0604 | 6G-4FFORX45S | 7104-22075 | 3/8 | 9.5 | 9/16–18 | 17 | .39 | 10.0 | 2.60 | 66.1 | 1.50 | 38.1 |
| G25235-0606 | 6G-6FFORX45S | 7104-22085 | 3/8 | 9.5 | 11/16–16 | 22 | .43 | 11.0 | 2.75 | 69.8 | 1.65 | 41.9 |
| G25235-0608 | 6G-8FFORX45S | 7104-22095 | 3/8 | 9.5 | 13/16–16 | 24 | .59 | 15.0 | 3.35 | 85.2 | 2.26 | 57.3 |
| G25234-0806 | 8G-6FFORX45S | 7104-22125 | 1/2 | 12.7 | 11/16–16 | 22 | .43 | 11.0 | 3.57 | 90.7 | 2.09 | 53.2 |
| G25235-0808 | 8G-8FFORX45S | 7104-22135 | 1/2 | 12.7 | 13/16–16 | 24 | .59 | 15.0 | 3.50 | 89.0 | 2.03 | 51.6 |
| G25235-0810 | 8G-10FFORX45S | 7104-22145 | 1/2 | 12.7 | 1–14 | 30 | .63 | 16.0 | 3.98 | 101.0 | 2.50 | 63.5 |
| G25235-0812 | 8G-12FFORX45S | 7104-22155 | 1/2 | 12.7 | 1 3/16–12 | 36 | .83 | 21.0 | 4.34 | 110.3 | 2.87 | 72.8 |
| G25235-1008 | 10G-8FFORX45S | 7104-22165 | 5/8 | 15.9 | 13/16–16 | 24 | .59 | 15.0 | 3.81 | 96.8 | 2.33 | 59.3 |
| G25235-1010 | 10G-10FFORX45S | 7104-22175 | 5/8 | 15.9 | 1–14 | 30 | .63 | 16.0 | 3.96 | 100.5 | 2.48 | 63.0 |
| G25235-1012 | 10G-12FFORX45S | 7104-22185 | 5/8 | 15.9 | 1 3/16–12 | 36 | .83 | 21.0 | 4.17 | 105.9 | 2.69 | 68.4 |
| G25235-1210 | 12G-10FFORX45S | 7104-22215 | 3/4 | 19.1 | 1–14 | 30 | .63 | 16.0 | 4.45 | 113.0 | 2.44 | 62.0 |
| G25235-1212 | 12G-12FFORX45S | 7104-22225 | 3/4 | 19.1 | 1 3/16–12 | 36 | .83 | 21.0 | 4.66 | 118.4 | 2.65 | 67.4 |
| G25235-1216 | 12G-16FFORX45S | 7104-22235 | 3/4 | 19.1 | 1 7/16–12 | 41 | .94 | 24.0 | 4.80 | 122.0 | 2.80 | 71.0 |
| G25235-1612 | 16G-12FFORX45S | 7104-22255 | 1 | 25.4 | 1 3/16–12 | 36 | .83 | 21.0 | 5.33 | 135.5 | 2.98 | 75.7 |
| G25235-1616 | 16G-16FFORX45S | 7104-22265 | 1 | 25.4 | 1 7/16–12 | 41 | .94 | 24.0 | 5.78 | 146.9 | 3.55 | 90.1 |
| G25235-2020 | 20G-20FFORX45S | 7104-22295 | 1 1/4 | 31.8 | 1 11/16–12 | 50 | .98 | 25.0 | 6.22 | 158.0 | 3.90 | 99.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Female Flat-Face O-Ring Swivel - 67 1/2° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | ≋ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G25238-0808 | 8G-8FFORX67-022 | 7104-07015 | 1/2 | 12.7 | 13/16–16 | .94 | .87 | 22.1 | 3.25 | 82.5 | 1.77 | 45.0 |

# Female Flat-Face O-Ring Swivel - 90° Bent Tube








| Part No. | Descr. | Prod. No. | ⊖ | | ≋ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25239-0404 | 4G-4FFORX90S | 7104-24045 | 1/4 | 6.4 | 9/16–18 | 17 | .83 | 21.0 | 2.37 | 60.2 | 1.35 | 34.2 |
| G25240-0404 | 4G-4FFORX90M | 7104-24055 | 1/4 | 6.4 | 9/16–18 | 17 | 1.26 | 32.0 | 2.21 | 56.2 | 1.19 | 30.2 |
| G25241-0404 | 4G-4FFORX90L | 7104-24065 | 1/4 | 6.4 | 9/16–18 | 17 | 1.81 | 46.0 | 2.21 | 56.2 | 1.19 | 30.2 |
| G25239-0406 | 4G-6FFORX90S | 7104-24095 | 1/4 | 6.4 | 11/16–16 | 22 | .91 | 23.0 | 2.50 | 63.4 | 1.47 | 37.4 |
| G25240-0406 | 4G-6FFORX90M | 7104-24105 | 1/4 | 6.4 | 11/16–16 | 22 | 1.50 | 38.0 | 2.50 | 63.4 | 1.47 | 37.4 |
| G25241-0406 | 4G-6FFORX90L | 7104-24115 | 1/4 | 6.4 | 11/16–16 | 22 | 2.13 | 54.0 | 2.43 | 61.6 | 1.40 | 35.6 |
| G25239-0408 | 4G-8FFORX90S | 7104-24145 | 1/4 | 6.4 | 13/16–16 | 24 | 1.14 | 29.0 | 2.83 | 72.0 | 1.81 | 46.0 |
| G25241-0408 | 4G-8FFORX90L | 7104-24165 | 1/4 | 6.4 | 13/16–16 | 24 | 2.52 | 64.0 | 2.64 | 67.1 | 1.62 | 41.1 |
| G25239-0506 | 5G-6FFORX90S | 7104-24955 | 5/16 | 7.9 | 11/16–16 | 22 | .91 | 23.0 | 2.83 | 72.0 | 1.73 | 44.0 |
| G25239-0604 | 6G-4FFORX90S | 7104-24195 | 3/8 | 9.5 | 9/16–18 | 17 | .83 | 21.0 | 2.42 | 61.4 | 1.32 | 33.6 |
| G25239-0606 | 6G-6FFORX90S | 7104-24245 | 3/8 | 9.5 | 11/16–16 | 22 | .91 | 23.0 | 2.85 | 72.5 | 1.76 | 44.6 |
| G25240-0606 | 6G-6FFORX90M | 7104-24255 | 3/8 | 9.5 | 11/16–16 | 22 | 1.50 | 38.0 | 2.50 | 63.6 | 1.41 | 35.7 |
| G25241-0606 | 6G-6FFORX90L | 7104-24265 | 3/8 | 9.5 | 11/16–16 | 22 | 2.13 | 54.0 | 2.73 | 69.3 | 1.63 | 41.4 |
| G25239-0608 | 6G-8FFORX90S | 7104-24295 | 3/8 | 9.5 | 13/16–16 | 24 | 1.14 | 29.0 | 2.87 | 73.0 | 1.78 | 45.1 |
| G25240-0608 | 6G-8FFORX90M | 7104-24305 | 3/8 | 9.5 | 13/16–16 | 24 | 1.61 | 41.0 | 2.70 | 68.5 | 1.60 | 40.6 |
| G25241-0608 | 6G-8FFORX90L | 7104-24315 | 3/8 | 9.5 | 13/16–16 | 24 | 2.52 | 64.0 | 2.72 | 69.0 | 1.62 | 41.1 |
| G25239-0806 | 8G-6FFORX90S | 7104-24345 | 1/2 | 12.7 | 11/16–16 | 22 | .91 | 23.0 | 3.29 | 83.5 | 1.81 | 46.0 |
| G25241-0806 | 8G-6FFORX90L | 7104-24365 | 1/2 | 12.7 | 11/16–16 | 22 | 2.13 | 54.0 | 3.16 | 80.3 | 1.69 | 42.8 |
| G25239-0808 | 8G-8FFORX90S | 7104-24395 | 1/2 | 12.7 | 13/16–16 | 24 | 1.14 | 29.0 | 3.30 | 83.9 | 1.83 | 46.5 |
| G25240-0808 | 8G-8FFORX90M | 7104-24405 | 1/2 | 12.7 | 13/16–16 | 24 | 1.61 | 41.0 | 3.30 | 83.9 | 1.83 | 46.5 |
| G25241-0808 | 8G-8FFORX90L | 7104-24415 | 1/2 | 12.7 | 13/16–16 | 24 | 2.52 | 64.0 | 3.30 | 83.9 | 1.83 | 46.5 |
| G25239-0810 | 8G-10FFORX90S | 7104-24445 | 1/2 | 12.7 | 1–14 | 30 | 1.26 | 32.0 | 3.66 | 92.9 | 2.18 | 55.4 |

## Female Flat-Face O-Ring Swivel - 90° Bent Tube - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25240-0810 | 8G-10FFORX90M | 7104-24455 | 1/2 | 12.7 | 1–14 | 30 | 1.85 | 47.0 | 3.67 | 93.2 | 2.19 | 55.7 |
| G25241-0810 | 8G-10FFORX90L | 7104-24465 | 1/2 | 12.7 | 1–14 | 30 | 2.76 | 70.0 | 3.57 | 90.6 | 2.09 | 53.1 |
| G25239-0812 | 8G-12FFORX90S | 7104-24475 | 1/2 | 12.7 | 1 3/16–12 | 36 | 1.89 | 48.0 | 4.05 | 102.9 | 2.57 | 65.4 |
| G25239-1008 | 10G-8FFORX90S | 7104-24495 | 5/8 | 15.9 | 13/16–16 | 24 | 1.14 | 29.0 | 3.64 | 92.4 | 2.16 | 54.9 |
| G25241-1008 | 10G-8FFORX90L | 7104-24515 | 5/8 | 15.9 | 13/16–16 | 24 | 2.52 | 64.0 | 3.64 | 92.4 | 2.16 | 54.9 |
| G25239-1010 | 10G-10FFORX90S | 7104-24545 | 5/8 | 15.9 | 1–14 | 30 | 1.26 | 32.0 | 3.64 | 92.5 | 2.17 | 55.0 |
| G25240-1010 | 10G-10FFORX90M | 7104-24555 | 5/8 | 15.9 | 1–14 | 30 | 1.85 | 47.0 | 3.65 | 92.8 | 2.18 | 55.3 |
| G25241-1010 | 10G-10FFORX90L | 7104-24565 | 5/8 | 15.9 | 1–14 | 30 | 2.76 | 70.0 | 3.55 | 90.2 | 2.07 | 52.7 |
| G25239-1012 | 10G-12FFORX90S | 7104-24595 | 5/8 | 15.9 | 1 3/16–12 | 36 | 1.89 | 48.0 | 3.79 | 96.3 | 2.31 | 58.8 |
| G25239-1210 | 12G-10FFORX90S | 7104-24635 | 3/4 | 19.1 | 1–14 | 30 | 1.26 | 32.0 | 4.09 | 104.0 | 2.09 | 53.0 |
| G25239-1212 | 12G-12FFORX90S | 7104-24645 | 3/4 | 19.1 | 1 3/16–12 | 36 | 1.89 | 48.0 | 4.28 | 108.8 | 2.28 | 57.8 |
| G25240-1212 | 12G-12FFORX90M | 7104-24655 | 3/4 | 19.1 | 1 3/16–12 | 36 | 2.28 | 58.0 | 4.29 | 109.0 | 2.28 | 58.0 |
| G25241-1212 | 12G-12FFORX90L | 7104-24665 | 3/4 | 19.1 | 1 3/16–12 | 36 | 3.78 | 96.0 | 4.65 | 118.2 | 2.65 | 67.2 |
| G25239-1216 | 12G-16FFORX90S | 7104-24695 | 3/4 | 19.1 | 1 7/16–12 | 41 | 2.20 | 56.0 | 5.06 | 128.5 | 3.05 | 77.5 |
| G25239-1612 | 16G-12FFORX90S | 7104-24735 | 1 | 25.4 | 1 3/16–12 | 36 | 1.89 | 48.0 | 5.09 | 129.4 | 2.86 | 72.6 |
| G25239-1616 | 16G-16FFORX90S | 7104-24745 | 1 | 25.4 | 1 7/16–12 | 41 | 2.20 | 56.0 | 5.11 | 129.9 | 2.88 | 73.1 |
| G25240-1616 | 16G-16FFORX90M | 7104-24755 | 1 | 25.4 | 1 7/16–12 | 41 | 2.80 | 71.0 | 5.11 | 129.9 | 2.88 | 73.1 |
| G25241-1616 | 16G-16FFORX90L | 7104-24765 | 1 | 25.4 | 1 7/16–12 | 41 | 4.49 | 114.0 | 5.11 | 129.9 | 2.88 | 73.1 |
| G25239-1620 | 16G-20FFORX90S | 7104-24905 | 1 | 25.4 | 1 11/16–12 | 50 | 2.52 | 64.0 | 5.11 | 129.9 | 2.88 | 73.1 |
| G25240-1620 | 16G-20FFORX90M | 7104-24915 | 1 | 25.4 | 1 11/16–12 | 50 | 3.07 | 78.0 | 6.14 | 156.0 | 3.91 | 99.2 |
| G25239-2020 | 20G-20FFORX90S | 7104-24795 | 1 1/4 | 31.8 | 1 11/16–12 | 50 | 2.52 | 64.0 | 5.91 | 150.0 | 3.58 | 91.0 |
| G25240-2020 | 20G-20FFORX90M | 7104-24805 | 1 1/4 | 31.8 | 1 11/16–12 | 50 | 3.07 | 78.0 | 5.51 | 140.0 | 3.19 | 81.0 |
| G25241-2020 | 20G-20FFORX90L | 7104-24815 | 1 1/4 | 31.8 | 1 11/16–12 | 50 | 5.08 | 129.0 | 5.51 | 140.0 | 3.19 | 81.0 |

## Code 61 O-Ring Flange





| Part No. | Descr. | Prod. No. | ⟷ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25300-0808 | 8G-8FL | 7103-25055 | 1/2 | 12.7 | 1.19 | 30.2 | 3.15 | 80.0 | 1.67 | 42.5 | .27 | 6.9 |
| G25300-0812 | 8G-12FL | 7103-25105 | 1/2 | 12.7 | 1.50 | 38.1 | 3.15 | 80.0 | 1.67 | 42.5 | .27 | 6.9 |
| G25300-1212 | 12G-12FL | 7103-25205 | 3/4 | 19.1 | 1.50 | 38.1 | 3.86 | 98.0 | 1.85 | 47.0 | .27 | 6.9 |
| G25300-1216 | 12G-16FL | 7103-25255 | 3/4 | 19.1 | 1.75 | 44.5 | 3.50 | 88.8 | 1.49 | 37.8 | .32 | 8.1 |
| G25300-1612 | 16G-12FL | 7103-25295 | 1 | 25.4 | 1.50 | 38.1 | 5.04 | 128.0 | 2.80 | 71.2 | .27 | 6.9 |
| G25300-1616 | 16G-16FL | 7103-25305 | 1 | 25.4 | 1.75 | 44.5 | 4.13 | 105.0 | 1.90 | 48.2 | .32 | 8.1 |
| G25300-1620 | 16G-20FL | 7103-25355 | 1 | 25.4 | 2.00 | 50.8 | 4.13 | 105.0 | 1.90 | 48.2 | .32 | 8.1 |
| G25300-1624 | 16G-24FL | 7100-03875 | 1 | 25.4 | 2.38 | 60.5 | 3.78 | 96.0 | 1.54 | 39.2 | .32 | 8.1 |
| G25300-2020 | 20G-20FL | 7103-25405 | 1 1/4 | 31.8 | 2.00 | 50.8 | 4.43 | 112.5 | 2.11 | 53.5 | .32 | 8.1 |
| G25300-2024 | 20G-24FL | 7103-25455 | 1 1/4 | 31.8 | 2.38 | 60.5 | 4.63 | 117.5 | 2.30 | 58.5 | .32 | 8.1 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Komatsu O-Ring Flange - Straight





| Part No. | Descr. | Prod. No. | ⟷ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25300-0810 | 8G-10FLK | 7100-03805 | 1/2 | 12.7 | 1.35 | 34.3 | 3.15 | 80.0 | 1.67 | 42.5 | .27 | 6.9 |
| G25300-1010 | 10G-10FLK | 7100-03825 | 5/8 | 15.9 | 1.35 | 34.3 | 4.69 | 119.0 | 3.21 | 81.5 | .27 | 6.9 |

# Code 61 O-Ring Flange - 22 1/2° Bent Tube




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25302-1212 | 12G-12FL22M | 7103-26155 | 3/4 | 19.1 | 1.50 | 38.1 | .43 | 11.0 | 4.76 | 121.0 | 2.76 | 70.0 | .27 | 6.9 |
| G25302-1216 | 12G-16FL22M-014 | 7100-03955 | 3/4 | 19.1 | 1.75 | 44.5 | .55 | 14.0 | 4.76 | 121.0 | 2.76 | 70.0 | .32 | 8.1 |
| G25302-1616 | 16G-16FL22M | 7103-26255 | 1 | 25.4 | 1.75 | 44.5 | .55 | 14.0 | 5.61 | 142.5 | 3.37 | 85.7 | .32 | 8.1 |
| G25302-2020 | 20G-20FL22M | 7103-26355 | 1 1/4 | 31.8 | 2.00 | 50.8 | .59 | 15.0 | 6.00 | 152.5 | 3.68 | 93.5 | .32 | 8.1 |

# Code 61 O-Ring Flange - 30° Bent Tube





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25304-1212 | 12G-12FL30M | 7103-26655 | 3/4 | 19.1 | 1.50 | 38.1 | .63 | 16.0 | 4.70 | 119.5 | 2.70 | 68.5 | .27 | 6.9 |
| G25304-1216 | 12G-16FL30M | 7100-04045 | 3/4 | 19.1 | 1.75 | 44.5 | .75 | 19.1 | 4.88 | 124.0 | 2.87 | 73.0 | .32 | 8.1 |
| G25304-1616 | 16G-16FL30M | 7103-26755 | 1 | 25.4 | 1.75 | 44.5 | .75 | 19.1 | 5.69 | 144.5 | 3.45 | 87.7 | .32 | 8.1 |
| G25304-1620 | 16G-20FL30M | 7103-26805 | 1 | 25.4 | 2.00 | 50.8 | .87 | 22.1 | 5.89 | 149.5 | 3.65 | 92.7 | .32 | 8.1 |

## Code 61 O-Ring Flange - 30° Bent Tube - Continued


| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25304-2020 | 20G-20FL30S | 7103-26845 | 1 1/4 | 31.8 | 2.00 | 50.8 | .79 | 20.1 | 6.04 | 153.4 | 3.72 | 94.4 | .32 | 8.1 |

## Code 61 O-Ring Flange - 45° Bent Tube




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25307-0808 | 8G-8FL45M | 7103-27085 | 1/2 | 12.7 | 1.19 | 30.2 | .75 | 19.1 | 3.85 | 97.8 | 2.37 | 60.3 | .27 | 6.9 |
| G25307-0812 | 8G-12FL45M | 7103-27165 | 1/2 | 12.7 | 1.50 | 38.1 | 1.02 | 26.0 | 4.13 | 104.8 | 2.65 | 67.3 | .27 | 6.9 |
| G25307-1012 | 10G-12FL45M | 7103-27205 | 5/8 | 15.9 | 1.50 | 38.1 | 1.02 | 26.0 | 4.43 | 112.6 | 2.96 | 75.1 | .27 | 6.9 |
| G25307-1212 | 12G-12FL45M | 7103-27245 | 3/4 | 19.1 | 1.50 | 38.1 | 1.02 | 26.0 | 4.82 | 122.5 | 2.81 | 71.5 | .27 | 6.9 |
| G25306-1216 | 12G-16FL45S | 7103-27315 | 3/4 | 19.1 | 1.75 | 44.5 | 1.10 | 28.0 | 4.90 | 124.5 | 2.89 | 73.5 | .32 | 8.1 |
| G25306-1616 | 16G-16FL45S | 7103-27395 | 1 | 25.4 | 1.75 | 44.5 | 1.10 | 28.0 | 5.61 | 142.5 | 3.37 | 85.7 | .32 | 8.1 |
| G25306-1620 | 16G-20FL45S | 7103-27475 | 1 | 25.4 | 2.00 | 50.8 | 1.26 | 32.0 | 5.87 | 149.0 | 3.63 | 92.2 | .32 | 8.1 |
| G25307-1624 | 16G-24FL45 | 7100-07185 | 1 | 25.4 | 2.38 | 60.5 | 1.06 | 26.9 | 5.30 | 134.5 | 3.06 | 77.7 | .32 | 8.1 |
| G25306-2020 | 20G-20FL45S | 7103-27555 | 1 1/4 | 31.8 | 2.00 | 50.8 | 1.26 | 32.0 | 6.18 | 157.0 | 3.86 | 98.0 | .32 | 8.1 |


## Komatsu O-Ring Flange - 45° Bent Tube




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25307-1010 | 10G-10FLK45 | 7100-04155 | 5/8 | 15.9 | 1.35 | 34.3 | 1.02 | 26.0 | 4.19 | 106.5 | 2.72 | 69.0 | .27 | 6.9 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Code 61 O-Ring Flange - 60° Bent Tube





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25309-1212 | 12G-12FL60M | 7103-28155 | 3/4 | 19.1 | 1.50 | 38.1 | 1.46 | 37.0 | 5.04 | 128.0 | 3.03 | 77.0 | .27 | 6.9 |
| G25309-1216 | 12G-16FL60M | 7103-28205 | 3/4 | 19.1 | 1.75 | 44.5 | 1.73 | 44.0 | 5.20 | 132.0 | 3.19 | 81.0 | .32 | 8.1 |
| G25309-1616 | 16G-16FL60M | 7103-28255 | 1 | 25.4 | 1.75 | 44.5 | 1.73 | 44.0 | 5.85 | 148.5 | 3.61 | 91.7 | .32 | 8.1 |
| G25308-2020 | 20G-20FL60S | 7103-28345 | 1 1/4 | 31.8 | 2.00 | 50.8 | 1.77 | 45.0 | 6.22 | 158.0 | 3.90 | 99.0 | .32 | 8.1 |

# Code 61 O-Ring Flange - 67 1/2° Bent Tube





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25311-1212 | 12G-12FL67M | 7100-04355 | 3/4 | 19.1 | 1.50 | 38.1 | 1.65 | 42.0 | 4.65 | 118.0 | 2.64 | 67.0 | .27 | 6.9 |
| G25311-2020 | 20G-20FL67S | 7100-04335 | 1 1/4 | 31.8 | 2.00 | 50.8 | 2.01 | 51.0 | 5.92 | 150.4 | 3.60 | 91.4 | .32 | 8.1 |

# Code 61 O-Ring Flange - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25315-0808 | 8G-8FL90M | 7103-29115 | 1/2 | 12.7 | 1.19 | 30.2 | 1.57 | 40.0 | 3.59 | 91.2 | 2.11 | 53.7 | .27 | 6.9 |
| G25315-0812 | 8G-12FL90M | 7103-29235 | 1/2 | 12.7 | 1.50 | 38.1 | 2.28 | 58.0 | 3.60 | 91.5 | 2.13 | 54.0 | .27 | 6.9 |
| G25315-1012 | 10G-12FL90M | 7103-29415 | 5/8 | 15.9 | 1.50 | 38.1 | 2.28 | 58.0 | 3.94 | 100.0 | 2.46 | 62.5 | .27 | 6.9 |
| G25315-1212 | 12G-12FL90M | 7103-29535 | 3/4 | 19.1 | 1.50 | 38.1 | 2.28 | 58.0 | 4.54 | 115.3 | 2.53 | 64.3 | .27 | 6.9 |
| G25314-1216 | 12G-16FL90S | 7103-29585 | 3/4 | 19.1 | 1.75 | 44.5 | 2.40 | 61.0 | 4.72 | 119.8 | 2.71 | 68.8 | .32 | 8.1 |
| G25315-1612 | 16G-12FL90M | 7103-29655 | 1 | 25.4 | 1.50 | 38.1 | 2.28 | 58.0 | 5.09 | 129.3 | 2.85 | 72.5 | .27 | 6.9 |
| G25314-1616 | 16G-16FL90S | 7103-29705 | 1 | 25.4 | 1.75 | 44.5 | 2.40 | 61.0 | 5.48 | 139.3 | 3.25 | 82.5 | .32 | 8.1 |
| G25314-1620 | 16G-20FL90S | 7103-29765 | 1 | 25.4 | 2.00 | 50.8 | 2.68 | 68.0 | 5.48 | 139.3 | 3.25 | 82.5 | .32 | 8.1 |
| G25314-1624 | 16G-24FL90S-081 | 7100-04555 | 1 | 25.4 | 2.38 | 60.5 | 3.19 | 81.0 | 5.57 | 141.6 | 3.34 | 84.8 | .32 | 8.1 |
| G25314-2020 | 20G-20FL90S | 7103-29885 | 1 1/4 | 31.8 | 2.00 | 50.8 | 2.68 | 68.0 | 6.22 | 158.1 | 3.90 | 99.1 | .32 | 8.1 |
| G25315-2020 | 20G-20FL90M | 7103-29895 | 1 1/4 | 31.8 | 2.00 | 50.8 | 3.54 | 90.0 | 5.31 | 135.0 | 2.99 | 76.0 | .32 | 8.1 |
| G25316-2020 | 20G-20FL90-102 | 7100-04565 | 1 1/4 | 31.8 | 2.00 | 50.8 | 4.00 | 101.6 | 5.43 | 138.0 | 3.11 | 79.0 | .32 | 8.1 |
| G25314-2024 | 20G-24FL90S | 7103-29945 | 1 1/4 | 31.8 | 2.38 | 60.5 | 3.19 | 81.0 | 6.22 | 158.1 | 3.90 | 99.1 | .32 | 8.1 |

# Komatsu O-Ring Flange - 90° Bent Tube






| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25315-1010 | 10G-10FLK90 | 7100-04475 | 5/8 | 15.9 | 1.35 | 34.3 | 2.17 | 55.0 | 3.90 | 99.0 | 2.42 | 61.5 | .27 | 6.9 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# SAE Male Inverted Swivel





| Part No. | Descr. | Prod. No. | ⊖ | | ≋ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G25500-0403 | 4G-3MIX | 7100-16205 | 1/4 | 6.4 | 3/8–24 | 1/2 | 3/8 | 2.52 | 64.0 | 1.50 | 38.0 |
| G25500-0404 | 4G-4MIX | 7100-16225 | 1/4 | 6.4 | 7/16–24 | 1/2 | 7/16 | 2.52 | 63.9 | 1.49 | 37.9 |
| G25500-0405 | 4G-5MIX | 7100-16235 | 1/4 | 6.4 | 1/2–20 | 1/2 | 1/2 | 2.52 | 63.9 | 1.49 | 37.9 |
| G25500-0604 | 6G-4MIX | 7100-16185 | 3/8 | 9.5 | 7/16–24 | 5/8 | 7/16 | 2.63 | 66.9 | 1.54 | 39.0 |
| G25500-0605 | 6G-5MIX | 7100-16245 | 3/8 | 9.5 | 1/2–20 | 5/8 | 1/2 | 2.56 | 64.9 | 1.46 | 37.0 |
| G25500-0606 | 6G-6MIX | 7100-16255 | 3/8 | 9.5 | 5/8–18 | 5/8 | 5/8 | 2.75 | 69.9 | 1.65 | 42.0 |
| G25500-0607 | 6G-7MIX | 7100-16265 | 3/8 | 9.5 | 11/16–18 | 5/8 | 11/16 | 2.76 | 70.0 | 1.66 | 42.1 |
| G25500-0806 | 8G-6MIX | 7100-06275 | 1/2 | 12.7 | 5/8–18 | 13/16 | 5/8 | 3.13 | 79.5 | 1.65 | 42.0 |
| G25500-0808 | 8G-8MIX | 7100-06285 | 1/2 | 12.7 | 3/4–18 | 13/16 | 3/4 | 3.30 | 83.8 | 1.82 | 46.3 |
| G25500-1010 | 10G-10MIX | 7100-06295 | 5/8 | 15.9 | 7/8–18 | 15/16 | 7/8 | 3.92 | 99.5 | 2.44 | 62.0 |


# SAE Male Inverted Swivel - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | ≋ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G25502-0403 | 4G-3MIX45-018 | 7100-16275 | 1/4 | 6.4 | 3/8–24 | 3/8 | .69 | 17.5 | 2.67 | 67.9 | 1.65 | 41.9 |
| G25502-0404 | 4G-4MIX45-024 | 7100-16285 | 1/4 | 6.4 | 7/16–24 | 7/16 | .93 | 23.5 | 3.04 | 77.3 | 2.02 | 51.2 |
| G25502-0604 | 6G-4MIX45 | 7100-16305 | 3/8 | 9.5 | 7/16–24 | 7/16 | 1.00 | 25.4 | 3.17 | 80.5 | 2.07 | 52.6 |
| G25502-0605 | 6G-5MIX45 | 7100-16315 | 3/8 | 9.5 | 1/2–20 | 1/2 | 1.00 | 25.4 | 3.13 | 79.5 | 2.03 | 51.6 |
| G25502-0606 | 6G-6MIX45 | 7100-16325 | 3/8 | 9.5 | 5/8–18 | 5/8 | 1.00 | 25.4 | 3.32 | 84.3 | 2.22 | 56.4 |
| G25502-0607 | 6G-7MIX45 | 7100-16335 | 3/8 | 9.5 | 11/16–18 | 11/16 | 1.00 | 25.4 | 3.39 | 86.0 | 2.29 | 58.1 |
| G25502-0808 | 8G-8MIX45 | 7100-16345 | 1/2 | 12.7 | 3/4–18 | 3/4 | 1.14 | 29.0 | 4.17 | 106.0 | 2.70 | 68.5 |
| G25502-1010 | 10G-10MIX45 | 7100-16435 | 5/8 | 15.9 | 7/8–18 | 7/8 | 1.38 | 35.1 | 2.33 | 59.2 | 1.31 | 33.2 |

# SAE Male Inverted Swivel - 90° Bent Tube









| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | mm | " | mm | " | mm |
| G25504-0404 | 4G-4MIX90 | 7100-16355 | 1/4 | 6.4 | 7/16–24 | 7/16 | 1.38 | 35.1 | 2.33 | 59.2 | 1.31 | 33.2 |
| G25504-0405 | 4G-5MIX90 | 7100-16365 | 1/4 | 6.4 | 1/2–20 | 1/2 | 1.38 | 35.1 | 2.46 | 62.5 | 1.44 | 36.5 |
| G25504-0506 | 5G-6MIX90-035 | 7100-16385 | 5/16 | 7.9 | 5/8–18 | 5/8 | 1.38 | 35.1 | 2.78 | 70.5 | 1.67 | 42.5 |
| G25504-0604 | 6G-4MIX90 | 7100-16395 | 3/8 | 9.5 | 7/16–24 | 7/16 | 1.38 | 35.1 | 2.44 | 62.0 | 1.34 | 34.1 |
| G25504-0605 | 6G-5MIX90 | 7100-16405 | 3/8 | 9.5 | 1/2–20 | 1/2 | 1.38 | 35.1 | 2.50 | 63.5 | 1.40 | 35.6 |
| G25504-0606 | 6G-6MIX90 | 7100-16415 | 3/8 | 9.5 | 5/8–18 | 5/8 | 1.38 | 35.1 | 2.80 | 71.0 | 1.70 | 43.1 |
| G25504-0607 | 6G-7MIX90 | 7100-16425 | 3/8 | 9.5 | 11/16–18 | 11/16 | 1.38 | 35.1 | 2.80 | 71.0 | 1.70 | 43.1 |
| G25504-0808 | 8G-8MIX90 | 7100-06435 | 1/2 | 12.7 | 3/4–18 | 3/4 | 1.64 | 41.7 | 3.29 | 83.5 | 1.81 | 46.0 |
| G25504-1010 | 10G-10MIX90 | 7100-06335 | 5/8 | 15.9 | 7/8–18 | 7/8 | 1.81 | 46.0 | 3.89 | 98.7 | 2.41 | 61.3 |

# SAE Male Flareless Assembly

See Accessories for Individual Sleeves and Nuts.





| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | " | mm | " | mm |
| G25510-0404 | 4G-4MFA | 7100-16445 | 1/4 | 6.4 | 7/16–20 | 1/2 | 9/16 | 2.09 | 53.0 | 1.06 | 27.0 |
| G25510-0405 | 4G-5MFA | 7100-16455 | 1/4 | 6.4 | 1/2–20 | 1/2 | 5/8 | 1.97 | 50.0 | .94 | 24.0 |
| G25510-0505 | 5G-5MFA | 7100-16515 | 5/16 | 7.9 | 1/2–20 | 5/8 | 5/8 | 2.13 | 54.0 | 1.02 | 26.0 |
| G25510-0506 | 5G-6MFA | 7100-16505 | 5/16 | 7.9 | 9/16–18 | 5/8 | 11/16 | 2.21 | 56.1 | 1.11 | 28.1 |
| G25510-0604 | 6G-4MFA | 7100-16465 | 3/8 | 9.5 | 7/16–20 | 5/8 | 9/16 | 2.17 | 55.0 | 1.07 | 27.1 |
| G25510-0605 | 6G-5MFA | 7100-16475 | 3/8 | 9.5 | 1/2–20 | 5/8 | 5/8 | 2.17 | 55.0 | 1.07 | 27.1 |
| G25510-0606 | 6G-6MFA | 7100-16485 | 3/8 | 9.5 | 9/16–18 | 5/8 | 11/16 | 2.20 | 56.0 | 1.11 | 28.1 |
| G25510-0608 | 6G-8MFA | 7100-16495 | 3/8 | 9.5 | 3/4–16 | 3/4 | 7/8 | 2.40 | 61.0 | 1.30 | 33.1 |
| G25510-0808 | 8G-8MFA | 7100-06505 | 1/2 | 12.7 | 3/4–16 | 13/16 | 7/8 | 2.78 | 70.5 | 1.30 | 33.0 |
| G25510-0810 | 8G-10MFA | 7100-06515 | 1/2 | 12.7 | 7/8–14 | 7/8 | 1 | 2.83 | 72.0 | 1.36 | 34.5 |
| G25510-1212 | 12G-12MFA | 7100-06525 | 3/4 | 19.1 | 1 1/16–12 | 1 1/16 | 1 1/4 | 3.54 | 90.0 | 1.54 | 39.0 |
| G25510-1616 | 16G-16MFA | 7100-06535 | 1 | 25.4 | 1 5/16–12 | 1 3/8 | 1 1/2 | 3.94 | 100.0 | 1.70 | 43.2 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# North American Stand Pipe


See Accessories for Individual Sleeves and Nuts.




| Part No. | Descr. | Prod. No. | ⊖ | | H1 | L | | C | | B | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm | " | mm | " |
| G25520-0404 | 4G-4NASP | 7100-08305 | 1/4 | 6.4 | 1/2 | 2.26 | 57.5 | 1.24 | 31.5 | .88 | 22.4 | 1/4 |
| G25520-0606 | 6G-6NASP | 7100-08335 | 3/8 | 9.5 | 5/8 | 2.34 | 59.5 | 1.24 | 31.6 | .88 | 22.4 | 3/8 |
| G25520-0808 | 8G-8NASP | 7100-08365 | 1/2 | 12.7 | 13/16 | 2.87 | 73.0 | 1.40 | 35.5 | 1.00 | 25.4 | 1/2 |
| G25520-1212 | 12G-12NASP | 7100-08435 | 3/4 | 19.1 | 1 1/16 | 3.58 | 91.0 | 1.57 | 40.0 | 1.16 | 29.5 | 3/4 |
| G25520-1616 | 16G-16NASP | 7100-08465 | 1 | 25.4 | 1 7/16 | 3.86 | 98.0 | 1.62 | 41.2 | 1.12 | 28.4 | 1 |

# Hose Length Extender





| Part No. | Descr. | Prod. No. | ⊖ | | L | | C | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G25535-2020 | 20G-20HLE | 7101-50705 | 1 1/4 | 31.8 | 5.96 | 151.5 | 1.32 | 33.5 |

# Female Air Brake Swivel





| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G25540-0606 | 6G-6FABX | 7100-13095 | 3/8 | 9.5 | 3/4–20 | 3/4 | 7/8 | 2.41 | 61.2 | 1.31 | 33.3 |
| G25540-0806 | 8G-6FABX | 7100-13105 | 1/2 | 12.7 | 3/4–20 | 13/16 | 7/8 | 2.74 | 69.7 | 1.27 | 32.2 |
| G25540-0808 | 8G-8FABX | 7100-13125 | 1/2 | 12.7 | 7/8–20 | 13/16 | 1 1/16 | 3.02 | 76.7 | 1.54 | 39.2 |

## Female Grease





| Part No. | Descr. | Prod. No. | ⟷ | | ⦚ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G25561-0408 | 4G-8FG | 7100-09605 | 1/4 | 6.4 | 1/2–27 | 11/16 | 1.87 | 47.5 | .85 | 21.5 |
| G25561-0608 | 6G-8FG | 7100-09615 | 3/8 | 9.5 | 1/2–27 | 11/16 | 1.93 | 49.0 | .83 | 21.2 |

## Female Parker Triple Thread Flare




| Part No. | Descr. | Prod. No. | ⟷ | | ⦚ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G25562-1616 | 16G-16FZX | 7100-00015 | 1 | 25.4 | 1 5/16–14 | 1 3/8 | 1 1/2 | 3.98 | 101.0 | 1.74 | 44.3 |


## Pressure Wash Swivel




| Part No. | Descr. | Prod. No. | ⟷ | | ⦚ | L | | C | |
|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm |
| G25563-0406 | 4G-6PWX | 7100-02905 | 1/4 | 6.4 | M22X1.5 | 2.52 | 64.0 | 1.50 | 38.0 |
| G25563-0606 | 6G-6PWX | 7100-02915 | 3/8 | 9.5 | M22X1.5 | 2.60 | 66.0 | 1.50 | 38.1 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# US Banjo




| Part No. | Descr. | Prod. No. | ⟷ | | L | | C | | BH |
|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | mm |
| G25564-0606 | 6G-6BJ | 7100-02945 | 3/4 | 19.1 | 2.28 | 57.9 | .74 | 18.8 | 3/8 |


# Male DIN 24° Cone - Light Series





| Part No. | Descr. | Prod. No. | ⟷ | | ⫶ | H1 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | mm |
| G25615-0406 | 4G-6MDL | 7100-92685 | 1/4 | 6.4 | M12X1.5 | 14 | 1.69 | 42.9 | .78 | 19.8 | 6.0 |
| G25615-0408 | 4G-8MDL | 7100-14835 | 1/4 | 6.4 | M14X1.5 | 17 | 1.97 | 50.0 | .94 | 24.0 | 8.0 |
| G25615-0410 | 4G-10MDL | 7100-14845 | 1/4 | 6.4 | M16X1.5 | 17 | 2.01 | 51.0 | .98 | 25.0 | 10.0 |
| G25615-0610 | 6G-10MDL | 7100-14865 | 3/8 | 9.5 | M16X1.5 | 17 | 2.07 | 52.5 | .97 | 24.6 | 10.0 |
| G25615-0612 | 6G-12MDL | 7100-14875 | 3/8 | 9.5 | M18X1.5 | 19 | 2.07 | 52.5 | .97 | 24.6 | 12.0 |
| G25615-0615 | 6G-15MDL | 7100-92695 | 3/8 | 9.5 | M22X1.5 | 24 | 1.86 | 47.3 | .94 | 23.9 | 15.0 |
| G25615-0815 | 8G-15MDL | 7100-04885 | 1/2 | 12.7 | M22X1.5 | 24 | 2.56 | 65.0 | 1.08 | 27.5 | 15.0 |
| G25615-1018 | 10G-18MDL | 7100-99685 | 5/8 | 15.9 | M26X1.5 | 27 | 2.52 | 64.0 | 1.04 | 26.5 | 18.0 |
| G25615-1022 | 10G-22MDL | 7100-04935 | 5/8 | 15.9 | M30X2.0 | 32 | 2.75 | 69.8 | 1.27 | 32.3 | 22.0 |
| G25615-1218 | 12G-18MDL | 7100-25085 | 3/4 | 19.1 | M26X1.5 | 27 | 3.07 | 78.0 | 1.06 | 27.0 | 18.0 |
| G25615-1222 | 12G-22MDL | 7100-25075 | 3/4 | 19.1 | M30X2.0 | 32 | 3.15 | 80.0 | 1.14 | 29.0 | 22.0 |
| G25615-1628 | 16G-28MDL | 7100-04915 | 1 | 25.4 | M36X2.0 | 41 | 3.70 | 94.0 | 1.46 | 37.2 | 28.0 |
| G25615-2035 | 20G-35MDL | 7100-04925 | 1 1/4 | 31.8 | M45X2.0 | 46 | 3.92 | 99.5 | 1.59 | 40.5 | 35.0 |


# Female DIN 24° Cone Swivel - Light Series with O-Ring





| Part No. | Descr. | Prod. No. | ⊖ | | ⫼ | H2 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | mm |
| G25645-0406 | 4G-6FDLORX | 7100-95665 | 1/4 | 6.4 | M12X1.5 | 14 | 2.04 | 51.8 | 1.13 | 28.8 | 6.0 |
| G25645-0408 | 4G-8FDLORX | 7100-95685 | 1/4 | 6.4 | M14X1.5 | 17 | 2.19 | 55.7 | 1.17 | 29.7 | 8.0 |
| G25645-0410 | 4G-10FDLORX | 7100-95705 | 1/4 | 6.4 | M16X1.5 | 19 | 2.18 | 55.3 | 1.15 | 29.3 | 10.0 |
| G25645-0412 | 4G-12FDLORX | 7100-25395 | 1/4 | 6.4 | M18X1.5 | 22 | 2.19 | 55.7 | 1.17 | 29.7 | 12.0 |
| G25645-0510 | 5G-10FDLORX | 7100-92015 | 5/16 | 7.9 | M16X1.5 | 19 | 2.12 | 53.9 | 1.17 | 29.7 | 10.0 |
| G25645-0512 | 5G-12FDLORX | 7100-92035 | 5/16 | 7.9 | M18X1.5 | 22 | 2.30 | 58.5 | 1.18 | 30.0 | 12.0 |
| G25645-0610 | 6G-10FDLORX | 7100-96065 | 3/8 | 9.5 | M16X1.5 | 19 | 2.25 | 57.1 | 1.07 | 27.1 | 10.0 |
| G25645-0612 | 6G-12FDLORX | 7100-96085 | 3/8 | 9.5 | M18X1.5 | 22 | 2.19 | 55.5 | 1.09 | 27.7 | 12.0 |
| G25645-0614 | 6G-14FDLORX | 7100-96105 | 3/8 | 9.5 | M20X1.5 | 24 | 2.38 | 60.4 | 1.85 | 30.1 | 14.0 |
| G25645-0615 | 6G-15FDLORX | 7100-96115 | 3/8 | 9.5 | M22X1.5 | 27 | 2.23 | 56.7 | 1.03 | 26.1 | 15.0 |
| G25645-0815 | 8G-15FDLORX | 7100-25445 | 1/2 | 12.7 | M22X1.5 | 27 | 2.64 | 67.0 | 1.16 | 29.5 | 15.0 |
| G25645-0818 | 8G-18FDLORX | 7100-96445 | 1/2 | 12.7 | M26X1.5 | 32 | 2.67 | 67.9 | 1.08 | 27.5 | 18.0 |
| G25645-1018 | 10G-18FDLORX | 7100-99535 | 5/8 | 15.9 | M26X1.5 | 32 | 2.67 | 67.8 | 1.16 | 29.5 | 18.0 |
| G25645-1218 | 12G-18FDLORX | 7100-99935 | 3/4 | 19.1 | M26X1.5 | 32 | 3.30 | 83.8 | 1.20 | 30.5 | 18.0 |
| G25645-1222 | 12G-22FDLORX | 7100-99955 | 3/4 | 19.1 | M30X2.0 | 36 | 3.38 | 85.8 | 1.28 | 32.5 | 22.0 |
| G25645-1628 | 16G-28FDLORX | 7100-92205 | 1 | 25.4 | M36X2.0 | 41 | 3.21 | 81.6 | 1.45 | 36.7 | 28.0 |
| G25645-2035 | 20G-35FDLORX | 7100-92215 | 1 1/4 | 31.8 | M45X2.0 | 50 | 3.56 | 90.4 | 1.74 | 44.1 | 35.0 |
| G25645-2042 | 20G-42FDLORX | 7100-95305 | 1 1/4 | 31.8 | M52X2.0 | 60 | 4.25 | 108.0 | 1.93 | 49.0 | 42.0 |

# Female DIN 24° Cone Swivel - Light Series with O-Ring - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | ⫼ | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | mm |
| G25650-0408 | 4G-8FDLORX45 | 7100-95755 | 1/4 | 6.4 | M14X1.5 | 19 | .64 | 16.2 | 2.46 | 62.6 | 1.44 | 36.5 | 8.0 |
| G25650-0410 | 4G-10FDLORX45 | 7100-95775 | 1/4 | 6.4 | M16X1.5 | 19 | .70 | 17.9 | 2.54 | 64.4 | 1.51 | 38.3 | 10.0 |
| G25650-0510 | 5G-10FDLORX45 | 7100-91895 | 5/16 | 7.9 | M16X1.5 | 19 | .67 | 17.0 | 2.50 | 63.4 | 1.55 | 39.3 | 10.0 |
| G25650-0610 | 6G-10FDLORX45 | 7100-96135 | 3/8 | 9.5 | M16X1.5 | 19 | .73 | 18.6 | 2.67 | 68.5 | 1.59 | 40.5 | 10.0 |
| G25650-0612 | 6G-12FDLORX45 | 7100-96155 | 3/8 | 9.5 | M18X1.5 | 22 | .74 | 18.9 | 2.71 | 68.8 | 1.61 | 40.9 | 12.0 |
| G25650-0615 | 6G-15FDLORX45 | 7100-96175 | 3/8 | 9.5 | M22X1.5 | 27 | .89 | 22.5 | 2.85 | 72.3 | 1.75 | 44.4 | 15.0 |
| G25650-0815 | 8G-15FDLORX45 | 7100-96475 | 1/2 | 12.7 | M22X1.5 | 27 | .80 | 20.2 | 3.33 | 84.6 | 1.85 | 47.0 | 15.0 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female DIN 24° Cone Swivel - Light Series with O-Ring - 45° Bent Tube - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | mm |
| G25650-0818 | 8G-18FDLORX45 | 7100-96495 | 1/2 | 12.7 | M26X1.5 | 32 | 1.06 | 26.9 | 3.74 | 94.9 | 2.25 | 57.2 | 18.0 |
| G25650-1018 | 10G-18FDLORX45 | 7100-99545 | 5/8 | 15.9 | M26X1.5 | 32 | .98 | 24.8 | 3.68 | 93.5 | 2.21 | 56.2 | 18.0 |
| G25650-1222 | 12G-22FDLORX45 | 7100-96715 | 3/4 | 19.1 | M30X2.0 | 36 | 1.17 | 29.8 | 4.12 | 104.6 | 2.60 | 66.1 | 22.0 |
| G25650-1628 | 16G-28FDLORX45 | 7100-92325 | 1 | 25.4 | M36X2.0 | 41 | 1.21 | 30.9 | 4.87 | 123.7 | 3.10 | 78.8 | 28.0 |
| G25650-2035 | 20G-35FDLORX45 | 7100-92335 | 1 1/4 | 31.8 | M45X2.0 | 50 | 1.48 | 37.5 | 5.48 | 139.3 | 3.68 | 93.4 | 35.0 |


## Female DIN 24° Cone Swivel - Light Series with O-Ring - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | mm |
| G25655-0406 | 4G-6FDLORX90 | 7100-95825 | 1/4 | 6.4 | M12X1.5 | 14 | 1.38 | 35.0 | 2.27 | 57.6 | 1.24 | 31.5 | 6.0 |
| G25655-0408 | 4G-8FDLORX90 | 7100-95845 | 1/4 | 6.4 | M14X1.5 | 17 | 1.38 | 35.0 | 2.36 | 60.0 | 1.34 | 34.0 | 8.0 |
| G25655-0410 | 4G-10FDLORX90 | 7100-95865 | 1/4 | 6.4 | M16X1.5 | 19 | 1.44 | 36.5 | 2.27 | 57.6 | 1.24 | 31.5 | 10.0 |
| G25655-0510 | 5G-10FDLORX90 | 7100-91725 | 5/16 | 7.9 | M16X1.5 | 19 | 1.44 | 36.5 | 2.31 | 58.6 | 1.35 | 34.4 | 10.0 |
| G25655-0610 | 6G-10FDLORX90 | 7100-96195 | 3/8 | 9.5 | M16X1.5 | 19 | 1.44 | 36.5 | 2.37 | 60.2 | 1.27 | 32.3 | 10.0 |
| G25655-0612 | 6G-12FDLORX90 | 7100-96215 | 3/8 | 9.5 | M18X1.5 | 22 | 1.46 | 37.0 | 2.37 | 60.1 | 1.27 | 32.2 | 12.0 |
| G25655-0615 | 6G-15FDLORX90 | 7100-96235 | 3/8 | 9.5 | M22X1.5 | 27 | 1.65 | 42.0 | 2.37 | 60.1 | 1.27 | 32.2 | 15.0 |
| G25655-0815 | 8G-15FDLORX90 | 7100-96505 | 1/2 | 12.7 | M22X1.5 | 27 | 1.65 | 42.0 | 3.06 | 77.8 | 1.59 | 40.3 | 15.0 |
| G25655-0818 | 8G-18FDLORX90 | 7100-96525 | 1/2 | 12.7 | M26X1.5 | 32 | 2.03 | 51.6 | 3.21 | 81.5 | 1.73 | 43.9 | 18.0 |
| G25655-1018 | 10G-18FDLORX90 | 7100-99555 | 5/8 | 15.9 | M26X1.5 | 32 | 2.03 | 51.5 | 3.35 | 85.1 | 1.88 | 47.8 | 18.0 |
| G25655-1218 | 12G-18FDLORX90 | 7100-96735 | 3/4 | 19.1 | M26X1.5 | 32 | 2.03 | 51.5 | 3.95 | 100.3 | 1.94 | 49.3 | 18.0 |
| G25655-1222 | 12G-22FDLORX90 | 7100-96755 | 3/4 | 19.1 | M30X2.0 | 36 | 2.44 | 62.0 | 4.22 | 107.3 | 2.22 | 56.3 | 22.0 |
| G25655-1628 | 16G-28FDLORX90 | 7100-92445 | 1 | 25.4 | M36X2.0 | 41 | 2.76 | 70.0 | 4.69 | 119.2 | 2.93 | 74.3 | 28.0 |
| G25655-2035 | 20G-35FDLORX90 | 7100-92455 | 1 1/4 | 31.8 | M45X2.0 | 50 | 3.15 | 80.0 | 5.07 | 128.8 | 3.26 | 82.8 | 35.0 |


# Female French GAZ Swivel





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | | " | mm | " | mm |
| G25680-0817 | 8G-17FFGX | 7100-96655 | 1/2 | 12.7 | M24X1.5 | 30 | | 2.40 | 61.0 | .93 | 23.5 |
| G25680-1021 | 10G-21FFGX | 7100-99595 | 5/8 | 15.9 | M30X1.5 | 36 | | 2.34 | 59.5 | .87 | 22.0 |
| G25680-1227 | 12G-27FFGX | 7100-25045 | 3/4 | 19.1 | M36X1.5 | 46 | | 2.91 | 74.0 | .91 | 23.0 |

# Male DIN 24° Cone - Heavy Series

See Accessories for Metric Bite Sleeves and Nuts.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | | " | mm | " | mm | mm |
| G25715-0408 | 4G-8MDH | 7100-15315 | 1/4 | 6.4 | M16X1.5 | 17 | | 2.09 | 53.0 | 1.06 | 27.0 | 8.0 |
| G25715-0410 | 4G-10MDH | 7100-15325 | 1/4 | 6.4 | M18X1.5 | 19 | | 2.07 | 52.5 | 1.04 | 26.5 | 10.0 |
| G25715-0512 | 5G-12MDH | 7100-93015 | 5/16 | 7.9 | M20X1.5 | 22 | | 2.04 | 51.9 | 1.09 | 27.8 | 12.0 |
| G25715-0610 | 6G-10MDH | 7100-15345 | 3/8 | 9.5 | M18X1.5 | 19 | | 2.17 | 55.0 | 1.07 | 27.1 | 10.0 |
| G25715-0612 | 6G-12MDH | 7100-15355 | 3/8 | 9.5 | M20X1.5 | 24 | | 2.26 | 57.5 | 1.17 | 29.6 | 12.0 |
| G25715-0614 | 6G-14MDH | 7100-15365 | 3/8 | 9.5 | M22X1.5 | 24 | | 2.34 | 59.5 | 1.24 | 31.6 | 14.0 |
| G25715-0812 | 8G-12MDH | 7100-94815 | 1/2 | 12.7 | M20X1.5 | 24 | | 2.42 | 61.5 | 1.14 | 29.0 | 12.0 |
| G25715-0816 | 8G-16MDH | 7100-05375 | 1/2 | 12.7 | M24X1.5 | 27 | | 2.72 | 69.0 | 1.24 | 31.5 | 16.0 |
| G25715-1020 | 10G-20MDH | 7100-99675 | 5/8 | 15.9 | M30X2.0 | 32 | | 2.87 | 73.0 | 1.40 | 35.5 | 20.0 |
| G25715-1220 | 12G-20MDH | 7100-25055 | 3/4 | 19.1 | M30X2.0 | 32 | | 3.43 | 87.0 | 1.42 | 36.0 | 20.0 |
| G25715-1225 | 12G-25MDH | 7100-25065 | 3/4 | 19.1 | M36X2.0 | 41 | | 3.58 | 91.0 | 1.58 | 40.0 | 25.0 |
| G25715-1630 | 16G-30MDH | 7100-92535 | 1 | 25.4 | M42X2.0 | 46 | | 3.48 | 88.3 | 1.67 | 42.4 | 30.0 |
| G25715-2038 | 20G-38MDH | 7100-92545 | 1 1/4 | 31.8 | M52X2.0 | 55 | | 3.72 | 94.4 | 1.93 | 49.1 | 38.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Female DIN 24° Cone Swivel - Heavy Series with O-Ring





| Part No. | Descr. | Prod. No. | ⟷ | | ⦀ | H2 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | mm |
| G25720-0408 | 4G-8FDHORX | 7100-95675 | 1/4 | 6.4 | M16X1.5 | 19 | 2.14 | 54.4 | 1.12 | 28.4 | 8.0 |
| G25720-0410 | 4G-10FDHORX | 7100-95695 | 1/4 | 6.4 | M18X1.5 | 22 | 2.18 | 55.3 | 1.15 | 29.3 | 10.0 |
| G25720-0412 | 4G-12FDHORX | 7100-25405 | 1/4 | 6.4 | M20X1.5 | 24 | 2.19 | 55.7 | 1.17 | 29.7 | 12.0 |
| G25720-0512 | 5G-12FDHORX | 7100-92045 | 5/16 | 7.9 | M20X1.5 | 24 | 2.28 | 58.0 | 1.18 | 30.0 | 12.0 |
| G25720-0514 | 5G-14FDHORX | 7100-94835 | 5/16 | 7.9 | M22X1.5 | 27 | 2.11 | 53.6 | 1.18 | 30.0 | 14.0 |
| G25720-0610 | 6G-10FDHORX | 7100-96055 | 3/8 | 9.5 | M18X1.5 | 22 | 2.17 | 55.0 | 1.07 | 27.1 | 10.0 |
| G25720-0612 | 6G-12FDHORX | 7100-96075 | 3/8 | 9.5 | M20X1.5 | 24 | 2.19 | 55.5 | 1.09 | 27.6 | 12.0 |
| G25720-0614 | 6G-14FDHORX | 7100-96095 | 3/8 | 9.5 | M22X1.5 | 27 | 2.28 | 58.0 | 1.85 | 30.1 | 14.0 |
| G25720-0812 | 8G-12FDHORX | 7100-93335 | 1/2 | 12.7 | M20X1.5 | 24 | 2.76 | 70.2 | 1.29 | 32.7 | 12.0 |
| G25720-0814 | 8G-14FDHORX | 7100-96415 | 1/2 | 12.7 | M22X1.5 | 27 | 2.68 | 68.0 | 1.20 | 30.5 | 14.0 |
| G25720-0816 | 8G-16FDHORX | 7100-96435 | 1/2 | 12.7 | M24X1.5 | 30 | 2.61 | 66.4 | 1.32 | 33.5 | 16.0 |
| G25720-0820 | 8G-20FDHORX | 7100-96455 | 1/2 | 12.7 | M30X2.0 | 36 | 2.79 | 70.9 | 1.50 | 38.1 | 20.0 |
| G25720-1016 | 10G-16FDHORX | 7100-99525 | 5/8 | 15.9 | M24X1.5 | 30 | 2.80 | 71.0 | 1.32 | 33.5 | 16.0 |
| G25720-1020 | 10G-20FDHORX | 7100-99565 | 5/8 | 15.9 | M30X2.0 | 36 | 2.87 | 73.0 | 1.40 | 35.5 | 20.0 |
| G25720-1220 | 12G-20FDHORX | 7100-99945 | 3/4 | 19.1 | M30X2.0 | 36 | 3.52 | 89.5 | 1.52 | 38.5 | 20.0 |
| G25720-1225 | 12G-25FDHORX | 7100-99965 | 3/4 | 19.1 | M36X2.0 | 46 | 3.54 | 90.0 | 1.54 | 39.0 | 25.0 |
| G25720-1625 | 16G-25FDHORX | 7100-93215 | 1 | 25.4 | M36X2.0 | 46 | 4.04 | 102.5 | 1.80 | 45.7 | 25.0 |
| G25720-1630 | 16G-30FDHORX | 7100-92235 | 1 | 25.4 | M42X2.0 | 50 | 3.70 | 94.1 | 1.94 | 49.2 | 30.0 |
| G25720-2038 | 20G-38FDHORX | 7100-92245 | 1 1/4 | 31.8 | M52X2.0 | 60 | 4.10 | 104.1 | 2.28 | 57.8 | 38.0 |

# Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 45° Bent Tube









| Part No. | Descr. | Prod. No. | ⟷ | | ⦀ | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | mm |
| G25725-0408 | 4G-8FDHORX45 | 7100-95745 | 1/4 | 6.4 | M16X1.5 | 19 | .64 | 16.2 | 2.46 | 62.6 | 1.44 | 36.5 | 8.0 |
| G25725-0410 | 4G-10FDHORX45 | 7100-95765 | 1/4 | 6.4 | M18X1.5 | 22 | .70 | 17.9 | 2.54 | 64.4 | 1.51 | 38.3 | 10.0 |
| G25725-0610 | 6G-10FDHORX45 | 7100-96125 | 3/8 | 9.5 | M18X1.5 | 22 | .73 | 18.6 | 2.70 | 68.5 | 1.59 | 40.5 | 10.0 |
| G25725-0612 | 6G-12FDHORX45 | 7100-96145 | 3/8 | 9.5 | M20X1.5 | 24 | .74 | 18.9 | 2.71 | 68.8 | 1.61 | 40.9 | 12.0 |
| G25725-0614 | 6G-14FDHORX45 | 7100-96165 | 3/8 | 9.5 | M22X1.5 | 27 | .83 | 21.0 | 2.79 | 70.9 | 1.69 | 43.0 | 14.0 |
| G25725-0814 | 8G-14FDHORX45 | 7100-96465 | 1/2 | 12.7 | M22X1.5 | 27 | 1.07 | 27.1 | 3.59 | 91.3 | 2.12 | 53.9 | 14.0 |

## Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 45° Bent Tube - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | mm |
| G25725-0816 | 8G-16FDHORX45 | 7100-96485 | 1/2 | 12.7 | M24X1.5 | 30 | .85 | 21.6 | 3.38 | 85.9 | 1.91 | 48.4 | 16.0 |
| G25725-1020 | 10G-20FDHORX45 | 7100-99575 | 5/8 | 15.9 | M30X2.0 | 36 | .98 | 24.9 | 3.67 | 93.1 | 2.20 | 55.8 | 20.0 |
| G25725-1220 | 12G-20FDHORX45 | 7100-96705 | 3/4 | 19.1 | M30X2.0 | 36 | .98 | 24.9 | 4.31 | 109.4 | 2.30 | 58.4 | 20.0 |
| G25725-1225 | 12G-25FDHORX45 | 7100-96725 | 3/4 | 19.1 | M36X2.0 | 46 | 1.23 | 31.2 | 4.67 | 118.6 | 2.66 | 67.6 | 25.0 |

## Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 90° Bent Tube









| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | mm |
| G25730-0408 | 4G-8FDHORX90 | 7100-95835 | 1/4 | 6.4 | M16X1.5 | 19 | 1.38 | 35.0 | 2.36 | 60.0 | 1.34 | 34.0 | 8.0 |
| G25730-0410 | 4G-10FDHORX90 | 7100-95855 | 1/4 | 6.4 | M18X1.5 | 22 | 1.44 | 36.5 | 2.27 | 57.6 | 1.24 | 31.5 | 10.0 |
| G25730-0512 | 5G-12FDHORX90 | 7100-91755 | 5/16 | 7.9 | M20X1.5 | 24 | 1.46 | 37.0 | 2.32 | 59.0 | 1.22 | 31.0 | 12.0 |
| G25730-0514 | 5G-14FDHORX90 | 7100-94845 | 5/16 | 7.9 | M22X1.5 | 27 | 1.57 | 40.0 | 2.15 | 54.6 | 1.22 | 31.0 | 14.0 |
| G25730-0610 | 6G-10FDHORX90 | 7100-96185 | 3/8 | 9.5 | M18X1.5 | 22 | 1.44 | 36.5 | 2.37 | 60.1 | 1.27 | 32.2 | 10.0 |
| G25730-0612 | 6G-12FDHORX90 | 7100-96205 | 3/8 | 9.5 | M20X1.5 | 24 | 1.46 | 37.0 | 2.37 | 60.1 | 1.27 | 32.2 | 12.0 |
| G25730-0614 | 6G-14FDHORX90 | 7100-96225 | 3/8 | 9.5 | M22X1.5 | 27 | 1.57 | 40.0 | 2.37 | 60.3 | 1.28 | 32.4 | 14.0 |
| G25730-0814 | 8G-14FDHORX90 | 7100-13005 | 1/2 | 12.7 | M22X1.5 | 27 | 2.01 | 51.0 | 3.11 | 79.0 | 1.64 | 41.6 | 14.0 |
| G25730-0816 | 8G-16FDHORX90 | 7100-96515 | 1/2 | 12.7 | M24X1.5 | 30 | 1.73 | 44.0 | 3.06 | 77.8 | 1.59 | 40.3 | 16.0 |
| G25730-1020 | 10G-20FDHORX90 | 7100-99585 | 5/8 | 15.9 | M30X2.0 | 36 | 2.01 | 51.0 | 3.31 | 84.1 | 1.84 | 46.8 | 20.0 |
| G25730-1025 | 10G-25FDHORX90 | 7100-99605 | 5/8 | 15.9 | M36X2.0 | 46 | 2.52 | 64.0 | 3.31 | 84.1 | 1.84 | 46.8 | 25.0 |
| G25730-1220 | 12G-20FDHORX90 | 7100-96745 | 3/4 | 19.1 | M30X2.0 | 36 | 2.01 | 51.0 | 3.95 | 100.3 | 1.94 | 49.3 | 20.0 |
| G25730-1225 | 12G-25FDHORX90 | 7100-96765 | 3/4 | 19.1 | M36X2.0 | 46 | 2.52 | 64.0 | 4.22 | 107.3 | 2.22 | 56.3 | 25.0 |
| G25730-1625 | 16G-25FDHORX90 | 7100-94925 | 1 | 25.4 | M36X2.0 | 46 | 2.99 | 76.0 | 5.43 | 137.8 | 3.19 | 81.0 | 25.0 |
| G25730-2038 | 20G-38FDHORX90 | 7100-94935 | 1 1/4 | 31.8 | M52X2.0 | 60 | 3.43 | 87.1 | 5.96 | 151.4 | 3.64 | 92.5 | 38.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Metric Light Stand Pipe


See Metric Stand Pipe Assembly in the Hose/Coupling Selection Section for sleeve and nut selection. See Accessories for Metric Bite Sleeve and Metric Bite Nut part numbers.




| Part No. | Descr. | Prod. No. | ⟷ | | H1 | L | | C | | B | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm | " | mm | mm |
| G25750-0406 | 4G-6MSP | 7100-93355 | 1/4 | 6.4 | 1/2 | 2.46 | 62.5 | 1.44 | 36.5 | .87 | 22.0 | 6.0 |
| G25750-0408 | 4G-8MSP | 7100-93365 | 1/4 | 6.4 | 1/2 | 2.46 | 62.5 | 1.44 | 36.5 | .87 | 22.0 | 8.0 |
| G25750-0410 | 4G-10MSP | 7100-93375 | 1/4 | 6.4 | 1/2 | 2.54 | 64.5 | 1.52 | 38.5 | .87 | 22.0 | 10.0 |
| G25750-0610 | 6G-10MSP | 7100-90325 | 3/8 | 9.5 | 5/8 | 2.62 | 66.5 | 1.52 | 38.6 | .91 | 23.0 | 10.0 |
| G25750-0612 | 6G-12MSP | 7100-90005 | 3/8 | 9.5 | 5/8 | 2.62 | 66.5 | 1.52 | 38.6 | .91 | 23.0 | 12.0 |
| G25750-0815 | 8G-15MSP | 7100-90045 | 1/2 | 12.7 | 13/16 | 3.00 | 76.3 | 1.53 | 38.8 | .98 | 25.0 | 15.0 |
| G25750-1018 | 10G-18MSP | 7100-99695 | 5/8 | 15.9 | 15/16 | 3.03 | 77.0 | 1.56 | 39.5 | .98 | 25.0 | 18.0 |
| G25750-1022 | 10G-22MSP | 7100-95335 | 5/8 | 15.9 | 15/16 | 3.11 | 79.0 | 1.63 | 41.5 | .98 | 25.0 | 22.0 |
| G25750-1218 | 12G-18MSP | 7100-95345 | 3/4 | 19.1 | 1 1/16 | 3.54 | 90.0 | 1.54 | 39.0 | 1.02 | 26.0 | 18.0 |
| G25750-1222 | 12G-22MSP | 7100-93465 | 3/4 | 19.1 | 1 1/16 | 3.67 | 93.2 | 1.66 | 42.2 | 1.10 | 28.0 | 22.0 |
| G25750-1628 | 16G-28MSP | 7100-95355 | 1 | 25.4 | 1 7/16 | 4.09 | 104.0 | 1.86 | 47.2 | 1.18 | 30.0 | 28.0 |


# International Thread Metric 7642 DIN Banjo




| Part No. | Descr. | Prod. No. | ⟷ | | L | | C | | BH |
|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | mm |
| G25770-0412 | 4G-12DBJ | 7100-91195 | 1/4 | 6.4 | 2.03 | 51.4 | 1.11 | 28.3 | 12.1 |
| G25770-0612 | 6G-12DBJ | 7100-98125 | 3/8 | 9.5 | 2.20 | 56.0 | 1.11 | 28.1 | 12.1 |
| G25770-0614 | 6G-14DBJ | 7100-98655 | 3/8 | 9.5 | 2.30 | 58.3 | 1.20 | 30.4 | 14.1 |
| G25770-0616 | 6G-16DBJ | 7100-91285 | 3/8 | 9.5 | 2.20 | 55.8 | 1.27 | 32.4 | 16.1 |
| G25770-0618 | 6G-18DBJ | 7100-91295 | 3/8 | 9.5 | 2.28 | 57.8 | 1.35 | 34.4 | 18.1 |
| G25770-0818 | 8G-18DBJ | 7100-91305 | 1/2 | 12.7 | 2.64 | 67.2 | 1.37 | 34.7 | 18.1 |
| G25770-1022 | 10G-22DBJ | 7100-99725 | 5/8 | 15.9 | 3.00 | 76.2 | 1.52 | 38.6 | 22.1 |
| G25770-1226 | 12G-26DBJ | 7100-25005 | 3/4 | 19.1 | 3.73 | 94.7 | 1.72 | 43.7 | 26.1 |
| G25770-1630 | 16G-30DBJ | 7100-94995 | 1 | 25.4 | 4.30 | 109.2 | 2.06 | 52.4 | 30.1 |


# Male British Standard Pipe Tapered/Japanese Tapered Thread





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | | " | mm | " | mm |
| G25795-0404 | 4G-4MBSPT | 7100-91075 | 1/4 | 6.4 | 1/4–19 | 14 | 1.89 | 48.0 | .97 | 24.8 |
| G25795-0606 | 6G-6MBSPT | 7100-91105 | 3/8 | 9.5 | 3/8–19 | 19 | 1.95 | 49.5 | 1.03 | 26.1 |
| G25795-0808 | 8G-8MBSPT | 7100-91125 | 1/2 | 12.7 | 1/2–14 | 22 | 2.49 | 63.4 | 1.22 | 30.9 |
| G25795-1010 | 10G-10MBSPT | 7100-99645 | 5/8 | 15.9 | 5/8–14 | 24 | 2.76 | 70.0 | 1.28 | 32.5 |
| G25795-1212 | 12G-12MBSPT | 7100-99925 | 3/4 | 19.1 | 3/4–14 | 32 | 3.50 | 89.0 | 1.50 | 38.0 |
| G25795-1616 | 16G-16MBSPT | 7100-91155 | 1 | 25.4 | 1–11 | 36 | 3.44 | 87.5 | 1.64 | 41.6 |

# Male British Standard Parallel Pipe





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | | " | mm | " | mm |
| G25810-0404 | 4G-4MBSPP | 7100-15515 | 1/4 | 6.4 | 1/4–19 | 19 | 2.03 | 51.5 | 1.00 | 25.4 |
| G25810-0604 | 6G-4MBSPP | 7100-98255 | 3/8 | 9.5 | 1/4–19 | 19 | 2.05 | 52.0 | .95 | 24.1 |
| G25810-0606 | 6G-6MBSPP | 7100-15525 | 3/8 | 9.5 | 3/8–19 | 22 | 2.17 | 55.0 | 1.07 | 27.1 |
| G25810-0608 | 6G-8MBSPP | 7100-15535 | 3/8 | 9.5 | 1/2–14 | 27 | 2.36 | 60.0 | 1.26 | 32.1 |
| G25810-0806 | 8G-6MBSPP | 7100-93245 | 1/2 | 12.7 | 3/8–19 | 22 | 2.30 | 58.5 | 1.02 | 26.0 |
| G25810-0808 | 8G-8MBSPP | 7100-05545 | 1/2 | 12.7 | 1/2–14 | 27 | 2.72 | 69.0 | 1.24 | 31.5 |
| G25810-1010 | 10G-10MBSPP | 7100-99625 | 5/8 | 15.9 | 5/8–14 | 30 | 2.83 | 72.0 | 1.36 | 34.5 |
| G25810-1012 | 10G-12MBSPP | 7100-99655 | 5/8 | 15.9 | 3/4–14 | 32 | 2.91 | 74.0 | 1.44 | 36.5 |
| G25810-1212 | 12G-12MBSPP | 7100-99905 | 3/4 | 19.1 | 3/4–14 | 32 | 3.54 | 90.0 | 1.54 | 39.0 |
| G25810-1616 | 16G-16MBSPP | 7100-05575 | 1 | 25.4 | 1–11 | 41 | 3.98 | 101.0 | 1.74 | 44.2 |
| G25810-2020 | 20G-20MBSPP | 7100-05585 | 1 1/4 | 31.8 | 1 1/4–11 | 50 | 4.33 | 110.0 | 2.01 | 51.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female British Standard Parallel Pipe O-Ring Swivel

Includes O–Ring sealing in flare.





H2





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | | " | mm | " | mm |
| G25830-0402 | 4G-2FBSPPX | 7100-97325 | 1/4 | 6.4 | 1/8–28 | 14 | 1.62 | 41.1 | .71 | 18.0 |
| G25830-0404 | 4G-4FBSPORX | 7100-95915 | 1/4 | 6.4 | 1/4–19 | 19 | 1.69 | 43.0 | 1.22 | 31.1 |
| G25830-0406 | 4G-6FBSPORX | 7100-95925 | 1/4 | 6.4 | 3/8–19 | 32 | 2.82 | 71.6 | .81 | 20.6 |
| G25830-0506 | 5G-6FBSPORX | 7100-95025 | 5/16 | 7.9 | 3/8–19 | 22 | 2.13 | 54.0 | 1.02 | 26.0 |
| G25830-0508 | 5G-8FBSPORX | 7100-94205 | 5/16 | 7.9 | 1/2–14 | 27 | 2.16 | 54.8 | 1.06 | 26.8 |
| G25830-0606 | 6G-6FBSPORX | 7100-96295 | 3/8 | 9.5 | 3/8–19 | 22 | 1.74 | 44.2 | .64 | 16.2 |
| G25830-0608 | 6G-8FBSPORX | 7100-96305 | 3/8 | 9.5 | 1/2–14 | 27 | 1.80 | 45.8 | .71 | 17.9 |
| G25830-0806 | 8G-6FBSPORX | 7100-97895 | 1/2 | 12.7 | 3/8–19 | 22 | 2.62 | 66.5 | 1.14 | 29.0 |
| G25830-0808 | 8G-8FBSPORX | 7100-96535 | 1/2 | 12.7 | 1/2–14 | 27 | 2.19 | 55.5 | .70 | 17.8 |
| G25830-0810 | 8G-10FBSPORX | 7100-96545 | 1/2 | 12.7 | 5/8–14 | 30 | 2.25 | 57.2 | .78 | 19.8 |
| G25830-0812 | 8G-12FBSPORX | 7100-96555 | 1/2 | 12.7 | 3/4–14 | 32 | 2.32 | 59.0 | .85 | 21.5 |
| G25830-1010 | 10G-10FBSPORX | 7100-99445 | 5/8 | 15.9 | 5/8–14 | 30 | 2.20 | 56.0 | .73 | 18.5 |
| G25830-1012 | 10G-12FBSPORX | 7100-99485 | 5/8 | 15.9 | 3/4–14 | 32 | 2.28 | 58.0 | .81 | 20.5 |
| G25830-1212 | 12G-12FBSPORX | 7100-99825 | 3/4 | 19.1 | 3/4–14 | 32 | 2.82 | 71.6 | .81 | 20.6 |
| G25830-1216 | 12G-16FBSPORX | 7100-99835 | 3/4 | 19.1 | 1–11 | 41 | 2.89 | 73.3 | .88 | 22.3 |
| G25830-1616 | 16G-16FBSPORX | 7100-95155 | 1 | 25.4 | 1–11 | 41 | 3.78 | 96.0 | 1.54 | 39.2 |
| G25830-2020 | 20G-20FBSPORX | 7100-95235 | 1 1/4 | 31.8 | 1 1/4–11 | 50 | 3.48 | 88.5 | 1.16 | 29.5 |

# Female British Standard Parallel Pipe O-Ring Swivel - 45° Bent Tube

Includes O–Ring sealing in flare.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | | " | mm | " | mm | " | mm |
| G25831-0404 | 4G-4FBSPORX45 | 7100-95935 | 1/4 | 6.4 | 1/4–19 | 19 | .46 | 11.5 | 2.25 | 57.1 | 1.22 | 31.1 |
| G25831-0606 | 6G-6FBSPORX45 | 7100-96315 | 3/8 | 9.5 | 3/8–19 | 22 | .60 | 15.2 | 2.63 | 66.9 | 1.54 | 39.0 |
| G25831-0608 | 6G-8FBSPORX45 | 7100-96325 | 3/8 | 9.5 | 1/2–14 | 22 | .76 | 19.3 | 2.79 | 71.0 | 1.69 | 43.0 |
| G25831-0808 | 8G-8FBSPORX45 | 7100-96565 | 1/2 | 12.7 | 1/2–14 | 27 | .67 | 17.0 | 3.21 | 81.5 | 1.73 | 44.0 |
| G25831-0810 | 8G-10FBSPORX45 | 7100-96575 | 1/2 | 12.7 | 5/8–14 | 30 | .91 | 23.0 | 3.53 | 89.8 | 2.06 | 52.3 |
| G25831-1010 | 10G-10FBSPORX45 | 7100-99455 | 5/8 | 15.9 | 5/8–14 | 30 | .84 | 21.3 | 3.53 | 89.6 | 2.05 | 52.1 |
| G25831-1012 | 10G-12FBSPORX45 | 7100-99495 | 5/8 | 15.9 | 3/4–14 | 32 | 1.27 | 32.2 | 3.92 | 99.5 | 2.44 | 62.0 |
| G25831-1212 | 12G-12FBSPORX45 | 7100-96795 | 3/4 | 19.1 | 3/4–14 | 32 | 1.11 | 28.3 | 4.54 | 115.4 | 2.54 | 64.4 |
| G25831-1616 | 16G-16FBSPORX45 | 7100-91535 | 1 | 25.4 | 1–11 | 41 | 1.22 | 30.9 | 4.87 | 123.6 | 3.10 | 78.8 |
| G25831-2020 | 20G-20FBSPORX45 | 7100-92715 | 1 1/4 | 31.8 | 1 1/4–11 | 50 | 1.48 | 37.5 | 5.50 | 139.6 | 3.68 | 93.4 |

# Female British Standard Parallel Pipe O-Ring Swivel - 90° Bent Tube


Includes O–Ring sealing in flare.





| Part No. | Descr. | Prod. No. | ⊖ | | ⫼ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25832-0404 | 4G-4FBSPORX90 | 7100-95955 | 1/4 | 6.4 | 1/4–19 | 19 | .93 | 23.3 | 2.07 | 52.5 | 1.04 | 26.5 |
| G25832-0606 | 6G-6FBSPORX90 | 7100-96335 | 3/8 | 9.5 | 3/8–19 | 22 | 1.26 | 32.0 | 2.44 | 61.9 | 1.34 | 34.0 |
| G25832-0608 | 6G-8FBSPORX90 | 7100-96345 | 3/8 | 9.5 | 1/2–14 | 22 | 1.48 | 37.5 | 2.37 | 60.1 | 1.27 | 32.2 |
| G25832-0808 | 8G-8FBSPORX90 | 7100-96585 | 1/2 | 12.7 | 1/2–14 | 27 | 1.47 | 37.3 | 3.07 | 78.0 | 1.59 | 40.5 |
| G25832-0810 | 8G-10FBSPORX90 | 7100-96595 | 1/2 | 12.7 | 5/8–14 | 30 | 1.81 | 46.0 | 3.16 | 80.2 | 1.69 | 42.8 |
| G25832-1010 | 10G-10FBSPORX90 | 7100-99465 | 5/8 | 15.9 | 5/8–14 | 30 | 1.81 | 46.0 | 3.31 | 84.1 | 1.84 | 46.6 |
| G25832-1012 | 10G-12FBSPORX90 | 7100-99505 | 5/8 | 15.9 | 3/4–14 | 32 | 2.36 | 60.0 | 3.31 | 84.1 | 1.84 | 46.6 |
| G25832-1212 | 12G-12FBSPORX90 | 7100-96805 | 3/4 | 19.1 | 3/4–14 | 32 | 2.36 | 60.0 | 4.21 | 107.0 | 2.21 | 56.0 |
| G25832-1216 | 12G-16FBSPORX90 | 7100-96815 | 3/4 | 19.1 | 1–11 | 41 | 2.76 | 70.0 | 4.42 | 112.2 | 2.41 | 61.2 |
| G25832-1616 | 16G-16FBSPORX90 | 7100-91635 | 1 | 25.4 | 1–11 | 41 | 2.76 | 70.0 | 4.69 | 119.2 | 2.93 | 74.3 |
| G25832-2020 | 20G-20FBSPORX90 | 7100-91645 | 1 1/4 | 31.8 | 1 1/4–11 | 50 | 3.15 | 80.0 | 5.07 | 128.8 | 3.26 | 82.8 |

# Female British Standard Parallel Pipe O-Ring Swivel - 90° Block





| Part No. | Descr. | Prod. No. | ⊖ | | ⫼ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25845-0404 | 4G-4FBSPORX90BL | 7100-91825 | 1/4 | 6.4 | 1/4–19 | 19 | .71 | 18.0 | 1.74 | 44.2 | .72 | 18.2 |
| G25845-0606 | 6G-6FBSPORX90BL | 7100-91835 | 3/8 | 9.5 | 3/8–19 | 22 | .83 | 21.0 | 1.71 | 43.5 | .79 | 20.0 |
| G25845-0808 | 8G-8FBSPORX90BL | 7100-91845 | 1/2 | 12.7 | 1/2–14 | 27 | .94 | 24.0 | 2.20 | 55.9 | .93 | 23.5 |
| G25845-1616 | 16G-16FBSPORX90BL | 7100-92585 | 1 | 25.4 | 1–11 | 41 | 1.42 | 36.1 | 3.17 | 80.5 | 1.36 | 34.6 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# International Thread British Std Pipe Banjo




| Part No. | Descr. | Prod. No. | ⟷ | | L | | C | | BH |
|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | mm |
| G25850-0404 | 4G-4BSPBJ | 7100-97305 | 1/4 | 6.4 | 2.10 | 53.4 | 1.19 | 30.3 | 13.2 |
| G25850-0606 | 6G-6BSPBJ | 7100-97635 | 3/8 | 9.5 | 2.20 | 55.8 | 1.30 | 32.4 | 16.8 |
| G25850-0808 | 8G-8BSPBJ | 7100-92925 | 1/2 | 12.7 | 2.80 | 70.7 | 1.50 | 38.2 | 21.0 |
| G25850-1212 | 12G-12BSPBJ | 7100-99815 | 3/4 | 19.1 | 3.73 | 94.7 | 1.72 | 43.7 | 26.5 |

# Female British Flat-Face Swivel









| Part No. | Descr. | Prod. No. | ⟷ | | ⦚ | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G25855-0606 | 6G-6FBFFX | 7100-96375 | 3/8 | 9.5 | 3/8–19 | 22 | 1.75 | 44.5 | .65 | 16.6 |
| G25855-0608 | 6G-8FBFFX | 7100-96385 | 3/8 | 9.5 | 1/2–14 | 27 | 1.73 | 44.0 | .63 | 16.1 |
| G25855-0808 | 8G-8FBFFX | 7100-96605 | 1/2 | 12.7 | 1/2–14 | 27 | 2.11 | 53.5 | .63 | 16.0 |
| G25855-0812 | 8G-12FBFFX | 7100-96625 | 1/2 | 12.7 | 3/4–14 | 32 | 2.03 | 51.5 | .55 | 14.0 |
| G25855-1012 | 10G-12FBFFX | 7100-99515 | 5/8 | 15.9 | 3/4–14 | 32 | 2.05 | 52.0 | .58 | 14.5 |
| G25855-1212 | 12G-12FBFFX | 7100-93325 | 3/4 | 19.1 | 3/4–14 | 32 | 2.07 | 52.6 | 1.04 | 26.4 |

# Female Komatsu Style Japanese Metric Swivel

These female swivels have been marked with two small notches on the hex to identify them as the Komatsu style.








| Part No. | Descr. | Prod. No. | ⟷ | | ⌇⌇⌇ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G25910-0404 | 4G-4FKX | 7100-03625 | 1/4 | 6.4 | M14X1.5 | 14 | 19 | 2.35 | 59.7 | 1.33 | 33.7 |
| G25910-0406 | 4G-6FKX | 7100-03635 | 1/4 | 6.4 | M18X1.5 | 14 | 24 | 2.44 | 62.0 | 1.42 | 36.0 |
| G25910-0606 | 6G-6FKX | 7100-03645 | 3/8 | 9.5 | M18X1.5 | 17 | 24 | 2.52 | 64.0 | 1.42 | 36.1 |
| G25910-0808 | 8G-8FKX | 7100-03655 | 1/2 | 12.7 | M22X1.5 | 22 | 27 | 3.07 | 78.1 | 1.60 | 40.6 |
| G25910-1010 | 10G-10FKX | 7100-03665 | 5/8 | 15.9 | M24X1.5 | 24 | 32 | 3.21 | 81.5 | 1.73 | 44.0 |
| G25910-1212 | 12G-12FKX | 7100-03675 | 3/4 | 19.1 | M30X1.5 | 30 | 36 | 3.95 | 100.3 | 1.94 | 49.3 |
| G25910-1616 | 16G-16FKX | 7100-03685 | 1 | 25.4 | M33X1.5 | 41 | 41 | 4.57 | 116.0 | 2.33 | 59.2 |
| G25910-2020 | 20G-20FKX | 7100-03775 | 1 1/4 | 31.8 | M36X1.5 | 44.5 | 50.8 | 4.82 | 122.4 | 2.44 | 62.0 |

# Female Komatsu Style Japanese Metric Swivel - 45° Bent Tube

These female swivels have been marked with two small notches on the hex to identify them as the Komatsu style.




| Part No. | Descr. | Prod. No. | ⟷ | | ⌇⌇⌇ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25911-0404 | 4G-4FKX45 | 7100-03035 | 1/4 | 6.4 | M14X1.5 | 19 | .75 | 19.1 | 2.93 | 74.3 | 1.90 | 48.3 |
| G25911-0606 | 6G-6FKX45 | 7100-03045 | 3/8 | 9.5 | M18X1.5 | 24 | 1.10 | 28.0 | 3.64 | 92.4 | 2.54 | 64.4 |
| G25911-0808 | 8G-8FKX45 | 7100-03055 | 1/2 | 12.7 | M22X1.5 | 27 | .71 | 18.0 | 3.85 | 97.7 | 2.37 | 60.3 |
| G25911-1010 | 10G-10FKX45 | 7100-03065 | 5/8 | 15.9 | M24X1.5 | 32 | 1.10 | 28.0 | 4.70 | 119.3 | 3.22 | 81.8 |
| G25911-1212 | 12G-12FKX45 | 7100-03075 | 3/4 | 19.1 | M30X1.5 | 36 | 1.18 | 30.0 | 5.64 | 143.2 | 3.63 | 92.2 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female Komatsu Style Japanese Metric Swivel - 90° Bent Tube


These female swivels have been marked with two small notches on the hex to identify them as the Komatsu style.





| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H1 | H2 | | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm | " | mm |
| G25913-0404 | 4G-4FKX90 | 7100-03125 | 1/4 | 6.4 | M14X1.5 | — | — | 19 | 1.50 | 38.0 | 2.47 | 62.7 | 1.44 | 36.7 |
| G25913-0606 | 6G-6FKX90 | 7100-03135 | 3/8 | 9.5 | M18X1.5 | — | — | 24 | 1.10 | 28.0 | 2.72 | 69.1 | 1.62 | 41.2 |
| G25913-0808 | 8G-8FKX90 | 7100-03145 | 1/2 | 12.7 | M22X1.5 | — | — | 27 | 1.38 | 35.0 | 3.63 | 92.2 | 2.15 | 54.7 |
| G25913-1010 | 10G-10FKX90 | 7100-06795 | 5/8 | 15.9 | M24X1.5 | 15/16 | 1 1/4 | — | 2.57 | 65.3 | 3.43 | 87.0 | 1.95 | 49.5 |
| G25913-1212 | 12G-12FKX90 | 7100-03165 | 3/4 | 19.1 | M30X1.5 | — | — | 36 | 2.48 | 63.0 | 5.33 | 135.5 | 3.33 | 84.5 |


# Female Japanese Industrial Standard Swivel





| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G25930-0404 | 4G-4FJISX | 7100-03305 | 1/4 | 6.4 | 1/4–19 | 14 | 19 | 2.32 | 59.0 | 1.30 | 33.0 |
| G25930-0606 | 6G-6FJISX | 7100-03325 | 3/8 | 9.5 | 3/8–19 | 17 | 22 | 2.46 | 62.5 | 1.36 | 34.6 |
| G25930-0808 | 8G-8FJISX | 7100-03345 | 1/2 | 12.7 | 1/2–14 | 22 | 27 | 3.15 | 79.9 | 1.67 | 42.4 |
| G25930-1212 | 12G-12FJISX | 7100-03365 | 3/4 | 19.1 | 3/4–14 | 30 | 36 | 3.79 | 96.3 | 1.78 | 45.3 |
| G25930-1616 | 16G-16FJISX | 7100-03385 | 1 | 25.4 | 1–11 | 41 | 41 | 4.28 | 108.6 | 2.04 | 51.8 |
| G25930-2020 | 20G-20FJISX | 7100-03405 | 1 1/4 | 31.8 | 1 1/4–11 | 50 | 50 | 4.89 | 124.1 | 2.56 | 65.1 |

# Female Japanese Inverted Flare Parallel Threads




| Part No. | Descr. | Prod. No. | ⟷ | | ⫼ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G25932-0404 | 4G-4FJISPX | 7100-20445 | 1/4 | 6.4 | 1/4–19 | 15 | 19 | 2.01 | 51.0 | .98 | 25.0 |
| G25932-0606 | 6G-6FJISPX | 7100-20455 | 3/8 | 9.5 | 3/8–19 | 18 | 22 | 2.17 | 55.0 | 1.03 | 26.2 |
| G25932-0808 | 8G-8JISPX | 7100-20465 | 1/2 | 12.7 | 1/2–14 | 22 | 27 | 2.56 | 65.0 | 1.16 | 29.5 |
| G25932-1212 | 12G-12JISPX | 7100-20485 | 3/4 | 19.1 | 3/4–14 | 30 | 36 | 3.37 | 85.5 | 1.36 | 34.5 |
| G25932-1616 | 16G-16JISPX | 7100-20495 | 1 | 25.4 | 1–11 | 41 | 41 | 3.84 | 97.5 | 1.60 | 40.7 |
| G25932-2020 | 20G-20FJISPX | 7100-20505 | 1 1/4 | 31.8 | 1 1/4–11 | 41 | 50 | 4.29 | 109.0 | 1.97 | 50.0 |

# Male Quick-Lok® High





| Part No. | Descr. | Prod. No. | ⟷ | | L | | C | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G25970-0404 | 4G-4MQLH | 7209-32005 | 1/4 | 6.4 | 2.64 | 67.0 | 1.61 | 41.0 |
| G25970-0606 | 6G-6MQLH | 7209-32025 | 3/8 | 9.5 | 2.72 | 69.0 | 1.62 | 41.1 |
| G25970-0808 | 8G-8MQLH | 7209-32055 | 1/2 | 12.7 | 3.11 | 79.0 | 1.63 | 41.5 |
| G25970-1010 | 10G-10MQLH | 7209-32085 | 5/8 | 15.9 | 3.11 | 79.0 | 1.63 | 41.5 |
| G25970-1212 | 12G-12MQLH | 7209-32105 | 3/4 | 19.1 | 3.66 | 93.0 | 1.65 | 42.0 |
| G25970-1616 | 16G-16MQLH | 7209-32125 | 1 | 25.4 | 3.98 | 101.0 | 1.74 | 44.2 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Quick-Lok® High - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G25971-0404 | 4G-4MQLH45S-008 | 7209-33005 | 1/4 | 6.4 | .30 | 7.5 | 2.96 | 75.1 | 1.93 | 49.1 |
| G25971-0606 | 6G-6MQLH45S-008 | 7209-33015 | 3/8 | 9.5 | .33 | 8.4 | 3.21 | 81.6 | 2.11 | 53.7 |
| G25971-0808 | 8G-8MQLH45S-010 | 7209-33025 | 1/2 | 12.7 | .41 | 10.4 | 3.77 | 95.7 | 2.29 | 58.2 |
| G25971-1010 | 10G-10MQLH45S-013 | 7209-33045 | 5/8 | 15.9 | .50 | 12.7 | 4.12 | 104.6 | 2.64 | 67.1 |
| G25971-1212 | 12G-12MQLH45S-014 | 7209-33055 | 3/4 | 19.1 | .56 | 14.2 | 4.88 | 124.0 | 2.87 | 73.0 |
| G25971-1616 | 16G-16MQLH45S-017 | 7209-33065 | 1 | 25.4 | .66 | 16.8 | 5.49 | 139.5 | 3.26 | 82.7 |

# Male Quick-Lok® High - 90° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G25972-0404 | 4G-4MQLH90S-018 | 7209-34005 | 1/4 | 6.4 | .71 | 18.0 | 2.19 | 55.6 | 1.17 | 29.6 |
| G25973-0404 | 4G-4MQLH90L-039 | 7209-34015 | 1/4 | 6.4 | 1.54 | 39.0 | 2.19 | 55.6 | 1.17 | 29.6 |
| G25972-0606 | 6G-6MQLH90S-020 | 7209-34045 | 3/8 | 9.5 | .79 | 20.1 | 2.47 | 62.8 | 1.37 | 34.8 |
| G25973-0606 | 6G-6MQLH90L-046 | 7209-34055 | 3/8 | 9.5 | 1.79 | 45.5 | 2.40 | 60.9 | 1.30 | 32.9 |
| G25972-0808 | 8G-8MQLH90S-026 | 7209-34085 | 1/2 | 12.7 | 1.01 | 25.6 | 3.16 | 80.3 | 1.69 | 42.9 |
| G25973-0808 | 8G-8MQLH90L-057 | 7209-34095 | 1/2 | 12.7 | 2.22 | 56.5 | 3.04 | 77.1 | 1.56 | 39.7 |
| G25972-1010 | 10G-10MQLH90S-033 | 7209-34115 | 5/8 | 15.9 | 1.29 | 32.8 | 3.55 | 90.1 | 2.07 | 52.6 |
| G25973-1010 | 10G-10MQLH90L-065 | 7209-34125 | 5/8 | 15.9 | 2.56 | 65.0 | 3.72 | 94.4 | 2.24 | 57.0 |
| G25972-1212 | 12G-12MQLH90S-037 | 7209-34155 | 3/4 | 19.1 | 1.45 | 36.8 | 4.33 | 110.1 | 2.33 | 59.1 |
| G25973-1212 | 12G-12MQLH90L-075 | 7209-34165 | 3/4 | 19.1 | 2.93 | 74.5 | 4.20 | 106.7 | 2.19 | 55.7 |
| G25972-1616 | 16G-16MQLH90S-044 | 7209-34195 | 1 | 25.4 | 1.72 | 43.8 | 5.48 | 139.1 | 3.24 | 82.3 |
| G25973-1616 | 16G-16MQLH90L-103 | 7209-34215 | 1 | 25.4 | 4.06 | 103.0 | 4.87 | 123.7 | 2.63 | 66.9 |

# Female Quick-Lok® High to Male O-Ring Boss Adapter




| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | L | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G25974-0404 | 4FQLH-4MB | 7209-05025 | 1/4 | 6.4 | 7/16–20 | 19 | 1.65 | 42.0 |
| G25974-0406 | 4FQLH-6MB | 7209-05035 | 1/4 | 6.4 | 9/16–18 | 19 | 1.65 | 42.0 |
| G25974-0604 | 6FQLH-4MB | 7209-05075 | 3/8 | 9.5 | 7/16–20 | 22 | 1.65 | 42.0 |
| G25974-0606 | 6FQLH-6MB | 7209-05085 | 3/8 | 9.5 | 9/16–18 | 22 | 1.69 | 43.0 |
| G25974-0608 | 6FQLH-8MB | 7209-05095 | 3/8 | 9.5 | 3/4–16 | 24 | 1.69 | 43.0 |
| G25974-0806 | 8FQLH-6MB | 7209-05135 | 1/2 | 12.7 | 9/16–18 | 24 | 1.71 | 43.5 |
| G25974-0808 | 8FQLH-8MB | 7209-05145 | 1/2 | 12.7 | 3/4–16 | 24 | 1.75 | 44.5 |
| G25974-0810 | 8FQLH-10MB | 7209-05155 | 1/2 | 12.7 | 7/8–14 | 27 | 1.81 | 46.0 |
| G25974-1008 | 10FQLH-8MB | 7209-05195 | 5/8 | 15.9 | 3/4–16 | 27 | 1.85 | 47.0 |
| G25974-1010 | 10FQLH-10MB | 7209-05205 | 5/8 | 15.9 | 7/8–14 | 27 | 1.85 | 47.0 |
| G25974-1012 | 10FQLH-12MB | 7209-05215 | 5/8 | 15.9 | 1 1/16–12 | 32 | 1.89 | 48.0 |
| G25974-1210 | 12FQLH-10MB | 7209-05255 | 3/4 | 19.1 | 7/8–14 | 32 | 1.89 | 48.0 |
| G25974-1212 | 12FQLH-12MB | 7209-05265 | 3/4 | 19.1 | 1 1/16–12 | 32 | 1.97 | 50.0 |
| G25974-1216 | 12FQLH-16MB | 7209-05275 | 3/4 | 19.1 | 1 5/16–12 | 41 | 1.97 | 50.0 |
| G25974-1612 | 16FQLH-12MB | 7209-05315 | 1 | 25.4 | 1 1/16–12 | 41 | 2.09 | 53.0 |
| G25974-1616 | 16FQLH-16MB | 7209-05325 | 1 | 25.4 | 1 5/16–12 | 41 | 1.97 | 50.0 |

# Female Quick-Lok® High to Female JIC 37° Flare





| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | L | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G25976-0404 | 4FQLH-4FJ | 7209-07505 | 1/4 | 6.4 | 7/16–20 | 19 | 1.69 | 42.9 |
| G25976-0606 | 6FQLH-6FJ | 7209-07535 | 3/8 | 9.5 | 9/16–18 | 22 | 1.69 | 42.9 |
| G25976-0808 | 8FQLH-8FJ | 7209-07565 | 1/2 | 12.7 | 3/4–16 | 24 | 1.81 | 46.0 |
| G25976-1010 | 10FQLH-10FJ | 7209-07595 | 5/8 | 15.9 | 7/8–14 | 27 | 1.93 | 49.0 |
| G25976-1616 | 16FQLH-16FJ | 7209-07655 | 1 | 25.4 | 1 5/16–12 | 41 | 2.11 | 53.6 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female Quick-Lok® High to Female Flat-Face





| Part No. | Descr. | Prod. No. | ⊖ | | ≋ | H1 | L | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G25978-0606 | 6FQLH-6FFOR | 7209-07695 | 3/8 | 9.5 | 11/16–16 | 22 | 1.60 | 40.6 |
| G25978-0808 | 8FQLH-8FFOR | 7209-07705 | 1/2 | 12.7 | 13/16–16 | 24 | 1.66 | 42.2 |
| G25978-1010 | 10FQLH-10FFOR | 7209-07715 | 5/8 | 15.9 | 1–14 | 30 | 1.71 | 43.4 |
| G25978-1212 | 12FQLH-12FFOR | 7209-07725 | 3/4 | 19.1 | 1 3/16–12 | 36 | 1.77 | 45.0 |

# Male Quick-Lok® Low





| Part No. | Descr. | Prod. No. | ⊖ | | L | | C | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| G25980-0406 | 4G-6MQLL | 7101-51225 | 1/4 | 6.4 | 2.68 | 68.0 | 1.65 | 42.0 |
| G25980-0606 | 6G-6MQLL | 7101-51015 | 3/8 | 9.5 | 2.76 | 70.0 | 1.66 | 42.1 |
| G25980-0808 | 8G-8MQLL | 7101-50745 | 1/2 | 12.7 | 3.43 | 87.0 | 1.95 | 49.5 |
| G25980-1212 | 12G-12MQLL | 7101-51595 | 3/4 | 19.1 | 4.06 | 103.0 | 2.05 | 52.0 |
| G25980-1616 | 16G-16MQLL | 7101-51515 | 1 | 25.4 | 4.53 | 115.0 | 2.29 | 58.2 |

# Male Quick-Lok® Low - 45° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G25981-0406 | 4G-6MQLL45-026 | 7101-51235 | 1/4 | 6.4 | 1.02 | 26.0 | 2.85 | 72.5 | 1.83 | 46.5 |
| G25981-0808 | 8G-8MQLL45-033 | 7101-50765 | 1/2 | 12.7 | 1.30 | 33.0 | 3.94 | 100.0 | 2.46 | 62.5 |
| G25981-1212 | 12G-12MQLL45-030 | 7101-51605 | 3/4 | 19.1 | 1.18 | 30.0 | 5.04 | 128.0 | 3.03 | 77.0 |
| G25981-1212 | 12G-12MQLL45-038 | 7101-52325 | 3/4 | 19.1 | 1.50 | 38.1 | 5.35 | 135.9 | 3.35 | 85.1 |

# Male Quick-Lok® Low - 90° Bent Tube






| Part No. | Descr. | Prod. No. | ⊖ | | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| G25982-0406 | 4G-6MQLL90-037 | 7101-51245 | 1/4 | 6.4 | 1.46 | 37.0 | 2.26 | 57.3 | 1.23 | 31.3 |
| G25982-0606 | 6G-6MQLL90-051 | 7101-52265 | 3/8 | 9.5 | 2.01 | 51.0 | 2.60 | 66.0 | 1.50 | 38.0 |
| G25983-0606 | 6G-6MQLL90-117 | 7101-51935 | 3/8 | 9.5 | 4.61 | 117.0 | 2.60 | 66.0 | 1.50 | 38.1 |
| G25984-0606 | 6G-6MQLL90-168 | 7101-51775 | 3/8 | 9.5 | 7.09 | 180.0 | 2.60 | 66.0 | 1.50 | 38.1 |
| G25982-0808 | 8G-8MQLL90-050 | 7101-51475 | 1/2 | 12.7 | 1.97 | 50.0 | 3.35 | 85.0 | 1.87 | 47.5 |
| G25982-1212 | 12G-12MQLL90-061 | 7101-51615 | 3/4 | 19.1 | 2.40 | 61.0 | 4.25 | 108.0 | 2.24 | 57.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Male Pipe (NPTF - 30° Cone Seat)





| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G25100-0402T | 4G-2MP-TCX | 7321-50905 | 1/4 | 6.4 | 1/8–27 | 1/2 | 1.96 | 49.8 | .94 | 23.9 |
| G25100-0404T | 4G-4MP-TCX | 7321-50865 | 1/4 | 6.4 | 1/4–18 | 9/16 | 2.17 | 55.0 | 1.14 | 29.0 |
| G25100-0406T | 4G-6MP-TCX | 7321-50885 | 1/4 | 6.4 | 3/8–18 | 11/16 | 2.17 | 55.0 | 1.14 | 29.0 |
| G25100-0408T | 4G-8MP-TCX | 7321-50925 | 1/4 | 6.4 | 1/2–14 | 7/8 | 2.44 | 62.0 | 1.41 | 35.8 |
| G25100-0604T | 6G-4MP-TCX | 7321-50915 | 3/8 | 9.5 | 1/4–18 | 5/8 | 2.32 | 58.9 | 1.22 | 31.0 |
| G25100-0606T | 6G-6MP-TCX | 7321-50855 | 3/8 | 9.5 | 3/8–18 | 11/16 | 2.32 | 58.9 | 1.22 | 31.0 |
| G25100-0608T | 6G-8MP-TCX | 7321-50945 | 3/8 | 9.5 | 1/2–14 | 7/8 | 2.51 | 63.8 | 1.42 | 36.1 |
| G25100-0806T | 8G-6MP-TCX | 7321-50935 | 1/2 | 12.7 | 3/8–18 | 13/16 | 2.72 | 69.0 | 1.24 | 31.5 |
| G25100-0808T | 8G-8MP-TCX | 7321-50845 | 1/2 | 12.7 | 1/2–14 | 7/8 | 2.87 | 73.0 | 1.40 | 35.5 |
| G25100-0812T | 8G-12MP-TCX | 7321-50955 | 1/2 | 12.7 | 3/4–14 | 1 1/16 | 2.95 | 74.9 | 1.47 | 37.3 |
| G25100-1008T | 10G-8MP-TCX | 7321-50995 | 5/8 | 15.9 | 1/2–14 | 15/16 | 2.95 | 75.0 | 1.48 | 37.5 |
| G25100-1012T | 10G-12MP-TCX | 7321-51015 | 5/8 | 15.9 | 3/4–14 | 1 1/16 | 2.95 | 75.0 | 1.48 | 37.5 |
| G25100-1208T | 12G-8MP-TCX | 7321-50985 | 3/4 | 19.1 | 1/2–14 | 1 1/16 | 3.46 | 87.9 | 1.45 | 36.8 |
| G25100-1212T | 12G-12MP-TCX | 7321-50875 | 3/4 | 19.1 | 3/4–14 | 1 1/16 | 3.46 | 87.9 | 1.45 | 36.8 |
| G25100-1216T | 12G-16MP-TCX | 7321-50975 | 3/4 | 19.1 | 1–11 1/2 | 1 3/8 | 3.77 | 95.8 | 1.77 | 45.0 |
| G25100-1612T | 16G-12MP-TCX | 7321-51005 | 1 | 25.4 | 3/4–14 | 1 3/8 | 3.93 | 99.8 | 1.70 | 43.2 |
| G25100-1616T | 16G-16MP-TCX | 7321-50895 | 1 | 25.4 | 1–11 1/2 | 1 3/8 | 4.11 | 104.4 | 1.87 | 47.5 |
| G25100-2020T | 20G-20MP-TCX | 7321-50965 | 1 1/4 | 31.8 | 1 1/4–11 1/2 | 1 3/4 | 4.44 | 112.8 | 2.12 | 53.8 |


# Female Pipe (NPTF - without 30° Cone Seat)





| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G25110-0402T | 4G-2FP-TCX | 7321-51055 | 1/4 | 6.4 | 1/8–27 | 9/16 | 1.74 | 44.2 | .72 | 18.3 |
| G25110-0404T | 4G-4FP-TCX | 7321-51025 | 1/4 | 6.4 | 1/4–18 | 11/16 | 1.98 | 50.3 | .96 | 24.4 |
| G25110-0604T | 6G-4FP-TCX | 7321-50335 | 3/8 | 9.5 | 1/4–18 | 11/16 | 2.00 | 50.8 | .90 | 22.9 |
| G25110-0606T | 6G-6FP-TCX | 7321-51035 | 3/8 | 9.5 | 3/8–18 | 13/16 | 2.06 | 52.3 | .96 | 24.4 |
| G25110-0608T | 6G-8FP-TCX | 7321-51065 | 3/8 | 9.5 | 1/2–14 | 1 | 2.24 | 56.9 | 1.14 | 29.0 |
| G25110-0806T | 8G-6FP-TCX | 7321-50385 | 1/2 | 12.7 | 3/8–18 | 13/16 | 2.46 | 62.5 | .98 | 24.9 |
| G25110-0808T | 8G-8FP-TCX | 7321-51045 | 1/2 | 12.7 | 1/2–14 | 1 | 2.63 | 66.8 | 1.16 | 29.5 |
| G25110-1212T | 12G-12FP-TCX | 7321-51075 | 3/4 | 19.1 | 3/4–14 | 1.25 | 3.22 | 81.8 | 1.22 | 31.0 |


## Male JIC 37° Flare




| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm |
| G25165-1212T | 12G-12MJ-TCX | 7321-52195 | 3/4 | 19.1 | 1 1/16–12 | | 27 | 3.72 | 94.5 | 1.71 | 43.5 |

## Female JIC 37° Flare Swivel









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | mm | " | mm | " | mm |
| G25170-0404T | 4G-4FJX-TCX | 7321-51105 | 1/4 | 6.4 | 7/16–20 | | 15 | 14 | 2.20 | 55.9 | 1.18 | 29.9 |
| G25170-0405T | 4G-5FJX-TCX | 7321-51215 | 1/4 | 6.4 | 1/2–20 | | 15 | 17 | 2.30 | 58.3 | 1.27 | 32.3 |
| G25170-0406T | 4G-6FJX-TCX | 7321-51135 | 1/4 | 6.4 | 9/16–18 | | 15 | 19 | 2.35 | 59.6 | 1.32 | 33.6 |
| G25170-0606T | 6G-6FJX-TCX | 7321-51085 | 3/8 | 9.5 | 9/16–18 | | 18 | 19 | 2.42 | 61.5 | 1.29 | 32.7 |
| G25170-0608T | 6G-8FJX-TCX | 7321-51125 | 3/8 | 9.5 | 3/4–16 | | 18 | 24 | 2.63 | 66.7 | 1.49 | 37.9 |
| G25170-0610T | 6G-10FJX-TCX | 7321-51205 | 3/8 | 9.5 | 7/8–14 | | 18 | 27 | 2.76 | 70.0 | 1.62 | 41.2 |
| G25170-0806T | 8G-6FJX-TCX | 7321-51225 | 1/2 | 12.7 | 9/16–18 | | 22 | 19 | 3.81 | 96.7 | 2.33 | 59.2 |
| G25170-0808T | 8G-8FJX-TCX | 7321-51095 | 1/2 | 12.7 | 3/4–16 | | 22 | 24 | 2.88 | 73.2 | 1.50 | 38.0 |
| G25170-0810T | 8G-10FJX-TCX | 7321-51145 | 1/2 | 12.7 | 7/8–14 | | 22 | 27 | 3.01 | 76.5 | 1.63 | 41.3 |
| G25170-0812T | 8G-12FJX-TCX | 7321-51185 | 1/2 | 12.7 | 1 1/16–12 | | 22 | 32 | 3.06 | 77.7 | 1.67 | 42.5 |
| G25170-1008T | 10G-8FJX-TCX | 7321-51255 | 5/8 | 15.9 | 3/4–16 | | 24 | 24 | 4.06 | 103.0 | 2.58 | 65.5 |
| G25170-1010T | 10G-10FJX-TCX | 7321-51165 | 5/8 | 15.9 | 7/8–14 | | 24 | 27 | 3.14 | 79.7 | 1.66 | 42.2 |
| G25170-1012T | 10G-12FJX-TCX | 7321-50535 | 5/8 | 15.9 | 1 1/16–12 | | 24 | 32 | 3.20 | 81.4 | 1.73 | 43.9 |
| G25170-1210T | 12G-10FJX-TCX | 7321-51235 | 3/4 | 19.1 | 7/8–14 | | 27 | 27 | 4.80 | 122.0 | 2.80 | 71.0 |
| G25170-1212T | 12G-12FJX-TCX | 7321-51115 | 3/4 | 19.1 | 1 1/16–12 | | 30 | 32 | 3.74 | 95.0 | 1.73 | 44.0 |
| G25170-1214T | 12G-14FJX-TCX | 7321-51295 | 3/4 | 19.1 | 1 3/16–12 | | 30 | 36 | 3.81 | 96.9 | 1.81 | 45.9 |
| G25170-1216T | 12G-16FJX-TCX | 7321-51195 | 3/4 | 19.1 | 1 5/16–12 | | 30 | 41 | 3.85 | 97.9 | 1.85 | 46.9 |
| G25170-1612T | 16G-12FJX-TCX | 7321-51245 | 1 | 25.4 | 1 1/16–12 | | 36 | 32 | 5.89 | 149.5 | 3.65 | 92.7 |
| G25170-1616T | 16G-16FJX-TCX | 7321-51155 | 1 | 25.4 | 1 5/16–12 | | 36 | 41 | 4.24 | 107.8 | 2.01 | 51.0 |
| G25170-1620T | 16G-20FJX-TCX | 7321-51305 | 1 | 25.4 | 1 5/8–12 | | 36 | 50 | 4.54 | 115.3 | 2.30 | 58.5 |
| G25170-2020T | 20G-20FJX-TCX | 7321-51175 | 1 1/4 | 31.8 | 1 5/8–12 | | 41 | 50 | 4.42 | 112.3 | 2.09 | 53.3 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Female JIC 37° Flare Swivel - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | ≡ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25174-0406T | 4G-6FJX45S-TCX | 7321-51375 | 1/4 | 6.4 | 9/16–18 | 19 | .43 | 11.0 | 2.69 | 68.3 | 1.67 | 42.3 |
| G25174-0606T | 6G-6FJX45S-TCX | 7321-51325 | 3/8 | 9.5 | 9/16–18 | 19 | .43 | 11.0 | 3.05 | 77.5 | 1.95 | 49.6 |
| G25174-0608T | 6G-8FJX45S-TCX | 7321-51385 | 3/8 | 9.5 | 3/4–16 | 24 | .59 | 15.0 | 3.51 | 89.1 | 2.41 | 61.2 |
| G25174-0808T | 8G-8FJX45S-TCX | 7321-51335 | 1/2 | 12.7 | 3/4–16 | 24 | .59 | 15.0 | 3.42 | 86.9 | 1.95 | 49.5 |
| G25174-0810T | 8G-10FJX45S-TCX | 7321-51365 | 1/2 | 12.7 | 7/8–14 | 27 | .63 | 16.0 | 3.81 | 96.8 | 2.34 | 59.4 |
| G25174-1010T | 10G-10FJX45S-TCX | 7321-51405 | 5/8 | 15.9 | 7/8–14 | 27 | .63 | 16.0 | 3.80 | 96.4 | 2.32 | 59.0 |
| G25174-1012T | 10G-12FJX45S-TCX | 7321-51415 | 5/8 | 15.9 | 1 1/16–12 | 32 | .83 | 21.0 | 4.57 | 116.0 | 3.09 | 78.5 |
| G25174-1212T | 12G-12FJX45S-TCX | 7321-51345 | 3/4 | 19.1 | 1 1/16–12 | 32 | .83 | 21.0 | 5.09 | 129.2 | 3.08 | 78.2 |


# Female JIC 37° Flare Swivel - 90° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | ≡ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25180-0808T | 8G-8FJX90M-TCX | 7321-51735 | 1/2 | 12.7 | 3/4–16 | 24 | 1.61 | 40.1 | 3.04 | 77.2 | 1.30 | 33.0 |
| G25180-1010T | 10G-10FJX90M-TCX | 7321-51745 | 5/8 | 15.9 | 7/8–14 | 27 | 1.86 | 47.2 | 3.63 | 92.2 | 2.15 | 54.6 |

# Female Flat-Face O-Ring Swivel




| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | mm | " | mm | " | mm |
| G25230-0404T | 4G-4FFORX-TCX | 7321-50305 | 1/4 | 6.4 | 9/16–18 | 15 | 17 | 2.07 | 52.7 | 1.05 | 26.7 |
| G25230-0406T | 4G-6FFORX-TCX | 7321-50325 | 1/4 | 6.4 | 11/16–16 | 15 | 22 | 2.01 | 51.1 | .99 | 25.1 |
| G25230-0604T | 6G-4FFORX-TCX | 7321-50445 | 3/8 | 9.5 | 9/16–18 | 17 | 17 | 3.08 | 78.3 | 1.98 | 50.3 |
| G25230-0606T | 6G-6FFORX-TCX | 7321-50015 | 3/8 | 9.5 | 11/16–16 | 18 | 22 | 2.27 | 57.7 | 1.14 | 28.9 |
| G25230-0608T | 6G-8FFORX-TCX | 7321-50345 | 3/8 | 9.5 | 13/16–16 | 18 | 24 | 2.26 | 57.4 | 1.13 | 28.6 |
| G25230-0806T | 8G-6FFORX-TCX | 7321-50375 | 1/2 | 12.7 | 11/16–16 | 22 | 22 | 3.78 | 95.9 | 2.30 | 58.4 |
| G25230-0808T | 8G-8FFORX-TCX | 7321-50425 | 1/2 | 12.7 | 13/16–16 | 22 | 24 | 2.62 | 66.5 | 1.23 | 31.3 |
| G25230-0810T | 8G-10FFORX-TCX | 7321-50755 | 1/2 | 12.7 | 1–14 | 22 | 30 | 2.76 | 70.0 | 1.37 | 34.8 |
| G25230-0812T | 8G-12FFORX-TCX | 7321-50355 | 1/2 | 12.7 | 1 3/16–12 | 22 | 36 | 2.81 | 71.5 | 1.43 | 36.3 |
| G25230-1010T | 10G-10FFORX-TCX | 7321-50545 | 5/8 | 15.9 | 1–14 | 24 | 30 | 2.99 | 76.0 | 1.52 | 38.5 |
| G25230-1012T | 10G-12FFORX-TCX | 7321-50635 | 5/8 | 15.9 | 1 3/16–12 | 24 | 36 | 3.03 | 77.0 | 1.56 | 39.5 |
| G25230-1210T | 12G-10FFORX-TCX | 7321-50125 | 3/4 | 19.1 | 1–14 | 30 | 30 | 3.74 | 95.1 | 1.74 | 44.1 |
| G25230-1212T | 12G-12FFORX-TCX | 7321-50025 | 3/4 | 19.1 | 1 3/16–12 | 30 | 36 | 3.65 | 92.8 | 1.65 | 41.8 |
| G25230-1216T | 12G-16FFORX-TCX | 7321-50465 | 3/4 | 19.1 | 1 7/16–12 | 30 | 41 | 3.48 | 88.3 | 1.47 | 37.3 |
| G25230-1616T | 16G-16FFORX-TCX | 7321-50205 | 1 | 25.4 | 1 7/16–12 | 36 | 41 | 4.09 | 104.0 | 1.86 | 47.2 |
| G25230-1620T | 16G-20FFORX-TCX | 7321-50215 | 1 | 25.4 | 1 11/16–12 | 36 | 50 | 4.06 | 103.0 | 1.82 | 46.2 |
| G25230-2020T | 20G-20FFORX-TCX | 7321-50255 | 1 1/4 | 31.8 | 1 11/16–12 | 41 | 50 | 4.29 | 109.0 | 1.97 | 50.0 |

# Female Flat-Face O-Ring Swivel - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm | " | mm |
| G25235-0404T | 4G-4FFORX45S-TCX | 7321-50275 | 1/4 | 6.4 | 9/16–18 | 17 | .39 | 10.0 | 2.57 | 65.2 | 1.54 | 39.2 |
| G25235-0406T | 4G-6FFORX45S-TCX | 7321-50475 | 1/4 | 6.4 | 11/16–16 | 22 | .43 | 11.0 | 2.70 | 68.5 | 1.67 | 42.5 |
| G25235-0604T | 6G-4FFORX45S-TCX | 7321-50695 | 3/8 | 9.5 | 9/16–18 | 17 | .39 | 10.0 | 2.60 | 66.1 | 1.50 | 38.1 |
| G25235-0606T | 6G-6FFORX45S-TCX | 7321-50035 | 3/8 | 9.5 | 11/16–16 | 22 | .43 | 11.0 | 2.75 | 69.8 | 1.65 | 41.9 |
| G25235-0608T | 6G-8FFORX45S-TCX | 7321-50045 | 3/8 | 9.5 | 13/16–16 | 24 | .59 | 15.0 | 3.35 | 85.2 | 2.26 | 57.3 |
| G25235-0808T | 8G-8FFORX45S-TCX | 7321-50395 | 1/2 | 12.7 | 13/16–16 | 24 | .59 | 15.0 | 3.50 | 89.0 | 2.03 | 51.6 |
| G25235-0810T | 8G-10FFORX45S-TCX | 7321-50765 | 1/2 | 12.7 | 1–14 | 30 | .63 | 16.0 | 3.98 | 101.0 | 2.50 | 63.5 |
| G25235-1010T | 10G-10FFORX45S-TCX | 7321-50625 | 5/8 | 15.9 | 1–14 | 30 | .63 | 16.0 | 3.96 | 100.5 | 2.48 | 63.0 |
| G25235-1210T | 12G-10FFORX45S-TCX | 7321-50055 | 3/4 | 19.1 | 1–14 | 30 | .63 | 16.0 | 4.45 | 113.0 | 2.44 | 62.0 |

## Female Flat-Face O-Ring Swivel - 45° Bent Tube - Continued


| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25235-1212T | 12G-12FFORX45S-TCX | 7321-50065 | 3/4 | 19.1 | 1 3/16–12 | 36 | .83 | 21.0 | 4.66 | 118.4 | 2.65 | 67.4 |
| G25235-1216T | 12G-16FFORX45S-TCX | 7321-50585 | 3/4 | 19.1 | 1 7/16–12 | 41 | .94 | 24.0 | 4.80 | 122.0 | 2.80 | 71.0 |
| G25235-1616T | 16G-16FFORX45S-TCX | 7321-50165 | 1 | 25.4 | 1 7/16–12 | 41 | .94 | 24.0 | 5.78 | 146.9 | 3.55 | 90.1 |
| G25235-2020T | 20G-20FFORX45S-TCX | 7321-50225 | 1 1/4 | 31.8 | 1 11/16–12 | 50 | .98 | 25.0 | 6.22 | 158.0 | 3.90 | 99.0 |

## Female Flat-Face O-Ring Swivel - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25239-0404T | 4G-4FFORX90S-TCX | 7321-50435 | 1/4 | 6.4 | 9/16–18 | 17 | .83 | 21.0 | 2.37 | 60.2 | 1.35 | 34.2 |
| G25239-0406T | 4G-6FFORX90S-TCX | 7321-50715 | 1/4 | 6.4 | 11/16–16 | 22 | .91 | 23.0 | 2.50 | 63.4 | 1.47 | 37.4 |
| G25239-0606T | 6G-6FFORX90S-TCX | 7321-50495 | 3/8 | 9.5 | 11/16–16 | 22 | .91 | 23.0 | 2.85 | 72.5 | 1.76 | 44.6 |
| G25239-0608T | 6G-8FFORX90S-TCX | 7321-50815 | 3/8 | 9.5 | 13/16–16 | 24 | 1.14 | 29.0 | 2.87 | 73.0 | 1.78 | 45.1 |
| G25239-0808T | 8G-8FFORX90S-TCX | 7321-50645 | 1/2 | 12.7 | 13/16–16 | 24 | 1.14 | 29.0 | 3.30 | 83.9 | 1.83 | 46.5 |
| G25239-0810T | 8G-10FFORX90S-TCX | 7321-50835 | 1/2 | 12.7 | 1–14 | 30 | 1.26 | 32.0 | 3.66 | 92.9 | 2.18 | 55.4 |
| G25239-1010T | 10G-10FFORX90S-TCX | 7321-50725 | 5/8 | 15.9 | 1–14 | 30 | 1.26 | 32.0 | 3.64 | 92.5 | 2.17 | 55.0 |
| G25239-1210T | 12G-10FFORX90S-TCX | 7321-50085 | 3/4 | 19.1 | 1–14 | 30 | 1.26 | 32.0 | 4.09 | 104.0 | 2.09 | 53.0 |
| G25239-1212T | 12G-12FFORX90S-TCX | 7321-50075 | 3/4 | 19.1 | 1 3/16–12 | 36 | 1.89 | 48.0 | 4.28 | 108.8 | 2.28 | 57.8 |
| G25239-1616T | 16G-16FFORX90S-TCX | 7321-50195 | 1 | 25.4 | 1 7/16–12 | 41 | 2.20 | 56.0 | 5.11 | 129.9 | 2.88 | 73.1 |
| G25239-2020T | 20G-20FFORX90S-TCX | 7321-50245 | 1 1/4 | 31.8 | 1 11/16–12 | 50 | 2.52 | 64.0 | 5.91 | 150.0 | 3.58 | 91.0 |

## Code 61 O-Ring Flange





| Part No. | Descr. | Prod. No. | ⊖ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25300-0808T | 8G-8FL-TCX | 7321-51575 | 1/2 | 12.7 | 1.19 | 30.2 | 3.15 | 80.0 | 1.67 | 42.5 | .27 | 6.9 |

## Code 61 O-Ring Flange - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25300-1212T | 12G-12FL-TCX | 7321-51555 | 3/4 | 19.1 | 1.50 | 38.1 | 3.86 | 98.0 | 1.85 | 47.0 | .27 | 6.9 |
| G25300-1216T | 12G-16FL-TCX | 7321-50005 | 3/4 | 19.1 | 1.75 | 44.5 | 3.50 | 88.8 | 1.49 | 37.8 | .32 | 8.1 |
| G25300-1616T | 16G-16FL-TCX | 7321-51565 | 1 | 25.4 | 1.75 | 44.5 | 4.13 | 105.0 | 1.90 | 48.2 | .32 | 8.1 |

## Code 61 O-Ring Flange - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G25315-1212T | 12G-12FL90M-TCX | 7321-50155 | 3/4 | 19.1 | 1.50 | 38.1 | 2.28 | 58.0 | 4.54 | 115.3 | 2.53 | 64.3 | .27 | 6.9 |
| G25314-2020T | 20G-20FL90S-TCX | 7321-50265 | 1 1/4 | 31.8 | 2.00 | 50.8 | 2.68 | 68.0 | 6.22 | 158.1 | 3.90 | 99.1 | .32 | 8.1 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# HYDRAULIC HOSE FOR STAINLESS STEEL BRAID COUPLINGS




Also available with MegaTuff® cover










Also available with MegaTuff® cover




Also available with MegaTuff® and XtraTuff® cover







Also available with MegaTuff® and XtraTuff® cover













Also available with MegaTuff® and XtraTuff® cover







Also available with MegaTuff® and XtraTuff® cover




EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# HYDRAULIC HOSE FOR STAINLESS STEEL BRAID COUPLINGS - CONTINUED











**The Gates eCrimp program** is a web based utility which allows users and distributors of Gates hydraulic and industrial hose products to find and print the most up to date crimp specifications with nothing more than an internet browser.


This program can be used to find crimp data for all Gates crimpers. Custom result may be printed by selecting the crimper, hose and coupling. Optionally results may also be limited by die set and working pressure.

The eCrimp web application can be directly accessed from a web browser by entering http://eCrimp.Gates.com for the website.

**The eCrimp mobile app** is available for download for the iPhone and iPad from the App Store.


# Male Pipe (NPTF - 30° Cone Seat)




| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm | " | mm |
| G17100-0404 | 4B-4MP-SS | 7362-00245 | 1/4 | 6.4 | 1/4–18 | .56 | 14.3 | 2.16 | 54.9 | 1.14 | 29.0 |
| G17100-0606 | 6B-6MP-SS | 7362-00275 | 3/8 | 9.5 | 3/8–18 | .68 | 17.5 | 2.32 | 58.9 | 1.22 | 31.0 |
| G17100-0808 | 8B-8MP-SS | 7362-00295 | 1/2 | 12.7 | 1/2–14 | .88 | 22.4 | 2.89 | 73.4 | 1.46 | 37.1 |
| G17100-1212 | 12B-12MP-SS | 7362-00325 | 3/4 | 19.1 | 3/4–14 | 1.06 | 27 | 3.21 | 81.5 | 1.51 | 38.4 |
| G17100-1616 | 16B-16MP-SS | 7362-00355 | 1 | 25.4 | 1–11 1/2 | 1.38 | 35 | 3.62 | 91.9 | 1.91 | 48.6 |
| G17100-2020 | 20B-20MP-SS | 7362-00385 | 1 1/4 | 31.8 | 1 1/4–11 1/2 | 1.75 | 44.5 | 4.44 | 113.0 | 2.14 | 54.6 |
| G17100-2424 | 24B-24MP-SS | 7362-00405 | 1 1/2 | 38.1 | 1 1/2–11 1/2 | 2 | 50.8 | 5.24 | 133.1 | 2.34 | 59.4 |
| G17100-3232 | 32B-32MP-SS | 7362-00425 | 2 | 50.8 | 2–11 1/2 | 2.50 | 63.5 | 6.05 | 153.7 | 2.43 | 61.7 |

# Female JIC 37° Flare Swivel





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | | H2 | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm | " | mm | " | mm |
| G17170-0606 | 6B-6FJX-SS | 7362-01225 | 3/8 | 9.5 | 9/16–18 | .62 | 15.8 | .75 | 19.1 | 2.35 | 59.7 | 1.26 | 31.8 |
| G17170-1212 | 12B-12FJX-SS | 7362-01315 | 3/4 | 19.1 | 1 1/16–12 | 1.06 | 26.9 | 1.25 | 31.8 | 3.41 | 86.6 | 1.71 | 43.4 |
| G17170-1616 | 16B-16FJX-SS | 7362-01375 | 1 | 25.4 | 1 5/16–12 | 1.37 | 34.8 | 1.50 | 38.1 | 3.66 | 92.9 | 1.95 | 49.5 |
| G17170-2020 | 20B-20FJX-SS | 7362-01405 | 1 1/4 | 31.8 | 1 5/8–12 | 1.88 | 47.6 | 2 | 50.8 | 4.72 | 119.9 | 2.42 | 61.5 |
| G17170-2424 | 24B-24FJX-SS | 7362-01435 | 1 1/2 | 38.1 | 1 7/8–12 | 2 | 50.8 | 2.25 | 57.2 | 5.39 | 136.9 | 2.50 | 63.5 |
| G17170-3232 | 32B-32FJX-SS | 7362-01465 | 2 | 50.8 | 2 1/2–12 | 2.75 | 69.9 | 3 | 76.2 | 6.48 | 164.6 | 2.86 | 72.6 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female JIC 37° Flare Swivel - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⟷ | | ⫼ | H2 | | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm | " | mm | " | mm |
| G17174-0606 | 6B-6FJX45S-SS | 7362-11235 | 3/8 | 9.5 | 9/16–18 | .75 | 19.1 | .43 | 11.0 | 2.94 | 74.6 | 1.84 | 46.7 |
| G17174-1212 | 12B-12FJX45S-SS | 7362-11345 | 3/4 | 19.1 | 1 1/16–12 | 1.25 | 31.8 | .83 | 21.0 | 5.27 | 133.8 | 3.56 | 90.4 |
| G17174-1616 | 16B-16FJX45S-SS | 7362-11385 | 1 | 25.4 | 1 5/16–12 | 1.50 | 38.1 | .94 | 23.9 | 5.06 | 128.5 | 3.36 | 85.3 |

## Female JIC 37° Flare Swivel - 90° Bent Tube





| Part No. | Descr. | Prod. No. | ⟷ | | ⫼ | H2 | | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm | " | mm | " | mm |
| G17180-0606 | 6B-6FJX90M-SS | 7362-21265 | 3/8 | 9.5 | 9/16–18 | .75 | 19.1 | 1.50 | 38.0 | 2.13 | 54.1 | 1.03 | 26.2 |
| G17179-1212 | 12B-12FJX90S-SS | 7362-21445 | 3/4 | 19.1 | 1 1/16–12 | 1.25 | 31.8 | 1.89 | 48.0 | 4.20 | 106.7 | 2.50 | 63.5 |
| G17180-1212 | 12B-12FJX90M-SS | 7362-21455 | 3/4 | 19.1 | 1 1/16–12 | 1.25 | 31.8 | 2.28 | 57.9 | 3.81 | 96.8 | 2.11 | 53.5 |
| G17180-1616 | 16B-16FJX90M-SS | 7362-21555 | 1 | 25.4 | 1 5/16–12 | 1.50 | 38.1 | 2.80 | 71.0 | 4.37 | 110.9 | 2.66 | 67.6 |

## Female SAE 45° Flare Swivel





| Part No. | Descr. | Prod. No. | ⟷ | | ⫼ | H1 | | H2 | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm | " | mm | " | mm |
| G17200-1212 | 12B-12FSX-SS | 7362-01335 | 3/4 | 19.1 | 1 1/16–14 | 1.06 | 26.9 | 1.25 | 31.8 | 3.41 | 86.6 | 1.71 | 43.4 |

# Dual Seat Female JIC 37°/SAE 45° Flare Swivel





| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | | H2 | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | mm | " | mm | " | mm | " | mm |
| G17210-0404 | 4B-4FJSX-SS | 7362-01205 | 1/4 | 6.4 | 7/16–20 | .50 | 12.7 | .56 | 14.2 | 2.24 | 57.0 | 1.21 | 30.9 |
| G17210-0808 | 8B-8FJSX-SS | 7362-01265 | 1/2 | 12.7 | 3/4–16 | .81 | 20.6 | .87 | 22.1 | 2.82 | 71.6 | 1.38 | 35.1 |
| G17210-1010 | 10B-10FJSX-SS | 7362-01285 | 5/8 | 15.9 | 7/8–14 | .93 | 23.6 | 1.06 | 26.9 | 3.06 | 77.7 | 1.61 | 41.4 |

# Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 45° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | mm | " | mm | " | mm | " | mm |
| G17211-0404 | 4B-4FJSX45S-SS | 7362-11205 | 1/4 | 6.4 | 7/16–20 | .56 | 14.2 | .39 | 10.0 | 2.59 | 65.7 | 1.56 | 39.6 |
| G17211-0808 | 8B-8FJSX45S-SS | 7362-11285 | 1/2 | 12.7 | 3/4–16 | .88 | 22.4 | .59 | 15.0 | 3.65 | 92.7 | 2.22 | 56.4 |
| G17211-1010 | 10B-10FJSX45S-SS | 7362-11305 | 5/8 | 15.9 | 7/8–14 | 1.06 | 26.9 | .63 | 16.0 | 4.04 | 102.6 | 2.60 | 66.1 |

# Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 90° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | mm | " | mm | " | mm | " | mm |
| G17212-0404 | 4B-4FJSX90S-SS | 7362-21205 | 1/4 | 6.4 | 7/16–20 | .56 | 14.2 | .83 | 21.1 | 2.08 | 52.8 | 1.06 | 26.9 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 90° Bent Tube - Continued


| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm | " | mm | " | mm |
| G17213-0404 | 4B-4FJSX90M-SS | 7362-21215 | 1/4 | 6.4 | 7/16–20 | .56 | 14.2 | 1.26 | 32.0 | 1.92 | 48.8 | .90 | 22.9 |
| G17212-0808 | 8B-8FJSX90S-SS | 7362-21345 | 1/2 | 12.7 | 3/4–16 | .87 | 22.1 | 1.14 | 29.0 | 3.30 | 83.8 | 1.87 | 47.5 |
| G17213-0808 | 8B-8FJSX90M-SS | 7362-21355 | 1/2 | 12.7 | 3/4–16 | .87 | 22.1 | 1.61 | 41.0 | 2.83 | 72.0 | 1.40 | 35.6 |
| G17212-1010 | 10B-10FJSX90S-SS | 7362-21395 | 5/8 | 15.9 | 7/8–14 | 1.06 | 26.9 | 1.26 | 32.0 | 3.37 | 85.7 | 1.93 | 49.1 |
| G17213-1010 | 10B-10FJSX90M-SS | 7362-21405 | 5/8 | 15.9 | 7/8–14 | 1.06 | 26.9 | 1.85 | 47.0 | 3.06 | 77.7 | 1.62 | 41.2 |

## Female Flat-Face O-Ring Swivel Metric Hex





| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | | H2 | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm | " | mm | " | mm |
| G17230-0404 | 4B-4FFORX-SS | 7362-03045 | 1/4 | 6.4 | 9/16–18 | .55 | 14 | .67 | 17 | 2.14 | 54.5 | 1.11 | 28.4 |
| G17230-0808 | 8B-8FFORX-SS | 7362-03085 | 1/2 | 12.7 | 13/16–16 | .87 | 22.2 | .87 | 24 | 2.89 | 73.4 | 1.46 | 37.1 |
| G17230-1010 | 10B-10FFORX-SS | 7362-03105 | 5/8 | 15.9 | 1–14 | .94 | 24 | 1.18 | 30 | 3.09 | 78.5 | 1.66 | 42.1 |
| G17230-1212 | 12B-12FFORX-SS | 7362-03125 | 3/4 | 19.1 | 1 3/16–12 | 1.18 | 30 | 1.42 | 36 | 3.42 | 87.0 | 1.72 | 43.7 |
| G17230-1616 | 16B-16FFORX-SS | 7362-03145 | 1 | 25.4 | 1 7/16–12 | 1.42 | 36 | 1.61 | 40.9 | 3.97 | 101.0 | 2.27 | 57.7 |
| G17230-2020 | 20B-20FFORX-SS | 7362-03165 | 1 1/4 | 31.8 | 1 11/16–12 | 1.81 | 46 | 1.97 | 41 | 4.88 | 124.0 | 2.58 | 65.6 |
| G17230-2424 | 24B-24FFORX-SS | 7362-03185 | 1 1/2 | 38.1 | 2–12 | 1.97 | 50 | 2.36 | 60 | 5.51 | 140.0 | 2.61 | 66.4 |

## Code 61 O-Ring Flange





| Part No. | Descr. | Prod. No. | ⊖ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G17300-2424 | 24B-24FL-SS | 7362-04475 | 1 1/2 | 38.1 | 2.38 | 60.5 | 5.89 | 149.6 | 2.99 | 75.9 | .32 | 8.1 |
| G17300-3232 | 32B-32FL-SS | 7362-04205 | 2 | 50.8 | 2.81 | 71.4 | 6.27 | 159.3 | 2.65 | 67.3 | .38 | 9.7 |

# Female DIN 24° Cone Swivel - Heavy Series with O-Ring




| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | mm |
| G17720-0410 | 4B-10FDHORX-SS | 7362-91665 | 1/4 | 6.4 | M18X1.5 | 22 | 2.24 | 57.0 | 1.22 | 31.0 | 10.0 |
| G17720-0612 | 6B-12FDHORX-SS | 7362-91965 | 3/4 | 19.1 | M20X1.5 | — | — | — | — | — | 12.0 |
| G17720-0816 | 8B-16FDHORX-SS | 7362-91725 | 1/2 | 12.7 | M24X1.5 | 30 | 2.80 | 71.0 | 1.36 | 34.5 | 16.0 |
| G17720-1220 | 12B-20FDHORX-SS | 7362-91755 | 3/4 | 19.1 | M30X2.0 | 36 | 3.23 | 82.0 | 1.52 | 38.6 | 20.0 |
| G17720-1625 | 16B-25FDHORX-SS | 7362-91775 | 1 | 25.4 | M36X2.0 | 41 | 3.62 | 92.0 | 1.92 | 48.7 | 25.0 |
| G17720-1630 | 16B-30FDHORX-SS | 7362-91785 | 1 | 25.4 | M42X2.0 | 50 | 3.72 | 94.5 | 2.02 | 51.3 | 30.0 |
| G17720-2038 | 20B-38FDHORX-SS | 7362-91795 | 1 1/4 | 31.8 | M52X2.0 | 60 | 4.84 | 123.0 | 2.54 | 64.5 | 38.0 |
| G17720-2438 | 24B-38FDHORX-SS | 7362-91805 | 1 1/4 | 31.8 | M52X2.0 | 60 | 5.57 | 141.5 | 2.67 | 67.8 | 38.0 |

# Non-Skive Ferrule




| Part No. | Descr. | Prod. No. | ⊖ | | L | |
|---|---|---|---|---|---|---|
| | | | " | mm | " | mm |
| G17995-0104 | 4B1F-1SS | 7362-51305 | 1/4 | 6.4 | 1.25 | 31.8 |
| G17995-0106 | 6B1F-1SS | 7362-51425 | 3/8 | 9.5 | 1.20 | 30.5 |
| G17995-0204 | 4B1F-2SS | 7362-51415 | 1/4 | 6.4 | 1.04 | 26.3 |
| G17995-0206 | 6B1F-2SS | 7362-51435 | 3/8 | 9.5 | 1.20 | 30.5 |
| G17995-0208 | 8B1F-1SS | 7362-51465 | 1/2 | 12.7 | 1.47 | 37.3 |
| G17995-0210 | 10B1F-1SS | 7362-51475 | 5/8 | 15.9 | 1.47 | 37.3 |
| G17995-0212D | 12B1F-2SS | 7362-51565 | 3/4 | 19.1 | 1.65 | 42.0 |
| G17995-0212 | 12B1F-1SS | 7362-51505 | 3/4 | 19.1 | 1.69 | 42.9 |
| G17995-0216D | 16B1F-2SS | 7362-51885 | 1 | 25.4 | 1.97 | 50.0 |
| G17995-0216 | 16B1F-3SS | 7362-51865 | 1 | 25.4 | 1.69 | 43.0 |
| G17995-0220 | 20B1F-1SS | 7362-51545 | 1 1/4 | 31.8 | 2.41 | 61.2 |
| G17995-0224 | 24B1F-2SS | 7362-51665 | 1 1/2 | 38.1 | 2.98 | 75.8 |
| G17995-0232 | 32B1F-2SS | 7362-51705 | 2 | 50.8 | 3.54 | 90.0 |
| G17995-0424 | 24B1F-4SS | 7362-51675 | 1 1/2 | 38.1 | 3.01 | 76.5 |
| G17995-0432 | 32B1F-4SS | 7362-51725 | 2 | 50.8 | 3.58 | 91.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# HYDRAULIC HOSE FOR POWER CRIMP® COUPLINGS







Also available with MegaTuff® and XtraTuff® cover



















**The Gates eCrimp program** is a web based utility which allows users and distributors of Gates hydraulic and industrial hose products to find and print the most up to date crimp specifications with nothing more than an internet browser.

This program can be used to find crimp data for all Gates crimpers. Custom result may be printed by selecting the crimper, hose and coupling. Optionally results may also be limited by die set and working pressure.


The eCrimp web application can be directly accessed from a web browser by entering http://eCrimp.Gates.com for the website.

**The eCrimp mobile app** is available for download for the iPhone and iPad from the App Store.


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Pipe (NPTF - 30° Cone Seat)




H1




| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | ||| " | " | mm | " | mm |
| 80001 | 3-2MP | 7334-36215 | 3/16 | 4.8 | 1/8–27 | | 1/2 | 2.03 | 51.6 | .94 | 23.9 |
| 80002 | 3-4MP | 7334-36245 | 3/16 | 4.8 | 1/4–18 | | 9/16 | 2.22 | 56.4 | 1.13 | 28.7 |
| 80004 | 4-4MP | 7301-09145 | 1/4 | 6.4 | 1/4–18 | | 9/16 | 2.22 | 56.4 | 1.13 | 28.7 |
| 80007 | 5-4MP | 7301-19145 | 5/16 | 7.9 | 1/4–18 | | 5/8 | 2.19 | 55.6 | 1.18 | 30.0 |
| 80009 | 6-6MP | 7306-29145 | 3/8 | 9.5 | 3/8–18 | | 11/16 | 2.22 | 56.4 | 1.20 | 30.5 |
| 80011 | 6-8MP | 7306-29165 | 3/8 | 9.5 | 1/2–14 | | 7/8 | 2.41 | 61.2 | 1.39 | 35.3 |
| 80012 | 8-6MP | 7301-39125 | 1/2 | 12.7 | 3/8–18 | | 13/16 | 2.70 | 68.6 | 1.26 | 32.0 |
| 80013 | 8-8MP | 7301-39145 | 1/2 | 12.7 | 1/2–14 | | 7/8 | 2.89 | 73.4 | 1.45 | 36.8 |
| 80018 | 12-12MP | 7301-59145 | 3/4 | 19.1 | 3/4–14 | | 1 1/16 | 3.21 | 81.5 | 1.50 | 38.1 |
| 80023 | 16-16MP | 7301-69145 | 1 | 25.4 | 1–11 1/2 | | 1 3/8 | 3.62 | 92.0 | 1.91 | 48.5 |
| 80025 | 24-24MP | 7301-89145 | 1 1/2 | 38.1 | 1 1/2–11 1/2 | | 2 | 4.83 | 122.7 | 2.19 | 55.6 |
| 80026 | 32-32MP | 7301-99145 | 2 | 50.8 | 2–11 1/2 | | 2 1/2 | 5.86 | 148.8 | 2.33 | 59.2 |

# Male Special Grease Fitting




H1


| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | ||| " | " | mm | " | mm |
| 80120 | 3-2MPG | 7334-32445 | 3/16 | 4.8 | 1/8–27 | | 9/16 | 1.34 | 34.0 | .56 | 14.2 |
| ⚠ 80140 | 3-2MPGB | 7334-37925 | 3/16 | 4.8 | 1/8–27 | | 9/16 | 1.34 | 34.0 | .78 | 19.8 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Male Pipe Swivel (NPTF - without 30° Cone Seat)


NOT TO BE USED AS A LIVE SWIVEL.





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | mm | | " | mm |
| 80031 | 3-2MPX | 7334-36335 | 3/16 | 4.8 | 1/8–27 | | 1/2 | 2.40 | 61.0 | 1.31 | 33.3 |
| 80039 | 8-8MPX | 7302-39145 | 1/2 | 12.7 | 1/2–14 | | 13/16 | 3.38 | 85.9 | 1.94 | 49.3 |


# Female Pipe (NPTF - without 30° Cone Seat)





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | mm | | " | mm |
| 80061 | 3-2FP | 7334-36225 | 3/16 | 4.8 | 1/8–27 | | 9/16 | 1.85 | 47.0 | .76 | 19.3 |

# Male JIC 37° Flare









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | mm | | " | mm |
| 80181 | 3-4MJ | 7334-36235 | 3/16 | 4.8 | 7/16–20 | | 1/2 | 2.09 | 53.1 | 1.00 | 25.4 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Female JIC 37° Flare Swivel





| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| 80131 | 3-3FJX | 7334-36315 | 3/16 | 4.8 | 3/8–24 | 1/2 | 9/16 | 2.20 | 55.9 | 1.11 | 28.2 |
| 80132 | 3-4FJX | 7334-36325 | 3/16 | 4.8 | 7/16–20 | 1/2 | 9/16 | 2.21 | 56.1 | 1.12 | 28.5 |
| 80134 | 4-4FJX | 7303-09245 | 1/4 | 6.4 | 7/16–20 | 1/2 | 9/16 | 2.13 | 54.1 | 1.04 | 26.4 |
| 80135 | 4-5FJX | 7303-09265 | 1/4 | 6.4 | 1/2–20 | 1/2 | 11/16 | 2.28 | 57.9 | 1.18 | 30.0 |
| 80136 | 4-6FJX | 7303-09285 | 1/4 | 6.4 | 9/16–18 | 9/16 | 3/4 | 2.28 | 57.9 | 1.18 | 30.0 |
| 80137 | 5-5FJX | 7303-19245 | 5/16 | 7.9 | 1/2–20 | 5/8 | 11/16 | 2.25 | 57.2 | 1.23 | 31.2 |
| 80138 | 5-6FJX | 7303-19265 | 5/16 | 7.9 | 9/16–18 | 5/8 | 3/4 | 2.24 | 56.9 | 1.22 | 31.0 |
| 80139 | 6-6FJX | 7308-29245 | 3/8 | 9.5 | 9/16–18 | 5/8 | 3/4 | 2.24 | 56.9 | 1.22 | 31.0 |
| 80141 | 6-8FJX | 7308-29265 | 3/8 | 9.5 | 3/4–16 | 11/16 | 7/8 | 2.35 | 59.7 | 1.33 | 33.8 |
| 80143 | 8-8FJX | 7303-39245 | 1/2 | 12.7 | 3/4–16 | 13/16 | 7/8 | 2.76 | 70.1 | 1.32 | 33.5 |
| 80144 | 8-10FJX | 7303-39265 | 1/2 | 12.7 | 7/8–14 | 13/16 | 1 1/16 | 2.98 | 75.7 | 1.54 | 39.1 |
| 80147 | 10-10FJX | 7303-49245 | 5/8 | 15.9 | 7/8–14 | 7/8 | 1 1/16 | 3.04 | 77.2 | 1.60 | 40.6 |
| 80148 | 10-12FJX | 7303-49265 | 5/8 | 15.9 | 1 1/16–12 | 1 | 1 1/4 | 3.12 | 79.3 | 1.68 | 42.7 |
| 80152 | 12-12FJX | 7303-59245 | 3/4 | 19.1 | 1 1/16–12 | 1 1/16 | 1 1/4 | 3.39 | 86.1 | 1.68 | 42.7 |
| 80158 | 16-16FJX | 7303-69245 | 1 | 25.4 | 1 5/16–12 | 1 3/8 | 1 1/2 | 3.63 | 92.2 | 1.92 | 48.8 |


# Female JIC 37° Flare Swivel - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm | " | mm |
| 83105 | 3C2-4FJX45S | 7303-01005 | 3/16 | 4.8 | 7/16–20 | 1/2 | 9/16 | .33 | 8.4 | 2.80 | 71.1 | 1.71 | 43.4 |


## Female JIC 37° Flare Swivel - 90° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | mm | " | mm | " | mm |
| 83125 | 3C2-4FJX90S | 7303-01505 | 3/16 | 4.8 | 7/16–20 | 9/16 | .68 | 17.3 | 2.54 | 64.5 | 1.45 | 36.8 |
| 83149 | 24C2-24FJX90S | 7334-41255 | 1 1/2 | 38.1 | 1 7/8–12 | 2 1/4 | 4.00 | 101.6 | 7.11 | 180.6 | 4.47 | 113.5 |


## Female Flat-Face O-Ring Swivel





| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | " | mm | " | mm |
| 83603 | 3C2-6FFORX | 7303-05945 | 3/16 | 4.8 | 11/16–16 | 5/8 | 13/16 | 2.63 | 66.8 | 1.54 | 39.1 |

## SAE Male Inverted Swivel









| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | " | mm | " | mm |
| 83301 | 3C2-3MIX | 7303-02995 | 3/16 | 4.8 | 3/8–24 | 1/2 | 3/8 | 2.67 | 67.8 | 1.58 | 40.1 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## SAE Male Inverted Swivel - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | ≡ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| 83302 | 3C2-3MIX45 | 7303-03205 | 3/16 | 4.8 | 3/8–24 | 3/8 | .58 | 14.7 | 2.78 | 70.6 | 1.69 | 42.9 |


## SAE Male Inverted Swivel - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | ≡ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| 83303 | 3C2-3MIX90 | 7303-03495 | 3/16 | 4.8 | 3/8–24 | 3/8 | 1.05 | 26.7 | 2.42 | 61.5 | 1.33 | 33.8 |

## Female Braze-On Stems






| Part No. | Descr. | Prod. No. | ⊖ | | L | | C | | ⊙ | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| 80410 | 3-4FBO | 7305-09135 | 3/16 | 4.8 | 1.76 | 44.7 | .68 | 17.3 | .56 | 14.2 |
| 80401 | 4-4FBO | 7305-09145 | 1/4 | 6.4 | 1.67 | 42.4 | .58 | 14.7 | .56 | 14.2 |
| 80402 | 4-5FBO | 7305-09165 | 1/4 | 6.4 | 1.67 | 42.4 | .58 | 14.7 | .56 | 14.2 |
| 80403 | 6-6FBO | 7334-36755 | 3/8 | 9.5 | 1.72 | 43.7 | .70 | 17.8 | .75 | 19.1 |
| 80400 | 6-8FBO | 7305-29165 | 3/8 | 9.5 | 1.72 | 43.7 | .70 | 17.8 | .88 | 22.4 |
| 80404 | 8-8FBO | 7305-39145 | 1/2 | 12.7 | 2.20 | 55.9 | .76 | 19.3 | .88 | 22.4 |
| 80405 | 8-10FBO | 7305-39165 | 1/2 | 12.7 | 2.20 | 55.9 | .76 | 19.3 | .88 | 22.4 |
| 80406 | 12-12FBO | 7305-59145 | 3/4 | 19.1 | 2.47 | 62.7 | .76 | 19.3 | 1.12 | 28.5 |
| 80407 | 12-16FBO | 7305-59165 | 3/4 | 19.1 | 2.75 | 69.9 | 1.04 | 26.4 | 1.38 | 35.1 |

## Female Braze-On Stems - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | L | | C | | ⊙ | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm |
| 80408 | 16-16FBO | 7305-69145 | 1 | 25.4 | 2.75 | 69.9 | 1.04 | 26.4 | 1.38 | 35.1 |
| 80409 | 20-20FBO | 7305-79145 | 1 1/4 | 31.8 | 3.29 | 83.6 | 1.11 | 28.2 | 1.81 | 46.0 |
| 80411 | 24-24FBO | 7305-89145 | 1 1/2 | 38.1 | 3.75 | 95.3 | 1.11 | 28.2 | 2.00 | 50.8 |


## Female DIN 24° Cone Swivel - Light Series





| Part No. | Descr. | Prod. No. | ⊖ | | ⌇ | H1 | H2 | L | | C | | ⊙ |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | mm | " | mm | " | mm | mm |
| 83709 | 3C2-6FDLX | 7303-08195 | 3/16 | 4.8 | M12X1.5 | 14 | 14 | 2.20 | 55.9 | 1.11 | 28.2 | 6.0 |

## Female DIN 24° Cone Swivel - Light Series - 90° Bent Tube








| Part No. | Descr. | Prod. No. | ⊖ | | ⌇ | H2 | T | | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | mm |
| 83740 | 3C2-6FDLX90 | 7303-08205 | 3/16 | 4.8 | M12X1.5 | 14 | 1.26 | 32.0 | 2.52 | 64.0 | 1.43 | 36.3 | 6.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Power Crimp® Two Ferrules (Steel) - PC2F Series




| Part No. | Descr. | Prod. No. | L | | ⌀ | |
|---|---|---|---|---|---|---|
| | | | " | mm | " | mm |
| 80415 | 3PC2F-2 | 7266-00075 | 1.00 | 25.4 | .76 | 19.3 |
| 80416 | 4PC2F-2 | 7266-00345 | 1.00 | 25.4 | .84 | 21.3 |
| 80461 | 4PC2F-4 | 7266-00395 | 1.20 | 30.5 | .89 | 22.6 |
| 80417 | 5PC2F-2 | 7266-00385 | 1.00 | 25.4 | .87 | 22.1 |
| 80418 | 6PC2F-2 | 7266-00335 | 1.00 | 25.4 | .94 | 23.9 |
| 80462 | 6PC2F-4 | 7266-00405 | 1.20 | 30.5 | 1.06 | 26.9 |
| 80419 | 8PC2F-2 | 7266-00025 | 1.25 | 31.8 | 1.13 | 28.7 |
| 80463 | 8PC2F-4 | 7266-00415 | 1.47 | 37.3 | 1.28 | 32.5 |
| 80476 | 10PC2F-2B | 7266-00465 | 1.47 | 37.3 | 1.32 | 33.5 |
| 80447 | 10PC2F-2C | 7266-08105 | 1.25 | 31.8 | 1.23 | 31.2 |
| 80423 | 12PC2F-2 | 7266-00185 | 1.47 | 37.3 | 1.50 | 38.1 |
| 80422 | 12PC2F-4 | 7266-00145 | 1.97 | 50.0 | 1.38 | 35.1 |
| 80424 | 16PC2F-2 | 7266-00135 | 1.97 | 50.0 | 1.75 | 44.5 |
| 80425 | 16PC2F-4 | 7266-00175 | 2.07 | 52.6 | 1.87 | 47.5 |
| 80427 | 20PC2F-2 | 7266-00225 | 2.35 | 59.7 | 2.25 | 57.2 |
| 80426 | 20PC2F-4 | 7266-00215 | 2.77 | 70.4 | 2.19 | 55.6 |
| 80428 | 24PC2F-4 | 7266-00355 | 2.88 | 73.2 | 2.55 | 64.8 |
| 80429 | 32PC2F-4 | 7266-00375 | 3.43 | 87.1 | 3.16 | 80.3 |

# Power Crimp® One Non-Skive Ferrules (Steel) - PC1FS Series




| Part No. | Descr. | Prod. No. | L | | ⌀ | |
|---|---|---|---|---|---|---|
| | | | " | mm | " | mm |
| 80481 | 3PC1FS | 7266-07035 | 1.20 | 30.5 | .83 | 21.1 |
| 80584 | 4M3KPC | 7266-07805 | 1.20 | 30.5 | .89 | 22.6 |
| 80468 | 4PC1F-M2S | 7266-07635 | 1.20 | 30.5 | .83 | 21.1 |
| 80482 | 4PC1FS | 7266-07045 | 1.28 | 32.5 | .87 | 22.1 |
| 80483 | 5PC1FS | 7266-07055 | 1.20 | 30.5 | .97 | 24.6 |
| 80585 | 6M3KPC | 7266-07815 | 1.20 | 30.5 | .97 | 24.6 |
| 81512 | 6PC1F-M2S | 7266-07375 | 1.20 | 30.5 | 1.06 | 26.9 |
| 80484 | 6PC1FS | 7266-07065 | 1.20 | 30.5 | .96 | 24.4 |
| 80586 | 8M3KPC | 7266-07825 | 1.50 | 38.1 | 1.15 | 29.2 |
| 80474 | 8PC1F-M2S | 7266-07395 | 1.47 | 37.3 | 1.20 | 30.5 |
| 80485 | 8PC1FS | 7266-07085 | 1.47 | 37.3 | 1.15 | 29.2 |

# Power Crimp® One Non-Skive Ferrules (Steel) - PC1FS Series - Continued


| Part No. | Descr. | Prod. No. | L | | O | |
|---|---|---|---|---|---|---|
| | | | " | mm | " | mm |
| 80477 | 10PC1F-M2S | 7266-07415 | 1.47 | 37.3 | 1.31 | 33.3 |
| 80486 | 10PC1FS-M3K | 7266-07105 | 1.49 | 37.9 | 1.21 | 30.7 |
| 80475 | 12PC1F-M2S | 7266-07435 | 1.69 | 42.9 | 1.57 | 39.9 |
| 80487 | 12PC1FS-M3K | 7266-07125 | 1.69 | 42.9 | 1.53 | 38.9 |
| 80480 | 16PC1F-M2S | 7266-07475 | 1.69 | 42.9 | 1.94 | 49.3 |
| 80488 | 16PC1FS | 7266-07165 | 1.69 | 42.9 | 1.32 | 33.5 |
| 80489 | 20PC1FS | 7266-07205 | 2.41 | 61.2 | 2.38 | 60.5 |
| 80491 | 24PC1FS | 7266-07245 | 2.69 | 68.3 | 2.69 | 68.3 |
| 80492 | 32PC1FS | 7266-07325 | 3.56 | 90.4 | 3.25 | 82.6 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male Pipe (NPTF - 30° Cone Seat)





| Part No. | Descr. | Prod. No. | ⊖ | | ⦀ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G27100-0402 | 4C1T-2RMP | 7231-81241 | 1/4 | 6.4 | 1/8–27 | 1/2 | 2.30 | 58.4 | 1.29 | 32.8 |
| G27100-0404 | 4C1T-4RMP | 7231-81210 | 1/4 | 6.4 | 1/4–18 | 9/16 | 2.52 | 64.0 | 1.51 | 38.4 |
| G27100-0604 | 6C1T-4RMP | 7231-81242 | 3/8 | 9.5 | 1/4–18 | 9/16 | 2.68 | 68.1 | 1.54 | 39.1 |
| G27100-0606 | 6C1T-6RMP | 7231-81211 | 3/8 | 9.5 | 3/8–18 | 11/16 | 2.53 | 64.3 | 1.39 | 35.3 |
| G27100-0806 | 8C1T-6RMP | 7231-81243 | 1/2 | 12.7 | 3/8–18 | 11/16 | 3.05 | 77.5 | 1.70 | 43.2 |
| G27100-0808 | 8C1T-8RMP | 7231-81212 | 1/2 | 12.7 | 1/2–14 | 7/8 | 3.06 | 77.7 | 1.71 | 43.4 |
| G27100-0812 | 8C1T-12RMP | 7231-81244 | 1/2 | 12.7 | 3/4–14 | 1 1/16 | 3.13 | 79.5 | 1.87 | 47.5 |
| G27100-1212 | 12C1T-12RMP | 7231-81213 | 3/4 | 19.1 | 3/4–14 | 1 1/16 | 3.19 | 81.0 | 1.73 | 43.9 |
| G27100-1616 | 16C1T-16RMP | 7231-81214 | 1 | 25.4 | 1–11 1/2 | 1 3/8 | 3.78 | 96.0 | 2.10 | 53.3 |

## Male Pipe Swivel (NPTF - without 30° Cone Seat)









| Part No. | Descr. | Prod. No. | ⊖ | | ⦀ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G27105-0404 | 4C1T-4RMPX | 7231-22445 | 1/4 | 6.4 | 1/4–18 | 7/16 | 7/8 | 3.18 | 80.8 | 2.17 | 55.1 |
| G27105-0606 | 6C1T-6RMPX | 7231-22455 | 3/8 | 9.5 | 3/8–18 | 5/8 | 7/8 | 3.51 | 89.2 | 2.23 | 56.6 |
| G27105-0808 | 8C1T-8RMPX | 7231-22465 | 1/2 | 12.7 | 1/2–14 | 3/4 | 1 | 3.99 | 101.4 | 2.63 | 66.8 |
| G27105-1212 | 12C1T-12RMPX | 7231-22475 | 3/4 | 19.1 | 3/4–14 | 1 1/16 | 1 5/16 | 4.27 | 108.5 | 2.73 | 69.3 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male O-Ring Boss





| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G27120-0606 | 6C1T-6RMB | 7231-22255 | 3/8 | 9.5 | 9/16–18 | 11/16 | 2.52 | 64.0 | 1.24 | 31.5 |
| G27120-0608 | 6C1T-8RMB | 7231-22265 | 3/8 | 9.5 | 3/4–16 | 7/8 | 2.59 | 65.8 | 1.32 | 33.5 |
| G27120-0808 | 8C1T-8RMB | 7231-22275 | 1/2 | 12.7 | 3/4–16 | 7/8 | 2.87 | 72.9 | 1.52 | 38.6 |
| G27120-0810 | 8C1T-10RMB | 7231-22285 | 1/2 | 12.7 | 7/8–14 | 1 | 3.11 | 79.0 | 1.76 | 44.7 |


## Male JIC 37° Flare





| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G27165-0606 | 6C1T-6RMJ | 7231-22185 | 3/8 | 9.5 | 9/16–18 | 9/16 | 2.68 | 68.1 | 1.40 | 35.6 |
| G27165-0808 | 8C1T-8RMJ | 7231-22195 | 1/2 | 12.7 | 3/4–16 | 3/4 | 3.05 | 77.5 | 1.70 | 43.2 |
| G27165-0810 | 8C1T-10RMJ | 7231-22205 | 1/2 | 12.7 | 7/8–14 | 7/8 | 3.31 | 84.1 | 1.96 | 49.9 |
| G27165-1212 | 12C1T-12RMJ | 7231-22215 | 3/4 | 19.1 | 1 1/16–12 | 1 1/16 | 3.52 | 89.4 | 1.98 | 50.3 |

## Female JIC 37° Flare Swivel









| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G27170-0404 | 4C1T-4RFJX | 7231-81215 | 1/4 | 6.4 | 7/16–20 | 9/16 | 9/16 | 2.47 | 62.7 | 1.46 | 37.1 |
| G27170-0405 | 4C1T-5RFJX | 7231-81216 | 1/4 | 6.4 | 1/2–20 | 11/16 | 11/16 | 2.58 | 65.5 | 1.57 | 39.9 |
| G27170-0606 | 6C1T-6RFJX | 7231-81217 | 3/8 | 9.5 | 9/16–18 | 3/4 | 3/4 | 2.80 | 71.1 | 1.65 | 41.9 |
| G27170-0608 | 6C1T-8RFJX | 7231-81218 | 3/8 | 9.5 | 3/4–16 | 3/4 | 7/8 | 2.91 | 73.9 | 1.76 | 44.7 |

## Female JIC 37° Flare Swivel - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm |
| G27170-0808 | 8C1T-8RFJX | 7231-81219 | 1/2 | 12.7 | 3/4–16 | | 13/16 | 7/8 | 3.24 | 82.3 | 1.89 | 48.1 |
| G27170-0810 | 8C1T-10RFJX | 7231-81220 | 1/2 | 12.7 | 7/8–14 | | 13/16 | 1 1/16 | 3.34 | 84.8 | 1.99 | 50.6 |
| G27170-1212 | 12C1T-12RFJX | 7231-81221 | 3/4 | 19.1 | 1 1/16–12 | | 1 1/8 | 1 1/4 | 3.45 | 87.6 | 1.91 | 48.5 |
| G27170-1616 | 16C1T-16RFJX | 7231-81222 | 1 | 25.4 | 1 5/16–12 | | 1 3/8 | 1 1/2 | 3.90 | 99.1 | 2.22 | 56.4 |


## Female JIC 37° Flare Swivel - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm | " | mm |
| G27175-0404 | 4C1T-4RFJX45 | 7231-22545 | 1/4 | 6.4 | 7/16–20 | | 3/8 | 9/16 | .33 | 8.4 | 2.80 | 71.1 | 1.79 | 45.5 |
| G27175-0606 | 6C1T-6RFJX45 | 7231-22555 | 3/8 | 9.5 | 9/16–18 | | 1/2 | 11/16 | .39 | 10.0 | 3.37 | 85.6 | 1.79 | 45.5 |
| G27175-0808 | 8C1T-8RFJX45 | 7231-22565 | 1/2 | 12.7 | 3/4–16 | | 5/8 | 7/8 | .55 | 14.0 | 4.11 | 104.4 | 2.10 | 53.3 |
| G27175-1212 | 12C1T-12RFJX45 | 7231-22575 | 3/4 | 19.1 | 1 1/16–12 | | 1 1/4 | 1 1/4 | .78 | 19.8 | 4.70 | 119.4 | 3.16 | 80.3 |

## Female JIC 37° Flare Swivel - 90° Bent Tube









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm | " | mm |
| G27180-0404 | 4C1T-4RFJX90 | 7231-22655 | 1/4 | 6.4 | 7/16–20 | | 3/8 | 9/16 | .68 | 17.3 | 2.69 | 68.3 | 1.68 | 42.7 |
| G27180-0606 | 6C1T-6RFJX90 | 7231-22665 | 3/8 | 9.5 | 9/16–18 | | 1/2 | 11/16 | .85 | 21.6 | 3.28 | 83.3 | 2.00 | 50.8 |
| G27180-0608 | 6C1T-8RFJX90 | 7231-22675 | 3/8 | 9.5 | 3/4–16 | | 5/8 | 7/8 | 1.09 | 27.7 | 3.58 | 90.9 | 2.31 | 58.7 |
| G27180-0808 | 8C1T-8RFJX90 | 7231-22685 | 1/2 | 12.7 | 3/4–16 | | 5/8 | 7/8 | 1.09 | 27.7 | 3.86 | 98.1 | 2.51 | 63.8 |
| G27180-0810 | 8C1T-10RFJX90 | 7231-22695 | 1/2 | 12.7 | 7/8–14 | | 3/4 | 1 | 1.23 | 31.2 | 3.92 | 99.6 | 2.59 | 65.8 |
| G27180-1212 | 12C1T-12RFJX90 | 7231-22705 | 3/4 | 19.1 | 1 1/16–12 | | 1 1/4 | 1 1/4 | 1.82 | 46.2 | 4.59 | 116.6 | 3.05 | 77.5 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male Pipe (NPTF - 30° Cone Seat)





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G28100-0402 | 4C2AT-2RMP | 7231-81247 | 1/4 | 6.4 | 1/8–27 | 1/2 | 2.30 | 58.4 | 1.23 | 31.2 |
| G28100-0404 | 4C2AT-4RMP | 7231-81223 | 1/4 | 6.4 | 1/4–18 | 9/16 | 2.52 | 64.0 | 1.45 | 36.8 |
| G28100-0604 | 6C2AT-4RMP | 7231-81248 | 3/8 | 9.5 | 1/4–18 | 9/16 | 2.68 | 68.1 | 1.45 | 36.8 |
| G28100-0606 | 6C2AT-6RMP | 7231-81224 | 3/8 | 9.5 | 3/8–18 | 11/16 | 2.53 | 64.3 | 1.30 | 33.0 |
| G28100-0806 | 8C2AT-6RMP | 7231-81249 | 1/2 | 12.7 | 3/8–18 | 11/16 | 3.05 | 77.5 | 1.63 | 41.4 |
| G28100-0808 | 8C2AT-8RMP | 7231-81225 | 1/2 | 12.7 | 1/2–14 | 7/8 | 3.06 | 77.7 | 1.64 | 41.7 |
| G28100-0812 | 8C2AT-12RMP | 7231-81251 | 1/2 | 12.7 | 3/4–14 | 1 1/16 | 3.13 | 79.5 | 1.71 | 43.4 |
| G28100-1212 | 12C2AT-12RMP | 7231-81226 | 3/4 | 19.1 | 3/4–14 | 1 1/16 | 3.19 | 81.0 | 1.65 | 41.9 |
| G28100-1616 | 16C2AT-16RMP | 7231-81227 | 1 | 25.4 | 1–11 1/2 | 1 3/8 | 3.78 | 96.0 | 2.04 | 51.8 |
| G28100-2020 | 20C2AT-20RMP | 7231-81228 | 1 1/4 | 31.8 | 1 1/4–11 1/2 | 1 3/4 | 4.59 | 116.6 | 2.49 | 63.3 |
| G28100-2424 | 24C2AT-24RMP | 7231-81252 | 1 1/2 | 38.1 | 1 1/2–11 1/2 | 2 | 5.18 | 131.6 | 2.68 | 68.1 |


## Male Pipe Swivel (NPTF - without 30° Cone Seat)





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G28105-0404 | 4C2AT-4RMPX | 7231-22495 | 1/4 | 6.4 | 1/4–18 | 7/16 | 11/16 | 3.18 | 80.8 | 2.11 | 53.6 |
| G28105-0606 | 6C2AT-6RMPX | 7231-22505 | 3/8 | 9.5 | 3/8–18 | 5/8 | 7/8 | 3.51 | 89.2 | 2.27 | 57.7 |
| G28105-0808 | 8C2AT-8RMPX | 7231-22515 | 1/2 | 12.7 | 1/2–14 | 3/4 | 1 | 3.99 | 101.4 | 2.56 | 65.0 |
| G28105-1212 | 12C2AT-12RMPX | 7231-22525 | 3/4 | 19.1 | 3/4–14 | 1 1/16 | 1 5/16 | 4.27 | 108.5 | 2.73 | 69.3 |


## Male O-Ring Boss





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G28120-0606 | 6C2AT-6RMB | 7231-22355 | 3/8 | 9.5 | 9/16–18 | 11/16 | 2.52 | 64.0 | 1.28 | 32.5 |
| G28120-0608 | 6C2AT-8RMB | 7231-22365 | 3/8 | 9.5 | 3/4–16 | 7/8 | 2.59 | 65.8 | 1.36 | 34.5 |
| G28120-0808 | 8C2AT-8RMB | 7231-22375 | 1/2 | 12.7 | 3/4–16 | 7/8 | 2.87 | 72.9 | 1.45 | 36.8 |
| G28120-0810 | 8C2AT-10RMB | 7231-22385 | 1/2 | 12.7 | 7/8–14 | 1 | 3.11 | 79.0 | 1.59 | 40.4 |


## Male JIC 37° Flare





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G28165-0606 | 6C2AT-6RMJ | 7231-22025 | 3/8 | 9.5 | 9/16–18 | 9/16 | 2.68 | 68.1 | 1.45 | 36.8 |
| G28165-0808 | 8C2AT-8RMJ | 7231-22045 | 1/2 | 12.7 | 3/4–16 | 3/4 | 3.05 | 77.5 | 1.63 | 41.4 |
| G28165-0810 | 8C2AT-10RMJ | 7231-22055 | 1/2 | 12.7 | 7/8–14 | 7/8 | 3.31 | 84.1 | 1.89 | 48.1 |
| G28165-1212 | 12C2AT-12RMJ | 7231-22065 | 3/4 | 19.1 | 1 1/16–12 | 1 1/16 | 3.52 | 89.4 | 1.98 | 50.3 |

## Female JIC 37° Flare Swivel




| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G28170-0404 | 4C2AT-4RFJX | 7231-81229 | 1/4 | 6.4 | 7/16–20 | 9/16 | 9/16 | 2.47 | 62.7 | 1.40 | 35.6 |
| G28170-0405 | 4C2AT-5RFJX | 7231-81230 | 1/4 | 6.4 | 1/2–20 | 11/16 | 11/16 | 2.58 | 65.5 | 1.57 | 39.9 |
| G28170-0606 | 6C2AT-6RFJX | 7231-81231 | 3/8 | 9.5 | 9/16–18 | 3/4 | 3/4 | 2.80 | 71.1 | 1.56 | 39.6 |
| G28170-0608 | 6C2AT-8RFJX | 7231-81232 | 3/8 | 9.5 | 3/4–16 | 3/4 | 3/4 | 2.91 | 73.9 | 1.67 | 42.4 |
| G28170-0808 | 8C2AT-8RFJX | 7231-81233 | 1/2 | 12.7 | 3/4–16 | 13/16 | 7/8 | 3.24 | 82.3 | 1.82 | 46.2 |
| G28170-0810 | 8C2AT-10RFJX | 7231-81234 | 1/2 | 12.7 | 7/8–14 | 13/16 | 1 1/16 | 3.34 | 84.8 | 1.92 | 48.8 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female JIC 37° Flare Swivel - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G28170-1212 | 12C2AT-12RFJX | 7231-81235 | 3/4 | 19.1 | 1 1/16–12 | 1 1/8 | 1 1/2 | 3.45 | 87.6 | 1.91 | 48.5 |
| G28170-1616 | 16C2AT-16RFJX | 7231-81236 | 1 | 25.4 | 1 5/16–12 | 1 3/8 | 1 1/2 | 3.90 | 99.1 | 2.16 | 54.9 |
| G28170-2020 | 20C2AT-20RFJX | 7231-81237 | 1 1/4 | 31.8 | 1 5/8–12 | 1 7/8 | 2 | 4.85 | 123.2 | 2.74 | 69.6 |
| G28170-2424 | 24C2AT-24RFJX | 7231-81254 | 1 1/2 | 38.1 | 1 7/8–12 | 2 1/8 | 2 1/4 | 5.26 | 133.6 | 2.76 | 70.1 |


## Female JIC 37° Flare Swivel - 45° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm | " | mm |
| G28175-0404 | 4C2AT-4RFJX45 | 7231-22595 | 1/4 | 6.4 | 7/16–20 | 3/8 | 9/16 | .33 | 8.4 | 2.80 | 71.1 | 1.73 | 43.9 |
| G28175-0606 | 6C2AT-6RFJX45 | 7231-22605 | 3/8 | 9.5 | 9/16–18 | 1/2 | 11/16 | .39 | 10.0 | 3.37 | 85.6 | 2.14 | 54.4 |
| G28175-0808 | 8C2AT-8RFJX45 | 7231-22615 | 1/2 | 12.7 | 3/4–16 | 5/8 | 7/8 | .55 | 14.0 | 4.11 | 104.4 | 2.68 | 68.1 |
| G28175-1212 | 12C2AT-12RFJX45 | 7231-22625 | 3/4 | 19.1 | 1 1/16–12 | 7/8 | 1 1/4 | .78 | 19.8 | 4.70 | 119.4 | 3.16 | 80.3 |

## Female JIC 37° Flare Swivel - 90° Bent Tube





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm | " | mm |
| G28180-0404 | 4C2AT-4RFJX90 | 7231-22755 | 1/4 | 6.4 | 7/16–20 | 3/8 | 9/16 | .68 | 17.3 | 2.69 | 68.3 | 1.62 | 41.2 |
| G28180-0606 | 6C2AT-6RFJX90 | 7231-22765 | 3/8 | 9.5 | 9/16–18 | 1/2 | 11/16 | .85 | 21.6 | 3.28 | 83.3 | 2.04 | 51.8 |
| G28180-0608 | 6C2AT-8RFJX90 | 7231-22775 | 3/8 | 9.5 | 3/4–16 | 5/8 | 7/8 | 1.09 | 27.7 | 3.58 | 90.9 | 2.35 | 59.7 |
| G28180-0808 | 8C2AT-8RFJX90 | 7231-22785 | 1/2 | 12.7 | 3/4–16 | 5/8 | 7/8 | 1.09 | 27.7 | 3.86 | 98.1 | 2.42 | 61.5 |
| G28180-0810 | 8C2AT-10RFJX90 | 7231-22795 | 1/2 | 12.7 | 7/8–14 | 3/4 | 1 | 1.23 | 31.2 | 3.92 | 99.6 | 2.50 | 63.5 |
| G28180-1212 | 12C2AT-12RFJX90 | 7231-22805 | 3/4 | 19.1 | 1 1/16–12 | 7/8 | 1 1/4 | 1.82 | 46.2 | 4.59 | 116.6 | 3.05 | 77.5 |

# Female Flat-Face O-Ring Swivel


SAE J1453 O–Ring Face Seal.




| Part No. | Descr. | Prod. No. | ⟷ | | ≋ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G28230-0404 | 4C2AT-4RFFORX | 7231-14105 | 1/4 | 6.4 | 9/16–18 | 43/64 | 43/64 | 2.50 | 63.5 | 1.43 | 36.3 |
| G28230-0606 | 6C2AT-6RFFORX | 7231-14125 | 3/8 | 9.5 | 11/16–16 | 7/8 | 7/8 | 2.88 | 73.2 | 1.64 | 41.7 |
| G28230-0808 | 8C2AT-8RFFORX | 7231-14145 | 1/2 | 12.7 | 13/16–16 | 61/64 | 61/64 | 3.37 | 85.6 | 1.94 | 49.3 |
| G28230-1212 | 12C2AT-12RFFORX | 7231-14165 | 3/4 | 19.1 | 1 3/16–12 | 1 1/8 | 1 13/32 | 2.03 | 51.6 | 3.57 | 90.7 |

# Female Flat-Face O-Ring Swivel - 45° Bent Tube

SAE J1453 O–Ring Face Seal.





| Part No. | Descr. | Prod. No. | ⟷ | | ≋ | H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm | " | mm |
| G28234-0404 | 4C2AT-4RFFORX45S | 7231-14305 | 1/4 | 6.4 | 9/16–18 | 3/8 | 9/16 | .68 | 17.3 | 2.69 | 68.3 | 1.62 | 41.2 |
| G28234-0606 | 6C2AT-6RFFORX45S | 7231-14325 | 3/8 | 9.5 | 11/16–16 | 1/2 | 11/16 | .85 | 21.6 | 3.28 | 83.3 | 2.04 | 51.8 |
| G28234-0808 | 8C2AT-8RFFORX45S | 7231-14345 | 1/2 | 12.7 | 13/16–16 | 5/8 | 7/8 | 1.09 | 27.7 | 3.86 | 98.1 | 2.42 | 61.5 |
| G28234-1212 | 12C2AT-12RFFORX45S | 7231-14365 | 3/4 | 19.1 | 1 3/16–12 | 7/8 | 1 1/4 | 1.82 | 46.2 | 4.59 | 116.6 | 3.05 | 77.5 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female Flat-Face O-Ring Swivel - 90° Bent Tube

SAE J1453 O–Ring Face Seal.




| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm | " | mm |
| G28239-0404 | 4C2AT-4RFFORX90S | 7231-14505 | 1/4 | 6.4 | 9/16–18 | 3/8 | 9/16 | .68 | 17.3 | 2.69 | 68.3 | 1.62 | 41.2 |
| G28239-0606 | 6C2AT-6RFFORX90S | 7231-14525 | 3/8 | 9.5 | 11/16–16 | 1/2 | 11/16 | .85 | 21.6 | 3.28 | 83.3 | 2.04 | 51.8 |
| G28239-0808 | 8C2AT-8RFFORX90S | 7231-14545 | 1/2 | 12.7 | 13/16–16 | 5/8 | 7/8 | 1.09 | 27.7 | 3.86 | 98.1 | 2.42 | 61.5 |
| G28239-1212 | 12C2AT-12RFFORX90S | 7231-14565 | 3/4 | 19.1 | 1 3/16–12 | — | 7/8 | 1.88 | 40.8 | 4.54 | 115.3 | 3.00 | 76.2 |

# HYDRAULIC HOSE FOR C5C, C5CXH, C5D & C5M COUPLINGS













# HYDRAULIC HOSE FOR C5E COUPLINGS




**The Gates eCrimp program** is a web based utility which allows users and distributors of Gates hydraulic and industrial hose products to find and print the most up to date crimp specifications with nothing more than an internet browser.

This program can be used to find crimp data for all Gates crimpers. Custom result may be printed by selecting the crimper, hose and coupling. Optionally results may also be limited by die set and working pressure.

The eCrimp web application can be directly accessed from a web browser by entering http://eCrimp.Gates.com for the website.


**The eCrimp mobile app** is available for download for the iPhone and iPad from the App Store.


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Pipe (NPTF - 30° Cone Seat) - Steel

DOT FMVSS 106–74 Type AII.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G34100-0402 | 4C5-2RMP | 7236-04015 | 3/16 | 4.8 | 1/8–27 | 1/2 | 1.64 | 41.7 | .94 | 23.9 |
| G34100-0404 | 4C5-4RMP | 7236-04025 | 3/16 | 4.8 | 1/4–18 | 9/16 | 1.83 | 46.5 | 1.13 | 28.7 |
| G34100-0502 | 5C5X-2RMP | 7237-00145 | 1/4 | 6.4 | 1/8–27 | 1/2 | 1.77 | 45.0 | 1.00 | 25.4 |
| G34100-0504 | 5C5X-4RMP | 7237-00155 | 1/4 | 6.4 | 1/4–18 | 9/16 | 1.96 | 49.8 | 1.19 | 30.2 |
| G34100-0604 | 6C5-4RMP | 7236-04055 | 5/16 | 7.9 | 1/4–18 | 9/16 | 2.17 | 55.1 | 1.22 | 31.0 |
| G34100-0606 | 6C5-6RMP | 7236-04275 | 5/16 | 7.9 | 3/8–18 | 11/16 | 2.17 | 55.1 | 1.22 | 31.0 |
| G34100-0806 | 8C5X-6RMP | 7237-00195 | 13/32 | 10.3 | 3/8–18 | 11/16 | 2.46 | 62.5 | 1.34 | 34.0 |
| G34100-0808 | 8C5X-8RMP | 7237-00205 | 13/32 | 10.3 | 1/2–14 | 7/8 | 2.71 | 68.8 | 1.59 | 40.4 |
| G34100-1008 | 10C5-8RMP | 7236-04085 | 1/2 | 12.7 | 1/2–14 | 1 1/16 | 2.88 | 73.2 | 1.59 | 40.4 |
| G34100-1012 | 10C5-12RMP | 7236-04095 | 1/2 | 12.7 | 3/4–14 | 1 | 2.95 | 74.9 | 1.66 | 42.2 |
| G34100-1208 | 12C5X-8RMP | 7237-00235 | 5/8 | 15.9 | 1/2–14 | 7/8 | 3.15 | 80.0 | 1.59 | 40.4 |
| G34100-1212 | 12C5X-12RMP | 7237-00245 | 5/8 | 15.9 | 3/4–14 | 1 1/16 | 3.25 | 82.6 | 1.69 | 42.9 |
| G34100-1612 | 16C5-12RMP | 7236-86412 | 7/8 | 22.2 | 3/4–14 | 1 1/8 | 2.71 | 68.8 | 1.53 | 38.9 |
| G34100-1616 | 16C5-16RMP | 7236-86413 | 7/8 | 22.2 | 1–11 1/2 | 1 3/8 | 2.90 | 73.7 | 1.72 | 43.7 |
| G34100-2020 | 20C5-20RMP | 7236-86428 | 1 1/8 | 28.6 | 1 1/4–11 1/2 | 1 11/16 | 3.25 | 82.6 | 1.88 | 47.8 |
| G34100-2424 | 24C5-24RMP | 7236-86388 | 1 3/8 | 34.9 | 1 1/2–11 1/2 | 2 | 3.45 | 87.6 | 2.03 | 51.6 |
| G34100-3232 | 32C5-32RMP | 7236-86389 | 1 13/16 | 46.0 | 2–11 1/2 | 2 1/2 | 4.07 | 103.4 | 2.22 | 56.4 |

# Male Pipe (NPTF - 30° Cone Seat) - Brass

DOT FMVSS 106–74 Type AII.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| ⚠ G34100-0606B | 6C5-6RMPB | 7236-03015 | 5/16 | 7.9 | 3/8–18 | 11/16 | 2.17 | 55.1 | 1.22 | 31.0 |
| ⚠ G34100-0808B | 8C5-8RMPB | 7236-03085 | 13/32 | 10.3 | 1/2–14 | 7/8 | 2.71 | 68.8 | 1.59 | 40.4 |
| ⚠ G34100-1008B | 10C5-8RMPB | 7236-03035 | 1/2 | 12.7 | 1/2–14 | 7/8 | 2.88 | 73.2 | 1.59 | 40.4 |
| ⚠ G34100-1616B | 16C5-16RMPB | 7236-03065 | 7/8 | 22.2 | 1–11 1/2 | 1 3/8 | 2.91 | 73.9 | 1.72 | 43.7 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Male O-Ring Boss - Steel

DOT FMVSS 106–74 Type AII.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | mm | | " | mm |
| G34120-0404 | 4C5-4RMB | 7236-86451 | 3/16 | 4.8 | 7/16–20 | | 5/8 | 1.66 | 42.2 | .94 | 23.9 |
| G34120-0606 | 6C5-6RMB | 7236-86453 | 5/16 | 7.9 | 9/16–18 | | 11/16 | 2.00 | 50.8 | 1.05 | 26.7 |
| G34120-0808 | 8C5X-8RMB | 7237-00635 | 13/32 | 10.3 | 3/4–16 | | 15/16 | 2.35 | 59.7 | 1.19 | 30.2 |

# Male JIC 37° Flare - Steel

DOT FMVSS 106–74 Type AII.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | mm | | " | mm |
| G34165-0404 | 4C5-4RMJ | 7236-86431 | 3/16 | 4.8 | 7/16–20 | | 1/2 | 1.79 | 45.5 | 1.09 | 27.7 |
| G34165-0505 | 5C5X-5RMJ | 7237-00655 | 1/4 | 6.4 | 1/2–20 | | 1/2 | 1.96 | 49.8 | 1.19 | 30.2 |
| G34165-0606 | 6C5-6RMJ | 7236-86433 | 5/16 | 7.9 | 9/16–18 | | 9/16 | 2.17 | 55.1 | 1.22 | 31.0 |
| G34165-0808 | 8C5X-8RMJ | 7237-00675 | 13/32 | 10.3 | 3/4–16 | | 3/4 | 2.56 | 65.0 | 1.44 | 36.6 |
| G34165-1010 | 10C5-10RMJ | 7236-86435 | 1/2 | 12.7 | 7/8–14 | | 7/8 | 2.88 | 73.2 | 1.59 | 40.4 |
| G34165-1212 | 12C5X-12RMJ | 7237-00695 | 5/8 | 15.9 | 1 1/16–12 | | 1 1/16 | 3.34 | 84.8 | 1.78 | 45.2 |
| G34165-1616 | 16C5-16RMJ | 7236-86437 | 7/8 | 22.2 | 1 5/16–12 | | 1 5/16 | 2.87 | 72.9 | 1.69 | 42.9 |

# Female JIC 37° Flare Swivel - Steel

DOT FMVSS 106–74 Type AII.




| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm |
| G34170-0606 | 6C5-6RFJX | 7238-86443 | 5/16 | 7.9 | 9/16–18 | | 3/4 | 3/4 | 2.39 | 60.7 | 1.44 | 36.6 |
| G34170-0806 | 8C5X-6RFJX | 7237-00415 | 13/32 | 10.3 | 9/16–18 | | 3/4 | 3/4 | 2.66 | 67.6 | 1.54 | 39.1 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Female JIC 37° Flare Swivel - Steel - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm |
| G34170-1012 | 10C5-12RFJX | 7238-04325 | 1/2 | 12.7 | 1 1/16–12 | | 1 1/4 | 1 1/4 | 3.22 | 81.8 | 1.93 | 49.0 |
| G34170-1212 | 12C5X-12RFJX | 7237-00455 | 5/8 | 15.9 | 1 1/16–12 | | 1 1/4 | 1 1/4 | 3.50 | 88.9 | 1.94 | 49.3 |
| G34170-1616 | 16C5-16RFJX | 7238-86447 | 7/8 | 22.2 | 1 5/16–12 | | 1 1/2 | 1 1/2 | 3.12 | 79.3 | 1.94 | 49.3 |
| G34170-2020 | 20C5-20RFJX | 7238-86394 | 1 1/8 | 28.6 | 1 5/8–12 | | 2 | 2 | 3.56 | 90.4 | 2.19 | 55.6 |
| G34170-2424 | 24C5-24RFJX | 7238-86395 | 1 3/8 | 34.9 | 1 7/8–12 | | 2 1/4 | 2 1/4 | 3.79 | 96.3 | 2.37 | 60.2 |
| G34170-3232 | 32C5-32RFJX | 7238-86396 | 1 13/16 | 46.0 | 2 1/2–12 | | 2 1/2 | 2 7/8 | 4.99 | 126.8 | 2.72 | 69.1 |

## Female JIC 37° Flare Swivel - Brass

DOT FMVSS 106–74 Type AII.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm |
| ⚠ G34170-0606B | 6C5-6RFJXB | 7238-04075 | 5/16 | 7.9 | 9/16–18 | | 3/4 | 3/4 | 2.39 | 60.7 | 1.44 | 36.6 |
| ⚠ G34170-1212B | 12C5-12RFJXB | 7238-04085 | 5/8 | 15.9 | 1 1/16–12 | | 1 1/4 | 1 1/4 | 3.50 | 88.9 | 1.94 | 49.3 |
| ⚠ G34170-1616B | 16C5-16RFJXB | 7238-04095 | 7/8 | 22.2 | 1 5/16–12 | | 1 1/2 | 1 1/2 | 3.12 | 79.3 | 1.94 | 49.3 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## Female JIC 37° Flare Swivel - 45° Bent Tube - Steel

DOT FMVSS 106–74 Type AII.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm | " | mm |
| G34175-0606 | 6C5-6RFJX45 | 7235-86464 | 5/16 | 7.9 | 9/16–18 | | 1/2 | 11/16 | .41 | 10.4 | 2.40 | 61.0 | 1.45 | 36.8 |
| G34175-1212 | 12C5X-12RFJX45S | 7237-00535 | 5/8 | 15.9 | 1 1/16–12 | | 7/8 | 1 1/4 | .78 | 19.8 | 4.27 | 108.5 | 2.71 | 68.8 |
| G34175-1616 | 16C5-16RFJX45 | 7235-86468 | 7/8 | 22.2 | 1 5/16–12 | | — | 1 1/2 | .88 | 22.4 | 4.03 | 102.4 | 2.84 | 72.1 |

# Female JIC 37° Flare Swivel - 90° Bent Tube - Steel

DOT FMVSS 106–74 Type AII.









| Part No. | Descr. | Prod. No. | ⟷ | | ≡ | H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm | " | mm |
| G34180-0606 | 6C5-6RFJX90 | 7235-86471 | 5/16 | 7.9 | 9/16–18 | 1/2 | 11/16 | .84 | 21.3 | 2.28 | 57.9 | 1.33 | 33.8 |
| G34181-0606 | 6C5-6RFJX90L | 7235-04205 | 5/16 | 7.9 | 9/16–18 | 1/2 | 11/16 | 2.19 | 55.6 | 2.28 | 57.9 | 1.33 | 33.8 |
| G34180-1212 | 12C5X-12RFJX90S | 7237-00545 | 5/8 | 15.9 | 1 1/16–12 | 7/8 | 1 1/4 | 1.81 | 46.0 | 4.22 | 107.2 | 2.66 | 67.6 |
| G34181-1212 | 12C5X-12RFJX90L | 7237-00555 | 5/8 | 15.9 | 1 1/16–12 | 7/8 | 1 1/4 | 3.75 | 95.3 | 4.22 | 107.2 | 2.66 | 67.6 |
| G34180-1616 | 16C5-16RFJX90 | 7235-86475 | 7/8 | 22.2 | 1 5/16–12 | — | 1 1/2 | 2.16 | 54.9 | 3.95 | 100.3 | 2.76 | 70.1 |
| G34181-1616 | 16C5-16RFJX90L | 7235-86482 | 7/8 | 22.2 | 1 5/16–12 | — | 1 1/2 | 4.34 | 110.2 | 3.95 | 100.3 | 2.76 | 70.1 |
| G34179-2020 | 20C5-20RFJX90S | 7235-20265 | 1 1/8 | 28.6 | 1 5/8–12 | — | 2 | 2.75 | 69.9 | 5.07 | 128.8 | 3.70 | 94.0 |
| G34181-2020 | 20C5-20RFJX90L | 7235-20255 | 1 1/8 | 28.6 | 1 5/8–12 | — | 2 | 5.50 | 139.7 | 5.26 | 133.6 | 3.89 | 98.8 |

# Male SAE 45° Flare - Steel

DOT FMVSS 106–74 Type AII.





| Part No. | Descr. | Prod. No. | ⟷ | | ≡ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G34195-0404 | 4C5-4RMS | 7236-86414 | 3/16 | 4.8 | 7/16–20 | 1/2 | 1.76 | 44.7 | 1.06 | 26.9 |
| G34195-0505 | 5C5X-5RMS | 7237-00725 | 1/4 | 6.4 | 1/2–20 | 1/2 | 1.96 | 49.8 | 1.19 | 30.2 |
| G34195-0606 | 6C5-6RMS | 7236-86416 | 5/16 | 7.9 | 5/8–18 | 5/8 | 2.23 | 56.6 | 1.28 | 32.5 |
| G34195-0808 | 8C5X-8RMS | 7237-00745 | 13/32 | 10.3 | 3/4–16 | 3/4 | 2.65 | 67.3 | 1.53 | 38.9 |
| G34195-1010 | 10C5-10RMS | 7236-86418 | 1/2 | 12.7 | 7/8–14 | 7/8 | 3.01 | 76.5 | 1.72 | 43.7 |
| G34195-1212 | 12C5X-12RMS | 7237-00765 | 5/8 | 15.9 | 1 1/16–14 | 1 1/16 | 3.50 | 88.9 | 1.94 | 49.3 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female SAE 45° Flare Swivel - Steel

DOT FMVSS 106–74 Type AII.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm |
| G34200-0606 | 6C5-6RFSX | 7238-04235 | 5/16 | 7.9 | 5/8–18 | | 3/4 | 3/4 | 2.42 | 61.5 | 1.47 | 37.3 |
| G34200-1012 | 10C5-12RFSX | 7238-04335 | 1/2 | 12.7 | 1 1/16–14 | | 1 1/4 | 1 1/4 | 3.22 | 81.8 | 1.93 | 49.0 |
| G34200-1212 | 12C5X-12RFSX | 7237-00795 | 5/8 | 15.9 | 1 1/16–14 | | 1 1/4 | 1 1/4 | 3.50 | 88.9 | 1.94 | 49.3 |

# Female SAE 45° Flare Swivel - Brass

DOT FMVSS 106–74 Type AII.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm |
| ⚠ G34200-0606B | 6C5-6RFSXB | 7238-04045 | 5/16 | 7.9 | 5/8–18 | | 3/4 | 3/4 | 2.42 | 61.5 | 1.47 | 37.3 |
| ⚠ G34200-1212B | 12C5-12RFSXB | 7238-04055 | 5/8 | 15.9 | 1 1/16–14 | | 1 1/4 | 1 1/4 | 3.50 | 88.9 | 1.94 | 49.3 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Female SAE 45° Flare Swivel - 45° Bent Tube - Steel

DOT FMVSS 106–74 Type AII.





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm | " | mm |
| G34202-0606 | 6C5-6RFSX45 | 7235-04855 | 5/16 | 7.9 | 5/8–18 | | 1/2 | 3/4 | .41 | 10.4 | 2.42 | 61.5 | 1.47 | 37.3 |


## Female SAE 45° Flare Swivel - 45° Bent Tube - Steel - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm | " | mm |
| G34202-1212 | 12C5X-12RFSX45S | 7237-00835 | 5/8 | 15.9 | 1 1/16–14 | 7/8 | 1 1/4 | .74 | 18.9 | 4.27 | 108.5 | 2.71 | 68.8 |

## Female SAE 45° Flare Swivel - 90° Bent Tube - Steel

DOT FMVSS 106–74 Type AII.





| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm | " | mm |
| G34205-0606 | 6C5-6RFSX90 | 7235-04915 | 5/16 | 7.9 | 5/8–18 | 1/2 | 3/4 | .84 | 21.3 | 2.28 | 57.9 | 1.33 | 33.8 |
| G34206-0606 | 6C5-6RFSX90L | 7235-86497 | 5/16 | 7.9 | 5/8–18 | 1/2 | 3/4 | 2.19 | 55.6 | 2.28 | 57.9 | 1.22 | 31.0 |
| G34205-1212 | 12C5X-12RFSX90S | 7237-00845 | 5/8 | 15.9 | 1 1/16–14 | 7/8 | 1 1/4 | 1.81 | 46.0 | 4.72 | 119.9 | 2.66 | 67.6 |
| G34206-1212 | 12C5X-12RFSX90L | 7237-00855 | 5/8 | 15.9 | 1 1/16–14 | 7/8 | 1 1/4 | 3.75 | 95.3 | 4.22 | 107.2 | 2.16 | 54.9 |

## Dual Seat Female JIC 37°/SAE 45° Flare Swivel - Steel

DOT FMVSS 106–74 Type AII.





| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G34210-0404 | 4C5-4RFJSX | 7238-04215 | 3/16 | 4.8 | 7/16–20 | 9/16 | 9/16 | 1.92 | 48.8 | 1.22 | 31.0 |
| G34210-0504 | 5C5X-4RFJSX | 7237-00875 | 1/4 | 6.4 | 7/16–20 | 9/16 | 9/16 | 2.05 | 52.1 | 1.28 | 32.5 |
| G34210-0505 | 5C5X-5RFJSX | 7237-00885 | 1/4 | 6.4 | 1/2–20 | 11/16 | 11/16 | 2.11 | 53.6 | 1.34 | 34.0 |
| G34210-0608 | 6C5-8RFJSX | 7238-04295 | 5/16 | 7.9 | 3/4–16 | 7/8 | 7/8 | 2.48 | 63.0 | 1.53 | 38.9 |
| G34210-0808 | 8C5X-8RFJSX | 7237-00905 | 13/32 | 10.3 | 3/4–16 | 7/8 | 7/8 | 2.75 | 69.9 | 1.63 | 41.4 |
| G34210-1008 | 10C5-8RFJSX | 7238-04315 | 1/2 | 12.7 | 3/4–16 | 7/8 | 7/8 | 2.93 | 74.4 | 1.64 | 41.7 |
| G34210-1010 | 10C5-10RFJSX | 7238-04255 | 1/2 | 12.7 | 7/8–14 | 1 1/16 | 1 1/16 | 3.10 | 78.7 | 1.81 | 46.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Dual Seat Female JIC 37°/SAE 45° Flare Swivel - Brass

DOT FMVSS 106–74 Type AII.





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| ⚠ G34210-0505B | 5C5-5RFJSXB | 7238-04005 | 1/4 | 6.4 | 1/2–20 | 11/16 | 11/16 | 2.11 | 53.6 | 1.34 | 34.0 |
| ⚠ G34210-0808B | 8C5-8RFJSXB | 7238-04015 | 13/32 | 10.3 | 3/4–16 | 7/8 | 7/8 | 2.75 | 69.9 | 1.63 | 41.4 |
| ⚠ G34210-1010B | 10C5-10RFJSXB | 7238-04025 | 1/2 | 12.7 | 7/8–14 | 1 1/16 | 1 1/16 | 3.10 | 78.7 | 1.81 | 46.0 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 45° Bent Tube - Steel


DOT FMVSS 106–74 Type AII.




| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm | " | mm |
| G34211-0404 | 4C5-4RFJSX45 | 7235-20005 | 3/16 | 4.8 | 7/16–20 | 7/16 | 9/16 | .34 | 8.6 | 1.90 | 48.3 | 1.21 | 30.7 |
| G34211-0505 | 5C5X-5RFJSX45S | 7237-00945 | 1/4 | 6.4 | 1/2–20 | 7/16 | 5/8 | .38 | 9.7 | 2.11 | 53.6 | 1.34 | 34.0 |
| G34211-0608 | 6C5-8RFJSX45 | 7235-20045 | 5/16 | 7.9 | 3/4–16 | 5/8 | 7/8 | .56 | 14.2 | 2.71 | 68.8 | 1.76 | 44.7 |
| G34211-0808 | 8C5X-8RFJSX45S | 7237-00965 | 13/32 | 10.3 | 3/4–16 | 5/8 | 7/8 | .56 | 14.2 | 2.98 | 75.7 | 1.86 | 47.2 |
| G34211-1010 | 10C5-10RFJSX45 | 7235-20035 | 1/2 | 12.7 | 7/8–14 | 3/4 | 1 | .63 | 16.0 | 3.60 | 91.4 | 2.31 | 58.7 |

# Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 90° Bent Tube - Steel


DOT FMVSS 106–74 Type AII.





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm | " | mm |
| G34212-0404 | 4C5-4RFJSX90 | 7235-20105 | 3/16 | 4.8 | 7/16–20 | | 7/16 | 9/16 | .69 | 17.5 | 1.78 | 45.2 | 1.08 | 27.4 |
| G34213-0404 | 4C5-4RFJSX90L | 7235-20205 | 3/16 | 4.8 | 7/16–20 | | 7/16 | 9/16 | 1.81 | 46.0 | 1.78 | 45.2 | 1.08 | 27.4 |
| G34212-0505 | 5C5X-5RFJSX90S | 7237-01005 | 1/4 | 6.4 | 1/2–20 | | 7/16 | 5/8 | .78 | 19.8 | 2.02 | 51.3 | 1.25 | 31.8 |
| G34213-0505 | 5C5X-5RFJSX90L | 7237-01015 | 1/4 | 6.4 | 1/2–20 | | 7/16 | 5/8 | 1.78 | 45.2 | 2.02 | 51.3 | 1.25 | 31.8 |
| G34212-0808 | 8C5X-8RFJSX90S | 7237-01025 | 13/32 | 10.3 | 3/4–16 | | 5/8 | 7/8 | 1.09 | 27.7 | 2.79 | 70.9 | 1.67 | 42.4 |
| G34213-0808 | 8C5X-8RFJSX90L | 7237-01035 | 13/32 | 10.3 | 3/4–16 | | 5/8 | 7/8 | 2.44 | 62.0 | 2.79 | 70.9 | 1.67 | 42.4 |
| G34212-1010 | 10C5-10RFJSX90 | 7235-20135 | 1/2 | 12.7 | 7/8–14 | | 3/4 | 1 | 1.25 | 31.8 | 3.41 | 86.6 | 2.12 | 53.9 |
| G34213-1010 | 10C5-10RFJSX90L | 7235-20235 | 1/2 | 12.7 | 7/8–14 | | 3/4 | 1 | 2.56 | 65.0 | 3.41 | 86.6 | 2.12 | 53.9 |

# Female Flat-Face Swivel - Steel

DOT FMVSS 106–74 Type AII.
SAE J1453 O–Ring Face Seal.





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm |
| G34230-0404 | 4C5-4RFFORX | 7238-01505 | 3/16 | 4.8 | 9/16–18 | | 9/16 | 11/16 | 2.07 | 52.6 | 1.32 | 33.5 |
| G34230-0606 | 6C5-6RFFORX | 7238-01265 | 5/16 | 7.9 | 11/16–16 | | 1/2 | 13/16 | 2.53 | 64.3 | 1.58 | 40.1 |
| G34230-0808 | 8C5X-8RFFORX | 7237-01085 | 13/32 | 10.3 | 13/16–16 | | 13/16 | 15/16 | 2.92 | 74.2 | 1.77 | 45.0 |
| G34230-1010 | 10C5-10RFFORX | 7238-01545 | 1/2 | 12.7 | 1–14 | | 15/16 | 1 1/8 | 3.23 | 82.0 | 1.94 | 49.3 |
| G34230-1212 | 12C5X-12RFFORX | 7237-01105 | 5/8 | 15.9 | 1 3/16–12 | | 7/8 | 1 3/8 | 3.70 | 94.0 | 2.12 | 53.9 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female Flat-Face Swivel - 45° Bent Tube - Steel

DOT FMVSS 106–74 Type AII.
SAE J1453 O–Ring Face Seal.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm | " | mm |
| G34235-0404 | 4C5-4RFFORX45 | 7235-05275 | 3/16 | 4.8 | 9/16–18 | | 1/2 | 11/16 | .41 | 10.4 | 2.42 | 61.5 | 1.67 | 42.4 |

# Female Flat-Face Swivel - 90° Bent Tube - Steel

DOT FMVSS 106–74 Type AII.
SAE J1453 O–Ring Face Seal.





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm | " | mm |
| G34240-0404 | 4C5-4RFFORX90 | 7235-05285 | 3/16 | 4.8 | 9/16–18 | | 1/2 | 11/16 | .82 | 20.8 | 2.17 | 55.1 | 1.42 | 36.1 |
| G34239-0606 | 6C5-6RFFORX90S | 7235-05305 | 5/16 | 7.9 | 11/16–16 | | 1/2 | 13/16 | .90 | 22.9 | 2.77 | 70.4 | 1.82 | 46.2 |

# Special Flange - 90° - Engine Oil Connection (Code 61 2-Bolt)


DOT FMVSS 106–74 Type AII.





| Part No. | Descr. | Prod. No. | ⟷ | | H1 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm | " | mm |
| G34342-2020 | 20C5-20RFL90S | 7235-20275 | 1 1/8 | 28.6 | 1 9/16 | 2.50 | 63.5 | 4.95 | 125.7 | 3.95 | 100.3 |

# Male SAE 45° Flare Inverted Swivel - Steel

DOT FMVSS 106–74 Type AII.





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm |
| G34500-0404 | 4C5-4RMIX | 7235-86372 | 3/16 | 4.8 | 7/16–24 | | 7/16 | 7/16 | 2.41 | 61.2 | 1.72 | 43.7 |
| G34500-0505 | 5C5X-5RMIX | 7237-01155 | 1/4 | 6.4 | 1/2–20 | | 7/16 | 1/2 | 2.63 | 66.8 | 1.84 | 46.7 |
| G34500-0506 | 5C5X-6RMIX | 7237-01165 | 1/4 | 6.4 | 5/8–18 | | 1/2 | 5/8 | 2.59 | 65.8 | 1.82 | 46.2 |
| G34500-0605 | 6C5-5RMIX | 7235-01035 | 5/16 | 7.9 | 1/2–20 | | 1/2 | 1/2 | 2.60 | 66.0 | 1.65 | 41.9 |
| G34500-0606 | 6C5-6RMIX | 7235-86382 | 5/16 | 7.9 | 5/8–18 | | 1/2 | 5/8 | 2.86 | 72.6 | 1.91 | 48.5 |
| G34500-0608 | 6C5-8RMIX | 7235-01055 | 5/16 | 7.9 | 3/4–18 | | 5/8 | 3/4 | 3.23 | 82.0 | 2.28 | 57.9 |
| G34500-0806 | 8C5X-6RMIX | 7237-01205 | 13/32 | 10.3 | 5/8–18 | | 5/8 | 5/8 | 3.13 | 79.5 | 2.01 | 51.1 |
| G34500-0808 | 8C5X-8RMIX | 7237-01215 | 13/32 | 10.3 | 3/4–18 | | 5/8 | 3/4 | 3.49 | 88.7 | 2.37 | 60.2 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male SAE 45° Flare Inverted Swivel - 45° Bent Tube - Steel

DOT FMVSS 106–74 Type AII.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm | " | mm |
| G34502-0404 | 4C5-4RMIX45 | 7235-05005 | 3/16 | 4.8 | 7/16–24 | | 7/16 | 7/16 | .62 | 15.8 | 2.18 | 55.4 | 1.48 | 37.6 |
| G34502-0606 | 6C5-6RMIX45 | 7235-05015 | 5/16 | 7.9 | 5/8–18 | | 1/2 | 5/8 | .94 | 23.9 | 3.03 | 77.0 | 2.09 | 53.1 |
| G34502-0808 | 8C5X-8RMIX45-028 | 7237-01245 | 13/32 | 10.3 | 3/4–18 | | 5/8 | 3/4 | 1.09 | 27.7 | 3.44 | 87.4 | 2.32 | 58.9 |

# Male SAE 45° Flare Inverted Swivel - 90° Bent Tube - Steel

DOT FMVSS 106–74 Type AII.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm | " | mm |
| G34504-0404 | 4C5-4RMIX90 | 7235-05105 | 3/16 | 4.8 | 7/16–24 | | 7/16 | 7/16 | 1.56 | 39.6 | 2.17 | 55.1 | 1.47 | 37.3 |
| G34504-0505 | 5C5X-5RMIX90-042 | 7237-01265 | 1/4 | 6.4 | 1/2–20 | | 7/16 | 1/2 | 1.66 | 42.2 | 2.43 | 61.7 | 1.66 | 42.2 |
| G34504-0606 | 6C5-6RMIX90 | 7235-86387 | 5/16 | 7.9 | 5/8–18 | | 1/2 | 5/8 | 1.69 | 42.9 | 2.64 | 67.1 | 1.69 | 42.9 |
| G34504-0608 | 6C5-8RMIX90 | 7235-05135 | 5/16 | 7.9 | 3/4–18 | | 5/8 | 3/4 | 1.78 | 45.2 | 2.73 | 69.3 | 1.78 | 45.2 |
| G34504-0806 | 8C5X-6RMIX90-043 | 7237-01295 | 13/32 | 10.3 | 5/8–18 | | 5/8 | 5/8 | 1.69 | 42.9 | 2.81 | 71.4 | 1.69 | 42.9 |
| G34504-0808 | 8C5X-8RMIX90-045 | 7237-01305 | 13/32 | 10.3 | 3/4–18 | | 5/8 | 3/4 | 1.78 | 45.2 | 2.90 | 73.7 | 1.78 | 45.2 |

# SAE Male Flareless Assembly - Steel

DOT FMVSS 106–74 Type AII.





| Part No. | Descr. | Prod. No. | ⊖ | | ⋔ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G34510-0404 | 4C5-4RMFA | 7236-04855 | 3/16 | 4.8 | 7/16–20 | 1/2 | 9/16 | 1.81 | 46.0 | 1.06 | 26.9 |
| G34510-0505 | 5C5X-5RMFA | 7237-01325 | 1/4 | 6.4 | 1/2–20 | 9/16 | 5/8 | 1.91 | 48.5 | 1.12 | 28.5 |
| G34510-0604 | 6C5-4RMFA | 7236-04875 | 5/16 | 7.9 | 7/16–20 | 9/16 | 9/16 | 2.03 | 51.6 | 1.13 | 28.7 |
| G34510-0606 | 6C5-6RMFA | 7236-04885 | 5/16 | 7.9 | 9/16–18 | 5/8 | 11/16 | 2.05 | 52.1 | 1.15 | 29.2 |
| G34510-0808 | 8C5X-8RMFA | 7237-01355 | 13/32 | 10.3 | 3/4–16 | 13/16 | 7/8 | 2.52 | 64.0 | 1.37 | 34.8 |
| G34510-1010 | 10C5-10RMFA | 7236-04905 | 1/2 | 12.7 | 7/8–14 | 15/16 | 1 | 2.77 | 70.4 | 1.48 | 37.6 |

# Female Air Brake Swivel - Steel


DOT FMVSS 106–74 Type AII.





| Part No. | Descr. | Prod. No. | ⊖ | | ⋔ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G34540-0606 | 6C5-6RFABX | 7238-04425 | 5/16 | 7.9 | 3/4–20 | 7/8 | 7/8 | 2.29 | 58.2 | 1.34 | 34.0 |
| G34540-0806 | 8C5X-6RFABX | 7237-01395 | 13/32 | 10.3 | 3/4–20 | 7/8 | 7/8 | 2.60 | 66.0 | 1.48 | 37.6 |

# Parker Triple Thread Female Swivel - Steel

DOT FMVSS 106–74 Type AII.





| Part No. | Descr. | Prod. No. | ⊖ | | ⋔ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G34562-1616 | 16C5-16RFZX | 7238-86461 | 7/8 | 22.2 | 1 5/16–14 | 1 1/2 | 1 1/2 | 2.90 | 73.7 | 1.72 | 43.7 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Pipe (NPTF - 30° Cone Seat) - Steel

DOT FMVSS Type A1 (No mandrel required).









| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G35100-0402 | 4C5E-2RMP | 7236-00755 | 3/16 | 4.8 | 1/8–27 | 1/2 | 1.53 | 38.9 | .81 | 20.6 |
| G35100-0404 | 4C5E-4RMP | 7236-00765 | 3/16 | 4.8 | 1/4–18 | 9/16 | 1.75 | 44.5 | 1.03 | 26.2 |
| G35100-0504 | 5C5E-4RMP | 7236-00775 | 1/4 | 6.4 | 1/4–18 | 9/16 | 1.76 | 44.7 | .96 | 24.4 |
| G35100-0604 | 6C5E-4RMP | 7236-00785 | 5/16 | 7.9 | 1/4–18 | 9/16 | 1.85 | 47.0 | 1.00 | 25.4 |
| G35100-0606 | 6C5E-6RMP | 7236-00795 | 5/16 | 7.9 | 3/8–18 | 11/16 | 1.89 | 48.0 | 1.04 | 26.4 |
| G35100-0806 | 8C5E-6RMP | 7236-00805 | 13/32 | 10.3 | 3/8–18 | 11/16 | 2.19 | 55.6 | 1.19 | 30.2 |
| G35100-0808 | 8C5E-8RMP | 7236-00815 | 13/32 | 10.3 | 1/2–14 | 7/8 | 2.29 | 58.2 | 1.29 | 32.8 |
| G35100-1008 | 10C5E-8RMP | 7236-00825 | 1/2 | 12.7 | 1/2–14 | 7/8 | 2.38 | 60.5 | 1.31 | 33.3 |
| G35100-1212 | 12C5E-12RMP | 7236-00835 | 5/8 | 15.9 | 3/4–14 | 1 1/16 | 2.59 | 65.8 | 1.44 | 36.6 |
| G35100-1216 | 12C5E-16RMP | 7236-00845 | 5/8 | 15.9 | 1–11 1/2 | 1 3/8 | 2.87 | 72.9 | 1.72 | 43.7 |
| G35100-1612 | 16C5E-12RMP | 7236-00865 | 7/8 | 22.2 | 3/4–14 | 1 1/16 | 2.49 | 63.3 | 1.43 | 36.3 |
| G35100-1616 | 16C5E-16RMP | 7236-00855 | 7/8 | 22.2 | 1–11 1/2 | 1 3/8 | 2.80 | 71.1 | 1.74 | 44.2 |
| G35100-2020 | 20C5E-20RMP | 7236-00885 | 1 1/8 | 28.6 | 1 1/4–11 1/2 | 1 3/4 | 2.92 | 74.2 | 1.80 | 45.7 |

# Female JIC 37° Flare Swivel - Steel

DOT FMVSS Type A1 (No mandrel required).









| Part No. | Descr. | Prod. No. | ⟷ | | ⫴ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G35170-0606 | 6C5E-6RFJX | 7238-01025 | 5/16 | 7.9 | 9/16–18 | 3/4 | 3/4 | 2.04 | 51.8 | 1.19 | 30.2 |
| G35170-1212 | 12C5E-12RFJX | 7238-01055 | 5/8 | 15.9 | 1 1/16–12 | 1 1/4 | 1 1/4 | 2.92 | 74.2 | 1.78 | 45.2 |
| G35170-1616 | 16C5E-16RFJX | 7238-01065 | 7/8 | 22.2 | 1 5/16–12 | 1 1/2 | 1 1/2 | 2.90 | 73.7 | 1.84 | 46.7 |
| G35170-2020 | 20C5E-20RFJX | 7238-01215 | 1 1/8 | 28.6 | 1 5/8–12 | 1 9/16 | 2 | 3.34 | 84.8 | 2.20 | 55.9 |

# Female JIC 37° Flare Swivel - 45° Bent Tube - Steel

DOT FMVSS Type A1 (No mandrel required).









| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm | " | mm |
| G35175-0606 | 6C5E-6RFJX45 | 7235-20415 | 5/16 | 7.9 | 9/16–18 | 1/2 | 11/16 | .41 | 10.4 | 2.33 | 59.2 | 1.48 | 37.6 |
| G35175-1212 | 12C5E-12RFJX45 | 7235-20455 | 5/8 | 15.9 | 1 1/16–12 | 7/8 | 1 1/4 | .78 | 19.8 | 3.63 | 92.2 | 2.49 | 63.3 |

# Female JIC 37° Flare Swivel - 90° Bent Tube - Steel

DOT FMVSS Type A1 (No mandrel required).





| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm | " | mm |
| G35180-0606 | 6C5E-6RFJX90 | 7235-00305 | 5/16 | 7.9 | 9/16–18 | 1/2 | 11/16 | .91 | 23.4 | 2.21 | 56.1 | 1.78 | 45.2 |
| G35180-1212 | 12C5E-12RFJX90 | 7235-00265 | 5/8 | 15.9 | 1 1/16–12 | 7/8 | 1 1/4 | 1.81 | 46.0 | 3.58 | 90.9 | 2.44 | 62.0 |
| G35180-1616 | 16C5E-16RFJX90 | 7235-00285 | 7/8 | 22.2 | 1 5/16–12 | — | 1 1/2 | 2.16 | 54.9 | 3.72 | 94.5 | 2.66 | 67.6 |
| G35180-2020 | 20C5E-20RFJX90 | 7235-20345 | 1 1/8 | 28.6 | 1 5/8–12 | 2 | 1 9/16 | 2.65 | 67.3 | 5.58 | 141.7 | 4.45 | 113.0 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female SAE 45° Flare Swivel - Steel

DOT FMVSS Type A1 (No mandrel required).









| Part No. | Descr. | Prod. No. | ⊖ | | ≡ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G35200-0606 | 6C5E-6RFSX | 7238-00955 | 5/16 | 7.9 | 5/8–18 | 3/4 | 3/4 | 2.13 | 54.1 | 1.28 | 32.5 |
| G35200-1212 | 12C5E-12RFSX | 7238-00985 | 5/8 | 15.9 | 1 1/16–14 | 1 1/4 | 1 1/4 | 2.94 | 74.7 | 1.80 | 45.7 |

# Female SAE 45° Flare Swivel - 45° Bent Tube - Steel

DOT FMVSS Type A1 (No mandrel required).









| Part No. | Descr. | Prod. No. | ⊖ | | ≡ | H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm | " | mm |
| G35202-0606 | 6C5E-6RFSX45 | 7235-20425 | 5/16 | 7.9 | 5/8–18 | 1/2 | 3/4 | .41 | 10.4 | 2.33 | 59.2 | 1.48 | 37.6 |
| G35202-1212 | 12C5E-12RFSX45 | 7235-20465 | 5/8 | 15.9 | 1 1/16–14 | 7/8 | 1 1/4 | .78 | 19.8 | 3.63 | 92.2 | 2.49 | 63.3 |

# Female SAE 45° Flare Swivel - 90° Bent Tube - Steel

DOT FMVSS Type A1 (No mandrel required).





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm | " | mm |
| G35205-0606 | 6C5E-6RFSX90 | 7235-00315 | 5/16 | 7.9 | 5/8–18 | | 1/2 | 3/4 | .84 | 21.3 | 2.21 | 56.1 | 1.36 | 34.5 |
| G35205-1212 | 12C5E-12RFSX90 | 7235-00275 | 5/8 | 15.9 | 1 1/16–14 | | 7/8 | 1 1/4 | 1.81 | 46.0 | 3.58 | 90.9 | 2.44 | 62.0 |

# Dual Seat Female JIC 37°/SAE 45° Flare Swivel - Steel

DOT FMVSS Type A1 (No mandrel required).





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm |
| G35210-0404 | 4C5E-4RFJSX | 7238-01005 | 3/16 | 4.8 | 7/16–20 | | 1/2 | 9/16 | 1.82 | 46.2 | 1.10 | 27.9 |
| G35210-0505 | 5C5E-5RFJSX | 7238-01015 | 1/4 | 6.4 | 1/2–20 | | 1/2 | 11/16 | 2.00 | 50.8 | 1.21 | 30.7 |
| G35210-0808 | 8C5E-8RFJSX | 7238-01035 | 13/32 | 10.3 | 3/4–16 | | 7/8 | 7/8 | 2.45 | 62.2 | 1.45 | 36.8 |
| G35210-1010 | 10C5E-10RFJSX | 7238-01045 | 1/2 | 12.7 | 7/8–14 | | 1 1/16 | 1 1/16 | 2.72 | 69.1 | 1.65 | 41.9 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 45° Bent Tube - Steel


DOT FMVSS Type A1 (No mandrel required).




| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm | " | mm |
| G35211-0404 | 4C5E-4RFJSX45 | 7235-20405 | 3/16 | 4.8 | 7/16–20 | | 1/2 | 9/16 | .34 | 8.6 | 1.92 | 48.8 | 1.20 | 30.5 |
| G35211-0808 | 8C5E-8RFJSX45 | 7235-20435 | 13/32 | 10.3 | 3/4–16 | | 11/16 | 7/8 | .56 | 14.2 | 2.73 | 69.3 | 1.73 | 43.9 |
| G35211-1010 | 10C5E-10RFJSX45 | 7235-20445 | 1/2 | 12.7 | 7/8–14 | | 3/4 | 1 | .63 | 16.0 | 3.17 | 80.5 | 2.11 | 53.6 |

# Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 90° Bent Tube - Steel


DOT FMVSS Type A1 (No mandrel required).




| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm | " | mm |
| G35212-0404 | 4C5E-4RFJSX90 | 7235-20305 | 3/16 | 4.8 | 7/16–20 | | 1/2 | 9/16 | .69 | 17.5 | 1.72 | 43.7 | 1.00 | 25.4 |
| G35212-0808 | 8C5E-8RFJSX90 | 7235-20315 | 13/32 | 10.3 | 3/4–16 | | 11/16 | 7/8 | 1.09 | 27.7 | 2.54 | 64.5 | 1.54 | 39.1 |
| G35212-1010 | 10C5E-10RFJSX90 | 7235-20325 | 1/2 | 12.7 | 7/8–14 | | 3/4 | 1 | 1.25 | 31.8 | 2.97 | 75.4 | 1.91 | 48.5 |

# Special Flange - 90° - Engine Oil Connection (Code 61 2-Bolt) - Steel


DOT FMVSS Type A1 (No mandrel required).





| Part No. | Descr. | Prod. No. | ⊖ | | H1 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm | " | mm | " | mm |
| G35342-2020 | 20C5E-20RFL90S | 7235-20355 | 1 1/8 | 28.6 | 1 9/16 | 2.50 | 63.5 | 4.95 | 125.7 | 3.82 | 97.0 |

# Male SAE 45° Flare Inverted Swivel - Steel

DOT FMVSS Type A1 (No mandrel required).





| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G35500-0404 | 4C5E-4RMIX | 7235-02855 | 3/16 | 4.8 | 7/16–24 | 1/2 | 7/16 | 2.05 | 52.1 | 1.33 | 33.8 |
| G35500-0505 | 5C5E-5RMIX | 7235-02865 | 1/4 | 6.4 | 1/2–20 | 1/2 | 1/2 | 2.26 | 57.4 | 1.45 | 36.8 |
| G35500-0605 | 6C5E-5RMIX | 7235-02875 | 5/16 | 7.9 | 1/2–20 | 1/2 | 1/2 | 2.39 | 60.7 | 1.54 | 39.1 |
| G35500-0606 | 6C5E-6RMIX | 7235-02885 | 5/16 | 7.9 | 5/8–18 | 1/2 | 5/8 | 2.71 | 68.8 | 1.86 | 47.2 |
| G35500-0808 | 8C5E-8RMIX | 7235-02895 | 13/32 | 10.3 | 3/4–18 | 11/16 | 3/4 | 3.24 | 82.3 | 2.24 | 56.9 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male SAE 45° Flare Inverted Swivel - 45° Bent Tube - Steel

DOT FMVSS Type A1 (No mandrel required).









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm | " | mm |
| G35502-0606 | 6C5E-6RMIX45 | 7235-02795 | 5/16 | 7.9 | 5/8–18 | | 1/2 | 5/8 | .84 | 21.3 | 3.79 | 96.3 | 2.94 | 74.7 |
| G35502-0808 | 8C5E-8RMIX45 | 7235-02905 | 13/32 | 10.3 | 3/4–18 | | 11/16 | 3/4 | 1.09 | 27.7 | 4.24 | 107.7 | 3.24 | 82.3 |

# Male SAE 45° Flare Inverted Swivel - 90° Bent Tube - Steel

DOT FMVSS Type A1 (No mandrel required).









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm | " | mm |
| G35504-0404 | 4C5E-4RMIX90 | 7235-02805 | 3/16 | 4.8 | 7/16–24 | | 1/2 | 7/16 | 1.25 | 31.8 | 2.05 | 52.1 | 1.33 | 33.8 |
| G35504-0505 | 5C5E-5RMIX90 | 7235-02815 | 1/4 | 6.4 | 1/2–20 | | 1/2 | 1/2 | 1.50 | 38.1 | 2.25 | 57.2 | 1.46 | 37.1 |
| G35504-0605 | 6C5E-5RMIX90 | 7235-02825 | 5/16 | 7.9 | 1/2–20 | | 1/2 | 1/2 | 1.50 | 38.1 | 2.39 | 60.7 | 1.54 | 39.1 |
| G35504-0606 | 6C5E-6RMIX90 | 7235-02835 | 5/16 | 7.9 | 5/8–18 | | 1/2 | 5/8 | 1.63 | 41.4 | 2.71 | 68.8 | 1.86 | 47.2 |
| G35504-0808 | 8C5E-8RMIX90 | 7235-02845 | 13/32 | 10.3 | 3/4–18 | | 11/16 | 3/4 | 2.00 | 50.8 | 3.24 | 82.3 | 2.24 | 56.9 |

# SAE Male Flareless Assembly - Steel

DOT FMVSS Type A1 (No mandrel required).









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | " | " | mm | " | mm |
| G35510-0404 | 4C5E-4RMFA | 7236-04955 | 3/16 | 4.8 | | 7/16–20 | 1/2 | 9/16 | 1.68 | 42.7 | .96 | 24.4 |
| G35510-0505 | 5C5E-5RMFA | 7236-04965 | 1/4 | 6.4 | | 1/2–20 | 9/16 | 5/8 | 1.72 | 43.7 | .92 | 23.4 |
| G35510-0604 | 6C5E-4RMFA | 7236-04975 | 5/16 | 7.9 | | 7/16–20 | 9/16 | 9/16 | 2.12 | 53.9 | 1.01 | 25.7 |
| G35510-0606 | 6C5E-6RMFA | 7236-04985 | 5/16 | 7.9 | | 9/16–18 | 5/8 | 11/16 | 1.87 | 47.5 | 1.03 | 26.2 |
| G35510-0808 | 8C5E-8RMFA | 7236-04995 | 13/32 | 10.3 | | 3/4–16 | 13/16 | 7/8 | 2.15 | 54.6 | 1.15 | 29.2 |
| G35510-1010 | 10C5E-10RMFA | 7236-05005 | 1/2 | 12.7 | | 7/8–14 | 15/16 | 1 | 2.34 | 59.4 | 1.27 | 32.3 |

# Parker Triple Thread Female Swivel - Steel

DOT FMVSS Type A1 (No mandrel required).




| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | " | mm | " | mm |
| G35562-1616 | 16C5E-16RFZX | 7238-01075 | 7/8 | 22.2 | 1 5/16–14 | 1 1/2 | 1 1/2 | 2.74 | 69.6 | 1.68 | 42.7 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# HYDRAULIC HOSE FOR C14 COUPLINGS







**The Gates eCrimp program** is a web based utility which allows users and distributors of Gates hydraulic and industrial hose products to find and print the most up to date crimp specifications with nothing more than an internet browser.

This program can be used to find crimp data for all Gates crimpers. Custom result may be printed by selecting the crimper, hose and coupling. Optionally results may also be limited by die set and working pressure.


The eCrimp web application can be directly accessed from a web browser by entering http://eCrimp.Gates.com for the website.

**The eCrimp mobile app** is available for download for the iPhone and iPad from the App Store.


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Pipe (NPTF - 30° Cone Seat) - Stainless Steel





H1





| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G40100-0402S | 4C14-2MP-SS | 7753-00085 | 3/16 | 4.8 | 1/8–27 | 7/16 | 1.26 | 32.0 | .81 | 20.6 |
| G40100-0404S | 4C14-4MP-SS | 7753-00015 | 3/16 | 4.8 | 1/4–18 | 9/16 | 1.47 | 37.3 | 1.02 | 25.9 |
| G40100-0504S | 5C14-4MP-SS | 7753-00025 | 1/4 | 6.4 | 1/4–18 | 9/16 | 1.47 | 37.3 | 1.02 | 25.9 |
| G40100-0604S | 6C14-4MP-SS | 7753-00095 | 5/16 | 7.9 | 1/4–18 | 9/16 | 1.60 | 40.7 | 1.05 | 26.7 |
| G40100-0606S | 6C14-6MP-SS | 7753-00035 | 5/16 | 7.9 | 3/8–18 | 11/16 | 1.63 | 41.4 | 1.08 | 27.4 |
| G40100-0806S | 8C14-6MP-SS | 7753-00105 | 13/32 | 10.3 | 3/8–18 | 11/16 | 1.68 | 42.7 | 1.07 | 27.2 |
| G40100-0808S | 8C14-8MP-SS | 7753-00045 | 13/32 | 10.3 | 1/2–14 | 7/8 | 1.93 | 49.0 | 1.32 | 33.5 |
| G40100-1008S | 10C14-8MP-SS | 7753-00055 | 1/2 | 12.7 | 1/2–14 | 7/8 | 2.05 | 52.1 | 1.35 | 34.3 |
| G40100-1212S | 12C14-12MP-SS | 7753-00065 | 5/8 | 15.9 | 3/4–14 | 1 1/16 | 2.21 | 56.1 | 1.44 | 36.6 |
| G40100-1616S | 16C14-16MP-SS | 7753-00075 | 7/8 | 22.2 | 1–11 1/2 | 1 3/8 | 2.56 | 65.0 | 1.65 | 41.9 |

# Male Pipe (NPTF - 30° Cone Seat) - Brass





H1




| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| ⚠ G40100-0402B | 4C14-2MP-B | 7753-10085 | 3/16 | 4.8 | 1/8–27 | 7/16 | 1.26 | 32.0 | .81 | 20.6 |
| ⚠ G40100-0404B | 4C14-4MP-B | 7753-10015 | 3/16 | 4.8 | 1/4–18 | 9/16 | 1.47 | 37.3 | 1.02 | 25.9 |
| ⚠ G40100-0504B | 5C14-4MP-B | 7753-10025 | 1/4 | 6.4 | 1/4–18 | 9/16 | 1.47 | 37.3 | 1.02 | 25.9 |
| ⚠ G40100-0604B | 6C14-4MP-B | 7753-10095 | 5/16 | 7.9 | 1/4–18 | 9/16 | 1.60 | 40.7 | 1.05 | 26.7 |
| ⚠ G40100-0606B | 6C14-6MP-B | 7753-10035 | 5/16 | 7.9 | 3/8–18 | 11/16 | 1.63 | 41.4 | 1.08 | 27.4 |
| ⚠ G40100-0806B | 8C14-6MP-B | 7753-10105 | 13/32 | 10.3 | 3/8–18 | 11/16 | 1.68 | 42.7 | 1.07 | 27.2 |
| ⚠ G40100-0808B | 8C14-8MP-B | 7753-10045 | 13/32 | 10.3 | 1/2–14 | 7/8 | 1.93 | 49.0 | 1.32 | 33.5 |
| ⚠ G40100-1008B | 10C14-8MP-B | 7753-10055 | 1/2 | 12.7 | 1/2–14 | 7/8 | 2.05 | 52.1 | 1.35 | 34.3 |
| ⚠ G40100-1212B | 12C14-12MP-B | 7753-10065 | 5/8 | 15.9 | 3/4–14 | 1 1/16 | 2.21 | 56.1 | 1.44 | 36.6 |
| ⚠ G40100-1616B | 16C14-16MP-B | 7753-10075 | 7/8 | 22.2 | 1–11 1/2 | 1 3/8 | 2.56 | 65.0 | 1.65 | 41.9 |


⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Dual Seat Female JIC 37°/SAE 45° Flare Swivel - Stainless Steel




| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | mm | " | mm |
| G40170-0404S | 4C14-4FJSX-SS | 7753-00125 | 3/16 | 4.8 | 7/16–20 | | 9/16 | .95 | 24.1 | .87 | 22.1 |
| G40170-0505S | 5C14-5FJSX-SS | 7753-00135 | 1/4 | 6.4 | 1/2–20 | | 11/16 | 1.01 | 25.7 | .94 | 23.9 |
| G40170-0808S | 8C14-8FJSX-SS | 7753-00155 | 13/32 | 10.3 | 3/4–16 | | 7/8 | 1.30 | 33.0 | 1.13 | 28.7 |
| G40170-1010S | 10C14-10FJSX-SS | 7753-00165 | 1/2 | 12.7 | 7/8–14 | | 1 1/16 | 1.47 | 37.3 | 1.29 | 32.8 |
| G40170-1616S | 16C14-16FJSX-SS | 7753-00185 | 7/8 | 22.2 | 1 5/16–12 | | 1 1/2 | 1.75 | 44.5 | 1.46 | 37.1 |

# Dual Seat Female JIC 37°/SAE 45° Flare Swivel - Brass





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | mm | " | mm |
| ⚠ G40170-0404B | 4C14-4FJSX-B | 7753-10125 | 3/16 | 4.8 | 7/16–20 | | 9/16 | .95 | 24.1 | .79 | 20.1 |
| ⚠ G40170-0505B | 5C14-5FJSX-B | 7753-10135 | 1/4 | 6.4 | 1/2–20 | | 11/16 | 1.01 | 25.7 | .94 | 23.9 |
| ⚠ G40170-0808B | 8C14-8FJSX-B | 7753-10155 | 13/32 | 10.3 | 3/4–16 | | 7/8 | 1.30 | 33.0 | 1.13 | 28.7 |
| ⚠ G40170-1010B | 10C14-10FJSX-B | 7753-10165 | 1/2 | 12.7 | 7/8–14 | | 1 1/16 | 1.47 | 37.3 | 1.29 | 32.8 |
| ⚠ G40170-1616B | 16C14-16FJSX-B | 7753-10185 | 7/8 | 22.2 | 1 5/16–12 | | 1 1/2 | 1.75 | 44.5 | 1.46 | 37.1 |


⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Female JIC 37° Flare Swivel - Stainless Steel





| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G40170-0606S | 6C14-6FJX-SS | 7753-00145 | 5/16 | 7.9 | 9/16–18 | 3/4 | 1.19 | 30.2 | 1.01 | 25.7 |
| G40170-1212S | 12C14-12FJX-SS | 7753-00175 | 5/8 | 15.9 | 1 1/16–12 | 1 1/4 | 1.56 | 39.6 | 1.36 | 34.5 |

## Female JIC 37° Flare Swivel - Brass









| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| ⚠ G40170-0606B | 6C14-6FJX-B | 7753-10145 | 5/16 | 7.9 | 9/16–18 | 3/4 | 1.19 | 30.2 | 1.01 | 25.7 |
| ⚠ G40170-1212B | 12C14-12FJX-B | 7753-10175 | 5/8 | 15.9 | 1 1/16–12 | 1 1/4 | 1.56 | 39.6 | 1.36 | 34.5 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## Female JIC 37° Flare Swivel - 45° Bent Tube - Steel









| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G40175-0404 | 4C14-4FJX45 | 7753-20495 | 3/16 | 4.8 | 7/16–20 | 9/16 | .41 | 10.4 | 1.69 | 42.9 | 1.25 | 31.8 |

## Female JIC 37° Flare Swivel - 45° Bent Tube - Steel - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | mm | " | mm | " | mm |
| G40175-0505 | 5C14-5FJX45 | 7753-20505 | 1/4 | 6.4 | 1/2–20 | 5/8 | .49 | 12.5 | 1.85 | 47.0 | 1.44 | 36.6 |
| G40175-0606 | 6C14-6FJX45 | 7753-20515 | 5/16 | 7.9 | 9/16–18 | 11/16 | .55 | 14.0 | 2.13 | 54.1 | 1.62 | 41.2 |
| G40175-0808 | 8C14-8FJX45 | 7753-20525 | 13/32 | 10.3 | 3/4–16 | 7/8 | .63 | 16.0 | 2.44 | 62.0 | 1.88 | 47.8 |
| G40175-1010 | 10C14-10FJX45 | 7753-20535 | 1/2 | 12.7 | 7/8–14 | 1 | .75 | 19.1 | 2.78 | 70.6 | 2.08 | 52.8 |
| G40175-1212 | 12C14-12FJX45 | 7753-20545 | 5/8 | 15.9 | 1 1/16–12 | 1 1/4 | .90 | 22.9 | 3.92 | 99.6 | 3.15 | 80.0 |
| G40175-1616 | 16C14-16FJX45 | 7753-20555 | 7/8 | 22.2 | 1 5/16–12 | 1 1/2 | 1.13 | 28.7 | 4.77 | 121.2 | 3.86 | 98.0 |

## Female JIC 37° Flare Swivel - 90° Bent Tube - Steel









| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | mm | " | mm | " | mm |
| G40179-0404 | 4C14-4FJX90 | 7753-20565 | 3/16 | 4.8 | 7/16–20 | 9/16 | .71 | 18.0 | 1.42 | 36.1 | 1.00 | 25.4 |
| G40179-0505 | 5C14-5FJX90 | 7753-20575 | 1/4 | 6.4 | 1/2–20 | 5/8 | .88 | 22.4 | 1.55 | 39.4 | 1.06 | 26.9 |
| G40179-0606 | 6C14-6FJX90 | 7753-20585 | 5/16 | 7.9 | 9/16–18 | 11/16 | 1.00 | 25.4 | 1.80 | 45.7 | 1.25 | 31.8 |
| G40179-0808 | 8C14-8FJX90 | 7753-20595 | 13/32 | 10.3 | 3/4–16 | 7/8 | 1.18 | 30.0 | 2.10 | 53.3 | 1.50 | 38.1 |
| G40179-1010 | 10C14-10FJX90 | 7753-20605 | 1/2 | 12.7 | 7/8–14 | 1 | 1.50 | 38.1 | 2.47 | 62.7 | 1.81 | 46.0 |
| G40179-1212 | 12C14-12FJX90 | 7753-20615 | 5/8 | 15.9 | 1 1/16–12 | 1 1/4 | 2.00 | 50.8 | 3.88 | 98.6 | 3.11 | 79.0 |
| G40179-1616 | 16C14-16FJX90 | 7753-20625 | 7/8 | 22.2 | 1 5/16–12 | 1 1/2 | 2.48 | 63.0 | 4.64 | 117.9 | 3.73 | 94.7 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female SAE 45° Flare Swivel - Brass









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| ⚠ G40200-0606B | 6C14-6FSX-B | 7753-10195 | 5/16 | 7.9 | 5/8–18 | 3/4 | 1.19 | 30.2 | 1.01 | 25.7 |
| ⚠ G40200-1212B | 12C14-12FSX-B | 7753-10205 | 5/8 | 15.9 | 1 1/16–14 | 1 1/4 | 1.56 | 39.6 | 1.36 | 34.5 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


# Female SAE 45° Flare Swivel - 45° Bent Tube - Steel





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G40202-0404 | 4C14-4FSX45 | 7753-20215 | 3/16 | 4.8 | 7/16–20 | 9/16 | .41 | 10.4 | 1.69 | 42.9 | 1.25 | 31.8 |
| G40202-0505 | 5C14-5FSX45 | 7753-20225 | 1/4 | 6.4 | 1/2–20 | 5/8 | .49 | 12.5 | 1.85 | 47.0 | 1.44 | 36.6 |
| G40202-0606 | 6C14-6FSX45 | 7753-20235 | 5/16 | 7.9 | 5/8–18 | 3/4 | .55 | 14.0 | 2.13 | 54.1 | 1.62 | 41.2 |
| G40202-0808 | 8C14-8FSX45 | 7753-20245 | 13/32 | 10.3 | 3/4–16 | 7/8 | .63 | 16.0 | 2.44 | 62.0 | 1.88 | 47.8 |
| G40202-1010 | 10C14-10FSX45 | 7753-20635 | 1/2 | 12.7 | 7/8–14 | 1 | .75 | 19.1 | 2.78 | 70.6 | 2.12 | 53.9 |
| G40202-1212 | 12C14-12FSX45 | 7753-20645 | 5/8 | 15.9 | 1 1/16–14 | 1 1/4 | .90 | 22.9 | 3.92 | 99.6 | 3.15 | 80.0 |


# Female SAE 45° Flare Swivel - 90° Bent Tube - Steel




| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G40205-0404 | 4C14-4FSX90 | 7753-20255 | 3/16 | 4.8 | 7/16–20 | 9/16 | .71 | 18.0 | 1.42 | 36.1 | 1.00 | 25.4 |
| G40205-0505 | 5C14-5FSX90 | 7753-20265 | 1/4 | 6.4 | 1/2–20 | 5/8 | .88 | 22.4 | 1.55 | 39.4 | 1.06 | 26.9 |
| G40205-0606 | 6C14-6FSX90 | 7753-20275 | 5/16 | 7.9 | 5/8–18 | 3/4 | 1.00 | 25.4 | 1.80 | 45.7 | 1.25 | 31.8 |
| G40205-0808 | 8C14-8FSX90 | 7753-20285 | 13/32 | 10.3 | 3/4–16 | 7/8 | 1.18 | 30.0 | 2.10 | 53.3 | 1.50 | 38.1 |
| G40205-1010 | 10C14-10FSX90 | 7753-20295 | 1/2 | 12.7 | 7/8–14 | 1 1/16 | 1.50 | 38.1 | 2.47 | 62.7 | 1.81 | 46.0 |
| G40205-1212 | 12C14-12FSX90 | 7753-20665 | 5/8 | 15.9 | 1 1/16–14 | 1 1/4 | 2.00 | 50.8 | 3.88 | 98.6 | 3.11 | 79.0 |

# Air Brake Compression - Brass





| Part No. | Descr. | Prod. No. | ⊖ | | ⫴ | H1 | H2 | L | | C | | ⫴ |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm | " |
| ⚠ G40460-0808B | 8C14-8ABC-B | 7753-10365 | 13/32 | 10.3 | 11/16–20 | 7/8 | 13/16 | 1.71 | 43.4 | 1.10 | 27.9 | .50 |
| ⚠ G40460-1010B | 10C14-10ABC-B | 7753-10385 | 1/2 | 12.7 | 13/16–18 | 7/8 | 15/16 | 1.89 | 48.0 | 1.19 | 30.2 | .63 |
| ⚠ G40460-1212B | 12C14-12ABC-B | 7753-10395 | 5/8 | 15.9 | 1–18 | 1 1/16 | 1 1/8 | 2.13 | 54.1 | 1.36 | 34.5 | .75 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Straight Tube Assembly - Brass





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | H2 | L | | C | | ⬡ |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm | " |
| ⚠ G40461-1008B | 10C14-8STA-B | 7753-10415 | 1/2 | 12.7 | 11/16–20 | | 3/4 | 13/16 | 3.18 | 80.8 | 2.21 | 56.1 | .50 |
| ⚠ G40461-1010B | 10C14-10STA-B | 7753-10425 | 1/2 | 12.7 | 13/16–18 | | 3/4 | 15/16 | 3.50 | 88.9 | 2.53 | 64.3 | .63 |
| ⚠ G40461-1212B | 12C14-12STA-B | 7753-10435 | 5/8 | 15.9 | 1–18 | | 7/8 | 1 1/8 | 3.67 | 93.2 | 2.61 | 66.3 | .75 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


# SAE Male Inverted Swivel - Steel





| Part No. | Descr. | Prod. No. | ⟷ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm |
| G40500-0404 | 4C14-4MIX | 7753-20305 | 3/16 | 4.8 | 7/16–24 | | 7/16 | 7/16 | 1.84 | 46.7 | 1.39 | 35.3 |
| G40500-0505 | 5C14-5MIX | 7753-20315 | 1/4 | 6.4 | 1/2–20 | | 1/2 | 1/2 | 1.90 | 48.3 | 1.45 | 36.8 |
| G40500-0606 | 6C14-6MIX | 7753-20325 | 5/16 | 7.9 | 5/8–18 | | 9/16 | 5/8 | 2.07 | 52.6 | 1.52 | 38.6 |
| G40500-0808 | 8C14-8MIX | 7753-20335 | 13/32 | 10.3 | 3/4–18 | | 5/8 | 3/4 | 2.21 | 56.1 | 1.60 | 40.6 |
| G40500-1010 | 10C14-10MIX | 7753-20345 | 1/2 | 12.7 | 7/8–18 | | 3/4 | 7/8 | 2.47 | 62.7 | 1.77 | 45.0 |


# SAE Male Inverted Swivel - 45° Bent Tube - Steel





| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | " | mm | " | mm | " | mm |
| G40502-0404 | 4C14-4MIX45 | 7753-20355 | 3/16 | 4.8 | 7/16–24 | 7/16 | 7/16 | .73 | 18.6 | 1.99 | 50.6 | 1.53 | 38.9 |
| G40502-0606 | 6C14-6MIX45 | 7753-20365 | 5/16 | 7.9 | 5/8–18 | 9/16 | 5/8 | .94 | 23.9 | 2.48 | 63.0 | 1.93 | 49.0 |
| G40502-0808 | 8C14-8MIX45 | 7753-20375 | 13/32 | 10.3 | 3/4–18 | 5/8 | 3/4 | 1.14 | 29.0 | 2.95 | 74.9 | 2.10 | 53.3 |
| G40502-1010 | 10C14-10MIX45 | 7753-20695 | 1/2 | 12.7 | 7/8–18 | 3/4 | 7/8 | 1.34 | 34.0 | 3.37 | 85.6 | 2.67 | 67.8 |
| G40502-1212 | 12C14-12MIX45 | 7753-20705 | 5/8 | 15.9 | 1 1/16–16 | 7/8 | 1 1/16 | 1.54 | 39.1 | 4.56 | 115.8 | 3.79 | 96.3 |

# SAE Male Inverted Swivel - 90° Bent Tube - Steel








| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | " | mm | " | mm | " | mm |
| G40504-0404 | 4C14-4MIX90 | 7753-20385 | 3/16 | 4.8 | 7/16–24 | 7/16 | 7/16 | 1.30 | 33.0 | 1.42 | 36.1 | .97 | 24.6 |
| G40504-0505 | 5C14-5MIX90 | 7753-20395 | 1/4 | 6.4 | 1/2–20 | 1/2 | 1/2 | 1.48 | 37.6 | 1.54 | 39.1 | 1.09 | 27.7 |
| G40504-0606 | 6C14-6MIX90 | 7753-20405 | 5/16 | 7.9 | 5/8–18 | 9/16 | 5/8 | 1.63 | 41.4 | 1.80 | 45.7 | 1.25 | 31.8 |
| G40504-0808 | 8C14-8MIX90 | 7753-20415 | 13/32 | 10.3 | 3/4–18 | 5/8 | 3/4 | 1.91 | 48.5 | 2.10 | 53.3 | 1.77 | 45.0 |
| G40504-1010 | 10C14-10MIX90 | 7753-20425 | 1/2 | 12.7 | 7/8–18 | 3/4 | 7/8 | 2.16 | 54.9 | 2.47 | 62.7 | 1.77 | 45.0 |
| G40504-1212 | 12C14-12MIX90 | 7753-20715 | 5/8 | 15.9 | 1 1/16–16 | 7/8 | 1 1/16 | 2.66 | 67.6 | 3.60 | 91.4 | 2.83 | 71.9 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Two-Bolt Flange Swivel - Brass (Steel Flange) - Laundry Flange




| Part No. | Descr. | Prod. No. | ⊖ | | L | | C | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm |
| ⚠ G40543-1212 | 12C14-12TBFLX | 7753-10265 | 5/8 | 15.9 | 2.27 | 57.7 | .59 | 15.0 |
| ⚠ G40543-1616 | 16C14-16TBFLX | 7753-10275 | 7/8 | 22.2 | 2.45 | 62.2 | .81 | 20.6 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## C14 Assembly with Two Female Dual Seat JIC 37°/SAE 45° Flare Swivel (FJSX) Couplings-Steel



| Part No. | Descr. | Prod. No. | ⊖ | | L | |
|---|---|---|---|---|---|---|
| | | | " | mm | " | mm |
| G89170-1018 | 10C14-10FJSX-10FJSX-18 | 4479-0002 | 1/2 | 12.7 | 18.00 | 457.2 |
| G89170-1024 | 10C14-10FJSX-10FJSX-24 | 4479-0003 | 1/2 | 12.7 | 24.00 | 609.6 |
| G89170-1030 | 10C14-10FJSX-10FJSX-30 | 4479-0004 | 1/2 | 12.7 | 30.00 | 762.0 |
| G89170-1036 | 10C14-10FJSX-10FJSX-36 | 4479-0005 | 1/2 | 12.7 | 36.00 | 914.4 |
| G89170-1042 | 10C14-10FJSX-10FJSX-42 | 4479-0006 | 1/2 | 12.7 | 42.00 | 1066.8 |
| G89170-1048 | 10C14-10FJSX-10FJSX-48 | 4479-0007 | 1/2 | 12.7 | 48.00 | 1219.2 |
| G89170-1054 | 10C14-10FJSX-10FJSX-54 | 4479-0008 | 1/2 | 12.7 | 54.00 | 1371.6 |
| G89170-1072 | 10C14-10FJSX-10FJSX-72 | 4479-0009 | 1/2 | 12.7 | 72.00 | 1828.8 |
| G89170-1084 | 10C14-10FJSX-10FJSX-84 | 4479-0010 | 1/2 | 12.7 | 84.00 | 2133.6 |

## C14 Assembly with Two Air Brake Compression (ABC) Couplings - Steel



| Part No. | Descr. | Prod. No. | ⊖ | | L | |
|---|---|---|---|---|---|---|
| | | | " | mm | " | mm |
| G89460-1018 | 10C14-10ABC-10ABC-18 | 4479-0011 | 1/2 | 12.7 | 18.00 | 457.2 |
| G89460-1024 | 10C14-10ABC-10ABC-24 | 4479-0012 | 1/2 | 12.7 | 24.00 | 609.6 |

# C14 Assembly with Two Straight Tube Assembly (STA) Couplings - Steel



| Part No. | Descr. | Prod. No. | ⟷ | | L | |
|---|---|---|---|---|---|---|
| | | | " | mm | " | mm |
| G89461-1024 | 10C14-10STA-10STA-24 | 4479-0014 | 1/2 | 12.7 | 24.00 | 609.6 |
| G89461-1036 | 10C14-10STA-10STA-36 | 4479-0015 | 1/2 | 12.7 | 36.00 | 914.4 |
| G89461-1224 | 12C14-12STA-12STA-24 | 4479-0020 | 5/8 | 15.9 | 24.00 | 609.6 |

# C14 One Straight Tube Assembly (STA) and One Air Brake Compression (ABC) Couplings - Steel



| Part No. | Descr. | Prod. No. | ⟷ | | L | |
|---|---|---|---|---|---|---|
| | | | " | mm | " | mm |
| G89462-1018 | 10C14-10STA-10ABC-18 | 4479-0016 | 1/2 | 12.7 | 18.00 | 457.2 |
| G89462-1024 | 10C14-10STA-10ABC-24 | 4479-0017 | 1/2 | 12.7 | 24.00 | 609.6 |
| G89462-1036 | 10C14-10STA-10ABC-36 | 4479-0018 | 1/2 | 12.7 | 36.00 | 914.4 |
| G89462-1048 | 10C14-10STA-10ABC-48 | 4479-0019 | 1/2 | 12.7 | 48.00 | 1219.2 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# HYDRAULIC HOSE FOR GL COUPLINGS






















**The Gates eCrimp program** is a web based utility which allows users and distributors of Gates hydraulic and industrial hose products to find and print the most up to date crimp specifications with nothing more than an internet browser.

This program can be used to find crimp data for all Gates crimpers. Custom result may be printed by selecting the crimper, hose and coupling. Optionally results may also be limited by die set and working pressure.

The eCrimp web application can be directly accessed from a web browser by entering http://eCrimp.Gates.com for the website.


**The eCrimp mobile app** is available for download for the iPhone and iPad from the App Store.


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Pipe (NPTF - 30° Cone Seat)

Special GL Dies Required.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | mm | " | mm |
| G43100-1212 | 12GL-12MP | 7348-00015 | 3/4 | 19.1 | 3/4–14 | | 1 3/4 | 3.46 | 87.9 | 1.46 | 37.1 |
| G43100-1216 | 12GL-16MP | 7348-00025 | 3/4 | 19.1 | 1–11 1/2 | | 1 3/8 | 1.77 | 45.0 | 1.64 | 41.7 |
| G43100-1616 | 16GL-16MP | 7348-00035 | 1 | 25.4 | 1–11 1/2 | | 1 3/8 | 4.11 | 104.4 | 1.88 | 47.8 |
| G43100-2020 | 20GL-20MP | 7348-00045 | 1 1/4 | 31.8 | 1 1/4–11 1/2 | | 1 3/4 | 2.13 | 54.1 | 2.09 | 53.1 |
| G43100-2424 | 24GL-24MP | 7348-00055 | 1 1/2 | 38.1 | 1 1/2–11 1/2 | | 2 | 4.83 | 122.7 | 2.19 | 55.6 |
| G43100-3232 | 32GL-32MP | 7348-00065 | 2 | 50.8 | 2–11 1/2 | | 2 1/2 | 5.39 | 136.9 | 2.33 | 59.2 |

# Male Pipe Swivel (NPTF - without 30° Cone Seat)

NOT TO BE USED AS A LIVE SWIVEL.
Special GL Dies Required.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | mm | " | mm |
| G43105-1616 | 16GL-16MPX | 7348-00115 | 1 | 25.4 | 1–11 1/2 | | 1 5/8 | 4.73 | 120.1 | 2.50 | 63.5 |

# Female JIC 37° Flare Swivel

Special GL Dies Required.





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm |
| G43170-1212 | 12GL-12FJX | 7348-00205 | 3/4 | 19.1 | 1 1/16–12 | | 1 1/16 | 1 1/4 | 3.68 | 93.5 | 1.67 | 42.4 |


## Female JIC 37° Flare Swivel - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm |
| G43170-1214 | 12GL-14FJX | 7348-00215 | 3/4 | 19.1 | 1 3/16–12 | | 1 1/8 | 1 3/8 | 3.65 | 92.7 | 1.64 | 41.7 |
| G43170-1216 | 12GL-16FJX | 7348-00225 | 3/4 | 19.1 | 1 5/16–12 | | 1 1/4 | 1 1/2 | 3.78 | 96.0 | 1.77 | 45.0 |
| G43170-1616 | 16GL-16FJX | 7348-00235 | 1 | 25.4 | 1 5/16–12 | | 1 3/8 | 1 1/2 | 4.17 | 105.9 | 1.94 | 49.3 |
| G43170-2020 | 20GL-20FJX | 7348-00245 | 1 1/4 | 31.8 | 1 5/8–12 | | 1 3/4 | 2 | 4.58 | 116.3 | 2.26 | 57.4 |
| G43170-2420 | 24GL-20FJX | 7348-00195 | 1 1/2 | 38.1 | 1 5/8–12 | | 1 3/4 | 2 | 4.84 | 122.9 | 2.20 | 55.9 |
| G43170-2424 | 24GL-24FJX | 7348-00255 | 1 1/2 | 38.1 | 1 7/8–12 | | 2 | 2 1/4 | 5.19 | 131.8 | 2.55 | 64.8 |
| G43170-3232 | 32GL-32FJX | 7348-00265 | 2 | 50.8 | 2 1/2–12 | | 2 1/2 | 2 7/8 | 5.98 | 151.9 | 2.92 | 74.2 |
| G43170-4040 | 40GL-40FJX | 7305-05475 | 2 1/2 | 63.5 | 3–12 | | 3 | 3 1/2 | 5.36 | 136.1 | 2.91 | 73.9 |

## Female JIC 37° Flare Swivel - 45° Bent Tube

Special GL Dies Required.









| Part No. | Descr. | Prod. No. | ⊖ | | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | mm | " | mm | " | mm |
| G43174-1212 | 12GL-12FJX45S-021 | 7348-01265 | 3/4 | 19.1 | 1 1/16–12 | | 1 1/4 | .83 | 21.1 | 4.76 | 120.9 | 2.76 | 70.1 |

## Female JIC 37° Flare Swivel - 90° Bent Tube

Special GL Dies Required.





| Part No. | Descr. | Prod. No. | ⊖ | | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | mm | " | mm | " | mm |
| G43179-1212 | 12GL-12FJX90S | 7348-01385 | 3/4 | 19.1 | 1 1/16–12 | | 1 1/4 | 1.89 | 48.0 | 4.61 | 117.1 | 2.60 | 66.0 |
| G43179-1616 | 16GL-16FJX90S | 7348-01485 | 1 | 25.4 | 1 5/16–12 | | 1 1/2 | 2.20 | 55.9 | 5.12 | 130.1 | 2.88 | 73.2 |
| G43180-2020 | 20GL-20FJX90M | 7348-01525 | 1 1/4 | 31.8 | 1 5/8–12 | | 2 | 3.07 | 78.0 | 6.24 | 158.5 | 3.91 | 99.3 |
| G43180-2420 | 24GL-20FJX90M | 7348-01585 | 1 1/2 | 38.1 | 1 5/8–12 | | 2 | 3.07 | 78.0 | 6.24 | 158.5 | 3.91 | 99.3 |
| G43181-2420 | 24GL-20FJX90L | 7348-01595 | 1 1/2 | 38.1 | 1 5/8–12 | | 2 | 5.08 | 129.0 | 5.59 | 142.0 | 2.96 | 75.2 |


## Female JIC 37° Flare Swivel - 90° Bent Tube - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G43183-2424 | 24GL-24FJX90-092 | 7348-01545 | 1 1/2 | 38.1 | 1 7/8–12 | 2 1/4 | 4.05 | 102.9 | 7.10 | 180.3 | 4.85 | 123.2 |

## Female Flat-Face Swivel

SAE J1453 O–Ring Face Seal.
Special GL Dies Required.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm | " | mm |
| G43230-1212 | 12GL-12FFORX | 7348-00305 | 3/4 | 19.1 | 1 3/16–12 | 1 1/16 | 1 3/8 | 3.78 | 96.0 | 1.77 | 45.0 | | |
| G43230-1616 | 16GL-16FFORX | 7348-00355 | 1 | 25.4 | 1 7/16–12 | 1 3/8 | 1 5/8 | 4.46 | 113.3 | 2.22 | 56.4 | | |
| G43230-2020 | 20GL-20FFORX | 7348-00365 | 1 1/4 | 31.8 | 1 11/16–12 | 1 3/4 | 1 7/8 | 4.50 | 114.3 | 2.18 | 55.4 | | |
| G43230-2424 | 24GL-24FFORX | 7348-00375 | 1 1/2 | 38.1 | 2–12 | 1 3/8 | 2 1/4 | 3.98 | 101.1 | 1.74 | 44.2 | | |

## Female Flat-Face Swivel - 45° Bent Tube

SAE J1453 O–Ring Face Seal.
Special GL Dies Required.









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G43234-1212 | 12GL-12FFORX45S | 7348-00405 | 3/4 | 19.1 | 1 3/16–12 | 1 3/8 | .83 | 21.1 | 4.67 | 118.6 | 2.66 | 67.6 |
| G43234-1616 | 16GL-16FFORX45S | 7348-00415 | 1 | 25.4 | 1 7/16–12 | 1 5/8 | .94 | 23.9 | 5.08 | 129.0 | 2.85 | 72.4 |
| G43234-2020 | 20GL-20FFORX45S | 7348-00425 | 1 1/4 | 31.8 | 1 11/16–12 | 1 7/8 | .98 | 24.9 | 5.81 | 147.6 | 3.49 | 88.7 |

# Female Flat-Face Swivel - 90° Bent Tube

SAE J1453 O–Ring Face Seal.
Special GL Dies Required.





| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G43239-1212 | 12GL-12FFORX90S | 7348-00455 | 3/4 | 19.1 | 1 3/16–12 | 1 3/8 | 1.89 | 48.0 | 4.28 | 108.7 | 2.28 | 57.9 |
| G43240-1212 | 12GL-12FFORX90M | 7348-02155 | 3/4 | 19.1 | 1 3/16–12 | 1 1/4 | 1.89 | 48.0 | 4.61 | 117.1 | 2.60 | 66.0 |
| G43239-1616 | 16GL-16FFORX90S | 7348-00465 | 1 | 25.4 | 1 7/16–12 | 1 5/8 | 2.20 | 55.9 | 5.11 | 129.8 | 2.88 | 73.2 |
| G43239-2020 | 20GL-20FFORX90S | 7348-00475 | 1 1/4 | 31.8 | 1 11/16–12 | 1 7/8 | 2.52 | 64.0 | 5.51 | 140.0 | 3.19 | 81.0 |
| G43240-2424 | 24GL-24FFORX90M | 7350-24985 | 1 1/2 | 38.1 | 2–12 | 2 1/3 | 3.39 | 86.1 | 7.26 | 184.4 | 4.62 | 117.4 |

# Code 61 O-Ring Flange

Special GL Dies Required.





| Part No. | Descr. | Prod. No. | ⊖ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| G43300-1212 | 12GL-12FL | 7348-00505 | 3/4 | 19.1 | 1.50 | 38.1 | 3.86 | 98.1 | 1.85 | 47.0 | .27 | 6.9 |
| G43300-1616 | 16GL-16FL | 7348-00555 | 1 | 25.4 | 1.75 | 44.5 | 3.78 | 96.0 | 1.54 | 39.1 | .32 | 8.1 |
| G43300-2020 | 20GL-20FL | 7348-00525 | 1 1/4 | 31.8 | 2.00 | 50.8 | 4.43 | 112.5 | 2.11 | 53.6 | .32 | 8.1 |
| G43300-2424 | 24GL-24FL | 7348-00535 | 1 1/2 | 38.1 | 2.38 | 60.5 | 4.94 | 125.5 | 2.30 | 58.4 | .32 | 8.1 |
| G43300-3232 | 32GL-32FL | 7348-00545 | 2 | 50.8 | 2.81 | 71.4 | 5.61 | 142.5 | 2.54 | 64.5 | .38 | 9.7 |
| G43300-3240 | 32GL-40FL | 7350-25575 | 2 | 50.8 | 3.31 | 84.1 | 5.61 | 142.5 | 2.55 | 64.7 | .38 | 9.7 |
| G43300-4040 | 40GL-40FL | 7305-05505 | 2 1/2 | 63.5 | 3.31 | 84.1 | 5.66 | 143.8 | 3.15 | 80.0 | .38 | 9.7 |
| G43300-4048 | 40GL-48FL | 7305-05605 | 2 1/2 | 63.5 | 4.00 | 101.6 | 5.66 | 143.8 | 3.21 | 81.5 | .38 | 9.7 |
| G43300-4056 | 40GL-56FL | 7305-05705 | 2 1/2 | 63.5 | 4.50 | 114.3 | 5.33 | 135.4 | 2.77 | 70.4 | .44 | 11.2 |
| G43300-4064 | 40GL-64FL | 7305-05795 | 2 1/2 | 63.5 | 5.00 | 127.0 | 5.33 | 135.4 | 2.88 | 73.2 | .44 | 11.2 |
| G43300-4848 | 48GL-48FL | 7305-05805 | 3 | 76.2 | 4.00 | 101.6 | 6.54 | 166.1 | 3.46 | 87.9 | .38 | 9.7 |
| G43300-5656 | 56GL-56FL | 7305-06305 | 3 1/2 | 88.9 | 4.50 | 114.3 | 6.70 | 170.2 | 3.06 | 77.7 | .44 | 11.2 |
| G43300-6464 | 64GL-64FL | 7305-06695 | 4 | 101.6 | 5.00 | 127.0 | 7.74 | 196.6 | 3.70 | 94.0 | .44 | 11.2 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Code 61 O-Ring Flange - 22° Bent Tube


Special GL Dies Required.




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G43302-2424 | 24GL-24FL22M-018 | 7348-00575 | 1 1/2 | 38.1 | 2.38 | 60.5 | .71 | 18.0 | 6.39 | 162.3 | 3.76 | 95.5 | .32 | 8.1 |
| G43302-4040 | 40GL-40FL22 | 7305-05515 | 2 1/2 | 63.5 | 3.31 | 84.1 | .63 | 16.0 | 6.81 | 173.0 | 4.36 | 110.7 | .38 | 9.7 |
| G43302-4048 | 40GL-48FL22 | 7305-05615 | 2 1/2 | 63.5 | 4.00 | 101.6 | .67 | 17.0 | 6.86 | 174.2 | 4.41 | 112.0 | .38 | 9.7 |

# Code 61 O-Ring Flange - 30° Bent Tube


Special GL Dies Required.




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G43304-1212 | 12GL-12FL30M | 7348-00605 | 3/4 | 19.1 | 1.50 | 38.1 | .63 | 16.0 | 4.51 | 114.6 | 2.50 | 63.5 | .27 | 6.9 |
| G43304-1616 | 16GL-16FL30M | 7348-00615 | 1 | 25.4 | 1.75 | 44.5 | .75 | 19.1 | 4.92 | 125.0 | 2.69 | 68.3 | .32 | 8.1 |
| G43304-2020 | 20GL-20FL30M | 7348-00625 | 1 1/4 | 31.8 | 2.00 | 50.8 | .87 | 22.1 | 5.37 | 136.4 | 3.05 | 77.5 | .32 | 8.1 |
| G43304-2424 | 24GL-24FL30M | 7348-00635 | 1 1/2 | 38.1 | 2.38 | 60.5 | 1.18 | 30.0 | 6.86 | 174.2 | 4.22 | 107.2 | .32 | 8.1 |
| G43304-3232 | 32GL-32FL30M | 7348-00645 | 2 | 50.8 | 2.81 | 71.4 | 1.26 | 32.0 | 7.78 | 197.6 | 4.72 | 119.9 | .38 | 9.7 |
| G43304-4040 | 40GL-40FL30 | 7305-05525 | 2 1/2 | 63.5 | 3.31 | 84.1 | 1.08 | 27.4 | 7.30 | 185.4 | 4.85 | 123.2 | .38 | 9.7 |
| G43304-4048 | 40GL-48FL30 | 7305-05625 | 2 1/2 | 63.5 | 4.00 | 101.6 | 1.08 | 27.4 | 7.36 | 186.9 | 4.91 | 124.7 | .38 | 9.7 |
| G43304-4848 | 48GL-48FL30 | 7305-05825 | 3 | 76.2 | 4.00 | 101.6 | 1.12 | 28.5 | 8.23 | 209.0 | 5.15 | 130.8 | .38 | 9.7 |

# Code 61 O-Ring Flange - 45° Bent Tube


Special GL Dies Required.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G43307-1212 | 12GL-12FL45M | 7348-00705 | 3/4 | 19.1 | 1.50 | 38.1 | 1.02 | 25.9 | 4.67 | 118.6 | 2.66 | 67.6 | .27 | 6.9 |
| G43306-1616 | 16GL-16FL45S | 7348-00715 | 1 | 25.4 | 1.75 | 44.5 | 1.10 | 27.9 | 5.11 | 129.8 | 2.87 | 72.9 | .32 | 8.1 |
| G43306-2020 | 20GL-20FL45S | 7348-00725 | 1 1/4 | 31.8 | 2.00 | 50.8 | 1.26 | 32.0 | 5.59 | 142.0 | 3.29 | 83.6 | .32 | 8.1 |
| G43306-2424 | 24GL-24FL45S | 7348-00735 | 1 1/2 | 38.1 | 2.38 | 60.5 | 1.50 | 38.1 | 6.62 | 168.2 | 3.99 | 101.4 | .32 | 8.1 |
| G43306-3232 | 32GL-32FL45S | 7348-00745 | 2 | 50.8 | 2.81 | 71.4 | 2.05 | 52.1 | 8.07 | 205.0 | 5.00 | 127.0 | .38 | 9.7 |
| G43306-3240 | 32GL-40FL45S | 7348-00785 | 2 | 50.8 | 3.31 | 84.1 | 2.05 | 52.1 | 9.18 | 233.2 | 6.11 | 155.2 | .38 | 9.7 |
| G43307-4040 | 40GL-40FL45 | 7305-05535 | 2 1/2 | 63.5 | 3.31 | 84.1 | 1.72 | 43.7 | 7.72 | 196.1 | 5.27 | 133.9 | .38 | 9.7 |
| G43307-4048 | 40GL-48FL45 | 7305-05635 | 2 1/2 | 63.5 | 4.00 | 101.6 | 1.76 | 44.7 | 7.76 | 197.1 | 5.31 | 134.9 | .38 | 9.7 |
| G43307-4848 | 48GL-48FL45 | 7305-05835 | 3 | 76.2 | 4.00 | 101.6 | 2.03 | 51.6 | 9.18 | 233.2 | 6.10 | 154.9 | .38 | 9.7 |
| G43307-5656 | 56GL-56FL45 | 7305-06335 | 3 1/2 | 88.9 | 4.50 | 114.3 | 2.13 | 54.1 | 9.66 | 245.4 | 6.02 | 152.9 | .44 | 11.2 |
| G43307-5664 | 56GL-64FL45 | 7305-06385 | 3 1/2 | 88.9 | 5.00 | 127.0 | 2.13 | 54.1 | 9.66 | 245.4 | 6.02 | 152.9 | .44 | 11.2 |
| G43307-6565 | 64GL-64FL45 | 7305-06725 | 4 | 101.6 | 5.00 | 127.0 | 3.61 | 91.7 | 12.70 | 322.6 | 8.66 | 220.0 | .38 | 9.7 |

# Code 61 O-Ring Flange - 60° Bent Tube

Special GL Dies Required.





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G43309-1212 | 12GL-12FL60M | 7348-00805 | 3/4 | 19.1 | 1.50 | 38.1 | 1.46 | 37.1 | 4.61 | 117.1 | 2.60 | 66.0 | .27 | 6.9 |
| G43309-1616 | 16GL-16FL60M | 7348-00815 | 1 | 25.4 | 1.75 | 44.5 | 1.73 | 43.9 | 5.14 | 130.7 | 2.90 | 73.7 | .32 | 8.1 |
| G43308-2020 | 20GL-20FL60S | 7348-00825 | 1 1/4 | 31.8 | 2.00 | 50.8 | 1.77 | 45.0 | 5.67 | 144.0 | 3.35 | 85.1 | .32 | 8.1 |
| G43308-2424 | 24GL-24FL60S | 7348-00835 | 1 1/2 | 38.1 | 2.38 | 60.5 | 2.09 | 53.1 | 6.63 | 168.4 | 3.99 | 101.4 | .32 | 8.1 |
| G43309-3232 | 32GL-32FL60S | 7348-00845 | 2 | 50.8 | 2.81 | 71.4 | 2.95 | 74.9 | 8.59 | 218.2 | 5.52 | 140.2 | .38 | 9.7 |
| G43309-4040 | 40GL-40FL60 | 7305-05545 | 2 1/2 | 63.5 | 3.31 | 84.1 | 2.63 | 66.8 | 8.13 | 206.5 | 5.68 | 144.3 | .38 | 9.7 |
| G43309-4848 | 48GL-48FL60 | 7305-05845 | 3 | 76.2 | 4.00 | 101.6 | 3.11 | 79.0 | 9.66 | 245.4 | 6.58 | 167.1 | .38 | 9.7 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Code 61 O-Ring Flange - 67 1/2° Bent Tube


Special GL Dies Required.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G43311-3232 | 32GL-32FL67S | 7348-00875 | 2 | 50.8 | 2.81 | 71.4 | 3.35 | 85.1 | 8.56 | 217.4 | 5.49 | 139.5 | .38 | 9.7 |
| G43311-4040 | 40GL-40FL67 | 7305-05555 | 2 1/2 | 63.5 | 3.31 | 84.1 | 3.13 | 79.5 | 8.22 | 208.8 | 5.77 | 146.6 | .38 | 9.7 |
| G43311-4848 | 48GL-48FL67 | 7305-05905 | 3 | 76.2 | 4.00 | 101.6 | 3.87 | 98.3 | 9.50 | 241.3 | 6.42 | 163.1 | .38 | 9.7 |
| G43311-6464 | 64GL-64FL67 | 7305-06635 | 4 | 101.6 | 5.00 | 127.0 | 6.90 | 175.3 | 14.20 | 360.7 | 10.17 | 258.3 | .44 | 11.2 |

# Code 61 O-Ring Flange - 90° Bent Tube


Special GL Dies Required.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G43315-1212 | 12GL-12FL90M | 7348-00905 | 3/4 | 19.1 | 1.50 | 38.1 | 2.28 | 57.9 | 4.40 | 111.8 | 2.39 | 60.7 | .27 | 6.9 |
| G43314-1216 | 12GL-16FL90S | 7348-00915 | 3/4 | 19.1 | 1.75 | 44.5 | 2.40 | 61.0 | 4.40 | 111.8 | 2.39 | 60.7 | .32 | 8.1 |
| G43314-1616 | 16GL-16FL90S | 7348-00925 | 1 | 25.4 | 1.75 | 44.5 | 2.40 | 61.0 | 5.04 | 128.0 | 2.81 | 71.4 | .32 | 8.1 |
| G43314-1620 | 16GL-20FL90S | 7348-00935 | 1 | 25.4 | 2.00 | 50.8 | 2.68 | 68.1 | 5.04 | 128.0 | 2.81 | 71.4 | .32 | 8.1 |
| G43314-2020 | 20GL-20FL90S | 7348-00945 | 1 1/4 | 31.8 | 2.00 | 50.8 | 2.68 | 68.1 | 5.41 | 137.4 | 3.09 | 78.5 | .32 | 8.1 |
| G43314-2024 | 20GL-24FL90-068 | 7348-00955 | 1 1/4 | 31.8 | 2.38 | 60.5 | 2.68 | 68.1 | 5.41 | 137.4 | 3.09 | 78.5 | .32 | 8.1 |
| G43314-2424 | 24GL-24FL90S | 7348-00965 | 1 1/2 | 38.1 | 2.38 | 60.5 | 3.12 | 79.3 | 6.26 | 159.0 | 3.62 | 92.0 | .32 | 8.1 |
| G43314-3232 | 32GL-32FL90S | 7348-00975 | 2 | 50.8 | 2.81 | 71.4 | 4.50 | 114.3 | 8.73 | 221.7 | 5.20 | 132.1 | .38 | 9.7 |
| G43314-3240 | 32GL-40FL90-114 | 7348-00775 | 2 | 50.8 | 3.31 | 84.1 | 4.50 | 114.3 | 8.77 | 222.8 | 5.71 | 145.0 | .38 | 9.7 |
| G43315-4040 | 40GL-40FL90 | 7305-05565 | 2 1/2 | 63.5 | 3.31 | 84.1 | 4.62 | 117.4 | 8.06 | 204.7 | 5.61 | 142.5 | .38 | 9.7 |
| G43315-4048 | 40GL-48FL90 | 7305-05665 | 2 1/2 | 63.5 | 4.00 | 101.6 | 4.62 | 117.4 | 8.12 | 206.3 | 5.67 | 144.0 | .38 | 9.7 |
| G43315-4848 | 48GL-48FL90 | 7305-05855 | 3 | 76.2 | 4.00 | 101.6 | 5.50 | 139.7 | 9.70 | 246.4 | 6.62 | 168.2 | .38 | 9.7 |
| G43315-5656 | 56GL-56FL90 | 7305-06365 | 3 1/2 | 88.9 | 4.50 | 114.3 | 5.63 | 143.0 | 10.17 | 258.3 | 6.53 | 165.9 | .44 | 11.2 |
| G43315-5664 | 56GL-64FL90 | 7305-06395 | 3 1/2 | 88.9 | 5.00 | 127.0 | 6.90 | 175.3 | 10.09 | 256.3 | 6.45 | 163.8 | .44 | 11.2 |
| G43315-6464 | 64GL-64FL90 | 7305-06645 | 4 | 101.6 | 5.00 | 127.0 | 7.38 | 187.5 | 12.61 | 320.3 | 8.58 | 217.9 | .44 | 11.2 |

# Code 61 Captive O-Ring Flange


Special GL Dies Required.




| Part No. | Descr. | Prod. No. | ⟷ | | M | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm |
| | 56GL-56FLCF | 7348-02705 | 3 1/2 | 88.9 | 4.50 | 114.3 | 6.70 | 170.2 | 3.06 | 77.7 | .42 | .5 |
| G43333-6464 | 64GL-64FLCF | 7348-02755 | 4 | 101.6 | 5.00 | 127.0 | 7.74 | 196.6 | 3.70 | 94.0 | .44 | 5.0 |

# Code 61 Captive O-Ring Flange - 45° Bent Tube

Special GL Dies Required.





| Part No. | Descr. | Prod. No. | ⟷ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G43334-5656 | 56GL-56FLCF45-054 | 7348-02715 | 3 1/2 | 88.9 | 4.50 | 114.3 | 2.13 | 54.1 | 9.67 | 245.6 | 6.02 | 152.9 | .42 | 4.5 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Code 61 Captive O-Ring Flange - 90° Bent Tube

Special GL Dies Required.




| Part No. | Descr. | Prod. No. | ⊖ | | M | | T | | L | | C | | F | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | mm | " | mm | " | mm | " | mm | " | mm |
| G43335-5656 | 56GL-56FLCF90-143 | 7348-02725 | 3 1/2 | 88.9 | 4.50 | 114.3 | 5.64 | 143.3 | 10.20 | 258.3 | 6.53 | 165.9 | .42 | 4.5 |

# HYDRAULIC HOSE FOR GLX COUPLINGS









































EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Pipe (NPTF 30° Cone Seat)





| Part No. | Descr. | Prod. No. | ⟷ | | ≋ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G44100-0402 | 4GLX-2MP | 7107-00105 | 1/4 | 6.4 | 1/8–27 | 1/2 | 2.01 | 51.1 | .98 | 24.9 |
| G44100-0404 | 4GLX-4MP | 7107-00115 | 1/4 | 6.4 | 1/4–18 | 9/16 | 2.17 | 55.1 | 1.14 | 29.0 |
| G44100-0604 | 6GLX-4MP | 7107-00135 | 3/8 | 9.5 | 1/4–18 | 11/16 | 2.32 | 58.9 | 1.22 | 31.0 |
| G44100-0606 | 6GLX-6MP | 7107-00145 | 3/8 | 9.5 | 3/8–18 | 11/16 | 2.32 | 58.9 | 1.22 | 31.0 |
| G44100-0806 | 8GLX-6MP | 7107-00165 | 1/2 | 12.7 | 3/8–18 | 13/16 | 2.72 | 69.1 | 1.24 | 31.5 |
| G44100-0808 | 8GLX-8MP | 7107-00175 | 1/2 | 12.7 | 1/2–14 | 7/8 | 2.78 | 70.6 | 1.40 | 35.6 |
| G44100-0812 | 8GLX-12MP | 7107-00785 | 1/2 | 12.7 | 3/4–14 | 13/16 | 3.46 | 87.9 | 1.45 | 36.8 |
| G44100-1008 | 10GLX-8MP | 7107-00195 | 5/8 | 15.9 | 1/2–14 | 15/16 | 2.40 | 61.0 | 1.55 | 39.4 |
| G44100-1208 | 12GLX-8MP | 7107-00215 | 3/4 | 19.1 | 1/2–14 | 1 1/16 | 3.46 | 87.9 | 1.46 | 37.1 |
| G44100-1212 | 12GLX-12MP | 7107-00225 | 3/4 | 19.1 | 3/4–14 | 1 1/16 | 3.46 | 87.9 | 1.46 | 37.1 |
| G44100-1616 | 16GLX-16MP | 7107-00255 | 1 | 25.4 | 1–11 1/2 | 1 3/8 | 4.11 | 104.4 | 1.88 | 47.8 |
| G44100-2020 | 20GLX-20MP | 7107-00265 | 1 1/4 | 31.8 | 1 1/4–11 1/2 | 1 3/4 | 4.41 | 112.0 | 2.09 | 53.1 |

# MPX Male NPTF Swivel





| Part No. | Descr. | Prod. No. | ⟷ | | ≋ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G44105-0404 | 4GLX-4MPX | 7107-00565 | 1/4 | 6.4 | 1/4–18 | 1/2 | 11/16 | 2.61 | 66.3 | 1.58 | 40.1 |
| G44105-0606 | 6GLX-6MPX | 7107-00575 | 3/8 | 9.5 | 3/8–18 | 5/8 | 7/8 | 2.81 | 71.4 | 1.72 | 43.7 |
| G44105-0808 | 8GLX-8MPX | 7107-00585 | 1/2 | 12.7 | 1/2–14 | 13/16 | 1 | 3.42 | 86.9 | 1.95 | 49.5 |
| G44105-1212 | 12GLX-12MPX | 7107-00595 | 3/4 | 19.1 | 3/4–14 | 1 1/16 | 1 5/16 | 4.02 | 102.1 | 2.01 | 51.1 |
| G44105-1616 | 16GLX-16MPX | 7107-00605 | 1 | 25.4 | 1–11 1/2 | 1 3/8 | 1 5/8 | 4.73 | 120.1 | 2.50 | 63.5 |
| G44105-2020 | 20GLX-20MPX | 7107-00615 | 1 1/4 | 31.8 | 1 1/4–11 1/2 | 1 7/8 | 2 | 5.30 | 134.6 | 2.98 | 75.7 |

# FP Female NPTF




| Part No. | Descr. | Prod. No. | ⊖ | | ≋ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G44110-0404 | 4GLX-4FP | 7107-00415 | 1/4 | 6.4 | 1/4–18 | 11/16 | 1.99 | 50.6 | .96 | 24.4 |
| G44110-0604 | 6GLX-4FP | 7107-00425 | 3/8 | 9.5 | 1/4–18 | 11/16 | 2.07 | 52.6 | .97 | 24.6 |
| G44110-0606 | 6GLX-6FP | 7107-00435 | 3/8 | 9.5 | 3/8–18 | 13/16 | 2.07 | 52.6 | .97 | 24.6 |
| G44110-0806 | 8GLX-6FP | 7107-00445 | 1/2 | 12.7 | 3/8–18 | 13/16 | 2.48 | 63.0 | 1.00 | 25.4 |
| G44110-0808 | 8GLX-8FP | 7107-00455 | 1/2 | 12.7 | 1/2–14 | 1 | 2.64 | 67.1 | 1.16 | 29.5 |
| G44110-1212 | 12GLX-12FP | 7107-00465 | 3/4 | 19.1 | 3/4–14 | 1 1/4 | 3.23 | 82.0 | 1.22 | 31.0 |
| G44110-1616 | 16GLX-16FP | 7107-00475 | 1 | 25.4 | 1–11 1/2 | 1 1/2 | 3.86 | 98.1 | 1.62 | 41.2 |

# FPX Female NPSM Swivel





| Part No. | Descr. | Prod. No. | ⊖ | | ≋ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G44111-0404 | 4GLX-4FPX | 7107-00345 | 1/4 | 6.4 | 1/4–18 | 1/2 | 11/16 | 2.24 | 56.9 | 1.22 | 31.0 |
| G44111-0604 | 6GLX-4FPX | 7107-00355 | 3/8 | 9.5 | 1/4–18 | 5/8 | 11/16 | 2.40 | 61.0 | 1.30 | 33.0 |
| G44111-0606 | 6GLX-6FPX | 7107-00365 | 3/8 | 9.5 | 3/8–18 | 5/8 | 7/8 | 2.49 | 63.3 | 1.39 | 35.3 |
| G44111-0806 | 8GLX-6FPX | 7107-00375 | 1/2 | 12.7 | 3/8–18 | 13/16 | 7/8 | 2.85 | 72.4 | 1.38 | 35.1 |
| G44111-0808 | 8GLX-8FPX | 7107-00385 | 1/2 | 12.7 | 1/2–14 | 13/16 | 1 | 2.89 | 73.4 | 1.41 | 35.8 |
| G44111-1212 | 12GLX-12FPX | 7107-00395 | 3/4 | 19.1 | 3/4–14 | 1 1/16 | 1 1/4 | 3.72 | 94.5 | 1.71 | 43.4 |
| G44111-1616 | 16GLX-16FPX | 7107-00405 | 1 | 25.4 | 1–11 1/2 | 1 3/8 | 1 1/2 | 4.11 | 104.4 | 1.87 | 47.5 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female JIC 37° Flare Swivel





| Part No. | Descr. | Prod. No. | ⊖ | | ≋ | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G44170-0404 | 4GLX-4FJX | 7107-00275 | 1/4 | 6.4 | 7/16–20 | 1/2 | 9/16 | 2.10 | 53.3 | 1.08 | 27.4 |
| G44170-0606 | 6GLX-6FJX | 7107-00285 | 3/8 | 9.5 | 9/16–18 | 5/8 | 3/4 | 2.31 | 58.7 | 1.19 | 30.2 |
| G44170-0808 | 8GLX-8FJX | 7107-00295 | 1/2 | 12.7 | 3/4–16 | 13/16 | 7/8 | 2.82 | 71.6 | 1.34 | 34.0 |
| G44170-1010 | 10GLX-10FJX | 7107-00305 | 5/8 | 15.9 | 7/8–14 | — | 1 1/16 | 2.27 | 57.7 | 1.42 | 36.1 |
| G44170-1212 | 12GLX-12FJX | 7107-00315 | 3/4 | 19.1 | 1 1/16–12 | 1 1/16 | 1 1/4 | 3.68 | 93.5 | 1.67 | 42.4 |
| G44170-1616 | 16GLX-16FJX | 7107-00325 | 1 | 25.4 | 1 5/16–12 | 1 3/8 | 1 1/2 | 4.17 | 105.9 | 1.94 | 49.3 |
| G44170-2020 | 20GLX-20FJX | 7107-00335 | 1 1/4 | 31.8 | 1 5/8–12 | 1 3/4 | 2 | 4.58 | 116.3 | 2.26 | 57.4 |

# MS 45° SAE Male Solid




| Part No. | Descr. | Prod. No. | ⊖ | | ≋ | H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G44195-0404 | 4GLX-4MS | 7107-00525 | 1/4 | 6.4 | 7/16–20 | 1/2 | 2.11 | 53.6 | 1.08 | 27.4 |
| G44195-0606 | 6GLX-6MS | 7107-00535 | 3/8 | 9.5 | 5/8–18 | 5/8 | 2.38 | 60.5 | 1.28 | 32.5 |
| G44195-0808 | 8GLX-8MS | 7107-00545 | 1/2 | 12.7 | 3/4–16 | 13/16 | 2.89 | 73.4 | 1.42 | 36.1 |
| G44195-1212 | 12GLX-12MS | 7107-00555 | 3/4 | 19.1 | 1 1/16–14 | 1 1/16 | 3.78 | 96.0 | 1.77 | 45.0 |

# FSX 45° SAE Female Swivel




| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | | " | " | " | mm | " | mm |
| G44200-0404 | 4GLX-4FSX | 7107-00485 | 1/4 | 6.4 | 7/16–20 | | 1/2 | 9/16 | 2.24 | 56.9 | 1.22 | 31.0 |
| G44200-0606 | 6GLX-6FSX | 7107-00495 | 3/8 | 9.5 | 5/8–18 | | 5/8 | 3/4 | 2.44 | 62.0 | 1.35 | 34.3 |
| G44200-0808 | 8GLX-8FSX | 7107-00505 | 1/2 | 12.7 | 3/4–16 | | 13/16 | 7/8 | 2.82 | 71.6 | 1.34 | 34.0 |
| G44200-1212 | 12GLX-12FSX | 7107-00515 | 3/4 | 19.1 | 1 1/16–14 | | 1 1/16 | 1 1/4 | 3.68 | 93.5 | 1.67 | 42.4 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# HYDRAULIC HOSE FOR PCTS THERMOPLASTIC COUPLINGS










**The Gates eCrimp program** is a web based utility which allows users and distributors of Gates hydraulic and industrial hose products to find and print the most up to date crimp specifications with nothing more than an internet browser.

This program can be used to find crimp data for all Gates crimpers. Custom result may be printed by selecting the crimper, hose and coupling. Optionally results may also be limited by die set and working pressure.


The eCrimp web application can be directly accessed from a web browser by entering http://eCrimp.Gates.com for the website.


**The eCrimp mobile app** is available for download for the iPhone and iPad from the App Store.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male Pipe (NPTF - 30° Cone Seat)









| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G51100-0202 | 2PCTS-2MP | 7336-11985 | 1/8 | 3.2 | 1/8–27 | 1/2 | 1.34 | 34.0 | .74 | 18.8 |
| G51100-0204 | 2PCTS-4MP | 7336-11995 | 1/8 | 3.2 | 1/4–18 | 1/2 | 1.53 | 38.9 | .93 | 23.6 |
| G51100-0302 | 3PCTS-2MP | 7336-12005 | 3/16 | 4.8 | 1/8–27 | 9/16 | 1.94 | 49.3 | 1.08 | 27.4 |
| G51100-0304 | 3PCTS-4MP | 7336-12015 | 3/16 | 4.8 | 1/4–18 | 11/16 | 2.13 | 54.1 | 1.27 | 32.3 |
| G51100-0404 | 4PCTS-4MP | 7336-12035 | 1/4 | 6.4 | 1/4–18 | 11/16 | 2.34 | 59.4 | 1.25 | 31.8 |
| G51100-0406 | 4PCTS-6MP | 7336-12045 | 1/4 | 6.4 | 3/8–18 | 3/4 | 2.44 | 62.0 | 1.35 | 34.3 |
| G51100-0604 | 6PCTS-4MP | 7336-12075 | 3/8 | 9.5 | 1/4–18 | 3/4 | 2.66 | 67.6 | 1.37 | 34.8 |
| G51100-0606 | 6PCTS-6MP | 7336-12085 | 3/8 | 9.5 | 3/8–18 | 3/4 | 2.66 | 67.6 | 1.37 | 34.8 |
| G51100-0608 | 6PCTS-8MP | 7336-12095 | 3/8 | 9.5 | 1/2–14 | 15/16 | 2.92 | 74.2 | 1.63 | 41.4 |
| G51100-0808 | 8PCTS-8MP | 7336-12105 | 1/2 | 12.7 | 1/2–14 | 15/16 | 3.13 | 79.5 | 1.48 | 37.6 |

## Male Pipe Swivel (NPTF - without 30° Cone Seat)


NOT TO BE USED AS A LIVE SWIVEL.





| Part No. | Descr. | Prod. No. | ⊖ | | ||| H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm |
| G51105-0202 | 2PCTS-2MPX | 7337-11985 | 1/8 | 3.2 | 1/8–27 | 1/2 | 23/32 | 1.93 | 49.0 | 1.33 | 33.8 |
| G51105-0302 | 3PCTS-2MPX | 7337-12005 | 3/16 | 4.8 | 1/8–27 | 23/32 | 23/32 | 2.50 | 63.5 | 1.50 | 38.1 |
| G51105-0304 | 3PCTS-4MPX | 7337-12015 | 3/16 | 4.8 | 1/4–18 | 23/32 | 23/32 | 2.72 | 69.1 | 1.86 | 47.2 |
| G51105-0404 | 4PCTS-4MPX | 7337-12025 | 1/4 | 6.4 | 1/4–18 | 5/8 | 23/32 | 2.84 | 72.1 | 1.78 | 45.2 |


## Female JIC 37° Flare Swivel





| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G51170-0203 | 2PCTS-3FJX | 7338-11985 | 1/8 | 3.2 | 3/8–24 | 1/2 | 9/16 | 1.65 | 41.9 | 1.05 | 26.7 |
| G51170-0406 | 4PCTS-6FJX | 7338-12045 | 1/4 | 6.4 | 9/16–18 | 5/8 | 3/4 | 2.55 | 64.8 | 1.50 | 38.1 |
| G51170-0812 | 8PCTS-12FJX | 7338-12175 | 1/2 | 12.7 | 1 1/16–12 | 1 1/8 | 1 1/4 | 3.34 | 84.8 | 1.70 | 43.2 |
| G51170-1212 | 12PCTS-12FJX | 7338-01605 | 3/4 | 19.1 | 1 1/16–12 | 1 1/8 | 1 1/4 | 3.48 | 88.4 | 1.60 | 40.6 |
| G51170-1616 | 16PCTS-16FJX | 7338-01615 | 1 | 25.4 | 1 5/16–12 | 1 3/8 | 1 1/2 | 4.00 | 101.6 | 1.66 | 42.2 |


## Female JIC 37° Flare Swivel - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | | H2 | T | | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | mm | " | mm | " | mm |
| G51179-0304 | 3PCTS-4FJX90S | 7338-12695 | 3/16 | 4.8 | 7/16–20 | 9/16 | .78 | 19.8 | 2.45 | 62.2 | 1.58 | 40.1 |
| G51179-0606 | 6PCTS-6FJX90S | 7338-12785 | 3/8 | 9.5 | 9/16–18 | 11/16 | .85 | 21.6 | 3.25 | 82.6 | 1.95 | 49.5 |
| G51181-0808 | 8PCTS-8FJX90L | 7338-12835 | 1/2 | 12.7 | 3/4–16 | 7/8 | 2.43 | 61.7 | 3.83 | 97.3 | 2.19 | 55.6 |

## Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 45° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | " | " | mm | " | mm |
| G51210-0204 | 2PCTS-4FJSX | 7338-11995 | 1/8 | 3.2 | 7/16–20 | 1/2 | 5/8 | 1.73 | 44.0 | 1.12 | 28.5 |
| G51210-0304 | 3PCTS-4FJSX | 7338-12005 | 3/16 | 4.8 | 7/16–20 | 9/16 | 5/8 | 2.23 | 56.6 | 1.16 | 29.5 |
| G51210-0404 | 4PCTS-4FJSX | 7338-12025 | 1/4 | 6.4 | 7/16–20 | 5/8 | 5/8 | 2.53 | 64.3 | 1.47 | 37.3 |
| G51210-0505 | 5PCTS-5FJSX | 7338-12055 | 5/16 | 7.9 | 1/2–20 | 5/8 | 3/4 | 2.62 | 66.6 | 1.33 | 33.8 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# HYDRAULIC HOSE FOR POLARSEAL® (ACA) COUPLINGS




**The Gates eCrimp program** is a web based utility which allows users and distributors of Gates hydraulic and industrial hose products to find and print the most up to date crimp specifications with nothing more than an internet browser.

This program can be used to find crimp data for all Gates crimpers. Custom result may be printed by selecting the crimper, hose and coupling. Optionally results may also be limited by die set and working pressure.


The eCrimp web application can be directly accessed from a web browser by entering http://eCrimp.Gates.com for the website.

**The eCrimp mobile app** is available for download for the iPhone and iPad from the App Store.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male SAE 45° Flare - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ||| L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " |
| G45195-0606 | 6ACA-6MS | 7332-00015 | 5/16 | 5/8–18 | | 3.38 | 2.13 |
| G45195-0808 | 8ACA-8MS | 7332-00025 | 13/32 | 3/4–16 | | 3.50 | 2.25 |
| G45195-1010 | 10ACA-10MS | 7332-00035 | 1/2 | 7/8–14 | | 3.81 | 2.56 |
| G45195-1212 | 12ACA-12MS | 7332-00045 | 5/8 | 1 1/16–14 | | 4.00 | 2.75 |

## Male SAE 45° Flare - 45° Bent Tube - Aluminum




| Part No. | Descr. | Prod. No. | ⊖ | | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45196-0606 | 6ACA-6MS45 | 7332-00055 | 5/16 | 5/8–18 | .94 | 3.25 | 2.00 |
| G45196-0808 | 8ACA-8MS45 | 7332-00065 | 13/32 | 3/4–16 | 1.06 | 3.50 | 2.25 |
| G45196-1010 | 10ACA-10MS45 | 7332-00075 | 1/2 | 7/8–14 | 1.12 | 3.87 | 2.62 |
| G45196-1212 | 12ACA-12MS45 | 7332-00085 | 5/8 | 1 1/16–14 | 1.25 | 4.25 | 3.00 |

## Male SAE 45° Flare - 90° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45197-0606 | 6ACA-6MS90 | 7332-00095 | 5/16 | 5/8–18 | 1.75 | 2.56 | 1.31 |

## Male SAE 45° Flare - 90° Bent Tube - Aluminum - Continued


| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G45197-0808 | 8ACA-8MS90 | 7332-00105 | 13/32 | 3/4–16 | | 1.81 | 2.75 | 1.50 |
| G45197-1010 | 10ACA-10MS90 | 7332-00115 | 1/2 | 7/8–14 | | 2.19 | 3.00 | 1.75 |
| G45197-1212 | 12ACA-12MS90 | 7332-00125 | 5/8 | 1 1/16–14 | | 2.45 | 3.25 | 2.00 |

## Female SAE 45° Flare Swivel - Aluminum




| Part No. | Descr. | Prod. No. | ⊖ | ||| L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " |
| G45200-0606 | 6ACA-6FSX | 7332-00135 | 5/16 | 5/8–18 | | 2.88 | 1.63 |
| G45200-0608 | 6ACA-8FSX | 7332-00145 | 5/16 | 3/4–16 | | 2.69 | 1.44 |
| G45200-0806 | 8ACA-6FSX | 7332-02825 | 13/32 | 5/8–18 | | 2.69 | 1.44 |
| G45200-0808 | 8ACA-8FSX | 7332-00155 | 13/32 | 3/4–16 | | 2.69 | 1.44 |
| G45200-1008 | 10ACA-8FSX | 7332-02835 | 1/2 | 3/4–16 | | 3.00 | 1.75 |
| G45200-1010 | 10ACA-10FSX | 7332-00165 | 1/2 | 7/8–14 | | 3.00 | 1.75 |
| G45200-1210 | 12ACA-10FSX | 7332-00175 | 5/8 | 7/8–14 | | 3.25 | 2.00 |
| G45200-1212 | 12ACA-12FSX | 7332-00185 | 5/8 | 1 1/16–14 | | 3.25 | 2.00 |

## Female SAE 45° Flare Swivel - Steel





| Part No. | Descr. | Prod. No. | ⊖ | ||| L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " |
| G45200-0606S | 6ACA-6FSX-S | 7332-01755 | 5/16 | 5/8–18 | | 2.88 | 1.60 |
| G45200-0808S | 8ACA-8FSX-S | 7332-01765 | 13/32 | 3/4–16 | | 2.69 | 1.44 |
| G45200-1010S | 10ACA-10FSX-S | 7332-01775 | 1/2 | 7/8–14 | | 3.00 | 1.75 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female SAE 45° Flare Swivel - 45° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ≡ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45202-0606 | 6ACA-6FSX45 | 7332-00195 | 5/16 | 5/8–18 | .56 | 2.87 | 1.62 |
| G45202-0806 | 8ACA-6FSX45 | 7332-02855 | 13/32 | 5/8–18 | .63 | 3.04 | 1.79 |
| G45202-0808 | 8ACA-8FSX45 | 7332-00205 | 13/32 | 3/4–16 | .63 | 3.07 | 1.82 |
| G45202-1010 | 10ACA-10FSX45 | 7332-00215 | 1/2 | 7/8–14 | .88 | 3.63 | 2.38 |
| G45202-1210 | 12ACA-10FSX45 | 7332-02875 | 5/8 | 7/8–14 | 1.00 | 3.97 | 2.72 |
| G45202-1212 | 12ACA-12FSX45 | 7332-00225 | 5/8 | 1 1/16–14 | 1.00 | 4.00 | 2.75 |

# Female SAE 45° Flare Swivel - 90° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ≡ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45205-0606 | 6ACA-6FSX90 | 7332-00235 | 5/16 | 5/8–18 | 1.06 | 2.56 | 1.31 |
| G45205-0608 | 6ACA-8FSX90 | 7332-00245 | 5/16 | 3/4–16 | 1.25 | 2.75 | 1.50 |
| G45205-0806 | 8ACA-6FSX90 | 7332-02885 | 13/32 | 5/8–18 | 1.25 | 2.75 | 1.50 |
| G45205-0808 | 8ACA-8FSX90 | 7332-00255 | 13/32 | 3/4–16 | 1.25 | 2.75 | 1.50 |
| G45205-1008 | 10ACA-8FSX90 | 7332-02895 | 1/2 | 3/4–16 | 1.50 | 3.00 | 1.75 |
| G45205-1010 | 10ACA-10FSX90 | 7332-00265 | 1/2 | 7/8–14 | 1.50 | 3.00 | 1.75 |
| G45205-1210 | 12ACA-10FSX90 | 7332-00275 | 5/8 | 7/8–14 | 1.50 | 3.25 | 2.00 |
| G45205-1212 | 12ACA-12FSX90 | 7332-00285 | 5/8 | 1 1/16–14 | 1.50 | 3.85 | 2.00 |

# Female SAE 45° Flare Swivel - 90° Bent Tube - Steel




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G45205-0606S | 6ACA-6FSX90-S | 7332-01785 | 5/16 | 5/8–18 | | 1.06 | 2.56 | 1.31 |
| G45205-0808S | 8ACA-8FSX90-S | 7332-01795 | 13/32 | 3/4–16 | | 1.25 | 2.75 | 1.50 |
| G45205-1010S | 10ACA-10FSX90-S | 7332-01805 | 1/2 | 7/8–14 | | 1.50 | 3.00 | 1.75 |

# Male SAE Flareless Assembly - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ||| A1 | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G45510-0606 | 6ACA-6MFA | 7332-00295 | 5/16 | 9/16–18 | | 3/8 | 2.69 | 1.44 |
| G45510-0608 | 6ACA-8MFA | 7332-02905 | 5/16 | 3/4–16 | | 1/2 | 2.81 | 1.56 |
| G45510-0806 | 8ACA-6MFA | 7332-02915 | 13/32 | 9/16–18 | | 3/8 | 2.75 | 1.50 |
| G45510-0808 | 8ACA-8MFA | 7332-00305 | 13/32 | 3/4–16 | | 1/2 | 2.88 | 1.63 |
| G45510-0810 | 8ACA-10MFA | 7332-00315 | 13/32 | 7/8–14 | | 5/8 | 3.00 | 1.75 |
| G45510-1008 | 10ACA-8MFA | 7332-00325 | 1/2 | 3/4–16 | | 1/2 | 2.94 | 1.69 |
| G45510-1010 | 10ACA-10MFA | 7332-00335 | 1/2 | 7/8–14 | | 5/8 | 3.00 | 1.75 |
| G45510-1210 | 12ACA-10MFA | 7332-00345 | 5/8 | 7/8–14 | | 5/8 | 3.13 | 1.88 |
| G45510-1212 | 12ACA-12MFA | 7332-00355 | 5/8 | 1 1/16–12 | | 3/4 | 3.25 | 2.00 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male SAE Flareless Assembly - 90° Block - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ||| A1 | T | L | C |
|---|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " | " |
| G45511-0606 | 6ACA-6MFA90 | 7332-00365 | 5/16 | 9/16–18 | 3/8 | .78 | 2.24 | .99 |
| G45511-0608 | 6ACA-8MFA90 | 7332-02925 | 5/16 | 3/4–16 | 1/2 | .96 | 2.31 | 1.06 |
| G45511-0806 | 8ACA-6MFA90 | 7332-02935 | 13/32 | 9/16–18 | 3/8 | .78 | 2.28 | 1.03 |
| G45511-0808 | 8ACA-8MFA90 | 7332-00375 | 13/32 | 3/4–16 | 1/2 | .96 | 2.37 | 1.12 |
| G45511-0810 | 8ACA-10MFA90 | 7332-00385 | 13/32 | 7/8–14 | 5/8 | 1.08 | 2.43 | 1.18 |
| G45511-1008 | 10ACA-8MFA90 | 7332-00395 | 1/2 | 3/4–16 | 1/2 | .96 | 2.38 | 1.13 |
| G45511-1010 | 10ACA-10MFA90 | 7332-00405 | 1/2 | 7/8–14 | 5/8 | 1.08 | 2.44 | 1.19 |
| G45511-1210 | 12ACA-10MFA90 | 7332-00415 | 5/8 | 7/8–14 | 5/8 | 1.08 | 2.56 | 1.31 |
| G45511-1212 | 12ACA-12MFA90 | 7332-00425 | 5/8 | 1 1/16–12 | 3/4 | 1.19 | 2.66 | 1.41 |

# Female Braze-On Stems - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | A1 | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45527-0606 | 6ACA-6FBO | 7332-02945 | 5/16 | 3/8 | 2.10 | .85 |
| G45527-0808 | 8ACA-8FBO | 7332-02955 | 13/32 | 1/2 | 2.10 | .85 |
| G45527-1010 | 10ACA-10FBO | 7332-02965 | 1/2 | 5/8 | 2.10 | .85 |
| G45527-1210 | 12ACA-10FBO | 7332-02975 | 5/8 | 5/8 | 2.10 | .85 |
| G45527-1212 | 12ACA-12FBO | 7332-02985 | 5/8 | 3/4 | 2.10 | .85 |

## Female Braze-On Stems - Steel





| Part No. | Descr. | Prod. No. | ⟷ | A1 | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45527-0606S | 6ACA-6FBO-S | 7332-01905 | 5/16 | 3/8 | 2.10 | .85 |
| G45527-0808S | 8ACA-8FBO-S | 7332-01915 | 13/32 | 1/2 | 2.10 | .85 |
| G45527-1010S | 10ACA-10FBO-S | 7332-01925 | 1/2 | 5/8 | 2.10 | .85 |
| G45527-1210S | 12ACA-10FBO-S | 7332-01945 | 5/8 | 5/8 | 2.10 | .85 |
| G45527-1212S | 12ACA-12FBO-S | 7332-01935 | 5/8 | 3/4 | 2.10 | .85 |

## Hose Length Extender - Aluminum




| Part No. | Descr. | Prod. No. | ⟷ | A1 | A2 | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45535-0606 | 6ACA-6HLE | 7332-01385 | 5/16 | 5/16 | 5/16 | 4.00 | 1.50 |
| G45535-0608 | 6ACA-8HLE | 7332-01395 | 5/16 | 5/16 | 13/32 | 4.00 | 1.50 |
| G45535-0808 | 8ACA-8HLE | 7332-01405 | 13/32 | 13/32 | 13/32 | 4.00 | 1.50 |
| G45535-0810 | 8ACA-10HLE | 7332-01415 | 13/32 | 13/32 | 1/2 | 4.13 | 1.63 |
| G45535-1010 | 10ACA-10HLE | 7332-01425 | 1/2 | 1/2 | 1/2 | 4.13 | 1.63 |
| G45535-1210 | 12ACA-10HLE | 7332-02995 | 5/8 | 5/8 | 1/2 | 4.25 | 1.75 |
| G45535-1212 | 12ACA-12HLE | 7332-01435 | 5/8 | 5/8 | 5/8 | 4.25 | 1.75 |

## Hose Length Extender - Steel





| Part No. | Descr. | Prod. No. | ⟷ | A1 | A2 | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45535-1210S | 12ACA-10HLE-S | 7332-04485 | 5/8 | 5/8 | 1/2 | 1.75 | 5.27 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Hose Length Extender - 90° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | A1 | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45537-0606 | 6ACA-6HLE90 | 7332-01445 | 5/16 | 5/16 | 2.50 | 1.25 |
| G45537-0808 | 8ACA-8HLE90 | 7332-01455 | 13/32 | 13/32 | 2.62 | 1.37 |
| G45537-1010 | 10ACA-10HLE90 | 7332-01465 | 1/2 | 1/2 | 2.88 | 1.63 |
| G45537-1212 | 12ACA-12HLE90 | 7332-01475 | 5/8 | 5/8 | 3.25 | 2.00 |

## Hose Length Extender with Sight Glass - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | L | C |
|---|---|---|---|---|---|
| | | | " | " | " |
| G45538-0606 | 6ACA-6HLESG | 7332-01485 | 5/16 | 4.12 | 1.62 |

# Hose Length Extender - Tee - Aluminum




| Part No. | Descr. | Prod. No. | ⟷ | A1 | A2 | T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " | " |
| G45539-0606 | 6ACA-6HLET | 7332-02295 | 5/16 | 5/16 | 5/16 | 1.13 | 4.75 | 2.25 |
| G45539-0808 | 8ACA-8HLET | 7332-02305 | 13/32 | 13/32 | 13/32 | 1.19 | 4.88 | 2.38 |
| G45539-1010 | 10ACA-10HLET | 7332-02315 | 1/2 | 1/2 | 1/2 | 1.25 | 5.00 | 2.50 |
| G45539-1210 | 12ACA-10HLET | 7332-03015 | 5/8 | 5/8 | 1/2 | 1.34 | 5.25 | 2.75 |
| G45539-1212 | 12ACA-12HLET | 7332-02325 | 5/8 | 5/8 | 5/8 | 1.37 | 5.25 | 2.75 |

# Hose Length Extender - 180° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⟷ | T | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45541-0606 | 6ACA-6HLE180 | 7332-02255 | 5/16 | 3.00 | 3.88 | 2.63 |
| G45541-0808 | 8ACA-8HLE180 | 7332-02265 | 13/32 | 3.00 | 4.00 | 2.75 |
| G45541-1212 | 12ACA-12HLE180 | 7332-02285 | 5/8 | 3.00 | 4.50 | 3.25 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male SAE Tube O-Ring Nut Swivel with R134a Service Port - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45580-0606 | 6ACA-6MTON134SP | 7332-03025 | 5/16 | 5/8–18 | 3.35 | 2.10 |
| G45580-0808 | 8ACA-8MTON134SP | 7332-03035 | 13/32 | 3/4–16 | 3.35 | 2.10 |
| G45580-1010 | 10ACA-10MTON134SP | 7332-03045 | 1/2 | 7/8–14 | 3.59 | 2.34 |
| G45580-1212 | 12ACA-12MTON134SP | 7332-03055 | 5/8 | 1 1/16–14 | 3.72 | 2.47 |

# Male SAE Tube O-Ring Nut Swivel with R134a Service Port - 90° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45582-1010 | 10ACA-10MTON134SP90 | 7332-02585 | 1/2 | 7/8–14 | 1.50 | 3.85 | 2.60 |

# Male SAE Tube O-Ring Nut Swivel - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ||| L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45583-0606 | 6ACA-6MTON | 7332-00435 | 5/16 | 5/8–18 | 3.19 | 1.94 |
| G45583-0607 | 6ACA-7MTON | 7332-02115 | 5/16 | 11/16–16 | 3.00 | 1.75 |
| G45583-0608 | 6ACA-8MTON | 7332-03065 | 5/16 | 3/4–16 | 3.25 | 2.00 |
| G45583-0806 | 8ACA-6MTON | 7332-03075 | 13/32 | 5/8–18 | 3.25 | 2.00 |
| G45583-0808 | 8ACA-8MTON | 7332-00445 | 13/32 | 3/4–16 | 3.25 | 2.00 |
| G45583-1010 | 10ACA-10MTON | 7332-00455 | 1/2 | 7/8–14 | 3.38 | 2.13 |
| G45583-1210 | 12ACA-10MTON | 7332-03085 | 5/8 | 7/8–14 | 3.88 | 2.63 |
| G45583-1212 | 12ACA-12MTON | 7332-00465 | 5/8 | 1 1/16–14 | 3.88 | 2.63 |

# Male SAE Tube O-Ring Nut Swivel - Steel

O–Ring not included. Must be ordered separately.





| Part No. | Descr. | Prod. No. | ⊖ | ||| L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45583-0606S | 6ACA-6MTON-S | 7332-01285 | 5/16 | 5/8–18 | 3.19 | 1.94 |
| G45583-0607S | 6ACA-7MTON-S | 7332-02125 | 5/16 | 11/16–16 | 3.00 | 1.75 |
| G45583-1010S | 10ACA-10MTON-S | 7332-01865 | 1/2 | 7/8–14 | 3.38 | 2.13 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male SAE Tube O-Ring Nut - 45° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | | | " | " | " |
| G45584-0606 | 6ACA-6MTON45 | 7332-00475 | 5/16 | 5/8–18 | | .88 | 3.19 | 1.94 |
| G45584-0608 | 6ACA-8MTON45 | 7332-03095 | 5/16 | 3/4–16 | | 1.00 | 3.47 | 2.22 |
| G45584-0806 | 8ACA-6MTON45 | 7332-03105 | 13/32 | 5/8–18 | | 1.00 | 3.47 | 2.22 |
| G45584-0808 | 8ACA-8MTON45 | 7332-00485 | 13/32 | 3/4–16 | | 1.00 | 3.44 | 2.19 |
| G45584-1010 | 10ACA-10MTON45 | 7332-00495 | 1/2 | 7/8–14 | | 1.06 | 3.81 | 2.56 |
| G45584-1212 | 12ACA-12MTON45 | 7332-00505 | 5/8 | 1 1/16–14 | | 1.19 | 4.19 | 2.94 |

# Male SAE Tube O-Ring Nut - 45° Bent Tube - Steel


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | | | " | " | " |
| G45584-0606S | 6ACA-6MTON45-S | 7332-04415 | 5/16 | 5/8–18 | | .88 | 1.69 | 4.03 |
| G45584-1010S | 10ACA-10MTON45-S | 7332-04425 | 1/2 | 7/8–14 | | 1.06 | 2.31 | 4.63 |

# Male SAE Tube O-Ring Nut - 90° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45585-0606 | 6ACA-6MTON90 | 7332-00515 | 5/16 | 5/8–18 | 1.63 | 2.56 | 1.31 |
| G45585-0607 | 6ACA-7MTON90 | 7332-03115 | 5/16 | 11/16–16 | 1.56 | 2.56 | 1.31 |
| G45585-0608 | 6ACA-8MTON90 | 7332-03125 | 5/16 | 3/4–16 | 1.88 | 2.75 | 1.50 |
| G45585-0806 | 8ACA-6MTON90 | 7332-03135 | 13/32 | 5/8–18 | 1.88 | 2.75 | 1.50 |
| G45585-0808 | 8ACA-8MTON90 | 7332-00525 | 13/32 | 3/4–16 | 1.88 | 2.75 | 1.50 |
| G45585-1010 | 10ACA-10MTON90 | 7332-00535 | 1/2 | 7/8–14 | 2.12 | 3.00 | 1.75 |
| G45585-1210 | 12ACA-10MTON90 | 7332-03145 | 5/8 | 7/8–14 | 2.25 | 3.25 | 2.00 |
| G45585-1212 | 12ACA-12MTON90 | 7332-00545 | 5/8 | 1 1/16–14 | 2.25 | 3.25 | 2.00 |

# Male SAE Tube O-Ring Nut - 90° Bent Tube - Steel

O–Ring not included. Must be ordered separately.





| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45585-0606S | 6ACA-6MTON90-S | 7332-01295 | 5/16 | 5/8–18 | 1.63 | 2.56 | 1.31 |
| G45585-0808S | 8ACA-8MTON90-S | 7332-04435 | 13/32 | 3/4–16 | 1.88 | 1.25 | 4.73 |
| G45585-1010S | 10ACA-10MTON90-S | 7332-01875 | 1/2 | 7/8–14 | 2.12 | 3.00 | 1.75 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female SAE Tube O-Ring Nut Swivel with R12 Service Port - Aluminum


O–Ring not included. Must be ordered separately.
Service Ports: High Side; –6, –8 Hose; 3/8" Schrader Valve
Service Ports: Low Side; –10, –12 Hose; 1/4" Schrader Valve




| Part No. | Descr. | Prod. No. | ⊖ | | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45586-0606 | 6ACA-6FTONR12SP | 7332-01985 | 5/16 | 5/8–18 | 3.38 | 2.13 |
| G45586-0808 | 8ACA-8FTONR12SP | 7332-01995 | 13/32 | 3/4–16 | 3.38 | 2.13 |
| G45586-1010 | 10ACA-10FTONR12SP | 7332-02005 | 1/2 | 7/8–14 | 3.62 | 2.37 |

# Female SAE Tube O-Ring Nut Swivel with R12 Service Port - 90° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45587-0606 | 6ACA-6FTONR12SP90 | 7332-02015 | 5/16 | 5/8–18 | 1.12 | 3.62 | 2.37 |
| G45587-0808 | 8ACA-8FTONR12SP90 | 7332-02025 | 13/32 | 3/4–16 | 1.31 | 3.62 | 2.37 |
| G45587-1010 | 10ACA-10FTONR12SP90 | 7332-02035 | 1/2 | 7/8–14 | 1.50 | 3.88 | 2.63 |
| G45587-1210 | 12ACA-10FTONR12SP90 | 7332-02045 | 5/8 | 7/8–14 | 1.75 | 4.19 | 2.94 |

# Female SAE Tube O-Ring Nut Swivel with R134a Service Port - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ||| L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " |
| G45588-0606 | 6ACA-6FTON134SP | 7332-00555 | 5/16 | 5/8–18 | | 3.30 | 2.05 |
| G45588-0808 | 8ACA-8FTON134SP | 7332-00565 | 13/32 | 3/4–16 | | 3.38 | 2.13 |
| G45588-1010 | 10ACA-10FTON134SP | 7332-00575 | 1/2 | 7/8–14 | | 3.62 | 2.37 |
| G45588-1210 | 12ACA-10FTON134SP | 7332-00585 | 5/8 | 7/8–14 | | 3.75 | 2.50 |

# Female SAE Tube O-Ring Nut Swivel with R134a Service Port - Steel

O–Ring not included. Must be ordered separately.





| Part No. | Descr. | Prod. No. | ⊖ | ||| L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " |
| G45588-0606S | 6ACA-6FTON134SP-S | 7332-04405 | 5/16 | 5/8–18 | | 1.88 | 3.98 |
| G45588-0808S | 8ACA-8FTON134SP-S | 7332-02685 | 13/32 | 3/4–16 | | 3.38 | 2.13 |
| G45588-1010S | 10ACA-10FTON134SP-S | 7332-02695 | 1/2 | 7/8–14 | | 3.62 | 2.37 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female SAE Tube O-Ring Nut Swivel with R134a Service Port - 90° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ≋ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45589-0606 | 6ACA-6FTON134SP90 | 7332-00595 | 5/16 | 5/8–18 | 1.12 | 3.62 | 2.37 |
| G45589-0808 | 8ACA-8FTON134SP90 | 7332-00605 | 13/32 | 3/4–16 | 1.31 | 3.62 | 2.37 |
| G45589-1010 | 10ACA-10FTON134SP90 | 7332-00615 | 1/2 | 7/8–14 | 1.50 | 3.88 | 2.63 |
| G45589-1210 | 12ACA-10FTON134SP90 | 7332-00625 | 5/8 | 7/8–14 | 1.75 | 4.19 | 2.94 |

# Female SAE Tube O-Ring Nut Swivel with R134a Service Port - 90° Bent Tube - Steel


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ≋ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45589-0606S | 6ACA-6FTON134SP90-S | 7332-02075 | 5/16 | 5/8–18 | 1.12 | 3.62 | 2.37 |
| G45589-0808S | 8ACA-8FTON134SP90-S | 7332-01705 | 13/32 | 3/4–16 | 1.50 | 3.62 | 2.37 |
| G45589-1010S | 10ACA-10FTON134SP90-S | 7332-01715 | 1/2 | 7/8–14 | 1.75 | 3.88 | 2.63 |
| G45589-1210S | 12ACA-10FTON134SP90-S | 7332-02085 | 5/8 | 7/8–14 | 1.75 | 4.19 | 2.94 |

# Female SAE Tube O-Ring Nut Swivel - Aluminum

O–Ring not included. Must be ordered separately.





| Part No. | Descr. | Prod. No. | ⊖ | | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45590-0605 | 6ACA-5FTON* ** | 7332-00635 | 5/16 | 1/2–20 | 2.81 | 1.56 |
| G45590-0606 | 6ACA-6FTON | 7332-00645 | 5/16 | 5/8–18 | 2.88 | 1.63 |
| G45590-0608 | 6ACA-8FTON | 7332-00655 | 5/16 | 3/4–16 | 3.00 | 1.75 |
| G45590-0806 | 8ACA-6FTON | 7332-03165 | 13/32 | 5/8–18 | 3.00 | 1.75 |
| G45590-0808 | 8ACA-8FTON | 7332-00665 | 13/32 | 3/4–16 | 3.00 | 1.75 |
| G45590-1008 | 10ACA-8FTON | 7332-01505 | 1/2 | 3/4–16 | 3.19 | 1.94 |
| G45590-1010 | 10ACA-10FTON | 7332-00675 | 1/2 | 7/8–14 | 3.19 | 1.94 |
| G45590-1012 | 10ACA-12FTON | 7332-01515 | 1/2 | 1 1/16–14 | 3.31 | 2.06 |
| G45590-1210 | 12ACA-10FTON | 7332-00685 | 5/8 | 7/8–14 | 3.31 | 2.06 |
| G45590-1212 | 12ACA-12FTON | 7332-00695 | 5/8 | 1 1/16–14 | 3.31 | 2.06 |

**Standard and Metric threads are equivalent for 6ACA–5FTON.*
***Used on Toyota Receivers and Dryers.*

# Female SAE Tube O-Ring Nut Swivel - Steel

O–Ring not included. Must be ordered separately.





| Part No. | Descr. | Prod. No. | ⊖ | | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45590-0606S | 6ACA-6FTON-S | 7332-01275 | 5/16 | 5/8–18 | 2.88 | 1.63 |
| G45590-0808S | 8ACA-8FTON-S | 7332-01645 | 13/32 | 3/4–16 | 3.00 | 1.75 |
| G45590-1010S | 10ACA-10FTON-S | 7332-01655 | 1/2 | 7/8–14 | 3.19 | 1.94 |
| G45590-1210S | 12ACA-10FTON-S | 7332-01815 | 5/8 | 7/8–14 | 3.31 | 2.06 |
| G45590-1212S | 12ACA-12FTON-S | 7332-03175 | 5/8 | 1 1/16–14 | 3.31 | 2.06 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female SAE Tube O-Ring Nut Swivel - 45° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G45591-0606 | 6ACA-6FTON45 | 7332-00705 | 5/16 | 5/8–18 | | .56 | 2.87 | 1.52 |
| G45591-0806 | 8ACA-6FTON45 | 7332-03185 | 13/32 | 5/8–18 | | .63 | 3.04 | 1.79 |
| G45591-0808 | 8ACA-8FTON45 | 7332-00715 | 13/32 | 3/4–16 | | .63 | 3.07 | 1.82 |
| G45591-1008 | 10ACA-8FTON45 | 7332-03195 | 1/2 | 3/4–16 | | .88 | 3.60 | 2.35 |
| G45591-1010 | 10ACA-10FTON45 | 7332-00725 | 1/2 | 7/8–14 | | .88 | 3.63 | 2.38 |
| G45591-1210 | 12ACA-10FTON45 | 7332-03205 | 5/8 | 7/8–14 | | .94 | 3.91 | 2.66 |
| G45591-1212 | 12ACA-12FTON45 | 7332-00735 | 5/8 | 1 1/16–14 | | .94 | 3.94 | 2.69 |

# Female SAE Tube O-Ring Nut Swivel - 45° Bent Tube - Steel


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G45591-0606S | 6ACA-6FTON45-S | 7332-01665 | 5/16 | 5/8–18 | | .56 | 2.87 | 1.52 |
| G45591-0808S | 8ACA-8FTON45-S | 7332-02055 | 13/32 | 3/4–16 | | .63 | 3.07 | 1.82 |
| G45591-1010S | 10ACA-10FTON45-S | 7332-01675 | 1/2 | 7/8–14 | | .88 | 3.63 | 2.38 |

# Female SAE Tube O-Ring Nut Swivel - 90° Bent Tube - Aluminum

O–Ring not included. Must be ordered separately.





| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G45592-0605 | 6ACA-5FTON90* | 7332-00745 | 5/16 | 1/2–20 | | 1.12 | 2.75 | 1.63 |
| G45592-0606 | 6ACA-6FTON90 | 7332-00755 | 5/16 | 5/8–18 | | 1.12 | 2.56 | 1.31 |
| G45592-0608 | 6ACA-8FTON90 | 7332-00765 | 5/16 | 3/4–16 | | 1.31 | 2.75 | 1.50 |
| G45592-0806 | 8ACA-6FTON90 | 7332-03155 | 13/32 | 5/8–18 | | 1.31 | 2.75 | 1.50 |
| G45592-0808 | 8ACA-8FTON90 | 7332-00775 | 13/32 | 3/4–16 | | 1.31 | 2.75 | 1.50 |
| G45592-1008 | 10ACA-8FTON90 | 7332-01545 | 1/2 | 3/4–16 | | 1.50 | 3.00 | 1.75 |
| G45592-1010 | 10ACA-10FTON90 | 7332-00785 | 1/2 | 7/8–14 | | 1.50 | 3.00 | 1.75 |
| G45592-1012 | 10ACA-12FTON90 | 7332-01555 | 1/2 | 1 1/16–14 | | 1.75 | 3.25 | 2.00 |
| G45592-1210 | 12ACA-10FTON90 | 7332-00795 | 5/8 | 7/8–14 | | 1.75 | 3.25 | 2.00 |
| G45592-1212 | 12ACA-12FTON90 | 7332-00805 | 5/8 | 1 1/16–14 | | 1.75 | 3.25 | 2.00 |

**Used on Toyota Receivers and Dryers.*

# Female SAE Tube O-Ring Nut Swivel - 90° Bent Tube - Steel

O–Ring not included. Must be ordered separately.





| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G45592-0606S | 6ACA-6FTON90-S | 7332-01305 | 5/16 | 5/8–18 | | 1.12 | 2.56 | 1.31 |
| G45592-0808S | 8ACA-8FTON90-S | 7332-01685 | 13/32 | 3/4–16 | | 1.31 | 2.75 | 1.50 |
| G45592-1010S | 10ACA-10FTON90-S | 7332-01695 | 1/2 | 7/8–14 | | 1.50 | 3.00 | 1.75 |
| G45592-1210S | 12ACA-10FTON90-S | 7332-01825 | 5/8 | 7/8–14 | | 1.50 | 3.25 | 2.00 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female SAE Tube O-Ring Metric Nut Swivel - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ⫼ | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45593-0616 | 6ACA-16FTOMN | 7332-00815 | 5/16 | M16X1.5 | 2.81 | 1.56 |
| G45593-0618 | 6ACA-18FTOMN | 7332-03215 | 5/16 | M18X1.5 | 2.87 | 1.62 |
| G45593-0620 | 6ACA-20FTOMN | 7332-03225 | 5/16 | M20X1.5 | 2.94 | 1.69 |
| G45593-0820 | 8ACA-20FTOMN | 7332-03235 | 13/32 | M20X1.5 | 2.94 | 1.69 |
| G45593-1022 | 10ACA-22FTOMN | 7332-00825 | 1/2 | M22X1.5 | 3.19 | 1.94 |
| G45593-1024 | 10ACA-24FTOMN | 7332-00835 | 1/2 | M24X2.0 | 3.19 | 1.94 |
| G45593-1227 | 12ACA-27FTOMN | 7332-00845 | 5/8 | M27X2.0 | 3.31 | 2.06 |

# Female SAE Tube O-Ring Metric Nut Swivel - 45° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ⫼ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45594-0614 | 6ACA-14FTOMN45 | 7332-03245 | 5/16 | M14X1.5 | .63 | 3.47 | 2.22 |
| G45594-0616 | 6ACA-16FTOMN45 | 7332-03255 | 5/16 | M16X1.5 | .63 | 3.47 | 2.22 |
| G45594-0618 | 6ACA-18FTOMN45 | 7332-03265 | 5/16 | M18X1.5 | .69 | 3.53 | 2.28 |
| G45594-0620 | 6ACA-20FTOMN45 | 7332-03275 | 5/16 | M20X1.5 | .75 | 3.72 | 2.47 |
| G45594-0820 | 8ACA-20FTOMN45 | 7332-03285 | 13/32 | M20X1.5 | .75 | 3.72 | 2.47 |
| G45594-1022 | 10ACA-22FTOMN45 | 7332-03295 | 1/2 | M22X1.5 | .88 | 3.60 | 2.35 |
| G45594-1024 | 10ACA-24FTOMN45 | 7332-03305 | 1/2 | M24X2.0 | .88 | 3.60 | 2.35 |
| G45594-1227 | 12ACA-27FTOMN45 | 7332-03315 | 5/8 | M27X2.0 | 1.00 | 4.59 | 3.34 |

# Female SAE Tube O-Ring Metric Nut Swivel - 90° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G45595-0616 | 6ACA-16FTOMN90 | 7332-00855 | 5/16 | M16X1.5 | | 1.12 | 2.75 | 1.50 |
| G45595-0618 | 6ACA-18FTOMN90 | 7332-03325 | 5/16 | M18X1.5 | | 1.12 | 2.75 | 1.50 |
| G45595-0620 | 6ACA-20FTOMN90 | 7332-03335 | 5/16 | M20X1.5 | | 1.25 | 2.75 | 1.50 |
| G45595-0820 | 8ACA-20FTOMN90 | 7332-03345 | 13/32 | M20X1.5 | | 1.37 | 2.94 | 1.69 |
| G45595-1022 | 10ACA-22FTOMN90 | 7332-00865 | 1/2 | M22X1.5 | | 1.63 | 3.13 | 1.88 |
| G45595-1024 | 10ACA-24FTOMN90 | 7332-00875 | 1/2 | M24X2.0 | | 1.50 | 3.13 | 1.88 |
| G45595-1227 | 12ACA-27FTOMN90 | 7332-00885 | 5/8 | M27X2.0 | | 1.75 | 3.38 | 2.13 |

# Female SAE Tube O-Ring Nut Swivel - 90° Block - Steel

O–Ring not included. Must be ordered separately.





| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G45596-0808S | 8ACA-8FTON90BL-S | 7332-01835 | 13/32 | 3/4–16 | | .71 | 2.44 | 1.19 |
| G45596-1010S | 10ACA-10FTON90BL-S | 7332-01845 | 1/2 | 7/8–14 | | .71 | 2.50 | 1.25 |
| G45596-1210S | 12ACA-10FTON90BL-S | 7332-01855 | 5/8 | 7/8–14 | | .71 | 2.62 | 1.37 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male Inverted O-Ring - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ||| L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " |
| G45597-0606 | 6ACA-6MIO | 7332-00895 | 5/16 | 5/8–18 | | 2.94 | 1.69 |
| G45597-0808 | 8ACA-8MIO | 7332-00905 | 13/32 | 3/4–18 | | 3.13 | 1.88 |
| G45597-1010 | 10ACA-10MIO | 7332-00915 | 1/2 | 7/8–14 | | 3.62 | 2.37 |
| G45597-1212 | 12ACA-12MIO | 7332-00925 | 5/8 | 1 1/16–14 | | 3.88 | 2.63 |

## Male Inverted O-Ring - Steel


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ||| L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " |
| G45597-0606S | 6ACA-6MIO-S | 7332-01885 | 5/16 | 5/8–18 | | 2.94 | 1.69 |
| G45597-0808S | 8ACA-8MIO-S | 7332-01895 | 13/32 | 3/4–18 | | 3.13 | 1.88 |
| G45597-1010S | 10ACA-10MIO-S | 7332-03355 | 1/2 | 7/8–14 | | 3.62 | 2.37 |

## Male Inverted O-Ring - 45° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G45598-0606 | 6ACA-6MIO45 | 7332-03365 | 5/16 | 5/8–18 | | .75 | 3.03 | 1.78 |
| G45598-0808 | 8ACA-8MIO45 | 7332-03375 | 13/32 | 3/4–18 | | 1.00 | 3.41 | 2.16 |
| G45598-1010 | 10ACA-10MIO45 | 7332-03385 | 1/2 | 7/8–14 | | 1.25 | 3.97 | 2.72 |

# Male Inverted O-Ring - 90° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ≈ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45599-0606 | 6ACA-6MIO90 | 7332-00935 | 5/16 | 5/8–18 | 1.50 | 2.56 | 1.31 |
| G45599-0808 | 8ACA-8MIO90 | 7332-00945 | 13/32 | 3/4–18 | 1.75 | 2.75 | 1.50 |
| G45599-1010 | 10ACA-10MIO90 | 7332-00955 | 1/2 | 7/8–14 | 2.00 | 3.00 | 1.75 |

# Male Inverted O-Ring Bulkhead - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ≈ | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45600-0606 | 6ACA-6MIOBKHD | 7332-00965 | 5/16 | 5/8–18 | 4.00 | 2.75 |
| G45600-0808 | 8ACA-8MIOBKHD | 7332-00975 | 13/32 | 3/4–18 | 4.25 | 3.00 |
| G45600-1010 | 10ACA-10MIOBKHD | 7332-00985 | 1/2 | 7/8–14 | 4.44 | 3.19 |

# Male Inverted O-Ring Bulkhead - Steel

O–Ring not included. Must be ordered separately.





| Part No. | Descr. | Prod. No. | ⊖ | ≈ | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45600-0606S | 6ACA-6MIOBKHD-S | 7332-04445 | 5/16 | 5/8–18 | 1.82 | 2.36 |
| G45600-1010S | 10ACA-10MIOBKHD-S | 7332-04455 | 1/2 | 7/8–14 | 2.13 | 2.57 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Inverted O-Ring Bulkhead - 90° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⟷ | ≡ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45602-0606 | 6ACA-6MIOBKHD90 | 7332-00995 | 5/16 | 5/8–18 | 2.12 | 3.13 | 1.88 |
| G45602-0808 | 8ACA-8MIOBKHD90 | 7332-01005 | 13/32 | 3/4–18 | 2.44 | 3.25 | 2.00 |
| G45602-1010 | 10ACA-10MIOBKHD90 | 7332-01015 | 1/2 | 7/8–14 | 2.50 | 3.50 | 2.25 |

# Female SAE Tube Dual O-Ring Nut - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⟷ | ≡ | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45604-0808 | 8ACA-8FTDON | 7332-03395 | 13/32 | 13/16–16 | 3.55 | 2.30 |
| G45604-1010 | 10ACA-10FTDON | 7332-03405 | 1/2 | 15/16–16 | 3.79 | 2.54 |
| G45604-1212 | 12ACA-12FTDON | 7332-03415 | 5/8 | 1 1/16–14 | 3.96 | 2.71 |

# Female SAE Tube Dual O-Ring Nut - 45° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G45605-0808 | 8ACA-8FTDON45 | 7332-03425 | 13/32 | 13/16–16 | | 1.02 | 3.43 | 2.18 |
| G45605-1212 | 12ACA-12FTDON45 | 7332-03445 | 5/8 | 1 1/16–14 | | 1.40 | 4.37 | 3.12 |

# Female SAE Tube Dual O-Ring Nut - 90° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G45606-0808 | 8ACA-8FTDON90 | 7332-03455 | 13/32 | 13/16–16 | | 1.86 | 2.75 | 1.50 |
| G45606-1010 | 10ACA-10FTDON90 | 7332-03465 | 1/2 | 15/16–16 | | 1.91 | 3.00 | 1.75 |
| G45606-1212 | 12ACA-12FTDON90 | 7332-03475 | 5/8 | 1 1/16–14 | | 2.40 | 3.25 | 2.00 |

# Female SAE Tube Dual O-Ring Metric Nut - Aluminum

O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45607-0824 | 8ACA-24FTDOMN | 7332-03485 | 13/32 | M24X2.0 | 3.55 | 2.30 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female SAE Tube Dual O-Ring Metric Nut - Aluminum - Continued

| Part No. | Descr. | Prod. No. | ⊖ | | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45607-1024 | 10ACA-24FTDOMN | 7332-03495 | 1/2 | M24X2.0 | 3.79 | 2.54 |
| G45607-1227 | 12ACA-27FTDOMN | 7332-03505 | 5/8 | M27X2.0 | 3.96 | 2.71 |

## Female SAE Tube Dual O-Ring Metric Nut - 45° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45608-0824 | 8ACA-24FTDOMN45 | 7332-03515 | 13/32 | M24X2.0 | 1.02 | 3.43 | 2.18 |
| G45608-1024 | 10ACA-24FTDOMN45 | 7332-03525 | 1/2 | M24X2.0 | 1.30 | 4.02 | 2.77 |
| G45608-1227 | 12ACA-27FTDOMN45 | 7332-03535 | 5/8 | M27X2.0 | 1.40 | 4.37 | 3.12 |

## Female SAE Tube Dual O-Ring Metric Nut - 90° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45609-0824 | 8ACA-24FTDOMN90 | 7332-03545 | 13/32 | M24X2.0 | 1.86 | 2.75 | 1.50 |
| G45609-1024 | 10ACA-24FTDOMN90 | 7332-03555 | 1/2 | M24X2.0 | 1.91 | 3.00 | 1.75 |
| G45609-1227 | 12ACA-27FTDOMN90 | 7332-03565 | 5/8 | M27X2.0 | 2.40 | 3.25 | 2.00 |

# Female SAE Tube O-Ring Nut - 180° Bent Tube - Aluminum


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⟷ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G45610-0606 | 6ACA-6FTON180 | 7332-03575 | 5/16 | 5/8–18 | | 1.63 | 3.50 | 2.25 |
| G45610-0808 | 8ACA-8FTON180 | 7332-03585 | 13/32 | 3/4–16 | | 1.75 | 3.50 | 2.25 |
| G45610-1212 | 12ACA-12FTON180 | 7332-03595 | 5/8 | 1 1/16–14 | | 2.12 | 4.50 | 3.25 |

# Male Inverted O-Ring with R134a Service Port - Aluminum

O–Ring not included. Must be ordered separately.





| Part No. | Descr. | Prod. No. | ⟷ | | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45611-0606 | 6ACA-6MIO134SP | 7332-03605 | 5/16 | 5/8–18 | 3.47 | 2.22 |
| G45611-0808 | 8ACA-8MIO134SP | 7332-03615 | 13/32 | 3/4–18 | 4.22 | 2.97 |
| G45611-1010 | 10ACA-10MIO134SP | 7332-03625 | 1/2 | 7/8–14 | 4.22 | 2.97 |
| G45611-1212 | 12ACA-12MIO134SP | 7332-03635 | 5/8 | 1 1/16–14 | 4.47 | 3.22 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Male Inverted O-Ring with R134a Service Port - 90° Bent Tube - Aluminum

O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ≋ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45613-0606 | 6ACA-6MIO134SP90 | 7332-03645 | 5/16 | 5/8–18 | 1.50 | 3.59 | 2.34 |
| G45613-0808 | 8ACA-8MIO134SP90 | 7332-03655 | 13/32 | 3/4–18 | 1.80 | 3.59 | 2.34 |
| G45613-1010 | 10ACA-10MIO134SP90 | 7332-03665 | 1/2 | 7/8–14 | 2.00 | 3.85 | 2.60 |


# Universal Tee O-Ring Splicer English Threads - Aluminum




| Part No. | Descr. | Prod. No. | ⊖ | ≋ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45614-0606 | 6ACA-6TORSP | 7332-03675 | 5/16 | 5/8–18 | 2.47 | 2.50 | 1.25 |
| G45614-0608 | 6ACA-8TORSP | 7332-03685 | 5/16 | 3/4–16 | 2.97 | 2.62 | 1.37 |
| G45614-1010 | 10ACA-10TORSP | 7332-03695 | 1/2 | 7/8–14 | 3.53 | 2.75 | 1.50 |
| G45614-1012 | 10ACA-12TORSP | 7332-03705 | 1/2 | 1 1/16–14 | 4.10 | 2.94 | 1.69 |


# Female SAE Tube O-Ring Nut Swivel with R134a High Pressure Service Port - Aluminum

O–Ring not included. Must be ordered separately.





| Part No. | Descr. | Prod. No. | ⊖ | ||| L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " |
| G45688-1010 | 10ACA-10FTON134SPH | 7332-04245 | 1/2 | 7/8–14 | | 3.62 | 2.37 |

# Male Metric Flareless Assembly - Aluminum




| Part No. | Descr. | Prod. No. | ⊖ | ||| A1 | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | mm | " | " |
| G45935-0608 | 6ACA-8MMFA | 7332-01025 | 5/16 | 5/8–18 | | 8.0 | 2.77 | 1.52 |
| G45935-0812 | 8ACA-12MMFA | 7332-01035 | 13/32 | 3/4–16 | | 12.0 | 3.00 | 1.75 |
| G45935-1015 | 10ACA-14.5MMFA | 7332-01045 | 1/2 | 7/8–14 | | 14.5 | 3.12 | 1.87 |

# Female (Ford) Spring Lock Tee O-Ring Splicer - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | T | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45947-0608 | 6ACA-8FSLTORSP | 7332-03735 | 5/16 | 1.72 | 5.13 | 3.88 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female (Ford) Spring Lock Liquid Line Splicer - Aluminum





| Part No. | Descr. | Prod. No. | ⟷ | T | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45948-0608 | 6ACA-8FSLSP | 7332-03715 | 5/16 | 1.75 | 5.13 | 3.88 |

## Male (Ford) Spring Lock - 45° Bent Tube - Aluminum




| Part No. | Descr. | Prod. No. | ⟷ | T | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45949-0606 | 6ACA-6MSL45 | 7332-03725 | 5/16 | 1.25 | 3.97 | 2.72 |
| G45949-0608 | 6ACA-8MSL45 | 7332-03745 | 5/16 | 1.31 | 4.09 | 2.84 |
| G45949-0808 | 8ACA-8MSL45 | 7332-03755 | 13/32 | 1.31 | 4.09 | 2.84 |
| G45949-1010 | 10ACA-10MSL45 | 7332-03765 | 1/2 | 1.63 | 4.48 | 3.23 |
| G45949-1210 | 12ACA-10MSL45 | 7332-03785 | 5/8 | 1.63 | 4.48 | 3.23 |
| G45949-1212 | 12ACA-12MSL45 | 7332-03795 | 5/8 | 1.75 | 4.72 | 3.47 |

## Male (Ford) Spring Lock - Aluminum





| Part No. | Descr. | Prod. No. | ⟷ | L | C |
|---|---|---|---|---|---|
| | | | " | " | " |
| G45950-0606 | 6ACA-6MSL | 7332-01055 | 5/16 | 3.81 | 2.56 |
| G45950-0608 | 6ACA-8MSL | 7332-01575 | 5/16 | 3.88 | 2.63 |

## Male (Ford) Spring Lock - Aluminum - Continued


| Part No. | Descr. | Prod. No. | ⊖ " | L " | C " |
|---|---|---|---|---|---|
| G45950-0808 | 8ACA-8MSL | 7332-01065 | 13/32 | 3.88 | 2.63 |
| G45950-1010 | 10ACA-10MSL | 7332-01075 | 1/2 | 4.00 | 2.75 |
| G45950-1210 | 12ACA-10MSL | 7332-01585 | 5/8 | 4.00 | 2.75 |
| G45950-1212 | 12ACA-12MSL | 7332-01085 | 5/8 | 4.25 | 3.00 |

## Male (Ford) Spring Lock - 90° Bent Tube - Aluminum




| Part No. | Descr. | Prod. No. | ⊖ " | T " | L " | C " |
|---|---|---|---|---|---|---|
| G45951-0606 | 6ACA-6MSL90 | 7332-02135 | 5/16 | 2.19 | 2.88 | 1.63 |
| G45951-0608 | 6ACA-8MSL90 | 7332-02185 | 5/16 | 2.38 | 3.12 | 1.88 |
| G45951-0808 | 8ACA-8MSL90 | 7332-02145 | 13/32 | 2.38 | 2.94 | 1.69 |
| G45951-1010 | 10ACA-10MSL90 | 7332-02155 | 1/2 | 2.50 | 1.95 | 1.89 |
| G45951-1210 | 12ACA-10MSL90 | 7332-02175 | 5/8 | 2.50 | 3.13 | 1.89 |

## Female (Ford) Spring Lock - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ " | L " | C " |
|---|---|---|---|---|---|
| G45952-0606 | 6ACA-6FSL | 7332-01095 | 5/16 | 3.81 | 2.56 |
| G45952-0608 | 6ACA-8FSL | 7332-01595 | 5/16 | 3.85 | 2.59 |
| G45952-0808 | 8ACA-8FSL | 7332-01105 | 13/32 | 3.88 | 2.63 |
| G45952-1010 | 10ACA-10FSL | 7332-01115 | 1/2 | 4.13 | 2.88 |
| G45952-1210 | 12ACA-10FSL | 7332-01605 | 5/8 | 4.28 | 3.10 |
| G45952-1212 | 12ACA-12FSL | 7332-01125 | 5/8 | 4.25 | 3.00 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Female (Ford) Spring Lock - 90° Bent Tube - Aluminum




| Part No. | Descr. | Prod. No. | ⊖ | T | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45953-0606 | 6ACA-6FSL90 | 7332-02195 | 5/16 | 2.19 | 2.88 | 1.63 |
| G45953-0608 | 6ACA-8FSL90 | 7332-02245 | 5/16 | 2.38 | 3.12 | 1.88 |
| G45953-0808 | 8ACA-8FSL90 | 7332-02205 | 13/32 | 2.38 | 2.94 | 1.69 |
| G45953-1010 | 10ACA-10FSL90 | 7332-02215 | 1/2 | 2.50 | 3.13 | 1.89 |
| G45953-1210 | 12ACA-10FSL90 | 7332-02235 | 5/8 | 2.50 | 3.13 | 1.89 |
| G45953-1212 | 12ACA-12FSL90 | 7332-02225 | 5/8 | 3.20 | 3.69 | 2.44 |


## Hose Splicer with R12 Thread Service Port - Aluminum

Service Ports: High Side; –6, –8 Hose; 3/8" Schrader Valve
Service Ports: Low Side; –10, –12 Hose; 1/4" Schrader Valve




| Part No. | Descr. | Prod. No. | ⊖ | L | C |
|---|---|---|---|---|---|
| | | | " | " | " |
| G45954-0606 | 6ACA-R12SP | 7332-01135 | 5/16 | 4.50 | 2.00 |
| G45954-0808 | 8ACA-R12SP | 7332-01145 | 13/32 | 4.50 | 2.00 |
| G45954-1010 | 10ACA-R12SP | 7332-01155 | 1/2 | 4.63 | 2.13 |
| G45954-1212 | 12ACA-R12SP | 7332-01165 | 5/8 | 4.75 | 2.25 |


# Female (Ford) Spring Lock - 45° Bent Tube - Aluminum




| Part No. | Descr. | Prod. No. | ⊖ | T | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G45955-0606 | 6ACA-6FSL45 | 7332-03805 | 5/16 | 1.31 | 4.03 | 2.78 |
| G45955-0608 | 6ACA-8FSL45 | 7332-03815 | 5/16 | 1.37 | 4.15 | 2.90 |
| G45955-0808 | 8ACA-8FSL45 | 7332-03825 | 13/32 | 1.37 | 4.15 | 2.90 |
| G45955-1010 | 10ACA-10FSL45 | 7332-03835 | 1/2 | 1.69 | 4.54 | 3.29 |
| G45955-1210 | 12ACA-10FSL45 | 7332-03845 | 5/8 | 1.75 | 4.60 | 3.35 |
| G45955-1212 | 12ACA-12FSL45 | 7332-03855 | 5/8 | 1.75 | 4.72 | 3.47 |

# Hose Splicer with R134a Service Port - Aluminum

Service Ports: High Side; –6, –8 Hose; 3/8" Schrader Valve
Service Ports: Low Side; –10, –12 Hose; 1/4" Schrader Valve





| Part No. | Descr. | Prod. No. | ⊖ | L | C |
|---|---|---|---|---|---|
| | | | " | " | " |
| G45956-0606 | 6ACA-R134SP | 7332-01175 | 5/16 | 4.50 | 2.00 |
| G45956-0808 | 8ACA-R134SP | 7332-01185 | 13/32 | 4.50 | 2.00 |
| G45956-1010 | 10ACA-R134SP | 7332-01195 | 1/2 | 4.63 | 2.13 |
| G45956-1212 | 12ACA-R134SP | 7332-01205 | 5/8 | 4.75 | 2.25 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Hose Splicer with R134a Service Port - Steel

Service Ports: High Side; –6, –8 Hose
Service Ports: Low Side; –10, –12 Hose




| Part No. | Descr. | Prod. No. | ⊖ | L | C |
|---|---|---|---|---|---|
| | | | " | " | " |
| G45956-0606S | 6ACA-R134SP-S | 7332-01955 | 5/16 | 4.50 | 2.00 |
| G45956-0808S | 8ACA-R134SP-S | 7332-01965 | 13/32 | 4.50 | 2.00 |
| G45956-1010S | 10ACA-R134SP-S | 7332-01975 | 1/2 | 4.63 | 2.13 |
| G45956-1212S | 12ACA-R134SP-S | 7332-03005 | 5/8 | 4.75 | 2.25 |


# Female Rotalok (Compressor Connection) with R134a Service Port - 90° Block - Aluminum




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G45957-0816 | 8ACA-R134SP-RL | 7332-01215 | 13/32 | 1–14 | | .78 | 2.45 | 1.20 |
| G45957-1016 | 10ACA-R134SP-RL | 7332-01225 | 1/2 | 1–14 | | .78 | 2.51 | 1.26 |

# Compressor Female SAE Tube O-Ring Nut Swivel - 90° Bent Tube - Steel


O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45958-0606S | 6ACA-6CFTON90-S | 7332-04465 | 5/16 | 1–14 | .84 | .94 | 2.44 |
| G45958-0810S | 8ACA-10CFTON90-S | 7332-02335 | 13/32 | 1–14 | 1.50 | 3.01 | 1.42 |
| G45958-1010S | 10ACA-10CFTON90-S | 7332-04475 | 1/2 | 1–14 | .84 | .94 | 2.63 |
| G45958-1210S | 12ACA-10CFTON90-S | 7332-02065 | 5/8 | 1–14 | 1.63 | 3.18 | 1.60 |

# Compressor Female SAE Tube O-Ring Nut Swivel - 90° Block - Steel

O–Ring not included. Must be ordered separately.





| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45959-0810S | 8ACA-10CFTON90BL-S | 7332-02095 | 13/32 | 1–14 | .80 | 3.02 | 1.43 |
| G45959-1210S | 12ACA-10CFTON90BL-S | 7332-02105 | 5/8 | 1–14 | .80 | 3.14 | 1.55 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Compressor Female Tube O-Ring Nut with 134a Service Port - 90° Block - Steel

O–Ring not included. Must be ordered separately.





| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G45960-0810S | 8ACA-10CFTON134SP90BL-S | 7332-03865 | 13/32 | 1–14 | | .78 | 2.45 | 1.20 |
| G45960-1010S | 10ACA-10CFTON134SP90BL-S | 7332-03875 | 1/2 | 1–14 | | .78 | 2.51 | 1.26 |
| G45960-1210S | 12ACA-10CFTON134SP90BL-S | 7332-02755 | 5/8 | 1–14 | | .78 | 2.67 | 1.42 |

# Compressor Block - Single w/Switch or Service Port - 90° Bent Tube - Aluminum




| Part No. | Descr. | Prod. No. | ⊖ | | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45961-0808 | 8ACA-8CBSR12SP90 | 7332-03935 | 13/32 | 3/4–16 | 1.31 | 3.62 | 2.37 |
| G45961-1008 | 10ACA-8CBSR12SP90 | 7332-03945 | 1/2 | 3/4–16 | 1.31 | 3.88 | 2.63 |
| G45961-1208 | 12ACA-8CBSR12SP90 | 7332-03955 | 5/8 | 3/4–16 | 1.31 | 4.17 | 2.94 |

# Compressor Block - Single Reverse w/Switch or Service Port - 90° Bent Tube - Aluminum




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G45962-0808 | 8ACA-8CBSRR12SP90 | 7332-03965 | 13/32 | 3/4–16 | 1.31 | 3.62 | 2.37 |
| G45962-1008 | 10ACA-8CBSRR12SP90 | 7332-03975 | 1/2 | 3/4–16 | 1.31 | 3.88 | 2.63 |
| G45962-1208 | 12ACA-8CBSRR12SP90 | 7332-03985 | 5/8 | 3/4–16 | 1.31 | 4.17 | 2.94 |


# R12 Ferrules



| Part No. | Descr. | Prod. No. |
|---|---|---|
| 83930 | 6PCACF | 7334-71305 |
| 83931 | 8PCACF | 7334-71315 |
| 83932 | 10PCACF | 7334-71325 |
| 83933 | 12PCACF | 7334-71335 |

# Inline Orifice Tube

Description: The orifice tube is found on an accumulator air conditioning system. It is the dividing point between high and low pressure sides of the refrigeration system. The orifice tube filters and restricts high–pressure refrigerant in the liquid line and meters refrigerant flow as a low–pressure liquid. It is located in the refrigerant line between the condenser outlet and the evaporator inlet. The tube should be replaced any time the air conditioning system is opened for service.





| Part No. | Descr. | Prod. No. | ⊙ | L | |
|---|---|---|---|---|---|
| | | | " | " | mm |
| G46011-0062 | IOT-RED | 7332-02805 | .062 | 3.50 | 88.9 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Inline Orifice Tube - Continued


| Part No. | Descr. | Prod. No. | I.D. | L | |
|---|---|---|---|---|---|
| | | | " | " | mm |
| G46010-0072 | IOT-WHITE | 7332-02775 | .072 | 3.50 | 88.9 |
| G46011-0072 | IOT-BLUE | 7332-02785 | .072 | 3.50 | 88.9 |
| G46010-1072 | IOT-BLACK | 7332-02815 | .072 | 3.50 | 88.9 |

## Female Flareless Nut - Aluminum





| Part No. | Descr. | Prod. No. | | A1 |
|---|---|---|---|---|
| | | | " | " |
| G46050-0006 | 6ACFFN | 7332-04135 | 5/8–18 | 3/8 |
| G46050-0008 | 8ACFFN | 7332-04145 | 3/4–16 | 1/2 |
| G46050-0010 | 10ACFFN | 7332-04155 | 7/8–14 | 5/8 |
| G46050-0012 | 12ACFFN | 7332-04165 | 1 1/16–14 | 3/4 |

## Female Flareless Sleeve




| Part No. | Descr. | Prod. No. | A1 |
|---|---|---|---|
| | | | " |
| G46051-0006 | 6ACFFS | 7332-04175 | 3/8 |
| G46051-0008 | 8ACFFS | 7332-04185 | 1/2 |
| G46051-0010 | 10ACFFS | 7332-04195 | 5/8 |
| G46051-0012 | 12ACFFS | 7332-04205 | 3/4 |

## Metric Female Flareless Sleeve





| Part No. | Descr. | Prod. No. | A1 mm |
|---|---|---|---|
| G46052-0008 | 8ACMFFS | 7332-04215 | 8.0 |
| G46052-0012 | 12ACMFFS | 7332-04225 | 12.0 |
| G46052-0014 | 14.5ACMFFS | 7332-04235 | 14.5 |

## Accumulator/Compressor Sealing Washer



| Part No. | Descr. | Prod. No. | ⊖ " |
|---|---|---|---|
| G46091-0010 | 10CPWTN | 7332-04015 | 5/8 |
| G46092-0010 | 10CPWTK | 7332-04035 | 5/8 |
| G46090-0012 | 12ACMW | 7332-04005 | 3/4 |
| G46091-0012 | 12CPWTN | 7332-04025 | 3/4 |

## Valve Core



| Part No. | Descr. | Prod. No. | " |
|---|---|---|---|
| G46093-0000 | .210VC | 7332-04045 | .210x36 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Valve Cap for R12 Service Port




| Part No. | Descr. | Prod. No. | " |
|---|---|---|---|
| G46094-0004 | 4R12CAP | 7332-04055 | 7/16–20 |

## Red High Side Cap R134a Port



| Part No. | Descr. | Prod. No. | " |
|---|---|---|---|
| G46095-0008 | 8HS134CAP | 7332-04115 | 8 |

## Blue Low Side Cap R134a Port



| Part No. | Descr. | Prod. No. | " |
|---|---|---|---|
| G46096-0008 | 8LS134CAP | 7332-04125 | 8 |

## O-Ring for Switch



| Part No. | Descr. | Prod. No. | Inside Diameter |
|---|---|---|---|
| | | | " |
| G46097-0006 | 6SWOR | 7332-04065 | 3/8 |

## O-Rings for PolarSeal® Couplings



| Part No. | Descr. | Prod. No. | Inside Diameter | Wall Thickness |
|---|---|---|---|---|
| | | | " | " |
| G46098-0006 | 6ACOR | 7332-01235 | .30 | .070 |
| G46098-0008 | 8ACOR | 7332-01245 | .43 | .070 |
| G46098-0010 | 10ACOR | 7332-01255 | .55 | .070 |
| G46098-0012 | 12ACOR | 7332-01265 | .68 | .070 |

## O-Ring for Ford Spring Lock



| Part No. | Descr. | Prod. No. | Inside Diameter |
|---|---|---|---|
| | | | " |
| G46099-0006 | 6FSLOR | 7332-04075 | 3/8 |
| G46099-0008 | 8FSLOR | 7332-04085 | 1/2 |
| G46099-0010 | 10FSLOR | 7332-04095 | 5/8 |
| G46099-0012 | 12FSLOR | 7332-04105 | 3/4 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# HYDRAULIC HOSE FOR POLARSEAL® II (ACB & ACC) COUPLINGS




**The Gates eCrimp program** is a web based utility which allows users and distributors of Gates hydraulic and industrial hose products to find and print the most up to date crimp specifications with nothing more than an internet browser.

This program can be used to find crimp data for all Gates crimpers. Custom result may be printed by selecting the crimper, hose and coupling. Optionally results may also be limited by die set and working pressure.


The eCrimp web application can be directly accessed from a web browser by entering http://eCrimp.Gates.com for the website.

**The eCrimp mobile app** is available for download for the iPhone and iPad from the App Store.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male Flareless Assembly



| Part No. | Descr. | Prod. No. | Standard Pack |
|---|---|---|---|
| G46510-0606 | 6ACC-6MFA | 7332-51355 | 1 |
| G46510-0808 | 8ACC-8MFA | 7332-51365 | 1 |
| G46510-1010 | 10ACC-10MFA | 7332-51375 | 1 |
| G46510-1212 | 12ACC-12MFA | 7332-51385 | 1 |

## Male Flareless Assembly - 90° Bent Tube



| Part No. | Descr. | Prod. No. | Standard Pack |
|---|---|---|---|
| G46511-0606 | 6ACC-6MFA90 | 7332-51395 | 1 |
| G46511-0808 | 8ACC-8MFA90 | 7332-51405 | 1 |
| G46511-1010 | 10ACC-10MFA90 | 7332-51415 | 1 |
| G46511-1212 | 12ACC-12MFA90 | 7332-51425 | 1 |

## Weld On Hose End



| Part No. | Descr. | Prod. No. | ⊖ " |
|---|---|---|---|
| G46527-0606 | 6ACC-6FBO | 7332-51165 | 5/16 |
| G46527-0808 | 8ACC-8FBO | 7332-51175 | 13/32 |
| G46527-1010 | 10ACC-10FBO | 7332-51185 | 1/2 |
| G46527-1210 | 12ACC-10FBO | 7332-51345 | 5/8 |
| G46527-1212 | 12ACC-12FBO | 7332-51195 | 5/8 |
| G46527-1216 | 12ACC-16FBO | 7332-51205 | 5/8 |

## Splicer




| Part No. | Descr. | Prod. No. | ⊖ " | ||| " |
|---|---|---|---|---|
| G46535-0606 | 6ACC-6HLE | 7332-50915 | 5/16 | 6 |
| G46535-0808 | 8ACC-8HLE | 7332-50925 | 13/32 | 8 |
| G46535-1010 | 10ACC-10HLE | 7332-50935 | 1/2 | 10 |
| G46535-1212 | 12ACC-12HLE | 7332-50945 | 5/8 | 12 |

## T Splicer



| Part No. | Descr. | Prod. No. | ⊖ " | ||| " |
|---|---|---|---|---|
| G46539-0606 | 6ACC-6HLET | 7332-51085 | 5/16 | 6 |
| G46539-0808 | 8ACC-8HLET | 7332-51095 | 13/32 | 8 |
| G46539-1010 | 10ACC-10HLET | 7332-51105 | 1/2 | 10 |
| G46539-1212 | 12ACC-12HLET | 7332-51115 | 5/8 | 12 |

## Y Splicer




| Part No. | Descr. | Prod. No. | ⊖ " | ||| " |
|---|---|---|---|---|
| G46542-0808 | 8ACC-8HLEY | 7332-51135 | 13/32 | 8 |
| G46542-1010 | 10ACC-10HLEY | 7332-51145 | 1/2 | 10 |
| G46542-1212 | 12ACC-12HLEY | 7332-51155 | 5/8 | 12 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male O-Ring - 180° Bent Tube



| Part No. | Descr. | Prod. No. | ⊖ " | " |
|---|---|---|---|---|
| G46578-0606 | 6ACC-6MTON180 | 7332-50895 | 5/16 | 5/8–18 |
| G46578-1010 | 10ACC-10MTON180 | 7332-50905 | 5/8 | 7/8–14 |

## Male O-Ring with Switch or Service Port - 90° Bent Tube



| Part No. | Descr. | Prod. No. | ⊖ " | " |
|---|---|---|---|---|
| G46582-0808H | 8ACC-8MTON90134SWPH | 7332-50695 | 13/32 | 3/4–16 |

## Male O-Ring




| Part No. | Descr. | Prod. No. | ⊖ " | " |
|---|---|---|---|---|
| G46583-0606 | 6ACC-6MTON | 7332-50525 | 5/16 | 5/8–18 |
| G46583-0806 | 8ACC-6MTON | 7332-50585 | 13/32 | 5/8–18 |
| G46583-0808 | 8ACC-8MTON | 7332-50535 | 13/32 | 3/4–16 |
| G46583-1010 | 10ACC-10MTON | 7332-50545 | 1/2 | 7/8–14 |
| G46583-1210 | 12ACC-10MTON | 7332-50595 | 5/8 | 7/8–14 |
| G46583-1212 | 12ACC-12MTON | 7332-50565 | 5/8 | 1 1/16–14 |
| G46583-1610 | 16ACC-10MTON | 7332-50555 | 7/8 | 7/8–14 |
| G46583-1612 | 16ACC-12MTON | 7332-50575 | 7/8 | 1 1/16–14 |

## Male O-Ring - 45° Bent Tube




| Part No. | Descr. | Prod. No. | ⟷ " | " |
|---|---|---|---|---|
| G46584-0606 | 6ACC-6MTON45 | 7332-50605 | 5/16 | 5/8–18 |
| G46584-1210 | 12ACC-10MTON45 | 7332-50615 | 5/8 | 7/8–14 |

## Male O-Ring - 90° Bent Tube



| Part No. | Descr. | Prod. No. | ⊖ " | " |
|---|---|---|---|---|
| G46585-0606 | 6ACC-6MTON90 | 7332-50625 | 5/16 | 5/8–18 |
| G46585-0806 | 8ACC-6MTON90 | 7332-50665 | 13/32 | 5/8–18 |
| G46585-0808 | 8ACC-8MTON90 | 7332-50635 | 13/32 | 3/4–16 |
| G46585-1008 | 10ACC-8MTON90 | 7332-50675 | 1/2 | 3/4–16 |
| G46585-1010 | 10ACC-10MTON90 | 7332-50645 | 1/2 | 7/8–14 |
| G46585-1210 | 12ACC-10MTON90 | 7332-50685 | 5/8 | 7/8–14 |
| G46585-1212 | 12ACC-12MTON90 | 7332-50655 | 5/8 | 1 1/16–14 |

## Straight Female O-Ring with R134 Service Port H



| Part No. | Descr. | Prod. No. | ⊖ " | " |
|---|---|---|---|---|
| G46588-0808H | 8ACC-8FTON134SPH | 7332-50135 | 13/32 | 3/4–16 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Straight Female O-Ring with R134 Service Port H - Continued

| Part No. | Descr. | Prod. No. | ⊖ " | " |
|---|---|---|---|---|
| G46588-1008H | 10ACC-8FTON134SPH | 7332-50195 | 1/2 | 3/4–16 |

## Straight Female O-Ring with R134 Service Port L




| Part No. | Descr. | Prod. No. | ⊖ " | " |
|---|---|---|---|---|
| G46588-1010L | 10ACC-10FTON134SPL | 7332-50145 | 1/2 | 7/8–14 |
| G46588-1210L | 12ACC-10FTON134SPL | 7332-50205 | 5/8 | 7/8–14 |
| G46588-1212L | 12ACC-12FTON134SPL | 7332-50175 | 5/8 | 1 1/16–14 |
| G46588-1610L | 16ACC-10FTON134SPL | 7332-50155 | 7/8 | 7/8–14 |

## Straight Female O-Ring with Switch Port M




| Part No. | Descr. | Prod. No. | ⊖ " | " |
|---|---|---|---|---|
| G46588-1210M | 12ACC-10FTONMSWP | 7332-50215 | 5/8 | 7/8–14 |
| G46588-1212M | 12ACC-12FTONMSWP | 7332-50185 | 5/8 | 1 1/16–14 |

## Straight Female O-Ring with Switch Port P




| Part No. | Descr. | Prod. No. | ⊖ " | ||| " |
|---|---|---|---|---|
| G46588-0808P | 8ACC-8FTONSWP | 7332-50125 | 13/32 | 3/4–16 |
| G46588-1212P | 12ACC-12FTONSWP | 7332-50165 | 5/8 | 1 1/16–14 |

## Female O-Ring with R134 Service Port H - 90° Bent Tube



| Part No. | Descr. | Prod. No. | ⊖ " | ||| " |
|---|---|---|---|---|
| G46589-0608H | 6ACC-8FTON134SPH90 | 7332-50505 | 5/16 | 3/4–16 |
| G46589-0808H | 8ACC-8FTON134SPH90 | 7332-50415 | 13/32 | 3/4–16 |
| G46589-1008H | 10ACC-8FTON134SPH90 | 7332-50485 | 1/2 | 3/4–16 |
| G46589-1010H | 10ACC-10FTON134SPH90 | 7332-50445 | 1/2 | 7/8–14 |

## Female O-Ring with R134 Service Port L - 90° Bent Tube



| Part No. | Descr. | Prod. No. | ⊖ " | ||| " |
|---|---|---|---|---|
| G46589-1010L | 10ACC-10FTON134SPL90 | 7332-50425 | 1/2 | 7/8–14 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female O-Ring with R134 Service Port L - 90° Bent Tube - Continued


| Part No. | Descr. | Prod. No. | ⊖ " | " |
|---|---|---|---|---|
| G46589-1210L | 12ACC-10FTON134SPL90 | 7332-50515 | 5/8 | 7/8–14 |

## Female O-Ring with Switch Port M - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⊖ " | " |
|---|---|---|---|---|
| G46589-1010M | 10ACC-10FTONMSWP90 | 7332-50435 | 1/2 | 7/8–14 |
| G46589-1212M | 12ACC-12FTONMSWP90 | 7332-50465 | 5/8 | 1 1/16–14 |

## Female O-Ring with Switch Port P - 90° Bent Tube



| Part No. | Descr. | Prod. No. | ⊖ " | " |
|---|---|---|---|---|
| G46589-0808P | 8ACC-8FTONSWP90 | 7332-50405 | 13/32 | 3/4–16 |
| G46589-1008P | 10ACC-8FTONSWP90 | 7332-50475 | 1/2 | 3/4–16 |
| G46589-1210P | 12ACC-10FTONMSWP90 | 7332-50495 | 5/8 | 7/8–14 |
| G46589-1212P | 12ACC-12FTONSWP90 | 7332-50455 | 5/8 | 1 1/16–14 |

## Straight Female O-Ring



| Part No. | Descr. | Prod. No. | ⟷ " | ||| " |
|---|---|---|---|---|
| G46590-0606 | 6ACC-6FTON | 7332-50015 | 5/16 | 5/8–18 |
| G46590-0608 | 6ACC-8FTON | 7332-50105 | 5/16 | 3/4–16 |
| G46590-0806 | 8ACC-6FTON | 7332-50075 | 13/32 | 5/8–18 |
| G46590-0808 | 8ACC-8FTON | 7332-50025 | 13/32 | 3/4–16 |
| G46590-0810 | 8ACC-10FTON | 7332-50115 | 13/32 | 7/8–14 |
| G46590-1008 | 10ACC-8FTON | 7332-50085 | 1/2 | 3/4–16 |
| G46590-1010 | 10ACC-10FTON | 7332-50035 | 1/2 | 7/8–14 |
| G46590-1210 | 12ACC-10FTON | 7332-50095 | 5/8 | 7/8–14 |
| G46590-1212 | 12ACC-12FTON | 7332-50055 | 5/8 | 1 1/16–14 |
| G46590-1610 | 16ACC-10FTON | 7332-50045 | 7/8 | 7/8–14 |
| G46590-1612 | 16ACC-12FTON | 7332-50065 | 7/8 | 1 1/16–14 |

## Female O-Ring - 45° Bent Tube




| Part No. | Descr. | Prod. No. | ⟷ " | ||| " |
|---|---|---|---|---|
| G46591-0606 | 6ACC-6FTON45 | 7332-50225 | 5/16 | 5/8–18 |
| G46591-0808 | 8ACC-8FTON45 | 7332-50235 | 13/32 | 3/4–16 |
| G46591-1008 | 10ACC-8FTON45 | 7332-50275 | 1/2 | 3/4–16 |
| G46591-1010 | 10ACC-10FTON45 | 7332-50245 | 1/2 | 7/8–14 |
| G46591-1210 | 12ACC-10FTON45 | 7332-50285 | 5/8 | 7/8–14 |
| G46591-1212 | 12ACC-12FTON45 | 7332-50255 | 5/8 | 1 1/16–14 |
| G46591-1612 | 16ACC-12FTON45 | 7332-50265 | 7/8 | 1 1/16–14 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female O-Ring - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⟷ " | ≡ " |
|---|---|---|---|---|
| G46592-0606 | 6ACC-6FTON90 | 7332-50295 | 5/16 | 5/8–18 |
| G46592-0608 | 6ACC-8FTON90 | 7332-50385 | 5/16 | 3/4–16 |
| G46592-0806 | 8ACC-6FTON90 | 7332-50355 | 13/32 | 5/8–18 |
| G46592-0808 | 8ACC-8FTON90 | 7332-50305 | 13/32 | 3/4–16 |
| G46592-0810 | 8ACC-10FTON90 | 7332-50395 | 13/32 | 7/8–14 |
| G46592-1008 | 10ACC-8FTON90 | 7332-50365 | 1/2 | 3/4–16 |
| G46592-1010 | 10ACC-10FTON90 | 7332-50315 | 1/2 | 7/8–14 |
| G46592-1210 | 12ACC-10FTON90 | 7332-50375 | 5/8 | 7/8–14 |
| G46592-1212 | 12ACC-12FTON90 | 7332-50335 | 5/8 | 1 1/16–14 |
| G46592-1610 | 16ACC-10FTON90 | 7332-50325 | 7/8 | 7/8–14 |
| G46592-1612 | 16ACC-12FTON90 | 7332-50345 | 7/8 | 1 1/16–14 |

## Metric Female O-Ring




| Part No. | Descr. | Prod. No. | ⟷ " | ≡ " |
|---|---|---|---|---|
| G46593-0820 | 8ACC-20FTOMN | 7332-51215 | 13/32 | M20X1.5 |
| G46593-1027 | 10ACC-27FTOMN | 7332-51225 | 1/2 | M27X2.0 |

## Metric Female O-Ring - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⟷ " | ||| " |
|---|---|---|---|---|
| G46595-0618 | 6ACC-18FTOMN90 | 7332-51235 | 5/16 | M18X1.5 |
| G46595-0820 | 8ACC-20FTOMN90 | 7332-51245 | 13/32 | M20X1.5 |
| G46595-1227 | 12ACC-27FTOMN90 | 7332-51255 | 5/8 | M27X2.0 |

## Male Insert O-Ring



| Part No. | Descr. | Prod. No. | ⟷ " | ||| " |
|---|---|---|---|---|
| G46597-0606 | 6ACC-6MIO | 7332-50795 | 5/16 | 5/8–18 |
| G46597-0806 | 8ACC-6MIO | 7332-50815 | 13/32 | 5/8–18 |
| G46597-0808 | 8ACC-8MIO | 7332-50805 | 13/32 | 3/4–16 |
| G46597-1210 | 12ACC-10MIO | 7332-50825 | 5/8 | 7/8–14 |

## Male Insert O-Ring - 90° Bent Tube



| Part No. | Descr. | Prod. No. | ⟷ " | ||| " |
|---|---|---|---|---|
| G46599-0606 | 6ACC-6MIO90 | 7332-50835 | 5/16 | 5/8–18 |
| G46599-0806 | 8ACC-6MIO90 | 7332-50865 | 13/32 | 5/8–18 |
| G46599-0808 | 8ACC-8MIO90 | 7332-50845 | 13/32 | 3/4–16 |
| G46599-1008 | 10ACC-8MIO90 | 7332-50875 | 1/2 | 3/4–16 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male Insert O-Ring - 90° Bent Tube - Continued


| Part No. | Descr. | Prod. No. | ⟷ " | ||| " |
|---|---|---|---|---|
| G46599-1010 | 10ACC-10MIO90 | 7332-50855 | 1/2 | 7/8–14 |
| G46599-1210 | 12ACC-10MIO90 | 7332-50885 | 5/8 | 7/8–14 |

## Male Insert O-Ring Bulkhead




| Part No. | Descr. | Prod. No. | ⟷ " | ||| " |
|---|---|---|---|---|
| G46600-0606 | 6ACC-6MIOBKHD | 7332-50705 | 5/16 | 5/8–18 |
| G46600-0808 | 8ACC-8MIOBKHD | 7332-50715 | 13/32 | 3/4–16 |
| G46600-1010 | 10ACC-10MIOBKHD | 7332-50725 | 1/2 | 7/8–14 |
| G46600-1210 | 12ACC-10MIOBKHD | 7332-50745 | 5/8 | 7/8–14 |
| G46600-1612 | 16ACC-12MIOBKHD | 7332-50735 | 7/8 | 1 1/16–14 |

## Male Insert O-Ring Bulkhead - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⟷ " | ||| " |
|---|---|---|---|---|
| G46602-0606 | 6ACC-6MIOBKHD90 | 7332-50755 | 5/16 | 5/8–18 |
| G46602-0808 | 8ACC-8MIOBKHD90 | 7332-50765 | 13/32 | 3/4–16 |
| G46602-1010 | 10ACC-10MIOBKHD90 | 7332-50775 | 1/2 | 7/8–14 |
| G46602-1210 | 12ACC-10MIOBKHD90 | 7332-50785 | 5/8 | 7/8–14 |

## Splicer with R134 Service Port H



| Part No. | Descr. | Prod. No. | ⊖ " | ||| " |
|---|---|---|---|---|
| G46956-0606H | 6ACC-6HLE134SPH | 7332-50965 | 5/16 | 6 |
| G46956-0808H | 8ACC-8HLE134SPH | 7332-50985 | 13/32 | 8 |
| G46956-1010H | 10ACC-10HLE134SPH | 7332-51035 | 1/2 | 10 |

## Splicer with R134 Service Port L



| Part No. | Descr. | Prod. No. | ⊖ " | ||| " |
|---|---|---|---|---|
| G46956-1010L | 10ACC-10HLE134SPL | 7332-51015 | 1/2 | 10 |
| G46956-1212L | 12ACC-12HLE134SPL | 7332-51055 | 5/8 | 12 |
| G46956-1616L | 16ACC-16HLE134SPL | 7332-51075 | 7/8 | 16 |

## Splicer with Switch Port M



| Part No. | Descr. | Prod. No. | ⊖ " | ||| " |
|---|---|---|---|---|
| G46956-0808M | 8ACC-8HLEMSWP | 7332-50995 | 13/32 | 8 |
| G46956-1010M | 10ACC-10HLEMSWP | 7332-51025 | 1/2 | 10 |
| G46956-1212M | 12ACC-12HLEMSWP | 7332-51065 | 5/8 | 12 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Splicer with Switch Port P




| Part No. | Descr. | Prod. No. | ⟷ " | ≡ " |
|---|---|---|---|---|
| G46956-0606P | 6ACC-6HLESWP | 7332-50955 | 5/16 | 6 |
| G46956-0808P | 8ACC-8HLESWP | 7332-50975 | 13/32 | 8 |
| G46956-1010P | 10ACC-10HLESWP | 7332-51005 | 1/2 | 10 |
| G46956-1212P | 12ACC-12HLESWP | 7332-51045 | 5/8 | 12 |

## Metric Female O-Ring with Switch or Service Port - 90° Bent Tube




| Part No. | Descr. | Prod. No. | ⟷ " | ≡ " |
|---|---|---|---|---|
| G46963-0610 | 6ACC-10FTOMN90134SPH | 7332-51265 | 5/16 | M10X1.5 |

## Metric Male Insert O-Ring



| Part No. | Descr. | Prod. No. | ⟷ " | ≡ " |
|---|---|---|---|---|
| G46965-1020 | 10ACC-20MIOM | 7332-51285 | 1/2 | M20X1.5 |

# Clamp Assemblies




| Part No. | Descr. | Prod. No. | ⟷ " |
|---|---|---|---|
| G46995-0006 | 6CLAMP | 7332-51295 | 5/16 |
| G46995-0008 | 8CLAMP | 7332-51305 | 13/32 |
| G46995-0010 | 10CLAMP | 7332-51315 | 1/2 |
| G46995-0012 | 12CLAMP | 7332-51325 | 5/8 |
| G46995-0016 | 16CLAMP | 7332-51335 | 7/8 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female SAE 45° Flare Swivel - Aluminum





| Part No. | Descr. | Prod. No. | ⟷ | ||| L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " |
| G47200-0606 | 6ACB-6FSX | 7332-51435 | 1/3 | 5/8–18 | | 2.88 | 1.38 |
| G47200-0608 | 6ACB-8FSX | 7332-51445 | 1/3 | 3/4–16 | | 2.70 | 1.20 |
| G47200-0806 | 8ACB-6FSX | 7332-52335 | 2/5 | 5/8–18 | | 2.69 | 1.19 |
| G47200-0808 | 8ACB-8FSX | 7332-51455 | 2/5 | 3/4–16 | | 2.69 | 1.19 |
| G47200-1008 | 10ACB-8FSX | 7332-52345 | 1/2 | 3/4–16 | | 3.00 | 1.50 |
| G47200-1010 | 10ACB-10FSX | 7332-51465 | 1/2 | 7/8–14 | | 3.00 | 1.50 |
| G47200-1212 | 12ACB-12FSX | 7332-51475 | 5/8 | 1 1/16–14 | | 3.25 | 1.75 |

## Female SAE 45° Flare Swivel - Steel




| Part No. | Descr. | Prod. No. | ⟷ | ||| L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " |
| G47200-0606S | 6ACB-6FSX-S | 7332-20015 | 5/16 | 5/8–18 | | 2.88 | 1.63 |
| G47200-0808S | 8ACB-8FSX-S | 7332-20025 | 13/32 | 3/4–16 | | 2.69 | 1.44 |
| G47200-1210S | 12ACB-10FSX-S | 7332-20035 | 5/8 | 7/8–14 | | 3.25 | 2.00 |

## Female SAE 45° Flare Swivel - 45° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⟷ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G47202-0606 | 6ACB-6FSX45 | 7332-51485 | 1/3 | 5/8–18 | | .56 | 2.84 | 1.34 |
| G47202-0808 | 8ACB-8FSX45 | 7332-51495 | 2/5 | 3/4–16 | | .63 | 3.07 | 1.57 |
| G47202-1010 | 10ACB-10FSX45 | 7332-51505 | 1/2 | 7/8–14 | | .88 | 3.63 | 2.13 |
| G47202-1212 | 12ACB-12FSX45 | 7332-51515 | 5/8 | 1 1/16–14 | | 1.00 | 4.00 | 2.50 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female SAE 45° Flare Swivel - 45° Bent Tube - Steel





| Part No. | Descr. | Prod. No. | ⟷ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47202-1008S | 10ACB-8FSX45-S | 7332-20045 | 1/2 | 3/4–16 | .63 | 3.00 | 1.75 |

## Female SAE 45° Flare Swivel - 90° Bent Tube - Aluminum




| Part No. | Descr. | Prod. No. | ⟷ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47205-0606 | 6ACB-6FSX90 | 7332-51525 | 1/3 | 5/8–18 | 1.06 | 2.56 | 1.06 |
| G47205-0808 | 8ACB-8FSX90 | 7332-51535 | 2/5 | 3/4–16 | 1.25 | 2.75 | 1.25 |
| G47205-1010 | 10ACB-10FSX90 | 7332-51545 | 1/2 | 7/8–14 | 1.50 | 3.00 | 1.50 |
| G47205-1210 | 12ACB-10FSX90 | 7332-51555 | 5/8 | 7/8–14 | 1.50 | 3.25 | 1.75 |
| G47205-1212 | 12ACB-12FSX90 | 7332-51565 | 5/8 | 1 1/16–14 | 1.50 | 3.25 | 1.75 |

## Female SAE 45° Flare Swivel - 90° Bent Tube - Steel





| Part No. | Descr. | Prod. No. | ⟷ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47205-0606S | 6ACB-6FSX90-S | 7332-20055 | 5/16 | 5/8–18 | 1.06 | 2.56 | 1.31 |
| G47205-0808S | 8ACB-8FSX90-S | 7332-20075 | 13/32 | 3/4–16 | 1.25 | 2.75 | 1.50 |

## Female SAE 45° Flare Swivel - 90° Bent Tube - Steel - Continued


| Part No. | Descr. | Prod. No. | ⟷ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G47205-1008S | 10ACB-8FSX90-S | 7332-20085 | 1/2 | 3/4–16 | | 1.50 | 3.00 | 1.75 |
| G47205-1010S | 10ACB-10FSX90-S | 7332-20095 | 1/2 | 7/8–14 | | 1.50 | 3.00 | 1.75 |
| G47205-1210S | 12ACB-10FSX90-S | 7332-20105 | 5/8 | 7/8–14 | | 1.50 | 3.25 | 2.00 |
| G47205-1212S | 12ACB-12FSX90-S | 7332-20115 | 5/8 | 1 1/16–14 | | 1.50 | 3.85 | 2.00 |

## Male SAE Flareless Assembly - Steel




| Part No. | Descr. | Prod. No. | ⟷ | ||| A1 | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G47510-0606S | 6ACB-6MFA-S | 7332-51575 | 1/3 | 5/8–18 | | 3/8 | 2.69 | 1.19 |
| G47510-0608S | 6ACB-8MFA-S | 7332-20125 | 5/16 | 3/4–16 | | 1/2 | 2.81 | 1.56 |
| G47510-0806S | 8ACB-6MFA-S | 7332-20135 | 13/32 | 9/16–18 | | 3/8 | 2.75 | 1.50 |
| G47510-0808S | 8ACB-8MFA-S | 7332-20145 | 13/32 | 3/4–16 | | 1/2 | 2.88 | 1.63 |
| G47510-0810S | 8ACB-10MFA-S | 7332-20155 | 13/32 | 7/8–14 | | 5/8 | 3.00 | 1.75 |
| G47510-1008S | 10ACB-8MFA-S | 7332-20165 | 1/2 | 3/4–16 | | 1/2 | 2.94 | 1.69 |
| G47510-1010S | 10ACB-10MFA-S | 7332-20175 | 1/2 | 7/8–14 | | 5/8 | 3.00 | 1.75 |
| G47510-1210S | 12ACB-10MFA-S | 7332-20185 | 5/8 | 7/8–14 | | 5/8 | 3.13 | 1.88 |
| G47510-1212S | 12ACB-12MFA-S | 7332-20195 | 5/8 | 1 1/16–12 | | 3/4 | 3.25 | 2.00 |

## Male SAE Flareless Assembly - 90° Block - Steel





| Part No. | Descr. | Prod. No. | ⟷ | ||| A1 | T | L | C |
|---|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " | " |
| G47511-0606S | 6ACB-6MFA90-S | 7332-20205 | 5/16 | 9/16–18 | | 3/8 | .78 | 2.24 | .99 |
| G47511-0608S | 6ACB-8MFA90-S | 7332-20215 | 5/16 | 3/4–16 | | 1/2 | .96 | 2.31 | 1.06 |
| G47511-0808S | 8ACB-8MFA90-S | 7332-20225 | 13/32 | 3/4–16 | | 1/2 | .96 | 2.37 | 1.12 |

## Male SAE Flareless Assembly - 90° Block - Steel - Continued


| Part No. | Descr. | Prod. No. | ⊖ | | A1 | T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " | " |
| G47511-0810S | 8ACB-10MFA90-S | 7332-20235 | 13/32 | 7/8–14 | 5/8 | 1.08 | 2.43 | 1.18 |
| G47511-1008S | 10ACB-8MFA90-S | 7332-20245 | 1/2 | 3/4–16 | 1/2 | .96 | 2.38 | 1.13 |
| G47511-1010S | 10ACB-10MFA90-S | 7332-20255 | 1/2 | 7/8–14 | 5/8 | 1.08 | 2.44 | 1.19 |
| G47511-1210S | 12ACB-10MFA90-S | 7332-20265 | 5/8 | 7/8–14 | 5/8 | 1.08 | 2.56 | 1.31 |
| G47511-1212S | 12ACB-12MFA90-S | 7332-20275 | 5/8 | 1 1/16–12 | 3/4 | 1.19 | 2.66 | 1.41 |

## Female Braze-On Stems - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | A1 | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47527-0606 | 6ACB-6FBO | 7332-52355 | 1/3 | 3/8 | 2.10 | .60 |
| G47527-0808 | 8ACB-8FBO | 7332-52365 | 2/5 | 1/2 | 2.10 | .60 |
| G47527-1010 | 10ACB-10FBO | 7332-52375 | 1/2 | 5/8 | 2.10 | .60 |
| G47527-1210 | 12ACB-10FBO | 7332-52385 | 5/8 | 5/8 | 2.10 | .60 |
| G47527-1212 | 12ACB-12FBO | 7332-52395 | 5/8 | 3/4 | 2.10 | .60 |

## Female Braze-On Stems - Steel





| Part No. | Descr. | Prod. No. | ⊖ | A1 | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47527-0606S | 6ACB-6FBO-S | 7332-20285 | 5/16 | 3/8 | 2.10 | .85 |
| G47527-0808S | 8ACB-8FBO-S | 7332-20295 | 13/32 | 1/2 | 2.10 | .85 |
| G47527-1010S | 10ACB-10FBO-S | 7332-20305 | 1/2 | 5/8 | 2.10 | .85 |
| G47527-1210S | 12ACB-10FBO-S | 7332-20315 | 5/8 | 5/8 | 2.10 | .85 |
| G47527-1212S | 12ACB-12FBO-S | 7332-20325 | 5/8 | 3/4 | 2.10 | .85 |

# Hose Length Extender - Aluminum




| Part No. | Descr. | Prod. No. | ⊖ | A1 | A2 | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47535-0606 | 6ACB-6HLE | 7332-52135 | 1/3 | 5/16 | 5/16 | 4.50 | 1.50 |
| G47535-0608 | 6ACB-8HLE | 7332-52145 | 1/3, 2/5 | 5/16 | 13/32 | 4.50 | 1.50 |
| G47535-0808 | 8ACB-8HLE | 7332-52155 | 2/5 | 13/32 | 13/32 | 4.50 | 1.50 |
| G47535-0810 | 8ACB-10HLE | 7332-52165 | 2/5, 1/2 | 13/32 | 1/2 | 4.63 | 1.63 |
| G47535-1010 | 10ACB-10HLE | 7332-52175 | 1/2 | 1/2 | 1/2 | 4.63 | 1.63 |
| G47535-1210 | 12ACB-10HLE | 7332-52405 | 1/2, 5/8 | 5/8 | 1/2 | 4.75 | 1.75 |
| G47535-1212 | 12ACB-12HLE | 7332-52185 | 5/8 | 5/8 | 5/8 | 4.75 | 1.75 |

# Hose Length Extender - Steel





| Part No. | Descr. | Prod. No. | ⊖ | A1 | A2 | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47535-0606S | 6ACB-6HLE-S | 7332-20335 | 5/16 | 5/16 | 5/16 | 4.00 | 1.50 |
| G47535-0608S | 6ACB-8HLE-S | 7332-20345 | 5/16 | 5/16 | 13/32 | 4.00 | 1.50 |
| G47535-0808S | 8ACB-8HLE-S | 7332-20355 | 13/32 | 13/32 | 13/32 | 4.00 | 1.50 |
| G47535-0810S | 8ACB-10HLE-S | 7332-20365 | 13/32 | 13/32 | 1/2 | 4.13 | 1.63 |
| G47535-1010S | 10ACB-10HLE-S | 7332-20375 | 1/2 | 1/2 | 1/2 | 4.13 | 1.63 |
| G47535-1210S | 12ACB-10HLE-S | 7332-20385 | 5/8 | 5/8 | 1/2 | 4.25 | 1.75 |
| G47535-1212S | 12ACB-12HLE-S | 7332-20395 | 5/8 | 5/8 | 5/8 | 4.25 | 1.75 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Hose Length Extender - 90° Bent Tube - Steel





| Part No. | Descr. | Prod. No. | ⊖ | A1 | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47537-0606S | 6ACB-6HLE90-S | 7332-20405 | 5/16 | 5/16 | 2.50 | 1.25 |
| G47537-0808S | 8ACB-8HLE90-S | 7332-52765 | 2/5 | 1/2 | 2.87 | 1.37 |
| G47537-1010S | 10ACB-10HLE90-S | 7332-20415 | 1/2 | 1/2 | 2.88 | 1.63 |
| G47537-1212S | 12ACB-12HLE90-S | 7332-20425 | 5/8 | 5/8 | 3.25 | 2.00 |

# Hose Length Extender with Sight Glass - Steel





| Part No. | Descr. | Prod. No. | ⊖ | L | C |
|---|---|---|---|---|---|
| | | | " | " | " |
| G47538-0606S | 6ACB-6HLESG-S | 7332-20435 | 5/16 | 4.12 | 1.62 |

# Hose Length Extender - Tee - Aluminum




| Part No. | Descr. | Prod. No. | ⟷ | A1 | A2 | T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " | " |
| G47539-0606 | 6ACB-6HLET | 7332-52305 | 1/3 | 5/16 | 5/16 | .94 | 4.75 | 1.75 |
| G47539-1010 | 10ACB-10HLET | 7332-52315 | 1/2 | 1/2 | 1/2 | 1.00 | 5.00 | 2.00 |
| G47539-1212 | 12ACB-12HLET | 7332-52325 | 5/8 | 5/8 | 5/8 | 1.12 | 5.25 | 2.25 |

# Hose Length Extender - Tee - Steel





| Part No. | Descr. | Prod. No. | ⟷ | A1 | A2 | T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " | " |
| G47539-0606S | 6ACB-6HLET-S | 7332-20445 | 5/16 | 5/16 | 5/16 | 1.13 | 4.75 | 2.25 |
| G47539-0808S | 8ACB-8HLET-S | 7332-20455 | 13/32 | 13/32 | 13/32 | 1.19 | 4.88 | 2.38 |
| G47539-1010S | 10ACB-10HLET-S | 7332-20465 | 1/2 | 1/2 | 1/2 | 1.25 | 5.00 | 2.50 |
| G47539-1212S | 12ACB-12HLET-S | 7332-20475 | 5/8 | 5/8 | 5/8 | 1.37 | 5.25 | 2.75 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female O-Ring with R134 Service Port - 45° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ≈ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47576-0808 | 8ACB-8FTON134SP45 | 7332-52745 | 2/5 | 3/4–16 | .63 | 3.76 | 2.26 |
| G47576-1010 | 10ACB-10FTON134SP45 | 7332-52775 | 1/2 | 7/8–14 | .88 | 4.13 | 2.63 |

## Female O-Ring with R134 Service Port - 45° Bent Tube - Steel





| Part No. | Descr. | Prod. No. | ⊖ | ≈ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47576-0606S | 6ACB-6FTON134SP45-S | 7332-52735 | 1/3 | 5/8–18 | .56 | 3.69 | 2.19 |
| G47576-0808S | 8ACB-8FTON134SP45-S | 7332-52695 | 2/5 | 3/4–16 | .63 | 3.76 | 2.26 |
| G47576-1010S | 10ACB-10FTON134SP45-S | 7332-52705 | 1/2 | 7/8–14 | .88 | 4.13 | 2.63 |
| G47576-1210S | 12ACB-10FTON134SP45-S | 7332-52715 | 5/8 | 7/8–14 | .94 | 4.32 | 2.62 |

## Female O-Ring with R12 Service Port - 45° Bent Tube - Steel




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G47577-0606S | 6ACB-6FTONR12SP45-S | 7332-52785 | 1/3 | 5/8–18 | | .56 | 3.69 | 2.19 |
| G47577-0808S | 8ACB-8FTONR12SP45-S | 7332-52795 | 2/5 | 3/4–16 | | .63 | 3.76 | 2.26 |
| G47577-1010S | 10ACB-10FTONR12SP45-S | 7332-52805 | 1/2 | 7/8–14 | | .88 | 4.13 | 2.63 |

## Male SAE Tube O-Ring Nut Swivel with R134a Service Port - Steel





| Part No. | Descr. | Prod. No. | ⊖ | ||| L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " |
| G47580-0606S | 6ACB-6MTON134SP-S | 7332-20485 | 5/16 | 5/8–18 | | 3.35 | 2.10 |
| G47580-1010S | 10ACB-10MTON134SP-S | 7332-20495 | 1/2 | 7/8–14 | | 3.59 | 2.34 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male SAE Tube O-Ring Nut Swivel with R134a Service Port - 90° Bent Tube - Steel





| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G47582-1010S | 10ACB-10MTON134SP90-S | 7332-20505 | 1/2 | 7/8–14 | | 1.50 | 3.85 | 2.60 |

## Male SAE Tube O-Ring Nut Swivel - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ||| L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " |
| G47583-0606 | 6ACB-6MTON | 7332-51585 | 1/3 | 5/8–18 | | 3.19 | 1.69 |
| G47583-0806 | 8ACB-6MTON | 7332-52415 | 2/5 | 5/8–18 | | 3.25 | 1.75 |
| G47583-0808 | 8ACB-8MTON | 7332-51595 | 2/5 | 3/4–18 | | 3.25 | 1.75 |
| G47583-1010 | 10ACB-10MTON | 7332-51605 | 1/2 | 7/8–18 | | 3.38 | 1.88 |
| G47583-1210 | 12ACB-10MTON | 7332-52425 | 5/8 | 7/8–18 | | 3.88 | 2.38 |
| G47583-1212 | 12ACB-12MTON | 7332-51615 | 5/8 | 1 1/16–16 | | 3.88 | 2.38 |

# Male SAE Tube O-Ring Nut Swivel - Steel




| Part No. | Descr. | Prod. No. | ⊖ | ||| L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " |
| G47583-0606S | 6ACB-6MTON-S | 7332-20515 | 5/16 | 5/8–18 | | 3.19 | 1.94 |
| G47583-0607S | 6ACB-7MTON-S | 7332-20525 | 5/16 | 11/16–16 | | 3.00 | 1.75 |
| G47583-0806S | 8ACB-6MTON-S | 7332-20535 | 13/32 | 5/8–18 | | 3.25 | 2.00 |
| G47583-0808S | 8ACB-8MTON-S | 7332-20545 | 13/32 | 3/4–16 | | 3.25 | 2.00 |
| G47583-1008S | 10ACB-8MTON-S | 7332-52815 | 1/2 | 3/4–18 | | 3.38 | 1.88 |
| G47583-1010S | 10ACB-10MTON-S | 7332-20555 | 1/2 | 7/8–14 | | 3.38 | 2.13 |
| G47583-1210S | 12ACB-10MTON-S | 7332-20565 | 5/8 | 7/8–14 | | 3.88 | 2.63 |
| G47583-1212S | 12ACB-12MTON-S | 7332-20575 | 5/8 | 1 1/16–14 | | 3.88 | 2.63 |

# Male SAE Tube O-Ring Nut - 45° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G47584-0606 | 6ACB-6MTON45 | 7332-51625 | 1/3 | 5/8–18 | | .88 | 3.19 | 1.69 |
| G47584-0808 | 8ACB-8MTON45 | 7332-51635 | 2/5 | 3/4–18 | | 1.00 | 3.44 | 1.94 |
| G47584-1010 | 10ACB-10MTON45 | 7332-51645 | 1/2 | 7/8–18 | | .88 | 3.63 | 2.13 |
| G47584-1212 | 12ACB-12MTON45 | 7332-51655 | 5/8 | 1 1/16–16 | | 1.19 | 4.19 | 2.69 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male SAE Tube O-Ring Nut - 45° Bent Tube - Steel





| Part No. | Descr. | Prod. No. | ⊖ | | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47584-0606S | 6ACB-6MTON45-S | 7332-20585 | 5/16 | 5/8–18 | .88 | 3.19 | 1.94 |
| G47584-0806S | 8ACB-6MTON45-S | 7332-20595 | 13/32 | 5/8–18 | 1.00 | 3.47 | 2.22 |
| G47584-0808S | 8ACB-8MTON45-S | 7332-20605 | 13/32 | 3/4–16 | 1.00 | 3.44 | 2.19 |
| G47584-1010S | 10ACB-10MTON45-S | 7332-20615 | 1/2 | 7/8–14 | 1.06 | 3.81 | 2.56 |
| G47584-1212S | 12ACB-12MTON45-S | 7332-20625 | 5/8 | 1 1/16–14 | 1.19 | 4.19 | 2.94 |

## Male SAE Tube O-Ring Nut - 90° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47585-0606 | 6ACB-6MTON90 | 7332-51665 | 1/3 | 5/8–18 | 1.63 | 2.56 | 1.06 |
| G47585-0806 | 8ACB-6MTON90 | 7332-52435 | 2/5 | 5/8–18 | 1.88 | 2.75 | 1.25 |
| G47585-0808 | 8ACB-8MTON90 | 7332-51675 | 2/5 | 3/4–18 | 1.88 | 2.75 | 1.25 |
| G47585-1010 | 10ACB-10MTON90 | 7332-51685 | 1/2 | 7/8–18 | 2.12 | 3.00 | 1.50 |
| G47585-1210 | 12ACB-10MTON90 | 7332-52445 | 5/8 | 7/8–18 | 2.25 | 3.25 | 1.75 |
| G47585-1212 | 12ACB-12MTON90 | 7332-51695 | 5/8 | 1 1/16–16 | 2.25 | 3.25 | 1.75 |

# Male SAE Tube O-Ring Nut - 90° Bent Tube - Steel




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G47585-0606S | 6ACB-6MTON90-S | 7332-20635 | 5/16 | 5/8–18 | | 1.63 | 2.56 | 1.31 |
| G47585-0607S | 6ACB-7MTON90-S | 7332-20645 | 5/16 | 11/16–16 | | 1.56 | 2.56 | 1.31 |
| G47585-0806S | 8ACB-6MTON90-S | 7332-20655 | 13/32 | 5/8–18 | | 1.88 | 2.75 | 1.50 |
| G47585-0808S | 8ACB-8MTON90-S | 7332-20665 | 13/32 | 3/4–16 | | 1.88 | 2.75 | 1.50 |
| G47585-1010S | 10ACB-10MTON90-S | 7332-20675 | 1/2 | 7/8–14 | | 2.12 | 3.00 | 1.75 |
| G47585-1210S | 12ACB-10MTON90-S | 7332-20685 | 5/8 | 7/8–14 | | 2.25 | 3.25 | 2.00 |
| G47585-1212S | 12ACB-12MTON90-S | 7332-20695 | 5/8 | 1 1/16–14 | | 2.25 | 3.25 | 2.00 |

# Female SAE Tube O-Ring Nut Swivel with R12 Service Port - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47586-0808 | 8ACB-8FTONR12SP | 7332-52235 | 2/5 | 3/4–16 | 3.38 | 1.88 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female SAE Tube O-Ring Nut Swivel with R12 Service Port - Steel





| Part No. | Descr. | Prod. No. | ⟷ | | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47586-0606S | 6ACB-6FTONR12SP-S | 7332-20705 | 5/16 | 5/8–18 | 3.38 | 2.13 |
| G47586-0808S | 8ACB-8FTONR12SP-S | 7332-20715 | 13/32 | 3/4–16 | 3.38 | 2.13 |
| G47586-1010S | 10ACB-10FTONR12SP-S | 7332-20725 | 1/2 | 7/8–14 | 3.62 | 2.37 |

## Female SAE Tube O-Ring Nut Swivel with R12 Service Port - 90° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⟷ | | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47587-0606 | 6ACB-6FTONR12SP90 | 7332-52245 | 1/3 | 5/8–18 | 1.12 | 3.62 | 2.12 |

# Female SAE Tube O-Ring Nut Swivel with R12 Service Port - 90° Bent Tube - Steel




| Part No. | Descr. | Prod. No. | ⊖ | ≋ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47587-0606S | 6ACB-6FTONR12SP90-S | 7332-20735 | 5/16 | 5/8–18 | 1.12 | 3.62 | 2.37 |
| G47587-0808S | 8ACB-8FTONR12SP90-S | 7332-20745 | 13/32 | 3/4–16 | 1.31 | 3.62 | 2.37 |
| G47587-1010S | 10ACB-10FTONR12SP90-S | 7332-20755 | 1/2 | 7/8–14 | 1.50 | 3.88 | 2.63 |
| G47587-1210S | 12ACB-10FTONR12SP90-S | 7332-20765 | 5/8 | 7/8–14 | 1.75 | 4.19 | 2.94 |

# Female SAE Tube O-Ring Nut Swivel with R134a Service Port - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ≋ | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47588-0606 | 6ACB-6FTON134SP | 7332-51705 | 1/3 | 5/8–18 | 3.38 | 1.88 |
| G47588-0808 | 8ACB-8FTON134SP | 7332-51715 | 2/5 | 3/4–16 | 3.38 | 1.88 |
| G47588-1010 | 10ACB-10FTON134SP | 7332-51725 | 1/2 | 7/8–14 | 3.62 | 2.12 |
| G47588-1210 | 12ACB-10FTON134SP | 7332-51735 | 5/8 | 7/8–14 | 3.75 | 2.25 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female SAE Tube O-Ring Nut Swivel with R134a Service Port - Steel





| Part No. | Descr. | Prod. No. | ⊖ | ≡ | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47588-0606S | 6ACB-6FTON134SP-S | 7332-20775 | 5/16 | 5/8–18 | 3.30 | 2.05 |
| G47588-0808S | 8ACB-8FTON134SP-S | 7332-20785 | 13/32 | 3/4–16 | 3.38 | 2.13 |
| G47588-1010S | 10ACB-10FTON134SP-S | 7332-20795 | 1/2 | 7/8–14 | 3.62 | 2.37 |
| G47588-1210S | 12ACB-10FTON134SP-S | 7332-20805 | 5/8 | 7/8–14 | 3.75 | 2.50 |
| G47588-1212S | 12ACB-12FTON134SP-S | 7332-52725 | 5/8 | 1 1/16–14 | 3.75 | 2.25 |

## Female SAE Tube O-Ring Nut Swivel with R134a Service Port - 90° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ≡ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47589-0606 | 6ACB-6FTON134SP90 | 7332-51745 | 1/3 | 5/8–18 | 1.12 | 3.62 | 2.12 |
| G47589-0808 | 8ACB-8FTON134SP90 | 7332-51755 | 2/5 | 3/4–16 | 1.31 | 3.62 | 2.12 |
| G47589-1010 | 10ACB-10FTON134SP90 | 7332-51765 | 1/2 | 7/8–14 | 1.50 | 3.88 | 2.38 |
| G47589-1210 | 12ACB-10FTON134SP90 | 7332-51775 | 5/8 | 7/8–14 | 1.75 | 4.19 | 2.69 |

# Female SAE Tube O-Ring Nut Swivel with R134a Service Port - 90° Bent Tube - Steel




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " | " |
| G47589-0606S | 6ACB-6FTON134SP90-S | 7332-20815 | 5/16 | 5/8–18 | 1.12 | 3.62 | 2.37 |
| G47589-0808S | 8ACB-8FTON134SP90-S | 7332-20825 | 13/32 | 3/4–16 | 1.31 | 3.62 | 2.37 |
| G47589-1010S | 10ACB-10FTON134SP90-S | 7332-20835 | 1/2 | 7/8–14 | 1.50 | 3.88 | 2.63 |
| G47589-1210S | 12ACB-10FTON134SP90-S | 7332-20845 | 5/8 | 7/8–14 | 1.75 | 4.19 | 2.94 |

# Female SAE Tube O-Ring Nut Swivel - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47590-0606 | 6ACB-6FTON | 7332-51785 | 1/3 | 5/8–18 | 2.88 | 1.38 |
| G47590-0608 | 6ACB-8FTON | 7332-51795 | 1/3 | 3/4–16 | 3.00 | 1.50 |
| G47590-0806 | 8ACB-6FTON | 7332-52465 | 2/5 | 5/8–18 | 3.00 | 1.50 |
| G47590-0808 | 8ACB-8FTON | 7332-51805 | 2/5 | 3/4–16 | 3.00 | 1.50 |
| G47590-1008 | 10ACB-8FTON | 7332-52195 | 1/2 | 3/4–16 | 3.19 | 1.69 |
| G47590-1010 | 10ACB-10FTON | 7332-51815 | 1/2 | 7/8–14 | 3.19 | 1.69 |
| G47590-1012 | 10ACB-12FTON | 7332-52205 | 1/2 | 1 1/16–14 | 3.31 | 1.81 |
| G47590-1210 | 12ACB-10FTON | 7332-51825 | 5/8 | 7/8–14 | 3.31 | 1.81 |
| G47590-1212 | 12ACB-12FTON | 7332-51835 | 5/8 | 1 1/16–14 | 3.31 | 1.81 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female SAE Tube O-Ring Nut Swivel - Steel





| Part No. | Descr. | Prod. No. | ⊖ | | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47590-0606S | 6ACB-6FTON-S | 7332-20855 | 5/16 | 5/8–18 | 2.88 | 1.63 |
| G47590-0608S | 6ACB-8FTON-S | 7332-20865 | 5/16 | 3/4–16 | 3.00 | 1.75 |
| G47590-0806S | 8ACB-6FTON-S | 7332-20875 | 13/32 | 5/8–18 | 3.00 | 1.75 |
| G47590-0808S | 8ACB-8FTON-S | 7332-20885 | 13/32 | 3/4–16 | 3.00 | 1.75 |
| G47590-1008S | 10ACB-8FTON-S | 7332-20895 | 1/2 | 3/4–16 | 3.19 | 1.94 |
| G47590-1010S | 10ACB-10FTON-S | 7332-20905 | 1/2 | 7/8–14 | 3.19 | 1.94 |
| G47590-1012S | 10ACB-12FTON-S | 7332-20915 | 1/2 | 1 1/16–14 | 3.31 | 2.06 |
| G47590-1210S | 12ACB-10FTON-S | 7332-20925 | 5/8 | 7/8–14 | 3.31 | 2.06 |
| G47590-1212S | 12ACB-12FTON-S | 7332-20935 | 5/8 | 1 1/16–14 | 3.31 | 2.06 |

## Female SAE Tube O-Ring Nut Swivel - 45° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47591-0606 | 6ACB-6FTON45 | 7332-51845 | 1/3 | 5/8–18 | .63 | 2.87 | 1.37 |
| G47591-0806 | 8ACB-6FTON45 | 7332-52475 | 2/5 | 5/8–18 | .63 | 3.07 | 1.57 |
| G47591-0808 | 8ACB-8FTON45 | 7332-51855 | 2/5 | 3/4–16 | .63 | 3.07 | 1.57 |
| G47591-1008 | 10ACB-8FTON45 | 7332-52485 | 1/2 | 3/4–16 | .88 | 3.63 | 2.13 |
| G47591-1010 | 10ACB-10FTON45 | 7332-51865 | 1/2 | 7/8–14 | .88 | 3.63 | 2.13 |
| G47591-1210 | 12ACB-10FTON45 | 7332-52495 | 5/8 | 7/8–14 | .94 | 3.94 | 2.44 |
| G47591-1212 | 12ACB-12FTON45 | 7332-51875 | 5/8 | 1 1/16–14 | .94 | 3.94 | 2.44 |

# Female SAE Tube O-Ring Nut Swivel - 45° Bent Tube - Steel




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G47591-0606S | 6ACB-6FTON45-S | 7332-20945 | 5/16 | 5/8–18 | | .56 | 2.87 | 1.52 |
| G47591-0806S | 8ACB-6FTON45-S | 7332-20955 | 13/32 | 5/8–18 | | .63 | 3.04 | 1.79 |
| G47591-0808S | 8ACB-8FTON45-S | 7332-20965 | 13/32 | 3/4–16 | | .63 | 3.07 | 1.82 |
| G47591-1008S | 10ACB-8FTON45-S | 7332-20975 | 1/2 | 3/4–16 | | .88 | 3.60 | 2.35 |
| G47591-1010S | 10ACB-10FTON45-S | 7332-20985 | 1/2 | 7/8–14 | | .88 | 3.63 | 2.38 |
| G47591-1210S | 12ACB-10FTON45-S | 7332-20995 | 5/8 | 7/8–14 | | .94 | 3.91 | 2.66 |
| G47591-1212S | 12ACB-12FTON45-S | 7332-21005 | 5/8 | 1 1/16–14 | | .94 | 3.94 | 2.69 |

# Female SAE Tube O-Ring Nut Swivel - 90° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | | " | " | " |
| G47592-0606 | 6ACB-6FTON90 | 7332-51885 | 1/3 | 5/8–18 | | 1.12 | 2.56 | 1.06 |
| G47592-0608 | 6ACB-8FTON90 | 7332-51895 | 1/3 | 3/4–16 | | 1.31 | 2.75 | 1.25 |
| G47592-0806 | 8ACB-6FTON90 | 7332-52455 | 2/5 | 5/8–18 | | 1.31 | 2.75 | 1.25 |
| G47592-0808 | 8ACB-8FTON90 | 7332-51905 | 2/5 | 3/4–16 | | 1.31 | 2.75 | 1.25 |
| G47592-1008 | 10ACB-8FTON90 | 7332-52215 | 1/2 | 3/4–16 | | 1.50 | 3.00 | 1.50 |
| G47592-1010 | 10ACB-10FTON90 | 7332-51915 | 1/2 | 7/8–14 | | 1.50 | 3.00 | 1.50 |
| G47592-1012 | 10ACB-12FTON90 | 7332-52225 | 1/2 | 1 1/16–14 | | 1.75 | 3.25 | 1.75 |
| G47592-1210 | 12ACB-10FTON90 | 7332-51925 | 5/8 | 7/8–14 | | 1.75 | 3.25 | 1.75 |
| G47592-1212 | 12ACB-12FTON90 | 7332-51935 | 5/8 | 1 1/16–14 | | 1.75 | 3.25 | 1.75 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female SAE Tube O-Ring Nut Swivel - 90° Bent Tube - Steel





| Part No. | Descr. | Prod. No. | ⊖ | ≋ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47592-0606S | 6ACB-6FTON90-S | 7332-21015 | 5/16 | 5/8–18 | 1.12 | 2.56 | 1.31 |
| G47592-0608S | 6ACB-8FTON90-S | 7332-21025 | 5/16 | 3/4–16 | 1.31 | 2.75 | 1.50 |
| G47592-0806S | 8ACB-6FTON90-S | 7332-21035 | 13/32 | 5/8–18 | 1.31 | 2.75 | 1.50 |
| G47592-0808S | 8ACB-8FTON90-S | 7332-21045 | 13/32 | 3/4–16 | 1.31 | 2.75 | 1.50 |
| G47592-1008S | 10ACB-8FTON90-S | 7332-21055 | 1/2 | 3/4–16 | 1.50 | 3.00 | 1.75 |
| G47592-1010S | 10ACB-10FTON90-S | 7332-21065 | 1/2 | 7/8–14 | 1.50 | 3.00 | 1.75 |
| G47592-1012S | 10ACB-12FTON90-S | 7332-21075 | 1/2 | 1 1/16–14 | 1.75 | 3.25 | 2.00 |
| G47592-1210S | 12ACB-10FTON90-S | 7332-21085 | 5/8 | 7/8–14 | 1.75 | 3.25 | 2.00 |
| G47592-1212S | 12ACB-12FTON90-S | 7332-21095 | 5/8 | 1 1/16–14 | 1.75 | 3.25 | 2.00 |

## Female SAE Tube O-Ring Metric Nut Swivel - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ≋ | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47593-0620 | 6ACB-20FTOMN | 7332-52505 | 1/3 | M18X1.5 | 2.94 | 1.44 |
| G47593-0820 | 8ACB-20FTOMN | 7332-52515 | 2/5 | M18X1.5 | 2.94 | 1.44 |
| G47593-1022 | 10ACB-22FTOMN | 7332-51945 | 1/2 | M18X1.5 | 3.19 | 1.69 |

## Female SAE Tube O-Ring Metric Nut Swivel - Steel





| Part No. | Descr. | Prod. No. | ⟷ | ≡ | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47593-0820S | 8ACB-20FTOMN-S | 7332-21105 | 13/32 | M20X1.5 | 2.94 | 1.69 |
| G47593-1227S | 12ACB-27FTOMN-S | 7332-21115 | 5/8 | M27X2.0 | 3.31 | 2.06 |

## Female SAE Tube O-Ring Metric Nut Swivel - 45° Bent Tube - Aluminum




| Part No. | Descr. | Prod. No. | ⟷ | ≡ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47594-0618 | 6ACB-18FTOMN45 | 7332-52525 | 1/3 | M18X1.5 | .69 | 3.56 | 2.06 |
| G47594-0620 | 6ACB-20FTOMN45 | 7332-52535 | 1/3 | M18X1.5 | .75 | 3.07 | 1.57 |
| G47594-0820 | 8ACB-20FTOMN45 | 7332-52545 | 2/5 | M18X1.5 | .75 | 3.75 | 2.25 |
| G47594-1227 | 12ACB-27FTOMN45 | 7332-52555 | 5/8 | M27X2.0 | 1.00 | 4.62 | 3.12 |

## Female SAE Tube O-Ring Metric Nut Swivel - 45° Bent Tube - Steel





| Part No. | Descr. | Prod. No. | ⟷ | ≡ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47594-0820S | 8ACB-20FTOMN45-S | 7332-21125 | 13/32 | M20X1.5 | .75 | 3.72 | 2.47 |
| G47594-1227S | 12ACB-27FTOMN45-S | 7332-21135 | 5/8 | M27X2.0 | 1.00 | 4.59 | 3.34 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female SAE Tube O-Ring Metric Nut Swivel - 90° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47595-0618 | 6ACB-18FTOMN90 | 7332-52565 | 1/3 | M18X1.5 | 1.12 | 2.75 | 1.25 |
| G47595-0820 | 8ACB-20FTOMN90 | 7332-52575 | 2/5 | M18X1.5 | 1.37 | 2.94 | 1.44 |
| G47595-1227 | 12ACB-27FTOMN90 | 7332-51955 | 5/8 | M27X2.0 | 1.75 | 3.38 | 1.88 |

## Female SAE Tube O-Ring Metric Nut Swivel - 90° Bent Tube - Steel





| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47595-0820S | 8ACB-20FTOMN90-S | 7332-21145 | 13/32 | M20X1.5 | 1.37 | 2.94 | 1.69 |
| G47595-1227S | 12ACB-27FTOMN90-S | 7332-21155 | 5/8 | M27X2.0 | 1.75 | 3.38 | 2.13 |

# Female SAE Tube O-Ring Nut Swivel - 90° Block - Steel





| Part No. | Descr. | Prod. No. | ⊖ | ≋ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47596-0808S | 8ACB-8FTON90BL-S | 7332-21165 | 13/32 | 3/4–16 | .71 | 2.44 | 1.19 |
| G47596-1010S | 10ACB-10FTON90BL-S | 7332-21175 | 1/2 | 7/8–14 | .71 | 2.50 | 1.25 |
| G47596-1210S | 12ACB-10FTON90BL-S | 7332-21185 | 5/8 | 7/8–14 | .71 | 2.62 | 1.37 |

# Male Inverted O-Ring - Aluminum




| Part No. | Descr. | Prod. No. | ⊖ | ≋ | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47597-0606 | 6ACB-6MIO | 7332-51965 | 1/3 | 5/8–18 | 2.94 | 1.44 |
| G47597-0808 | 8ACB-8MIO | 7332-51975 | 2/5 | 3/4–16 | 3.13 | 1.63 |
| G47597-1010 | 10ACB-10MIO | 7332-51985 | 1/2 | 7/8–14 | 3.62 | 2.12 |
| G47597-1212 | 12ACB-12MIO | 7332-51995 | 5/8 | 1 1/16–14 | 3.88 | 2.38 |

# Male Inverted O-Ring - Steel





| Part No. | Descr. | Prod. No. | ⊖ | ≋ | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47597-0606S | 6ACB-6MIO-S | 7332-21195 | 5/16 | 5/8–18 | 2.94 | 1.69 |
| G47597-0808S | 8ACB-8MIO-S | 7332-21205 | 13/32 | 3/4–18 | 3.13 | 1.88 |
| G47597-1010S | 10ACB-10MIO-S | 7332-21215 | 1/2 | 7/8–14 | 3.62 | 2.37 |
| G47597-1212S | 12ACB-12MIO-S | 7332-21225 | 5/8 | 1 1/16–14 | 3.88 | 2.63 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male Inverted O-Ring - 45° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47598-0606 | 6ACB-6MIO45 | 7332-52585 | 1/3 | 5/8–18 | .75 | 3.06 | 1.56 |
| G47598-0808 | 8ACB-8MIO45 | 7332-52595 | 2/5 | 3/4–16 | 1.00 | 3.44 | 1.94 |
| G47598-1010 | 10ACB-10MIO45 | 7332-52605 | 1/2 | 7/8–14 | 1.25 | 4.00 | 2.50 |

## Male Inverted O-Ring - 45° Bent Tube - Steel





| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47598-1010S | 10ACB-10MIO45-S | 7332-21235 | 1/2 | 7/8–14 | 1.25 | 3.97 | 2.72 |

## Male Inverted O-Ring - 90° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47599-0606 | 6ACB-6MIO90 | 7332-52005 | 1/3 | 5/8–18 | 1.50 | 2.56 | 1.06 |
| G47599-0808 | 8ACB-8MIO90 | 7332-52015 | 2/5 | 3/4–16 | 1.75 | 2.75 | 1.25 |
| G47599-1010 | 10ACB-10MIO90 | 7332-52025 | 1/2 | 7/8–16 | 2.00 | 3.00 | 1.50 |

# Male Inverted O-Ring - 90° Bent Tube - Steel





| Part No. | Descr. | Prod. No. | ⊖ | ≋ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47599-0606S | 6ACB-6MIO90-S | 7332-21245 | 5/16 | 5/8–18 | 1.50 | 2.56 | 1.31 |
| G47599-0808S | 8ACB-8MIO90-S | 7332-21255 | 13/32 | 3/4–18 | 1.75 | 2.75 | 1.50 |
| G47599-1010S | 10ACB-10MIO90-S | 7332-21265 | 1/2 | 7/8–14 | 2.00 | 3.00 | 1.75 |

# Male Inverted O-Ring Bulkhead - Steel




| Part No. | Descr. | Prod. No. | ⊖ | ≋ | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47600-0606S | 6ACB-6MIOBKHD-S | 7332-21275 | 5/16 | 5/8–18 | 4.00 | 2.75 |
| G47600-0808S | 8ACB-8MIOBKHD-S | 7332-21285 | 13/32 | 3/4–18 | 4.25 | 3.00 |
| G47600-1010S | 10ACB-10MIOBKHD-S | 7332-21295 | 1/2 | 7/8–14 | 4.44 | 3.19 |

# Male Inverted O-Ring Bulkhead - 90° Bent Tube - Steel





| Part No. | Descr. | Prod. No. | ⊖ | ≋ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47602-0606S | 6ACB-6MIOBKHD90-S | 7332-21305 | 5/16 | 5/8–18 | 2.12 | 3.13 | 1.88 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male Inverted O-Ring Bulkhead - 90° Bent Tube - Steel - Continued


| Part No. | Descr. | Prod. No. | ⟷ | ≡ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47602-0808S | 8ACB-8MIOBKHD90-S | 7332-21315 | 13/32 | 3/4–18 | 2.44 | 3.25 | 2.00 |
| G47602-1010S | 10ACB-10MIOBKHD90-S | 7332-21325 | 1/2 | 7/8–14 | 2.50 | 3.50 | 2.25 |

## Female SAE Tube O-Ring Nut - 180° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⟷ | ≡ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47610-0606 | 6ACB-6FTON180 | 7332-52615 | 1/3 | 5/8–18 | 1.65 | 1.00 | 2.15 |
| G47610-0808 | 8ACB-8FTON180 | 7332-52625 | 2/5 | 3/4–16 | 1.75 | 1.00 | 2.25 |
| G47610-1212 | 12ACB-12FTON180 | 7332-52635 | 5/8 | 1 1/16–14 | 2.12 | 1.50 | 2.94 |

## Female SAE Tube O-Ring Nut - 180° Bent Tube - Steel





| Part No. | Descr. | Prod. No. | ⟷ | ≡ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47610-0606S | 6ACB-6FTON180-S | 7332-21335 | 5/16 | 5/8–18 | 1.63 | 3.50 | 2.25 |
| G47610-1010S | 10ACB-10FTON180-S | 7332-52755 | 5/8 | 7/8–14 | 3.00 | 4.00 | 2.50 |

## Universal Tee O-Ring Splicer English Threads - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47614-1010 | 10ACB-10TORSP | 7332-52645 | 1/2 | 7/8–14 | 3.33 | 2.75 | 1.25 |

## Male (Ford) Spring Lock - 45° Bent Tube - Aluminum




| Part No. | Descr. | Prod. No. | ⊖ | T | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47949-0606 | 6ACB-6MSL45 | 7332-52655 | 1/3 | 1.25 | 4.00 | 2.50 |
| G47949-0808 | 8ACB-8MSL45 | 7332-52665 | 2/5 | 1.31 | 4.12 | 2.62 |
| G47949-1010 | 10ACB-10MSL45 | 7332-52675 | 1/2 | 1.63 | 4.51 | 3.01 |
| G47949-1212 | 12ACB-12MSL45 | 7332-52685 | 5/8 | 1.75 | 4.75 | 3.25 |

## Male (Ford) Spring Lock - Aluminum




| Part No. | Descr. | Prod. No. | ⊖ | L | C |
|---|---|---|---|---|---|
| | | | " | " | " |
| G47950-0606 | 6ACB-6MSL | 7332-52035 | 1/3 | 3.81 | 2.31 |
| G47950-0808 | 8ACB-8MSL | 7332-52045 | 2/5 | 3.88 | 2.38 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male (Ford) Spring Lock - Aluminum - Continued


| Part No. | Descr. | Prod. No. | ⊖ | L | C |
|---|---|---|---|---|---|
| | | | " | " | " |
| G47950-1010 | 10ACB-10MSL | 7332-52055 | 1/2 | 4.00 | 2.50 |

## Male (Ford) Spring Lock - 90° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | T | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47951-0608 | 6ACB-8MSL90 | 7332-52275 | 1/3 | 2.38 | 3.31 | 1.81 |
| G47951-0808 | 8ACB-8MSL90 | 7332-52255 | 2/5 | 2.38 | 2.94 | 1.44 |
| G47951-1010 | 10ACB-10MSL90 | 7332-52265 | 1/2 | 2.50 | 3.13 | 1.63 |

## Female (Ford) Spring Lock - 90° Bent Tube - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | T | L | C |
|---|---|---|---|---|---|---|
| | | | " | " | " | " |
| G47953-0606 | 6ACB-6FSL90 | 7332-52285 | 1/3 | 2.19 | 2.88 | 1.38 |
| G47953-1010 | 10ACB-10FSL90 | 7332-52295 | 1/2 | 2.50 | 3.13 | 1.63 |

## Hose Splicer with R12 Thread Service Port - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | L | C |
|---|---|---|---|---|---|
| | | | " | " | " |
| G47954-0606 | 6ACB-R12SP | 7332-52065 | 1/3 | 4.50 | 1.50 |
| G47954-1010 | 10ACB-R12SP | 7332-52075 | 1/2 | 4.63 | 1.63 |
| G47954-1212 | 12ACB-R12SP | 7332-52085 | 5/8 | 4.75 | 1.75 |

## Hose Splicer with R12 Thread Service Port - Steel




| Part No. | Descr. | Prod. No. | ⊖ | L | C |
|---|---|---|---|---|---|
| | | | " | " | " |
| G47954-0606S | 6ACB-R12SP-S | 7332-21345 | 5/16 | 4.50 | 2.00 |
| G47954-0808S | 8ACB-R12SP-S | 7332-21355 | 13/32 | 4.50 | 2.00 |
| G47954-1010S | 10ACB-R12SP-S | 7332-21365 | 1/2 | 4.63 | 2.13 |

## Hose Splicer with R134a Service Port - Aluminum





| Part No. | Descr. | Prod. No. | ⊖ | L | C |
|---|---|---|---|---|---|
| | | | " | " | " |
| G47956-0606 | 6ACB-R134SP | 7332-52095 | 1/3 | 4.50 | 1.50 |
| G47956-0808 | 8ACB-R134SP | 7332-52105 | 2/5 | 4.50 | 1.50 |
| G47956-1010 | 10ACB-R134SP | 7332-52115 | 1/2 | 4.63 | 1.63 |
| G47956-1212 | 12ACB-R134SP | 7332-52125 | 5/8 | 4.75 | 1.75 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Hose Splicer with R134a Service Port - Steel





| Part No. | Descr. | Prod. No. | ⊖ | L | C |
|---|---|---|---|---|---|
| | | | " | " | " |
| G47956-0606S | 6ACB-R134SP-S | 7332-21375 | 5/16 | 4.50 | 2.00 |
| G47956-0808S | 8ACB-R134SP-S | 7332-21385 | 13/32 | 4.50 | 2.00 |
| G47956-1010S | 10ACB-R134SP-S | 7332-21395 | 1/2 | 4.63 | 2.13 |
| G47956-1212S | 12ACB-R134SP-S | 7332-21405 | 5/8 | 4.75 | 2.25 |

## Compressor Female SAE Tube O-Ring Nut Swivel - 90° Bent Tube - Steel




| Part No. | Descr. | Prod. No. | ⊖ | ||| T | L | C |
|---|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " | |
| G47958-0606S | 6ACB-6CFTON90-S | 7332-21415 | 5/16 | 1–14 | .84 | .94 | 2.44 |
| G47958-1010S | 10ACB-10CFTON90-S | 7332-21425 | 1/2 | 1–14 | .84 | .94 | 2.63 |

# Compressor Female Tube O-Ring Nut with 134a Service Port - 90° Block - Steel





| Part No. | Descr. | Prod. No. | ⟷ | ≀≀≀ | T | L | C |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | " |
| G47960-0810S | 8ACB-10CFTON134SP90BL-S | 7332-21435 | 13/32 | 1–14 | .78 | 2.45 | 1.20 |
| G47960-1010S | 10ACB-10CFTON134SP90BL-S | 7332-21445 | 1/2 | 1–14 | .78 | 2.51 | 1.26 |
| G47960-1210S | 12ACB-10CFTON134SP90BL-S | 7332-21455 | 5/8 | 1–14 | .78 | 2.67 | 1.42 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# SAE Male Flareless (includes Sleeve and Nut)




| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | " | mm | " | mm | " |
| G50510-0604 | 6PS-4MFA | 7334-28615 | 3/8 | 9.7 | 7/16–20 | 11/16 | 9/16 | 2.37 | 60.2 | 1.00 | 25.4 | 1/4 |
| G50510-0605 | 6PS-5MFA | 7334-28625 | 3/8 | 9.7 | 1/2–20 | 11/16 | 5/8 | 2.37 | 60.2 | 1.00 | 25.4 | 5/16 |
| G50510-0606 | 6PS-6MFA | 7334-28635 | 3/8 | 9.7 | 5/8–18 | 11/16 | 11/16 | 2.39 | 60.7 | 1.01 | 25.7 | 3/8 |

# SAE Metric Male Flareless (includes Sleeve and Nut)




| Part No. | Descr. | Prod. No. | ⊖ | | | H1 | H2 | L | | C | | A1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | " | mm | " | mm | mm |
| G50510-0608 | 6PSM-8MFA | 7334-28935 | 3/8 | 9.7 | 3/4–16 | 11/16 | 11/16 | 2.31 | 58.7 | .93 | 23.6 | 8.0 |
| G50510-0610 | 6PSM-10MFA | 7334-28945 | 3/8 | 9.7 | 7/8–14 | 11/16 | 3/4 | 2.35 | 59.7 | .97 | 24.6 | 10.0 |
| G50510-0612 | 6PSM-12MFA | 7334-28955 | 3/8 | 9.7 | 1 1/16–12 | 3/4 | 7/8 | 2.35 | 59.7 | .97 | 24.6 | 12.0 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## NOTES

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Pipe NPTF Plug

For use up to SAE 100R2 maximum working pressure.








| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| | | | " |
| G60102-0002 | 2MP-PLUG | 7259-22815 | 1/8–27 |
| G60102-0004 | 4MP-PLUG | 7259-22825 | 1/4–18 |
| G60102-0006 | 6MP-PLUG | 7259-22835 | 3/8–18 |
| G60102-0008 | 8MP-PLUG | 7259-22845 | 1/2–14 |
| G60102-0012 | 12MP-PLUG | 7259-22855 | 3/4–14 |
| G60102-0016 | 16MP-PLUG | 7259-22865 | 1–11 1/2 |
| G60102-0020 | 20MP-PLUG | 7259-22875 | 1 1/4–11 1/2 |
| G60102-0024 | 24MP-PLUG | 7259-24395 | 1 1/2–11 1/2 |
| G60102-0032 | 32MP-PLUG | 7259-32765 | 2–11 1/2 |

# Male Pipe NPTF to Male Pipe NPTF

For use up to SAE 100R2 maximum working pressure.






| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60110-0202 | 2MP-2MP | 7259-23695 | 1/8–27 | 1/8–27 |
| G60110-0402 | 4MP-2MP | 7259-23705 | 1/4–18 | 1/8–27 |
| G60110-0404 | 4MP-4MP | 7259-23715 | 1/4–18 | 1/4–18 |
| G60110-0602 | 6MP-2MP | 7259-06455 | 3/8–18 | 1/8–27 |
| G60110-0604 | 6MP-4MP | 7259-23725 | 3/8–18 | 1/4–18 |
| G60110-0606 | 6MP-6MP | 7259-23735 | 3/8–18 | 3/8–18 |
| G60110-0804 | 8MP-4MP | 7259-23745 | 1/2–14 | 1/4–18 |
| G60110-0806 | 8MP-6MP | 7259-23755 | 1/2–14 | 3/8–18 |
| G60110-0808 | 8MP-8MP | 7259-23765 | 1/2–14 | 1/2–14 |
| G60110-1204 | 12MP-4MP | 7259-07405 | 3/4–14 | 1/4–18 |
| G60110-1206 | 12MP-6MP | 7259-06395 | 3/4–14 | 3/8–18 |
| G60110-1208 | 12MP-8MP | 7259-23775 | 3/4–14 | 1/2–14 |
| G60110-1212 | 12MP-12MP | 7259-23785 | 3/4–14 | 3/4–14 |
| G60110-1606 | 16MP-6MP | 7259-07325 | 1–11 1/2 | 3/8–18 |
| G60110-1608 | 16MP-8MP | 7259-06235 | 1–11 1/2 | 1/2–14 |
| G60110-1612 | 16MP-12MP | 7259-23795 | 1–11 1/2 | 3/4–14 |
| G60110-1616 | 16MP-16MP | 7259-23805 | 1–11 1/2 | 1–11 1/2 |
| G60110-2012 | 20MP-12MP | 7259-08015 | 1 1/4–11 1/2 | 3/4–14 |
| G60110-2016 | 20MP-16MP | 7259-05875 | 1 1/4–11 1/2 | 1–11 1/2 |
| G60110-2020 | 20MP-20MP | 7259-23815 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |
| G60110-2412 | 24MP-12MP | 7259-08545 | 1 1/2–11 1/2 | 3/4–14 |
| G60110-2416 | 24MP-16MP | 7259-08025 | 1 1/2–11 1/2 | 1–11 1/2 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male Pipe NPTF to Male Pipe NPTF - Continued

| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60110-2420 | 24MP-20MP | 7259-08125 | 1 1/2–11 1/2 | 1 1/4–11 1/2 |
| G60110-2424 | 24MP-24MP | 7259-23825 | 1 1/2–11 1/2 | 1 1/2–11 1/2 |
| G60110-3224 | 32MP-24MP | 7259-08555 | 2–11 1/2 | 1 1/2–11 1/2 |
| G60110-3232 | 32MP-32MP | 7259-23835 | 2–11 1/2 | 2–11 1/2 |

## Male Pipe NPTF to Male Pipe NPTF - 90°

For use up to SAE 100R2 maximum working pressure.









| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60115-0202 | 2MP-2MP90 | 7259-25205 | 1/8–27 | 1/8–27 |
| G60115-0404 | 4MP-4MP90 | 7259-25215 | 1/4–18 | 1/4–18 |
| G60115-0604 | 6MP-4MP90 | 7259-70755 | 3/8–18 | 1/4–18 |
| G60115-0606 | 6MP-6MP90 | 7259-25225 | 3/8–18 | 3/8–18 |
| G60115-0804 | 8MP-4MP90 | 7259-08565 | 1/2–14 | 1/4–18 |
| G60115-0806 | 8MP-6MP90 | 7259-70855 | 1/2–14 | 3/8–18 |
| G60115-0808 | 8MP-8MP90 | 7259-25235 | 1/2–14 | 1/2–14 |
| G60115-1208 | 12MP-8MP90 | 7259-05725 | 3/4–14 | 1/2–14 |
| G60115-1212 | 12MP-12MP90 | 7259-25245 | 3/4–14 | 3/4–14 |
| G60115-1612 | 16MP-12MP90 | 7259-09835 | 1–11 1/2 | 3/4–14 |
| G60115-1616 | 16MP-16MP90 | 7259-25255 | 1–11 1/2 | 1–11 1/2 |
| G60115-2020 | 20MP-20MP90 | 7259-08575 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |
| G60115-2424 | 24MP-24MP90 | 7259-07155 | 1 1/2–11 1/2 | 1 1/2–11 1/2 |

## Male Pipe NPTF to Female Pipe NPTF Reducer Bushing - Short

For use up to SAE 100R2 maximum working pressure.







| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60130-0402 | 4MP-2FPS | 7259-22595 | 1/4–18 | 1/8–27 |
| G60130-0602 | 6MP-2FPS | 7259-22605 | 3/8–18 | 1/8–27 |
| G60130-0604 | 6MP-4FPS | 7259-22615 | 3/8–18 | 1/4–18 |
| G60130-0802 | 8MP-2FPS | 7259-05815 | 1/2–14 | 1/8–27 |


## Male Pipe NPTF to Female Pipe NPTF Reducer Bushing - Short - Continued


| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60130-0804 | 8MP-4FPS | 7259-22635 | 1/2–14 | 1/4–18 |
| G60130-0806 | 8MP-6FPS | 7259-22645 | 1/2–14 | 3/8–18 |
| G60130-1202 | 12MP-2FPS | 7259-07335 | 3/4–14 | 1/8–27 |
| G60130-1204 | 12MP-4FPS | 7259-22665 | 3/4–14 | 1/4–18 |
| G60130-1206 | 12MP-6FPS | 7259-22675 | 3/4–14 | 3/8–18 |
| G60130-1208 | 12MP-8FPS | 7259-22685 | 3/4–14 | 1/2–14 |
| G60130-1602 | 16MP-2FPS | 7259-08585 | 1–11 1/2 | 1/8–27 |
| G60130-1604 | 16MP-4FPS | 7259-05355 | 1–11 1/2 | 1/4–18 |
| G60130-1606 | 16MP-6FPS | 7259-06665 | 1–11 1/2 | 3/8–18 |
| G60130-1608 | 16MP-8FPS | 7259-22725 | 1–11 1/2 | 1/2–14 |
| G60130-1612 | 16MP-12FPS | 7259-22735 | 1–11 1/2 | 3/4–14 |
| G60130-2004 | 20MP-4FPS | 7259-07475 | 1 1/4–11 1/2 | 1/4–18 |
| G60130-2008 | 20MP-8FPS | 7259-05525 | 1 1/4–11 1/2 | 1/2–14 |
| G60130-2012 | 20MP-12FPS | 7259-22755 | 1 1/4–11 1/2 | 3/4–14 |
| G60130-2016 | 20MP-16FPS | 7259-22765 | 1 1/4–11 1/2 | 1–11 1/2 |
| G60130-2412 | 24MP-12FPS | 7259-22785 | 1 1/2–11 1/2 | 3/4–14 |
| G60130-2416 | 24MP-16FPS | 7259-22795 | 1 1/2–11 1/2 | 1–11 1/2 |
| G60130-2420 | 24MP-20FPS | 7259-22805 | 1 1/2–11 1/2 | 1 1/4–11 1/2 |
| G60130-3220 | 32MP-20FPS | 7259-05425 | 2–11 1/2 | 1 1/4–11 1/2 |
| G60130-3224 | 32MP-24FPS | 7259-32825 | 2–11 1/2 | 1 1/2–11 1/2 |

## Male Pipe NPTF to Female Pipe NPTF Increasing Bushing - Long

For use up to SAE 100R2 maximum working pressure.







| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60132-0204 | 2MP-4FPL | 7259-25365 | 1/8–27 | 1/4–18 |
| G60132-0206 | 2MP-6FPL | 7259-08365 | 1/8–27 | 3/8–18 |
| G60132-0402 | 4MP-2FPL | 7259-08615 | 1/4–18 | 1/8–27 |
| G60132-0404 | 4MP-4FPL | 7259-00475 | 1/4–18 | 1/4–18 |
| G60132-0406 | 4MP-6FPL | 7259-25385 | 1/4–18 | 3/8–18 |
| G60132-0408 | 4MP-8FPL | 7259-05515 | 1/4–18 | 1/2–14 |
| G60132-0604 | 6MP-4FPL | 7259-05025 | 3/8–18 | 1/4–18 |
| G60132-0606 | 6MP-6FPL | 7259-00535 | 3/8–18 | 3/8–18 |
| G60132-0608 | 6MP-8FPL | 7259-25415 | 3/8–18 | 1/2–14 |
| G60132-0808 | 8MP-8FPL | 7259-05175 | 1/2–14 | 1/2–14 |
| G60132-0812 | 8MP-12FPL | 7259-25435 | 1/2–14 | 3/4–14 |
| G60132-0816 | 8MP-16FPL | 7259-07755 | 1/2–14 | 1–11 1/2 |
| G60132-1208 | 12MP-8FPL | 7259-00315 | 3/4–14 | 1/2–14 |
| G60132-1212 | 12MP-12FPL | 7259-06545 | 3/4–14 | 3/4–14 |
| G60132-1216 | 12MP-16FPL | 7259-25455 | 3/4–14 | 1–11 1/2 |
| G60132-1612 | 16MP-12FPL | 7259-05735 | 1–11 1/2 | 3/4–14 |
| G60132-1616 | 16MP-16FPL | 7259-08635 | 1–11 1/2 | 1–11 1/2 |
| G60132-1620 | 16MP-20FPL | 7259-25475 | 1–11 1/2 | 1 1/4–11 1/2 |
| G60132-1624 | 16MP-24FPL | 7259-08645 | 1–11 1/2 | 1 1/2–11 1/2 |
| G60132-2020 | 20MP-20FPL | 7259-07345 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |


## Male Pipe NPTF to Female Pipe NPTF Increasing Bushing - Long - Continued


| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60132-2024 | 20MP-24FPL | 7259-25495 | 1 1/4–11 1/2 | 1 1/2–11 1/2 |
| G60132-2432 | 24MP-32FPL | 7259-07765 | 1 1/2–11 1/2 | 2–11 1/2 |

## Female Pipe NPTF to Male Pipe NPTF - 45°

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60134-0606 | 6FP-6MP45 | 7259-50465 | 3/8–18 | 3/8–18 |
| G60134-0808 | 8FP-8MP45 | 7259-50475 | 1/2–14 | 1/2–14 |

## Male Pipe NPTF to Female Pipe NPTF - 90°

For use up to SAE 100R2 maximum working pressure.







| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60136-0202 | 2MP-2FP90 | 7259-24105 | 1/8–27 | 1/8–27 |
| G60136-0204 | 2MP-4FP90 | 7259-32835 | 1/8–27 | 1/4–18 |
| G60136-0402 | 4MP-2FP90 | 7259-32845 | 1/4–18 | 1/8–27 |
| G60136-0404 | 4MP-4FP90 | 7259-24115 | 1/4–18 | 1/4–18 |
| G60136-0406 | 4MP-6FP90 | 7259-32855 | 1/4–18 | 3/8–18 |
| G60136-0604 | 6MP-4FP90 | 7259-32865 | 3/8–18 | 1/4–18 |
| G60136-0606 | 6MP-6FP90 | 7259-24125 | 3/8–18 | 3/8–18 |
| G60136-0608 | 6MP-8FP90 | 7259-32875 | 3/8–18 | 1/2–14 |
| G60136-0804 | 8MP-4FP90 | 7259-08655 | 1/2–14 | 1/4–18 |
| G60136-0806 | 8MP-6FP90 | 7259-32885 | 1/2–14 | 3/8–18 |
| G60136-0808 | 8MP-8FP90 | 7259-24135 | 1/2–14 | 1/2–14 |
| G60136-0812 | 8MP-12FP90 | 7259-32895 | 1/2–14 | 3/4–14 |
| G60136-1208 | 12MP-8FP90 | 7259-32905 | 3/4–14 | 1/2–14 |


## Male Pipe NPTF to Female Pipe NPTF - 90° - Continued


| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60136-1212 | 12MP-12FP90 | 7259-24145 | 3/4–14 | 3/4–14 |
| G60136-1216 | 12MP-16FP90 | 7259-08375 | 3/4–14 | 1–11 1/2 |
| G60136-1612 | 16MP-12FP90 | 7259-08155 | 1–11 1/2 | 3/4–14 |
| G60136-1616 | 16MP-16FP90 | 7259-24155 | 1–11 1/2 | 1–11 1/2 |
| G60136-2016 | 20MP-16FP90 | 7259-08665 | 1 1/4–11 1/2 | 1–11 1/2 |
| G60136-2020 | 20MP-20FP90 | 7259-24165 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |
| G60136-2424 | 24MP-24FP90 | 7259-24175 | 1 1/2–11 1/2 | 1 1/2–11 1/2 |
| G60136-3232 | 32MP-32FP90 | 7259-24185 | 2–11 1/2 | 2–11 1/2 |

## Male Pipe NPTF to Female Pipe Swivel NPSM

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60140-0202 | 2MP-2FPX | 7259-00735 | 1/8–27 | 1/8–27 |
| G60140-0204 | 2MP-4FPX | 7259-10635 | 1/8–27 | 1/4–18 |
| G60140-0402 | 4MP-2FPX | 7259-05095 | 1/4–18 | 1/8–27 |
| G60140-0404 | 4MP-4FPX | 7259-00775 | 1/4–18 | 1/4–18 |
| G60140-0406 | 4MP-6FPX | 7259-10455 | 1/4–18 | 3/8–18 |
| G60140-0408 | 4MP-8FPX | 7259-07355 | 1/4–18 | 1/2–14 |
| G60140-0604 | 6MP-4FPX | 7259-10625 | 3/8–18 | 1/4–18 |
| G60140-0606 | 6MP-6FPX | 7259-00815 | 3/8–18 | 3/8–18 |
| G60140-0608 | 6MP-8FPX | 7259-10375 | 3/8–18 | 1/2–14 |
| G60140-0806 | 8MP-6FPX | 7259-10365 | 1/2–14 | 3/8–18 |
| G60140-0808 | 8MP-8FPX | 7259-00895 | 1/2–14 | 1/2–14 |
| G60140-0812 | 8MP-12FPX | 7259-10865 | 1/2–14 | 3/4–14 |
| G60140-1206 | 12MP-6FPX | 7259-06345 | 3/4–14 | 3/8–18 |
| G60140-1208 | 12MP-8FPX | 7259-10645 | 3/4–14 | 1/2–14 |
| G60140-1212 | 12MP-12FPX | 7259-00255 | 3/4–14 | 3/4–14 |
| G60140-1216 | 12MP-16FPX | 7259-32935 | 3/4–14 | 1–11 1/2 |
| G60140-1220 | 12MP-20FPX | 7259-08675 | 3/4–14 | 1 1/4–11 1/2 |
| G60140-1612 | 16MP-12FPX | 7259-10935 | 1–11 1/2 | 3/4–14 |
| G60140-1616 | 16MP-16FPX | 7259-00275 | 1–11 1/2 | 1–11 1/2 |
| G60140-1620 | 16MP-20FPX | 7259-11285 | 1–11 1/2 | 1 1/4–11 1/2 |
| G60140-2016 | 20MP-16FPX | 7259-05595 | 1 1/4–11 1/2 | 1–11 1/2 |
| G60140-2020 | 20MP-20FPX | 7259-10745 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |
| G60140-2024 | 20MP-24FPX | 7259-06375 | 1 1/4–11 1/2 | 1 1/2–11 1/2 |
| G60140-2420 | 24MP-20FPX | 7259-06305 | 1 1/2–11 1/2 | 1 1/4–11 1/2 |
| G60140-2424 | 24MP-24FPX | 7259-11345 | 1 1/2–11 1/2 | 1 1/2–11 1/2 |
| G60140-3232 | 32MP-32FPX | 7259-11435 | 2–11 1/2 | 2–11 1/2 |

# Male Pipe NPTF to Female Pipe Swivel NPSM - 45°

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60142-0202 | 2MP-2FPX45 | 7259-32945 | 1/8–27 | 1/8–27 |
| G60142-0204 | 2MP-4FPX45 | 7259-00505 | 1/8–27 | 1/4–18 |
| G60142-0402 | 4MP-2FPX45 | 7259-05985 | 1/4–18 | 1/8–27 |
| G60142-0404 | 4MP-4FPX45 | 7259-02115 | 1/4–18 | 1/4–18 |
| G60142-0406 | 4MP-6FPX45 | 7259-05265 | 1/4–18 | 3/8–18 |
| G60142-0604 | 6MP-4FPX45 | 7259-05555 | 3/8–18 | 1/4–18 |
| G60142-0606 | 6MP-6FPX45 | 7259-02155 | 3/8–18 | 3/8–18 |
| G60142-0608 | 6MP-8FPX45 | 7259-32955 | 3/8–18 | 1/2–14 |
| G60142-0804 | 8MP-4FPX45 | 7259-06465 | 1/2–14 | 1/4–18 |
| G60142-0806 | 8MP-6FPX45 | 7259-32965 | 1/2–14 | 3/8–18 |
| G60142-0808 | 8MP-8FPX45 | 7259-02125 | 1/2–14 | 1/2–14 |
| G60142-0812 | 8MP-12FPX45 | 7259-06115 | 1/2–14 | 3/4–14 |
| G60142-1208 | 12MP-8FPX45 | 7259-11535 | 3/4–14 | 1/2–14 |
| G60142-1212 | 12MP-12FPX45 | 7259-02235 | 3/4–14 | 3/4–14 |
| G60142-1216 | 12MP-16FPX45 | 7259-06125 | 3/4–14 | 1–11 1/2 |
| G60142-1612 | 16MP-12FPX45 | 7259-11625 | 1–11 1/2 | 3/4–14 |
| G60142-1616 | 16MP-16FPX45 | 7259-10765 | 1–11 1/2 | 1–11 1/2 |
| G60142-1620 | 16MP-20FPX45 | 7259-07855 | 1–11 1/2 | 1 1/4–11 1/2 |
| G60142-2016 | 20MP-16FPX45 | 7259-06685 | 1 1/4–11 1/2 | 1–11 1/2 |
| G60142-2020 | 20MP-20FPX45 | 7259-11355 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |
| G60142-2424 | 24MP-24FPX45 | 7259-11745 | 1 1/2–11 1/2 | 1 1/2–11 1/2 |
| G60142-3232 | 32MP-32FPX45 | 7259-32975 | 2–11 1/2 | 2–11 1/2 |

# Male Pipe NPTF to Female Pipe Swivel NPSM - 90°

For use up to SAE 100R2 maximum working pressure.







| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60144-0202 | 2MP-2FPX90 | 7259-08305 | 1/8–27 | 1/8–27 |
| G60144-0204 | 2MP-4FPX90 | 7259-00415 | 1/8–27 | 1/4–18 |
| G60144-0402 | 4MP-2FPX90 | 7259-05565 | 1/4–18 | 1/8–27 |
| G60144-0404 | 4MP-4FPX90 | 7259-02135 | 1/4–18 | 1/4–18 |
| G60144-0406 | 4MP-6FPX90 | 7259-10705 | 1/4–18 | 3/8–18 |


## Male Pipe NPTF to Female Pipe Swivel NPSM - 90° - Continued

| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60144-0408 | 4MP-8FPX90 | 7259-08685 | 1/4–18 | 1/2–14 |
| G60144-0604 | 6MP-4FPX90 | 7259-10525 | 3/8–18 | 1/4–18 |
| G60144-0606 | 6MP-6FPX90 | 7259-02165 | 3/8–18 | 3/8–18 |
| G60144-0608 | 6MP-8FPX90 | 7259-10325 | 3/8–18 | 1/2–14 |
| G60144-0804 | 8MP-4FPX90 | 7259-11175 | 1/2–14 | 1/4–18 |
| G60144-0806 | 8MP-6FPX90 | 7259-10265 | 1/2–14 | 3/8–18 |
| G60144-0808 | 8MP-8FPX90 | 7259-02205 | 1/2–14 | 1/2–14 |
| G60144-0812 | 8MP-12FPX90 | 7259-11075 | 1/2–14 | 3/4–14 |
| G60144-1206 | 12MP-6FPX90 | 7259-06045 | 3/4–14 | 3/8–18 |
| G60144-1208 | 12MP-8FPX90 | 7259-02245 | 3/4–14 | 1/2–14 |
| G60144-1212 | 12MP-12FPX90 | 7259-02265 | 3/4–14 | 3/4–14 |
| G60144-1216 | 12MP-16FPX90 | 7259-05195 | 3/4–14 | 1–11 1/2 |
| G60144-1220 | 12MP-20FPX90 | 7259-08705 | 3/4–14 | 1 1/4–11 1/2 |
| G60144-1608 | 16MP-8FPX90 | 7259-06775 | 1–11 1/2 | 1/2–14 |
| G60144-1612 | 16MP-12FPX90 | 7259-11275 | 1–11 1/2 | 3/4–14 |
| G60144-1616 | 16MP-16FPX90 | 7259-10335 | 1–11 1/2 | 1–11 1/2 |
| G60144-1620 | 16MP-20FPX90 | 7259-11475 | 1–11 1/2 | 1 1/4–11 1/2 |
| G60144-2012 | 20MP-12FPX90 | 7259-08165 | 1 1/4–11 1/2 | 3/4–14 |
| G60144-2016 | 20MP-16FPX90 | 7259-05435 | 1 1/4–11 1/2 | 1–11 1/2 |
| G60144-2020 | 20MP-20FPX90 | 7259-11055 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |
| G60144-2024 | 20MP-24FPX90 | 7259-07865 | 1 1/4–11 1/2 | 1 1/2–11 1/2 |
| G60144-2420 | 24MP-20FPX90 | 7259-06355 | 1 1/2–11 1/2 | 1 1/4–11 1/2 |
| G60144-2424 | 24MP-24FPX90 | 7259-11655 | 1 1/2–11 1/2 | 1 1/2–11 1/2 |
| G60144-3232 | 32MP-32FPX90 | 7259-32995 | 2–11 1/2 | 2–11 1/2 |

## Female Pipe NPTF to Female Pipe NPTF

For use up to SAE 100R2 maximum working pressure.







| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60152-0202 | 2FP-2FP | 7259-24415 | 1/8–27 | 1/8–27 |
| G60152-0402 | 4FP-2FP | 7259-05035 | 1/4–18 | 1/8–27 |
| G60152-0404 | 4FP-4FP | 7259-24425 | 1/4–18 | 1/4–18 |
| G60152-0602 | 6FP-2FP | 7259-08385 | 3/8–18 | 1/8–27 |
| G60152-0604 | 6FP-4FP | 7259-00495 | 3/8–18 | 1/4–18 |
| G60152-0606 | 6FP-6FP | 7259-24435 | 3/8–18 | 3/8–18 |
| G60152-0804 | 8FP-4FP | 7259-05575 | 1/2–14 | 1/4–18 |
| G60152-0806 | 8FP-6FP | 7259-00715 | 1/2–14 | 3/8–18 |
| G60152-0808 | 8FP-8FP | 7259-24445 | 1/2–14 | 1/2–14 |
| G60152-1208 | 12FP-8FP | 7259-00525 | 3/4–14 | 1/2–14 |
| G60152-1212 | 12FP-12FP | 7259-24455 | 3/4–14 | 3/4–14 |
| G60152-1608 | 16FP-8FP | 7259-08715 | 1–11 1/2 | 1/2–14 |
| G60152-1612 | 16FP-12FP | 7259-05745 | 1–11 1/2 | 3/4–14 |
| G60152-1616 | 16FP-16FP | 7259-24465 | 1–11 1/2 | 1–11 1/2 |
| G60152-2016 | 20FP-16FP | 7259-08395 | 1 1/4–11 1/2 | 1–11 1/2 |
| G60152-2020 | 20FP-20FP | 7259-24475 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |


## Female Pipe NPTF to Female Pipe NPTF - Continued

| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60152-2424 | 24FP-24FP | 7259-24885 | 1 1/2–11 1/2 | 1 1/2–11 1/2 |
| G60152-3232 | 32FP-32FP | 7259-24895 | 2–11 1/2 | 2–11 1/2 |

## Female Pipe NPTF to Female Pipe NPTF - 90°

For use up to SAE 100R2 maximum working pressure.









| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60156-0202 | 2FP-2FP90 | 7259-25015 | 1/8–27 | 1/8–27 |
| G60156-0402 | 4FP-2FP90 | 7259-33005 | 1/4–18 | 1/8–27 |
| G60156-0404 | 4FP-4FP90 | 7259-25025 | 1/4–18 | 1/4–18 |
| G60156-0604 | 6FP-4FP90 | 7259-33015 | 3/8–18 | 1/4–18 |
| G60156-0606 | 6FP-6FP90 | 7259-25035 | 3/8–18 | 3/8–18 |
| G60156-0804 | 8FP-4FP90 | 7259-08725 | 1/2–14 | 1/4–18 |
| G60156-0806 | 8FP-6FP90 | 7259-33025 | 1/2–14 | 3/8–18 |
| G60156-0808 | 8FP-8FP90 | 7259-25045 | 1/2–14 | 1/2–14 |
| G60156-1208 | 12FP-8FP90 | 7259-33035 | 3/4–14 | 1/2–14 |
| G60156-1212 | 12FP-12FP90 | 7259-25055 | 3/4–14 | 3/4–14 |
| G60156-1612 | 16FP-12FP90 | 7259-08175 | 1–11 1/2 | 3/4–14 |
| G60156-1616 | 16FP-16FP90 | 7259-25065 | 1–11 1/2 | 1–11 1/2 |
| G60156-2020 | 20FP-20FP90 | 7259-25075 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |
| G60156-2424 | 24FP-24FP90 | 7259-33055 | 1 1/2–11 1/2 | 1 1/2–11 1/2 |
| G60156-3232 | 32FP-32FP90 | 7259-07485 | 2–11 1/2 | 2–11 1/2 |

## Female Pipe NPTF to Female Pipe Swivel NPSM

For use up to SAE 100R2 maximum working pressure.







| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60160-0202 | 2FP-2FPX | 7259-33065 | 1/8–27 | 1/8–27 |
| G60160-0204 | 2FP-4FPX | 7259-00435 | 1/8–27 | 1/4–18 |
| G60160-0402 | 4FP-2FPX | 7259-07515 | 1/4–18 | 1/8–27 |
| G60160-0404 | 4FP-4FPX | 7259-00795 | 1/4–18 | 1/4–18 |


## Female Pipe NPTF to Female Pipe Swivel NPSM - Continued


| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60160-0406 | 4FP-6FPX | 7259-05205 | 1/4–18 | 3/8–18 |
| G60160-0604 | 6FP-4FPX | 7259-33085 | 3/8–18 | 1/4–18 |
| G60160-0606 | 6FP-6FPX | 7259-00835 | 3/8–18 | 3/8–18 |
| G60160-0608 | 6FP-8FPX | 7259-05105 | 3/8–18 | 1/2–14 |
| G60160-0804 | 8FP-4FPX | 7259-08735 | 1/2–14 | 1/4–18 |
| G60160-0806 | 8FP-6FPX | 7259-33095 | 1/2–14 | 3/8–18 |
| G60160-0808 | 8FP-8FPX | 7259-00915 | 1/2–14 | 1/2–14 |
| G60160-0812 | 8FP-12FPX | 7259-06695 | 1/2–14 | 3/4–14 |
| G60160-1208 | 12FP-8FPX | 7259-07165 | 3/4–14 | 1/2–14 |
| G60160-1212 | 12FP-12FPX | 7259-00925 | 3/4–14 | 3/4–14 |
| G60160-1216 | 12FP-16FPX | 7259-07775 | 3/4–14 | 1–11 1/2 |
| G60160-1612 | 16FP-12FPX | 7259-11595 | 1–11 1/2 | 3/4–14 |
| G60160-1616 | 16FP-16FPX | 7259-00905 | 1–11 1/2 | 1–11 1/2 |
| G60160-2020 | 20FP-20FPX | 7259-11015 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |
| G60160-2424 | 24FP-24FPX | 7259-11545 | 1 1/2–11 1/2 | 1 1/2–11 1/2 |
| G60160-3232 | 32FP-32FPX | 7259-11725 | 2–11 1/2 | 2–11 1/2 |

## Female Pipe NPTF to Female Pipe Swivel NPSM - 45°

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60162-0202 | 2FP-2FPX45 | 7259-06145 | 1/8–27 | 1/8–27 |
| G60162-0204 | 2FP-4FPX45 | 7259-08745 | 1/8–27 | 1/4–18 |
| G60162-0404 | 4FP-4FPX45 | 7259-11575 | 1/4–18 | 1/4–18 |
| G60162-0604 | 6FP-4FPX45 | 7259-06785 | 3/8–18 | 1/4–18 |
| G60162-0606 | 6FP-6FPX45 | 7259-11455 | 3/8–18 | 3/8–18 |
| G60162-0608 | 6FP-8FPX45 | 7259-08185 | 3/8–18 | 1/2–14 |
| G60162-0806 | 8FP-6FPX45 | 7259-06415 | 1/2–14 | 3/8–18 |
| G60162-0808 | 8FP-8FPX45 | 7259-11305 | 1/2–14 | 1/2–14 |
| G60162-1212 | 12FP-12FPX45 | 7259-11325 | 3/4–14 | 3/4–14 |
| G60162-1612 | 16FP-12FPX45 | 7259-06565 | 1–11 1/2 | 3/4–14 |
| G60162-1616 | 16FP-16FPX45 | 7259-11515 | 1–11 1/2 | 1–11 1/2 |
| G60162-2020 | 20FP-20FPX45 | 7259-33105 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |

# Female Pipe NPTF to Female Pipe Swivel NPSM - 90°

For use up to SAE 100R2 maximum working pressure.











| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60164-0202 | 2FP-2FPX90 | 7259-05475 | 1/8–27 | 1/8–27 |
| G60164-0204 | 2FP-4FPX90 | 7259-08755 | 1/8–27 | 1/4–18 |
| G60164-0402 | 4FP-2FPX90 | 7259-06285 | 1/4–18 | 1/8–27 |
| G60164-0404 | 4FP-4FPX90 | 7259-11005 | 1/4–18 | 1/4–18 |
| G60164-0406 | 4FP-6FPX90 | 7259-06245 | 1/4–18 | 3/8–18 |
| G60164-0604 | 6FP-4FPX90 | 7259-06825 | 3/8–18 | 1/4–18 |
| G60164-0606 | 6FP-6FPX90 | 7259-10955 | 3/8–18 | 3/8–18 |
| G60164-0608 | 6FP-8FPX90 | 7259-06965 | 3/8–18 | 1/2–14 |
| G60164-0806 | 8FP-6FPX90 | 7259-06855 | 1/2–14 | 3/8–18 |
| G60164-0808 | 8FP-8FPX90 | 7259-10615 | 1/2–14 | 1/2–14 |
| G60164-0812 | 8FP-12FPX90 | 7259-06485 | 1/2–14 | 3/4–14 |
| G60164-1208 | 12FP-8FPX90 | 7259-06585 | 3/4–14 | 1/2–14 |
| G60164-1212 | 12FP-12FPX90 | 7259-11095 | 3/4–14 | 3/4–14 |
| G60164-1612 | 16FP-12FPX90 | 7259-06595 | 1–11 1/2 | 3/4–14 |
| G60164-1616 | 16FP-16FPX90 | 7259-11765 | 1–11 1/2 | 1–11 1/2 |
| G60164-2016 | 20FP-16FPX90 | 7259-08405 | 1 1/4–11 1/2 | 1–11 1/2 |
| G60164-2020 | 20FP-20FPX90 | 7259-33115 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |
| G60164-2424 | 24FP-24FPX90 | 7259-33125 | 1 1/2–11 1/2 | 1 1/2–11 1/2 |
| G60164-3232 | 32FP-32FPX90 | 7259-33135 | 2–11 1/2 | 2–11 1/2 |

# Female Pipe NPTF - Tee

For use up to SAE 100R2 maximum working pressure.







| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60181-0202 | 2FP-2FP-2FP | 7259-23145 | 1/8–27 | 1/8–27 | 1/8–27 |
| G60181-0404 | 4FP-4FP-4FP | 7259-23155 | 1/4–18 | 1/4–18 | 1/4–18 |
| G60181-0606 | 6FP-6FP-6FP | 7259-23165 | 3/8–18 | 3/8–18 | 3/8–18 |
| G60181-0808 | 8FP-8FP-8FP | 7259-23175 | 1/2–14 | 1/2–14 | 1/2–14 |
| G60181-1212 | 12FP-12FP-12FP | 7259-23185 | 3/4–14 | 3/4–14 | 3/4–14 |
| G60181-1616 | 16FP-16FP-16FP | 7259-23195 | 1–11 1/2 | 1–11 1/2 | 1–11 1/2 |
| G60181-2020 | 20FP-20FP-20FP | 7259-33145 | 1 1/4–11 1/2 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |


## Female Pipe NPTF - Tee - Continued


| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60181-2424 | 24FP-24FP-24FP | 7259-33155 | 1 1/2–11 1/2 | 1 1/2–11 1/2 | 1 1/2–11 1/2 |
| G60181-3232 | 32FP-32FP-32FP | 7259-07245 | 2–11 1/2 | 2–11 1/2 | 2–11 1/2 |

## Female Pipe NPTF on Run to Male Pipe NPTF - Tee

For use up to SAE 100R2 maximum working pressure.











| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60183-0202 | 2FP-2FP-2MP | 7259-24905 | 1/8–27 | 1/8–27 | 1/8–27 |
| G60183-0404 | 4FP-4FP-4MP | 7259-24915 | 1/4–18 | 1/4–18 | 1/4–18 |
| G60183-0606 | 6FP-6FP-6MP | 7259-24925 | 3/8–18 | 3/8–18 | 3/8–18 |
| G60183-0808 | 8FP-8FP-8MP | 7259-24935 | 1/2–14 | 1/2–14 | 1/2–14 |
| G60183-1212 | 12FP-12FP-12MP | 7259-24945 | 3/4–14 | 3/4–14 | 3/4–14 |
| G60183-1616 | 16FP-16FP-16MP | 7259-24955 | 1–11 1/2 | 1–11 1/2 | 1–11 1/2 |
| G60183-2020 | 20FP-20FP-20MP | 7259-07875 | 1 1/4–11 1/2 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |
| G60183-2424 | 24FP-24FP-24MP | 7259-08765 | 1 1/2–11 1/2 | 1 1/2–11 1/2 | 1 1/2–11 1/2 |

## Female Pipe Swivel NPSM - Tee

For use up to SAE 100R2 maximum working pressure.









| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60184-0202 | 2FPX-2FPX-2FPX | 7253-33165 | 1/8–27 | 1/8–27 | 1/8–27 |
| G60184-0404 | 4FPX-4FPX-4FPX | 7253-33175 | 1/4–18 | 1/4–18 | 1/4–18 |
| G60184-0606 | 6FPX-6FPX-6FPX | 7253-33185 | 3/8–18 | 3/8–18 | 3/8–18 |
| G60184-0808 | 8FPX-8FPX-8FPX | 7259-33195 | 1/2–14 | 1/2–14 | 1/2–14 |
| G60184-1212 | 12FPX-12FPX-12FPX | 7259-33205 | 3/4–14 | 3/4–14 | 3/4–14 |
| G60184-1616 | 16FPX-16FPX-16FPX | 7253-33215 | 1–11 1/2 | 1–11 1/2 | 1–11 1/2 |
| G60184-2020 | 20FPX-20FPX-20FPX | 7253-33225 | 1 1/4–11 1/2 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |

# Female Pipe Swivel NPSM on Run to Male Pipe NPTF - Tee

For use up to SAE 100R2 maximum working pressure.











| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60186-0202 | 2FPX-2FPX-2MP | 7253-86585 | 1/8–27 | 1/8–27 | 1/8–27 |
| G60186-0404 | 4FPX-4FPX-4MP | 7253-86586 | 1/4–18 | 1/4–18 | 1/4–18 |
| G60186-0606 | 6FPX-6FPX-6MP | 7253-86587 | 3/8–18 | 3/8–18 | 3/8–18 |
| G60186-0808 | 8FPX-8FPX-8MP | 7253-86588 | 1/2–14 | 1/2–14 | 1/2–14 |
| G60186-1212 | 12FPX-12FPX-12MP | 7253-86589 | 3/4–14 | 3/4–14 | 3/4–14 |
| G60186-1616 | 16FPX-16FPX-16MP | 7253-86591 | 1–11 1/2 | 1–11 1/2 | 1–11 1/2 |
| G60186-2020 | 20FPX-20FPX-20MP | 7253-33235 | 1 1/4–11 1/2 | 1 1/4–11 1/2 | 1 1/4–11 1/2 |
| G60186-2424 | 24FPX-24FPX-24MP | 7259-07605 | 1 1/2–11 1/2 | 1 1/2–11 1/2 | 1 1/2–11 1/2 |

# Male O-Ring Boss Plug

For use up to SAE 100R2 maximum working pressure.









| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| | | | " |
| G60250-0002 | 2MB-PLUG | 7259-05415 | 5/16–24 |
| G60250-0003 | 3MB-PLUG | 7259-05255 | 3/8–24 |
| G60250-0004 | 4MB-PLUG | 7259-22975 | 7/16–20 |
| G60250-0005 | 5MB-PLUG | 7259-22985 | 1/2–20 |
| G60250-0006 | 6MB-PLUG | 7259-22995 | 9/16–18 |
| G60250-0008 | 8MB-PLUG | 7259-23005 | 3/4–16 |
| G60250-0010 | 10MB-PLUG | 7259-23015 | 7/8–14 |
| G60250-0012 | 12MB-PLUG | 7259-23025 | 1 1/16–12 |
| G60250-0014 | 14MB-PLUG | 7259-23035 | 1 3/16–12 |
| G60250-0016 | 16MB-PLUG | 7259-23045 | 1 5/16–12 |
| G60250-0020 | 20MB-PLUG | 7259-23055 | 1 5/8–12 |
| G60250-0024 | 24MB-PLUG | 7259-05185 | 1 7/8–12 |
| G60250-0032 | 32MB-PLUG | 7259-07615 | 2 1/2–12 |

# Male O-Ring Boss to Male Pipe NPTF

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60265-0808 | 8MB-8MP | 7259-50725 | 3/4–16 | 1/2–14 |
| G60265-1008 | 10MB-8MP | 7259-50735 | 7/8–14 | 1/2–14 |

# Male O-Ring Boss to Female Pipe NPTF

For use up to SAE 100R2 maximum working pressure.











| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60275-0302 | 3MB-2FP | 7259-08785 | 3/8–24 | 1/8–27 |
| G60275-0402 | 4MB-2FP | 7259-24205 | 7/16–20 | 1/8–27 |
| G60275-0404 | 4MB-4FP | 7259-00395 | 7/16–20 | 1/4–18 |
| G60275-0406 | 4MB-6FP | 7259-05145 | 7/16–20 | 3/8–18 |
| G60275-0502 | 5MB-2FP | 7259-05945 | 1/2–20 | 1/8–27 |
| G60275-0504 | 5MB-4FP | 7259-05755 | 1/2–20 | 1/4–18 |
| G60275-0602 | 6MB-2FP | 7259-08805 | 9/16–18 | 1/8–27 |
| G60275-0604 | 6MB-4FP | 7259-24215 | 9/16–18 | 1/4–18 |
| G60275-0606 | 6MB-6FP | 7259-00205 | 9/16–18 | 3/8–18 |
| G60275-0608 | 6MB-8FP | 7259-06605 | 9/16–18 | 1/2–14 |
| G60275-0804 | 8MB-4FP | 7259-00245 | 3/4–16 | 1/4–18 |
| G60275-0806 | 8MB-6FP | 7259-24225 | 3/4–16 | 3/8–18 |
| G60275-0808 | 8MB-8FP | 7259-33255 | 3/4–16 | 1/2–14 |
| G60275-0812 | 8MB-12FP | 7259-06715 | 3/4–16 | 3/4–14 |
| G60275-1004 | 10MB-4FP | 7259-07255 | 7/8–14 | 1/4–18 |
| G60275-1006 | 10MB-6FP | 7259-00335 | 7/8–14 | 3/8–18 |
| G60275-1008 | 10MB-8FP | 7259-24235 | 7/8–14 | 1/2–14 |
| G60275-1012 | 10MB-12FP | 7259-05315 | 7/8–14 | 3/4–14 |
| G60275-1208 | 12MB-8FP | 7259-24245 | 1 1/16–12 | 1/2–14 |
| G60275-1212 | 12MB-12FP | 7259-24255 | 1 1/16–12 | 3/4–14 |
| G60275-1216 | 12MB-16FP | 7259-06155 | 1 1/16–12 | 1–11 1/2 |
| G60275-1412 | 14MB-12FP | 7259-24265 | 1 3/16–12 | 3/4–14 |
| G60275-1608 | 16MB-8FP | 7259-05495 | 1 5/16–12 | 1/2–14 |
| G60275-1612 | 16MB-12FP | 7259-33265 | 1 5/16–12 | 3/4–14 |
| G60275-1616 | 16MB-16FP | 7259-24275 | 1 5/16–12 | 1–11 1/2 |
| G60275-2016 | 20MB-16FP | 7259-05445 | 1 5/8–12 | 1–11 1/2 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male O-Ring Boss to Female Pipe Swivel NPSM

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60285-0402 | 4MB-2FPX | 7259-06725 | 7/16–20 | 1/8–27 |
| G60285-0404 | 4MB-4FPX | 7259-10475 | 7/16–20 | 1/4–18 |
| G60285-0406 | 4MB-6FPX | 7259-05395 | 7/16–20 | 3/8–18 |
| G60285-0504 | 5MB-4FPX | 7259-11065 | 1/2–20 | 1/4–18 |
| G60285-0508 | 5MB-8FPX | 7259-11735 | 1/2–20 | 1/2–14 |
| G60285-0604 | 6MB-4FPX | 7259-10585 | 9/16–18 | 1/4–18 |
| G60285-0606 | 6MB-6FPX | 7259-10445 | 9/16–18 | 3/8–18 |
| G60285-0608 | 6MB-8FPX | 7259-07495 | 9/16–18 | 1/2–14 |
| G60285-0804 | 8MB-4FPX | 7259-11115 | 3/4–16 | 1/4–18 |
| G60285-0806 | 8MB-6FPX | 7259-10535 | 3/4–16 | 3/8–18 |
| G60285-0808 | 8MB-8FPX | 7259-00295 | 3/4–16 | 1/2–14 |
| G60285-0812 | 8MB-12FPX | 7259-11105 | 3/4–16 | 3/4–14 |
| G60285-1006 | 10MB-6FPX | 7259-11155 | 7/8–14 | 3/8–18 |
| G60285-1008 | 10MB-8FPX | 7259-10215 | 7/8–14 | 1/2–14 |
| G60285-1012 | 10MB-12FPX | 7259-10665 | 7/8–14 | 3/4–14 |
| G60285-1208 | 12MB-8FPX | 7259-10725 | 1 1/16–12 | 1/2–14 |
| G60285-1212 | 12MB-12FPX | 7259-10315 | 1 1/16–12 | 3/4–14 |
| G60285-1216 | 12MB-16FPX | 7259-05535 | 1 1/16–12 | 1–11 1/2 |
| G60285-1412 | 14MB-12FPX | 7259-33275 | 1 3/16–12 | 3/4–14 |
| G60285-1612 | 16MB-12FPX | 7259-05115 | 1 5/16–12 | 3/4–14 |
| G60285-1616 | 16MB-16FPX | 7259-33285 | 1 5/16–12 | 1–11 1/2 |
| G60285-1620 | 16MB-20FPX | 7259-08035 | 1 5/16–12 | 1 1/4–11 1/2 |
| G60285-2012 | 20MB-12FPX | 7259-08815 | 1 5/8–12 | 3/4–14 |
| G60285-2016 | 20MB-16FPX | 7259-06925 | 1 5/8–12 | 1–11 1/2 |
| G60285-2020 | 20MB-20FPX | 7259-05605 | 1 5/8–12 | 1 1/4–11 1/2 |
| G60285-2420 | 24MB-20FPX | 7259-08825 | 1 7/8–12 | 1 1/4–11 1/2 |
| G60285-2424 | 24MB-24FPX | 7259-07625 | 1 7/8–12 | 1 1/2–11 1/2 |
| G60285-3232 | 32MB-32FPX | 7259-07885 | 2 1/2–12 | 2–11 1/2 |

# Male O-Ring Boss to Female Pipe Swivel NPSM - 45°

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60287-0402 | 4MB-2FPX45 | 7259-08835 | 7/16–20 | 1/8–27 |
| G60287-0404 | 4MB-4FPX45 | 7259-05015 | 7/16–20 | 1/4–18 |
| G60287-0406 | 4MB-6FPX45 | 7259-07795 | 7/16–20 | 3/8–18 |
| G60287-0604 | 6MB-4FPX45 | 7259-05825 | 9/16–18 | 1/4–18 |
| G60287-0606 | 6MB-6FPX45 | 7259-10915 | 9/16–18 | 3/8–18 |
| G60287-0608 | 6MB-8FPX45 | 7259-06365 | 9/16–18 | 1/2–14 |
| G60287-0804 | 8MB-4FPX45 | 7259-08845 | 3/4–16 | 1/4–18 |
| G60287-0806 | 8MB-6FPX45 | 7259-11495 | 3/4–16 | 3/8–18 |
| G60287-0808 | 8MB-8FPX45 | 7259-10875 | 3/4–16 | 1/2–14 |
| G60287-0812 | 8MB-12FPX45 | 7259-33295 | 3/4–16 | 3/4–14 |
| G60287-1006 | 10MB-6FPX45 | 7259-11645 | 7/8–14 | 3/8–18 |
| G60287-1008 | 10MB-8FPX45 | 7259-10815 | 7/8–14 | 1/2–14 |
| G60287-1012 | 10MB-12FPX45 | 7259-06575 | 7/8–14 | 3/4–14 |
| G60287-1208 | 12MB-8FPX45 | 7259-08205 | 1 1/16–12 | 1/2–14 |
| G60287-1212 | 12MB-12FPX45 | 7259-11315 | 1 1/16–12 | 3/4–14 |
| G60287-1216 | 12MB-16FPX45 | 7259-07265 | 1 1/16–12 | 1–11 1/2 |
| G60287-1612 | 16MB-12FPX45 | 7259-07425 | 1 5/16–12 | 3/4–14 |
| G60287-1616 | 16MB-16FPX45 | 7259-33325 | 1 5/16–12 | 1–11 1/2 |
| G60287-2020 | 20MB-20FPX45 | 7259-06615 | 1 5/8–12 | 1 1/4–11 1/2 |
| G60287-2424 | 24MB-24FPX45 | 7259-08415 | 1 7/8–12 | 1 1/2–11 1/2 |

# Male O-Ring Boss to Female Pipe Swivel NPSM - 90°

For use up to SAE 100R2 maximum working pressure.







| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60289-0402 | 4MB-2FPX90 | 7259-08215 | 7/16–20 | 1/8–27 |
| G60289-0404 | 4MB-4FPX90 | 7259-10835 | 7/16–20 | 1/4–18 |
| G60289-0406 | 4MB-6FPX90 | 7259-06625 | 7/16–20 | 3/8–18 |
| G60289-0604 | 6MB-4FPX90 | 7259-10405 | 9/16–18 | 1/4–18 |
| G60289-0606 | 6MB-6FPX90 | 7259-10285 | 9/16–18 | 3/8–18 |
| G60289-0608 | 6MB-8FPX90 | 7259-05045 | 9/16–18 | 1/2–14 |


## Male O-Ring Boss to Female Pipe Swivel NPSM - 90° - Continued


| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60289-0804 | 8MB-4FPX90 | 7259-06175 | 3/4–16 | 1/4–18 |
| G60289-0806 | 8MB-6FPX90 | 7259-10295 | 3/4–16 | 3/8–18 |
| G60289-0808 | 8MB-8FPX90 | 7259-10155 | 3/4–16 | 1/2–14 |
| G60289-0812 | 8MB-12FPX90 | 7259-11335 | 3/4–16 | 3/4–14 |
| G60289-1006 | 10MB-6FPX90 | 7259-11215 | 7/8–14 | 3/8–18 |
| G60289-1008 | 10MB-8FPX90 | 7259-10345 | 7/8–14 | 1/2–14 |
| G60289-1012 | 10MB-12FPX90 | 7259-11295 | 7/8–14 | 3/4–14 |
| G60289-1206 | 12MB-6FPX90 | 7259-07895 | 1 1/16–12 | 3/8–18 |
| G60289-1208 | 12MB-8FPX90 | 7259-00515 | 1 1/16–12 | 1/2–14 |
| G60289-1212 | 12MB-12FPX90 | 7259-10575 | 1 1/16–12 | 3/4–14 |
| G60289-1216 | 12MB-16FPX90 | 7259-06935 | 1 1/16–12 | 1–11 1/2 |
| G60289-1412 | 14MB-12FPX90 | 7259-07175 | 1 3/16–12 | 3/4–14 |
| G60289-1612 | 16MB-12FPX90 | 7259-05805 | 1 5/16–12 | 3/4–14 |
| G60289-1616 | 16MB-16FPX90 | 7259-11125 | 1 5/16–12 | 1–11 1/2 |
| G60289-1620 | 16MB-20FPX90 | 7259-06875 | 1 5/16–12 | 1 1/4–11 1/2 |
| G60289-2012 | 20MB-12FPX90 | 7259-06945 | 1 5/8–12 | 3/4–14 |
| G60289-2016 | 20MB-16FPX90 | 7259-06635 | 1 5/8–12 | 1–11 1/2 |
| G60289-2020 | 20MB-20FPX90 | 7259-05905 | 1 5/8–12 | 1 1/4–11 1/2 |
| G60289-2424 | 24MB-24FPX90 | 7259-08855 | 1 7/8–12 | 1 1/2–11 1/2 |
| G60289-3232 | 32MB-32FPX90 | 7259-08045 | 2 1/2–12 | 2–11 1/2 |

## Female O-Ring Boss to Male Pipe NPTF

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60291-0402 | 4FB-2MP | 7259-33335 | 7/16–20 | 1/8–27 |
| G60291-0404 | 4FB-4MP | 7259-06515 | 7/16–20 | 1/4–18 |
| G60291-0502 | 5FB-2MP | 7259-33355 | 1/2–20 | 1/8–27 |
| G60291-0604 | 6FB-4MP | 7259-33345 | 9/16–18 | 1/4–18 |
| G60291-0606 | 6FB-6MP | 7259-00385 | 9/16–18 | 3/8–18 |
| G60291-0608 | 6FB-8MP | 7259-00485 | 9/16–18 | 1/2–14 |
| G60291-0806 | 8FB-6MP | 7259-33365 | 3/4–16 | 3/8–18 |
| G60291-0808 | 8FB-8MP | 7259-08875 | 3/4–16 | 1/2–14 |
| G60291-1008 | 10FB-8MP | 7259-33375 | 7/8–14 | 1/2–14 |
| G60291-1208 | 12FB-8MP | 7259-06955 | 1 1/16–12 | 1/2–14 |
| G60291-1212 | 12FB-12MP | 7259-33385 | 1 1/16–12 | 3/4–14 |
| G60291-1612 | 16FB-12MP | 7259-08885 | 1 5/16–12 | 3/4–14 |
| G60291-1616 | 16FB-16MP | 7259-33395 | 1 5/16–12 | 1–11 1/2 |

# Male O-Ring Boss to Male JIC 37° Flare

For use up to SAE 100R2 maximum working pressure.





| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60301-0202 | 2MB-2MJ | 7259-07275 | 5/16–24 | 5/16–24 |
| G60301-0204 | 2MB-4MJ | 7259-08895 | 5/16–24 | 7/16–20 |
| G60301-0304 | 3MB-4MJ | 7259-06255 | 3/8–24 | 7/16–20 |
| G60301-0403 | 4MB-3MJ | 7259-08905 | 7/16–20 | 3/8–24 |
| G60301-0404 | 4MB-4MJ | 7259-10025 | 7/16–20 | 7/16–20 |
| G60301-0405 | 4MB-5MJ | 7259-05005 | 7/16–20 | 1/2–20 |
| G60301-0406 | 4MB-6MJ | 7259-33405 | 7/16–20 | 9/16–18 |
| G60301-0408 | 4MB-8MJ | 7259-08915 | 7/16–20 | 3/4–16 |
| G60301-0503 | 5MB-3MJ | 7253-86885 | 1/2–20 | 3/8–24 |
| G60301-0504 | 5MB-4MJ | 7259-10775 | 1/2–20 | 7/16–20 |
| G60301-0505 | 5MB-5MJ | 7259-10855 | 1/2–20 | 1/2–20 |
| G60301-0506 | 5MB-6MJ | 7259-33415 | 1/2–20 | 9/16–18 |
| G60301-0604 | 6MB-4MJ | 7259-10045 | 9/16–18 | 7/16–20 |
| G60301-0605 | 6MB-5MJ | 7259-00455 | 9/16–18 | 1/2–20 |
| G60301-0606 | 6MB-6MJ | 7259-04685 | 9/16–18 | 9/16–18 |
| G60301-0608 | 6MB-8MJ | 7259-10145 | 9/16–18 | 3/4–16 |
| G60301-0610 | 6MB-10MJ | 7259-33425 | 9/16–18 | 7/8–14 |
| G60301-0612 | 6MB-12MJ | 7259-07635 | 9/16–18 | 1 1/16–12 |
| G60301-0804 | 8MB-4MJ | 7259-00025 | 3/4–16 | 7/16–20 |
| G60301-0805 | 8MB-5MJ | 7259-06885 | 3/4–16 | 1/2–20 |
| G60301-0806 | 8MB-6MJ | 7259-04775 | 3/4–16 | 9/16–18 |
| G60301-0808 | 8MB-8MJ | 7259-10015 | 3/4–16 | 3/4–16 |
| G60301-0810 | 8MB-10MJ | 7259-10425 | 3/4–16 | 7/8–14 |
| G60301-0812 | 8MB-12MJ | 7259-10305 | 3/4–16 | 1 1/16–12 |
| G60301-0816 | 8MB-16MJ | 7259-07285 | 3/4–16 | 1 5/16–12 |
| G60301-1004 | 10MB-4MJ | 7259-00105 | 7/8–14 | 7/16–20 |
| G60301-1006 | 10MB-6MJ | 7259-10095 | 7/8–14 | 9/16–18 |
| G60301-1008 | 10MB-8MJ | 7259-10075 | 7/8–14 | 3/4–16 |
| G60301-1010 | 10MB-10MJ | 7259-10065 | 7/8–14 | 7/8–14 |
| G60301-1012 | 10MB-12MJ | 7259-00235 | 7/8–14 | 1 1/16–12 |
| G60301-1016 | 10MB-16MJ | 7259-00355 | 7/8–14 | 1 5/16–12 |
| G60301-1204 | 12MB-4MJ | 7259-07905 | 1 1/16–12 | 7/16–20 |
| G60301-1206 | 12MB-6MJ | 7259-00305 | 1 1/16–12 | 9/16–18 |
| G60301-1208 | 12MB-8MJ | 7259-10035 | 1 1/16–12 | 3/4–16 |
| G60301-1210 | 12MB-10MJ | 7259-10755 | 1 1/16–12 | 7/8–14 |
| G60301-1212 | 12MB-12MJ | 7259-10115 | 1 1/16–12 | 1 1/16–12 |
| G60301-1214 | 12MB-14MJ | 7259-08225 | 1 1/16–12 | 1 3/16–12 |
| G60301-1216 | 12MB-16MJ | 7259-10885 | 1 1/16–12 | 1 5/16–12 |
| G60301-1220 | 12MB-20MJ | 7259-06005 | 1 1/16–12 | 1 5/8–12 |
| G60301-1410 | 14MB-10MJ | 7259-08425 | 1 3/16–12 | 7/8–14 |
| G60301-1412 | 14MB-12MJ | 7259-06185 | 1 3/16–12 | 1 1/16–12 |
| G60301-1414 | 14MB-14MJ | 7259-07525 | 1 3/16–12 | 1 3/16–12 |
| G60301-1416 | 14MB-16MJ | 7259-08235 | 1 3/16–12 | 1 5/16–12 |
| G60301-1608 | 16MB-8MJ | 7259-00125 | 1 5/16–12 | 3/4–16 |
| G60301-1610 | 16MB-10MJ | 7259-11385 | 1 5/16–12 | 7/8–14 |
| G60301-1612 | 16MB-12MJ | 7259-10135 | 1 5/16–12 | 1 1/16–12 |
| G60301-1616 | 16MB-16MJ | 7259-10055 | 1 5/16–12 | 1 5/16–12 |
| G60301-1620 | 16MB-20MJ | 7259-05485 | 1 5/16–12 | 1 5/8–12 |


## Male O-Ring Boss to Male JIC 37° Flare - Continued


| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60301-2010 | 20MB-10MJ | 7253-86907 | 1 5/8–12 | 7/8–14 |
| G60301-2012 | 20MB-12MJ | 7259-11255 | 1 5/8–12 | 1 1/16–12 |
| G60301-2016 | 20MB-16MJ | 7259-10245 | 1 5/8–12 | 1 5/16–12 |
| G60301-2020 | 20MB-20MJ | 7259-11235 | 1 5/8–12 | 1 5/8–12 |
| G60301-2024 | 20MB-24MJ | 7259-06315 | 1 5/8–12 | 1 7/8–12 |
| G60301-2416 | 24MB-16MJ | 7259-00365 | 1 7/8–12 | 1 5/16–12 |
| G60301-2420 | 24MB-20MJ | 7259-05505 | 1 7/8–12 | 1 5/8–12 |
| G60301-2424 | 24MB-24MJ | 7259-05345 | 1 7/8–12 | 1 7/8–12 |
| G60301-3224 | 32MB-24MJ | 7259-07645 | 2 1/2–12 | 1 7/8–12 |
| G60301-3232 | 32MB-32MJ | 7259-09855 | 2 1/2–12 | 2 1/2–12 |

## Male O-Ring Boss to Male JIC 37° Flare - 45°

For use up to SAE 100R2 maximum working pressure.













| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60308-0404 | 4MB-4MJ45 | 7259-28565 | 7/16–20 | 7/16–20 |
| G60308-0406 | 4MB-6MJ45 | 7259-00095 | 7/16–20 | 9/16–18 |
| G60308-0505 | 5MB-5MJ45 | 7259-28575 | 1/2–20 | 1/2–20 |
| G60308-0506 | 5MB-6MJ45 | 7259-05405 | 1/2–20 | 9/16–18 |
| G60308-0604 | 6MB-4MJ45 | 7259-00065 | 9/16–18 | 7/16–20 |
| G60308-0606 | 6MB-6MJ45 | 7259-28585 | 9/16–18 | 9/16–18 |
| G60308-0608 | 6MB-8MJ45 | 7259-05335 | 9/16–18 | 3/4–16 |
| G60308-0806 | 8MB-6MJ45 | 7259-77595 | 3/4–16 | 9/16–18 |
| G60308-0808 | 8MB-8MJ45 | 7259-28255 | 3/4–16 | 3/4–16 |
| G60308-0810 | 8MB-10MJ45 | 7259-28415 | 3/4–16 | 7/8–14 |
| G60308-0812 | 8MB-12MJ45 | 7259-06895 | 3/4–16 | 1 1/16–12 |
| G60308-1008 | 10MB-8MJ45 | 7259-28425 | 7/8–14 | 3/4–16 |
| G60308-1010 | 10MB-10MJ45 | 7259-10895 | 7/8–14 | 7/8–14 |
| G60308-1012 | 10MB-12MJ45 | 7259-05785 | 7/8–14 | 1 1/16–12 |
| G60308-1210 | 12MB-10MJ45 | 7259-77605 | 1 1/16–12 | 7/8–14 |
| G60308-1212 | 12MB-12MJ45 | 7259-28595 | 1 1/16–12 | 1 1/16–12 |
| G60308-1216 | 12MB-16MJ45 | 7259-28435 | 1 1/16–12 | 1 5/16–12 |
| G60308-1414 | 14MB-14MJ45 | 7259-28605 | 1 3/16–12 | 1 3/16–12 |
| G60308-1612 | 16MB-12MJ45 | 7259-28445 | 1 5/16–12 | 1 1/16–12 |
| G60308-1616 | 16MB-16MJ45 | 7259-28615 | 1 5/16–12 | 1 5/16–12 |
| G60308-1620 | 16MB-20MJ45 | 7259-08065 | 1 5/16–12 | 1 5/8–12 |
| G60308-2016 | 20MB-16MJ45 | 7259-07295 | 1 5/8–12 | 1 5/16–12 |
| G60308-2020 | 20MB-20MJ45 | 7259-05955 | 1 5/8–12 | 1 5/8–12 |
| G60308-2424 | 24MB-24MJ45 | 7259-06975 | 1 7/8–12 | 1 7/8–12 |

# Male O-Ring Boss to Male JIC 37° Flare - 90°

For use up to SAE 100R2 maximum working pressure.





| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60312-0202 | 2MB-2MJ90 | 7259-08925 | 5/16–24 | 5/16–24 |
| G60312-0303 | 3MB-3MJ90 | 7259-77615 | 3/8–24 | 3/8–24 |
| G60312-0404 | 4MB-4MJ90 | 7259-28265 | 7/16–20 | 7/16–20 |
| G60312-0405 | 4MB-5MJ90 | 7259-77625 | 7/16–20 | 1/2–20 |
| G60312-0406 | 4MB-6MJ90 | 7259-28455 | 7/16–20 | 9/16–18 |
| G60312-0408 | 4MB-8MJ90 | 7259-09825 | 7/16–20 | 3/4–16 |
| G60312-0504 | 5MB-4MJ90 | 7259-05615 | 1/2–20 | 7/16–20 |
| G60312-0505 | 5MB-5MJ90 | 7259-28625 | 1/2–20 | 1/2–20 |
| G60312-0506 | 5MB-6MJ90 | 7259-05075 | 1/2–20 | 9/16–18 |
| G60312-0508 | 5MB-8MJ90 | 7259-06985 | 1/2–20 | 3/4–16 |
| G60312-0604 | 6MB-4MJ90 | 7259-28465 | 9/16–18 | 7/16–20 |
| G60312-0605 | 6MB-5MJ90 | 7259-28475 | 9/16–18 | 1/2–20 |
| G60312-0606 | 6MB-6MJ90 | 7259-28275 | 9/16–18 | 9/16–18 |
| G60312-0608 | 6MB-8MJ90 | 7259-28485 | 9/16–18 | 3/4–16 |
| G60312-0610 | 6MB-10MJ90 | 7259-28495 | 9/16–18 | 7/8–14 |
| G60312-0612 | 6MB-12MJ90 | 7259-07915 | 9/16–18 | 1 1/16–12 |
| G60312-0804 | 8MB-4MJ90 | 7259-05165 | 3/4–16 | 7/16–20 |
| G60312-0805 | 8MB-5MJ90 | 7259-08075 | 3/4–16 | 1/2–20 |
| G60312-0806 | 8MB-6MJ90 | 7259-28505 | 3/4–16 | 9/16–18 |
| G60312-0808 | 8MB-8MJ90 | 7259-28285 | 3/4–16 | 3/4–16 |
| G60312-0810 | 8MB-10MJ90 | 7259-28515 | 3/4–16 | 7/8–14 |
| G60312-0812 | 8MB-12MJ90 | 7259-28525 | 3/4–16 | 1 1/16–12 |
| G60312-0816 | 8MB-16MJ90 | 7259-08445 | 3/4–16 | 1 5/16–12 |
| G60312-1005 | 10MB-5MJ90 | 7259-08935 | 7/8–14 | 1/2–20 |
| G60312-1006 | 10MB-6MJ90 | 7259-00215 | 7/8–14 | 9/16–18 |
| G60312-1008 | 10MB-8MJ90 | 7259-28295 | 7/8–14 | 3/4–16 |
| G60312-1010 | 10MB-10MJ90 | 7259-28635 | 7/8–14 | 7/8–14 |
| G60312-1012 | 10MB-12MJ90 | 7259-28535 | 7/8–14 | 1 1/16–12 |
| G60312-1016 | 10MB-16MJ90 | 7259-05275 | 7/8–14 | 1 5/16–12 |
| G60312-1206 | 12MB-6MJ90 | 7259-05065 | 1 1/16–12 | 9/16–18 |
| G60312-1208 | 12MB-8MJ90 | 7259-00055 | 1 1/16–12 | 3/4–16 |
| G60312-1210 | 12MB-10MJ90 | 7259-28545 | 1 1/16–12 | 7/8–14 |
| G60312-1212 | 12MB-12MJ90 | 7259-28645 | 1 1/16–12 | 1 1/16–12 |
| G60312-1214 | 12MB-14MJ90 | 7259-08945 | 1 1/16–12 | 1 3/16–12 |
| G60312-1216 | 12MB-16MJ90 | 7259-28555 | 1 1/16–12 | 1 5/16–12 |
| G60312-1220 | 12MB-20MJ90 | 7259-08435 | 1 1/16–12 | 1 5/8–12 |
| G60312-1412 | 14MB-12MJ90 | 7259-06435 | 1 3/16–12 | 1 1/16–12 |
| G60312-1414 | 14MB-14MJ90 | 7259-28655 | 1 3/16–12 | 1 3/16–12 |
| G60312-1416 | 14MB-16MJ90 | 7259-07305 | 1 3/16–12 | 1 5/16–12 |
| G60312-1420 | 14MB-20MJ90 | 7259-08955 | 1 3/16–12 | 1 5/8–12 |
| G60312-1608 | 16MB-8MJ90 | 7259-05885 | 1 5/16–12 | 3/4–16 |
| G60312-1610 | 16MB-10MJ90 | 7259-08965 | 1 5/16–12 | 7/8–14 |


## Male O-Ring Boss to Male JIC 37° Flare - 90° - Continued


| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60312-1612 | 16MB-12MJ90 | 7259-28315 | 1 5/16–12 | 1 1/16–12 |
| G60312-1614 | 16MB-14MJ90 | 7259-08975 | 1 5/16–12 | 1 3/16–12 |
| G60312-1616 | 16MB-16MJ90 | 7259-28325 | 1 5/16–12 | 1 5/16–12 |
| G60312-1620 | 16MB-20MJ90 | 7259-77655 | 1 5/16–12 | 1 5/8–12 |
| G60312-1624 | 16MB-24MJ90 | 7259-08255 | 1 5/16–12 | 1 7/8–12 |
| G60312-2010 | 20MB-10MJ90 | 7259-08265 | 1 5/8–12 | 7/8–14 |
| G60312-2012 | 20MB-12MJ90 | 7259-05995 | 1 5/8–12 | 1 1/16–12 |
| G60312-2016 | 20MB-16MJ90 | 7259-05055 | 1 5/8–12 | 1 5/16–12 |
| G60312-2020 | 20MB-20MJ90 | 7259-77665 | 1 5/8–12 | 1 5/8–12 |
| G60312-2024 | 20MB-24MJ90 | 7259-06015 | 1 5/8–12 | 1 7/8–12 |
| G60312-2420 | 24MB-20MJ90 | 7259-06525 | 1 7/8–12 | 1 5/8–12 |
| G60312-2424 | 24MB-24MJ90 | 7259-77675 | 1 7/8–12 | 1 7/8–12 |
| G60312-3232 | 32MB-32MJ90 | 7259-07135 | 2 1/2–12 | 2 1/2–12 |

## Male O-Ring Boss to Female JIC 37° Flare Swivel

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60320-0606 | 6MB-6FJX | 7259-42155 | 9/16–18 | 9/16–18 |
| G60320-0808 | 8MB-8FJX | 7259-42185 | 3/4–16 | 3/4–16 |

## Male JIC 37° Flare on Run to Male O-Ring Boss - Tee

For use up to SAE 100R2 maximum working pressure.





| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60350-0404 | 4MJ-4MJ-4MB | 7259-33615 | 7/16–20 | 7/16–20 | 7/16–20 |
| G60350-0505 | 5MJ-5MJ-5MB | 7259-33625 | 1/2–20 | 1/2–20 | 1/2–20 |
| G60350-0606 | 6MJ-6MJ-6MB | 7259-33635 | 9/16–18 | 9/16–18 | 9/16–18 |


## Male JIC 37° Flare on Run to Male O-Ring Boss - Tee - Continued


| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60350-0608 | 6MJ-6MJ-8MB | 7259-06165 | 9/16–18 | 9/16–18 | 3/4–16 |
| G60350-0808 | 8MJ-8MJ-8MB | 7259-33645 | 3/4–16 | 3/4–16 | 3/4–16 |
| G60350-0810 | 8MJ-8MJ-10MB | 7259-07655 | 3/4–16 | 3/4–16 | 7/8–14 |
| G60350-1010 | 10MJ-10MJ-10MB | 7259-33655 | 7/8–14 | 7/8–14 | 7/8–14 |
| G60350-1210 | 12MJ-12MJ-10MB | 7259-08985 | 1 1/16–12 | 1 1/16–12 | 7/8–14 |
| G60350-1212 | 12MJ-12MJ-12MB | 7259-33665 | 1 1/16–12 | 1 1/16–12 | 1 1/16–12 |
| G60350-1414 | 14MJ-14MJ-14MB | 7259-08995 | 1 3/16–12 | 1 3/16–12 | 1 3/16–12 |
| G60350-1616 | 16MJ-16MJ-16MB | 7259-33675 | 1 5/16–12 | 1 5/16–12 | 1 5/16–12 |
| G60350-2020 | 20MJ-20MJ-20MB | 7259-09005 | 1 5/8–12 | 1 5/8–12 | 1 5/8–12 |
| G60350-2424 | 24MJ-24MJ-24MB | 7259-09015 | 1 7/8–12 | 1 7/8–12 | 1 7/8–12 |

## Male O-Ring Boss to Male JIC 37° Flare to Male JIC 37° Flare - Tee

For use up to SAE 100R2 maximum working pressure.









| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60352-0404 | 4MB-4MJ-4MJ | 7259-33685 | 7/16–20 | 7/16–20 | 7/16–20 |
| G60352-0505 | 5MB-5MJ-5MJ | 7259-33695 | 1/2–20 | 1/2–20 | 1/2–20 |
| G60352-0606 | 6MB-6MJ-6MJ | 7259-33705 | 9/16–18 | 9/16–18 | 9/16–18 |
| G60352-0608 | 6MB-8MJ-6MJ | 7259-00185 | 9/16–18 | 3/4–16 | 9/16–18 |
| G60352-0808 | 8MB-8MJ-8MJ | 7259-33715 | 3/4–16 | 3/4–16 | 3/4–16 |
| G60352-1010 | 10MB-10MJ-10MJ | 7259-33725 | 7/8–14 | 7/8–14 | 7/8–14 |
| G60352-1212 | 12MB-12MJ-12MJ | 7259-33735 | 1 1/16–12 | 1 1/16–12 | 1 1/16–12 |
| G60352-1216 | 12MB-12MJ-16MJ | 7259-09025 | 1 1/16–12 | 1 1/16–12 | 1 5/16–12 |
| G60352-1414 | 14MB-14MJ-14MJ | 7259-09035 | 1 3/16–12 | 1 3/16–12 | 1 3/16–12 |
| G60352-1616 | 16MB-16MJ-16MJ | 7259-33745 | 1 5/16–12 | 1 5/16–12 | 1 5/16–12 |
| G60352-2020 | 20MB-20MJ-20MJ | 7259-07535 | 1 5/8–12 | 1 5/8–12 | 1 5/8–12 |
| G60352-2424 | 24MB-24MJ-24MJ | 7259-09045 | 1 7/8–12 | 1 7/8–12 | 1 7/8–12 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female JIC 37° Flare Cap

For use up to SAE 100R2 maximum working pressure.








| Part No. | Descr. | Prod. No. | " |
|---|---|---|---|
| G60401-0002 | 2FJ-CAP | 7259-09865 | 5/16–24 |
| G60401-0003 | 3FJ-CAP | 7259-07435 | 3/8–24 |
| G60401-0004 | 4FJ-CAP | 7259-24305 | 7/16–20 |
| G60401-0005 | 5FJ-CAP | 7259-24315 | 1/2–20 |
| G60401-0006 | 6FJ-CAP | 7259-24325 | 9/16–18 |
| G60401-0008 | 8FJ-CAP | 7259-24335 | 3/4–16 |
| G60401-0010 | 10FJ-CAP | 7259-24345 | 7/8–14 |
| G60401-0012 | 12FJ-CAP | 7259-24355 | 1 1/16–12 |
| G60401-0014 | 14FJ-CAP | 7259-00445 | 1 3/16–12 |
| G60401-0016 | 16FJ-CAP | 7259-24365 | 1 5/16–12 |
| G60401-0020 | 20FJ-CAP | 7253-24375 | 1 5/8–12 |
| G60401-0024 | 24FJ-CAP | 7259-24385 | 1 7/8–12 |
| G60401-0032 | 32FJ-CAP | 7259-24405 | 2 1/2–12 |

# Male JIC 37° Flare Plug

For use up to SAE 100R2 maximum working pressure.









| Part No. | Descr. | Prod. No. | " |
|---|---|---|---|
| G60402-0003 | 3MJ-PLUG | 7259-09775 | 3/8–24 |
| G60402-0004 | 4MJ-PLUG | 7259-22885 | 7/16–20 |
| G60402-0005 | 5MJ-PLUG | 7259-22895 | 1/2–20 |
| G60402-0006 | 6MJ-PLUG | 7259-22905 | 9/16–18 |
| G60402-0008 | 8MJ-PLUG | 7259-22915 | 3/4–16 |
| G60402-0010 | 10MJ-PLUG | 7259-22925 | 7/8–14 |
| G60402-0012 | 12MJ-PLUG | 7259-22935 | 1 1/16–12 |
| G60402-0014 | 14MJ-PLUG | 7259-22945 | 1 3/16–12 |
| G60402-0016 | 16MJ-PLUG | 7259-22955 | 1 5/16–12 |
| G60402-0020 | 20MJ-PLUG | 7259-22965 | 1 5/8–12 |
| G60402-0024 | 24MJ-PLUG | 7259-33755 | 1 7/8–12 |
| G60402-0032 | 32MJ-PLUG | 7259-33765 | 2 1/2–12 |

# Male JIC 37° Flare to Female Braze - On

For use up to SAE 100R2 maximum working pressure.









| Part No. | Descr. | Prod. No. | ⟷ " | " |
|---|---|---|---|---|
| G60405-2020 | 20MJ-20FBO | 7253-28735 | 1 1/4 | 1 5/8–12 |

# Male JIC 37° Flare to Male JIC 37° Flare

For use up to SAE 100R2 maximum working pressure.





| Part No. | Descr. | Prod. No. | " | " |
|---|---|---|---|---|
| G60410-0202 | 2MJ-2MJ | 7259-77775 | 5/16–24 | 5/16–24 |
| G60410-0302 | 3MJ-2MJ | 7259-09065 | 3/8–24 | 5/16–24 |
| G60410-0303 | 3MJ-3MJ | 7259-77785 | 3/8–24 | 3/8–24 |
| G60410-0403 | 4MJ-3MJ | 7259-09075 | 7/16–20 | 3/8–24 |
| G60410-0404 | 4MJ-4MJ | 7259-10125 | 7/16–20 | 7/16–20 |
| G60410-0504 | 5MJ-4MJ | 7259-77795 | 1/2–20 | 7/16–20 |
| G60410-0505 | 5MJ-5MJ | 7259-10735 | 1/2–20 | 1/2–20 |
| G60410-0604 | 6MJ-4MJ | 7259-00285 | 9/16–18 | 7/16–20 |
| G60410-0605 | 6MJ-5MJ | 7259-77805 | 9/16–18 | 1/2–20 |
| G60410-0606 | 6MJ-6MJ | 7259-06265 | 9/16–18 | 9/16–18 |
| G60410-0804 | 8MJ-4MJ | 7259-06505 | 3/4–16 | 7/16–20 |
| G60410-0805 | 8MJ-5MJ | 7259-09085 | 3/4–16 | 1/2–20 |
| G60410-0806 | 8MJ-6MJ | 7259-00075 | 3/4–16 | 9/16–18 |
| G60410-0808 | 8MJ-8MJ | 7259-06275 | 3/4–16 | 3/4–16 |
| G60410-1004 | 10MJ-4MJ | 7259-07195 | 7/8–14 | 7/16–20 |
| G60410-1006 | 10MJ-6MJ | 7259-07805 | 7/8–14 | 9/16–18 |
| G60410-1008 | 10MJ-8MJ | 7259-00375 | 7/8–14 | 3/4–16 |
| G60410-1010 | 10MJ-10MJ | 7259-10225 | 7/8–14 | 7/8–14 |
| G60410-1204 | 12MJ-4MJ | 7259-09095 | 1 1/16–12 | 7/16–20 |
| G60410-1206 | 12MJ-6MJ | 7259-08455 | 1 1/16–12 | 9/16–18 |
| G60410-1208 | 12MJ-8MJ | 7259-77815 | 1 1/16–12 | 3/4–16 |
| G60410-1210 | 12MJ-10MJ | 7259-00565 | 1 1/16–12 | 7/8–14 |
| G60410-1212 | 12MJ-12MJ | 7259-10235 | 1 1/16–12 | 1 1/16–12 |
| G60410-1412 | 14MJ-12MJ | 7259-09105 | 1 3/16–12 | 1 1/16–12 |
| G60410-1414 | 14MJ-14MJ | 7259-77825 | 1 3/16–12 | 1 3/16–12 |
| G60410-1608 | 16MJ-8MJ | 7259-07205 | 1 5/16–12 | 3/4–16 |
| G60410-1610 | 16MJ-10MJ | 7259-07505 | 1 5/16–12 | 7/8–14 |
| G60410-1612 | 16MJ-12MJ | 7259-77835 | 1 5/16–12 | 1 1/16–12 |
| G60410-1616 | 16MJ-16MJ | 7259-10655 | 1 5/16–12 | 1 5/16–12 |


## Male JIC 37° Flare to Male JIC 37° Flare - Continued

| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60410-2012 | 20MJ-12MJ | 7259-09115 | 1 5/8–12 | 1 1/16–12 |
| G60410-2016 | 20MJ-16MJ | 7259-06555 | 1 5/8–12 | 1 5/16–12 |
| G60410-2020 | 20MJ-20MJ | 7259-11145 | 1 5/8–12 | 1 5/8–12 |
| G60410-2412 | 24MJ-12MJ | 7259-09125 | 1 7/8–12 | 1 1/16–12 |
| G60410-2420 | 24MJ-20MJ | 7259-09135 | 1 7/8–12 | 1 5/8–12 |
| G60410-2424 | 24MJ-24MJ | 7259-33845 | 1 7/8–12 | 1 7/8–12 |
| G60410-3232 | 32MJ-32MJ | 7259-33855 | 2 1/2–12 | 2 1/2–12 |

## Male JIC 37° Flare to Male JIC 37° Flare - 90°

For use up to SAE 100R2 maximum working pressure.










| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60417-0202 | 2MJ-2MJ90 | 7259-09145 | 5/16–24 | 5/16–24 |
| G60417-0404 | 4MJ-4MJ90 | 7259-77845 | 7/16–20 | 7/16–20 |
| G60417-0505 | 5MJ-5MJ90 | 7259-05865 | 1/2–20 | 1/2–20 |
| G60417-0604 | 6MJ-4MJ90 | 7259-07925 | 9/16–18 | 7/16–20 |
| G60417-0606 | 6MJ-6MJ90 | 7259-77855 | 9/16–18 | 9/16–18 |
| G60417-0806 | 8MJ-6MJ90 | 7259-06745 | 3/4–16 | 9/16–18 |
| G60417-0808 | 8MJ-8MJ90 | 7259-77865 | 3/4–16 | 3/4–16 |
| G60417-1010 | 10MJ-10MJ90 | 7259-77875 | 7/8–14 | 7/8–14 |
| G60417-1212 | 12MJ-12MJ90 | 7259-77885 | 1 1/16–12 | 1 1/16–12 |
| G60417-1414 | 14MJ-14MJ90 | 7259-08275 | 1 3/16–12 | 1 3/16–12 |
| G60417-1612 | 16MJ-12MJ90 | 7259-09155 | 1 5/16–12 | 1 1/16–12 |
| G60417-1616 | 16MJ-16MJ90 | 7259-77895 | 1 5/16–12 | 1 5/16–12 |
| G60417-2020 | 20MJ-20MJ90 | 7259-07095 | 1 5/8–12 | 1 5/8–12 |
| G60417-2424 | 24MJ-24MJ90 | 7259-07105 | 1 7/8–12 | 1 7/8–12 |
| G60417-3232 | 32MJ-32MJ90 | 7259-08465 | 2 1/2–12 | 2 1/2–12 |

# Male JIC 37° Flare to Female JIC 37° Flare

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60420-0406 | 4MJ-6FJ | 7259-33865 | 7/16–20 | 9/16–18 |
| G60420-0504 | 5MJ-4FJ | 7259-07445 | 1/2–20 | 7/16–20 |
| G60420-0506 | 5MJ-6FJ | 7259-09175 | 1/2–20 | 9/16–18 |
| G60420-0604 | 6MJ-4FJ | 7259-00015 | 9/16–18 | 7/16–20 |
| G60420-0606 | 6MJ-6FJ | 7259-09195 | 9/16–18 | 9/16–18 |
| G60420-0608 | 6MJ-8FJ | 7259-33875 | 9/16–18 | 3/4–16 |
| G60420-0610 | 6MJ-10FJ | 7259-33885 | 9/16–18 | 7/8–14 |
| G60420-0804 | 8MJ-4FJ | 7259-00935 | 3/4–16 | 7/16–20 |
| G60420-0808 | 8MJ-8FJ | 7259-06135 | 3/4–16 | 3/4–16 |
| G60420-0810 | 8MJ-10FJ | 7253-33895 | 3/4–16 | 7/8–14 |
| G60420-0812 | 8MJ-12FJ | 7259-33905 | 3/4–16 | 1 1/16–12 |
| G60420-1004 | 10MJ-4FJ | 7259-05915 | 7/8–14 | 7/16–20 |
| G60420-1006 | 10MJ-6FJ | 7259-05375 | 7/8–14 | 9/16–18 |
| G60420-1008 | 10MJ-8FJ | 7259-00705 | 7/8–14 | 3/4–16 |
| G60420-1012 | 10MJ-12FJ | 7259-33915 | 7/8–14 | 1 1/16–12 |
| G60420-1016 | 10MJ-16FJ | 7259-33925 | 7/8–14 | 1 5/16–12 |
| G60420-1204 | 12MJ-4FJ | 7259-05235 | 1 1/16–12 | 7/16–20 |
| G60420-1206 | 12MJ-6FJ | 7259-00145 | 1 1/16–12 | 9/16–18 |
| G60420-1208 | 12MJ-8FJ | 7259-00115 | 1 1/16–12 | 3/4–16 |
| G60420-1212 | 12MJ-12FJ | 7259-09205 | 1 1/16–12 | 1 1/16–12 |
| G60420-1216 | 12MJ-16FJ | 7253-33935 | 1 1/16–12 | 1 5/16–12 |
| G60420-1220 | 12MJ-20FJ | 7253-33945 | 1 1/16–12 | 1 5/8–12 |
| G60420-1616 | 16MJ-16FJ | 7259-09215 | 1 5/16–12 | 1 5/16–12 |
| G60420-1620 | 16MJ-20FJ | 7259-33955 | 1 5/16–12 | 1 5/8–12 |
| G60420-2016 | 20MJ-16FJ | 7259-05085 | 1 5/8–12 | 1 5/16–12 |

# Male JIC 37° Flare to Female JIC 37° Flare Swivel - 90°

For use up to SAE 100R2 maximum working pressure.




| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60422-0404 | 4MJ-4FJX90 | 7259-23285 | 7/16–20 | 7/16–20 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male JIC 37° Flare to Female JIC 37° Flare Swivel - 90° - Continued


| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60422-0505 | 5MJ-5FJX90 | 7259-24025 | 1/2–20 | 1/2–20 |
| G60422-0604 | 6MJ-4FJX90 | 7259-06905 | 9/16–18 | 7/16–20 |
| G60422-0606 | 6MJ-6FJX90 | 7259-23295 | 9/16–18 | 9/16–18 |
| G60422-0806 | 8MJ-6FJX90 | 7259-06205 | 3/4–16 | 9/16–18 |
| G60422-0808 | 8MJ-8FJX90 | 7259-23305 | 3/4–16 | 3/4–16 |
| G60422-0810 | 8MJ-10FJX90 | 7259-06385 | 3/4–16 | 7/8–14 |
| G60422-1010 | 10MJ-10FJX90 | 7259-23315 | 7/8–14 | 7/8–14 |
| G60422-1212 | 12MJ-12FJX90 | 7259-23325 | 1 1/16–12 | 1 1/16–12 |
| G60422-1414 | 14MJ-14FJX90 | 7259-06215 | 1 3/16–12 | 1 3/16–12 |
| G60422-1616 | 16MJ-16FJX90 | 7259-23335 | 1 5/16–12 | 1 5/16–12 |
| G60422-2020 | 20MJ-20FJX90 | 7259-24075 | 1 5/8–12 | 1 5/8–12 |
| G60422-2424 | 24MJ-24FJX90 | 7259-24085 | 1 7/8–12 | 1 7/8–12 |
| G60422-3232 | 32MJ-32FJX90 | 7259-24095 | 2 1/2–12 | 2 1/2–12 |

## Male JIC 37° Flare to Female JIC 37° Flare Swivel - 45°

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60424-0404 | 4MJ-4FJX45 | 7259-23215 | 7/16–20 | 7/16–20 |
| G60424-0505 | 5MJ-5FJX45 | 7259-33965 | 1/2–20 | 1/2–20 |
| G60424-0606 | 6MJ-6FJX45 | 7259-23225 | 9/16–18 | 9/16–18 |
| G60424-0808 | 8MJ-8FJX45 | 7259-23235 | 3/4–16 | 3/4–16 |
| G60424-1010 | 10MJ-10FJX45 | 7259-23245 | 7/8–14 | 7/8–14 |
| G60424-1212 | 12MJ-12FJX45 | 7259-23255 | 1 1/16–12 | 1 1/16–12 |
| G60424-1414 | 14MJ-14FJX45 | 7259-06995 | 1 3/16–12 | 1 3/16–12 |
| G60424-1616 | 16MJ-16FJX45 | 7259-23265 | 1 5/16–12 | 1 5/16–12 |
| G60424-2020 | 20MJ-20FJX45 | 7259-23275 | 1 5/8–12 | 1 5/8–12 |
| G60424-2424 | 24MJ-24FJX45 | 7259-05455 | 1 7/8–12 | 1 7/8–12 |
| G60424-3232 | 32MJ-32FJX45 | 7259-07935 | 2 1/2–12 | 2 1/2–12 |

# Male JIC 37° Flare to Male JIC 37° Flare Bulkhead

For use up to SAE 100R2 maximum working pressure.









| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60445-0303 | 3MJ-3BKHD | 7259-09295 | 3/8–24 | 3/8–24 |
| G60445-0404 | 4MJ-4BKHD | 7259-24505 | 7/16–20 | 7/16–20 |
| G60445-0505 | 5MJ-5BKHD | 7259-24515 | 1/2–20 | 1/2–20 |
| G60445-0606 | 6MJ-6BKHD | 7259-24525 | 9/16–18 | 9/16–18 |
| G60445-0808 | 8MJ-8BKHD | 7259-24535 | 3/4–16 | 3/4–16 |
| G60445-1010 | 10MJ-10BKHD | 7259-24545 | 7/8–14 | 7/8–14 |
| G60445-1212 | 12MJ-12BKHD | 7259-24555 | 1 1/16–12 | 1 1/16–12 |
| G60445-1414 | 14MJ-14BKHD | 7259-08495 | 1 3/16–12 | 1 3/16–12 |
| G60445-1616 | 16MJ-16BKHD | 7259-24565 | 1 5/16–12 | 1 5/16–12 |
| G60445-2020 | 20MJ-20BKHD | 7259-34155 | 1 5/8–12 | 1 5/8–12 |
| G60445-2424 | 24MJ-24BKHD | 7259-34165 | 1 7/8–12 | 1 7/8–12 |

# Male JIC 37° Flare to Male JIC 37° Flare Bulkhead - 45°

For use up to SAE 100R2 maximum working pressure.









| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60446-0404 | 4MJ-4BKHD45 | 7259-34175 | 7/16–20 | 7/16–20 |
| G60446-0505 | 5MJ-5BKHD45 | 7259-34185 | 1/2–20 | 1/2–20 |
| G60446-0606 | 6MJ-6BKHD45 | 7259-34195 | 9/16–18 | 9/16–18 |
| G60446-0808 | 8MJ-8BKHD45 | 7259-34205 | 3/4–16 | 3/4–16 |
| G60446-1010 | 10MJ-10BKHD45 | 7259-34215 | 7/8–14 | 7/8–14 |
| G60446-1212 | 12MJ-12BKHD45 | 7259-34225 | 1 1/16–12 | 1 1/16–12 |
| G60446-1616 | 16MJ-16BKHD45 | 7259-34235 | 1 5/16–12 | 1 5/16–12 |

# Male JIC 37° Flare to Male JIC 37° Flare Bulkhead - 90°

For use up to SAE 100R2 maximum working pressure.









| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60447-0404 | 4MJ-4BKHD90 | 7259-34255 | 7/16–20 | 7/16–20 |
| G60447-0505 | 5MJ-5BKHD90 | 7259-34265 | 1/2–20 | 1/2–20 |
| G60447-0606 | 6MJ-6BKHD90 | 7259-34275 | 9/16–18 | 9/16–18 |
| G60447-0808 | 8MJ-8BKHD90 | 7259-34285 | 3/4–16 | 3/4–16 |
| G60447-1010 | 10MJ-10BKHD90 | 7259-34295 | 7/8–14 | 7/8–14 |
| G60447-1212 | 12MJ-12BKHD90 | 7259-34305 | 1 1/16–12 | 1 1/16–12 |
| G60447-1414 | 14MJ-14BKHD90 | 7259-09315 | 1 3/16–12 | 1 3/16–12 |
| G60447-1616 | 16MJ-16BKHD90 | 7259-34315 | 1 5/16–12 | 1 5/16–12 |
| G60447-2020 | 20MJ-20BKHD90 | 7259-34325 | 1 5/8–12 | 1 5/8–12 |
| G60447-2424 | 24MJ-24BKHD90 | 7259-09325 | 1 7/8–12 | 1 7/8–12 |

# Male JIC 37° Flare Tee

For use up to SAE 100R2 maximum working pressure.





| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60469-0202 | 2MJ-2MJ-2MJ | 7259-77905 | 5/16–24 | 5/16–24 | 5/16–24 |
| G60469-0303 | 3MJ-3MJ-3MJ | 7259-08095 | 3/8–24 | 3/8–24 | 3/8–24 |
| G60469-0404 | 4MJ-4MJ-4MJ | 7259-23345 | 7/16–20 | 7/16–20 | 7/16–20 |
| G60469-0505 | 5MJ-5MJ-5MJ | 7259-34335 | 1/2–20 | 1/2–20 | 1/2–20 |
| G60469-0606 | 6MJ-6MJ-6MJ | 7259-23355 | 9/16–18 | 9/16–18 | 9/16–18 |
| G60469-0608 | 6MJ-6MJ-8MJ | 7253-34345 | 9/16–18 | 9/16–18 | 3/4–16 |
| G60469-0808 | 8MJ-8MJ-8MJ | 7259-23365 | 3/4–16 | 3/4–16 | 3/4–16 |
| G60469-1010 | 10MJ-10MJ-10MJ | 7259-23375 | 7/8–14 | 7/8–14 | 7/8–14 |
| G60469-1212 | 12MJ-12MJ-12MJ | 7259-23385 | 1 1/16–12 | 1 1/16–12 | 1 1/16–12 |


## Male JIC 37° Flare Tee - Continued


| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60469-1414 | 14MJ-14MJ-14MJ | 7259-09335 | 1 3/16–12 | 1 3/16–12 | 1 3/16–12 |
| G60469-1612 | 16MJ-16MJ-12MJ | 7259-34365 | 1 5/16–12 | 1 5/16–12 | 1 1/16–12 |
| G60469-1616 | 16MJ-16MJ-16MJ | 7259-23395 | 1 5/16–12 | 1 5/16–12 | 1 5/16–12 |
| G60469-2020 | 20MJ-20MJ-20MJ | 7259-23405 | 1 5/8–12 | 1 5/8–12 | 1 5/8–12 |
| G60469-2424 | 24MJ-24MJ-24MJ | 7259-07555 | 1 7/8–12 | 1 7/8–12 | 1 7/8–12 |
| G60469-3232 | 32MJ-32MJ-32MJ | 7259-07455 | 2 1/2–12 | 2 1/2–12 | 2 1/2–12 |

## Male JIC 37° Flare on Run to Female JIC 37° Flare Swivel - Tee

For use up to SAE 100R2 maximum working pressure.











| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60470-0404 | 4MJ-4MJ-4FJX | 7259-24805 | 7/16–20 | 7/16–20 | 7/16–20 |
| G60470-0505 | 5MJ-5MJ-5FJX | 7259-06535 | 1/2–20 | 1/2–20 | 1/2–20 |
| G60470-0606 | 6MJ-6MJ-6FJX | 7259-24815 | 9/16–18 | 9/16–18 | 9/16–18 |
| G60470-0808 | 8MJ-8MJ-8FJX | 7259-24825 | 3/4–16 | 3/4–16 | 3/4–16 |
| G60470-1010 | 10MJ-10MJ-10FJX | 7259-34405 | 7/8–14 | 7/8–14 | 7/8–14 |
| G60470-1212 | 12MJ-12MJ-12FJX | 7259-24835 | 1 1/16–12 | 1 1/16–12 | 1 1/16–12 |
| G60470-1414 | 14MJ-14MJ-14FJX | 7259-07945 | 1 3/16–12 | 1 3/16–12 | 1 3/16–12 |
| G60470-1616 | 16MJ-16MJ-16FJX | 7259-24845 | 1 5/16–12 | 1 5/16–12 | 1 5/16–12 |
| G60470-2020 | 20MJ-20MJ-20FJX | 7259-34415 | 1 5/8–12 | 1 5/8–12 | 1 5/8–12 |
| G60470-2424 | 24MJ-24MJ-24FJX | 7259-08505 | 1 7/8–12 | 1 7/8–12 | 1 7/8–12 |
| G60470-3232 | 32MJ-32MJ-32FJX | 7259-09345 | 2 1/2–12 | 2 1/2–12 | 2 1/2–12 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male JIC 37° Flare on Run to Male JIC 37° Flare Bulkhead - Tee

For use up to SAE 100R2 maximum working pressure.









| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60471-0404 | 4MJ-4MJ-4BKHD | 7259-34425 | 7/16–20 | 7/16–20 | 7/16–20 |
| G60471-0505 | 5MJ-5MJ-5BKHD | 7259-34435 | 1/2–20 | 1/2–20 | 1/2–20 |
| G60471-0606 | 6MJ-6MJ-6BKHD | 7259-34445 | 9/16–18 | 9/16–18 | 9/16–18 |
| G60471-0808 | 8MJ-8MJ-8BKHD | 7259-34455 | 3/4–16 | 3/4–16 | 3/4–16 |
| G60471-1010 | 10MJ-10MJ-10BKHD | 7259-34465 | 7/8–14 | 7/8–14 | 7/8–14 |
| G60471-1212 | 12MJ-12MJ-12BKHD | 7259-34475 | 1 1/16–12 | 1 1/16–12 | 1 1/16–12 |
| G60471-1616 | 16MJ-16MJ-16BKHD | 7259-34485 | 1 5/16–12 | 1 5/16–12 | 1 5/16–12 |

# Male JIC 37° Flare to Male JIC 37° Flare Bulkhead to Male JIC 37° Flare - Tee

For use up to SAE 100R2 maximum working pressure.










| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60472-0404 | 4MJ-4BKHD-4MJ | 7259-34495 | 7/16–20 | 7/16–20 | 7/16–20 |
| G60472-0606 | 6MJ-6BKHD-6MJ | 7259-34515 | 9/16–18 | 9/16–18 | 9/16–18 |
| G60472-0808 | 8MJ-8BKHD-8MJ | 7259-34525 | 3/4–16 | 3/4–16 | 3/4–16 |
| G60472-1010 | 10MJ-10BKHD-10MJ | 7259-34535 | 7/8–14 | 7/8–14 | 7/8–14 |
| G60472-1212 | 12MJ-12BKHD-12MJ | 7259-34545 | 1 1/16–12 | 1 1/16–12 | 1 1/16–12 |
| G60472-1616 | 16MJ-16BKHD-16MJ | 7259-34555 | 1 5/16–12 | 1 5/16–12 | 1 5/16–12 |

# Male JIC 37° Flare to Female JIC 37° Flare Swivel to Male JIC 37° Flare - Tee

For use up to SAE 100R2 maximum working pressure.













| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60473-0404 | 4MJ-4FJX-4MJ | 7259-24705 | 7/16–20 | 7/16–20 | 7/16–20 |
| G60473-0505 | 5MJ-5FJX-5MJ | 7259-77915 | 1/2–20 | 1/2–20 | 1/2–20 |
| G60473-0606 | 6MJ-6FJX-6MJ | 7259-24725 | 9/16–18 | 9/16–18 | 9/16–18 |
| G60473-0808 | 8MJ-8FJX-8MJ | 7259-24735 | 3/4–16 | 3/4–16 | 3/4–16 |
| G60473-1010 | 10MJ-10FJX-10MJ | 7259-24745 | 7/8–14 | 7/8–14 | 7/8–14 |
| G60473-1212 | 12MJ-12FJX-12MJ | 7259-24755 | 1 1/16–12 | 1 1/16–12 | 1 1/16–12 |
| G60473-1414 | 14MJ-14FJX-14MJ | 7259-08325 | 1 3/16–12 | 1 3/16–12 | 1 3/16–12 |
| G60473-1616 | 16MJ-16FJX-16MJ | 7259-24765 | 1 5/16–12 | 1 5/16–12 | 1 5/16–12 |
| G60473-2020 | 20MJ-20FJX-20MJ | 7259-77925 | 1 5/8–12 | 1 5/8–12 | 1 5/8–12 |
| G60473-2424 | 24MJ-24FJX-24MJ | 7259-07955 | 1 7/8–12 | 1 7/8–12 | 1 7/8–12 |
| G60473-3232 | 32MJ-32FJX-32MJ | 7259-09355 | 2 1/2–12 | 2 1/2–12 | 2 1/2–12 |

# Male JIC 37° Flare to Male Pipe NPTF

For use up to SAE 100R2 maximum working pressure.





| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60490-0202 | 2MJ-2MP | 7259-77935 | 5/16–24 | 1/8–27 |
| G60490-0302 | 3MJ-2MP | 7259-77945 | 3/8–24 | 1/8–27 |
| G60490-0402 | 4MJ-2MP | 7259-10085 | 7/16–20 | 1/8–27 |
| G60490-0404 | 4MJ-4MP | 7259-04195 | 7/16–20 | 1/4–18 |
| G60490-0406 | 4MJ-6MP | 7259-10385 | 7/16–20 | 3/8–18 |
| G60490-0408 | 4MJ-8MP | 7259-70455 | 7/16–20 | 1/2–14 |
| G60490-0412 | 4MJ-12MP | 7259-07215 | 7/16–20 | 3/4–14 |
| G60490-0502 | 5MJ-2MP | 7259-10995 | 1/2–20 | 1/8–27 |
| G60490-0504 | 5MJ-4MP | 7259-10415 | 1/2–20 | 1/4–18 |
| G60490-0506 | 5MJ-6MP | 7259-25665 | 1/2–20 | 3/8–18 |
| G60490-0508 | 5MJ-8MP | 7259-07835 | 1/2–20 | 1/2–14 |


# Male JIC 37° Flare to Male Pipe NPTF - Continued


| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60490-0602 | 6MJ-2MP | 7259-10565 | 9/16–18 | 1/8–27 |
| G60490-0604 | 6MJ-4MP | 7259-25635 | 9/16–18 | 1/4–18 |
| G60490-0606 | 6MJ-6MP | 7259-04225 | 9/16–18 | 3/8–18 |
| G60490-0608 | 6MJ-8MP | 7259-10205 | 9/16–18 | 1/2–14 |
| G60490-0612 | 6MJ-12MP | 7259-00425 | 9/16–18 | 3/4–14 |
| G60490-0802 | 8MJ-2MP | 7259-09875 | 3/4–16 | 1/8–27 |
| G60490-0804 | 8MJ-4MP | 7259-10435 | 3/4–16 | 1/4–18 |
| G60490-0806 | 8MJ-6MP | 7259-10105 | 3/4–16 | 3/8–18 |
| G60490-0808 | 8MJ-8MP | 7259-04235 | 3/4–16 | 1/2–14 |
| G60490-0812 | 8MJ-12MP | 7259-10545 | 3/4–16 | 3/4–14 |
| G60490-0816 | 8MJ-16MP | 7259-05835 | 3/4–16 | 1–11 1/2 |
| G60490-1004 | 10MJ-4MP | 7259-07965 | 7/8–14 | 1/4–18 |
| G60490-1006 | 10MJ-6MP | 7259-10785 | 7/8–14 | 3/8–18 |
| G60490-1008 | 10MJ-8MP | 7259-25715 | 7/8–14 | 1/2–14 |
| G60490-1012 | 10MJ-12MP | 7259-10595 | 7/8–14 | 3/4–14 |
| G60490-1206 | 12MJ-6MP | 7259-07225 | 1 1/16–12 | 3/8–18 |
| G60490-1208 | 12MJ-8MP | 7259-10255 | 1 1/16–12 | 1/2–14 |
| G60490-1212 | 12MJ-12MP | 7259-25735 | 1 1/16–12 | 3/4–14 |
| G60490-1216 | 12MJ-16MP | 7259-10355 | 1 1/16–12 | 1–11 1/2 |
| G60490-1220 | 12MJ-20MP | 7259-05765 | 1 1/16–12 | 1 1/4–11 1/2 |
| G60490-1224 | 12MJ-24MP | 7259-07665 | 1 1/16–12 | 1 1/2–11 1/2 |
| G60490-1412 | 14MJ-12MP | 7259-77965 | 1 3/16–12 | 3/4–14 |
| G60490-1416 | 14MJ-16MP | 7259-07975 | 1 3/16–12 | 1–11 1/2 |
| G60490-1608 | 16MJ-8MP | 7259-06095 | 1 5/16–12 | 1/2–14 |
| G60490-1612 | 16MJ-12MP | 7259-10485 | 1 5/16–12 | 3/4–14 |
| G60490-1616 | 16MJ-16MP | 7259-04275 | 1 5/16–12 | 1–11 1/2 |
| G60490-1620 | 16MJ-20MP | 7259-34565 | 1 5/16–12 | 1 1/4–11 1/2 |
| G60490-1624 | 16MJ-24MP | 7259-06065 | 1 5/16–12 | 1 1/2–11 1/2 |
| G60490-2012 | 20MJ-12MP | 7259-07675 | 1 5/8–12 | 3/4–14 |
| G60490-2016 | 20MJ-16MP | 7259-11465 | 1 5/8–12 | 1–11 1/2 |
| G60490-2020 | 20MJ-20MP | 7259-10465 | 1 5/8–12 | 1 1/4–11 1/2 |
| G60490-2024 | 20MJ-24MP | 7259-34575 | 1 5/8–12 | 1 1/2–11 1/2 |
| G60490-2416 | 24MJ-16MP | 7259-07125 | 1 7/8–12 | 1–11 1/2 |
| G60490-2420 | 24MJ-20MP | 7259-34585 | 1 7/8–12 | 1 1/4–11 1/2 |
| G60490-2424 | 24MJ-24MP | 7259-11245 | 1 7/8–12 | 1 1/2–11 1/2 |
| G60490-2432 | 24MJ-32MP | 7259-09375 | 1 7/8–12 | 2–11 1/2 |
| G60490-3216 | 32MJ-16MP | 7259-09385 | 2 1/2–12 | 1–11 1/2 |
| G60490-3220 | 32MJ-20MP | 7259-09395 | 2 1/2–12 | 1 1/4–11 1/2 |
| G60490-3224 | 32MJ-24MP | 7259-34595 | 2 1/2–12 | 1 1/2–11 1/2 |
| G60490-3232 | 32MJ-32MP | 7259-11365 | 2 1/2–12 | 2–11 1/2 |

# Male JIC 37° Flare to Male Pipe NPTF - 45°

For use up to SAE 100R2 maximum working pressure.









| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60497-0202 | 2MJ-2MP45 | 7259-09415 | 5/16–24 | 1/8–27 |
| G60497-0302 | 3MJ-2MP45 | 7259-77975 | 3/8–24 | 1/8–27 |
| G60497-0402 | 4MJ-2MP45 | 7259-10505 | 7/16–20 | 1/8–27 |
| G60497-0404 | 4MJ-4MP45 | 7259-10825 | 7/16–20 | 1/4–18 |
| G60497-0406 | 4MJ-6MP45 | 7259-34605 | 7/16–20 | 3/8–18 |
| G60497-0408 | 4MJ-8MP45 | 7259-09425 | 7/16–20 | 1/2–14 |
| G60497-0502 | 5MJ-2MP45 | 7259-11635 | 1/2–20 | 1/8–27 |
| G60497-0504 | 5MJ-4MP45 | 7259-11265 | 1/2–20 | 1/4–18 |
| G60497-0506 | 5MJ-6MP45 | 7259-07685 | 1/2–20 | 3/8–18 |
| G60497-0602 | 6MJ-2MP45 | 7259-77985 | 9/16–18 | 1/8–27 |
| G60497-0604 | 6MJ-4MP45 | 7259-10925 | 9/16–18 | 1/4–18 |
| G60497-0606 | 6MJ-6MP45 | 7259-10715 | 9/16–18 | 3/8–18 |
| G60497-0608 | 6MJ-8MP45 | 7259-11135 | 9/16–18 | 1/2–14 |
| G60497-0612 | 6MJ-12MP45 | 7259-07315 | 9/16–18 | 3/4–14 |
| G60497-0804 | 8MJ-4MP45 | 7259-77995 | 3/4–16 | 1/4–18 |
| G60497-0806 | 8MJ-6MP45 | 7259-10695 | 3/4–16 | 3/8–18 |
| G60497-0808 | 8MJ-8MP45 | 7259-10495 | 3/4–16 | 1/2–14 |
| G60497-0812 | 8MJ-12MP45 | 7259-11395 | 3/4–16 | 3/4–14 |
| G60497-1006 | 10MJ-6MP45 | 7259-11505 | 7/8–14 | 3/8–18 |
| G60497-1008 | 10MJ-8MP45 | 7259-10395 | 7/8–14 | 1/2–14 |
| G60497-1012 | 10MJ-12MP45 | 7259-34615 | 7/8–14 | 3/4–14 |
| G60497-1208 | 12MJ-8MP45 | 7259-11375 | 1 1/16–12 | 1/2–14 |
| G60497-1212 | 12MJ-12MP45 | 7259-10845 | 1 1/16–12 | 3/4–14 |
| G60497-1216 | 12MJ-16MP45 | 7259-05775 | 1 1/16–12 | 1–11 1/2 |
| G60497-1412 | 14MJ-12MP45 | 7259-09885 | 1 3/16–12 | 3/4–14 |
| G60497-1608 | 16MJ-8MP45 | 7259-09435 | 1 5/16–12 | 1/2–14 |
| G60497-1612 | 16MJ-12MP45 | 7259-11585 | 1 5/16–12 | 3/4–14 |
| G60497-1616 | 16MJ-16MP45 | 7259-11035 | 1 5/16–12 | 1–11 1/2 |
| G60497-1620 | 16MJ-20MP45 | 7259-07845 | 1 5/16–12 | 1 1/4–11 1/2 |
| G60497-2016 | 20MJ-16MP45 | 7259-07985 | 1 5/8–12 | 1–11 1/2 |
| G60497-2020 | 20MJ-20MP45 | 7259-11485 | 1 5/8–12 | 1 1/4–11 1/2 |
| G60497-2024 | 20MJ-24MP45 | 7259-08105 | 1 5/8–12 | 1 1/2–11 1/2 |
| G60497-2424 | 24MJ-24MP45 | 7259-11695 | 1 7/8–12 | 1 1/2–11 1/2 |
| G60497-3232 | 32MJ-32MP45 | 7259-11675 | 2 1/2–12 | 2–11 1/2 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male JIC 37° Flare to Male Pipe NPTF - 90°

For use up to SAE 100R2 maximum working pressure.













| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60499-0202 | 2MJ-2MP90 | 7259-11755 | 5/16–24 | 1/8–27 |
| G60499-0302 | 3MJ-2MP90 | 7259-78005 | 3/8–24 | 1/8–27 |
| G60499-0402 | 4MJ-2MP90 | 7259-10175 | 7/16–20 | 1/8–27 |
| G60499-0404 | 4MJ-4MP90 | 7259-10195 | 7/16–20 | 1/4–18 |
| G60499-0406 | 4MJ-6MP90 | 7259-34645 | 7/16–20 | 3/8–18 |
| G60499-0408 | 4MJ-8MP90 | 7259-09815 | 7/16–20 | 1/2–14 |
| G60499-0412 | 4MJ-12MP90 | 7259-07695 | 7/16–20 | 3/4–14 |
| G60499-0502 | 5MJ-2MP90 | 7259-11425 | 1/2–20 | 1/8–27 |
| G60499-0504 | 5MJ-4MP90 | 7259-11045 | 1/2–20 | 1/4–18 |
| G60499-0506 | 5MJ-6MP90 | 7259-34655 | 1/2–20 | 3/8–18 |
| G60499-0602 | 6MJ-2MP90 | 7259-11085 | 9/16–18 | 1/8–27 |
| G60499-0604 | 6MJ-4MP90 | 7259-28385 | 9/16–18 | 1/4–18 |
| G60499-0606 | 6MJ-6MP90 | 7259-28185 | 9/16–18 | 3/8–18 |
| G60499-0608 | 6MJ-8MP90 | 7259-10185 | 9/16–18 | 1/2–14 |
| G60499-0612 | 6MJ-12MP90 | 7259-05545 | 9/16–18 | 3/4–14 |
| G60499-0804 | 8MJ-4MP90 | 7259-11025 | 3/4–16 | 1/4–18 |
| G60499-0806 | 8MJ-6MP90 | 7259-10165 | 3/4–16 | 3/8–18 |
| G60499-0808 | 8MJ-8MP90 | 7259-28205 | 3/4–16 | 1/2–14 |
| G60499-0812 | 8MJ-12MP90 | 7259-10275 | 3/4–16 | 3/4–14 |
| G60499-0816 | 8MJ-16MP90 | 7259-07575 | 3/4–16 | 1–11 1/2 |
| G60499-1006 | 10MJ-6MP90 | 7259-11195 | 7/8–14 | 3/8–18 |
| G60499-1008 | 10MJ-8MP90 | 7259-28375 | 7/8–14 | 1/2–14 |
| G60499-1012 | 10MJ-12MP90 | 7259-10555 | 7/8–14 | 3/4–14 |
| G60499-1016 | 10MJ-16MP90 | 7259-07705 | 7/8–14 | 1–11 1/2 |
| G60499-1206 | 12MJ-6MP90 | 7259-07995 | 1 1/16–12 | 3/8–18 |
| G60499-1208 | 12MJ-8MP90 | 7259-10795 | 1 1/16–12 | 1/2–14 |
| G60499-1212 | 12MJ-12MP90 | 7259-28395 | 1 1/16–12 | 3/4–14 |
| G60499-1216 | 12MJ-16MP90 | 7259-34665 | 1 1/16–12 | 1–11 1/2 |
| G60499-1220 | 12MJ-20MP90 | 7259-06835 | 1 1/16–12 | 1 1/4–11 1/2 |
| G60499-1408 | 14MJ-8MP90 | 7259-09445 | 1 3/16–12 | 1/2–14 |
| G60499-1412 | 14MJ-12MP90 | 7259-07585 | 1 3/16–12 | 3/4–14 |
| G60499-1608 | 16MJ-8MP90 | 7259-09455 | 1 5/16–12 | 1/2–14 |
| G60499-1612 | 16MJ-12MP90 | 7259-11205 | 1 5/16–12 | 3/4–14 |
| G60499-1616 | 16MJ-16MP90 | 7259-28405 | 1 5/16–12 | 1–11 1/2 |
| G60499-1620 | 16MJ-20MP90 | 7259-34675 | 1 5/16–12 | 1 1/4–11 1/2 |
| G60499-1624 | 16MJ-24MP90 | 7259-07715 | 1 5/16–12 | 1 1/2–11 1/2 |
| G60499-2016 | 20MJ-16MP90 | 7259-11565 | 1 5/8–12 | 1–11 1/2 |
| G60499-2020 | 20MJ-20MP90 | 7259-10905 | 1 5/8–12 | 1 1/4–11 1/2 |
| G60499-2024 | 20MJ-24MP90 | 7259-34685 | 1 5/8–12 | 1 1/2–11 1/2 |
| G60499-2420 | 24MJ-20MP90 | 7259-34695 | 1 7/8–12 | 1 1/4–11 1/2 |
| G60499-2424 | 24MJ-24MP90 | 7259-11445 | 1 7/8–12 | 1 1/2–11 1/2 |
| G60499-3224 | 32MJ-24MP90 | 7259-08335 | 2 1/2–12 | 1 1/2–11 1/2 |
| G60499-3232 | 32MJ-32MP90 | 7259-11685 | 2 1/2–12 | 2–11 1/2 |

# Male JIC 37° Flare to Female Pipe NPTF

For use up to SAE 100R2 maximum working pressure.









| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60510-0202 | 2MJ-2FP | 7259-78015 | 5/16–24 | 1/8–27 |
| G60510-0302 | 3MJ-2FP | 7259-08515 | 3/8–24 | 1/8–27 |
| G60510-0304 | 3MJ-4FP | 7259-08525 | 3/8–24 | 1/4–18 |
| G60510-0402 | 4MJ-2FP | 7259-11165 | 7/16–20 | 1/8–27 |
| G60510-0404 | 4MJ-4FP | 7259-10965 | 7/16–20 | 1/4–18 |
| G60510-0406 | 4MJ-6FP | 7259-06915 | 7/16–20 | 3/8–18 |
| G60510-0408 | 4MJ-8FP | 7259-09475 | 7/16–20 | 1/2–14 |
| G60510-0502 | 5MJ-2FP | 7259-11665 | 1/2–20 | 1/8–27 |
| G60510-0504 | 5MJ-4FP | 7259-11615 | 1/2–20 | 1/4–18 |
| G60510-0602 | 6MJ-2FP | 7259-09485 | 9/16–18 | 1/8–27 |
| G60510-0604 | 6MJ-4FP | 7259-10515 | 9/16–18 | 1/4–18 |
| G60510-0606 | 6MJ-6FP | 7259-10685 | 9/16–18 | 3/8–18 |
| G60510-0608 | 6MJ-8FP | 7259-34715 | 9/16–18 | 1/2–14 |
| G60510-0804 | 8MJ-4FP | 7259-09495 | 3/4–16 | 1/4–18 |
| G60510-0806 | 8MJ-6FP | 7259-10945 | 3/4–16 | 3/8–18 |
| G60510-0808 | 8MJ-8FP | 7259-10605 | 3/4–16 | 1/2–14 |
| G60510-0812 | 8MJ-12FP | 7259-34725 | 3/4–16 | 3/4–14 |
| G60510-1006 | 10MJ-6FP | 7259-34735 | 7/8–14 | 3/8–18 |
| G60510-1008 | 10MJ-8FP | 7259-10805 | 7/8–14 | 1/2–14 |
| G60510-1012 | 10MJ-12FP | 7259-34745 | 7/8–14 | 3/4–14 |
| G60510-1208 | 12MJ-8FP | 7259-34755 | 1 1/16–12 | 1/2–14 |
| G60510-1212 | 12MJ-12FP | 7259-10675 | 1 1/16–12 | 3/4–14 |
| G60510-1216 | 12MJ-16FP | 7259-06655 | 1 1/16–12 | 1–11 1/2 |
| G60510-1412 | 14MJ-12FP | 7259-08345 | 1 3/16–12 | 3/4–14 |
| G60510-1612 | 16MJ-12FP | 7259-07005 | 1 5/16–12 | 3/4–14 |
| G60510-1616 | 16MJ-16FP | 7259-10985 | 1 5/16–12 | 1–11 1/2 |
| G60510-1620 | 16MJ-20FP | 7259-34765 | 1 5/16–12 | 1 1/4–11 1/2 |
| G60510-2016 | 20MJ-16FP | 7259-08535 | 1 5/8–12 | 1–11 1/2 |
| G60510-2020 | 20MJ-20FP | 7259-25925 | 1 5/8–12 | 1 1/4–11 1/2 |
| G60510-2424 | 24MJ-24FP | 7259-25935 | 1 7/8–12 | 1 1/2–11 1/2 |
| G60510-3232 | 32MJ-32FP | 7259-34775 | 2 1/2–12 | 2–11 1/2 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male JIC 37° Flare to Female Pipe NPTF - 90°

For use up to SAE 100R2 maximum working pressure.













| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60514-0402 | 4MJ-2FP90 | 7259-25105 | 7/16–20 | 1/8–27 |
| G60514-0404 | 4MJ-4FP90 | 7259-34785 | 7/16–20 | 1/4–18 |
| G60514-0502 | 5MJ-2FP90 | 7259-07365 | 1/2–20 | 1/8–27 |
| G60514-0504 | 5MJ-4FP90 | 7259-34805 | 1/2–20 | 1/4–18 |
| G60514-0602 | 6MJ-2FP90 | 7259-09505 | 9/16–18 | 1/8–27 |
| G60514-0604 | 6MJ-4FP90 | 7259-25115 | 9/16–18 | 1/4–18 |
| G60514-0606 | 6MJ-6FP90 | 7259-34825 | 9/16–18 | 3/8–18 |
| G60514-0608 | 6MJ-8FP90 | 7259-00405 | 9/16–18 | 1/2–14 |
| G60514-0804 | 8MJ-4FP90 | 7259-09515 | 3/4–16 | 1/4–18 |
| G60514-0806 | 8MJ-6FP90 | 7259-25125 | 3/4–16 | 3/8–18 |
| G60514-0808 | 8MJ-8FP90 | 7259-34835 | 3/4–16 | 1/2–14 |
| G60514-1008 | 10MJ-8FP90 | 7259-25135 | 7/8–14 | 1/2–14 |
| G60514-1208 | 12MJ-8FP90 | 7259-34845 | 1 1/16–12 | 1/2–14 |
| G60514-1212 | 12MJ-12FP90 | 7259-25145 | 1 1/16–12 | 3/4–14 |
| G60514-1412 | 14MJ-12FP90 | 7259-09525 | 1 3/16–12 | 3/4–14 |
| G60514-1616 | 16MJ-16FP90 | 7259-25155 | 1 5/16–12 | 1–11 1/2 |
| G60514-2020 | 20MJ-20FP90 | 7259-34855 | 1 5/8–12 | 1 1/4–11 1/2 |
| G60514-2424 | 24MJ-24FP90 | 7259-07725 | 1 7/8–12 | 1 1/2–11 1/2 |

# Female JIC 37° Flare Swivel to Male Pipe NPTF

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60520-0402 | 4FJX-2MP | 7253-34865 | 7/16–20 | 1/8–27 |
| G60520-0404 | 4FJX-4MP | 7259-34875 | 7/16–20 | 1/4–18 |
| G60520-0604 | 6FJX-4MP | 7259-34885 | 9/16–18 | 1/4–18 |
| G60520-0606 | 6FJX-6MP | 7259-34895 | 9/16–18 | 3/8–18 |
| G60520-0806 | 8FJX-6MP | 7259-34905 | 3/4–16 | 3/8–18 |
| G60520-0808 | 8FJX-8MP | 7259-34915 | 3/4–16 | 1/2–14 |
| G60520-1008 | 10FJX-8MP | 7259-09565 | 7/8–14 | 1/2–14 |
| G60520-1208 | 12FJX-8MP | 7259-51055 | 1 1/16–12 | 1/2–14 |
| G60520-1212 | 12FJX-12MP | 7259-34925 | 1 1/16–12 | 3/4–14 |
| G60520-1616 | 16FJX-16MP | 7253-34935 | 1 5/16–12 | 1–11 1/2 |
| G60520-2020 | 20FJX-20MP | 7259-34945 | 1 5/8–12 | 1 1/4–11 1/2 |

# Female JIC 37° Flare Swivel to Male Pipe NPTF - 90°

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60524-0402 | 4FJX-2MP90 | 7253-34955 | 7/16–20 | 1/8–27 |
| G60524-0404 | 4FJX-4MP90 | 7259-05325 | 7/16–20 | 1/4–18 |
| G60524-0604 | 6FJX-4MP90 | 7253-34965 | 9/16–18 | 1/4–18 |
| G60524-0606 | 6FJX-6MP90 | 7253-34975 | 9/16–18 | 3/8–18 |
| G60524-0806 | 8FJX-6MP90 | 7253-34985 | 3/4–16 | 3/8–18 |
| G60524-0808 | 8FJX-8MP90 | 7253-34995 | 3/4–16 | 1/2–14 |
| G60524-1008 | 10FJX-8MP90 | 7253-35015 | 7/8–14 | 1/2–14 |
| G60524-1212 | 12FJX-12MP90 | 7253-35025 | 1 1/16–12 | 3/4–14 |
| G60524-1616 | 16FJX-16MP90 | 7259-35285 | 1 5/16–12 | 1–11 1/2 |
| G60524-2020 | 20FJX-20MP90 | 7259-35295 | 1 5/8–12 | 1 1/4–11 1/2 |
| G60524-2424 | 24FJX-24MP90 | 7259-35035 | 1 7/8–12 | 1 1/2–11 1/2 |

# Female JIC 37° Flare Swivel to Female Pipe NPTF

For use up to SAE 100R2 maximum working pressure.











| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60530-0402 | 4FJX-2FP | 7253-35045 | 7/16–20 | 1/8–27 |
| G60530-0404 | 4FJX-4FP | 7253-35055 | 7/16–20 | 1/4–18 |
| G60530-0606 | 6FJX-6FP | 7253-35075 | 9/16–18 | 3/8–18 |
| G60530-0806 | 8FJX-6FP | 7253-35095 | 3/4–16 | 3/8–18 |
| G60530-0808 | 8FJX-8FP | 7253-35105 | 3/4–16 | 1/2–14 |
| G60530-1008 | 10FJX-8FP | 7253-35115 | 7/8–14 | 1/2–14 |
| G60530-1212 | 12FJX-12FP | 7253-35125 | 1 1/16–12 | 3/4–14 |
| G60530-1616 | 16FJX-16FP | 7259-35135 | 1 5/16–12 | 1–11 1/2 |
| G60530-2020 | 20FJX-20FP | 7259-35145 | 1 5/8–12 | 1 1/4–11 1/2 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male JIC 37° Flare Bulkhead to Male Pipe NPTF

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60541-0402 | 4MJBKHD-2MP | 7259-09945 | 7/16–20 | 1/8–27 |
| G60541-0404 | 4MJBKHD-4MP | 7259-35155 | 7/16–20 | 1/4–18 |
| G60541-0604 | 6MJBKHD-4MP | 7259-35165 | 9/16–18 | 1/4–18 |
| G60541-0806 | 8MJBKHD-6MP | 7259-35175 | 3/4–16 | 3/8–18 |
| G60541-0808 | 8MJBKHD-8MP | 7259-09905 | 3/4–16 | 1/2–14 |
| G60541-1008 | 10MJBKHD-8MP | 7259-35185 | 7/8–14 | 1/2–14 |
| G60541-1208 | 12MJBKHD-8MP | 7259-35275 | 1 1/16–12 | 1/2–14 |
| G60541-1212 | 12MJBKHD-12MP | 7259-35195 | 1 1/16–12 | 3/4–14 |
| G60541-1616 | 16MJBKHD-16MP | 7253-35205 | 1 5/16–12 | 1–11 1/2 |
| G60541-2020 | 20MJBKHD-20MP | 7259-09965 | 1 5/8–12 | 1 1/4–11 1/2 |

# Male JIC 37° Flare on Run to Male Pipe NPTF - Tee

For use up to SAE 100R2 maximum working pressure.





| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60551-0302 | 3MJ-3MJ-2MP | 7259-09605 | 3/8–24 | 3/8–24 | 1/8–27 |
| G60551-0402 | 4MJ-4MJ-2MP | 7259-23415 | 7/16–20 | 7/16–20 | 1/8–27 |
| G60551-0404 | 4MJ-4MJ-4MP | 7259-35215 | 7/16–20 | 7/16–20 | 1/4–18 |
| G60551-0406 | 4MJ-4MJ-6MP | 7259-05855 | 7/16–20 | 7/16–20 | 3/8–18 |
| G60551-0502 | 5MJ-5MJ-2MP | 7259-07385 | 1/2–20 | 1/2–20 | 1/8–27 |
| G60551-0504 | 5MJ-5MJ-4MP | 7259-35225 | 1/2–20 | 1/2–20 | 1/4–18 |
| G60551-0604 | 6MJ-6MJ-4MP | 7259-23425 | 9/16–18 | 9/16–18 | 1/4–18 |
| G60551-0606 | 6MJ-6MJ-6MP | 7259-35235 | 9/16–18 | 9/16–18 | 3/8–18 |
| G60551-0608 | 6MJ-6MJ-8MP | 7259-35245 | 9/16–18 | 9/16–18 | 1/2–14 |
| G60551-0806 | 8MJ-8MJ-6MP | 7259-23435 | 3/4–16 | 3/4–16 | 3/8–18 |
| G60551-0808 | 8MJ-8MJ-8MP | 7259-35255 | 3/4–16 | 3/4–16 | 1/2–14 |
| G60551-0812 | 8MJ-8MJ-12MP | 7259-09615 | 3/4–16 | 3/4–16 | 3/4–14 |
| G60551-1008 | 10MJ-10MJ-8MP | 7259-23445 | 7/8–14 | 7/8–14 | 1/2–14 |
| G60551-1208 | 12MJ-12MJ-8MP | 7259-07395 | 1 1/16–12 | 1 1/16–12 | 1/2–14 |
| G60551-1212 | 12MJ-12MJ-12MP | 7259-23455 | 1 1/16–12 | 1 1/16–12 | 3/4–14 |
| G60551-1216 | 12MJ-12MJ-16MP | 7259-07735 | 1 1/16–12 | 1 1/16–12 | 1–11 1/2 |
| G60551-1412 | 14MJ-14MJ-12MP | 7259-09625 | 1 3/16–12 | 1 3/16–12 | 3/4–14 |
| G60551-1612 | 16MJ-16MJ-12MP | 7259-09635 | 1 5/16–12 | 1 5/16–12 | 3/4–14 |


## Male JIC 37° Flare on Run to Male Pipe NPTF - Tee - Continued

| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60551-1616 | 16MJ-16MJ-16MP | 7259-23465 | 1 5/16–12 | 1 5/16–12 | 1–11 1/2 |
| G60551-2020 | 20MJ-20MJ-20MP | 7259-35265 | 1 5/8–12 | 1 5/8–12 | 1 1/4–11 1/2 |
| G60551-2424 | 24MJ-24MJ-24MP | 7259-08355 | 1 7/8–12 | 1 7/8–12 | 1 1/2–11 1/2 |

## Female Flat-Face O-Ring Cap

For use up to SAE 100R2 maximum working pressure.








| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| | | | " |
| G60701-0004 | 4FFOR-CAP | 7253-32125 | 9/16–18 |
| G60701-0006 | 6FFOR-CAP | 7253-32135 | 11/16–16 |
| G60701-0008 | 8FFOR-CAP | 7253-32145 | 13/16–16 |
| G60701-0010 | 10FFOR-CAP | 7253-32155 | 1–14 |
| G60701-0012 | 12FFOR-CAP | 7253-32165 | 1 3/16–12 |
| G60701-0016 | 16FFOR-CAP | 7253-32175 | 1 7/16–12 |
| G60701-0020 | 20FFOR-CAP | 7253-32185 | 1 11/16–12 |
| G60701-0024 | 24FFOR-CAP | 7253-32195 | 2–12 |

## Male Flat-Face O-Ring Plug

For use up to SAE 100R2 maximum working pressure.







| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| | | | " |
| G60702-0004 | 4MFFOR-PLUG | 7259-32045 | 9/16–18 |
| G60702-0006 | 6MFFOR-PLUG | 7259-32055 | 11/16–16 |
| G60702-0008 | 8MFFOR-PLUG | 7259-32065 | 13/16–16 |
| G60702-0010 | 10MFFOR-PLUG | 7259-32075 | 1–14 |
| G60702-0012 | 12MFFOR-PLUG | 7259-32085 | 1 3/16–12 |
| G60702-0016 | 16MFFOR-PLUG | 7259-32095 | 1 7/16–12 |
| G60702-0020 | 20MFFOR-PLUG | 7259-32105 | 1 11/16–12 |
| G60702-0024 | 24MFFOR-PLUG | 7259-32115 | 2–12 |
| G60702-0032 | 32MFFOR-PLUG | 7259-09655 | 2 1/2–12 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Flat-Face O-Ring to Male Flat-Face O-Ring

For use up to SAE 100R2 maximum working pressure.







| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60705-0404 | 4MFFOR-4MFFOR | 7259-43965 | 9/16–18 | 9/16–18 |
| G60705-0604 | 6MFFOR-4MFFOR | 7259-43975 | 11/16–16 | 9/16–18 |
| G60705-0606 | 6MFFOR-6MFFOR | 7259-43985 | 11/16–16 | 11/16–16 |
| G60705-0806 | 8MFFOR-6MFFOR | 7259-43995 | 13/16–16 | 11/16–16 |
| G60705-0808 | 8MFFOR-8MFFOR | 7259-44005 | 13/16–16 | 13/16–16 |
| G60705-1010 | 10MFFOR-10MFFOR | 7259-44025 | 1–14 | 1–14 |
| G60705-1212 | 12MFFOR-12MFFOR | 7259-44045 | 1 3/16–12 | 1 3/16–12 |
| G60705-1616 | 16MFFOR-16MFFOR | 7259-44065 | 1 7/16–12 | 1 7/16–12 |
| G60705-2020 | 20MFFOR-20MFFOR | 7259-44075 | 1 11/16–12 | 1 11/16–12 |
| G60705-2424 | 24MFFOR-24MFFOR | 7259-44085 | 2–12 | 2–12 |

# Male Flat-Face O-Ring to Male Flat-Face O-Ring - 90°

For use up to SAE 100R2 maximum working pressure.









| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60712-0404 | 4MFFOR-4MFFOR90 | 7259-44105 | 9/16–18 | 9/16–18 |
| G60712-0808 | 8MFFOR-8MFFOR90 | 7259-44125 | 13/16–16 | 13/16–16 |

# Male Flat-Face O-Ring to Female Flat-Face Swivel - 90°

For use up to SAE 100R2 maximum working pressure.











| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60724-0404 | 4MFFOR-4FFORX90 | 7259-06075 | 9/16–18 | 9/16–18 |
| G60724-0606 | 6MFFOR-6FFORX90 | 7259-31905 | 11/16–16 | 11/16–16 |
| G60724-0808 | 8MFFOR-8FFORX90 | 7259-00345 | 13/16–16 | 13/16–16 |
| G60724-1010 | 10MFFOR-10FFORX90 | 7259-05585 | 1–14 | 1–14 |
| G60724-1212 | 12MFFOR-12FFORX90 | 7259-06085 | 1 3/16–12 | 1 3/16–12 |
| G60724-1616 | 16MFFOR-16FFORX90 | 7259-05285 | 1 7/16–12 | 1 7/16–12 |
| G60724-2020 | 20MFFOR-20FFORX90 | 7259-09665 | 1 11/16–12 | 1 11/16–12 |
| G60724-2424 | 24MFFOR-24FFORX90 | 7259-09675 | 2–12 | 2–12 |

# Male Flat-Face O-Ring Tee

For use up to SAE 100R2 maximum working pressure.








| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60740-0404 | 4MFFOR-4MFFOR-4MFFOR | 7259-04805 | 9/16–18 | 9/16–18 | 9/16–18 |
| G60740-0606 | 6MFFOR-6MFFOR-6MFFOR | 7259-04815 | 11/16–16 | 11/16–16 | 11/16–16 |
| G60740-0808 | 8MFFOR-8MFFOR-8MFFOR | 7259-04825 | 13/16–16 | 13/16–16 | 13/16–16 |
| G60740-1010 | 10MFFOR-10MFFOR-10MFFOR | 7259-04835 | 1–14 | 1–14 | 1–14 |
| G60740-1212 | 12MFFOR-12MFFOR-12MFFOR | 7259-04845 | 1 3/16–12 | 1 3/16–12 | 1 3/16–12 |
| G60740-1616 | 16MFFOR-16MFFOR-16MFFOR | 7259-04855 | 1 7/16–12 | 1 7/16–12 | 1 7/16–12 |
| G60740-2020 | 20MFFOR-20MFFOR-20MFFOR | 7259-04865 | 1 11/16–12 | 1 11/16–12 | 1 11/16–12 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Flat-Face O-Ring on Run to Female Flat-Face Swivel - Tee

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60742-0404 | 4MFFOR-4MFFOR-4FFORX | 7259-31805 | 9/16–18 | 9/16–18 | 9/16–18 |
| G60742-0606 | 6MFFOR-6MFFOR-6FFORX | 7259-31815 | 11/16–16 | 11/16–16 | 11/16–16 |
| G60742-0808 | 8MFFOR-8MFFOR-8FFORX | 7259-31825 | 13/16–16 | 13/16–16 | 13/16–16 |
| G60742-1010 | 10MFFOR-10MFFOR-10FFORX | 7259-09685 | 1–14 | 1–14 | 1–14 |
| G60742-1212 | 12MFFOR-12MFFOR-12FFORX | 7259-09695 | 1 3/16–12 | 1 3/16–12 | 1 3/16–12 |
| G60742-1616 | 16MFFOR-16MFFOR-16FFORX | 7259-09705 | 1 7/16–12 | 1 7/16–12 | 1 7/16–12 |
| G60742-2020 | 20MFFOR-20MFFOR-20FFORX | 7259-09715 | 1 11/16–12 | 1 11/16–12 | 1 11/16–12 |

# Male Flat-Face O-Ring to Female Flat-Face O-Ring to Male Flat-Face O-Ring - Tee

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60744-0404 | 4MFFOR-4FFORX-4MFFOR | 7259-00265 | 9/16–18 | 9/16–18 | 9/16–18 |
| G60744-0606 | 6MFFOR-6FFORX-6MFFOR | 7259-00135 | 11/16–16 | 11/16–16 | 11/16–16 |
| G60744-0808 | 8MFFOR-8FFORX-8MFFOR | 7259-00225 | 13/16–16 | 13/16–16 | 13/16–16 |
| G60744-1010 | 10MFFOR-10FFORX-10MFFOR | 7259-06815 | 1–14 | 1–14 | 1–14 |
| G60744-1212 | 12MFFOR-12FFORX-12MFFOR | 7259-00555 | 1 3/16–12 | 1 3/16–12 | 1 3/16–12 |
| G60744-1616 | 16MFFOR-16FFORX-16MFFOR | 7259-06025 | 1 7/16–12 | 1 7/16–12 | 1 7/16–12 |
| G60744-2020 | 20MFFOR-20FFORX-20MFFOR | 7259-04785 | 1 11/16–12 | 1 11/16–12 | 1 11/16–12 |

# Male Flat-Face O-Ring to Male Pipe NPTF

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60770-0402 | 4MFFOR-2MP | 7259-30615 | 9/16–18 | 1/8–27 |
| G60770-0404 | 4MFFOR-4MP | 7259-30625 | 9/16–18 | 1/4–18 |
| G60770-0406 | 4MFFOR-6MP | 7259-30635 | 9/16–18 | 3/8–18 |
| G60770-0604 | 6MFFOR-4MP | 7259-30645 | 11/16–16 | 1/4–18 |
| G60770-0606 | 6MFFOR-6MP | 7259-30655 | 11/16–16 | 3/8–18 |
| G60770-0608 | 6MFFOR-8MP | 7259-30665 | 11/16–16 | 1/2–14 |
| G60770-0804 | 8MFFOR-4MP | 7259-09845 | 13/16–16 | 1/4–18 |
| G60770-0806 | 8MFFOR-6MP | 7259-30675 | 13/16–16 | 3/8–18 |
| G60770-0808 | 8MFFOR-8MP | 7259-30685 | 13/16–16 | 1/2–14 |
| G60770-0812 | 8MFFOR-12MP | 7259-06845 | 13/16–16 | 3/4–14 |
| G60770-1008 | 10MFFOR-8MP | 7259-30695 | 1–14 | 1/2–14 |
| G60770-1012 | 10MFFOR-12MP | 7259-06755 | 1–14 | 3/4–14 |
| G60770-1208 | 12MFFOR-8MP | 7259-06035 | 1 3/16–12 | 1/2–14 |
| G60770-1212 | 12MFFOR-12MP | 7259-30705 | 1 3/16–12 | 3/4–14 |
| G60770-1216 | 12MFFOR-16MP | 7259-08115 | 1 3/16–12 | 1–11 1/2 |
| G60770-1612 | 16MFFOR-12MP | 7259-07075 | 1 7/16–12 | 3/4–14 |
| G60770-1616 | 16MFFOR-16MP | 7259-30715 | 1 7/16–12 | 1–11 1/2 |
| G60770-2020 | 20MFFOR-20MP | 7259-30725 | 1 11/16–12 | 1 1/4–11 1/2 |
| G60770-2424 | 24MFFOR-24MP | 7259-07595 | 2–12 | 1 1/2–11 1/2 |

# Male Flat-Face O-Ring to Female JIC 37° Flare Swivel

For use up to SAE 100R2 maximum working pressure.











| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60785-0404 | 4MFFOR-4FJX | 7259-09995 | 9/16–18 | 7/16–20 |
| G60785-0606 | 6MFFOR-6FJX | 7259-05135 | 11/16–16 | 9/16–18 |
| G60785-0808 | 8MFFOR-8FJX | 7259-05365 | 13/16–16 | 3/4–16 |
| G60785-1010 | 10MFFOR-10FJX | 7259-06335 | 1–14 | 7/8–14 |
| G60785-1212 | 12MFFOR-12FJX | 7259-05215 | 1 3/16–12 | 1 1/16–12 |
| G60785-1616 | 16MFFOR-16FJX | 7259-06765 | 1 7/16–12 | 1 5/16–12 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Flat-Face O-Ring to Male O-Ring Boss

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60800-0404 | 4MFFOR-4MB | 7259-30015 | 9/16–18 | 7/16–20 |
| G60800-0406 | 4MFFOR-6MB | 7259-29905 | 9/16–18 | 9/16–18 |
| G60800-0408 | 4MFFOR-8MB | 7259-30115 | 9/16–18 | 3/4–16 |
| G60800-0604 | 6MFFOR-4MB | 7259-30025 | 11/16–16 | 7/16–20 |
| G60800-0606 | 6MFFOR-6MB | 7259-00085 | 11/16–16 | 9/16–18 |
| G60800-0608 | 6MFFOR-8MB | 7259-29925 | 11/16–16 | 3/4–16 |
| G60800-0610 | 6MFFOR-10MB | 7259-30095 | 11/16–16 | 7/8–14 |
| G60800-0806 | 8MFFOR-6MB | 7259-30035 | 13/16–16 | 9/16–18 |
| G60800-0808 | 8MFFOR-8MB | 7259-29915 | 13/16–16 | 3/4–16 |
| G60800-0810 | 8MFFOR-10MB | 7259-30105 | 13/16–16 | 7/8–14 |
| G60800-0812 | 8MFFOR-12MB | 7259-30125 | 13/16–16 | 1 1/16–12 |
| G60800-0816 | 8MFFOR-16MB | 7259-08005 | 13/16–16 | 1 5/16–12 |
| G60800-1008 | 10MFFOR-8MB | 7259-00155 | 1–14 | 3/4–16 |
| G60800-1010 | 10MFFOR-10MB | 7259-30045 | 1–14 | 7/8–14 |
| G60800-1012 | 10MFFOR-12MB | 7259-00165 | 1–14 | 1 1/16–12 |
| G60800-1208 | 12MFFOR-8MB | 7259-30135 | 1 3/16–12 | 3/4–16 |
| G60800-1210 | 12MFFOR-10MB | 7259-05385 | 1 3/16–12 | 7/8–14 |
| G60800-1212 | 12MFFOR-12MB | 7259-30055 | 1 3/16–12 | 1 1/16–12 |
| G60800-1216 | 12MFFOR-16MB | 7259-30175 | 1 3/16–12 | 1 5/16–12 |
| G60800-1612 | 16MFFOR-12MB | 7259-30185 | 1 7/16–12 | 1 1/16–12 |
| G60800-1616 | 16MFFOR-16MB | 7259-50255 | 1 7/16–12 | 1 5/16–12 |
| G60800-1620 | 16MFFOR-20MB | 7259-00045 | 1 7/16–12 | 1 5/8–12 |
| G60800-2016 | 20MFFOR-16MB | 7259-30145 | 1 11/16–12 | 1 5/16–12 |
| G60800-2020 | 20MFFOR-20MB | 7259-30075 | 1 11/16–12 | 1 5/8–12 |
| G60800-2024 | 20MFFOR-24MB | 7259-09745 | 1 11/16–12 | 1 7/8–12 |
| G60800-2420 | 24MFFOR-20MB | 7259-09755 | 2–12 | 1 5/8–12 |
| G60800-2424 | 24MFFOR-24MB | 7259-00175 | 2–12 | 1 7/8–12 |
| G60800-3232 | 32MFFOR-32MB | 7259-00325 | 2 1/2–12 | 2 1/2–12 |

# Male Flat-Face O-Ring to Male O-Ring Boss - 45°

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60805-0404 | 4MFFOR-4MB45 | 7259-30935 | 9/16–18 | 7/16–20 |
| G60805-0406 | 4MFFOR-6MB45 | 7259-30305 | 9/16–18 | 9/16–18 |
| G60805-0604 | 6MFFOR-4MB45 | 7259-30945 | 11/16–16 | 7/16–20 |
| G60805-0606 | 6MFFOR-6MB45 | 7259-30225 | 11/16–16 | 9/16–18 |
| G60805-0608 | 6MFFOR-8MB45 | 7259-30955 | 11/16–16 | 3/4–16 |
| G60805-0806 | 8MFFOR-6MB45 | 7259-30965 | 13/16–16 | 9/16–18 |
| G60805-0808 | 8MFFOR-8MB45 | 7259-30975 | 13/16–16 | 3/4–16 |
| G60805-0810 | 8MFFOR-10MB45 | 7259-30295 | 13/16–16 | 7/8–14 |
| G60805-0812 | 8MFFOR-12MB45 | 7259-30985 | 13/16–16 | 1 1/16–12 |
| G60805-1008 | 10MFFOR-8MB45 | 7259-30995 | 1–14 | 3/4–16 |
| G60805-1010 | 10MFFOR-10MB45 | 7259-31005 | 1–14 | 7/8–14 |
| G60805-1012 | 10MFFOR-12MB45 | 7259-31015 | 1–14 | 1 1/16–12 |
| G60805-1210 | 12MFFOR-10MB45 | 7259-31025 | 1 3/16–12 | 7/8–14 |
| G60805-1212 | 12MFFOR-12MB45 | 7259-31035 | 1 3/16–12 | 1 1/16–12 |
| G60805-1216 | 12MFFOR-16MB45 | 7259-31045 | 1 3/16–12 | 1 5/16–12 |
| G60805-1612 | 16MFFOR-12MB45 | 7259-31055 | 1 7/16–12 | 1 1/16–12 |
| G60805-1616 | 16MFFOR-16MB45 | 7259-31065 | 1 7/16–12 | 1 5/16–12 |
| G60805-1620 | 16MFFOR-20MB45 | 7259-31075 | 1 7/16–12 | 1 5/8–12 |
| G60805-2020 | 20MFFOR-20MB45 | 7259-31085 | 1 11/16–12 | 1 5/8–12 |
| G60805-2424 | 24MFFOR-24MB45 | 7259-31095 | 2–12 | 1 7/8–12 |

# Male Flat-Face O-Ring to Male O-Ring Boss - 90°

For use up to SAE 100R2 maximum working pressure.






| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60810-0404 | 4MFFOR-4MB90 | 7259-30415 | 9/16–18 | 7/16–20 |
| G60810-0406 | 4MFFOR-6MB90 | 7259-30735 | 9/16–18 | 9/16–18 |
| G60810-0408 | 4MFFOR-8MB90 | 7259-30745 | 9/16–18 | 3/4–16 |
| G60810-0604 | 6MFFOR-4MB90 | 7259-30495 | 11/16–16 | 7/16–20 |
| G60810-0606 | 6MFFOR-6MB90 | 7259-30425 | 11/16–16 | 9/16–18 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male Flat-Face O-Ring to Male O-Ring Boss - 90° - Continued


| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60810-0608 | 6MFFOR-8MB90 | 7259-30755 | 11/16–16 | 3/4–16 |
| G60810-0612 | 6MFFOR-12MB90 | 7259-30765 | 11/16–16 | 1 1/16–12 |
| G60810-0806 | 8MFFOR-6MB90 | 7259-66215 | 13/16–16 | 9/16–18 |
| G60810-0808 | 8MFFOR-8MB90 | 7259-30435 | 13/16–16 | 3/4–16 |
| G60810-0810 | 8MFFOR-10MB90 | 7259-30515 | 13/16–16 | 7/8–14 |
| G60810-0812 | 8MFFOR-12MB90 | 7259-30525 | 13/16–16 | 1 1/16–12 |
| G60810-1008 | 10MFFOR-8MB90 | 7259-30555 | 1–14 | 3/4–16 |
| G60810-1010 | 10MFFOR-10MB90 | 7259-30445 | 1–14 | 7/8–14 |
| G60810-1012 | 10MFFOR-12MB90 | 7259-30775 | 1–14 | 1 1/16–12 |
| G60810-1208 | 12MFFOR-8MB90 | 7259-30785 | 1 3/16–12 | 3/4–16 |
| G60810-1210 | 12MFFOR-10MB90 | 7259-30795 | 1 3/16–12 | 7/8–14 |
| G60810-1212 | 12MFFOR-12MB90 | 7259-30455 | 1 3/16–12 | 1 1/16–12 |
| G60810-1216 | 12MFFOR-16MB90 | 7259-30805 | 1 3/16–12 | 1 5/16–12 |
| G60810-1612 | 16MFFOR-12MB90 | 7259-30545 | 1 7/16–12 | 1 1/16–12 |
| G60810-1616 | 16MFFOR-16MB90 | 7259-30465 | 1 7/16–12 | 1 5/16–12 |
| G60810-1620 | 16MFFOR-20MB90 | 7259-30815 | 1 7/16–12 | 1 5/8–12 |
| G60810-2016 | 20MFFOR-16MB90 | 7259-30825 | 1 11/16–12 | 1 5/16–12 |
| G60810-2020 | 20MFFOR-20MB90 | 7259-30475 | 1 11/16–12 | 1 5/8–12 |
| G60810-2024 | 20MFFOR-24MB90 | 7259-30835 | 1 11/16–12 | 1 7/8–12 |
| G60810-2420 | 24MFFOR-20MB90 | 7259-30845 | 2–12 | 1 5/8–12 |
| G60810-2424 | 24MFFOR-24MB90 | 7259-30855 | 2–12 | 1 7/8–12 |

## Male Flat-Face O-Ring to Male O-Ring Boss - 90° Long Drop

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60811-0404 | 4MFFOR-4MB90L | 7259-30875 | 9/16–18 | 7/16–20 |
| G60811-0606 | 6MFFOR-6MB90L | 7259-30885 | 11/16–16 | 9/16–18 |
| G60811-1212 | 12MFFOR-12MB90L | 7259-30915 | 1 3/16–12 | 1 1/16–12 |
| G60811-1616 | 16MFFOR-16MB90L | 7259-30925 | 1 7/16–12 | 1 5/16–12 |

# Male Flat-Face O-Ring on Run to Male O-Ring Boss - Tee

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60820-0404 | 4MFFOR-4MFFOR-4MB | 7259-31405 | 9/16–18 | 9/16–18 | 7/16–20 |
| G60820-0606 | 6MFFOR-6MFFOR-6MB | 7259-31515 | 11/16–16 | 11/16–16 | 9/16–18 |
| G60820-0808 | 8MFFOR-8MFFOR-8MB | 7259-31415 | 13/16–16 | 13/16–16 | 3/4–16 |
| G60820-1010 | 10MFFOR-10MFFOR-10MB | 7259-31425 | 1–14 | 1–14 | 7/8–14 |
| G60820-1212 | 12MFFOR-12MFFOR-12MB | 7259-31545 | 1 3/16–12 | 1 3/16–12 | 1 1/16–12 |
| G60820-1616 | 16MFFOR-16MFFOR-16MB | 7259-31555 | 1 7/16–12 | 1 7/16–12 | 1 5/16–12 |
| G60820-2020 | 20MFFOR-20MFFOR-20MB | 7259-31435 | 1 11/16–12 | 1 11/16–12 | 1 5/8–12 |

# Male Flat-Face O-Ring to Male O-Ring Boss to Male Flat-Face O-Ring - Tee

For use up to SAE 100R2 maximum working pressure.











| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G60821-0404 | 4MFFOR-4MB-4MFFOR | 7259-31455 | 9/16–18 | 7/16–20 | 9/16–18 |
| G60821-0606 | 6MFFOR-6MB-6MFFOR | 7259-31605 | 11/16–16 | 9/16–18 | 11/16–16 |
| G60821-0808 | 8MFFOR-8MB-8MFFOR | 7259-31465 | 13/16–16 | 3/4–16 | 13/16–16 |
| G60821-1010 | 10MFFOR-10MB-10MFFOR | 7259-31615 | 1–14 | 7/8–14 | 1–14 |
| G60821-1212 | 12MFFOR-12MB-12MFFOR | 7259-31475 | 1 3/16–12 | 1 1/16–12 | 1 3/16–12 |
| G60821-1616 | 16MFFOR-16MB-16MFFOR | 7259-31485 | 1 7/16–12 | 1 5/16–12 | 1 7/16–12 |
| G60821-2020 | 20MFFOR-20MB-20MFFOR | 7259-31495 | 1 11/16–12 | 1 5/8–12 | 1 11/16–12 |
| G60821-2424 | 24MFFOR-24MB-24MFFOR | 7259-31505 | 2–12 | 1 7/8–12 | 2–12 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female Flat-Face Swivel to Male JIC 37° Flare

For use up to SAE 100R2 maximum working pressure.












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G60880-0404 | 4FFORX-4MJ | 7253-31705 | 9/16–18 | 7/16–20 |
| G60880-0606 | 6FFORX-6MJ | 7253-31715 | 11/16–16 | 9/16–18 |
| G60880-0808 | 8FFORX-8MJ | 7253-31725 | 13/16–16 | 3/4–16 |
| G60880-1010 | 10FFORX-10MJ | 7253-31735 | 1–14 | 7/8–14 |
| G60880-1212 | 12FFORX-12MJ | 7253-31745 | 1 3/16–12 | 1 1/16–12 |
| G60880-1616 | 16FFORX-16MJ | 7253-31755 | 1 7/16–12 | 1 5/16–12 |

# Code 61 O-Ring Flange to Male JIC 37° Flare

O–Ring not included. Must be ordered separately.









| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60900-0808 | 8FL-8MJ | 7253-86931 | 3/4–16 | 1.19 | 30.2 | .27 | 6.9 |
| G60900-1212 | 12FL-12MJ | 7253-86932 | 1 1/16–12 | 1.50 | 38.1 | .27 | 6.9 |
| G60900-1616 | 16FL-16MJ | 7253-86933 | 1 5/16–12 | 1.75 | 44.5 | .32 | 8.1 |
| G60900-2020 | 20FL-20MJ | 7253-86934 | 1 5/8–12 | 2.00 | 50.8 | .32 | 8.1 |
| G60900-2424 | 24FL-24MJ | 7253-86935 | 1 7/8–12 | 2.38 | 60.5 | .32 | 8.1 |
| G60900-3232 | 32FL-32MJ | 7253-86936 | 2 1/2–12 | 2.81 | 71.4 | .38 | 9.7 |

# Code 61 O-Ring Flange to Male JIC 37° Flare - High Pressure

No braze joints, solid one–piece construction for increased reliability.
O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60901-1212 | 12FL5K-12MJ | 7253-13015 | 1 1/16–12 | 1.50 | 38.1 | .27 | 6.9 |
| G60901-1612 | 16FL5K-12MJ | 7253-12405 | 1 1/16–12 | 1.75 | 44.5 | .32 | 8.1 |
| G60901-1616 | 16FL5K-16MJ | 7253-13035 | 1 5/16–12 | 1.75 | 44.5 | .32 | 8.1 |
| G60901-1620 | 16FL5K-20MJ | 7253-12425 | 1 5/8–12 | 1.75 | 44.5 | .32 | 8.1 |
| G60901-2016 | 20FL4K-16MJ | 7253-12485 | 1 5/16–12 | 2.00 | 50.8 | .32 | 8.1 |
| G60901-2020 | 20FL4K-20MJ | 7253-12475 | 1 5/8–12 | 2.00 | 50.8 | .32 | 8.1 |


NOTE: FL5K maximum working pressure is 5,000 psi; FL4K maximum working pressure is 4,000 psi.


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Code 61 O-Ring Flange to Male JIC 37° Flare - 45°

O–Ring not included. Must be ordered separately.









| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60905-0808 | 8FL-8MJ45 | 7253-86937 | 3/4–16 | 1.19 | 30.2 | .27 | 6.9 |
| G60905-1212 | 12FL-12MJ45 | 7253-86938 | 1 1/16–12 | 1.50 | 38.1 | .27 | 6.9 |
| G60905-1616 | 16FL-16MJ45 | 7253-86939 | 1 5/16–12 | 1.75 | 44.5 | .32 | 8.1 |
| G60905-2020 | 20FL-20MJ45 | 7253-86941 | 1 5/8–12 | 2.00 | 50.8 | .32 | 8.1 |
| G60905-2424 | 24FL-24MJ45 | 7253-86942 | 1 7/8–12 | 2.38 | 60.5 | .32 | 8.1 |
| G60905-3232 | 32FL-32MJ45 | 7253-86943 | 2 1/2–12 | 2.81 | 71.4 | .38 | 9.7 |

# Code 61 O-Ring Flange to Male JIC 37° Flare - 45° - High Pressure

No braze joints, solid one–piece construction for increased reliability.
O–Ring not included. Must be ordered separately.









| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60906-1212 | 12FL5K-12MJ45 | 7253-13105 | 1 1/16–12 | 1.50 | 38.1 | .27 | 6.9 |
| G60906-1616 | 16FL5K-16MJ45 | 7253-13125 | 1 5/16–12 | 1.75 | 44.5 | .32 | 8.1 |
| G60906-2016 | 20FL4K-16MJ45 | 7253-12625 | 1 5/16–12 | 2.00 | 50.8 | .37 | 9.4 |
| G60906-2020 | 20FL4K-20MJ45 | 7253-12395 | 1 5/8–12 | 2.00 | 50.8 | .37 | 9.4 |

NOTE: FL5K maximum working pressure is 5,000 psi; FL4K maximum working pressure is 4,000 psi.

# Code 61 O-Ring Flange to Male JIC 37° Flare - 90°

O–Ring not included. Must be ordered separately.









| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60910-0808 | 8FL-8MJ90 | 7253-86944 | 3/4–16 | 1.19 | 30.2 | .27 | 6.9 |
| G60910-1212 | 12FL-12MJ90 | 7253-86945 | 1 1/16–12 | 1.50 | 38.1 | .27 | 6.9 |
| G60910-1616 | 16FL-16MJ90 | 7253-86946 | 1 5/16–12 | 1.75 | 44.5 | .32 | 8.1 |
| G60910-2020 | 20FL-20MJ90 | 7253-86947 | 1 5/8–12 | 2.00 | 50.8 | .32 | 8.1 |
| G60910-2424 | 24FL-24MJ90 | 7253-86948 | 1 7/8–12 | 2.38 | 60.5 | .32 | 8.1 |
| G60910-3232 | 32FL-32MJ90 | 7253-86949 | 2 1/2–12 | 2.81 | 71.4 | .38 | 9.7 |

# Code 61 O-Ring Flange to Male JIC 37° Flare - 90° - High Pressure

No braze joints, solid one–piece construction for increased reliability.
O–Ring not included. Must be ordered separately.




| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60911-1212 | 12FL5K-12MJ90 | 7253-13205 | 1 1/16–12 | 1.50 | 38.1 | .27 | 6.9 |
| G60911-1612 | 16FL5K-12MJ90 | 7253-12415 | 1 1/16–12 | 1.75 | 44.5 | .32 | 8.1 |
| G60911-1616 | 16FL5K-16MJ90 | 7253-13225 | 1 5/16–12 | 1.75 | 44.5 | .32 | 8.1 |
| G60911-2016 | 20FL4K-16MJ90 | 7253-12495 | 1 5/16–12 | 2.00 | 50.8 | .32 | 8.1 |
| G60911-2020 | 20FL4K-20MJ90 | 7253-12505 | 1 5/8–12 | 2.00 | 50.8 | .32 | 8.1 |


NOTE: FL5K maximum working pressure is 5,000 psi; FL4K maximum working pressure is 4,000 psi.


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Code 61 O-Ring Flange to Male Flat-Face O-Ring - High Pressure

For use up to SAE 100R2 maximum working pressure.
No braze joints, solid one–piece construction for increased reliability.
O–Ring not included. Must be ordered separately.









| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60915-1212 | 12FL5K-12MFFOR | 7253-13695 | 1 3/16–12 | 1.50 | 38.1 | .27 | 6.9 |
| G60915-1612 | 16FL5K-12MFFOR | 7253-17155 | 1 3/16–12 | 1.75 | 44.5 | .32 | 8.1 |
| G60915-1616 | 16FL5K-16MFFOR | 7253-13705 | 1 7/16–12 | 1.75 | 44.5 | .32 | 8.1 |
| G60915-2020 | 20FL4K-20MFFOR | 7253-13715 | 1 11/16–12 | 2.00 | 50.8 | .32 | 8.1 |

NOTE: FL5K maximum working pressure is 5,000 psi; FL4K maximum working pressure is 4,000 psi.

# Code 61 O-Ring Flange to Male Flat-Face O-Ring 45° - High Pressure

No braze joints, solid one–piece construction for increased reliability.
O–Ring not included. Must be ordered separately.









| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60920-1212 | 12FL5K-12MFFOR45 | 7253-13725 | 1 3/16–12 | 1.50 | 38.1 | .27 | 6.9 |
| G60920-1616 | 16FL5K-16MFFOR45 | 7253-13735 | 1 7/16–12 | 1.75 | 44.5 | .32 | 8.1 |
| G60920-2020 | 20FL4K-20MFFOR45 | 7253-13745 | 1 11/16–12 | 2.00 | 50.8 | .32 | 8.1 |

NOTE: FL5K maximum working pressure is 5,000 psi; FL4K maximum working pressure is 4,000 psi.

# Code 61 O-Ring Flange to Male Flat-Face O-Ring 90° - High Pressure

No braze joints, solid one–piece construction for increased reliability.
O–Ring not included. Must be ordered separately.









| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60925-1212 | 12FL5K-12MFFOR90 | 7253-13755 | 1 3/16–12 | 1.50 | 38.1 | .27 | 6.9 |
| G60925-1616 | 16FL5K-16MFFOR90 | 7253-13765 | 1 7/16–12 | 1.50 | 38.1 | .32 | 8.1 |
| G60925-2020 | 20FL4K-20MFFOR90 | 7253-13775 | 1 11/16–12 | 2.00 | 50.8 | .32 | 8.1 |

NOTE: FL5K maximum working pressure is 5,000 psi; FL4K maximum working pressure is 4,000 psi.

# Code 62 O-Ring Flange Heavy to Male JIC 37° Flare - (6,000 psi)

No braze joints, solid one–piece construction for increased reliability.
O–Ring not included. Must be ordered separately.





| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60930-1212 | 12FLH6K-12MJ | 7253-13305 | 1 1/16–12 | 1.63 | 41.4 | .35 | 8.9 |
| G60930-1612 | 16FLH6K-12MJ | 7253-12445 | 1 1/16–12 | 1.88 | 47.8 | .38 | 9.7 |
| G60930-1616 | 16FLH6K-16MJ | 7253-13325 | 1 5/16–12 | 1.88 | 47.8 | .38 | 9.7 |
| G60930-1620 | 16FLH6K-20MJ | 7253-12465 | 1 5/8–12 | 1.88 | 47.8 | .38 | 9.7 |
| G60930-2016 | 20FLH6K-16MJ | 7253-12515 | 1 5/16–12 | 2.13 | 54.1 | .41 | 10.4 |
| G60930-2020 | 20FLH6K-20MJ | 7253-13345 | 1 5/8–12 | 2.13 | 54.1 | .41 | 10.4 |
| G60930-2420 | 24FLH6K-20MJ | 7253-13375 | 1 5/8–12 | 2.50 | 63.5 | .50 | 12.7 |
| G60930-2424 | 24FLH6K-24MJ | 7253-13365 | 1 7/8–12 | 2.50 | 63.5 | .50 | 12.7 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Code 62 O-Ring Flange Heavy to Male JIC 37° Flare 45° - (6,000 psi)

No braze joints, solid one–piece construction for increased reliability.
O–Ring not included. Must be ordered separately.









| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60935-1212 | 12FLH6K-12MJ45 | 7253-13405 | 1 1/16–12 | 1.63 | 41.4 | .35 | 8.9 |
| G60935-1616 | 16FLH6K-16MJ45 | 7253-13425 | 1 5/16–12 | 1.88 | 47.8 | .38 | 9.7 |
| G60935-2020 | 20FLH6K-20MJ45 | 7253-13445 | 1 5/8–12 | 2.13 | 54.1 | .41 | 10.4 |

# Code 62 O-Ring Flange Heavy to Male JIC 37° Flare 90° - (6,000 psi)

No braze joints, solid one–piece construction for increased reliability.
O–Ring not included. Must be ordered separately.









| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60940-1212 | 12FLH6K-12MJ90 | 7253-13505 | 1 1/16–12 | 1.63 | 41.4 | .35 | 8.9 |
| G60940-1216 | 12FLH6K-16MJ90 | 7253-13515 | 1 5/16–12 | 1.63 | 41.4 | .35 | 8.9 |
| G60940-1612 | 16FLH6K-12MJ90 | 7253-12455 | 1 1/16–12 | 1.88 | 47.8 | .38 | 9.7 |
| G60940-1616 | 16FLH6K-16MJ90 | 7253-13535 | 1 5/16–12 | 1.88 | 47.8 | .38 | 9.7 |
| G60940-1620 | 16FLH6K-20MJ90 | 7253-13545 | 1 5/8–12 | 1.88 | 47.8 | .38 | 9.7 |
| G60940-2016 | 20FLH6K-16MJ90 | 7253-12525 | 1 5/16–12 | 2.13 | 54.1 | .41 | 10.4 |
| G60940-2020 | 20FLH6K-20MJ90 | 7253-13565 | 1 5/8–12 | 2.13 | 54.1 | .41 | 10.4 |
| G60940-2420 | 24FLH6K-20MJ90 | 7253-13575 | 1 5/8–12 | 2.50 | 63.5 | .50 | 12.7 |

# Code 62 O-Ring Flange Heavy to Male Flat-Face O-Ring - (6,000 psi)

No braze joints, solid one–piece construction for increased reliability.
O–Ring not included. Must be ordered separately.









| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60945-1212 | 12FLH6K-12MFFOR | 7253-13605 | 1 3/16–12 | 1.63 | 41.4 | .35 | 8.9 |
| G60945-1616 | 16FLH6K-16MFFOR | 7253-13615 | 1 7/16–12 | 1.88 | 47.8 | .38 | 9.7 |
| G60945-2020 | 20FLH6K-20MFFOR | 7253-13625 | 1 11/16–12 | 2.13 | 54.1 | .41 | 10.4 |

# Code 62 O-Ring Flange Heavy to Male Flat-Face O-Ring 45° - (6,000 psi)

No braze joints, solid one–piece construction for increased reliability.
O–Ring not included. Must be ordered separately.









| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60950-1212 | 12FLH6K-12MFFOR45 | 7253-13635 | 1 3/16–12 | 1.63 | 41.4 | .35 | 8.9 |
| G60950-1616 | 16FLH6K-16MFFOR45 | 7253-13645 | 1 7/16–12 | 1.88 | 47.8 | .38 | 9.7 |
| G60950-2020 | 20FLH6K-20MFFOR45 | 7253-13655 | 1 11/16–12 | 2.13 | 54.1 | .41 | 10.4 |

# Code 62 O-Ring Flange Heavy to Male Flat-Face O-Ring 90° - (6,000 psi)

No braze joints, solid one–piece construction for increased reliability.
O–Ring not included. Must be ordered separately.





| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60955-1212 | 12FLH6K-12MFFOR90 | 7253-13665 | 1 3/16–12 | 1.63 | 41.4 | .35 | 8.9 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Code 62 O-Ring Flange Heavy to Male Flat-Face O-Ring 90° - (6,000 psi) - Continued

| Part No. | Descr. | Prod. No. | | M | | F | |
|---|---|---|---|---|---|---|---|
| | | | " | " | mm | " | mm |
| G60955-1612 | 16FLH6K-12MFFOR90 | 7253-13465 | 1 3/16–12 | 1.88 | 47.8 | .38 | 9.7 |
| G60955-1616 | 16FLH6K-16MFFOR90 | 7253-13675 | 1 7/16–12 | 1.88 | 47.8 | .38 | 9.7 |
| G60955-2020 | 20FLH6K-20MFFOR90 | 7253-13685 | 1 11/16–12 | 2.13 | 54.1 | .41 | 10.4 |

# Male British Standard Pipe Tapered Thread to Male JIC 37° Flare













| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62150-0204 | 2MBSPT-4MJ | 7253-14255 | 1/8–28 | 7/16–20 |
| G62150-0205 | 2MBSPT-5MJ | 7253-60005 | 1/8–28 | 1/2–20 |
| G62150-0206 | 2MBSPT-6MJ | 7253-60015 | 1/8–28 | 9/16–18 |
| G62150-0404 | 4MBSPT-4MJ | 7253-14265 | 1/4–19 | 7/16–20 |
| G62150-0405 | 4MBSPT-5MJ | 7253-60025 | 1/4–19 | 1/2–20 |
| G62150-0406 | 4MBSPT-6MJ | 7253-60035 | 1/4–19 | 9/16–18 |
| G62150-0408 | 4MBSPT-8MJ | 7253-60045 | 1/4–19 | 3/4–16 |
| G62150-0604 | 6MBSPT-4MJ | 7253-60055 | 3/8–19 | 7/16–20 |
| G62150-0605 | 6MBSPT-5MJ | 7253-60065 | 3/8–19 | 1/2–20 |
| G62150-0606 | 6MBSPT-6MJ | 7253-14275 | 3/8–19 | 9/16–18 |
| G62150-0608 | 6MBSPT-8MJ | 7253-60075 | 3/8–19 | 3/4–16 |
| G62150-0610 | 6MBSPT-10MJ | 7253-60085 | 3/8–19 | 7/8–14 |
| G62150-0806 | 8MBSPT-6MJ | 7253-60095 | 1/2–14 | 9/16–18 |
| G62150-0808 | 8MBSPT-8MJ | 7253-14285 | 1/2–14 | 3/4–16 |
| G62150-0810 | 8MBSPT-10MJ | 7253-14295 | 1/2–14 | 7/8–14 |
| G62150-0812 | 8MBSPT-12MJ | 7253-60105 | 1/2–14 | 1 1/16–12 |
| G62150-1208 | 12MBSPT-8MJ | 7253-60115 | 3/4–14 | 3/4–16 |
| G62150-1210 | 12MBSPT-10MJ | 7253-60125 | 3/4–14 | 7/8–14 |
| G62150-1212 | 12MBSPT-12MJ | 7253-14305 | 3/4–14 | 1 1/16–12 |
| G62150-1214 | 12MBSPT-14MJ | 7253-60135 | 3/4–14 | 1 3/16–12 |
| G62150-1216 | 12MBSPT-16MJ | 7253-60145 | 3/4–14 | 1 5/16–12 |
| G62150-1612 | 16MBSPT-12MJ | 7253-60155 | 1–11 | 1 1/16–12 |
| G62150-1616 | 16MBSPT-16MJ | 7253-14315 | 1–11 | 1 5/16–12 |
| G62150-1620 | 16MBSPT-20MJ | 7253-60165 | 1–11 | 1 5/8–12 |
| G62150-2016 | 20MBSPT-16MJ | 7253-60175 | 1 1/4–11 | 1 5/16–12 |
| G62150-2020 | 20MBSPT-20MJ | 7253-60185 | 1 1/4–11 | 1 5/8–12 |
| G62150-2424 | 24MBSPT-24MJ | 7253-60195 | 1 1/2–11 | 1 7/8–12 |
| G62150-3232 | 32MBSPT-32MJ | 7253-60205 | 2–11 | 2 1/2–12 |

# Male British Standard Pipe Tapered Thread to Male JIC 37° Flare - 45°





| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62153-0204 | 2MBSPT-4MJ45 | 7253-60215 | 1/8–28 | 7/16–20 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male British Standard Pipe Tapered Thread to Male JIC 37° Flare - 45° - Continued

| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62153-0404 | 4MBSPT-4MJ45 | 7253-60225 | 1/4–19 | 7/16–20 |
| G62153-0406 | 4MBSPT-6MJ45 | 7253-60235 | 1/4–19 | 9/16–18 |
| G62153-0606 | 6MBSPT-6MJ45 | 7253-60245 | 3/8–19 | 9/16–18 |
| G62153-0608 | 6MBSPT-8MJ45 | 7253-60255 | 3/8–19 | 3/4–16 |
| G62153-0808 | 8MBSPT-8MJ45 | 7253-60265 | 1/2–14 | 3/4–16 |
| G62153-0810 | 8MBSPT-10MJ45 | 7253-60275 | 1/2–14 | 7/8–14 |
| G62153-1212 | 12MBSPT-12MJ45 | 7253-60285 | 3/4–14 | 1 1/16–12 |
| G62153-1216 | 12MBSPT-16MJ45 | 7253-60295 | 3/4–14 | 1 5/16–12 |
| G62153-1616 | 16MBSPT-16MJ45 | 7253-60305 | 1–11 | 1 5/16–12 |

## Male British Standard Pipe Tapered Thread to Male JIC 37° Flare - 90°













| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62155-0204 | 2MBSPT-4MJ90 | 7253-60315 | 1/8–28 | 7/16–20 |
| G62155-0404 | 4MBSPT-4MJ90 | 7253-60325 | 1/4–19 | 7/16–20 |
| G62155-0405 | 4MBSPT-5MJ90 | 7253-60335 | 1/4–19 | 1/2–20 |
| G62155-0406 | 4MBSPT-6MJ90 | 7253-60345 | 1/4–19 | 9/16–18 |
| G62155-0606 | 6MBSPT-6MJ90 | 7253-60355 | 3/8–19 | 9/16–18 |
| G62155-0608 | 6MBSPT-8MJ90 | 7253-60365 | 3/8–19 | 3/4–16 |
| G62155-0806 | 8MBSPT-6MJ90 | 7253-60375 | 1/2–14 | 9/16–18 |
| G62155-0808 | 8MBSPT-8MJ90 | 7253-60385 | 1/2–14 | 3/4–16 |
| G62155-0810 | 8MBSPT-10MJ90 | 7253-60395 | 1/2–14 | 7/8–14 |
| G62155-0812 | 8MBSPT-12MJ90 | 7253-60405 | 1/2–14 | 1 1/16–12 |
| G62155-1212 | 12MBSPT-12MJ90 | 7253-60415 | 3/4–14 | 1 1/16–12 |
| G62155-1216 | 12MBSPT-16MJ90 | 7253-60425 | 3/4–14 | 1 5/16–12 |
| G62155-1616 | 16MBSPT-16MJ90 | 7253-60435 | 1–11 | 1 5/16–12 |
| G62155-2020 | 20MBSPT-20MJ90 | 7253-60445 | 1 1/4–11 | 1 5/8–12 |
| G62155-2424 | 24MBSPT-24MJ90 | 7253-60455 | 1 1/2–11 | 1 7/8–12 |

# Male British Standard Pipe Parallel to Male Pipe NPTF












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62200-0202 | 2MBSPP-2MP | 7253-60475 | 1/8–28 | 1/8–27 |
| G62200-0204 | 2MBSPP-4MP | 7253-60485 | 1/8–28 | 1/4–18 |
| G62200-0402 | 4MBSPP-2MP | 7253-60495 | 1/4–19 | 1/8–27 |
| G62200-0404 | 4MBSPP-4MP | 7253-15075 | 1/4–19 | 1/4–18 |
| G62200-0406 | 4MBSPP-6MP | 7253-60505 | 1/4–19 | 3/8–18 |
| G62200-0408 | 4MBSPP-8MP | 7253-60515 | 1/4–19 | 1/2–14 |
| G62200-0602 | 6MBSPP-2MP | 7253-60525 | 3/8–19 | 1/8–27 |
| G62200-0604 | 6MBSPP-4MP | 7253-60535 | 3/8–19 | 1/4–18 |
| G62200-0606 | 6MBSPP-6MP | 7253-15085 | 3/8–19 | 3/8–18 |
| G62200-0608 | 6MBSPP-8MP | 7253-60545 | 3/8–19 | 1/2–14 |
| G62200-0612 | 6MBSPP-12MP | 7253-60555 | 3/8–19 | 3/4–14 |
| G62200-0616 | 6MBSPP-16MP | 7253-60565 | 3/8–19 | 1–11 1/2 |
| G62200-0804 | 8MBSPP-4MP | 7253-60575 | 1/2–14 | 1/4–18 |
| G62200-0806 | 8MBSPP-6MP | 7253-60585 | 1/2–14 | 3/8–18 |
| G62200-0808 | 8MBSPP-8MP | 7253-15095 | 1/2–14 | 1/2–14 |
| G62200-0812 | 8MBSPP-12MP | 7253-60595 | 1/2–14 | 3/4–14 |
| G62200-0816 | 8MBSPP-16MP | 7253-60605 | 1/2–14 | 1–11 1/2 |
| G62200-1008 | 10MBSPP-8MP | 7253-60615 | 5/8–14 | 1/2–14 |
| G62200-1012 | 10MBSPP-12MP | 7253-60625 | 5/8–14 | 3/4–14 |
| G62200-1208 | 12MBSPP-8MP | 7253-60635 | 3/4–14 | 1/2–14 |
| G62200-1212 | 12MBSPP-12MP | 7253-15105 | 3/4–14 | 3/4–14 |
| G62200-1216 | 12MBSPP-16MP | 7253-60645 | 3/4–14 | 1–11 1/2 |
| G62200-1220 | 12MBSPP-20MP | 7253-60655 | 3/4–14 | 1 1/4–11 1/2 |
| G62200-1612 | 16MBSPP-12MP | 7253-60665 | 1–11 | 3/4–14 |
| G62200-1616 | 16MBSPP-16MP | 7253-15115 | 1–11 | 1–11 1/2 |
| G62200-1620 | 16MBSPP-20MP | 7253-60675 | 1–11 | 1 1/4–11 1/2 |
| G62200-2016 | 20MBSPP-16MP | 7253-60685 | 1 1/4–11 | 1–11 1/2 |
| G62200-2020 | 20MBSPP-20MP | 7253-60695 | 1 1/4–11 | 1 1/4–11 1/2 |
| G62200-2024 | 20MBSPP-24MP | 7253-60705 | 1 1/4–11 | 1 1/2–11 1/2 |
| G62200-2420 | 24MBSPP-20MP | 7253-60715 | 1 1/2–11 | 1 1/4–11 1/2 |
| G62200-2424 | 24MBSPP-24MP | 7253-60725 | 1 1/2–11 | 1 1/2–11 1/2 |
| G62200-3232 | 32MBSPP-32MP | 7253-60735 | 2–11 | 2–11 1/2 |

# Male British Standard Pipe Parallel to Female Pipe NPTF







| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62220-0202 | 2MBSPP-2FP | 7253-60745 | 1/8–28 | 1/8–27 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male British Standard Pipe Parallel to Female Pipe NPTF - Continued

| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62220-0204 | 2MBSPP-4FP | 7253-60755 | 1/8–28 | 1/4–18 |
| G62220-0402 | 4MBSPP-2FP | 7253-60765 | 1/4–19 | 1/8–27 |
| G62220-0404 | 4MBSPP-4FP | 7253-60775 | 1/4–19 | 1/4–18 |
| G62220-0406 | 4MBSPP-6FP | 7253-60785 | 1/4–19 | 3/8–18 |
| G62220-0602 | 6MBSPP-2FP | 7253-60795 | 3/8–19 | 1/8–27 |
| G62220-0604 | 6MBSPP-4FP | 7253-60805 | 3/8–19 | 1/4–18 |
| G62220-0606 | 6MBSPP-6FP | 7253-60815 | 3/8–19 | 3/8–18 |
| G62220-0804 | 8MBSPP-4FP | 7253-60825 | 1/2–14 | 1/4–18 |
| G62220-0806 | 8MBSPP-6FP | 7253-60835 | 1/2–14 | 3/8–18 |
| G62220-0808 | 8MBSPP-8FP | 7253-60845 | 1/2–14 | 1/2–14 |
| G62220-1208 | 12MBSPP-8FP | 7253-60855 | 3/4–14 | 1/2–14 |
| G62220-1212 | 12MBSPP-12FP | 7253-60865 | 3/4–14 | 3/4–14 |
| G62220-1616 | 16MBSPP-16FP | 7253-60875 | 1–11 | 1–11 1/2 |
| G62220-2016 | 20MBSPP-16FP | 7253-60885 | 1 1/4–11 | 1–11 1/2 |
| G62220-2020 | 20MBSPP-20FP | 7253-60895 | 1 1/4–11 | 1 1/4–11 1/2 |
| G62220-2420 | 24MBSPP-20FP | 7253-60905 | 1 1/2–11 | 1 1/4–11 1/2 |
| G62220-2424 | 24MBSPP-24FP | 7253-60915 | 1 1/2–11 | 1 1/2–11 1/2 |
| G62220-3232 | 32MBSPP-32FP | 7253-60925 | 2–11 | 2–11 1/2 |

## Male British Standard Pipe Parallel to Male JIC 37° Flare









| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62300-0204 | 2MBSPP-4MJ | 7253-60935 | 1/8–28 | 7/16–20 |
| G62300-0205 | 2MBSPP-5MJ | 7253-60945 | 1/8–28 | 1/2–20 |
| G62300-0206 | 2MBSPP-6MJ | 7253-60955 | 1/8–28 | 9/16–18 |
| G62300-0404 | 4MBSPP-4MJ | 7253-15015 | 1/4–19 | 7/16–20 |
| G62300-0405 | 4MBSPP-5MJ | 7253-60965 | 1/4–19 | 1/2–20 |
| G62300-0406 | 4MBSPP-6MJ | 7253-60975 | 1/4–19 | 9/16–18 |
| G62300-0408 | 4MBSPP-8MJ | 7253-60985 | 1/4–19 | 3/4–16 |
| G62300-0604 | 6MBSPP-4MJ | 7253-60995 | 3/8–19 | 7/16–20 |
| G62300-0605 | 6MBSPP-5MJ | 7253-61005 | 3/8–19 | 1/2–20 |
| G62300-0606 | 6MBSPP-6MJ | 7253-15025 | 3/8–19 | 9/16–18 |
| G62300-0608 | 6MBSPP-8MJ | 7253-61015 | 3/8–19 | 3/4–16 |
| G62300-0806 | 8MBSPP-6MJ | 7253-61025 | 1/2–14 | 9/16–18 |
| G62300-0808 | 8MBSPP-8MJ | 7253-15035 | 1/2–14 | 3/4–16 |
| G62300-0810 | 8MBSPP-10MJ | 7253-61035 | 1/2–14 | 7/8–14 |
| G62300-0812 | 8MBSPP-12MJ | 7253-61045 | 1/2–14 | 1 1/16–12 |
| G62300-1008 | 10MBSPP-8MJ | 7253-61055 | 5/8–14 | 3/4–16 |
| G62300-1010 | 10MBSPP-10MJ | 7253-15045 | 5/8–14 | 7/8–14 |
| G62300-1012 | 10MBSPP-12MJ | 7253-61065 | 5/8–14 | 1 1/16–12 |
| G62300-1208 | 12MBSPP-8MJ | 7253-61075 | 3/4–14 | 3/4–16 |
| G62300-1210 | 12MBSPP-10MJ | 7253-61085 | 3/4–14 | 7/8–14 |
| G62300-1212 | 12MBSPP-12MJ | 7253-15055 | 3/4–14 | 1 1/16–12 |
| G62300-1214 | 12MBSPP-14MJ | 7253-61095 | 3/4–14 | 1 3/16–12 |


## Male British Standard Pipe Parallel to Male JIC 37° Flare - Continued

| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62300-1216 | 12MBSPP-16MJ | 7253-61105 | 3/4–14 | 1 5/16–12 |
| G62300-1612 | 16MBSPP-12MJ | 7253-61115 | 1–11 | 1 1/16–12 |
| G62300-1614 | 16MBSPP-14MJ | 7253-61125 | 1–11 | 1 3/16–12 |
| G62300-1616 | 16MBSPP-16MJ | 7253-15065 | 1–11 | 1 5/16–12 |
| G62300-1620 | 16MBSPP-20MJ | 7253-61135 | 1–11 | 1 5/8–12 |
| G62300-2016 | 20MBSPP-16MJ | 7253-61145 | 1 1/4–11 | 1 5/16–12 |
| G62300-2020 | 20MBSPP-20MJ | 7253-61155 | 1 1/4–11 | 1 5/8–12 |
| G62300-2024 | 20MBSPP-24MJ | 7253-61165 | 1 1/4–11 | 1 7/8–12 |
| G62300-2420 | 24MBSPP-20MJ | 7253-61175 | 1 1/2–11 | 1 5/8–12 |
| G62300-2424 | 24MBSPP-24MJ | 7253-61185 | 1 1/2–11 | 1 7/8–12 |
| G62300-3232 | 32MBSPP-32MJ | 7253-61195 | 2–11 | 2 1/2–12 |

## Male British Standard Pipe Parallel to Male JIC 37° Flare - 45°













| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62305-0204 | 2MBSPP-4MJ45 | 7253-61205 | 1/8–28 | 7/16–20 |
| G62305-0404 | 4MBSPP-4MJ45 | 7253-61215 | 1/4–19 | 7/16–20 |
| G62305-0406 | 4MBSPP-6MJ45 | 7253-61225 | 1/4–19 | 9/16–18 |
| G62305-0606 | 6MBSPP-6MJ45 | 7253-61235 | 3/8–19 | 9/16–18 |
| G62305-0608 | 6MBSPP-8MJ45 | 7253-61245 | 3/8–19 | 3/4–16 |
| G62305-0808 | 8MBSPP-8MJ45 | 7253-61255 | 1/2–14 | 3/4–16 |
| G62305-0810 | 8MBSPP-10MJ45 | 7253-61265 | 1/2–14 | 7/8–14 |
| G62305-0812 | 8MBSPP-12MJ45 | 7253-61275 | 1/2–14 | 1 1/16–12 |
| G62305-1212 | 12MBSPP-12MJ45 | 7253-61285 | 3/4–14 | 1 1/16–12 |
| G62305-1616 | 16MBSPP-16MJ45 | 7253-61295 | 1–11 | 1 5/16–12 |

# Male British Standard Pipe Parallel to Male JIC 37° Flare - 90°













| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62310-0204 | 2MBSPP-4MJ90 | 7253-61305 | 1/8–28 | 7/16–20 |
| G62310-0404 | 4MBSPP-4MJ90 | 7253-61315 | 1/4–19 | 7/16–20 |
| G62310-0405 | 4MBSPP-5MJ90 | 7253-61325 | 1/4–19 | 1/2–20 |
| G62310-0406 | 4MBSPP-6MJ90 | 7253-61335 | 1/4–19 | 9/16–18 |
| G62310-0408 | 4MBSPP-8MJ90 | 7253-61345 | 1/4–19 | 3/4–16 |
| G62310-0604 | 6MBSPP-4MJ90 | 7253-61355 | 3/8–19 | 7/16–20 |
| G62310-0605 | 6MBSPP-5MJ90 | 7253-61365 | 3/8–19 | 1/2–20 |
| G62310-0608 | 6MBSPP-8MJ90 | 7253-61385 | 3/8–19 | 3/4–16 |
| G62310-0806 | 8MBSPP-6MJ90 | 7253-61395 | 1/2–14 | 9/16–18 |
| G62310-0810 | 8MBSPP-10MJ90 | 7253-61415 | 1/2–14 | 7/8–14 |
| G62310-0812 | 8MBSPP-12MJ90 | 7253-61425 | 1/2–14 | 1 1/16–12 |
| G62310-1208 | 12MBSPP-8MJ90 | 7253-61435 | 3/4–14 | 3/4–16 |
| G62310-1210 | 12MBSPP-10MJ90 | 7253-61445 | 3/4–14 | 7/8–14 |
| G62310-1216 | 12MBSPP-16MJ90 | 7253-61465 | 3/4–14 | 1 5/16–12 |
| G62310-1612 | 16MBSPP-12MJ90 | 7253-61475 | 1–11 | 1 1/16–12 |
| G62310-1616 | 16MBSPP-16MJ90 | 7253-61485 | 1–11 | 1 5/16–12 |
| G62310-1620 | 16MBSPP-20MJ90 | 7253-61495 | 1–11 | 1 5/8–12 |
| G62310-2016 | 20MBSPP-16MJ90 | 7253-61505 | 1 1/4–11 | 1 5/16–12 |
| G62310-2020 | 20MBSPP-20MJ90 | 7253-61515 | 1 1/4–11 | 1 5/8–12 |
| G62310-2424 | 24MBSPP-24MJ90 | 7253-61525 | 1 1/2–11 | 1 7/8–12 |

# Male British Standard Pipe Parallel to Female JIC 37° Flare Swivel











| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62320-0204 | 2MBSPP-4FJX | 7253-61535 | 1/8–28 | 7/16–20 |
| G62320-0404 | 4MBSPP-4FJX | 7253-15125 | 1/4–19 | 7/16–20 |
| G62320-0405 | 4MBSPP-5FJX | 7253-61545 | 1/4–19 | 1/2–20 |
| G62320-0406 | 4MBSPP-6FJX | 7253-61555 | 1/4–19 | 9/16–18 |
| G62320-0604 | 6MBSPP-4FJX | 7253-61565 | 3/8–19 | 7/16–20 |
| G62320-0606 | 6MBSPP-6FJX | 7253-15135 | 3/8–19 | 9/16–18 |


## Male British Standard Pipe Parallel to Female JIC 37° Flare Swivel - Continued

| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62320-0608 | 6MBSPP-8FJX | 7253-61575 | 3/8–19 | 3/4–16 |
| G62320-0804 | 8MBSPP-4FJX | 7253-61585 | 1/2–14 | 7/16–20 |
| G62320-0806 | 8MBSPP-6FJX | 7253-61595 | 1/2–14 | 9/16–18 |
| G62320-0808 | 8MBSPP-8FJX | 7253-15145 | 1/2–14 | 3/4–16 |
| G62320-0810 | 8MBSPP-10FJX | 7253-61605 | 1/2–14 | 7/8–14 |
| G62320-0812 | 8MBSPP-12FJX | 7253-61615 | 1/2–14 | 1 1/16–12 |
| G62320-1008 | 10MBSPP-8FJX | 7253-61625 | 5/8–14 | 3/4–16 |
| G62320-1010 | 10MBSPP-10FJX | 7253-15155 | 5/8–14 | 7/8–14 |
| G62320-1208 | 12MBSPP-8FJX | 7253-61635 | 3/4–14 | 3/4–16 |
| G62320-1212 | 12MBSPP-12FJX | 7253-15165 | 3/4–14 | 1 1/16–12 |
| G62320-1216 | 12MBSPP-16FJX | 7253-61645 | 3/4–14 | 1 5/16–12 |
| G62320-1616 | 16MBSPP-16FJX | 7253-15175 | 1–11 | 1 5/16–12 |
| G62320-1620 | 16MBSPP-20FJX | 7253-61655 | 1–11 | 1 5/8–12 |
| G62320-2016 | 20MBSPP-16FJX | 7253-61665 | 1 1/4–11 | 1 5/16–12 |
| G62320-2020 | 20MBSPP-20FJX | 7253-61675 | 1 1/4–11 | 1 5/8–12 |
| G62320-2424 | 24MBSPP-24FJX | 7253-61685 | 1 1/2–11 | 1 7/8–12 |
| G62320-3232 | 32MBSPP-32FJX | 7253-61695 | 2–11 | 2 1/2–12 |

## Male British Standard Pipe Parallel with O-Ring to Male JIC 37° Flare













| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62450-0204 | 2MBSPPOR-4MJ | 7253-14005 | 1/8–28 | 7/16–20 |
| G62450-0404 | 4MBSPPOR-4MJ | 7253-14015 | 1/4–19 | 7/16–20 |
| G62450-0405 | 4MBSPPOR-5MJ | 7253-61705 | 1/4–19 | 1/2–20 |
| G62450-0406 | 4MBSPPOR-6MJ | 7253-14025 | 1/4–19 | 9/16–18 |
| G62450-0604 | 6MBSPPOR-4MJ | 7253-14035 | 3/8–19 | 7/16–20 |
| G62450-0605 | 6MBSPPOR-5MJ | 7253-61715 | 3/8–19 | 1/2–20 |
| G62450-0606 | 6MBSPPOR-6MJ | 7253-14045 | 3/8–19 | 9/16–18 |
| G62450-0608 | 6MBSPPOR-8MJ | 7253-14055 | 3/8–19 | 3/4–16 |
| G62450-0806 | 8MBSPPOR-6MJ | 7253-14075 | 1/2–14 | 9/16–18 |
| G62450-0808 | 8MBSPPOR-8MJ | 7253-14085 | 1/2–14 | 3/4–16 |
| G62450-0810 | 8MBSPPOR-10MJ | 7253-61725 | 1/2–14 | 7/8–14 |
| G62450-0812 | 8MBSPPOR-12MJ | 7253-14605 | 1/2–14 | 1 1/16–12 |
| G62450-1208 | 12MBSPPOR-8MJ | 7253-61735 | 3/4–14 | 3/4–16 |
| G62450-1210 | 12MBSPPOR-10MJ | 7253-61745 | 3/4–14 | 7/8–14 |
| G62450-1212 | 12MBSPPOR-12MJ | 7253-14095 | 3/4–14 | 1 1/16–12 |
| G62450-1216 | 12MBSPPOR-16MJ | 7253-61755 | 3/4–14 | 1 5/16–12 |
| G62450-1612 | 16MBSPPOR-12MJ | 7253-61765 | 1–11 | 1 1/16–12 |
| G62450-1616 | 16MBSPPOR-16MJ | 7253-14105 | 1–11 | 1 5/16–12 |
| G62450-2020 | 20MBSPPOR-20MJ | 7253-14115 | 1 1/4–11 | 1 5/8–12 |
| G62450-2024 | 20MBSPPOR-24MJ | 7253-61775 | 1 1/4–11 | 1 7/8–12 |
| G62450-2424 | 24MBSPPOR-24MJ | 7253-61785 | 1 1/2–11 | 1 7/8–12 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male British Standard Pipe Parallel with O-Ring to Male JIC 37° Flare - 90°













| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62460-0606 | 6MBSPPOR-6MJ90 | 7253-14505 | 3/8–19 | 9/16–18 |
| G62460-0808 | 8MBSPPOR-8MJ90 | 7253-14515 | 1/2–14 | 3/4–16 |
| G62460-1212 | 12MBSPPOR-12MJ90 | 7253-14525 | 3/4–14 | 1 1/16–12 |

# Male British Standard Pipe Parallel with O-Ring to Male Flat-Face O-Ring












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62470-0204 | 2MBSPPOR-4MFFOR | 7253-61795 | 1/8–28 | 9/16–18 |
| G62470-0404 | 4MBSPPOR-4MFFOR | 7253-61805 | 1/4–19 | 9/16–18 |
| G62470-0406 | 4MBSPPOR-6MFFOR | 7253-61815 | 1/4–19 | 11/16–16 |
| G62470-0606 | 6MBSPPOR-6MFFOR | 7253-61825 | 3/8–19 | 11/16–16 |
| G62470-0608 | 6MBSPPOR-8MFFOR | 7253-61835 | 3/8–19 | 13/16–16 |
| G62470-0806 | 8MBSPPOR-6MFFOR | 7253-61845 | 1/2–14 | 11/16–16 |
| G62470-0808 | 8MBSPPOR-8MFFOR | 7253-61855 | 1/2–14 | 13/16–16 |
| G62470-0810 | 8MBSPPOR-10MFFOR | 7253-61865 | 1/2–14 | 1–14 |
| G62470-1212 | 12MBSPPOR-12MFFOR | 7253-61875 | 3/4–14 | 1 3/16–12 |
| G62470-1216 | 12MBSPPOR-16MFFOR | 7253-61885 | 3/4–14 | 1 7/16–12 |
| G62470-1612 | 16MBSPPOR-12MFFOR | 7253-61895 | 1–11 | 1 3/16–12 |
| G62470-1616 | 16MBSPPOR-16MFFOR | 7253-61905 | 1–11 | 1 7/16–12 |
| G62470-2020 | 20MBSPPOR-20MFFOR | 7253-61915 | 1 1/4–11 | 1 11/16–12 |
| G62470-2424 | 24MBSPPOR-24MFFOR | 7253-61925 | 1 1/2–11 | 2–12 |

# Male British Standard Pipe Parallel with O-Ring to Male Flat-Face O-Ring - Long












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62471-0608 | 6MBSPPOR-8MFFORL | 7253-61935 | 3/8–19 | 13/16–16 |
| G62471-0808 | 8MBSPPOR-8MFFORL | 7253-61945 | 1/2–14 | 13/16–16 |
| G62471-0810 | 8MBSPPOR-10MFFORL | 7253-61955 | 1/2–14 | 1–14 |
| G62471-1210 | 12MBSPPOR-10MFFORL | 7253-61965 | 3/4–14 | 1–14 |
| G62471-1212 | 12MBSPPOR-12MFFORL | 7253-61975 | 3/4–14 | 1 3/16–12 |
| G62471-1616 | 16MBSPPOR-16MFFORL | 7253-61985 | 1–11 | 1 7/16–12 |
| G62471-2020 | 20MBSPPOR-20MFFORL | 7253-61995 | 1 1/4–11 | 1 11/16–12 |

# Male British Standard Pipe Parallel with O-Ring to Male Flat-Face O-Ring - 45°












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62473-0204 | 2MBSPPOR-4MFFOR45 | 7253-62005 | 1/8–28 | 9/16–18 |
| G62473-0404 | 4MBSPPOR-4MFFOR45 | 7253-62015 | 1/4–19 | 9/16–18 |
| G62473-0406 | 4MBSPPOR-6MFFOR45 | 7253-62025 | 1/4–19 | 11/16–16 |
| G62473-0606 | 6MBSPPOR-6MFFOR45 | 7253-62035 | 3/8–19 | 11/16–16 |
| G62473-0608 | 6MBSPPOR-8MFFOR45 | 7253-62045 | 3/8–19 | 13/16–16 |
| G62473-0808 | 8MBSPPOR-8MFFOR45 | 7253-62055 | 1/2–14 | 13/16–16 |
| G62473-0810 | 8MBSPPOR-10MFFOR45 | 7253-62065 | 1/2–14 | 1–14 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male British Standard Pipe Parallel with O-Ring to Male Flat-Face O-Ring - 90°











| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62475-0204 | 2MBSPPOR-4MFFOR90 | 7253-62075 | 1/8–28 | 9/16–18 |
| G62475-0404 | 4MBSPPOR-4MFFOR90 | 7253-62085 | 1/4–19 | 9/16–18 |
| G62475-0406 | 4MBSPPOR-6MFFOR90 | 7253-62095 | 1/4–19 | 11/16–16 |
| G62475-0408 | 4MBSPPOR-8MFFOR90 | 7253-62105 | 1/4–19 | 13/16–16 |
| G62475-0606 | 6MBSPPOR-6MFFOR90 | 7253-62115 | 3/8–19 | 11/16–16 |
| G62475-0608 | 6MBSPPOR-8MFFOR90 | 7253-62125 | 3/8–19 | 13/16–16 |
| G62475-0806 | 8MBSPPOR-6MFFOR90 | 7253-62135 | 1/2–14 | 11/16–16 |
| G62475-0808 | 8MBSPPOR-8MFFOR90 | 7253-62145 | 1/2–14 | 13/16–16 |
| G62475-0810 | 8MBSPPOR-10MFFOR90 | 7253-62155 | 1/2–14 | 1–14 |
| G62475-0812 | 8MBSPPOR-12MFFOR90 | 7253-62165 | 1/2–14 | 1 3/16–12 |
| G62475-1212 | 12MBSPPOR-12MFFOR90 | 7253-62175 | 3/4–14 | 1 3/16–12 |
| G62475-1216 | 12MBSPPOR-16MFFOR90 | 7253-62185 | 3/4–14 | 1 7/16–12 |
| G62475-1612 | 16MBSPPOR-12MFFOR90 | 7253-62195 | 1–11 | 1 3/16–12 |
| G62475-1616 | 16MBSPPOR-16MFFOR90 | 7253-62205 | 1–11 | 1 7/16–12 |
| G62475-2016 | 20MBSPPOR-16MFFOR90 | 7253-62215 | 1 1/4–11 | 1 7/16–12 |
| G62475-2020 | 20MBSPPOR-20MFFOR90 | 7253-62225 | 1 1/4–11 | 1 11/16–12 |
| G62475-2424 | 24MBSPPOR-24MFFOR90 | 7253-62235 | 1 1/2–11 | 2–12 |

# Female British Standard Pipe Parallel to Male Pipe NPTF











| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62500-0202 | 2FBSPP-2MP | 7253-62245 | 1/8–28 | 1/8–27 |
| G62500-0204 | 2FBSPP-4MP | 7253-62255 | 1/8–28 | 1/4–18 |
| G62500-0404 | 4FBSPP-4MP | 7253-62265 | 1/4–19 | 1/4–18 |
| G62500-0406 | 4FBSPP-6MP | 7253-62275 | 1/4–19 | 3/8–18 |
| G62500-0408 | 4FBSPP-8MP | 7253-62285 | 1/4–19 | 1/2–14 |
| G62500-0606 | 6FBSPP-6MP | 7253-62295 | 3/8–19 | 3/8–18 |
| G62500-0608 | 6FBSPP-8MP | 7253-62305 | 3/8–19 | 1/2–14 |
| G62500-0808 | 8FBSPP-8MP | 7253-62315 | 1/2–14 | 1/2–14 |
| G62500-0812 | 8FBSPP-12MP | 7253-62325 | 1/2–14 | 3/4–14 |
| G62500-1212 | 12FBSPP-12MP | 7253-62335 | 3/4–14 | 3/4–14 |
| G62500-1216 | 12FBSPP-16MP | 7253-62345 | 3/4–14 | 1–11 1/2 |
| G62500-1616 | 16FBSPP-16MP | 7253-62355 | 1–11 | 1–11 1/2 |

## Female British Standard Pipe Parallel to Male Pipe NPTF - Continued

| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62500-2020 | 20FBSPP-20MP | 7253-62365 | 1 1/4–11 | 1 1/4–11 1/2 |
| G62500-2024 | 20FBSPP-24MP | 7253-62375 | 1 1/4–11 | 1 1/2–11 1/2 |
| G62500-2424 | 24FBSPP-24MP | 7253-62385 | 1 1/2–11 | 1 1/2–11 1/2 |
| G62500-3232 | 32FBSPP-32MP | 7253-62395 | 2–11 | 2–11 1/2 |


## Female British Standard Pipe Parallel to Female Pipe NPTF







| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62520-0404 | 4FBSPP-4FP | 7253-65525 | 1/4–19 | 1/4–18 |
| G62520-0606 | 6FBSPP-6FP | 7253-65535 | 3/8–19 | 3/8–18 |
| G62520-0808 | 8FBSPP-8FP | 7253-65545 | 1/2–14 | 1/2–14 |
| G62520-1212 | 12FBSPP-12FP | 7253-65555 | 3/4–14 | 3/4–14 |
| G62520-1616 | 16FBSPP-16FP | 7253-65565 | 1–11 | 1–11 1/2 |
| G62520-2020 | 20FBSPP-20FP | 7253-65575 | 1 1/4–11 | 1 1/4–11 1/2 |

## Female British Standard Pipe Parallel to Male JIC 37° Flare









| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62550-0204 | 2FBSPP-4MJ | 7253-14155 | 1/8–28 | 7/16–20 |
| G62550-0404 | 4FBSPP-4MJ | 7253-14225 | 1/4–19 | 7/16–20 |
| G62550-0406 | 4FBSPP-6MJ | 7253-14165 | 1/4–19 | 9/16–18 |
| G62550-0606 | 6FBSPP-6MJ | 7253-14175 | 3/8–19 | 9/16–18 |
| G62550-0808 | 8FBSPP-8MJ | 7253-14185 | 1/2–14 | 3/4–16 |
| G62550-1212 | 12FBSPP-12MJ | 7253-14195 | 3/4–14 | 1 1/16–12 |
| G62550-1616 | 16FBSPP-16MJ | 7253-14205 | 1–11 | 1 5/16–12 |
| G62550-2020 | 20FBSPP-20MJ | 7253-14215 | 1 1/4–11 | 1 5/8–12 |
| G62550-2424 | 24FBSPP-24MJ | 7253-62415 | 1 1/2–11 | 1 7/8–12 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Female British Standard Pipe Parallel Swivel to Male Pipe NPTF - 90°







| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62605-0202 | 2FBSPPX-2MP90 | 7253-62425 | 1/8–28 | 1/8–27 |
| G62605-0404 | 4FBSPPX-4MP90 | 7253-62435 | 1/4–19 | 1/4–18 |
| G62605-0606 | 6FBSPPX-6MP90 | 7253-62445 | 3/8–19 | 3/8–18 |
| G62605-0808 | 8FBSPPX-8MP90 | 7253-62455 | 1/2–14 | 1/2–14 |
| G62605-1212 | 12FBSPPX-12MP90 | 7253-62465 | 3/4–14 | 3/4–14 |
| G62605-1616 | 16FBSPPX-16MP90 | 7253-62475 | 1–11 | 1–11 1/2 |
| G62605-2020 | 20FBSPPX-20MP90 | 7253-62485 | 1 1/4–11 | 1 1/4–11 1/2 |
| G62605-2424 | 24FBSPPX-24MP90 | 7253-62495 | 1 1/2–11 | 1 1/2–11 1/2 |


## Female British Standard Pipe Parallel Swivel to Male JIC 37° Flare







| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62650-0204 | 2FBSPPX-4MJ | 7253-62545 | 1/8–28 | 7/16–20 |
| G62650-0404 | 4FBSPPX-4MJ | 7253-15245 | 1/4–19 | 7/16–20 |
| G62650-0405 | 4FBSPPX-5MJ | 7253-62555 | 1/4–19 | 1/2–20 |
| G62650-0406 | 4FBSPPX-6MJ | 7253-62565 | 1/4–19 | 9/16–18 |
| G62650-0604 | 6FBSPPX-4MJ | 7253-62575 | 3/8–19 | 7/16–20 |
| G62650-0605 | 6FBSPPX-5MJ | 7253-62585 | 3/8–19 | 1/2–20 |
| G62650-0606 | 6FBSPPX-6MJ | 7253-15255 | 3/8–19 | 9/16–18 |
| G62650-0608 | 6FBSPPX-8MJ | 7253-62595 | 3/8–19 | 3/4–16 |
| G62650-0610 | 6FBSPPX-10MJ | 7253-62605 | 3/8–19 | 7/8–14 |
| G62650-0806 | 8FBSPPX-6MJ | 7253-62615 | 1/2–14 | 9/16–18 |
| G62650-0808 | 8FBSPPX-8MJ | 7253-15265 | 1/2–14 | 3/4–16 |
| G62650-0810 | 8FBSPPX-10MJ | 7253-62625 | 1/2–14 | 7/8–14 |
| G62650-1008 | 10FBSPPX-8MJ | 7253-62635 | 5/8–14 | 3/4–16 |
| G62650-1010 | 10FBSPPX-10MJ | 7253-15275 | 5/8–14 | 7/8–14 |
| G62650-1208 | 12FBSPPX-8MJ | 7253-62645 | 3/4–14 | 3/4–16 |
| G62650-1210 | 12FBSPPX-10MJ | 7253-62655 | 3/4–14 | 7/8–14 |
| G62650-1212 | 12FBSPPX-12MJ | 7253-15285 | 3/4–14 | 1 1/16–12 |
| G62650-1216 | 12FBSPPX-16MJ | 7253-62665 | 3/4–14 | 1 5/16–12 |
| G62650-1612 | 16FBSPPX-12MJ | 7253-62675 | 1–11 | 1 1/16–12 |
| G62650-1616 | 16FBSPPX-16MJ | 7253-15295 | 1–11 | 1 5/16–12 |
| G62650-2020 | 20FBSPPX-20MJ | 7253-62685 | 1 1/4–11 | 1 5/8–12 |
| G62650-2424 | 24FBSPPX-24MJ | 7253-62695 | 1 1/2–11 | 1 7/8–12 |


# Female British Standard Pipe Parallel Swivel to Female JIC 37° Flare Swivel








| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62660-0404 | 4FBSPPX-4FJX | 7253-15305 | 1/4–19 | 7/16–20 |
| G62660-0406 | 4FBSPPX-6FJX | 7253-62505 | 1/4–19 | 9/16–18 |
| G62660-0606 | 6FBSPPX-6FJX | 7253-15315 | 3/8–19 | 9/16–18 |
| G62660-0608 | 6FBSPPX-8FJX | 7253-62515 | 3/8–19 | 3/4–16 |
| G62660-0806 | 8FBSPPX-6FJX | 7253-62525 | 1/2–14 | 9/16–18 |
| G62660-0808 | 8FBSPPX-8FJX | 7253-15325 | 1/2–14 | 3/4–16 |
| G62660-1010 | 10FBSPPX-10FJX | 7253-15335 | 5/8–14 | 7/8–14 |
| G62660-1212 | 12FBSPPX-12FJX | 7253-15345 | 3/4–14 | 1 1/16–12 |
| G62660-1616 | 16FBSPPX-16FJX | 7253-15355 | 1–11 | 1 5/16–12 |
| G62660-2020 | 20FBSPPX-20FJX | 7253-62535 | 1 1/4–11 | 1 5/8–12 |

# Female British Flat-Face O-Ring to Male JIC 37° Flare






| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G62801-0606 | 6FBFFOR-6MJ | 7253-62705 | 3/8–19 | 9/16–18 |
| G62801-0806 | 8FBFFOR-6MJ | 7253-62715 | 1/2–14 | 9/16–18 |
| G62801-0808 | 8FBFFOR-8MJ | 7253-62725 | 1/2–14 | 3/4–16 |
| G62801-0810 | 8FBFFOR-10MJ | 7253-62735 | 1/2–14 | 7/8–14 |
| G62801-1008 | 10FBFFOR-8MJ | 7253-62745 | 5/8–14 | 3/4–16 |
| G62801-1208 | 12FBFFOR-8MJ | 7253-62755 | 3/4–14 | 3/4–16 |
| G62801-1210 | 12FBFFOR-10MJ | 7253-62765 | 3/4–14 | 7/8–14 |
| G62801-1212 | 12FBFFOR-12MJ | 7253-62775 | 3/4–14 | 1 1/16–12 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Male Metric O-Ring Plug




| Part No. | Descr. | Prod. No. | " |
|---|---|---|---|
| G63099-0012 | 12MMOR-PLUG | 7253-65415 | M12X1.5 |
| G63099-0014 | 14MMOR-PLUG | 7253-65425 | M14X1.5 |
| G63099-0016 | 16MMOR-PLUG | 7253-65435 | M16X1.5 |
| G63099-0018 | 18MMOR-PLUG | 7253-65445 | M18X1.5 |
| G63099-0020 | 20MMOR-PLUG | 7253-65455 | M20X1.5 |
| G63099-0022 | 22MMOR-PLUG | 7253-65465 | M22X1.5 |
| G63099-0024 | 24MMOR-PLUG | 7253-65475 | M24X1.5 |
| G63099-0026 | 26MMOR-PLUG | 7253-65485 | M26X1.5 |
| G63099-0030 | 30MMOR-PLUG | 7253-65495 | M30X2.0 |
| G63099-0036 | 36MMOR-PLUG | 7253-65505 | M36X2.0 |
| G63099-0042 | 42MMOR-PLUG | 7253-65515 | M42X2.0 |

# Male Metric with O-Ring to Female Pipe NPTF












| Part No. | Descr. | Prod. No. | " | " |
|---|---|---|---|---|
| G63120-1002 | 10MM-2FP | 7253-62785 | M10X1.0 | 1/8–27 |
| G63120-1202 | 12MM-2FP | 7253-62795 | M12X1.5 | 1/8–27 |
| G63120-1204 | 12MM-4FP | 7253-62805 | M12X1.5 | 1/4–18 |
| G63120-1206 | 12MM-6FP | 7253-62815 | M12X1.5 | 3/8–18 |
| G63120-1404 | 14MM-4FP | 7253-62825 | M14X1.5 | 1/4–18 |
| G63120-1606 | 16MM-6FP | 7253-62835 | M16X1.5 | 3/8–18 |
| G63120-1608 | 16MM-8FP | 7253-62845 | M16X1.5 | 1/2–14 |
| G63120-1806 | 18MM-6FP | 7253-62855 | M18X1.5 | 3/8–18 |
| G63120-1808 | 18MM-8FP | 7253-62865 | M18X1.5 | 1/2–14 |
| G63120-2004 | 20MM-4FP | 7253-62875 | M20X1.5 | 1/4–18 |
| G63120-2006 | 20MM-6FP | 7253-62885 | M20X1.5 | 3/8–18 |
| G63120-2008 | 20MM-8FP | 7253-62895 | M20X1.5 | 1/2–14 |
| G63120-2206 | 22MM-6FP | 7253-62905 | M22X1.5 | 3/8–18 |
| G63120-2208 | 22MM-8FP | 7253-62915 | M22X1.5 | 1/2–14 |
| G63120-2212 | 22MM-12FP | 7253-62925 | M22X1.5 | 3/4–14 |
| G63120-2412 | 24MM-12FP | 7253-62935 | M24X1.5 | 3/4–14 |
| G63120-2612 | 26MM-12FP | 7253-62945 | M26X1.5 | 3/4–14 |
| G63120-2712 | 27MM-12FP | 7253-62955 | M27X2.0 | 3/4–14 |
| G63120-3316 | 33MM-16FP | 7253-62965 | M33X2.0 | 1–11 1/2 |

# Male Metric with O-Ring to Male JIC 37° Flare













| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G63150-1004 | 10MM-4MJ | 7253-14355 | M10X1.0 | 7/16–20 |
| G63150-1204 | 12MM-4MJ | 7253-14365 | M12X1.5 | 7/16–20 |
| G63150-1205 | 12MM-5MJ | 7253-62975 | M12X1.5 | 1/2–20 |
| G63150-1206 | 12MM-6MJ | 7253-62985 | M12X1.5 | 9/16–18 |
| G63150-1404 | 14MM-4MJ | 7253-62995 | M14X1.5 | 7/16–20 |
| G63150-1406 | 14MM-6MJ | 7253-14375 | M14X1.5 | 9/16–18 |
| G63150-1408 | 14MM-8MJ | 7253-63005 | M14X1.5 | 3/4–16 |
| G63150-1605 | 16MM-5MJ | 7253-63015 | M16X1.5 | 1/2–20 |
| G63150-1606 | 16MM-6MJ | 7253-14385 | M16X1.5 | 9/16–18 |
| G63150-1608 | 16MM-8MJ | 7253-14395 | M16X1.5 | 3/4–16 |
| G63150-1808 | 18MM-8MJ | 7253-14405 | M18X1.5 | 3/4–16 |
| G63150-1810 | 18MM-10MJ | 7253-14415 | M18X1.5 | 7/8–14 |
| G63150-2010 | 20MM-10MJ | 7253-14425 | M20X1.5 | 7/8–14 |
| G63150-2208 | 22MM-8MJ | 7253-63025 | M22X1.5 | 3/4–16 |
| G63150-2210 | 22MM-10MJ | 7253-14435 | M22X1.5 | 7/8–14 |
| G63150-2212 | 22MM-12MJ | 7253-14445 | M22X1.5 | 1 1/16–12 |
| G63150-2612 | 26MM-12MJ | 7253-63035 | M26X1.5 | 1 1/16–12 |
| G63150-2712 | 27MM-12MJ | 7253-14455 | M27X2.0 | 1 1/16–12 |
| G63150-2716 | 27MM-16MJ | 7253-63045 | M27X2.0 | 1 5/16–12 |
| G63150-3316 | 33MM-16MJ | 7253-14465 | M33X2.0 | 1 5/16–12 |
| G63150-3320 | 33MM-20MJ | 7253-63055 | M33X2.0 | 1 5/8–12 |
| G63150-4220 | 42MM-20MJ | 7253-14475 | M42X2.0 | 1 5/8–12 |
| G63150-4824 | 48MM-24MJ | 7253-63065 | M48X2.0 | 1 7/8–12 |

# Male Metric with O-Ring to Male JIC 37° Flare - 90°






| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G63160-1004 | 10MM-4MJ90 | 7253-65585 | M10X1.0 | 7/16–20 |
| G63160-1204 | 12MM-4MJ90 | 7253-65595 | M12X1.5 | 7/16–20 |
| G63160-1205 | 12MM-5MJ90 | 7253-65615 | M12X1.5 | 1/2–20 |
| G63160-1206 | 12MM-6MJ90 | 7253-65625 | M12X1.5 | 9/16–18 |
| G63160-1404 | 14MM-4MJ90 | 7253-65605 | M14X1.5 | 7/16–20 |
| G63160-1406 | 14MM-6MJ90 | 7253-65635 | M14X1.5 | 9/16–18 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male Metric with O-Ring to Male JIC 37° Flare - 90° - Continued

| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G63160-1606 | 16MM-6MJ90 | 7253-65645 | M16X1.5 | 9/16–18 |
| G63160-1608 | 16MM-8MJ90 | 7253-65655 | M16X1.5 | 3/4–16 |
| G63160-1808 | 18MM-8MJ90 | 7253-65665 | M18X1.5 | 3/4–16 |
| G63160-1810 | 18MM-10MJ90 | 7253-65685 | M18X1.5 | 7/8–14 |
| G63160-2010 | 20MM-10MJ90 | 7253-65695 | M20X1.5 | 7/8–14 |
| G63160-2208 | 22MM-8MJ90 | 7253-65675 | M22X1.5 | 3/4–16 |
| G63160-2210 | 22MM-10MJ90 | 7253-65705 | M22X1.5 | 7/8–14 |
| G63160-2212 | 22MM-12MJ90 | 7253-65715 | M22X1.5 | 1 1/16–12 |
| G63160-2612 | 26MM-12MJ90 | 7253-65725 | M26X1.5 | 1 1/16–12 |
| G63160-2716 | 27MM-16MJ90 | 7253-65735 | M27X2.0 | 1 5/16–12 |
| G63160-3316 | 33MM-16MJ90 | 7253-65745 | M33X2.0 | 1 5/16–12 |
| G63160-4220 | 42MM-20MJ90 | 7253-65755 | M42X2.0 | 1 5/8–12 |

## Male DIN 24° Cone - Light Series to Male JIC 37° Flare













| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G63350-0604 | 6MDL-4MJ | 7253-63075 | M12X1.5 | 7/16–20 |
| G63350-0804 | 8MDL-4MJ | 7253-15365 | M14X1.5 | 7/16–20 |
| G63350-0806 | 8MDL-6MJ | 7253-63095 | M14X1.5 | 9/16–18 |
| G63350-1004 | 10MDL-4MJ | 7253-63105 | M16X1.5 | 7/16–20 |
| G63350-1006 | 10MDL-6MJ | 7253-15375 | M16X1.5 | 9/16–18 |
| G63350-1008 | 10MDL-8MJ | 7253-63115 | M16X1.5 | 3/4–16 |
| G63350-1206 | 12MDL-6MJ | 7253-15585 | M18X1.5 | 9/16–18 |
| G63350-1208 | 12MDL-8MJ | 7253-63135 | M18X1.5 | 3/4–16 |
| G63350-1508 | 15MDL-8MJ | 7253-15385 | M22X1.5 | 3/4–16 |
| G63350-1510 | 15MDL-10MJ | 7253-63145 | M22X1.5 | 7/8–14 |
| G63350-1512 | 15MDL-12MJ | 7253-63155 | M22X1.5 | 1 1/16–12 |
| G63350-1810 | 18MDL-10MJ | 7253-15515 | M26X1.5 | 7/8–14 |
| G63350-1812 | 18MDL-12MJ | 7253-63165 | M26X1.5 | 1 1/16–12 |
| G63350-2212 | 22MDL-12MJ | 7253-15395 | M30X2.0 | 1 1/16–12 |
| G63350-2816 | 28MDL-16MJ | 7253-15405 | M36X2.0 | 1 5/16–12 |
| G63350-3520 | 35MDL-20MJ | 7253-63175 | M45X2.0 | 1 5/8–12 |
| G63350-4224 | 42MDL-24MJ | 7253-63185 | M52X2.0 | 1 7/8–12 |

# Female DIN 24° Cone Swivel - Light Series to Male JIC 37° Flare













| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G63450-0604 | 6FDLX-4MJ | 7253-64725 | M12X1.5 | 7/16–20 |
| G63450-0605 | 6FDLX-5MJ | 7253-64735 | M12X1.5 | 1/2–20 |
| G63450-0804 | 8FDLX-4MJ | 7253-15465 | M14X1.5 | 7/16–20 |
| G63450-0806 | 8FDLX-6MJ | 7253-64755 | M14X1.5 | 9/16–18 |
| G63450-1006 | 10FDLX-6MJ | 7253-15475 | M16X1.5 | 9/16–18 |
| G63450-1008 | 10FDLX-8MJ | 7253-64775 | M16X1.5 | 3/4–16 |
| G63450-1206 | 12FDLX-6MJ | 7253-15545 | M18X1.5 | 9/16–18 |
| G63450-1208 | 12FDLX-8MJ | 7253-64795 | M18X1.5 | 3/4–16 |
| G63450-1210 | 12FDLX-10MJ | 7253-64805 | M18X1.5 | 7/8–14 |
| G63450-1506 | 15FDLX-6MJ | 7253-64815 | M22X1.5 | 9/16–18 |
| G63450-1508 | 15FDLX-8MJ | 7253-15485 | M22X1.5 | 3/4–16 |
| G63450-1510 | 15FDLX-10MJ | 7253-64835 | M22X1.5 | 7/8–14 |
| G63450-2212 | 22FDLX-12MJ | 7253-15495 | M30X2.0 | 1 1/16–12 |
| G63450-2816 | 28FDLX-16MJ | 7253-15505 | M36X2.0 | 1 5/16–12 |

# Male DIN 24° Cone - Heavy Series to Male JIC 37° Flare




| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G63650-0604 | 6MDH-4MJ | 7253-63195 | M14X1.5 | 7/16–20 |
| G63650-0804 | 8MDH-4MJ | 7253-63205 | M16X1.5 | 7/16–20 |
| G63650-0806 | 8MDH-6MJ | 7253-63215 | M16X1.5 | 9/16–18 |
| G63650-1004 | 10MDH-4MJ | 7253-15415 | M18X1.5 | 7/16–20 |
| G63650-1008 | 10MDH-8MJ | 7253-63225 | M18X1.5 | 3/4–16 |
| G63650-1206 | 12MDH-6MJ | 7253-63235 | M20X1.5 | 9/16–18 |
| G63650-1208 | 12MDH-8MJ | 7253-63245 | M20X1.5 | 3/4–16 |
| G63650-1210 | 12MDH-10MJ | 7253-63255 | M20X1.5 | 7/8–14 |
| G63650-1406 | 14MDH-6MJ | 7253-15425 | M22X1.5 | 9/16–18 |
| G63650-1408 | 14MDH-8MJ | 7253-63265 | M22X1.5 | 3/4–16 |
| G63650-1608 | 16MDH-8MJ | 7253-15435 | M24X1.5 | 3/4–16 |
| G63650-1610 | 16MDH-10MJ | 7253-63285 | M24X1.5 | 7/8–14 |
| G63650-1612 | 16MDH-12MJ | 7253-63275 | M24X1.5 | 1 1/16–12 |
| G63650-2010 | 20MDH-10MJ | 7253-15525 | M30X2.0 | 7/8–14 |
| G63650-2012 | 20MDH-12MJ | 7253-63295 | M30X2.0 | 1 1/16–12 |
| G63650-2512 | 25MDH-12MJ | 7253-15445 | M36X2.0 | 1 1/16–12 |
| G63650-2516 | 25MDH-16MJ | 7253-63305 | M36X2.0 | 1 5/16–12 |
| G63650-3016 | 30MDH-16MJ | 7253-15455 | M42X2.0 | 1 5/16–12 |
| G63650-3820 | 38MDH-20MJ | 7253-63315 | M52X2.0 | 1 5/8–12 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male DIN 24° Cone - Heavy Series to Male JIC 37° Flare - Continued

| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G63650-3824 | 38MDH-24MJ | 7253-63325 | M52X2.0 | 1 7/8–12 |

## Female DIN 24° Cone Swivel - Heavy Series to Male JIC 37° Flare









| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G63750-1004 | 10FDHX-4MJ | 7253-15605 | M18X1.5 | 7/16–20 |
| G63750-1205 | 12FDHX-5MJ | 7253-15615 | M20X1.5 | 1/2–20 |
| G63750-1206 | 12FDHX-6MJ | 7253-64845 | M20X1.5 | 9/16–18 |
| G63750-1208 | 12FDHX-8MJ | 7253-64855 | M20X1.5 | 3/4–16 |
| G63750-1210 | 12FDHX-10MJ | 7253-64865 | M20X1.5 | 7/8–14 |
| G63750-1406 | 14FDHX-6MJ | 7253-15625 | M22X1.5 | 9/16–18 |
| G63750-1608 | 16FDHX-8MJ | 7253-15635 | M24X1.5 | 3/4–16 |
| G63750-2010 | 20FDHX-10MJ | 7253-15645 | M30X2.0 | 7/8–14 |
| G63750-2512 | 25FDHX-12MJ | 7253-15655 | M36X2.0 | 1 1/16–12 |
| G63750-3016 | 30FDHX-16MJ | 7253-15665 | M42X2.0 | 1 5/16–12 |
| G63750-3820 | 38FDHX-20MJ | 7253-15675 | M52X2.0 | 1 5/8–12 |


## Male Kobelco Plug








| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| | | | " |
| G63980-0022 | 22MKB-PLUG | 7253-65295 | M30X1.5 |

# Male Kobelco to Male JIC 37° Flare




| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G63990-2212 | 22MKB-12MJ | 7253-66105 | M30X1.5 | 1 1/16–12 |
| G63990-2812 | 28MKB-12MJ | 7253-65305 | M36X1.5 | 1 1/16–12 |
| G63990-2816 | 28MKB-16MJ | 7253-65315 | M36X1.5 | 1 5/16–12 |
| G63990-3516 | 35MKB-16MJ | 7253-65325 | M45X1.5 | 1 5/16–12 |
| G63990-3520 | 35MKB-20MJ | 7253-65335 | M45X1.5 | 1 5/8–12 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# British Bonded Seal



| Part No. | Descr. | Prod. No. | ⟷ " |
|---|---|---|---|
| G64075-0002 | 2BBDS | 7253-63335 | 3/8 |
| G64075-0004 | 4BBDS | 7253-63345 | 17/32 |
| G64075-0006 | 6BBDS | 7253-63355 | 21/32 |
| G64075-0008 | 8BBDS | 7253-63365 | 13/16 |
| G64075-0010 | 10BBDS | 7253-63375 | 29/32 |
| G64075-0012 | 12BBDS | 7253-63385 | 1 1/32 |
| G64075-0016 | 16BBDS | 7253-63395 | 1 11/32 |
| G64075-0020 | 20BBDS | 7253-63405 | 1 21/32 |
| G64075-0024 | 24BBDS | 7253-63415 | 1 7/8 |
| G64075-0032 | 32BBDS | 7253-63425 | 2 11/32 |
| G64075-0040 | 40BBDS | 7253-63435 | 2 1/2 |
| G64075-0048 | 48BBDS | 7253-63445 | 3 |


# Male British Standard Pipe Parallel with O-Ring Plug







| Part No. | Descr. | Prod. No. | ||| " |
|---|---|---|---|
| G64094-0002 | 2MBSPOR-PLUG | 7253-65345 | 1/8–28 |
| G64094-0004 | 4MBSPOR-PLUG | 7253-65355 | 1/4–19 |
| G64094-0006 | 6MBSPOR-PLUG | 7253-65365 | 3/8–19 |
| G64094-0008 | 8MBSPOR-PLUG | 7253-65375 | 1/2–14 |
| G64094-0012 | 12MBSPOR-PLUG | 7253-65385 | 3/4–14 |
| G64094-0016 | 16MBSPOR-PLUG | 7253-65395 | 1–11 |
| G64094-0020 | 20MBSPOR-PLUG | 7253-65405 | 1 1/4–11 |


# Female British Standard Pipe Parallel Cap



| Part No. | Descr. | Prod. No. | " |
|---|---|---|---|
| G64097-0002 | 2FBSPP-CAP | 7253-63455 | 1/8–28 |
| G64097-0004 | 4FBSPP-CAP | 7253-63465 | 1/4–19 |
| G64097-0006 | 6FBSPP-CAP | 7253-63475 | 3/8–19 |
| G64097-0008 | 8FBSPP-CAP | 7253-63485 | 1/2–14 |
| G64097-0010 | 10FBSPP-CAP | 7253-63495 | 5/8–14 |
| G64097-0012 | 12FBSPP-CAP | 7253-63505 | 3/4–14 |
| G64097-0016 | 16FBSPP-CAP | 7253-63515 | 1–11 |
| G64097-0020 | 20FBSPP-CAP | 7253-63525 | 1 1/4–11 |
| G64097-0024 | 24FBSPP-CAP | 7253-63535 | 1 1/2–11 |
| G64097-0032 | 32FBSPP-CAP | 7253-63545 | 2–11 |

# Male British Standard Pipe Tapered Thread Plug








| Part No. | Descr. | Prod. No. | " |
|---|---|---|---|
| G64098-0002 | 2MBSPT-PLUG | 7253-63555 | 1/8–28 |
| G64098-0004 | 4MBSPT-PLUG | 7253-63565 | 1/4–19 |
| G64098-0006 | 6MBSPT-PLUG | 7253-63575 | 3/8–19 |
| G64098-0008 | 8MBSPT-PLUG | 7253-63585 | 1/2–14 |
| G64098-0010 | 10MBSPT-PLUG | 7253-63595 | 5/8–14 |
| G64098-0012 | 12MBSPT-PLUG | 7253-63605 | 3/4–14 |
| G64098-0016 | 16MBSPT-PLUG | 7253-63615 | 1–11 |
| G64098-0020 | 20MBSPT-PLUG | 7253-63625 | 1 1/4–11 |
| G64098-0024 | 24MBSPT-PLUG | 7253-63635 | 1 1/2–11 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Male British Standard Pipe Parallel Plug







| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| | | | " |
| G64099-0002 | 2MBSPP-PLUG | 7253-63655 | 1/8–28 |
| G64099-0004 | 4MBSPP-PLUG | 7253-63665 | 1/4–19 |
| G64099-0006 | 6MBSPP-PLUG | 7253-63675 | 3/8–19 |
| G64099-0008 | 8MBSPP-PLUG | 7253-63685 | 1/2–14 |
| G64099-0010 | 10MBSPP-PLUG | 7253-63695 | 5/8–14 |
| G64099-0012 | 12MBSPP-PLUG | 7253-63705 | 3/4–14 |
| G64099-0016 | 16MBSPP-PLUG | 7253-63715 | 1–11 |
| G64099-0020 | 20MBSPP-PLUG | 7253-63725 | 1 1/4–11 |
| G64099-0024 | 24MBSPP-PLUG | 7253-63735 | 1 1/2–11 |
| G64099-0032 | 32MBSPP-PLUG | 7253-63745 | 2–11 |

# Male British Standard Pipe Parallel to Female British Standard Pipe Parallel Swivel






| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G64350-0202 | 2MBSPP-2FBSPPX | 7253-63775 | 1/8–28 | 1/8–28 |
| G64350-0204 | 2MBSPP-4FBSPPX | 7253-63785 | 1/8–28 | 1/4–19 |
| G64350-0402 | 4MBSPP-2FBSPPX | 7253-63795 | 1/4–19 | 1/8–28 |
| G64350-0404 | 4MBSPP-4FBSPPX | 7253-15185 | 1/4–19 | 1/4–19 |
| G64350-0406 | 4MBSPP-6FBSPPX | 7253-63805 | 1/4–19 | 3/8–19 |
| G64350-0408 | 4MBSPP-8FBSPPX | 7253-63815 | 1/4–19 | 1/2–14 |
| G64350-0604 | 6MBSPP-4FBSPPX | 7253-63825 | 3/8–19 | 1/4–19 |
| G64350-0606 | 6MBSPP-6FBSPPX | 7253-15195 | 3/8–19 | 3/8–19 |
| G64350-0608 | 6MBSPP-8FBSPPX | 7253-63835 | 3/8–19 | 1/2–14 |
| G64350-0806 | 8MBSPP-6FBSPPX | 7253-63845 | 1/2–14 | 3/8–19 |
| G64350-0808 | 8MBSPP-8FBSPPX | 7253-15205 | 1/2–14 | 1/2–14 |
| G64350-0810 | 8MBSPP-10FBSPPX | 7253-63855 | 1/2–14 | 5/8–14 |
| G64350-0812 | 8MBSPP-12FBSPPX | 7253-63865 | 1/2–14 | 3/4–14 |
| G64350-1008 | 10MBSPP-8FBSPPX | 7253-63875 | 5/8–14 | 1/2–14 |
| G64350-1010 | 10MBSPP-10FBSPPX | 7253-15215 | 5/8–14 | 5/8–14 |
| G64350-1012 | 10MBSPP-12FBSPPX | 7253-63885 | 5/8–14 | 3/4–14 |
| G64350-1206 | 12MBSPP-6FBSPPX | 7253-63895 | 3/4–14 | 3/8–19 |
| G64350-1208 | 12MBSPP-8FBSPPX | 7253-63905 | 3/4–14 | 1/2–14 |
| G64350-1210 | 12MBSPP-10FBSPPX | 7253-63915 | 3/4–14 | 5/8–14 |
| G64350-1212 | 12MBSP-12FBSPX | 7253-15225 | 3/4–14 | 3/4–14 |
| G64350-1216 | 12MBSPP-16FBSPPX | 7253-63925 | 3/4–14 | 1–11 |
| G64350-1220 | 12MBSPP-20FBSPPX | 7253-63935 | 3/4–14 | 1 1/4–11 |

## Male British Standard Pipe Parallel to Female British Standard Pipe Parallel Swivel - Continued

| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G64350-1612 | 16MBSPP-12FBSPPX | 7253-63945 | 1–11 | 3/4–14 |
| G64350-1616 | 16MBSPP-16FBSPPX | 7253-15235 | 1–11 | 1–11 |
| G64350-1620 | 16MBSPP-20FBSPPX | 7253-63955 | 1–11 | 1 1/4–11 |
| G64350-2016 | 20MBSPP-16FBSPPX | 7253-63965 | 1 1/4–11 | 1–11 |
| G64350-2020 | 20MBSPP-20FBSPPX | 7253-63975 | 1 1/4–11 | 1 1/4–11 |
| G64350-2024 | 20MBSPP-24FBSPPX | 7253-63985 | 1 1/4–11 | 1 1/2–11 |
| G64350-2420 | 24MBSPP-20FBSPPX | 7253-63995 | 1 1/2–11 | 1 1/4–11 |
| G64350-2424 | 24MBSPP-24FBSPPX | 7253-64005 | 1 1/2–11 | 1 1/2–11 |
| G64350-3232 | 32MBSPP-32FBSPPX | 7253-64015 | 2–11 | 2–11 |

## Metric Bonded Seal



| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| | | | mm |
| G64775-0006 | 6MBDS | 7253-64025 | 6.0 |
| G64775-0008 | 8MBDS | 7253-64035 | 8.0 |
| G64775-0010 | 10MBDS | 7253-64045 | 10.0 |
| G64775-0012 | 12MBDS | 7253-64055 | 12.0 |
| G64775-0014 | 14MBDS | 7253-64065 | 14.0 |
| G64775-0016 | 16MBDS | 7253-64075 | 16.0 |
| G64775-0018 | 18MBDS | 7253-64085 | 18.0 |
| G64775-0020 | 20MBDS | 7253-64095 | 20.0 |
| G64775-0022 | 22MBDS | 7253-64105 | 22.0 |
| G64775-0024 | 24MBDS | 7253-64115 | 24.0 |
| G64775-0026 | 26MBDS | 7253-64125 | 26.0 |
| G64775-0027 | 27MBDS | 7253-64135 | 27.0 |
| G64775-0030 | 30MBDS | 7253-64145 | 30.0 |
| G64775-0033 | 33MBDS | 7253-64155 | 33.0 |
| G64775-0036 | 36MBDS | 7253-64165 | 36.0 |
| G64775-0042 | 42MBDS | 7253-64175 | 42.0 |
| G64775-0045 | 45MBDS | 7253-64185 | 45.0 |
| G64775-0050 | 50MBDS | 7253-64195 | 50.0 |
| G64775-0052 | 52MBDS | 7253-64205 | 52.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Male Metric Plug



| Part No. | Descr. | Prod. No. | " |
|---|---|---|---|
| G64790-0008 | 8MM-PLUG | 7253-64215 | M08X1.0 |
| G64790-0010 | 10MM-PLUG | 7253-64225 | M10X1.5 |
| G64790-0012 | 12MM-PLUG | 7253-64235 | M12X1.5 |
| G64790-0014 | 14MM-PLUG | 7253-64245 | M14X1.5 |
| G64790-0016 | 16MM-PLUG | 7253-64255 | M16X1.5 |
| G64790-0018 | 18MM-PLUG | 7253-64265 | M18X1.5 |
| G64790-0020 | 20MM-PLUG | 7253-64275 | M20X1.5 |
| G64790-0022 | 22MM-PLUG | 7253-64285 | M22X1.5 |
| G64790-0024 | 24MM-PLUG | 7253-64295 | M24X1.5 |
| G64790-0026 | 26MM-PLUG | 7253-64305 | M26X1.5 |
| G64790-0030 | 30MM-PLUG | 7253-64315 | M30X1.5 |


# Male DIN 24° Cone - Light Series Plug







| Part No. | Descr. | Prod. No. | " |
|---|---|---|---|
| G64792-0006 | 6MDL-PLUG | 7253-64325 | M12X1.5 |
| G64792-0008 | 8MDL-PLUG | 7253-64335 | M14X1.5 |
| G64792-0010 | 10MDL-PLUG | 7253-64345 | M16X1.5 |
| G64792-0012 | 12MDL-PLUG | 7253-64355 | M18X1.5 |
| G64792-0015 | 15MDL-PLUG | 7253-64365 | M22X1.5 |
| G64792-0018 | 18MDL-PLUG | 7253-64375 | M26X1.5 |
| G64792-0022 | 22MDL-PLUG | 7253-64385 | M30X2.0 |
| G64792-0028 | 28MDL-PLUG | 7253-64395 | M36X2.0 |
| G64792-0035 | 35MDL-PLUG | 7253-64405 | M45X2.0 |
| G64792-0042 | 42MDL-PLUG | 7253-64415 | M52X2.0 |

## Female DIN 24° Cone - Light Series Cap







| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| | | | " |
| G64793-0006 | 6FDL-CAP | 7253-64425 | M12X1.5 |
| G64793-0008 | 8FDL-CAP | 7253-64435 | M14X1.5 |
| G64793-0010 | 10FDL-CAP | 7253-64445 | M16X1.5 |
| G64793-0012 | 12FDL-CAP | 7253-64455 | M18X1.5 |
| G64793-0015 | 15FDL-CAP | 7253-64465 | M22X1.5 |
| G64793-0018 | 18FDL-CAP | 7253-64475 | M26X1.5 |
| G64793-0022 | 22FDL-CAP | 7253-64485 | M30X2.0 |
| G64793-0028 | 28FDL-CAP | 7253-64495 | M36X2.0 |
| G64793-0035 | 35FDL-CAP | 7253-64505 | M45X2.0 |
| G64793-0042 | 42FDL-CAP | 7253-64515 | M52X2.0 |

## Male DIN 24° Cone - Heavy Series Plug








| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| | | | " |
| G64794-0008 | 8MDH-PLUG | 7253-64535 | M16X1.5 |
| G64794-0010 | 10MDH-PLUG | 7253-64545 | M18X1.5 |
| G64794-0012 | 12MDH-PLUG | 7253-64555 | M20X1.5 |
| G64794-0014 | 14MDH-PLUG | 7253-64565 | M22X1.5 |
| G64794-0016 | 16MDH-PLUG | 7253-64575 | M24X1.5 |
| G64794-0020 | 20MDH-PLUG | 7253-64585 | M30X2.0 |
| G64794-0025 | 25MDH-PLUG | 7253-64595 | M36X2.0 |
| G64794-0030 | 30MDH-PLUG | 7253-64605 | M42X2.0 |
| G64794-0038 | 38MDH-PLUG | 7253-64615 | M52X2.0 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Female DIN 24° Cone - Heavy Series Cap







| Part No. | Descr. | Prod. No. | " |
|---|---|---|---|
| G64795-0008 | 8FDH-CAP | 7253-64635 | M16X1.5 |
| G64795-0010 | 10FDH-CAP | 7253-64645 | M18X1.5 |
| G64795-0012 | 12FDH-CAP | 7253-64655 | M20X1.5 |
| G64795-0014 | 14FDH-CAP | 7253-64665 | M22X1.5 |
| G64795-0016 | 16FDH-CAP | 7253-64675 | M24X1.5 |
| G64795-0020 | 20FDH-CAP | 7253-64685 | M30X2.0 |
| G64795-0025 | 25FDH-CAP | 7253-64695 | M36X2.0 |
| G64795-0030 | 30FDH-CAP | 7253-64705 | M42X2.0 |
| G64795-0038 | 38FDH-CAP | 7253-64715 | M52X2.0 |


# Female Japanese Industrial Standard Cap







| Part No. | Descr. | Prod. No. | " |
|---|---|---|---|
| G65097-0004 | 4FJIS-CAP | 7253-64875 | 1/4–19 |
| G65097-0006 | 6FJIS-CAP | 7253-64885 | 3/8–19 |
| G65097-0008 | 8FJIS-CAP | 7253-64895 | 1/2–14 |
| G65097-0012 | 12FJIS-CAP | 7253-64905 | 3/4–14 |
| G65097-0016 | 16FJIS-CAP | 7253-64915 | 1–11 |
| G65097-0020 | 20FJIS-CAP | 7253-64925 | 1 1/4–11 |
| G65097-0032 | 32FJIS-CAP | 7253-64945 | 2–11 |


# Male Japanese Industrial Standard Plug









| Part No. | Descr. | Prod. No. | " |
|---|---|---|---|
| G65099-0004 | 4MJIS-PLUG | 7253-64955 | 1/4–19 |
| G65099-0006 | 6MJIS-PLUG | 7253-64965 | 3/8–19 |
| G65099-0008 | 8MJIS-PLUG | 7253-64975 | 1/2–14 |
| G65099-0012 | 12MJIS-PLUG | 7253-64985 | 3/4–14 |
| G65099-0016 | 16MJIS-PLUG | 7253-64995 | 1–11 |
| G65099-0020 | 20MJIS-PLUG | 7253-65005 | 1 1/4–11 |
| G65099-0024 | 24MJIS-PLUG | 7253-65015 | 1 1/2–11 |
| G65099-0032 | 32MJIS-PLUG | 7253-65025 | 2–11 |

# Female Japanese Industrial Standard to Male JIC 37° Flare







| Part No. | Descr. | Prod. No. | " | " |
|---|---|---|---|---|
| G65100-0404 | 4FJIS-4MJ | 7253-65035 | 1/4–19 | 7/16–20 |
| G65100-0604 | 6FJIS-4MJ | 7253-65045 | 3/8–19 | 7/16–20 |
| G65100-0606 | 6FJIS-6MJ | 7253-65055 | 3/8–19 | 9/16–18 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female Japanese Industrial Standard to Male JIC 37° Flare - Continued

| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G65100-0808 | 8FJIS-8MJ | 7253-65075 | 1/2–14 | 3/4–16 |
| G65100-1212 | 12FJIS-12MJ | 7253-65085 | 3/4–14 | 1 1/16–12 |
| G65100-1616 | 16FJIS-16MJ | 7253-65095 | 1–11 | 1 5/16–12 |
| G65100-2020 | 20FJIS-20MJ | 7253-65105 | 1 1/4–11 | 1 5/8–12 |


## Female Komatsu Cap







| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| | | | " |
| G65597-0004 | 4FK-CAP | 7253-65115 | M14X1.5 |
| G65597-0006 | 6FK-CAP | 7253-65125 | M18X1.5 |
| G65597-0008 | 8FK-CAP | 7253-65135 | M22X1.5 |
| G65597-0010 | 10FK-CAP | 7253-65145 | M24X1.5 |
| G65597-0012 | 12FK-CAP | 7253-65155 | M30X1.5 |
| G65597-0016 | 16FK-CAP | 7253-65165 | M33X1.5 |


## Male Komatsu Plug









| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| | | | " |
| G65599-0004 | 4MK-PLUG | 7253-65175 | M14X1.5 |
| G65599-0006 | 6MK-PLUG | 7253-65185 | M18X1.5 |
| G65599-0008 | 8MK-PLUG | 7253-65195 | M22X1.5 |
| G65599-0010 | 10MK-PLUG | 7253-65205 | M24X1.5 |
| G65599-0012 | 12MK-PLUG | 7253-65215 | M30X1.5 |
| G65599-0016 | 16MK-PLUG | 7253-65225 | M33X1.5 |

## Female Komatsu to Male JIC 37° Flare







| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G65600-0404 | 4FK-4MJ | 7253-65235 | M14X1.5 | 7/16–20 |
| G65600-0606 | 6FK-6MJ | 7253-65245 | M18X1.5 | 9/16–18 |
| G65600-0808 | 8FK-8MJ | 7253-65255 | M22X1.5 | 3/4–16 |
| G65600-1010 | 10FK-10MJ | 7253-65265 | M24X1.5 | 7/8–14 |
| G65600-1212 | 12FK-12MJ | 7253-65275 | M30X1.5 | 1 1/16–12 |
| G65600-1616 | 16FK-16MJ | 7253-65285 | M33X1.5 | 1 5/16–12 |


## Male Komatsu to Male Komatsu








| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G65700-0404 | 4MK-4MK | 7253-65765 | M14X1.5 | M14X1.5 |
| G65700-0606 | 6MK-6MK | 7253-65775 | M18X1.5 | M18X1.5 |
| G65700-0808 | 8MK-8MK | 7253-65785 | M22X1.5 | M22X1.5 |
| G65700-1010 | 10MK-10MK | 7253-65795 | M24X1.5 | M24X1.5 |
| G65700-1212 | 12MK-12MK | 7253-65805 | M30X1.5 | M30X1.5 |
| G65700-1616 | 16MK-16MK | 7253-65815 | M33X1.5 | M33X1.5 |

## Male Komatsu to Male JIC 37° Flare











| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G65750-0404 | 4MK-4MJ | 7253-65825 | M14X1.5 | 7/16–20 |
| G65750-0606 | 6MK-6MJ | 7253-65835 | M18X1.5 | 9/16–18 |
| G65750-0808 | 8MK-8MJ | 7253-65845 | M22X1.5 | 3/4–16 |
| G65750-1010 | 10MK-10MJ | 7253-65855 | M24X1.5 | 7/8–14 |
| G65750-1212 | 12MK-12MJ | 7253-65865 | M30X1.5 | 1 1/16–12 |
| G65750-1616 | 16MK-16MJ | 7253-65875 | M33X1.5 | 1 5/16–12 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male Komatsu to Female Komatsu - 90°












| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G65800-0404 | 4MK-4FK90 | 7253-65945 | M14X1.5 | M14X1.5 |
| G65800-0606 | 6MK-6FK90 | 7253-65965 | M18X1.5 | M18X1.5 |
| G65800-0808 | 8MK-8FK90 | 7253-65975 | M22X1.5 | M22X1.5 |
| G65800-1010 | 10MK-10FK90 | 7253-65985 | M24X1.5 | M24X1.5 |
| G65800-1212 | 12MK-12FK90 | 7253-65995 | M30X1.5 | M30X1.5 |
| G65800-1616 | 16MK-16FK90 | 7253-66005 | M33X1.5 | M33X1.5 |

## Male Komatsu to Female Komatsu to Male Komatsu - Tee






| Part No. | Descr. | Prod. No. | | | |
|---|---|---|---|---|---|
| | | | " | " | " |
| G65950-0404 | 4MK-4FK-4MK | 7253-65885 | M14X1.5 | M14X1.5 | M14X1.5 |
| G65950-0606 | 6MK-6FK-6MK | 7253-65905 | M18X1.5 | M18X1.5 | M18X1.5 |
| G65950-0808 | 8MK-8FK-8MK | 7253-65915 | M22X1.5 | M22X1.5 | M22X1.5 |
| G65950-1010 | 10MK-10FK-10MK | 7253-65925 | M24X1.5 | M24X1.5 | M24X1.5 |
| G65950-1212 | 12MK-12FK-12MK | 7253-65935 | M30X1.5 | M30X1.5 | M30X1.5 |

## Bite Sleeve




| Part No. | Descr. | Prod. No. |
|---|---|---|
| G73050-0003 | 3ERBS | 7259-90025 |
| G73050-0004 | 4ERBS | 7259-90035 |
| G73050-0006 | 6ERBS | 7259-90055 |
| G73050-0008 | 8ERBS | 7259-90065 |

## Tube Sleeve Nut



| Part No. | Descr. | Prod. No. |
|---|---|---|
| G73060-0006 | 6ERTSN | 7259-90165 |

## Ermeto to Male Pipe




| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| | | | " |
| G73100-0402 | 4ERT-2MP | 7259-90505 | 1/8–27 |
| G73100-0404 | 4ERT-4MP | 7259-90515 | 1/4–18 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Ermeto to Male Pipe - 90°




| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| | | | " |
| G73104-0402 | 4ERT-2MP90 | 7259-90975 | 1/8–27 |

## Ermeto to Ermeto




| Part No. | Descr. | Prod. No. | ⊖ | |
|---|---|---|---|---|
| | | | " | mm |
| G73400-0303 | 3ERT-3ERT | 7259-90375 | 3/16 | 4.8 |
| G73400-0404 | 4ERT-4ERT | 7259-90385 | 1/4 | 6.4 |
| G73400-0505 | 5ERT-5ERT | 7259-90395 | 5/16 | 7.9 |
| G73400-0606 | 6ERT-6ERT | 7259-90405 | 3/8 | 9.5 |
| G73400-0808 | 8ERT-8ERT | 7259-90415 | 1/2 | 12.7 |
| G73400-1010 | 10ERT-10ERT | 7259-90425 | 5/8 | 15.9 |

## Male Ball Valve to Female Pipe




| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94011-0404 | 4MQBA-4FP | 7252-89315 | 1/4–18 | 4000 | 12000 |
| G94011-0606 | 6MQBA-6FP | 7252-89345 | 3/8–18 | 3000 | 9000 |
| G94011-0808 | 8MQBA-8FP | 7252-89325 | 1/2–14 | 3000 | 10500 |
| G94011-0812 | 8MQBA-12FP | 7252-89305 | 3/4–14 | 3000 | 10500 |
| G94011-1212 | 12MQBA-12FP | 7252-89685 | 3/4–14 | 4000 | 11000 |

## Male Ball Valve to Female O-Ring Boss



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94012-0808 | 8MQBA-8FB | 7252-89335 | 3/4–16 | 3000 | 10500 |

## Female Ball Valve To Female Pipe




| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94021-0404 | 4FQBA-4FP | 7252-89415 | 1/4–18 | 4000 | 12000 |
| G94021-0606D | 6FQBADA-6FP* | 7252-89695 | 3/8–18 | 3000 | 9000 |
| G94021-0808D | 8FQBADA-8FP* | 7252-89445 | 1/2–14 | 3000 | 10500 |
| G94021-0808 | 8FQBA-8FP | 7252-89425 | 1/2–14 | 3000 | 10500 |
| G94021-0812D | 8FQBADA-12FP* | 7252-89705 | 3/4–14 | 3000 | 10500 |
| G94021-1212 | 12FQBA-12FP | 7252-89715 | 3/4–14 | 4000 | 11000 |

**Double–Acting Sleeve*

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female Ball Valve To Female O-Ring Boss



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94022-0808 | 8FQBA-8FB | 7252-89435 | 3/4–16 | 3000 | 10500 |

# O-Ring



| Part No. | Descr. | Prod. No. |
|---|---|---|
| G94025-0004 | 4QDAOR | 7252-59415 |
| G94025-0006 | 6QDAOR | 7252-59695 |
| G94025-0008 | 8QDAOR | 7252-59425 |
| G94025-0012 | 12QDAOR | 7252-59715 |

# QD Dust Plug



| Part No. | Descr. | Prod. No. |
|---|---|---|
| G94080-0004 | 4QDADP | 7252-89465 |
| G94080-0006 | 6QDADP | 7252-89485 |
| G94080-0008 | 8QDADP | 7252-89475 |

# QD Dust Cap




| Part No. | Descr. | Prod. No. |
|---|---|---|
| G94090-0004 | 4QDADC | 7252-89565 |
| G94090-0006 | 6QDADC | 7252-89585 |
| G94090-0008 | 8QDADC | 7252-89575 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male Poppet Valve to Female Pipe




| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94111-0404 | 4MQPA-4FP | 7252-89725 | 1/4–18 | 3000 | 12000 |
| G94111-0606 | 6MQPA-6FP | 7252-89735 | 3/8–18 | 3000 | 12000 |
| G94111-0808 | 8MQPA-8FP | 7252-89365 | 1/2–14 | 4000 | 16000 |
| G94111-1616 | 16MQPA-16FP | 7252-89745 | 1–11 1/2 | 3000 | 12000 |

## Female Poppet Valve to Female Pipe




| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94121-0404 | 4FQPA-4FP | 7252-89755 | 1/4–18 | 3000 | 12000 |
| G94121-0606 | 6FQPA-6FP | 7252-89765 | 3/8–18 | 3000 | 12000 |
| G94121-0808 | 8FQPA-8FP | 7252-89775 | 1/2–14 | 4000 | 16000 |
| G94121-1616 | 16FQPA-16FP | 7252-89785 | 1–11 1/2 | 3000 | 12000 |

## Male Ball Valve to Female Pipe




| Part No. | Descr. | Prod. No. | " | |
|---|---|---|---|---|
| G94211-0808 | 8MQBAJD-8FP | 7252-89355 | 1/2–14 | 3000 |

## Male Ball Valve to Female O-Ring Boss



| Part No. | Descr. | Prod. No. | " | |
|---|---|---|---|---|
| G94212-0808 | 8MQBAJD-8FB | 7252-89375 | 3/4–16 | 3000 |

## Female Ball Valve to Female Pipe




| Part No. | Descr. | Prod. No. | " | |
|---|---|---|---|---|
| G94221-0808 | 8FQBAJD-8FP | 7252-89455 | 1/2–14 | 3000 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Tip - Ball Valve to Female Pipe



| Part No. | Descr. | Prod. No. | " | |
|---|---|---|---|---|
| G94311-0808 | 8MQBAIHC-8FP | 7252-89385 | 1/2–14 | 2500 |

# Male Tip - Ball Valve to Female Pipe




| Part No. | Descr. | Prod. No. | " | |
|---|---|---|---|---|
| G94411-0808 | 8MQBAJIC-8FP | 7252-89395 | 1/2–14 | 3000 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Poppet Valve to Female Pipe



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94511-0404 | 4MQPI-4FP | 7252-89015 | 1/4–18 | 7500 | 30000 |
| G94511-0606 | 6MQPI-6FP | 7252-89025 | 3/8–18 | 5000 | 20000 |
| G94511-0808 | 8MQPI-8FP | 7252-89035 | 1/2–14 | 5000 | 20000 |
| G94511-1212 | 12MQPI-12FP | 7252-89045 | 3/4–14 | 4000 | 16000 |
| G94511-1616 | 16MQPI-16FP | 7252-89055 | 1–11 1/2 | 4000 | 16000 |

# Female Poppet Valve to Female Pipe



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94521-0404 | 4FQPI-4FP | 7252-89115 | 1/4–18 | 7500 | 30000 |
| G94521-0606 | 6FQPI-6FP | 7252-89125 | 3/8–18 | 5000 | 20000 |
| G94521-0808 | 8FQPI-8FP | 7252-89135 | 1/2–14 | 5000 | 20000 |
| G94521-1212 | 12FQPI-12FP | 7252-89145 | 3/4–14 | 4000 | 16000 |
| G94521-1616 | 16FQPI-16FP | 7252-89155 | 1–11 1/2 | 4000 | 16000 |

# O-Ring

90 Durometer Hardness.

Caution: DO NOT USE these O–Rings with phosphate esters, diesters or phosphate ester emulsion hydraulic fluids. Instead, use O–Rings made of Viton, EPDM or CPE polymers or other materials compatible with the fluids.
These O–Rings are compounded from a Nitrile polymer for use with petroleum–based hydraulic fluids, water and glycol and oil–water emulsions.



| Part No. | Descr. | Prod. No. |
|---|---|---|
| G94525-0004 | 4QDIOR | 7252-59115 |
| G94525-0006 | 6QDIOR | 7252-59125 |
| G94525-0008 | 8QDIOR | 7252-59135 |

## O-Ring - Continued

| Part No. | Descr. | Prod. No. |
|---|---|---|
| G94525-0012 | 12QDIOR | 7252-59145 |
| G94525-0016 | 16QDIOR | 7252-59155 |

## Backup Ring



| Part No. | Descr. | Prod. No. |
|---|---|---|
| G94526-0004 | 4QDIBR | 7252-49115 |
| G94526-0006 | 6QDIBR | 7252-49125 |
| G94526-0008 | 8QDIBR | 7252-49135 |
| G94526-0012 | 12QDIBR | 7252-49145 |
| G94526-0016 | 16QDIBR | 7252-49155 |


## QD Plug - Cap Combination



| Part No. | Descr. | Prod. No. |
|---|---|---|
| G94581-0004 | 4QDIDP/C | 7252-87005 |
| G94581-0006 | 6QDIDP/C | 7252-87595 |
| G94581-0008 | 8QDIDP/C | 7252-87605 |
| G94581-0012 | 12QDIDP/C | 7252-87615 |
| G94581-0016 | 16QDIDP/C | 7252-87625 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Male Flush Face Valve to Female Pipe



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94911-0404 | 4MQFF-4FP | 7252-87015 | 1/4–18 | 3000 | 12000 |
| G94911-0606 | 6MQFF-6FP | 7252-88005 | 3/8–18 | 3000 | 12000 |
| G94911-0608 | 6MQFF-8FP | 7252-88015 | 1/2–14 | 3000 | 12000 |
| G94911-0808 | 8MQFF-8FP | 7252-87025 | 1/2–14 | 3000 | 12000 |
| G94911-0808P | 8CPMQFF-8FP* | 7252-87435 | 1/2–14 | 3000 | 12000 |
| G94911-1212 | 12MQFF-12FP | 7252-87035 | 3/4–14 | 3000 | 12000 |
| G94911-1616 | 16MQFF-16FP | 7252-87045 | 1–11 1/2 | 3000 | 12000 |

**Connect–under–pressure coupler.*


# Male Flush Face Valve to Female O-Ring Boss



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94912-0404 | 4MQFF-4FB | 7252-87055 | 7/16–20 | 3000 | 12000 |
| G94912-0608 | 6MQFF-8FB | 7252-88025 | 3/4–16 | 3000 | 12000 |
| G94912-0808 | 8MQFF-8FB | 7252-87065 | 3/4–16 | 3000 | 12000 |
| G94912-0808P | 8CPMQFF-8FB* | 7252-87445 | 3/4–16 | 3000 | 12000 |
| G94912-0810P | 8CPMQFF-10FB* | 7252-87455 | 7/8–14 | 3000 | 12000 |
| G94912-0812 | 8MQFF-12FB | 7252-87075 | 1 1/16–12 | 3000 | 12000 |
| G94912-0812P | 8CPMQFF-12FB* | 7252-87465 | 1 1/16–12 | 3000 | 12000 |
| G94912-1012 | 10MQFF-12FB | 7252-87085 | 1 1/16–12 | 3000 | 12000 |
| G94912-1212 | 12MQFF-12FB | 7252-87095 | 1 1/16–12 | 3000 | 12000 |
| G94912-1616 | 16MQFF-16FB | 7252-87105 | 1 5/16–12 | 3000 | 12000 |


**Connect–under–pressure coupler.*

## Male Flush Face Valve to JIC 37° Flare Bulkhead




| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94913-0810 | 8MQFF-10BKHD | 7252-87395 | 7/8–14 | 3625 | 14500 |
| G94913-1012 | 10MQFF-12BKHD | 7252-87405 | 1 1/16–12 | 3625 | 14500 |

## Male Flush Face Valve to Female British Pipe Parallel



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94915-0404 | 4MQFF-4FBPP | 7252-87115 | 1/4–19 | 4568 | 18270 |
| G94915-0808 | 8MQFF-8FBPP | 7252-87125 | 1/2–14 | 3625 | 14500 |
| G94915-1212 | 12MQFF-12FBPP | 7252-87135 | 3/4–14 | 3625 | 14500 |
| G94915-1616 | 16MQFF-16FBPP | 7252-87145 | 1–11 | 2900 | 11600 |

## Female Flush Face Valve to Female Pipe




| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94921-0404 | 4FQFF-4FP | 7252-87155 | 1/4–18 | 3000 | 12000 |
| G94921-0606 | 6FQFF-6FP | 7252-88035 | 3/8–18 | 3000 | 12000 |
| G94921-0608 | 6FQFF-8FP | 7252-88045 | 1/2–14 | 3000 | 12000 |
| G94921-0808 | 8FQFF-8FP | 7252-87165 | 1/2–14 | 3000 | 12000 |
| G94921-0808P | 8CPFQFF-8FP* | 7252-87475 | 1/2–14 | 3000 | 12000 |
| G94921-1212 | 12FQFF-12FP | 7252-87175 | 3/4–14 | 3000 | 12000 |
| G94921-1616 | 16FQFF-16FP | 7252-87185 | 1–11 1/2 | 3000 | 12000 |

**Connect–under–pressure coupler.*

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Female Flush Face Valve to Female O-Ring Boss



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94922-0404 | 4FQFF-4FB | 7252-87195 | 7/16–20 | 3000 | 12000 |
| G94922-0608 | 6FQFF-8FB | 7252-88055 | 3/4–16 | 3000 | 12000 |
| G94922-0808 | 8FQFF-8FB | 7252-87205 | 3/4–16 | 3000 | 12000 |
| G94922-0808P | 8CPFQFF-8FB* | 7252-87485 | 3/4–16 | 3000 | 12000 |
| G94922-0810P | 8CPFQFF-10FB* | 7252-87495 | 7/8–14 | 3000 | 12000 |
| G94922-0812 | 8FQFF-12FB | 7252-87215 | 1 1/16–12 | 3000 | 12000 |
| G94922-0812P | 8CPFQFF-12FB* | 7252-87505 | 1 1/16–12 | 3000 | 12000 |
| G94922-1012 | 10FQFF-12FB | 7252-87225 | 1 1/16–12 | 3000 | 12000 |
| G94922-1212 | 12FQFF-12FB | 7252-87235 | 1 1/16–12 | 3000 | 12000 |
| G94922-1616 | 16FQFF-16FB | 7252-87245 | 1 5/16–12 | 3000 | 12000 |


**Connect–under–pressure coupler.*

## Female Flush Face to JIC 37° Flare Bulkhead



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94923-0810 | 8FQFF-10BKHD | 7252-87415 | 7/8–14 | 3625 | 14500 |
| G94923-1012 | 10FQFF-12BKHD | 7252-87425 | 1 1/16–12 | 3625 | 14500 |

## Female Flush Face Valve to Female British Pipe Parallel



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G94925-0808 | 8FQFF-8FBPP | 7252-87265 | 1/2–14 | 3625 | 14500 |
| G94925-1212 | 12FQFF-12FBPP | 7252-87275 | 3/4–14 | 3625 | 14500 |
| G94925-1616 | 16FQFF-16FBPP | 7252-87285 | 1–11 | 2900 | 11600 |

# Dust Plug



| Part No. | Descr. | Prod. No. |
|---|---|---|
| G94980-0004 | 4QDFFDP | 7252-87295 |
| G94980-0006 | 6QDFFDP | 7252-88065 |
| G94980-0008 | 8QDFFDP | 7252-87305 |
| G94980-0010 | 10QDFFDP | 7252-87315 |
| G94980-0012 | 12QDFFDP | 7252-87325 |
| G94980-0016 | 16QDFFDP | 7252-87335 |

# Dust Cap




| Part No. | Descr. | Prod. No. |
|---|---|---|
| G94990-0004 | 4QDFFDC | 7252-87345 |
| G94990-0006 | 6QDFFDC | 7252-88075 |
| G94990-0008 | 8QDFFDC | 7252-87355 |
| G94990-0010 | 10QDFFDC | 7252-87365 |
| G94990-0012 | 12QDFFDC | 7252-87375 |
| G94990-0016 | 16QDFFDC | 7252-87385 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male Flush Face Valve



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G95011-0604 | 6MQFFH-4FP | 7252-88085 | 1/4–18 | 10000 | 20000 |
| G95011-0606 | 6MQFFH-6FP | 7252-88095 | 3/8–18 | 10000 | 20000 |
| G95011-0808 | 8MQFFH-8FP | 7252-88145 | 1/2–14 | 5000 | 10000 |
| G95011-1212 | 12MQFFH-12FP | 7252-88155 | 3/4–14 | 5000 | 10000 |
| G95011-1616A | 16MQFFH-16FPA* | 7252-88325 | 1–11 1/2 | 5000 | 10000 |
| G95011-1616 | 16MQFFH-16FP | 7252-88165 | 1–11 1/2 | 5000 | 10000 |

**This coupling features a higher working pressure and flatter face for minimization of fluid loss.*

## Female Flush Face Valve



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G95021-0604 | 6FQFFH-4FP | 7252-88105 | 1/4–18 | 10000 | 20000 |
| G95021-0606 | 6FQFFH-6FP | 7252-88115 | 3/8–18 | 10000 | 20000 |
| G95021-0808 | 8FQFFH-8FP | 7252-88175 | 1/2–14 | 5000 | 10000 |
| G95021-1212 | 12FQFFH-12FP | 7252-88185 | 3/4–14 | 5000 | 10000 |
| G95021-1616A | 16FQFFH-16FPA* | 7252-88335 | 1–11 1/2 | 5000 | 10000 |
| G95021-1616 | 16FQFFH-16FP | 7252-88195 | 1–11 1/2 | 5000 | 10000 |

**This coupling features a higher working pressure and flatter face for minimization of fluid loss.*

## QD Dust Plug



| Part No. | Descr. | Prod. No. |
|---|---|---|
| G95080-0006 | 6QDFFHDP | 7252-88125 |
| G95080-0008 | 8QDFFHDP | 7252-88205 |
| G95080-0012 | 12QDFFHDP | 7252-88215 |
| G95080-0016 | 16QDFFHDP | 7252-88225 |

# QD Dust Cap




| Part No. | Descr. | Prod. No. |
|---|---|---|
| G95090-0006 | 6QDFFHDC | 7252-88135 |
| G95090-0008 | 8QDFFHDC | 7252-88235 |
| G95090-0012 | 12QDFFHDC | 7252-88245 |
| G95090-0016 | 16QDFFHDC | 7252-88255 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male (Brass) - Less Flange



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| ⚠ G95111-1212 | 12MQW-12FP | 7252-88525 | 3/4–14 | 3000 | 9000 |
| ⚠ G95111-1616 | 16MQW-16FP | 7252-88535 | 1–11 1/2 | 3000 | 9000 |
| ⚠ G95111-2020 | 20MQW-20FP | 7252-88545 | 1 1/4–11 1/2 | 2750 | 8250 |
| ⚠ G95111-2424 | 24MQW-24FP | 7252-88555 | 1 1/2–11 1/2 | 2500 | 7500 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## Female (Brass) - Wing Nut (Cast Iron)



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| ⚠ G95121-1212 | 12FQW-12FP | 7252-88585 | 3/4–14 | 3000 | 9000 |
| ⚠ G95121-1616 | 16FQW-16FP | 7252-88595 | 1–11 1/2 | 3000 | 9000 |
| ⚠ G95121-2020 | 20FQW-20FP | 7252-88605 | 1 1/4–11 1/2 | 2750 | 8250 |
| ⚠ G95121-2424 | 24FQW-24FP | 7252-88615 | 1 1/2–11 1/2 | 2500 | 7500 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## Dust Plug



| Part No. | Descr. | Prod. No. |
|---|---|---|
| G95180-0012 | 12QWDP | 7252-88645 |
| G95180-0016 | 16QWDP | 7252-88655 |

## Dust Plug - Continued

| Part No. | Descr. | Prod. No. |
|---|---|---|
| G95180-0020 | 20QWDP | 7252-88665 |
| G95180-0024 | 24QWDP | 7252-88675 |


## Dust Cap



| Part No. | Descr. | Prod. No. |
|---|---|---|
| G95190-0012 | 12QWDC | 7252-88705 |
| G95190-0016 | 16QWDC | 7252-88715 |
| G95190-0020 | 20QWDC | 7252-88725 |
| G95190-0024 | 24QWDC | 7252-88735 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male Acme Flat Threads to Female Pipe



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G95211-1212 | 12MQWH-12FP | 7252-88745 | 3/4–14 | 5000 | 20000 |
| G95211-1616 | 16MQWH-16FP | 7252-88755 | 1–11 1/2 | 5000 | 20000 |
| G95211-2020 | 20MQWH-20FP | 7252-88765 | 1 1/4–11 1/2 | 5000 | 15000 |
| G95211-2424 | 24MQWH-24FP | 7252-88775 | 1 1/2–11 1/2 | 5000 | 15000 |
| G95211-3232 | 32MQWH-32FP | 7252-88785 | 2–11 1/2 | 5000 | 15000 |

## Female Wing Nut to Female Pipe



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G95221-1212 | 12FQWH-12FP* | 7252-88795 | 3/4–14 | 5000 | 20000 |
| G95221-1616 | 16FQWH-16FP | 7252-88805 | 1–11 1/2 | 5000 | 20000 |
| G95221-2020 | 20FQWH-20FP | 7252-88815 | 1 1/4–11 1/2 | 5000 | 15000 |
| G95221-2424 | 24FQWH-24FP | 7252-88825 | 1 1/2–11 1/2 | 5000 | 15000 |
| G95221-3232 | 32FQWH-32FP | 7252-88835 | 2–11 1/2 | 5000 | 15000 |

**Features a hex nut on the coupler.*

## Dust Plug



| Part No. | Descr. | Prod. No. |
|---|---|---|
| G95280-0012 | 12QWHDP | 7252-88845 |
| G95280-0016 | 16QWHDP | 7252-88855 |
| G95280-0020 | 20QWHDP | 7252-88865 |
| G95280-0024 | 24QWHDP | 7252-88875 |
| G95280-0032 | 32QWHDP | 7252-88885 |

# Dust Cap




| Part No. | Descr. | Prod. No. |
|---|---|---|
| G95290-0012 | 12QWHDC | 7252-88895 |
| G95290-0016 | 16QWHDC | 7252-88905 |
| G95290-0020 | 20QWHDC | 7252-88915 |
| G95290-0024 | 24QWHDC | 7252-88925 |
| G95290-0032 | 32QWHDC | 7252-88935 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Male Poppet Valve to Female Pipe

Recommended for MobileCrimp® crimper–to–pump connection.




| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G95311-0606 | 6MQFFVH-6FP | 7252-88315 | 3/8–18 | 14500 | 28000 |

## Female Screw to Connect to Female Pipe




| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G95321-0606 | 6FQFFVH-6FP | 7252-88305 | 3/8–18 | 14500 | 28000 |

## Male Poppet Valve to Female Pipe



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G95611-0404 | 4MQP-4FP | 7252-89905 | 1/4–18 | 4600 | 18400 |
| G95611-0606 | 6MQP-6FP | 7252-89915 | 3/8–18 | 4600 | 18400 |
| G95611-0808 | 8MQP-8FP | 7252-89925 | 1/2–14 | 4000 | 16000 |
| G95611-1212 | 12MQP-12FP | 7252-89935 | 3/4–14 | 4000 | 16000 |
| G95611-1616 | 16MQP-16FP | 7252-89945 | 1–11 1/2 | 3000 | 12000 |

## Female Poppet Valve to Female Pipe



| Part No. | Descr. | Prod. No. | " | | |
|---|---|---|---|---|---|
| G95621-0404 | 4FQP-4FP | 7252-89955 | 1/4–18 | 4600 | 18400 |
| G95621-0606 | 6FQP-6FP | 7252-89965 | 3/8–18 | 4600 | 18400 |
| G95621-1212 | 12FQP-12FP | 7252-89985 | 3/4–14 | 4000 | 16000 |
| G95621-1616 | 16FQP-16FP | 7252-89995 | 1–11 1/2 | 3000 | 12000 |

## O-Ring



| Part No. | Descr. | Prod. No. |
|---|---|---|
| G95625-0004 | 4QDOR | 7252-59955 |
| G95625-0006 | 6QDOR | 7252-59965 |
| G95625-0008 | 8QDOR | 7252-59975 |
| G95625-0012 | 12QDOR | 7252-59985 |
| G95625-0016 | 16QDOR | 7252-59995 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Backup Ring



| Part No. | Descr. | Prod. No. |
|---|---|---|
| G95626-0004 | 4QDBR | 7252-49955 |
| G95626-0006 | 6QDBR | 7252-49965 |
| G95626-0008 | 8QDBR | 7252-49975 |
| G95626-0012 | 12QDBR | 7252-49985 |
| G95626-0016 | 16QDBR | 7252-49995 |

## QD Dust Plug




| Part No. | Descr. | Prod. No. |
|---|---|---|
| G95680-0004 | 4QDDP | 7252-89805 |
| G95680-0006 | 6QDDP | 7252-89815 |
| G95680-0008 | 8QDDP | 7252-89825 |
| G95680-0012 | 12QDDP | 7252-89835 |
| G95680-0016 | 16QDDP | 7252-89845 |

## QD Dust Cap




| Part No. | Descr. | Prod. No. |
|---|---|---|
| G95690-0004 | 4QDDC | 7252-89855 |
| G95690-0006 | 6QDDC | 7252-01395 |
| G95690-0008 | 8QDDC | 7252-89875 |
| G95690-0012 | 12QDDC | 7252-89885 |
| G95690-0016 | 16QDDC | 7252-89895 |

## John Deere Old Style to ISO Style




| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| G95961-0808 | 8MJD-8FISO | 7252-89615 | 3000 |

## ISO Style to John Deere Old Style




| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| G95962-0808 | 8MISO-8FJD | 7252-89625 | 3000 |

## Int'l Harvester to John Deere Old Style



| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| G95963-0808 | 8MIHC-8FJD | 7252-89635 | 3000 |

## Int'l Harvester Old Style to ISO Style




| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| G95964-0808 | 8MIHC-8FISO | 7252-89645 | 3000 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## ISO Style to Int'l Harvester Old Style



| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| G95965-0808 | 8MISO-8FIHC | 7252-89655 | 3000 |

## ISO Style to John Deere Old Style - (Double Shutoff)




| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| G95966-0808 | 8MISO-8FJDDSO | 7252-89665 | 3000 |

## ISO Style to Int'l Harvester Old Style - (Double Shutoff)




| Part No. | Descr. | Prod. No. | |
|---|---|---|---|
| G95967-0808 | 8MISO-8FIHCDSO | 7252-89675 | 3000 |

## Female Pipe NPTF




| Part No. | Descr. | Prod. No. | ⟷ " | ≋ " | 🕒 |
|---|---|---|---|---|---|
| G96110-0404 | 4FP-4FPBV | 7317-00015 | 1/4 | 1/4–18 | 7350 |
| G96110-0606 | 6FP-6FPBV | 7317-00025 | 3/8 | 3/8–18 | 7350 |
| G96110-0808 | 8FP-8FPBV | 7317-00035 | 1/2 | 1/2–14 | 7350 |
| G96110-1212 | 12FP-12FPBV | 7317-00045 | 3/4 | 3/4–14 | 5880 |
| G96110-1616 | 16FP-16FPBV | 7317-00055 | 1 | 1–11 1/2 | 5145 |
| G96110-2016 | 20FP-16FPBV | 7317-00065 | 1 | 1 1/4–11 1/2 | 5145 |


## Female O-Ring Boss



| Part No. | Descr. | Prod. No. | ⟷ " | ≋ " | 🕒 |
|---|---|---|---|---|---|
| G96115-0404 | 4FB-4FBBV | 7317-00075 | 1/4 | 7/16–20 | 7350 |
| G96115-0606 | 6FB-6FBBV | 7317-00085 | 3/8 | 9/16–18 | 7350 |
| G96115-0808 | 8FB-8FBBV | 7317-00095 | 1/2 | 3/4–16 | 7350 |
| G96115-1212 | 12FB-12FBBV | 7317-00105 | 3/4 | 1 1/16–12 | 5880 |
| G96115-1616 | 16FB-16FBBV | 7317-00115 | 1 | 1 5/16–12 | 5145 |

## Code 61 O-Ring Flange









| Part No. | Descr. | Prod. No. | ⟷ " | Nom. Flg. Size " | 🕒 |
|---|---|---|---|---|---|
| G96300-0808 | 8FL-8FLBV | 7317-00215 | 1/2 | 1/2 | 3000 |
| G96300-1212 | 12FL-12FLBV | 7317-00225 | 3/4 | 3/4 | 3000 |
| G96300-1616 | 16FL-16FLBV | 7317-00235 | 1 | 1 | 3000 |
| G96310-2020 | 20FL-20FLBV | 7317-00245 | 1 1/4 | 1 1/4 | 3000 |

## Code 61 O-Ring Flange - Continued

| Part No. | Descr. | Prod. No. | ⊖ " | Nom. Flg. Size " | |
|---|---|---|---|---|---|
| G96310-2424 | 24FL-24FLBV | 7317-00255 | 1 1/2 | 1 1/2 | 3000 |
| G96310-3232 | 32FL-32FLBV | 7317-00265 | 2 | 2 | 3000 |


## Code 62 O-Ring Flange




| Part No. | Descr. | Prod. No. | ⊖ " | Nom. Flg. Size " | |
|---|---|---|---|---|---|
| G96350-0808 | 8FLH-8FLHBV | 7317-00275 | 1/2 | 1/2 | 6000 |
| G96350-1212 | 12FLH-12FLHBV | 7317-00285 | 3/4 | 3/4 | 6000 |
| G96350-1616 | 16FLH-16FLHBV | 7317-00295 | 1 | 1 | 6000 |
| G96355-2020 | 20FLH-20FLHBV | 7317-00305 | 1 1/4 | 1 1/4 | 6000 |
| G96355-2424 | 24FLH-24FLHBV | 7317-00315 | 1 1/2 | 1 1/2 | 6000 |
| G96355-3232 | 32FLH-32FLHBV | 7317-00325 | 2 | 2 | 6000 |

# Female Pipe NPTF



| Part No. | Descr. | Prod. No. | ⊖ " | ||| " | |
|---|---|---|---|---|---|---|
| G96120-2020 | 20FP-20FPBV | 7317-00125 | 1 1/4 | 1 1/4–11 1/2 | 6175 |
| G96120-2424 | 24FP-24FPBV | 7317-00135 | 1 1/2 | 1 1/2–11 1/2 | 6175 |
| G96120-3232 | 32FP-32FPBV | 7317-00145 | 2 | 2–11 1/2 | 6175 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Ball Valve Lock Out Kits

| Part No. | Descr. | Prod. No. |
|---|---|---|
| G96050-0408 | 1/4" THRU 1/2" BV LOCK OUT KIT | 7317-00335 |
| G96050-1216 | 3/4" THRU 1" BV LOCK OUT KIT | 7317-00345 |
| G96050-2032 | 1 1/4" THRU 2" BV LOCK OUT KIT | 7317-00355 |

# Female Pipe NPTF





| Part No. | Descr. | Prod. No. | ⊖ " | ||| " | |
|---|---|---|---|---|---|---|
| G96210-0404 | 4FP-4FP-4FPBV | 7317-00155 | 1/4 | 1/4–18 | 5880 |
| G96210-0606 | 6FP-6FP-6FPBV | 7317-00165 | 3/8 | 3/8–18 | 5880 |
| G96210-0808 | 8FP-8FP-8FPBV | 7317-00175 | 1/2 | 1/2–14 | 5145 |
| G96210-1212 | 12FP-12FP-12FPBV | 7317-00185 | 3/4 | 3/4–14 | 5145 |
| G96210-1616 | 16FP-16FP-16FPBV | 7317-00195 | 1 | 1–11 1/2 | 5145 |
| G96211-2020 | 20FP-20FP-20FPBV | 7317-00205 | 1 1/4 | 1 1/4–11 1/2 | 5145 |

## Male Pipe to Female Pipe - 90°




| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G93340-0606 | 6MP-6FP-LX90 | 7252-10175 | 3/8–18 | 3/8–18 |
| G93340-0808 | 8MP-8FP-LX90 | 7252-10185 | 1/2–14 | 1/2–14 |
| G93340-1212 | 12MP-12FP-LX90 | 7252-10195 | 3/4–14 | 3/4–14 |
| G93340-1616 | 16MP-16FP-LX90 | 7252-10205 | 1–11 1/2 | 1–11 1/2 |

## Male BSPP to Male BSPP



| Part No. | Descr. | Prod. No. | | | | Hex Shank | Hex Body | Overall Length | Diameter |
|---|---|---|---|---|---|---|---|---|---|
| | | | | " | " | " | " | " | " |
| G93345-0808 | 8BSPP-8BSPP-LX | 7252-12415 | 6000 | 1/2–14 | 1/2–14 | 3/4 | 1 5/16 | 3.44 | 1.53 |
| G93345-1212 | 12BSPP-12BSPP-LX | 7252-12425 | 6000 | 3/4–14 | 3/4–14 | 15/16 | 1 5/8 | 4.52 | 2.00 |
| G93345-1616 | 16BSPP-16BSPP-LX | 7252-12435 | 6000 | 1–11 | 1–11 | 1 3/16 | 1 7/8 | 5.06 | 2.22 |

## Male JIC to Male JIC




| Part No. | Descr. | Prod. No. | | | | Hex Shank | Hex Body | Overall Length | Diameter |
|---|---|---|---|---|---|---|---|---|---|
| | | | | " | " | " | " | " | " |
| G93410-0606 | 6MJ-6MJ-LX | 7252-12345 | 6000 | 9/16–18 | 9/16–18 | 1/2 | 1 | 2.91 | 1.25 |
| G93410-0808 | 8MJ-8MJ-LX | 7252-12355 | 6000 | 3/4–16 | 3/4–16 | 11/16 | 1 1/4 | 3.88 | 1.50 |
| G93410-1212 | 12MJ-12MJ-LX | 7252-12365 | 6000 | 1 1/16–12 | 1 1/16–12 | 15/16 | 1 5/8 | 4.94 | 2.00 |
| G93410-1616 | 16MJ-16MJ-LX | 7252-12375 | 6000 | 1 5/16–12 | 1 5/16–12 | 1 3/16 | 1 7/8 | 5.56 | 2.22 |
| G93410-2020 | 20MJ-20MJ-LX | 7252-12385 | 5500 | 1 5/8–12 | 1 5/8–12 | 1 1/2 | 2 3/8 | 6.06 | 2.75 |
| G93410-2424 | 24MJ-24MJ-LX | 7252-12395 | 4500 | 1 7/8–12 | 1 7/8–12 | 1 3/4 | 2 1/2 | 6.44 | 3.00 |
| G93410-3232 | 32MJ-32MJ-LX | 7252-12405 | 3000 | 2 1/2–12 | 2 1/2–12 | 2 5/16 | 3 1/4 | 7.69 | 3.88 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male JIC to Male JIC - 90°




| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G93420-0606 | 6MJ-6MJ-LX90S | 7252-10095 | 9/16–18 | 9/16–18 |
| G93415-0808 | 8MJ-8MJ-LX90 | 7252-10255 | 3/4–16 | 3/4–16 |
| G93420-0808 | 8MJ-8MJ-LX90S | 7252-10105 | 3/4–16 | 3/4–16 |
| G93415-1212 | 12MJ-12MJ-LX90 | 7252-10265 | 1 1/16–12 | 1 1/16–12 |
| G93420-1212 | 12MJ-12MJ-LX90S | 7252-10115 | 1 1/16–12 | 1 1/16–12 |
| G93415-1616 | 16MJ-16MJ-LX90 | 7252-10275 | 1 5/16–12 | 1 5/16–12 |
| G93420-1616 | 16MJ-16MJ-LX90S | 7252-10125 | 1 5/16–12 | 1 5/16–12 |
| G93415-2020 | 20MJ-20MJ-LX90 | 7252-10285 | 1 5/8–12 | 1 5/8–12 |

## Male JIC to Female JIC/Boss



| Part No. | Descr. | Prod. No. | | | | Hex Shank | Hex Body | Overall Length | Diameter |
|---|---|---|---|---|---|---|---|---|---|
| | | | | " | " | " | " | " | " |
| G93450-0808 | 8MJ-8FJ/FB-LX | 7252-12285 | 6000 | 3/4–16 | 3/4–16 | 11/16 | 1 1/4 | 3.31 | 1.50 |
| G93450-1212 | 12MJ-12FJ/FB-LX | 7252-12295 | 6000 | 1 1/16–12 | 1 1/16–12 | 15/16 | 1 5/8 | 4.12 | 2.00 |
| G93450-1616 | 16MJ-16FJ/FB-LX | 7252-12305 | 6000 | 1 5/16–12 | 1 5/16–12 | 1 3/16 | 1 7/8 | 4.63 | 2.22 |
| G93450-2020 | 20MJ-20FJ/FB-LX | 7252-12315 | 5500 | 1 5/8–12 | 1 5/8–12 | 1 1/2 | 2 3/8 | 5.12 | 2.75 |
| G93450-2424 | 24MJ-24FJ/FB-LX | 7252-12325 | 4500 | 1 7/8–12 | 1 7/8–12 | 1 3/4 | 2 1/2 | 5.34 | 3.00 |
| G93450-3232 | 32MJ-32FJ/FB-LX | 7252-12335 | 3000 | 2 1/2–12 | 2 1/2–12 | 2 5/16 | 3 1/4 | 6.50 | 3.88 |

## Male JIC to Female Boss - 90°




| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G93455-0808 | 8MJ-8FB-LX90 | 7252-10215 | 3/4–16 | 3/4–16 |
| G93455-1212 | 12MJ-12FB-LX90 | 7252-10225 | 1 1/16–12 | 1 1/16–12 |
| G93455-1616 | 16MJ-16FB-LX90 | 7252-10235 | 1 5/16–12 | 1 5/16–12 |

## Male JIC to Female Boss - 90° - Continued

| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G93455-2020 | 20MJ-20FB-LX90 | 7252-10245 | 1 5/8–12 | 1 5/8–12 |

## Male Boss to Female JIC/Boss - 90°




| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G93460-0606 | 6MB-6FJ/FB-LX90S | 7252-10015 | 9/16–18 | 9/16–18 |
| G93460-0808 | 8MB-8FJ/FB-LX90S | 7252-10025 | 3/4–16 | 3/4–16 |
| G93460-1212 | 12MB-12FJ/FB-LX90S | 7252-10035 | 1 1/16–12 | 1 1/16–12 |
| G93460-1616 | 16MB-16FJ/FB-LX90S | 7252-10045 | 1 5/16–12 | 1 5/16–12 |

## JIC Seal Kit

| Part No. | Descr. | Prod. No. | Standard Pack |
|---|---|---|---|
| G93500-0006 | 6JIC SWIVEL SEAL KIT | 7252-12155 | 1 |
| G93500-0008 | 8JIC SWIVEL SEAL KIT | 7252-12165 | 1 |
| G93500-0012 | 12JIC SWIVEL SEAL KIT | 7252-12175 | 1 |
| G93500-0016 | 16JIC SWIVEL SEAL KIT | 7252-12185 | 1 |
| G93500-0020 | 20JIC SWIVEL SEAL KIT | 7252-12195 | 1 |
| G93500-0024 | 24JIC SWIVEL SEAL KIT | 7252-12205 | 1 |
| G93500-0032 | 32JIC SWIVEL SEAL KIT | 7252-12215 | 1 |


## Male JIC to Female Pipe



| Part No. | Descr. | Prod. No. | | | | Hex Shank | Hex Body | Overall Length | Diameter |
|---|---|---|---|---|---|---|---|---|---|
| | | | | " | " | " | " | " | " |
| G93510-0808 | 8MJ-8FP-LX | 7252-12255 | 6000 | 3/4–16 | 1/2–14 | 11/16 | 1 1/4 | 3.31 | 1.50 |
| G93510-1212 | 12MJ-12FP-LX | 7252-12265 | 6000 | 1 1/16–12 | 3/4–14 | 15/16 | 1 5/8 | 4.19 | 2.00 |
| G93510-1616 | 16MJ-16FP-LX | 7252-12275 | 6000 | 1 5/16–12 | 1–11 1/2 | 1 3/16 | 1 7/8 | 4.88 | 2.22 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male Boss to Female Pipe - 90°



| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G93520-0606 | 6MB-6FP-LX90S | 7252-10135 | 9/16–18 | 3/8–18 |
| G93520-0808 | 8MB-8FP-LX90S | 7252-10145 | 3/4–16 | 1/2–14 |
| G93520-1212 | 12MB-12FP-LX90S | 7252-10155 | 1 1/16–12 | 3/4–14 |
| G93520-1616 | 16MB-16FP-LX90S | 7252-10165 | 1 5/16–12 | 1–11 1/2 |

## Male Boss to Male JIC - 90°



| Part No. | Descr. | Prod. No. | | |
|---|---|---|---|---|
| | | | " | " |
| G93530-0606 | 6MB-6MJ-LX90S | 7252-10055 | 9/16–18 | 9/16–18 |
| G93530-0808 | 8MB-8MJ-LX90S | 7252-10065 | 3/4–16 | 3/4–16 |
| G93530-1212 | 12MB-12MJ-LX90S | 7252-10075 | 1 1/16–12 | 1 1/16–12 |
| G93530-1616 | 16MB-16MJ-LX90S | 7252-10085 | 1 5/16–12 | 1 5/16–12 |


## ORS Seal Kit

| Part No. | Descr. | Prod. No. | Standard Pack |
|---|---|---|---|
| G93600-0012 | 12ORS LIVE SWIVEL SEAL KIT | 7252-12235 | 1 |
| G93600-0016 | 16ORS LIVE SWIVEL SEAL KIT | 7252-12245 | 1 |

## ORS/BSPP Seal Kit


| Part No. | Descr. | Prod. No. | Standard Pack |
|---|---|---|---|
| G93700-0008 | 8ORS/8BSPP LIVE SWVL SEAL KIT | 7252-12225 | 1 |

## Male ORFS to Female ORFS



| Part No. | Descr. | Prod. No. | | | | Hex Shank | Hex Body | Overall Length | Diameter |
|---|---|---|---|---|---|---|---|---|---|
| | | | | " | " | " | " | " | " |
| G93724-1212 | 12MFFOR-12FFORX-LX | 7252-12445 | 6000 | 1 3/16–12 | 1 3/16–12 | 1 1/16 | 1 3/4 | 3.86 | 2.09 |
| G93724-1616 | 16MFFOR-16FFORX-LX | 7252-12455 | 6000 | 1 7/16–12 | 1 7/16–12 | 1 5/16 | 2 | 4.38 | 2.31 |

## Male ORFS to Male ORFS



| Part No. | Descr. | Prod. No. | | | | Hex Shank | Hex Body | Overall Length | Diameter |
|---|---|---|---|---|---|---|---|---|---|
| | | | | " | " | " | " | " | " |
| G93742-0808 | 8MFFOR-8MFFOR-LX | 7252-12465 | 6000 | 13/16–16 | 13/16–16 | 3/4 | 15/16 | 3.50 | 1.53 |
| G93742-1212 | 12MFFOR-12MFFOR-LX | 7252-12475 | 6000 | 1 3/16–12 | 1 3/16–12 | 1 1/16 | 1 3/4 | 4.52 | 2.09 |
| G93742-1616 | 16MFFOR-16MFFOR-LX | 7252-12485 | 6000 | 1 7/16–12 | 1 7/16–12 | 1 5/16 | 2 | 5.12 | 2.31 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Tube Assembly Equipment



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| 91025 | 7468-1040 | Bend–N–Fit Tube Bender | 1 |

# Steel Power Steering & Transmission Oil Cooler Tubing - Male O-Ring



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A35001-2405 | 7821-0113 | 24" – 5/16" Male O–Ring | 2 |
| A35001-2406 | 7821-0118 | 24" – 3/8" Male O–Ring | 2 |
| A35001-2407 | 7821-0126 | 24" – 7/16" Male O–Ring | 2 |
| A35001-2414 | 7821-0104 | 24" – 14mm Male O–Ring | 2 |
| A35001-2416 | 7821-0110 | 24" – 16mm Male O–Ring | 2 |

# Steel Power Steering & Transmission Oil Cooler Tubing - Male Inverted Flare



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A35003-2406 | 7821-0117 | 24" – 3/8" Inverted Male Flare | 2 |
| A35003-2414 | 7821-0103 | 24" – 14mm Male Inverted Flare | 2 |
| A35003-2416 | 7821-0109 | 24" – 16mm Male Inverted Flare | 2 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Steel Power Steering & Transmission Oil Cooler Tubing - Male SAE



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A35004-2406 | 7821-0119 | 24" – 3/8" Male SAE | 2 |

# Steel Power Steering & Transmission Oil Cooler Tubing - Long Swivel O-Ring



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A35005-2416 | 7821-0108 | 24" – 16mm Long Swivel O–Ring | 2 |

# Steel Power Steering & Transmission Oil Cooler Tubing - Swivel O-Ring Type I



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A35006-2406 | 7821-0120 | 24" – 3/8" Swivel O–Ring Type I | 2 |

# Steel Power Steering & Transmission Oil Cooler Tubing - Swivel O-Ring Type II



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| ⚠ A35007-2405 | 7821-0114 | 24" – 5/16" Swivel O–Ring Type II | 2 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Steel Power Steering & Transmission Oil Cooler Tubing - Swivel O-Ring Type III



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A35008-2416 | 7821-0111 | 24" – 16mm Swivel O–Ring Type III | 2 |

# Steel Power Steering & Transmission Oil Cooler Tubing - Male Captive O-Ring



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A35010-2412 | 7821-0101 | 24" – 12mm Male Captive O–Ring | 2 |

# Steel Power Steering & Transmission Oil Cooler Tubing - Captive O-Ring



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A35011-2418 | 7821-0112 | 24" – 18mm Captive O–Ring | 2 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Steel Power Steering & Transmission Oil Cooler Tubing - Female SAE



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A35012-2406 | 7821-0116 | 24" – 3/8" Female SAE | 2 |
| A35012-2408 | 7821-0127 | 24" – 1/2" Female SAE | 2 |
| A35012-2416 | 7821-0107 | 24" – 16mm Female SAE | 2 |

# Steel Power Steering & Transmission Oil Cooler Tubing - Beaded Tube



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A35020-2406 | 7821-0115 | 24" – 3/8" Beaded Tube | 2 |

# Steel Power Steering & Transmission Oil Cooler Tubing - Male Single Bead Quick Connect



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A35023-2406 | 7821-0124 | 24" – 3/8" Male Single Bead Quick Connect | 2 |

# Steel Power Steering & Transmission Oil Cooler Tubing - Double Beaded Pipe



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A35025-2406 | 7821-0121 | 24" – 3/8" Double Beaded Pipe | 2 |

# Steel Power Steering & Transmission Oil Cooler Tubing - GM Quick Connect



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A35030-2406 | 7821-0123 | 24" – 3/8" GM Quick Connect | 2 |

# Aluminum Air Conditioning Tubing - Male Tube O-Ring



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A45001-2406 | 7821-2024 | 24" – 3/8" Male Tube O–Ring | 2 |
| A45001-2408 | 7821-2025 | 24" – 1/2" Male Tube O–Ring | 2 |

# Aluminum Air Conditioning Tubing - Male SAE



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A45004-2406 | 7821-2020 | 24" – 3/8" Male SAE | 2 |
| A45004-2408 | 7821-2021 | 24" – 1/2" Male SAE | 2 |

# Aluminum Air Conditioning Tubing - Male Inverted O-Ring



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A45009-2406 | 7821-2029 | 24" – 3/8" Male Inverted O–Ring | 2 |
| A45009-2408 | 7821-2030 | 24" – 1/2" Male Inverted O–Ring | 2 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Aluminum Air Conditioning Tubing - Female Tube O-Ring



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A45011-2406 | 7821-2022 | 24" – 3/8" Female Tube O–Ring | 2 |
| A45011-2408 | 7821-2023 | 24" – 1/2" Female Tube O–Ring | 2 |
| A45011-2416 | 7821-2026 | 24" – 16mm Female Tube O–Ring | 2 |
| A45011-2418 | 7821-2027 | 24" – 18mm Female Tube O–Ring | 2 |
| A45011-2420 | 7821-2028 | 24" – 20mm Female Tube O–Ring | 2 |

# Aluminum Air Conditioning Tubing - Female SAE



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A45012-2406 | 7821-2018 | 24" – 3/8" Female SAE | 2 |
| A45012-2408 | 7821-2019 | 24" – 1/2" Female SAE | 2 |

# Aluminum Air Conditioning Tubing - Male Ford Spring Lock



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| ⚠ A45035-2406 | 7821-2031 | 24" – 3/8" Male Ford Spring Lock | 2 |
| ⚠ A45035-2408 | 7821-2032 | 24" – 1/2" Male Ford Spring Lock | 2 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Aluminum Air Conditioning Tubing - Female Ford Spring Lock



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| A45036-2406 | 7821-2033 | 24" – 3/8" Female Ford Spring Lock | 2 |
| A45036-2408 | 7821-2034 | 24" – 1/2" Female Ford Spring Lock | 2 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# LifeGuard® Tools

| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| 78075 | 7484-1600 | LifeGuard Sleeve Guide Table | 1 |
| 78076 | 7482-1604 | LifeGuard Sleeve Bullets –4, –6, –8 | 1 |

# LifeGuard® 3000, 4000 and 5000






| Part No. | Descr. | Prod. No. | A Inside Flat | B Sleeve I.D. | Standard Pack |
|---|---|---|---|---|---|
| | | | " | " | |
| G81102-0014 | 14LG3K | 7277-1850 | 1.11 | .71 | 120 |
| G81102-0016 | 16LG3K | 7277-1851 | 1.42 | .91 | 120 |
| G81102-0020 | 20LG3K | 7277-1852 | 1.67 | 1.06 | 120 |
| G81102-0022 | 22LG3K | 7277-1853 | 2.13 | 1.35 | 120 |
| G81102-0026 | 26LG3K | 7277-1854 | 2.36 | 1.50 | 120 |
| G81102-0032 | 32LG3K | 7277-1855 | 2.78 | 1.99 | 120 |
| G81104-0014 | 14LG4K | 7277-1960 | 1.38 | .88 | 120 |
| G81104-0016 | 16LG4K | 7277-1961 | 1.62 | 1.03 | 120 |
| G81104-0020 | 20LG4K | 7277-1962 | 1.91 | 1.22 | 120 |
| G81104-0022 | 22LG4K | 7277-1963 | 1.98 | 1.26 | 120 |
| G81104-0026 | 26LG4K | 7277-1964 | 2.50 | 1.59 | 120 |
| G81104-0032 | 32LG4K | 7277-1965 | 2.78 | 1.99 | 120 |
| G81105-0014 | 14LG5K | 7277-1950 | 1.38 | .88 | 120 |
| G81105-0016 | 16LG5K | 7277-1951 | 1.62 | 1.03 | 120 |
| G81105-0020 | 20LG5K | 7277-1952 | 1.91 | 1.22 | 120 |
| G81105-0022 | 22LG5K | 7277-1953 | 2.13 | 1.35 | 120 |
| G81105-0026 | 26LG5K | 7277-1954 | 2.50 | 1.59 | 120 |

# LifeGuard® Clamp Collars - Stainless Steel



| Part No. | Descr. | Prod. No. | ⟷ | Standard Pack |
|---|---|---|---|---|
| | | | " | |
| G81995-0406S | 6SC-4-SS | 7334-48535 | 1.15 | 1 |
| G81995-0408S | 8SC-4-SS | 7334-48545 | 1.40 | 1 |
| G81995-0410S | 10SC-4-SS | 7334-48605 | 1.62 | 1 |
| G81995-0412S | 12SC-4-SS | 7334-48615 | 1.87 | 1 |
| G81995-0516S | 16SC-5-SS | 7334-48815 | 2.09 | 1 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Clamp Collar for Nylon Sleeve and LifeGuard® Sleeve




| Part No. | Descr. | Prod. No. | ⟷ " | Standard Pack |
|---|---|---|---|---|
| G81995-0104 | 4SC-1 | 7334-60035 | .86 | 1 |
| G81995-0104X | 4SC-1 XBULK | 7334-6003 | .86 | 1300 |
| G81995-0106 | 6SC-1 | 7334-60125 | 1.00 | 1 |
| G81995-0106X | 6SC-1 XBULK | 7334-6012 | 1.00 | 2000 |
| G81995-0108 | 8SC-1 | 7334-60315 | 1.18 | 1 |
| G81995-0108X | 8SC-1 XBULK | 7334-6031 | 1.18 | 2000 |
| G81995-0110 | 10SC-1 | 7334-60545 | 1.40 | 1 |
| G81995-0110X | 10SC-1 XBULK | 7334-6054 | 1.40 | 250 |
| G81995-0112 | 12SC-1 | 7334-60755 | 1.62 | 1 |
| G81995-0112X | 12SC-1 XBULK | 7334-6075 | 1.62 | 1000 |
| G81995-0116X | 16SC-2 XBULK | 7334-4882 | 2.06 | 150 |
| G81995-0204X | 4SC-2 XBULK | 7334-6001 | .81 | 900 |
| G81995-0210 | 10SC-2 | 7334-60515 | 1.26 | 1 |
| G81995-0210X | 10SC-2 XBULK | 7334-6051 | 1.26 | 100000 |
| G81995-0212 | 12SC-2 | 7334-60715 | 1.45 | 1 |
| G81995-0212X | 12SC-2 XBULK | 7334-6071 | 1.45 | 1250 |
| G81995-0306 | 6SC-3 | 7334-60145 | 1.05 | 1 |
| G81995-0306X | 6SC-3 XBULK | 7334-6014 | 1.05 | 2000 |
| G81995-0406 | 6SC-4 | 7334-60155 | 1.15 | 1 |
| G81995-0406X | 6SC-4 XBULK | 7334-6015 | 1.15 | 400 |
| G81995-0408 | 8SC-4 | 7334-60555 | 1.62 | 1 |
| G81995-0408X | 8SC-4 XBULK | 7334-6055 | 1.62 | 200 |
| G81995-0410 | 10SC-4 | 7334-60565 | 2.37 | 1 |
| G81995-0410X | 10SC-4 XBULK | 7334-6056 | 2.37 | 200 |
| G81995-0412 | 12SC-4 | 7334-60575 | 1.87 | 1 |
| G81995-0412X | 12SC-4 XBULK | 7334-6057 | 1.87 | 150 |
| G81995-0416 | 16SC-4 | 7334-60585 | 1.40 | 1 |

# Nylon Protective Sleeve

Do not use the Nylon Sleeve where ambient temperatures exceed 250°F.

Description: Gates Nylon Sleeves perform a dual role: (1) they provide excellent abrasion resistance to protect individual hose; and (2) they can be used to bundle several hose assemblies together for maximum protection. Downtime and maintenance costs are reduced. These Nylon Sleeves are unique because they form an extra protective layer against abrasive forces. Specifically, thousands of tiny Nylon filaments, woven into the texturized yarn, "friz" into a self–renewing shield that is extremely resistant to severe abrasion. This nylon sleeving has MSHA flame–resistance approval. Add 1/8" for installation.






| Part No. | Descr. | Prod. No. | A Inside Flat | B Sleeve I.D. | Standard Pack |
|---|---|---|---|---|---|
| | | | " | " | |
| G81800-0010 | HG-10 | 7277-1067 | 1.07 | .68 | 300 |
| G81800-0014 | HG-14 | 7277-1010 | 1.42 | .90 | 300 |
| G81800-0016 | HG-16 | 7277-1011 | 1.67 | 1.06 | 300 |
| G81800-0020 | HG-20 | 7277-1012 | 1.92 | 1.22 | 300 |
| G81800-0024 | HG-24 | 7277-1013 | 2.24 | 1.42 | 300 |
| G81800-0026 | HG-26 | 7277-1377 | 2.50 | 1.59 | 300 |
| G81800-0028 | HG-28 | 7277-1014 | 2.85 | 1.81 | 300 |
| G81800-0032 | HG-32 | 7277-1015 | 3.44 | 2.19 | 300 |
| G81800-0038 | HG-38 | 7277-1016 | 3.74 | 2.38 | 300 |
| G81800-0042 | HG-42 | 7277-1018 | 4.12 | 2.62 | 300 |
| G81800-0046 | HG-46 | 7277-1024 | 4.53 | 2.88 | 300 |
| G81800-0064 | HG-64 | 7277-1276 | 6.91 | 4.40 | 100 |
| G81801-0014 | HG 14 X25FT | 7277-1278 | 1.42 | .90 | 25 |
| G81801-0016 | HG 16 X25FT | 7277-1279 | 1.67 | 1.06 | 25 |
| G81801-0020 | HG 20 X25FT | 7277-1280 | 1.92 | 1.22 | 25 |
| G81801-0024 | HG 24 X25FT | 7277-1281 | 2.24 | 1.42 | 25 |
| G81801-0026 | HG 26 X25FT | 7277-1378 | 2.50 | 1.59 | 25 |
| G81801-0028 | HG 28 X25FT | 7277-1282 | 2.85 | 1.81 | 25 |
| G81801-0032 | HG 32 X25FT | 7277-1283 | 3.44 | 2.19 | 25 |
| G81801-0038 | HG 38 X25FT | 7277-1284 | 3.74 | 2.38 | 25 |

NOTE: Be sure to heat the cut edges of the Nylon Hose Sleeve. You may have to use a banded clamp or nylon tie to fasten the sleeve securely.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# PolySleeve™ High Density Polyethylene Hose Wrap

Description: Gates PolySleeve is a spiral wrap designed to protect or bundle hose for appearance and safety. PolySleeve protects hose from chaffing, rubbing, crushing, ultraviolet rays and other hazards that cause hose failures. It can be an easy and economical way to protect equipment, reduce downtime, improve sighting and improve overall appearance. PolySleeve can be installed easily – even after the hose assembly or assemblies are in place. The edges are rounded, so installers won't cut their hands. Just wrap a section of Gates PolySleeve in the abrasion area or wrap it around any number of hose for better appearance or safety. It is offered in either black or yellow in a full range of sizes.
This product is made of heavy–wall, high–density polyethylene (HDPE) and has a wide temperature range. At –40°F it starts to become somewhat brittle, and at 280°F it starts to become soft. After temperature is normalized, PolySleeve returns to its original state quickly. PolySleeve is made with an anti–static material, so it won't build up a static charge.


Features Advantages: Available in two colors (black and yellow), multiple sizes for individual hose or bundling.
Comes with rounded edges both inside and out for added safety.
Easy to install before or after assembly fabrication or installation.
Effective temperature range from –40°F to +280°F (–40°C to +130°C).
Guards against harsh environmental conditions for reduced downtime.
Safe, affordable protection for hydraulic and pneumatic lines.



| Part No. | Descr. | Prod. No. | Color | Coil I.D. | Fits Max. Hose O.D. | Fits Min. Hose O.D. | Wall Thickness | Width | Standard Pack |
|---|---|---|---|---|---|---|---|---|---|
| | | | | " | " | " | " | " | |
| G80901-0006 | 6PSB POLY SLEEVE | 7277-1174 | Black | .38 | .52 | .38 | .060 | 3/8 | 165 |
| G80901-0008 | 8PSB POLY SLEEVE | 7277-1175 | Black | .50 | .64 | .52 | .070 | 9/16 | 66 |
| G80901-0012 | 12PSB POLY SLEEVE | 7277-1176 | Black | .63 | .85 | .63 | .080 | 5/8 | 66 |
| G80901-0016 | 16PSB POLY SLEEVE | 7277-1177 | Black | .84 | 1.08 | .86 | .080 | 7/8 | 66 |
| G80901-0020 | 20PSB POLY SLEEVE | 7277-1178 | Black | 1.06 | 1.35 | 1.10 | .100 | 15/16 | 66 |
| G80901-0024 | 24PSB POLY SLEEVE | 7277-1179 | Black | 1.34 | 1.74 | 1.36 | .120 | 1 3/16 | 66 |
| G80901-0028 | 28PSB POLY SLEEVE | 7277-1180 | Black | 1.73 | 2.18 | 1.75 | .120 | 1 7/16 | 66 |
| G80901-0036 | 36PSB POLY SLEEVE | 7277-1181 | Black | 2.17 | 2.61 | 2.19 | .160 | 1 1/2 | 66 |
| G80901-0044 | 44PSB POLY SLEEVE | 7277-1182 | Black | 2.60 | 3.11 | 2.62 | .180 | 1 11/16 | 66 |
| G80901-0048 | 48PSB POLY SLEEVE | 7277-1183 | Black | 3.10 | 3.95 | 3.12 | .220 | 1 7/8 | 66 |
| G80901-0056 | 56PSB POLY SLEEVE | 7277-1184 | Black | 3.90 | 4.25 | 3.95 | .220 | 2 1/4 | 40 |
| G80901-0072 | 72PSB POLY SLEEVE | 7277-0001 | Black | 4.33 | 12.00 | 4.35 | .220 | 1 3/8 | 40 |
| G80902-0006 | 6PSY POLY SLEEVE | 7277-1185 | Yellow | .38 | .52 | .38 | .060 | 3/8 | 165 |
| G80902-0008 | 8PSY POLY SLEEVE | 7277-1186 | Yellow | .50 | .64 | .52 | .070 | 9/16 | 66 |
| G80902-0012 | 12PSY POLY SLEEVE | 7277-1187 | Yellow | .63 | .85 | .63 | .080 | 5/8 | 66 |
| G80902-0016 | 16PSY POLY SLEEVE | 7277-1188 | Yellow | .84 | 1.08 | .86 | .080 | 7/8 | 66 |
| G80902-0020 | 20PSY POLY SLEEVE | 7277-1189 | Yellow | 1.06 | 1.35 | 1.10 | .100 | 15/16 | 66 |
| G80902-0024 | 24PSY POLY SLEEVE | 7277-1190 | Yellow | 1.34 | 1.74 | 1.36 | .120 | 1 3/16 | 66 |
| G80902-0028 | 28PSY POLY SLEEVE | 7277-1191 | Yellow | 1.73 | 2.18 | 1.75 | .120 | 1 7/16 | 66 |
| G80902-0036 | 36PSY POLY SLEEVE | 7277-1192 | Yellow | 2.17 | 2.61 | 2.19 | .160 | 1 1/2 | 66 |
| G80902-0044 | 44PSY POLY SLEEVE | 7277-1193 | Yellow | 2.60 | 3.11 | 2.62 | .180 | 1 11/16 | 66 |
| G80902-0048 | 48PSY POLY SLEEVE | 7277-1194 | Yellow | 3.10 | 3.95 | 3.12 | .220 | 1 7/8 | 66 |
| G80902-0056 | 56PSY POLY SLEEVE | 7277-1195 | Yellow | 3.90 | 4.25 | 3.95 | .220 | 2 1/4 | 40 |

# Plastic Protective Coil Sleeves


Description: Economical, lightweight plastic sleeving protects hose from water, air, gasoline and hydraulic fluids. Effective temperature range from –40°F to +250°F (–40°C to +121°C).




| Part No. | Descr. | Prod. No. | A Coil I.D. | B Strip Width | Thickness | Standard Pack |
|---|---|---|---|---|---|---|
| | | | " | " | " | |
| G81900-0004 | 1/4" CS1151-100FT | 7277-1151 | 1/4 | 1/4 | .040 | 100 |
| G81900-0006 | 3/8" CS1152-100FT | 7277-1152 | 3/8 | 1/4 | .040 | 100 |
| G81900-0008 | 1/2" CS1153-100FT | 7277-1153 | 1/2 | 3/8 | .070 | 100 |
| G81900-0010 | 5/8" CS1154-50FT | 7277-1154 | 5/8 | 3/8 | .070 | 50 |
| G81900-0012 | 3/4" CS1155-50FT | 7277-1155 | 3/4 | 3/8 | .070 | 50 |
| G81900-0016 | 1" CS1156-50FT | 7277-1156 | 1 | 5/8 | .115 | 50 |
| G81900-0022 | 1 3/8" CS1157-25FT | 7277-1157 | 1 3/8 | 5/8 | .115 | 25 |
| G81900-0030 | 1 7/8" CS1158-25FT | 7277-1158 | 1 7/8 | 5/8 | .115 | 25 |

# Plated Flat Armor Spring Guards

Description: For proper spring guard selection compare the outside diameter of the hose to the inside diameter of the spring guard. Allow 1/32" for installation.




| Part No. | Descr. | Prod. No. | A (+.015) | B | C | P | Standard Pack |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | |
| G82801-0008 | 35/64" FSG-25FT | 7277-0500 | .550 | .019 | 3/8 | 1/2 | 25 |
| G82801-0009 | 21/32" FSG-25FT | 7277-0501 | .656 | .019 | 3/8 | 1/2 | 25 |
| G82801-0010 | 39/64" FSG-25FT | 7277-0533 | .609 | .032 | 1/4 | 3/8 | 25 |
| G82801-0011 | 22/32" FSG-25FT | 7277-0502 | .719 | .019 | 3/8 | 1/2 | 25 |
| G82801-0012 | 13/16" FSG-25FT | 7277-0503 | .812 | .028 | 1/4 | 3/8 | 25 |
| G82801-0013 | 51/64" FSG-25FT | 7277-0534 | .797 | .032 | 3/8 | 1/2 | 25 |
| G82801-0014 | 7/8" FSG-25FT | 7277-0504 | .875 | .028 | 1/2 | 5/8 | 25 |
| G82801-0015 | 61/64" FSG-25FT | 7277-0505 | .953 | .028 | 1/2 | 5/8 | 25 |
| G82801-0016 | 1" FSG-25FT | 7277-0506 | 1.000 | .028 | 1/2 | 5/8 | 25 |
| G82801-0017 | 1 3/32" FSG-25FT | 7277-0530 | 1.093 | .028 | 1/2 | 5/8 | 25 |
| G82801-0019 | 1 7/32" FSG-25FT | 7277-0507 | 1.219 | .028 | 1/2 | 5/8 | 25 |
| G82801-0020 | 1 9/32" FSG-25FT | 7277-0508 | 1.281 | .028 | 1/2 | 5/8 | 25 |
| G82801-0022 | 1 3/8" FSG-25FT | 7277-0532 | 1.375 | .028 | 1/2 | 5/8 | 25 |
| G82801-0025 | 1 9/16" FSG-25FT | 7277-0520 | 1.562 | .028 | 1/2 | 5/8 | 25 |
| G82801-0026 | 1 5/8" FSG-25FT | 7277-0509 | 1.625 | .028 | 1/2 | 5/8 | 25 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Plated Flat Armor Spring Guards - Continued

| Part No. | Descr. | Prod. No. | A (+.015) | B | C | P | Standard Pack |
|---|---|---|---|---|---|---|---|
| | | | " | " | " | " | |
| G82801-0027 | 1 11/16" FSG-5FT | 7277-0529 | 1.687 | .028 | 1/2 | 5/8 | 5 |
| G82801-0028 | 1 51/64" FSG-15FT | 7277-0525 | 1.797 | .028 | 1/2 | 5/8 | 15 |
| G82801-0029 | 1 27/32" FSG-15FT | 7277-0531 | 1.844 | .028 | 1/2 | 5/8 | 15 |
| G82801-0033 | 2 3/32" FSG-10FT | 7277-0527 | 2.093 | .028 | 1/2 | 5/8 | 10 |
| G82801-0037 | 2 11/32" FSG-5FT | 7277-0528 | 2.343 | .028 | 1/2 | 5/8 | 5 |
| G82801-0046 | 2 7/8" FSG-5FT | 7277-0526 | 2.875 | .028 | 1/2 | 5/8 | 5 |

## Plated Wire Spring Guards

Description: For proper spring guard selection compare the outside diameter of the hose to the inside diameter of the spring guard. Allow 1/32" for installation.




| Part No. | Descr. | Prod. No. | A (+.015) | G | P | Standard Pack |
|---|---|---|---|---|---|---|
| | | | " | " | " | |
| G83801-0009 | 35/64" RSG-25FT | 7277-0521 | .550 | 14 (.080) | 7/32 | 25 |
| G83801-0010 | 49/64" RSG-25FT | 7277-0510 | .676 | 14 (.080) | 7/32 | 25 |
| G83801-0011 | 11/16" RSG-25FT | 7277-0535 | .682 | 16 (.065) | 7/32 | 25 |
| G83801-0012 | 47/64" RSG-25FT | 7277-0511 | .738 | 14 (.080) | 7/32 | 25 |
| G83801-0014 | 55/64" RSG-25FT | 7277-0512 | .852 | 14 (.080) | 7/32 | 25 |
| G83801-0015 | 59/64" RSG-25FT | 7277-0513 | .915 | 14 (.080) | 7/32 | 25 |
| G83801-0016 | 63/64" RSG-25FT | 7277-0514 | .977 | 14 (.080) | 7/32 | 25 |
| G83801-0017 | 1 3/64" RSG-25FT | 7277-0515 | 1.040 | 14 (.080) | 7/32 | 25 |
| G83801-0018 | 1 1/8" RSG-25FT | 7277-0522 | 1.122 | 14 (.080) | 7/32 | 25 |
| G83801-0020 | 1 9/32" RSG-25FT | 7277-0516 | 1.278 | 11 (.120) | 11/32 | 25 |
| G83801-0021 | 1 11/32" RSG-25FT | 7277-0517 | 1.340 | 11 (.120) | 11/32 | 25 |
| G83801-0025 | 1 37/64" RSG-25FT | 7277-0518 | 1.578 | 11 (.120) | 11/32 | 25 |
| G83801-0026 | 1 5/8" RSG-25FT | 7277-0519 | 1.625 | 11 (.120) | 11/32 | 25 |
| G83801-0029 | 1 27/32" RSG-10FT | 7277-0524 | 1.847 | 14 (.080) | 13/32 | 10 |
| G83801-0034 | 2 1/8" RSG-7FT | 7277-0548 | 2.120 | 11 (.120) | 11/32 | 7 |
| G83801-0040 | 2 7/64" RSG-7FT | 7277-0523 | 2.112 | 14 (.080) | 13/32 | 7 |

# HeatGuard® Tape

Description: HeatGuard Tape is designed to provide a non–adhesive insulating wrap that can be used as a substitute for HeatGuard protective sheathing, offering resistance to molten metal splash, radiant heat, abrasion, corrosive atmosphere, moisture, chemicals, vibration and electricity. HeatGuard Tape is white knitted fiberglass yarn woven in a flat strip and coated on one side with iron oxide red silicone rubber with a nominal thickness of 0.147".

Temperature Range: Rated for 500°F (260°C) continuous exposure, up to 2000°F (1093°C) for 15–20 minutes and up to 3000°F (1650°C) for 15–30 seconds.




| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| G81100-0100 | 7277-0010 | HTG–1" Wide HeatGuard Tape | 100 |
| G81100-0200 | 7277-0011 | HTG–2" Wide HeatGuard Tape | 100 |
| G81100-0300 | 7277-0012 | HTG–3" Wide HeatGuard Tape | 100 |
| G81100-0400 | 7277-0013 | HTG–4" Wide HeatGuard Tape | 100 |
| G81100-0500 | 7277-0014 | HTG–5" Wide HeatGuard Tape | 100 |

# HeatGuard® Protective Sheathing

Description: Best of all, HeatGuard can pay for itself in reduced replacement and maintenance costs. It is available in two grades – HeatGuard and HeatGuard Hi–Temp. Contact Hose Product Application for details.
HeatGuard is a completely not–asbestos, heat–resistant, protective sleeving. It goes on easily over most hose and couplings, with only hose clamps or wire ties required for fastening. Nominal wall thickness – 0.135".

Temperature Range: HeatGuard coated fiberglass; –65°F to +500°F (–54°C to +260°C).



| Part No. | Descr. | Prod. No. | Inside Diameter " | Standard Pack |
|---|---|---|---|---|
| G81100-0004 | HTG-4 | 7277-1571 | .25 | 50 |
| G81100-0005 | HTG-5 | 7277-1572 | .31 | 50 |
| G81100-0006 | HTG-6 | 7277-1573 | .38 | 50 |
| G81100-0007 | HTG-7 | 7277-1574 | .44 | 50 |
| G81100-0008 | HTG-8 | 7277-1575 | .50 | 50 |
| G81100-0009 | HTG-9 | 7277-1576 | .56 | 50 |
| G81100-0010 | HTG-10 | 7277-1577 | .62 | 50 |
| G81100-0011 | HTG-11 | 7277-1578 | .69 | 50 |
| G81100-0012 | HTG-12 | 7277-1579 | .75 | 50 |
| G81100-0013 | HTG-13 | 7277-1580 | .81 | 50 |
| G81100-0014 | HTG-14 | 7277-1581 | .88 | 50 |
| G81100-0015 | HTG-15 | 7277-1582 | .94 | 50 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## HeatGuard® Protective Sheathing - Continued

| Part No. | Descr. | Prod. No. | Inside Diameter " | Standard Pack |
|---|---|---|---|---|
| G81100-0016 | HTG-16 | 7277-1196 | 1.00 | 50 |
| G81100-0018 | HTG-18 | 7277-1197 | 1.12 | 50 |
| G81100-0020 | HTG-20 | 7277-1583 | 1.25 | 50 |
| G81100-0022 | HTG-22 | 7277-1584 | 1.38 | 50 |
| G81100-0024 | HTG-24 | 7277-1585 | 1.50 | 50 |
| G81100-0026 | HTG-26 | 7277-1586 | 1.62 | 50 |
| G81100-0028 | HTG-28 | 7277-1587 | 1.75 | 50 |
| G81100-0030 | HTG-30 | 7277-1588 | 1.88 | 50 |
| G81100-0032 | HTG-32 | 7277-1589 | 2.00 | 50 |
| G81100-0034 | HTG-34 | 7277-1590 | 2.12 | 50 |
| G81100-0036 | HTG-36 | 7277-1591 | 2.25 | 50 |
| G81100-0038 | HTG-38 | 7277-1592 | 2.38 | 50 |
| G81100-0040 | HTG-40 | 7277-1593 | 2.50 | 50 |
| G81100-0044 | HTG-44 | 7277-1595 | 2.75 | 50 |
| G81100-0056 | HTG-56 | 7277-1600 | 3.50 | 50 |
| G81100-0064 | HTG-64 | 7277-1602 | 4.00 | 50 |

## HeatGuard® High-Temp Protective Sheathing

Description: HeatGuard Hi–Temp is a completely not–asbestos, heat–resistant, protective sleeving. It goes on easily over most hose and couplings, with only hose clamps or wire ties required for fastening. Nominal wall thickness – 0.142". It is available in two grades – HeatGuard and HeatGuard Hi–Temp. Contact Hose Product Application for details.
It is available in two grades – HeatGuard and HeatGuard Hi–Temp. Contact Hose Product Application for details.

Temperature Range: HeatGuard Hi–Temp is braided, coated fiberglass; meets SAE AS1072E specification; temperature range: –65°F to +500°F (–54°C to +260°C) for continuous exposure, up to 2000°F (1093°C) for 15–20 minutes and up to 3000°F (1650°C) for 15–30 seconds.



| Part No. | Descr. | Prod. No. | Inside Diameter " | Standard Pack |
|---|---|---|---|---|
| G81101-0024 | 24-HTGH | 7277-1611 | 1.50 | 50 |
| G81101-0028 | 28-HTGH | 7277-1612 | 1.75 | 50 |
| G81101-0034 | 34-HTGH | 7277-1613 | 2.12 | 50 |
| G81101-0052 | 52-HTGH | 7277-1616 | 3.25 | 50 |

# Clamp Collars

Description: Crimping Instruction: Care must be taken when crimping clamp collars onto a hydraulic hose. If crimp is too tight, hose will be crushed, dramatically reducing its service life. If crimp is to loose, collar could slide along hose's length causing abrasion and eventual hose cover failure. Remember: Clamp collars must be crimped before the hose couplings.
To locate clamps and protect hose. Previously available only through equipment dealerships, clamp collars are common on many types of construction equipment. The collars are actually crimped onto a hydraulic hose, reducing hose movement and minimizing abrasion.
Use the following instruction to determine crimp diameter, which can then be used to find crimping setting in Gates Crimp Data Manual (428–7365 Auto./35019 Ind.). The required clamp collar for a specific hydraulic hose is provided in Table 1. 1. Measure hose's outside diameter at the location where clamp collar will be crimped. This can be accomplished by using a pie tape or by using the average hose outside diameter measured with a dial caliper. 2. Measure wall thickness of clamp collar with a dial caliper. 3. Obtain crimp diameter by adding hose outside diameter to twice the clamp collar wall thickness; Crimp Diameter – (Hose O.D.) + (2 x .065).



| Part No. | Descr. | Prod. No. | Hydraulic Hose Applications |
|---|---|---|---|
| G52000-0210 | CC1.12 | 7334-45805 | 10M2T, 10G2, 10M3K |
| G52000-0210S | CC1.20 | 7334-37015 | 12M2T, 12G2, 12M4K |
| G52000-0212 | CC1.25 | 7334-45885 | 12M2T, 12G2, 12M4K |
| G52000-0412 | CC1.37 | 7334-45895 | 12C12, 12G4K |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Vinyl Bend Restrictor

Description: Gates tapered PVC sleeve reduces bending stress in the hose near the coupling to prevent damage, such as in power wash applications. Installed during hose assembly, this smoothly–finished product withstands temperatures from –40°F to +200°F (–40°C to +93°C).

Features Advantages: Friction Fit; no adhesives or clamps required to hold bend restrictor in place on hose assembly. Saves assembly cost.
Smooth finish will not scratch finish on equipment being washed. Attractive appearance enhances look of quality.
Tapered design reduces bending stress neat the hose–coupling junction so extra–long, more hose life can be expected.
Wide temperature helps give extra–long service life for both hot and cold power wash assemblies.






| Part No. | Descr. | Prod. No. | Color | Inside Diameter " | Length " | Hose Size and Type | Standard Pack |
|---|---|---|---|---|---|---|---|
| G80700-0106 | HBR1051 | 7277-10515 | Black | .73 | 6.0 | 6G1, 6G1H, 6M3K, 6M2T, 6PC3000, 6PC4000, 4PC6000 | 27 |
| G80700-0106X | HBR1051 XBULK | 7277-1051 | Black | .73 | 6.0 | 6G1, 6G1H, 6M3K, 6M2T, 6PC3000, 6PC4000, 4PC6000 | 380 |
| G80700-0108 | HBR1052 | 7277-10525 | Black | .84 | 7.00 | 8G1, 8G1H, 6PC5000 | 38 |
| G80700-0108X | HBR1052 XBULK | 7277-1052 | Black | .84 | 7.00 | 8G1, 8G1H, 6PC5000 | 200 |
| G80700-0110 | HBR1053 | 7277-10535 | Black | 1.00 | 8.0 | 10G1, 10G1H, 10M2T | 30 |
| G80700-0110X | HBR1053 XBULK | 7277-1053 | Black | 1.00 | 8.0 | 10G1, 10G1H, 10M2T | 150 |
| G80700-0204 | HBR1050 | 7277-10505 | Black | .63 | 5.5 | 4G1, 4G1H, 4G2, 4M3K, 4M2T, 4PC3500 | 39 |
| G80700-0204X | HBR1050 XBULK | 7277-1050 | Black | .63 | 5.5 | 4G1, 4G1H, 4G2, 4M3K, 4M2T, 4PC3500 | 410 |
| G80700-0206 | HBR1054 | 7277-10545 | Black | .77 | 7.00 | 6G2 | 45 |
| G80700-0206X | HBR1054 XBULK | 7277-1054 | Black | .77 | 7.00 | 6G2 | 300 |
| G80700-0208 | HBR1056 | 7277-10905 | Black | .91 | 7.00 | 8PC2500 | 34 |
| G80700-0404 | HBR1055 | 7277-10555 | Black | .53 | 5.3 | 4TH7/4TH7NC | 42 |
| G80700-0404X | HBR1055 XBULK | 7277-1055 | Black | .53 | 5.3 | 4TH7/4TH7NC | 440 |
| G80705-0108 | HBR1098 | 7277-10985 | Red | .91 | 7.00 | 8PC2500 | 34 |
| G80705-0108X | HBR1098 XBULK | 7277-1098 | Red | .91 | 7.00 | 8PC2500 | 190 |
| G80705-0206 | HBR1097 | 7277-10975 | Red | .76 | 7.00 | 6G2 | 45 |
| G80705-0206X | HBR1097 XBULK | 7277-1097 | Red | .76 | 7.00 | 6G2 | 300 |

# Code 61 Flange Cap

For maintenance use only. Not to be used under pressure.





| Part No. | Descr. | Prod. No. | Nom. Flg. Size | A | B | Standard Pack |
|---|---|---|---|---|---|---|
| | | | " | " | " | |
| G60897-0012 | 12FL-CAP | 7253-66115 | 3/4 | 1.88 | .41 | 1 |
| G60897-0016 | 16FL-CAP | 7253-66125 | 1 | 2.06 | .41 | 1 |
| G60897-0020 | 20FL-CAP | 7253-66135 | 1 1/4 | 2.31 | .47 | 1 |
| G60897-0024 | 24FL-CAP | 7253-66145 | 1 1/2 | 2.75 | .53 | 1 |
| G60897-0032 | 32FL-CAP | 7253-66155 | 2 | 3.06 | .53 | 1 |

# Flange Half Sets (Code 61 - SAE J518)

Each set contains 2 flange halves, 1 O–Ring and 4 bolts (Grade 8) with lock washers.







| Part No. | Descr. | Prod. No. | Nom. Flg. Size | A | B | Standard Pack |
|---|---|---|---|---|---|---|
| | | | " | " | " | |
| G60899-0008 | 8CFHS | 7253-07015 | 1/2 | 1.50 | .34 | 1 |
| G60899-0012 | 12CFHS | 7253-07025 | 3/4 | 1.88 | .41 | 1 |
| G60899-0016 | 16CFHS | 7253-07035 | 1 | 2.06 | .41 | 1 |
| G60899-0020 | 20CFHS | 7253-07045 | 1 1/4 | 2.31 | .47 | 1 |
| G60899-0024 | 24CFHS | 7253-07055 | 1 1/2 | 2.75 | .53 | 1 |
| G60899-0032 | 32CFHS | 7253-07065 | 2 | 3.06 | .53 | 1 |
| G60899-0040 | 40CFHS | 7253-01305 | 2 1/2 | 3.50 | .54 | 1 |
| G60899-0048 | 48CFHS | 7253-01315 | 3 | 4.19 | .66 | 1 |
| G60899-0056 | 56CFHS | 7253-01325 | 3 1/2 | 4.75 | .66 | 1 |
| G60899-0064 | 64CFHS | 7253-01335 | 4 | 4.75 | .66 | 1 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Code 62 Flange Cap


For maintenance use only. Not to be used under pressure.





| Part No. | Descr. | Prod. No. | Nom. Flg. Size | A | B | Standard Pack |
|---|---|---|---|---|---|---|
| | | | " | " | " | |
| G60927-0012 | 12FLH-CAP | 7253-66165 | 3/4 | 2.00 | .41 | 1 |
| G60927-0016 | 16FLH-CAP | 7253-66175 | 1 | 2.25 | .47 | 1 |
| G60927-0020 | 20FLH-CAP | 7253-66185 | 1 1/4 | 2.63 | .53 | 1 |
| G60927-0024 | 24FLH-CAP | 7253-66195 | 1 1/2 | 3.13 | .66 | 1 |
| G60927-0032 | 32FLH-CAP | 7253-66205 | 2 | 3.81 | .78 | 1 |

# Flange Half Sets (Code 62 - SAE J518)

Each set contains 2 flange halves, 1 O–Ring and 4 bolts (Grade 8) with lock washers.








| Part No. | Descr. | Prod. No. | Nom. Flg. Size | A | B | Standard Pack |
|---|---|---|---|---|---|---|
| | | | " | " | " | |
| G60929-0008 | 8FHHS | 7253-09775 | 1/2 | 1.55 | .34 | 1 |
| G60929-0012 | 12FHHS | 7253-09785 | 3/4 | 2.00 | .41 | 1 |
| G60929-0016 | 16FHHS | 7253-09795 | 1 | 2.25 | .47 | 1 |
| G60929-0020 | 20FHHS | 7253-09805 | 1 1/4 | 2.63 | .53 | 1 |
| G60929-0024 | 24FHHS | 7253-09815 | 1 1/2 | 3.13 | .66 | 1 |
| G60929-0032 | 32FHHS | 7253-09825 | 2 | 3.81 | .78 | 1 |

# Caterpillar-Style Flange Half Sets

Each set contains 2 flange halves, 1 O–Ring and 4 bolts (Grade 8) with lock washers.






| Part No. | Descr. | Prod. No. | Nom. Flg. Size | A | B | Standard Pack |
|---|---|---|---|---|---|---|
| | | | " | " | " | |
| G60959-0012 | 12CATFHS | 7253-37025 | 3/4 | 2.00 | .41 | 1 |
| G60959-0016 | 16CATFHS | 7253-37035 | 1 | 2.25 | .47 | 1 |
| G60959-0020 | 20CATFHS | 7253-37045 | 1 1/4 | 2.63 | .53 | 1 |
| G60959-0024 | 24CATFHS | 7253-37055 | 1 1/2 | 3.13 | .66 | 1 |
| G60959-0032 | 32CATFHS | 7253-37065 | 2 | 3.81 | .78 | 1 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# O-Rings for Straight Thread Boss Fittings

90 Durometer Hardness.



| Part No. | Descr. | Prod. No. | Inside Diameter " | Wall Thickness " | Standard Pack |
|---|---|---|---|---|---|
| G60248-0003 | 3 O-RING | 7254-0003 | 19/64 | 1/16 | 10 |
| G60248-0004 | 4 O-RING | 7254-0004 | 11/32 | 5/64 | 10 |
| G60248-0005 | 5 O-RING | 7254-0005 | 13/32 | 5/64 | 10 |
| G60248-0006 | 6 O-RING | 7254-0006 | 15/32 | 5/64 | 10 |
| G60248-0008 | 8 O-RING | 7254-0008 | 41/64 | 3/32 | 10 |
| G60248-0010 | 10 O-RING | 7254-0010 | 3/4 | 3/32 | 10 |
| G60248-0012 | 12 O-RING | 7254-0012 | 59/64 | 7/64 | 10 |
| G60248-0014 | 14 O-RING | 7254-0014 | 1 3/64 | 7/64 | 10 |
| G60248-0016 | 16 O-RING | 7254-0016 | 1 11/64 | 7/64 | 10 |
| G60248-0020 | 20 O-RING | 7254-0020 | 1 15/32 | 7/64 | 10 |

# O-Rings for Flat-Face Fittings

90 Durometer Hardness.

Caution: DO NOT USE these O–Rings with phosphate esters, diesters or phosphate ester emulsion hydraulic fluids. Instead, use O–Rings made of Viton, EPDM or CPE polymers or other materials compatible with the fluids.
These O–Rings are compounded from a Nitrile polymer for use with petroleum–based hydraulic fluids, water and glycol and oil–water emulsions.



| Part No. | Descr. | Prod. No. | Reference Coupling " | Arp. No. | Standard Pack |
|---|---|---|---|---|---|
| G60698-0004 | 4 O-RING FF | 7254-0125 | 1/4 | 011 | 10 |
| G60698-0006 | 6 O-RING FF | 7254-0126 | 3/8 | 012 | 10 |
| G60698-0008 | 8 O-RING FF | 7254-0127 | 1/2 | 014 | 10 |
| G60698-0010 | 10 O-RING FF | 7254-0128 | 5/8 | 016 | 10 |
| G60698-0012 | 12 O-RING FF | 7254-0129 | 3/4 | 018 | 10 |
| G60698-0016 | 16 O-RING FF | 7254-0130 | 1 | 021 | 10 |
| G60698-0020 | 20 O-RING FF | 7254-0131 | 1 1/4 | 025 | 10 |
| G60698-0024 | 24 O-RING FF | 7254-0132 | 1 1/2 | 029 | 10 |

NOTE: Standard O–Ring number.

# O-Rings for Code 61, Code 62, and Caterpillar-Style Flange Fittings

90 Durometer Hardness.



| Part No. | Descr. | Prod. No. | Inside Diameter | Wall Thickness | Standard Pack |
|---|---|---|---|---|---|
| | | | " | " | |
| G60898-0008 | 8 FLANGE O-RING | 7254-0001 | 3/4 | .139 | 10 |
| G60898-0010 | 10 FLANGE O-RING | 7254-0142 | 55/64 | .139 | 10 |
| G60898-0012 | 12 FLANGE O-RING | 7254-0007 | 1.00 | .139 | 10 |
| G60898-0016 | 16 FLANGE O-RING | 7254-0009 | 1 5/16 | .139 | 10 |
| G60898-0020 | 20 FLANGE O-RING | 7254-0011 | 1 1/2 | .139 | 10 |
| G60898-0024 | 24 FLANGE O-RING | 7254-0013 | 1 7/8 | .139 | 10 |
| G60898-0032 | 32 FLANGE O-RING | 7254-0015 | 2 1/4 | .139 | 10 |
| G60898-0040X | 40 FLANGE O-RING | 7254-0133 | 2 3/4 | .139 | 10 |
| G60898-0048 | 48 FLANGE O-RING | 7254-0134 | 3 3/8 | .139 | 10 |
| G60898-0056 | 56 FLANGE O-RING | 7254-0135 | 3 7/8 | .139 | 10 |
| G60898-0064X | 64 FLANGE O-RING | 7254-0136 | 4 3/8 | .139 | 10 |

# O-Rings for British Standard Parallel Pipe (BSPP Couplings)

70 Durometer Hardness.



| Part No. | Descr. | Prod. No. | Inside Diameter | Wall Thickness | Standard Pack |
|---|---|---|---|---|---|
| | | | mm | mm | |
| G64095-0004 | 4 O-RING FBSPP | 7254-1166 | 5.5 | 1.0 | 10 |
| G64095-0006 | 6 O-RING FBSPP | 7254-1154 | 7.1 | 1.6 | 10 |
| G64095-0008 | 8 O-RING FBSPP | 7254-1157 | 11.1 | 1.6 | 10 |
| G64095-0010 | 10 O-RING FBSPP | 7254-1159 | 12.1 | 1.6 | 10 |
| G64095-0012 | 12 O-RING FBSPP | 7254-1162 | 15.1 | 1.6 | 10 |
| G64095-0016 | 16 O-RING FBSPP | 7254-1164 | 20.1 | 1.6 | 10 |
| G64095-0020 | 20 O-RING FBSPP | 7254-1165 | 27.1 | 1.6 | 10 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# O-Rings for DIN Light & Heavy Series (MegaCrimp® and GlobalSpiral™ Couplings)

70 Durometer Hardness.



| Part No. | Descr. | Prod. No. | Inside Diameter mm | Wall Thickness mm | Standard Pack |
|---|---|---|---|---|---|
| G64780-0018 | 18 O-RING DIN L | 7254-0201 | 15.0 | 2.0 | 10 |
| G64780-0022 | 22 O-RING DIN L | 7254-0202 | 20.0 | 2.0 | 10 |
| G64780-0028 | 28 O-RING DIN L | 7254-0203 | 26.0 | 2.0 | 10 |
| G64780-0035 | 35 O-RING DIN L | 7254-0204 | 32.0 | 2.5 | 10 |
| G64780-0042 | 42 O-RING DIN L | 7254-0205 | 38.0 | 2.5 | 10 |
| G64781-0006 | 6 O-RING DIN H | 7254-0206 | 4.0 | 1.5 | 10 |
| G64781-0008 | 8 O-RING DIN H | 7254-0207 | 6.0 | 1.5 | 10 |
| G64781-0010 | 10 O-RING DIN H | 7254-0208 | 7.5 | 1.5 | 10 |
| G64781-0012 | 12 O-RING DIN H | 7254-0209 | 9.0 | 1.5 | 10 |
| G64781-0014 | 14 O-RING DIN H | 7254-1132 | 10.0 | 2.0 | 10 |
| G64781-0016 | 15/16 O-RING DIN L/H | 7254-0200 | 12.0 | 2.0 | 10 |
| G64781-0020 | 20 O-RING DIN H | 7254-0210 | 16.3 | 2.4 | 10 |
| G64781-0025 | 25 O-RING DIN H | 7254-0211 | 20.3 | 2.4 | 10 |
| G64781-0030 | 30 O-RING DIN H | 7254-0212 | 25.3 | 2.4 | 10 |
| G64781-0038 | 38 O-RING DIN H | 7254-0213 | 33.3 | 2.4 | 10 |


# O-Rings for DIN Heavy Series (MegaCrimp® and GlobalSpiral™ Couplings)

70 Durometer Hardness.




| Part No. | Descr. | Prod. No. | Inside Diameter mm | Wall Thickness mm | Standard Pack |
|---|---|---|---|---|---|
| G64782-0008 | 8 O-RING DIN H | 7254-0154 | 6.0 | 1.5 | 10 |
| G64782-0010 | 10 O-RING DIN H | 7254-0151 | 7.1 | 1.6 | 10 |
| G64782-0012 | 12 O-RING DIN H | 7254-0153 | 9.1 | 1.6 | 10 |
| G64782-0014 | 14 O-RING DIN H | 7254-0150 | 10.5 | 1.8 | 10 |
| G64782-0016 | 16 O-RING DIN H | 7254-0149 | 11.9 | 1.8 | 10 |
| G64782-0020 | 20 O-RING DIN H | 7254-0152 | 16.6 | 2.4 | 10 |
| G64782-0025 | 25 O-RING DIN H | 7254-0144 | 21.6 | 2.4 | 10 |
| G64782-0030 | 30 O-RING DIN H | 7254-0146 | 27.6 | 2.4 | 10 |
| G64782-0038 | 38 O-RING DIN H | 7254-0145 | 34.6 | 2.4 | 10 |

# Female Flareless Nut




| Part No. | Descr. | Prod. No. | A1 " | | H1 " | Standard Pack |
|---|---|---|---|---|---|---|
| G60050-0004 | 4FFN | 7334-40495 | 1/4 | 7/16–20 | 9/16 | 5 |
| G60050-0005 | 5FFN | 7334-40505 | 5/16 | 1/2–20 | 5/8 | 5 |
| G60050-0006 | 6FFN | 7334-40515 | 3/8 | 9/16–18 | 11/16 | 5 |
| G60050-0008 | 8FFN | 7334-40425 | 1/2 | 3/4–16 | 7/8 | 5 |
| G60050-0010 | 10FFN | 7334-40525 | 5/8 | 7/8–14 | 1 | 1 |
| G60050-0012 | 12FFN | 7334-40535 | 3/4 | 1 1/16–12 | 1 1/4 | 1 |
| G60050-0016 | 16FFN | 7334-40545 | 1 | 1 5/16–12 | 1 1/2 | 1 |


# Female Flareless Sleeve




| Part No. | Descr. | Prod. No. | A1 " | Standard Pack |
|---|---|---|---|---|
| G60051-0004 | 4FFS | 7334-40555 | 1/4 | 5 |
| G60051-0005 | 5FFS | 7334-40565 | 5/16 | 5 |
| G60051-0006 | 6FFS | 7334-40575 | 3/8 | 5 |
| G60051-0008 | 8FFS | 7334-40435 | 1/2 | 5 |
| G60051-0010 | 10FFS | 7334-40585 | 5/8 | 1 |
| G60051-0012 | 12FFS | 7334-40595 | 3/4 | 1 |
| G60051-0016 | 16FFS | 7334-40605 | 1 | 1 |

# Tube Sleeve

For use up to SAE 100R2 maximum working pressure.





| Part No. | Descr. | Prod. No. | A1 " | Standard Pack |
|---|---|---|---|---|
| G60394-0003 | 3TS | 7259-78275 | 3/16 | 5 |

## Tube Sleeve - Continued

| Part No. | Descr. | Prod. No. | A1 " | Standard Pack |
|---|---|---|---|---|
| G60394-0004 | 4TS | 7259-23905 | 1/4 | 5 |
| G60394-0005 | 5TS | 7259-23915 | 5/16 | 5 |
| G60394-0006 | 6TS | 7259-23925 | 3/8 | 5 |
| G60394-0008 | 8TS | 7259-23935 | 1/2 | 5 |
| G60394-0010 | 10TS | 7259-23945 | 5/8 | 1 |
| G60394-0012 | 12TS | 7259-23955 | 3/4 | 1 |
| G60394-0014 | 14TS | 7259-23965 | 7/8 | 1 |
| G60394-0016 | 16TS | 7259-23975 | 1 | 1 |
| G60394-0020 | 20TS | 7259-23985 | 1 1/4 | 1 |
| G60394-0024 | 24TS | 7259-23995 | 1 1/2 | 1 |
| G60394-0032 | 32TS | 7259-24005 | 2 | 1 |

## Tube Sleeve Nut

For use up to SAE 100R2 maximum working pressure.




| Part No. | Descr. | Prod. No. | A1 " | " | H1 " | Standard Pack |
|---|---|---|---|---|---|---|
| G60395-0002 | 2TSN | 7259-06805 | 1/8 | 5/16–24 | 3/8 | 1 |
| G60395-0003 | 3TSN | 7259-78295 | 3/16 | 3/8–24 | 1/4 | 1 |
| G60395-0004 | 4TSN | 7259-01105 | 1/4 | 7/16–20 | 9/16 | 1 |
| G60395-0005 | 5TSN | 7259-01115 | 5/16 | 1/2–20 | 5/8 | 1 |
| G60395-0006 | 6TSN | 7259-01125 | 3/8 | 9/16–18 | 11/16 | 1 |
| G60395-0006X | 6TSN XBULK | 7259-0112 | 3/8 | 9/16–18 | 11/16 | 950 |
| G60395-0008 | 8TSN | 7259-01135 | 1/2 | 3/4–16 | 7/8 | 1 |
| G60395-0010 | 10TSN | 7259-01145 | 5/8 | 7/8–14 | 1 | 1 |
| G60395-0012 | 12TSN | 7259-01155 | 3/4 | 1 1/16–12 | 1 1/4 | 1 |
| G60395-0014 | 14TSN | 7259-01165 | 7/8 | 1 3/16–12 | 1 3/8 | 1 |
| G60395-0016 | 16TSN | 7259-01175 | 1 | 1 5/16–12 | 1 1/2 | 1 |
| G60395-0020 | 20TSN | 7259-01185 | 1 1/4 | 1 5/8–12 | 2 | 1 |
| G60395-0032 | 32TSN | 7259-09055 | 2 | 2 1/2–12 | 2 7/8 | 1 |

# Locknuts for Bulkhead Fittings


For use up to SAE 100R2 maximum working pressure.




| Part No. | Descr. | Prod. No. | | H1 | Standard Pack |
|---|---|---|---|---|---|
| | | | " | " | |
| G60399-0004 | 4LN-SH | 7259-24605 | 7/16–20 | 11/16 | 5 |
| G60399-0005 | 5LN | 7253-24615 | 1/2–20 | 3/4 | 5 |
| G60399-0006 | 6LN-SH | 7259-24625 | 9/16–18 | 11/16 | 5 |
| G60399-0008 | 8LN-SH | 7259-24635 | 3/4–16 | 1 | 5 |
| G60399-0010 | 10LN-SH | 7259-24645 | 7/8–14 | 1 1/8 | 1 |
| G60399-0016 | 16LN-SH | 7259-24665 | 1 5/16–12 | 1 5/8 | 1 |

# SAE Tubing Sleeve Nut


For use up to SAE 100R2 maximum working pressure.



| Part No. | Descr. | Prod. No. | | | Standard Pack |
|---|---|---|---|---|---|
| | | | " | " | |
| ⚠ G60685-0004 | 4STSN | 7250-18195 | 1/4 | 7/16–20 | 1 |
| ⚠ G60685-0005 | 5STSN | 7250-18205 | 5/16 | 1/2–20 | 1 |
| ⚠ G60685-0006 | 6STSN | 7250-18215 | 3/8 | 5/8–18 | 1 |
| ⚠ G60685-0008 | 8STSN | 7250-18225 | 1/2 | 3/4–16 | 1 |
| ⚠ G60685-0010 | 10STSN | 7250-18235 | 5/8 | 7/8–14 | 1 |
| ⚠ G60685-0012 | 12STSN | 7250-18245 | 3/4 | 1 1/16–14 | 1 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Metric Bite Sleeve




| Part No. | Descr. | Prod. No. | A1 | Standard Pack |
|---|---|---|---|---|
| | | | mm | |
| G64787-0006 | 6BS | 7253-26815 | 6.0 | 5 |
| G64787-0008 | 8BS | 7253-26835 | 8.0 | 5 |


EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Metric Bite Sleeve - Continued

| Part No. | Descr. | Prod. No. | A1 mm | Standard Pack |
|---|---|---|---|---|
| G64787-0010 | 10BS | 7253-26855 | 10.0 | 1 |
| G64787-0012 | 12BS | 7253-26875 | 12.0 | 1 |
| G64787-0014 | 14BS | 7253-26895 | 14.0 | 1 |
| G64787-0015 | 15BS | 7253-26905 | 15.0 | 1 |
| G64787-0016 | 16BS | 7253-26915 | 16.0 | 1 |
| G64787-0018 | 18BS | 7253-26925 | 18.0 | 1 |
| G64787-0020 | 20BS | 7253-26935 | 20.0 | 1 |
| G64787-0022 | 22BS | 7253-26945 | 22.0 | 1 |
| G64787-0025 | 25BS | 7253-26955 | 25.0 | 1 |
| G64787-0028 | 28BS | 7253-26965 | 28.0 | 1 |
| G64787-0030 | 30BS | 7253-26975 | 30.0 | 1 |
| G64787-0035 | 35BS | 7253-26985 | 35.0 | 1 |
| G64787-0038 | 38BS | 7253-26995 | 38.0 | 1 |
| G64787-0042 | 42BS | 7253-27005 | 42.0 | 1 |

## Metric Bite Nut




| Part No. | Descr. | Prod. No. | " | A1 mm | Standard Pack |
|---|---|---|---|---|---|
| G64788-0006 | 6MNL | 7253-27105 | M12X1.5 | 6.0 | 5 |
| G64788-06LL | 6MNLL | 7314-06455 | M10X1.5 | 6.0 | 1 |
| G64788-0008 | 8MNL | 7253-27125 | M14X1.5 | 8.0 | 5 |
| G64788-0010 | 10MNL | 7253-27145 | M16X1.5 | 10.0 | 1 |
| G64788-0012 | 12MNL | 7253-27165 | M18X1.5 | 12.0 | 1 |
| G64788-0015 | 15MNL | 7253-27185 | M22X1.5 | 15.0 | 1 |
| G64788-0018 | 18MNL | 7253-27215 | M26X1.5 | 18.0 | 1 |
| G64788-0022 | 22MNL | 7253-27235 | M30X2.0 | 22.0 | 1 |
| G64788-0028 | 28MNL | 7253-27255 | M36X2.0 | 28.0 | 1 |
| G64788-0035 | 35MNL | 7253-27275 | M45X2.0 | 35.0 | 1 |
| G64788-0042 | 42MNL | 7253-27295 | M52X2.0 | 42.0 | 1 |
| G64789-0006 | 6MNH | 7253-27115 | M14X1.5 | 6.0 | 5 |
| G64789-0008 | 8MNH | 7253-27135 | M16X1.5 | 8.0 | 5 |
| G64789-0010 | 10MNH | 7253-27155 | M18X1.5 | 10.0 | 1 |
| G64789-0012 | 12MNH | 7253-27175 | M20X1.5 | 12.0 | 1 |
| G64789-0014 | 14MNH | 7253-27195 | M22X1.5 | 14.0 | 1 |
| G64789-0016 | 16MNH | 7253-27205 | M24X1.5 | 16.0 | 1 |
| G64789-0020 | 20MNH | 7253-27225 | M30X2.0 | 20.0 | 1 |
| G64789-0025 | 25MNH | 7253-27245 | M36X2.0 | 25.0 | 1 |
| G64789-0030 | 30MNH | 7253-27265 | M42X2.0 | 30.0 | 1 |
| G64789-0038 | 38MNH | 7253-27285 | M52X2.0 | 38.0 | 1 |

# Diagnostic Equipment

| Part No. | Descr. | Prod. No. | Standard Pack |
|---|---|---|---|
| | RFID BAND TAG - ORANGE | 7485-2110 | 400 |
| | RFID KEY TAG - ORANGE | 7485-2120 | 70 |
| | RFID LANYARD TAG 12 IN ORANGE | 7485-2130 | 70 |
| | RFID LANYARD TAG 24 IN ORANGE | 7485-2140 | 200 |
| | RFID LANYARD TAG 36 IN ORANGE | 7485-2150 | 70 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Gates GC®16XD™ Parts

| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| 78775 | 7482-7301 | GC16XD Handle Assembly | 1 |
| 78778 | 7482-7302 | GC16XD Foam Filler | 1 |
| 78779 | 7482-7303 | GC16XD Die Tub | 1 |
| 78759 | 7482-7304 | QC Tool (QCT) GC16–XD | 1 |
| 78781 | 7482-7305 | GC16XD End Caps | 1 |
| 78782 | 7482-7306 | GC16XD Stand Off Assembly (Long Version) | 1 |
| 78795 | 7482-7307 | GC16XD Die Retainer Sets | 1 |
| 78796 | 7482-7308 | GC16XD Dial Vernier Assembly | 1 |
| 78797 | 7482-7309 | GC16XD Bracket Assembly | 1 |
| 78733 | 7482-7313 | GC16XD Start Up Kit | 1 |

# MobileCrimp® 4-20 Positive Stop Spacers

| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| 78481 | 7482-1102 | B1 Spacer, PS | 1 |
| 78482 | 7482-1103 | W1 Spacer, PS | 1 |
| 78483 | 7482-1104 | R1 Spacer, PS | 1 |
| 78484 | 7482-1105 | B2 Spacer, PS | 1 |
| 78485 | 7482-1106 | W2 Spacer, PS | 1 |
| 78486 | 7482-1107 | R2 Spacer, PS | 1 |
| 78487 | 7482-1108 | B3 Spacer, PS | 1 |
| 78488 | 7482-1109 | W3 Spacer, PS | 1 |
| 78489 | 7482-1110 | R3 Spacer, PS | 1 |
| 78490 | 7482-1111 | B4 Spacer, PS | 1 |
| 78491 | 7482-1112 | W4 Spacer, PS | 1 |
| 78492 | 7482-1113 | R4 Spacer, PS | 1 |
| 78493 | 7482-1114 | B5 Spacer, PS | 1 |
| 78494 | 7482-1115 | W5 Spacer, PS | 1 |
| 78495 | 7482-1116 | R5 Spacer, PS | 1 |

# MobileCrimp® 4-20 Parts



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| 78450 | 7482-1000 | Magnet for Handling Die Sets | 1 |
| 78455 | 7482-1005 | Stand | 1 |
| 78456 | 7482-1006 | Pivot Spacer | 1 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## MobileCrimp® 4-20 Parts - Continued

| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| 78459 | 7482-1009 | Stand Clamp | 1 |
| 78462 | 7482-1012 | Pivot Knob | 1 |
| 78463 | 7482-1013 | Positive Stop Pressure Plate | 1 |
| 78465 | 7482-1015 | DD Computer Pressure Plate | 1 |
| 78467 | 7482-1017 | Hose Assembly | 125 |
| 78437 | 7482-1036 | Pusher | 1 |
| 78438 | 7482-1037 | Cover Plate | 1 |
| 78440 | 7482-1041 | Seal Kit Includes: Seal, Washer and Backup Ring | 1 |
| 78046 | 7482-1078 | DD Pressure Plate for 20G/MC38 | 1 |
| 78445 | 7482-1098 | Computer Cable | 1 |
| 78447 | 7482-1100 | Digital Dial Assy. Kit (To Upgrade PS) | 1 |
| 78449 | 7482-1117 | Ball Plunger for Top of Cylinder | 1 |
| 78427 | 7482-1147 | Die Spring | 1 |
| 78426 | 7482-1148 | Die Link | 1 |
| 78428 | 7482-1149 | Shoulder Screws | 1 |
| 78419 | 7482-1157 | Slydring for Piston | 1 |
| 78420 | 7482-1163 | Tall Handle for DD | 1 |
| 78421 | 7482-1164 | Locking Pin | 1 |
| 78422 | 7482-1165 | Chain for Locking Pin | 1 |
| 78424 | 7482-1168 | Cable Assy. for DD | 1 |
| 78396 | 7482-1170 | DD Top Mt Contrl Kit (side to top mount) | 1 |
| 78397 | 7482-1171 | DD Controller Top Mount | 1 |
| 78425 | 7482-1190 | Retaining Ring for Piston | 1 |

## Power Crimp® 707 Parts



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| 78251 | 7480-6591 | PC703 to PC707 Conversion Kit | 1 |
| 78717 | 7482-0054 | Crimp Switch Button for PC603/PC707 | 1 |
| 78718 | 7482-0105 | Piston New Design (Seals Included) | 1 |
| 78719 | 7482-0106 | Piston Rod | 1 |
| 78722 | 7482-0109 | Piston Rod Guide | 1 |
| 78723 | 7482-0110 | Base Plate (Machine) | 1 |
| 78724 | 7482-0111 | Tie Rod | 1 |
| 78725 | 7482-0112 | Pusher Cup (update design) | 1 |
| 78728 | 7482-0116 | Cylinder and Top Plate | 1 |
| 78729 | 7482-0118 | Spring Anchor | 1 |
| 78730 | 7482-0119 | Mounting Bracket | 1 |
| 78732 | 7482-0147 | O–Ring Between Piston and Rod | 1 |
| 78734 | 7482-0229 | Actuator Rod | 1 |

## Power Crimp® 707 Parts - Continued

| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| 78736 | 7482-0239 | Die Cone With Notch | 1 |
| 78737 | 7482-0243 | Tie Rod Nut | 1 |
| 78739 | 7482-0277 | Switch Box Complete w/115V Cord Assy. | 1 |
| 78740 | 7482-0280 | Digital Readout Meter | 1 |
| 78742 | 7482-0283 | PC707 Shroud Only | 1 |
| 78745 | 7482-0289 | PC707 Hose Assy. (Pump to Crimper) | 115 |
| 78746 | 7482-0291 | Magnet for Removing Dies | 1 |
| 78747 | 7482-0297 | Die Cone (No Notch) | 1 |
| 78252 | 7482-0442 | Microswitch | 1 |
| 78748 | 7482-0498 | 230V Cord Assy. for Digital Readout | 1 |
| 78760 | 7482-0499 | PC707 230V Converter Kit | 1 |
| 78754 | 7482-0747 | 115V Cord Assy for Digital Readout | 1 |
| 78478 | 7482-0789 | Die Cage Halves (Set of 2) for 700 Series | 1 |
| 78758 | 7482-0919 | Stainless Steel Washer | 1 |
| 78940 | 7482-0940 | Die Cage Halves for 739 | 1 |
| 78757 | 7482-1095 | PC707 Seal Kit for New Aluminum Piston Serial Nos. 14,000 and Up | 1 |
| 78750 | 7482-1215 | Silver Die Back Up Ring | 1 |
| 78761 | 7482-1422 | LifeGuard Plate | 1 |
| 78762 | 7482-1423 | LifeGuard Plate and Die Kit | 1 |
| 78749 | 7482-1672 | Screw for Die Fingers | 1 |
| 78755 | 7482-3011 | Molykote 3 oz. Jar G Die Lubricant | 1 |
| 78751 | 7482-6959 | Piston Return Spring for PC707/3000B | 1 |

## GC®32 Parts



| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| 78832 | 7482-7100 | Head Replacement Kit | 1 |
| 78833 | 7482-7101 | Panel Replacement Kit | 1 |
| 78834 | 7482-7102 | Valve Block Adapters | 1 |
| 78835 | 7482-7103 | Pilot Operated Check | 1 |
| 78836 | 7482-7104 | Quick Change Tool | 1 |
| 78837 | 7482-7105 | Dial Vernier | 1 |
| 78840 | 7482-7108 | Depth Stop | 1 |
| 78841 | 7482-7109 | Mirror | 1 |
| 78843 | 7482-7111 | Foot Pedal | 1 |
| 78847 | 7482-7115 | Control Panel Post | 1 |
| 78848 | 7482-7116 | Kicker Tubing (Upper) | 1 |
| 78849 | 7482-7117 | Kicker Tubing (Lower) | 1 |
| 78851 | 7482-7119 | Foam Fillers GC32–XD Set of 8 | 8 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## GC®32 Parts - Continued

| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| 78856 | 7482-7124 | Die Tubs | 1 |
| 78858 | 7482-7126 | Head Seal | 1 |
| 78907 | 7482-7175 | Breather Cap | 1 |
| 78909 | 7482-7179 | Kicker | 1 |
| 78910 | 7482-7180 | 2 Position 3–Way Solenoid | 1 |
| 78918 | 7482-7188 | Dial Vernier Locking Plate | 1 |
| 78924 | 7482-7193 | Relief Valve | 1 |
| 78925 | 7482-7194 | Back Press. Cont. Cartridge | 1 |
| 78927 | 7482-7196 | Oil Filter Element | 1 |
| 74827208 | 7482-7208 | Control Box CSA | 1 |
| 74827227 | 7482-7227 | Surge Protector w/Hubbell Plug | 144 |
| 79006 | 7482-7246 | QTC Repair Kit GC32/96 series up to 2" | 1 |
| 78047 | 7482-7247 | GC96TS, TSi, GC32TSi Power Supply | 4 |
| 78048 | 7482-7248 | GC96 GC32XD Transformer | 4 |
| 74827267 | 7482-7267 | GC32 Inverter | 1 |
| 78002 | 7482-7268 | Die Retention Plate Kit | 1 |

## Gates GC®96 Parts

| Part No. | Prod. No. | Descr. | Standard Pack |
|---|---|---|---|
| 74829100 | 7482-9100 | GC96TS Control Box with Potentiometer | 1 |
| 74829181 | 7482-9181 | GC96TS Die Release Tool | 1 |

Stop searching and start saving with these great hydraulic assortments. For once, all your hydraulic components will be in one place. And they are organized by size and style.

# O-Ring (OR, FLOR, ORFF) Assortment Kit

**Part Number:** 85001
**Product Number:** 7369-0001




| O-Rings for Straight-Thread Boss Fittings | | |
|---|---|---|
| Descr. | Part No. | Quantity |
| 4 O-RING | G60248-0004 | 10 |
| 6 O-RING | G60248-0006 | 10 |
| 8 O-RING | G60248-0008 | 10 |
| 10 O-RING | G60248-0010 | 10 |
| 12 O-RING | G60248-0012 | 10 |
| 16 O-RING | G60248-0016 | 10 |
| 20 O-RING | G60248-0020 | 10 |

| O-Rings for Code 61 & 62 Flange Fittings | | |
|---|---|---|
| Descr. | Part No. | Quantity |
| 12 FLANGE O-RING | G60898-0012 | 10 |
| 16 FLANGE O-RING | G60898-0016 | 10 |
| 20 FLANGE O-RING | G60898-0020 | 10 |

| O-Rings for Flat-Face Fittings | | |
|---|---|---|
| Descr. | Part No. | Quantity |
| 4 O-RING FF | G60698-0004 | 10 |
| 6 O-RING FF | G60698-0006 | 10 |
| 8 O-RING FF | G60698-0008 | 10 |
| 10 O-RING FF | G60698-0010 | 10 |
| 12 O-RING FF | G60698-0012 | 10 |
| 14 O-RING FF | G60698-0016 | 10 |

# Flat-Face Plug (MFFOR) and Cap (FFOR) Kit

**Part Number:** 85002
**Product Number:** 7369-0002




| Flat-Face O-Ring Caps | | |
|---|---|---|
| Descr. | Part No. | Quantity |
| 4FFOR-CAP | G60701-0004 | 2 |
| 6FFOR-CAP | G60701-0006 | 2 |
| 8FFOR-CAP | G60701-0008 | 2 |
| 10FFOR-CAP | G60701-0010 | 2 |
| 12FFOR-CAP | G60701-0012 | 2 |
| 16FFOR-CAP | G60701-0016 | 2 |

| Flat-Face O-Ring Plugs | | |
|---|---|---|
| Descr. | Part No. | Quantity |
| 4MFFOR-PLUG | G60702-0004 | 2 |
| 6MFFOR-PLUG | G60702-0006 | 2 |
| 8MFFOR-PLUG | G60702-0008 | 2 |
| 10MFFOR-PLUG | G60702-0010 | 2 |
| 12MFFOR-PLUG | G60702-0012 | 2 |
| 16MFFOR-PLUG | G60702-0016 | 2 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# JIC Plug (MJ) and Cap (FJ) Kit

**Part Number:** 85003
**Product Number:** 7369-0003




| Male 37° Flare (JIC) Plug | | |
|---|---|---|
| Descr. | Part No. | Quantity |
| 4MJ-PLUG | G60402-0004 | 2 |
| 5MJ-PLUG | G60402-0005 | 2 |
| 6MJ-PLUG | G60402-0006 | 2 |
| 8MJ-PLUG | G60402-0008 | 2 |
| 10MJ-PLUG | G60402-0010 | 2 |
| 12MJ-PLUG | G60402-0012 | 2 |
| 14MJ-PLUG | G60402-0014 | 2 |
| 16MJ-PLUG | G60402-0016 | 2 |
| 20MJ-PLUG | G60402-0020 | 2 |

| Female 37° Flare (JIC) Cap | | |
|---|---|---|
| Descr. | Part No. | Quantity |
| 4FJ-CAP | G60401-0004 | 2 |
| 5FJ-CAP | G60401-0005 | 2 |
| 6FJ-CAP | G60401-0006 | 2 |
| 8FJ-CAP | G60401-0008 | 2 |
| 10FJ-CAP | G60401-0010 | 2 |
| 12FJ-CAP | G60401-0012 | 2 |
| 16FJ-CAP | G60401-0016 | 2 |
| 20FJ-CAP | G60401-0020 | 2 |

# Male Pipe (MP) and O-Ring Boss (MB) Plug Kit

**Part Number:** 85004
**Product Number:** 7369-0004




*Space for plugs,
but not included in kit.

| Male Pipe Plug | | |
|---|---|---|
| Descr. | Part No. | Quantity |
| 2MP-PLUG | G60102-0002 | 2 |
| 4MP-PLUG | G60102-0004 | 2 |
| 6MP-PLUG | G60102-0006 | 2 |
| 8MP-PLUG | G60102-0008 | 2 |
| 12MP-PLUG | G60102-0012 | 2 |
| 16MP-PLUG | G60102-0016 | 2 |
| 20MP-PLUG | G60102-0020 | 2 |
| 24MP-PLUG | G60102-0024 | Optional* |

| Male O-Ring Boss Plug | | |
|---|---|---|
| Descr. | Part No. | Quantity |
| 4MB-PLUG | G60250-0004 | 2 |
| 5MB-PLUG | G60250-0005 | 2 |
| 6MB-PLUG | G60250-0006 | 2 |
| 8MB-PLUG | G60250-0008 | 2 |
| 10MB-PLUG | G60250-0010 | 2 |
| 12MB-PLUG | G60250-0012 | 2 |
| 16MB-PLUG | G60250-0016 | 1 |

# Rubber Air Brake & C14 Assembly Assortments

**Assortment Part Number:** 91181, **Assortment Product Number:** 7626-0105

| Part No. | Descr. | Length | Unit Count |
|---|---|---|---|
| G89170-1036 | 10C14-10FJSX-10FJSX-36 | 36” | 1 |
| G89170-1048 | 10C14-10FJSX-10FJSX-48 | 48” | 1 |
| G89170-1054 | 10C14-10FJSX-10FJSX-54 | 54” | 1 |
| G89170-1084 | 10C14-10FJSX-10FJSX-84 | 84” | 1 |
| 27245 | 3/8” Hose, 6AB-4MP-6MPA-20 | 20” | 1 |
| 27246 | 3/8” Hose, 6AB-4MP-6MPA-24 | 24” | 1 |
| 27248 | 3/8” Hose, 6AB-4MP-6MPA-30 | 30” | 1 |
| 27252 | 1/2” Hose, 8AB-6MP-6MPA-18 | 18” | 1 |
| 27253 | 1/2” Hose, 8AB-6MP-6MPA-20 | 20” | 1 |
| 27254 | 1/2” Hose, 8AB-6MP-6MPA-24 | 24” | 2 |
| 27255 | 1/2” Hose, 8AB-6MP-6MPA-28 | 28” | 2 |
| 27256 | 1/2” Hose, 8AB-6MP-6MPA-30 | 30” | 2 |
| 27257 | 1/2” Hose, 8AB-6MP-6MPA-32 | 32” | 1 |
| 27258 | 1/2” Hose, 8AB-6MP-6MPA-36 | 36” | 2 |
| 27259 | 1/2” Hose, 8AB-6MP-6MPA-42 | 42” | 2 |
| 27266 | 3/8” Hose, 6AB-6MP-6MPA-24 | 24” | 2 |
| 27267 | 3/8” Hose, 6AB-6MP-6MPA-26 | 26” | 1 |
| 27268 | 3/8” Hose, 6AB-6MP-6MPA-28 | 28” | 2 |
| 27269 | 3/8” Hose, 6AB-6MP-6MPA-30 | 30” | 1 |
| 27270 | 3/8” Hose, 6AB-6MP-6MPA-32 | 32” | 1 |
| 27272 | 3/8” Hose, 6AB-6MP-6MPA-36 | 36” | 1 |
| 27275 | 3/8” Hose, 6AB-6MP-6MPA-42 | 42” | 1 |
| 27279 | 3/8” Hose, 6AB-6MP-6MPA-48 | 48” | 1 |
| 27281 | 3/8” Hose, 6AB-6MP-6MPA-60 | 60” | 1 |
| 91180 | Air Brake Hose Rack | — | 2 |
| — | Content Sheet | — | 1 |
| — | Part No. Decals | — | 24 |




**Assortment Part Number:** 91182, **Assortment Product Number:** 7626-0104

| Part No. | Descr. | Length | Unit Count |
|---|---|---|---|
| G89170-1048 | 10C14-10FJSX-10FJSX-48 | 48” | 1 |
| G89170-1054 | 10C14-10FJSX-10FJSX-54 | 54” | 1 |
| 27246 | 3/8” Hose, 6AB-4MP-6MPA-24 | 24” | 1 |
| 27254 | 1/2” Hose, 8AB-6MP-6MPA-24 | 24” | 2 |
| 27255 | 1/2” Hose, 8AB-6MP-6MPA-28 | 28” | 1 |
| 27256 | 1/2” Hose, 8AB-6MP-6MPA-30 | 30” | 2 |
| 27258 | 1/2” Hose, 8AB-6MP-6MPA-36 | 36” | 2 |
| 27259 | 1/2” Hose, 8AB-6MP-6MPA-42 | 42” | 1 |
| 27266 | 3/8” Hose, 6AB-6MP-6MPA-24 | 24” | 2 |
| 27268 | 3/8” Hose, 6AB-6MP-6MPA-28 | 28” | 1 |
| 27269 | 3/8” Hose, 6AB-6MP-6MPA-30 | 30” | 1 |
| 27272 | 3/8” Hose, 6AB-6MP-6MPA-36 | 36” | 1 |
| 91180 | Air Brake Hose Rack | — | 1 |
| — | Content Sheet | — | 1 |
| — | Part No. Decals | — | 12 |

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS




# Bonded Seals

**Part Number:** 85041
**Product Number:** 7369-5041

| Descr. | Part No. | Quantity |
|---|---|---|
| 2BBDS | G64075-0002 | Optional* |
| 4BBDS | G64075-0004 | 10 |
| 6BBDS | G64075-0006 | 10 |
| 8BBDS | G64075-0008 | 10 |
| 10BBDS | G64075-0010 | 10 |
| 12BBDS | G64075-0012 | 10 |
| 16BBDS | G64075-0016 | 10 |
| 20BBDS | G64075-0020 | Optional* |
| 24BBDS | G64075-0024 | Optional* |
| 32BBDS | G64075-0032 | Optional* |
| 6MBDS | G64775-0006 | 10 |
| 8MBDS | G64775-0008 | 10 |
| 10MBDS | G64775-0010 | 10 |
| 12MBDS | G64775-0012 | 10 |
| 14MBDS | G64775-0014 | 10 |
| 16MBDS | G64775-0016 | 10 |
| 18MBDS | G64775-0018 | 10 |
| 20MBDS | G64775-0020 | 10 |
| 22MBDS | G64775-0022 | 10 |
| 24MBDS | G64775-0024 | Optional* |
| 26MBDS | G64775-0026 | Optional* |
| 27MBDS | G64775-0027 | Optional* |
| 30MBDS | G64775-0030 | Optional* |
| 33MBDS | G64775-0033 | Optional* |
| 36MBDS | G64775-0036 | Optional* |
| 42MBDS | G64775-0042 | Optional* |

*Space for bonded seals, but not included in kit.




# British

**Part Number:** 85042
**Product Number:** 7369-5042

| Descr. | Part No. | Quantity |
|---|---|---|
| 2MBSPOR-PLUG | G64094-0002 | 2 |
| 4MBSPOR-PLUG | G64094-0004 | 2 |
| 6MBSPOR-PLUG | G64094-0006 | 2 |
| 8MBSPOR-PLUG | G64094-0008 | 2 |
| 12MBSPOR-PLUG | G64094-0012 | Optional* |
| 16MBSPOR-PLUG | G64094-0016 | Optional* |
| 20MBSPOR-PLUG | G64094-0020 | Optional* |
| 2MBSPP-PLUG | G64099-0002 | 2 |
| 4MBSPP-PLUG | G64099-0004 | 2 |
| 6MBSPP-PLUG | G64099-0006 | 2 |
| 8MBSPP-PLUG | G64099-0008 | 2 |
| 10MBSPP-PLUG | G64099-0010 | 2 |
| 12MBSPP-PLUG | G64099-0012 | 2 |
| 16MBSPP-PLUG | G64099-0016 | Optional* |
| 20MBSPP-PLUG | G64099-0020 | Optional* |
| 24MBSPP-PLUG | G64099-0024 | Optional* |
| 32MBSPP-PLUG | G64099-0032 | Optional* |
| 2MBSPT-PLUG | G64098-0002 | 2 |
| 4MBSPT-PLUG | G64098-0004 | 2 |
| 6MBSPT-PLUG | G64098-0006 | 2 |
| 8MBSPT-PLUG | G64098-0008 | 2 |
| 10MBSPT-PLUG | G64098-0010 | 2 |
| 12MBSPT-PLUG | G64098-0012 | 2 |
| 16MBSPT-PLUG | G64098-0016 | Optional* |
| 20MBSPT-PLUG | G64098-0020 | Optional* |
| 24MBSPT-PLUG | G64098-0024 | Optional* |
| 32MBSPT-PLUG | G64098-0032 | Optional* |
| 2FBSPP-CAP | G64097-0002 | 2 |
| 4FBSPP-CAP | G64097-0004 | 2 |
| 6FBSPP-CAP | G64097-0006 | 2 |
| 8FBSPP-CAP | G64097-0008 | 2 |
| 10FBSPP-CAP | G64097-0010 | 2 |
| 12FBSPP-CAP | G64097-0012 | 2 |
| 16FBSPP-CAP | G64097-0016 | Optional* |
| 20FBSPP-CAP | G64097-0020 | Optional* |
| 24FBSPP-CAP | G64097-0024 | Optional* |
| 32FBSPP-CAP | G64097-0032 | Optional* |

*Space for plugs and caps, but not included in kit.




## DIN Light

**Part Number:** 85043
**Product Number:** 7369-5043

| Descr. | Part No. | Quantity |
|---|---|---|
| 6MDL-PLUG | G64792-0006 | 2 |
| 8MDL-PLUG | G64792-0008 | 2 |
| 10MDL-PLUG | G64792-0010 | 2 |
| 12MDL-PLUG | G64792-0012 | 2 |
| 15MDL-PLUG | G64792-0015 | 2 |
| 18MDL-PLUG | G64792-0018 | 2 |
| 22MDL-PLUG | G64792-0022 | 2 |
| 28MDL-PLUG | G64792-0028 | Optional* |
| 35MDL-PLUG | G64792-0035 | Optional* |
| 42MDL-PLUG | G64792-0042 | Optional* |
| 6FDL-CAP | G64793-0006 | 2 |
| 8FDL-CAP | G64793-0008 | 2 |
| 10FDL-CAP | G64793-0010 | 2 |
| 12FDL-CAP | G64793-0012 | 2 |
| 15FDL-CAP | G64793-0015 | 2 |
| 18FDL-CAP | G64793-0018 | 2 |
| 22FDL-CAP | G64793-0022 | 2 |
| 28FDL-CAP | G64793-0028 | Optional* |
| 35FDL-CAP | G64793-0035 | Optional* |
| 42FDL-CAP | G64793-0042 | Optional* |

*Space for plugs and caps, but not included in kit.




## DIN Heavy

**Part Number:** 85044
**Product Number:** 7369-5044

| Descr. | Part No. | Quantity |
|---|---|---|
| 8MDH-PLUG | G64794-0008 | 2 |
| 10MDH-PLUG | G64794-0010 | 2 |
| 12MDH-PLUG | G64794-0012 | 2 |
| 14MDH-PLUG | G64794-0014 | 2 |
| 16MDH-PLUG | G64794-0016 | 2 |
| 20MDH-PLUG | G64794-0020 | 2 |
| 25MDH-PLUG | G64794-0025 | 2 |
| 30MDH-PLUG | G64794-0030 | Optional* |
| 38MDH-PLUG | G64794-0038 | Optional* |
| 8FDH-CAP | G64795-0008 | 2 |
| 10FDH-CAP | G64795-0010 | 2 |
| 12FDH-CAP | G64795-0012 | 2 |
| 14FDH-CAP | G64795-0014 | 2 |
| 16FDH-CAP | G64795-0016 | 2 |
| 20FDH-CAP | G64795-0020 | 2 |
| 25FDH-CAP | G64795-0025 | 2 |
| 30FDH-CAP | G64795-0030 | Optional* |
| 38FDH-CAP | G64795-0038 | Optional* |

*Space for plugs and caps, but not included in kit.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS







## Metric

**Part Number:** 85045
**Product Number:** 7369-5045

| Descr. | Part No. | Quantity |
|---|---|---|
| 8MM-PLUG | G64790-0008 | 2 |
| 10MM-PLUG | G64790-0010 | 2 |
| 12MM-PLUG | G64790-0012 | 2 |
| 14MM-PLUG | G64790-0014 | 2 |
| 16MM-PLUG | G64790-0016 | 2 |
| 18MM-PLUG | G64790-0018 | 2 |
| 20MM-PLUG | G64790-0020 | 2 |
| 22MM-PLUG | G64790-0022 | 2 |
| 24MM-PLUG | G64790-0024 | 2 |
| 26MM-PLUG | G64790-0026 | 2 |
| 30MM-PLUG | G64790-0030 | 2 |
| 22MKB-PLUG | G63980-0022 | 2 |

## Japanese

**Part Number:** 85046
**Product Number:** 7369-5046

| Descr. | Part No. | Quantity |
|---|---|---|
| 4FK-CAP | G65597-0004 | 2 |
| 6FK-CAP | G65597-0006 | 2 |
| 8FK-CAP | G65597-0008 | 2 |
| 10FK-CAP | G65597-0010 | 2 |
| 12FK-CAP | G65597-0012 | 2 |
| 16FK-CAP | G65597-0016 | Optional* |
| 4MK-PLUG | G65599-0004 | 2 |
| 6MK-PLUG | G65599-0006 | 2 |
| 8MK-PLUG | G65599-0008 | 2 |
| 10MK-PLUG | G65599-0010 | 2 |
| 12MK-PLUG | G65599-0012 | 2 |
| 16MK-PLUG | G65599-0016 | Optional* |
| 4FJIS-CAP | G65097-0004 | 2 |
| 6FJIS-CAP | G65097-0006 | 2 |
| 8FJIS-CAP | G65097-0008 | 2 |
| 12FJIS-CAP | G65097-0012 | 2 |
| 16FJIS-CAP | G65097-0016 | 2 |
| 20FJIS-CAP | G65097-0020 | Optional* |
| 24FJIS-CAP | G65097-0024 | Optional* |
| 32FJIS-CAP | G65097-0032 | Optional* |
| 4MJIS-PLUG | G65099-0004 | 2 |
| 6MJIS-PLUG | G65099-0006 | 2 |
| 8MJIS-PLUG | G65099-0008 | 2 |
| 12MJIS-PLUG | G65099-0012 | 2 |
| 16MJIS-PLUG | G65099-0016 | 2 |
| 20MJIS-PLUG | G65099-0020 | Optional* |
| 24MJIS-PLUG | G65099-0024 | Optional* |
| 32MJIS-PLUG | G65099-0032 | Optional* |

*Space for plugs and caps, but not included in kit.

## 1/2" ID Hose with 1/2" Female SAE Swivel at Both Ends



| Part No. | Descr. | Prod. No. | Length | |
|---|---|---|---|---|
| | | | " | mm |
| ⚠ 27693 | 8AB-8FSX-8FSX-18 | 7745-9146 | 18 | 457.0 |
| ⚠ 27695 | 8AB-8FSX-8FSX-24 | 7745-9138 | 24 | 610.0 |
| ⚠ 27696 | 8AB-8FSX-8FSX-30 | 7745-9139 | 30 | 762.0 |
| ⚠ 27697 | 8AB-8FSX-8FSX-36 | 7745-9140 | 36 | 914.4 |
| ⚠ 27698 | 8AB-8FSX-8FSX-42 | 7745-9141 | 42 | 1067.0 |
| ⚠ 27699 | 8AB-8FSX-8FSX-48 | 7745-9142 | 48 | 1219.0 |
| ⚠ 27701 | 8AB-8FSX-8FSX-60 | 7745-9144 | 60 | 1524.0 |
| ⚠ 27700 | AB-8FSX-8FSX-54 | 7745-9143 | 54 | 1372.0 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## 1/2" ID Hose with 3/8" Male Pipe NPTF Swivel at Both Ends



| Part No. | Descr. | Prod. No. | Length | |
|---|---|---|---|---|
| | | | " | mm |
| ⚠ 27602 | 8AB-6MPX-6MPX-08 | 7745-9083 | 8 | 203.0 |
| ⚠ 27603 | 8AB-6MPX-6MPX-12 | 7745-9084 | 12 | 305.0 |
| ⚠ 27605 | 8AB-6MPX-6MPX-16 | 7745-9085 | 16 | 406.0 |
| ⚠ 27607 | 8AB-6MPX-6MPX-20 | 7745-9086 | 20 | 508.0 |
| ⚠ 27609 | 8AB-6MPX-6MPX-24 | 7745-9087 | 24 | 610.0 |
| ⚠ 27611 | 8AB-6MPX-6MPX-28 | 7745-9088 | 28 | 711.0 |
| ⚠ 27613 | 8AB-6MPX-6MPX-32 | 7745-9089 | 32 | 813.0 |
| ⚠ 27615 | 8AB-6MPX-6MPX-36 | 7745-9090 | 36 | 914.4 |
| ⚠ 27618 | 8AB-6MPX-6MPX-42 | 7745-9091 | 42 | 1067.0 |
| ⚠ 27621 | 8AB-6MPX-6MPX-48 | 7749-9092 | 48 | 1219.0 |
| ⚠ 27624 | 8AB-6MPX-6MPX-54 | 7745-9093 | 54 | 1372.0 |
| ⚠ 27626 | 8AB-6MPX-6MPX-60 | 7745-9094 | 60 | 1524.0 |
| ⚠ 27627 | 8AB-6MPX-6MPX-66 | 7745-9095 | 66 | 1676.0 |
| ⚠ 27628 | 8AB-6MPX-6MPX-72 | 7745-9096 | 72 | 1829.0 |
| ⚠ 27629 | 8AB-6MPX-6MPX-84 | 7745-9097 | 84 | 2134.0 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## 3/8" ID Hose with 1/4" Male Pipe NPTF Swivel at Both Ends



| Part No. | Descr. | Prod. No. | Length | |
|---|---|---|---|---|
| | | | " | mm |
| ⚠ 27658 | 6AB-4MPX-4MPX-08 | 7745-9114 | 8 | 203.0 |
| ⚠ 27659 | 6AB-4MPX-4MPX-12 | 7745-9115 | 12 | 305.0 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## 3/8" ID Hose with 1/4" Male Pipe NPTF Swivel at Both Ends - Continued

| Part No. | Descr. | Prod. No. | Length | |
|---|---|---|---|---|
| | | | " | mm |
| ⚠ 27661 | 6AB-4MPX-4MPX-16 | 7745-9116 | 16 | 406.0 |
| ⚠ 27663 | 6AB-4MPX-4MPX-20 | 7745-9117 | 20 | 508.0 |
| ⚠ 27665 | 6AB-4MPX-4MPX-24 | 7745-9118 | 24 | 610.0 |
| ⚠ 27667 | 6AB-4MPX-4MPX-28 | 7745-9119 | 28 | 711.0 |
| ⚠ 27669 | 6AB-4MPX-4MPX-32 | 7745-9120 | 32 | 813.0 |
| ⚠ 27671 | 6AB-4MPX-4MPX-36 | 7745-9121 | 36 | 914.4 |
| ⚠ 27674 | 6AB-4MPX-4MPX-42 | 7745-9122 | 42 | 1067.0 |
| ⚠ 27677 | 6AB-4MPX-4MPX-48 | 7745-9123 | 48 | 1219.0 |
| ⚠ 27679 | 6AB-4MPX-4MPX-52 | 7745-9124 | 52 | 1321.0 |
| ⚠ 27681 | 6AB-4MPX-4MPX-60 | 7745-9125 | 60 | 1524.0 |
| ⚠ 27682 | 6AB-4MPX-4MPX-66 | 7745-9126 | 66 | 1676.0 |
| ⚠ 27683 | 6AB-4MPX-4MPX-72 | 7745-9127 | 72 | 1829.0 |
| ⚠ 27684 | 6AB-4MPX-4MPX-84 | 7745-9128 | 84 | 2134.0 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## 3/8" ID Hose with 3/8" Male Pipe NPTF Swivel at Both Ends



| Part No. | Descr. | Prod. No. | Length | |
|---|---|---|---|---|
| | | | " | mm |
| ⚠ 27630 | 6AB-6MPX-6MPX-08 | 7745-9098 | 8 | 203.0 |
| ⚠ 27631 | 6AB-6MPX-6MPX-12 | 7745-9099 | 12 | 305.0 |
| ⚠ 27633 | 6AB-6MPX-6MPX-16 | 7745-9100 | 16 | 406.0 |
| ⚠ 27635 | 6AB-6MPX-6MPX-20 | 7745-9101 | 20 | 51.0 |
| ⚠ 27637 | 6AB-6MPX-6MPX-24 | 7745-9102 | 24 | 610.0 |
| ⚠ 27639 | 6AB-6MPX-6MPX-28 | 7745-9103 | 28 | 711.0 |
| ⚠ 27641 | 6AB-6MPX-6MPX-32 | 7745-9104 | 32 | 813.0 |
| ⚠ 27643 | 6AB-6MPX-6MPX-36 | 7745-9105 | 36 | 914.4 |
| ⚠ 27646 | 6AB-6MPX-6MPX-42 | 7745-9106 | 42 | 1067.0 |
| ⚠ 27648 | 6AB-6MPX-6MPX-45 | 7745-9107 | 45 | 1143.0 |
| ⚠ 27650 | 6AB-6MPX-6MPX-48 | 7745-9108 | 48 | 1219.0 |
| ⚠ 27652 | 6AB-6MPX-6MPX-52 | 7745-9109 | 52 | 1321.0 |
| ⚠ 27654 | 6AB-6MPX-6MPX-60 | 7745-9110 | 60 | 1524.0 |
| ⚠ 27655 | 6AB-6MPX-6MPX-66 | 7745-9111 | 66 | 1676.0 |
| ⚠ 27656 | 6AB-6MPX-6MPX-72 | 7745-9112 | 72 | 1829.0 |
| ⚠ 27657 | 6AB-6MPX-6MPX-84 | 7745-9113 | 84 | 2134.0 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# 3/8" ID Hose with 3/8" Female SAE Swivel at Both Ends



| Part No. | Descr. | Prod. No. | Length | |
|---|---|---|---|---|
| | | | " | mm |
| ⚠ 27685 | 6AB-6FSX-6FSX-18 | 7745-9129 | 18 | 457.0 |
| ⚠ 27686 | 6AB-6FSX-6FSX-24 | 7745-9130 | 24 | 610.0 |
| ⚠ 27687 | 6AB-6FSX-6FSX-30 | 7745-9131 | 30 | 762.0 |
| ⚠ 27688 | 6AB-6FSX-6FSX-36 | 7745-9132 | 36 | 914.4 |
| ⚠ 27689 | 6AB-6FSX-6FSX-42 | 7745-9133 | 42 | 1067.0 |
| ⚠ 27690 | 6AB-6FSX-6FSX-48 | 7745-9134 | 48 | 1219.0 |
| ⚠ 27691 | 6AB-6FSX-6FSX-54 | 7745-9135 | 54 | 1372.0 |
| ⚠ 27692 | 6AB-6FSX-6FSX-60 | 7745-9136 | 60 | 1524.0 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

**Recommended For:** Air brake systems on trucks and buses. Offering includes a broad range of application coverage for use in the air brake system and with AB Series Rubber Air Brake Hose.

**Used With:** AB Series Rubber Air Brake Hose. **NOT** recommended for Nylon Air Brake Tubing.

**Features and Benefits:** Many fittings can be detached and reattached for reuse.

**Conformance:** Meets SAE J1402 and D.O.T. FMVSS-106 requirements.

**Working Pressure:** 225 psi (15 bar)

**Maximum Burst Pressure:** 900 psi (62 bar)


**Temperature Range:** -63°F to +250°F (-52° to +121°C)

**Material:** 360 Brass

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Male Air Brake to Male Pipe Adapter




| Part No. | Descr. | Prod. No. | A1 | | | | L | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | T2 (in) | " | mm |
| ⚠ G33030-0604 | 6MAB-4MP | 7250-03175 | 3/8 | 9.7 | 3/4–20 | 1/4–18 | 1.06 | 26.9 |
| ⚠ G33030-0606 | 6MAB-6MP | 7250-03185 | 3/8 | 9.7 | 3/4–20 | 3/8–18 | 1.12 | 28.5 |
| ⚠ G33030-0608 | 6MAB-8MP | 7250-03195 | 3/8 | 9.7 | 3/4–20 | 1/2–14 | 1.18 | 30.0 |
| ⚠ G33030-0806 | 8MAB-6MP | 7250-03205 | 1/2 | 12.7 | 7/8–20 | 3/8–18 | 1.18 | 30.0 |
| ⚠ G33030-0808 | 8MAB-8MP | 7250-03215 | 1/2 | 12.7 | 7/8–20 | 1/2–14 | 1.37 | 34.8 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Gladhand



| Part No. | Descr. | Prod. No. | Type |
|---|---|---|---|
| ⚠ G33031-0508 | 8GH-S | 7250-03225 | Service |
| ⚠ G33031-0608 | 8GH-U | 7250-03235 | Universal |
| ⚠ G33031-0708 | 8GH-E | 7250-03245 | Emergency |


⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Gladhand Seal



| Part No. | Descr. | Prod. No. |
|---|---|---|
| G33032-0006 | 6GH-SEAL | 7250-15595 |


# Sleeve




| Part No. | Descr. | Prod. No. | A1 | | L | |
|---|---|---|---|---|---|---|
| | | | " | mm | " | mm |
| ⚠ G33050-0006 | 6TS-6ABR | 7250-03265 | 3/8 | 9.7 | .69 | 17.5 |
| ⚠ G33050-0008 | 8TS-8ABR | 7250-03275 | 1/2 | 12.7 | .69 | 17.5 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Nut





| Part No. | Descr. | Prod. No. | A1 | | | L | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G33060-0006 | 6TSN-6ABR | 7250-03295 | 3/8 | 9.7 | 1 1/16 | 1.12 | 28.5 |
| ⚠ G33060-0008 | 8TSN-8ABR | 7250-03305 | 1/2 | 12.7 | 1 1/4 | 1.12 | 28.5 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Spring Guard Nut




| Part No. | Descr. | Prod. No. | A1 | | | L | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G33061-0006 | 6SGN-6ABR | 7250-03315 | 3/8 | 9.7 | 1 1/16 | 1.22 | 31.0 |
| ⚠ G33061-0008 | 8SGN-8ABR | 7250-03325 | 1/2 | 12.7 | 1 1/4 | 1.19 | 30.2 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


## Air Brake to Male Pipe with Nut and Sleeve




| Part No. | Descr. | Prod. No. | A1 | | | H2 | L | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | " | mm |
| ⚠ G33100-0604 | 6ABR-4MP | 7250-03335 | 3/8 | 9.7 | 1/4–18 | 31/32 | 2.12 | 53.9 |
| ⚠ G33100-0606 | 6ABR-6MP | 7250-03345 | 3/8 | 9.7 | 3/8–18 | 31/32 | 2.12 | 53.9 |
| ⚠ G33100-0608 | 6ABR-8MP | 7250-03355 | 3/8 | 9.7 | 1/2–14 | 31/32 | 2.27 | 57.7 |
| ⚠ G33100-0806 | 8ABR-6MP | 7250-03365 | 1/2 | 12.7 | 3/8–18 | 1 1/8 | 2.13 | 54.1 |
| ⚠ G33100-0808 | 8ABR-8MP | 7250-03375 | 1/2 | 12.7 | 1/2–14 | 1 1/8 | 2.29 | 58.2 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


## Air Brake to Male Pipe with Spring Guard




| Part No. | Descr. | Prod. No. | T1 (in) | H2 | L | |
|---|---|---|---|---|---|---|
| | | | | " | " | mm |
| ⚠ G33110-0604 | 6ABRSG-4MP | 7250-03385 | 1/4–18 | 31/32 | 4.80 | 121.9 |
| ⚠ G33110-0606 | 6ABRSG-6MP | 7250-03395 | 3/8–18 | 31/32 | 4.80 | 121.9 |
| ⚠ G33110-0608 | 6ABRSG-8MP | 7250-03405 | 1/2–14 | 31/32 | 4.90 | 124.5 |
| ⚠ G33110-0806 | 8ABRSG-6MP | 7250-03415 | 3/8–18 | 1 1/8 | 5.00 | 127.0 |
| ⚠ G33110-0808 | 8ABRSG-8MP | 7250-03425 | 1/2–14 | 1 1/8 | 5.20 | 132.1 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


## Air Brake to Male Pipe without Nut and Sleeve




| Part No. | Descr. | Prod. No. | A1 | | T1 (in) | H2 | L | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | | " | " | mm |
| ⚠ G33111-0604 | 6ABRI-4MP | 7250-03435 | 3/8 | 9.7 | 1/4–18 | 31/32 | 1.91 | 48.5 |
| ⚠ G33111-0606 | 6ABRI-6MP | 7250-03445 | 3/8 | 9.7 | 3/8–18 | 31/32 | 1.91 | 48.5 |
| ⚠ G33111-0608 | 6ABRI-8MP | 7250-03455 | 3/8 | 9.7 | 1/2–14 | 31/32 | 2.06 | 52.3 |
| ⚠ G33111-0806 | 8ABRI-6MP | 7250-03465 | 1/2 | 12.7 | 3/8–18 | 1 1/8 | 1.90 | 48.3 |
| ⚠ G33111-0808 | 8ABRI-8MP | 7250-03475 | 1/2 | 12.7 | 1/2–14 | 1 1/8 | 2.07 | 52.6 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## Air Brake Spring Guard





| Part No. | Descr. | Prod. No. | A1 | | L | |
|---|---|---|---|---|---|---|
| | | | " | mm | " | mm |
| ⚠ G33112-0006 | 6SGABR | 7250-03485 | 3/8 | 9.7 | 2.75 | 69.9 |
| ⚠ G33112-0008 | 8SGABR | 7250-03495 | 1/2 | 12.7 | 3.00 | 76.2 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## Air Brake to Female Air Brake Swivel




| Part No. | Descr. | Prod. No. | A1 | | | H2 | L | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | " | mm |
| ⚠ G33150-0606 | 6ABR-6FABX | 7250-03505 | 3/8 | 9.7 | 3/4–20 | 31/32 | 2.30 | 58.4 |
| ⚠ G33150-0808 | 8ABR-8FABX | 7250-03515 | 1/2 | 12.7 | 7/8–20 | 1 1/8 | 2.36 | 59.9 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


## Air Brake to Female Air Brake Swivel with Adapter




| Part No. | Descr. | Prod. No. | A1 | | | H2 | L | |
|---|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | " | mm |
| ⚠ G33151-0604 | 6ABR-6FABX-4MPA | 7250-03525 | 3/8 | 9.7 | 1/4–18 | 15/16 | 2.94 | 74.7 |
| ⚠ G33151-0606 | 6ABR-6FABX-6MPA | 7250-03535 | 3/8 | 9.7 | 3/8–18 | 1 1/8 | 2.94 | 74.7 |
| ⚠ G33151-0608 | 6ABR-8FABX-8MPA | 7250-03545 | 3/8 | 9.7 | 1/2–14 | 1 1/8 | 2.94 | 74.7 |
| ⚠ G33151-0806 | 8ABR-6FABX-6MPA | 7250-15605 | 1/2 | 12.7 | 3/8–18 | 1 1/8 | 2.94 | 74.7 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## Air Brake Union




| Part No. | Descr. | Prod. No. | A1 | | H2 | L | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | " | " | mm |
| ⚠ G33400-0606 | 6ABR-6ABR | 7250-03625 | 3/8 | 9.7 | 31/32 | 2.98 | 75.7 |
| ⚠ G33400-0808 | 8ABR-8ABR | 7250-03635 | 1/2 | 12.7 | 1 1/8 | 2.99 | 75.9 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

**Recommended For:** Fuel lines, fluid lines or vacuum lines in low and medium pressure applications.

**Used With:** LOC and LOL Hose

**Features and Benefits:** Lock-On barbed stem fittings are quick connecting and resistant to damage from high vibration diesel applications. Hose clamps or ferrules are not needed or recommended.


**Working Pressure:** 300 psi (21 bar)

**Temperature Range:** -40°F to 250°F (-40°C to +121°C)

**Material:** 360 Brass

## Assembly Instructions:

1. Measure and mark the hose length to be cut. When cutting, be sure to make the cut as even as possible. We recommended using a hand held hose cutter or a sharp knife.
2. Lubricate the hose and/or fittings with light oil or soapy water. Heavy oils or grease are not recommended as a lubricant.
3. Insert fitting until the first barb is in the hose.
4. Place the fitting end against a flat hard surface, such as a work bench, to finish inserting the fitting stem into the hose. You'll need to grip the hose approximately one inch from the end of the fitting and push until the end of the hose is fully over the stem and against the yellow plastic stop cap or the stop below the hex on the fitting. Note: a yellow stop cap is normally part of a Lock-On fitting.




**Precautions:**


- Make sure the Lock-On fitting is fully inserted into the hose. Lock-On fittings will properly grip hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.
- Using clamps with LOC Lock-On fittings is not recommended. Clamps will damage the seal causing leaks and an unsafe assembly.

## Lock-On Fitting and Hose Disassembly Instructions:

1. Secure the fitting using a vise, sturdy workbench or other stable surface.
2. Starting at the yellow plastic stop cap, carefully cut the hose lengthwise approximately one inch away from the yellow stop cap.




3. Cut slowly, making sure not to nick the fitting barbs.
4. Grip the hose firmly and give it a sharp downward tug away from the fitting to separate the fitting from the hose.




EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Male Pipe with Cone Seat









| Part No. | Descr. | Prod. No. | A1 | | | C | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G36100-0402 | 4LOC-2RMP | 7250-04435 | 1/4 | 6.4 | 1/8–27 | .56 | 14.2 |
| ⚠ G36100-0404 | 4LOC-4RMP | 7250-04445 | 1/4 | 6.4 | 1/4–18 | .81 | 20.6 |
| ⚠ G36100-0406 | 4LOC-6RMP | 7250-16065 | 1/4 | 6.4 | 3/8–18 | .88 | 22.4 |
| ⚠ G36100-0502 | 5LOC-2RMP | 7250-04455 | 5/16 | 7.9 | 1/8–27 | .81 | 20.6 |
| ⚠ G36100-0504 | 5LOC-4RMP | 7250-04465 | 5/16 | 7.9 | 1/4–18 | .77 | 19.6 |
| ⚠ G36100-0602 | 6LOC-2RMP | 7250-04475 | 3/8 | 9.5 | 1/8–27 | .56 | 14.2 |
| ⚠ G36100-0604 | 6LOC-4RMP | 7250-04485 | 3/8 | 9.5 | 1/4–18 | .81 | 20.6 |
| ⚠ G36100-0606 | 6LOC-6RMP | 7250-04495 | 3/8 | 9.5 | 3/8–18 | .88 | 22.4 |
| ⚠ G36100-0608 | 6LOC-8RMP | 7250-16075 | 3/8 | 9.5 | 1/2–14 | .88 | 22.4 |
| ⚠ G36100-0804 | 8LOC-4RMP | 7250-16085 | 1/2 | 12.7 | 1/4–18 | .81 | 20.6 |
| ⚠ G36100-0806 | 8LOC-6RMP | 7250-04505 | 1/2 | 12.7 | 3/8–18 | .88 | 22.4 |
| ⚠ G36100-0808 | 8LOC-8RMP | 7250-04515 | 1/2 | 12.7 | 1/2–14 | .88 | 22.4 |
| ⚠ G36100-0812 | 8LOC-12RMP | 7250-16095 | 1/2 | 12.7 | 3/4–14 | 1.13 | 28.7 |
| ⚠ G36100-1006 | 10LOC-6RMP | 7250-16105 | 5/8 | 15.9 | 3/8–18 | .88 | 22.4 |
| ⚠ G36100-1008 | 10LOC-8RMP | 7250-04525 | 5/8 | 15.9 | 1/2–14 | 1.06 | 26.9 |
| ⚠ G36100-1012 | 10LOC-12RMP | 7250-16115 | 5/8 | 15.9 | 3/4–14 | .88 | 22.4 |
| ⚠ G36100-1208 | 12LOC-8RMP | 7250-16125 | 3/4 | 19.1 | 1/2–14 | .88 | 22.4 |
| ⚠ G36100-1212 | 12LOC-12RMP | 7250-04535 | 3/4 | 19.1 | 3/4–14 | 1.13 | 28.7 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## Male Pipe Swivel without Cone Seat









| Part No. | Descr. | Prod. No. | A1 | | | C | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G36105-0404 | 4LOC-4RMPX | 7250-16135 | 1/4 | 6.4 | 1/4–18 | 1.81 | 46.0 |
| ⚠ G36105-0606 | 6LOC-6RMPX | 7250-16145 | 3/8 | 9.5 | 3/8–18 | 2.00 | 50.8 |
| ⚠ G36105-0808 | 8LOC-8RMPX | 7250-16155 | 1/2 | 12.7 | 1/2–14 | 2.38 | 60.5 |
| ⚠ G36105-1212 | 12LOC-12RMPX | 7250-16165 | 3/4 | 19.1 | 3/4–14 | 2.68 | 68.1 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## Male Pipe 90° Block with Cone Seat









| Part No. | Descr. | Prod. No. | A1 | | | C | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G36106-0402 | 4LOC-2RMP90 | 7250-16175 | 1/4 | 6.4 | 1/8–27 | .31 | 7.9 |
| ⚠ G36106-0404 | 4LOC-4RMP90 | 7250-16185 | 1/4 | 6.4 | 1/4–18 | .38 | 9.7 |
| ⚠ G36106-0502 | 5LOC-2RMP90 | 7250-04555 | 5/16 | 7.9 | 1/8–27 | .31 | 7.9 |
| ⚠ G36106-0504 | 5LOC-4RMP90 | 7250-04565 | 5/16 | 7.9 | 1/4–18 | .38 | 9.7 |
| ⚠ G36106-0602 | 6LOC-2RMP90 | 7250-04575 | 3/8 | 9.5 | 1/8–27 | .38 | 9.7 |
| ⚠ G36106-0604 | 6LOC-4RMP90 | 7250-04585 | 3/8 | 9.5 | 1/4–18 | .40 | 10.2 |
| ⚠ G36106-0606 | 6LOC-6RMP90 | 7250-16195 | 3/8 | 9.5 | 3/8–18 | .43 | 10.9 |
| ⚠ G36106-0808 | 8LOC-8RMP90 | 7250-16205 | 1/2 | 12.7 | 1/2–14 | .50 | 12.7 |
| ⚠ G36106-1212 | 12LOC-12RMP90 | 7250-16215 | 3/4 | 19.1 | 3/4–14 | .76 | 19.3 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## Female Pipe without Cone Seat





| Part No. | Descr. | Prod. No. | A1 | | | C | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G36110-0404 | 4LOC-4RFP | 7250-04595 | 1/4 | 6.4 | 1/4–18 | .50 | 12.7 |
| ⚠ G36110-0504 | 5LOC-4RFP | 7250-16225 | 5/16 | 7.9 | 1/4–18 | .50 | 12.7 |
| ⚠ G36110-0606 | 6LOC-6RFP | 7250-04605 | 3/8 | 9.5 | 3/8–18 | .63 | 16.0 |
| ⚠ G36110-0806 | 8LOC-6RFP | 7250-16235 | 1/2 | 12.7 | 3/8–18 | .63 | 16.0 |
| ⚠ G36110-0808 | 8LOC-8RFP | 7250-04615 | 1/2 | 12.7 | 1/2–14 | .75 | 19.1 |
| ⚠ G36110-1008 | 10LOC-8RFP | 7250-16245 | 5/8 | 15.9 | 1/2–14 | .75 | 19.1 |
| ⚠ G36110-1212 | 12LOC-12RFP | 7250-16255 | 3/4 | 19.1 | 3/4–14 | .93 | 23.6 |


⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## Female Pipe Swivel with Cone Seat









| Part No. | Descr. | Prod. No. | A1 | | | C | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G36111-0402 | 4LOC-2RFPX | 7250-16265 | 1/4 | 6.4 | 1/8–27 | 1.81 | 46.0 |
| ⚠ G36111-0404 | 4LOC-4RFPX | 7250-16275 | 1/4 | 6.4 | 1/4–18 | 1.81 | 46.0 |
| ⚠ G36111-0406 | 4LOC-6RFPX | 7250-16285 | 1/4 | 6.4 | 3/8–18 | 2.00 | 50.8 |
| ⚠ G36111-0604 | 6LOC-4RFPX | 7250-16295 | 3/8 | 9.5 | 1/4–18 | 1.81 | 46.0 |
| ⚠ G36111-0606 | 6LOC-6RFPX | 7250-16305 | 3/8 | 9.5 | 3/8–18 | 2.00 | 50.8 |
| ⚠ G36111-0608 | 6LOC-8RFPX | 7250-16315 | 3/8 | 9.5 | 1/2–14 | 2.38 | 60.5 |
| ⚠ G36111-0808 | 8LOC-8RFPX | 7250-16325 | 1/2 | 12.7 | 1/2–14 | 2.38 | 60.5 |
| ⚠ G36111-0812 | 8LOC-12RFPX | 7250-16335 | 1/2 | 12.7 | 3/4–14 | 2.68 | 68.1 |
| ⚠ G36111-1012 | 10LOC-12RFPX | 7250-16345 | 5/8 | 15.9 | 3/4–14 | 2.68 | 68.1 |
| ⚠ G36111-1212 | 12LOC-12RFPX | 7250-16355 | 3/4 | 19.1 | 3/4–14 | 2.68 | 68.1 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## Male JIC 37° Flare









| Part No. | Descr. | Prod. No. | A1 | | | C | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G36165-0404 | 4LOC-4RMJ | 7250-16365 | 1/4 | 6.4 | 7/16–20 | .81 | 20.6 |
| ⚠ G36165-0405 | 4LOC-5RMJ | 7250-16375 | 1/4 | 6.4 | 1/2–20 | .94 | 23.9 |
| ⚠ G36165-0406 | 4LOC-6RMJ | 7250-16385 | 1/4 | 6.4 | 9/16–18 | 1.00 | 25.4 |
| ⚠ G36165-0604 | 6LOC-4RMJ | 7250-16395 | 3/8 | 9.5 | 7/16–20 | .88 | 22.4 |
| ⚠ G36165-0605 | 6LOC-5RMJ | 7250-16405 | 3/8 | 9.5 | 1/2–20 | .94 | 23.9 |
| ⚠ G36165-0606 | 6LOC-6RMJ | 7250-16415 | 3/8 | 9.5 | 9/16–18 | 1.00 | 25.4 |
| ⚠ G36165-0608 | 6LOC-8RMJ | 7250-16425 | 3/8 | 9.5 | 3/4–16 | 1.19 | 30.2 |
| ⚠ G36165-0808 | 8LOC-8RMJ | 7250-16435 | 1/2 | 12.7 | 3/4–16 | 1.19 | 30.2 |
| ⚠ G36165-0810 | 8LOC-10RMJ | 7250-16445 | 1/2 | 12.7 | 7/8–14 | 1.27 | 32.3 |
| ⚠ G36165-1008 | 10LOC-8RMJ | 7250-16455 | 5/8 | 15.9 | 3/4–16 | 1.19 | 30.2 |
| ⚠ G36165-1010 | 10LOC-10RMJ | 7250-16465 | 5/8 | 15.9 | 7/8–14 | 1.27 | 32.3 |
| ⚠ G36165-1210 | 12LOC-10RMJ | 7250-16475 | 3/4 | 19.1 | 7/8–14 | 1.27 | 32.3 |
| ⚠ G36165-1212 | 12LOC-12RMJ | 7250-16485 | 3/4 | 19.1 | 1 1/16–12 | 1.33 | 33.8 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Female JIC 37° Flare Swivel









| Part No. | Descr. | Prod. No. | A1 | | | C | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G36170-0406 | 4LOC-6RFJX | 7250-16495 | 1/4 | 6.4 | 9/16–18 | .74 | 18.8 |
| ⚠ G36170-0606 | 6LOC-6RFJX | 7250-04625 | 3/8 | 9.5 | 9/16–18 | .81 | 20.6 |
| ⚠ G36170-1212 | 12LOC-12RFJX | 7250-04635 | 3/4 | 19.1 | 1 1/16–12 | 1.09 | 27.7 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Male SAE 45° Flare





| Part No. | Descr. | Prod. No. | A1 | | | C | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G36195-0404 | 4LOC-4RMS | 7250-04645 | 1/4 | 6.4 | 7/16–20 | .69 | 17.5 |
| ⚠ G36195-0405 | 4LOC-5RMS | 7250-04655 | 1/4 | 6.4 | 1/2–20 | .38 | 9.7 |
| ⚠ G36195-0406 | 4LOC-6RMS | 7250-04665 | 1/4 | 6.4 | 5/8–18 | .88 | 22.4 |
| ⚠ G36195-0505 | 5LOC-5RMS | 7250-04675 | 5/16 | 7.9 | 1/2–20 | .81 | 20.6 |
| ⚠ G36195-0604 | 6LOC-4RMS | 7250-16505 | 3/8 | 9.5 | 7/16–20 | .69 | 17.5 |
| ⚠ G36195-0605 | 6LOC-5RMS | 7250-16515 | 3/8 | 9.5 | 1/2–20 | .81 | 20.6 |
| ⚠ G36195-0606 | 6LOC-6RMS | 7250-04685 | 3/8 | 9.5 | 5/8–18 | .88 | 22.4 |
| ⚠ G36195-0608 | 6LOC-8RMS | 7250-16525 | 3/8 | 9.5 | 3/4–16 | 1.31 | 33.3 |
| ⚠ G36195-0808 | 8LOC-8RMS | 7250-18285 | 1/2 | 12.7 | 3/4–16 | 1.13 | 28.7 |
| ⚠ G36195-0810 | 8LOC-10RMS | 7250-16535 | 1/2 | 12.7 | 7/8–14 | 1.27 | 32.3 |
| ⚠ G36195-1008 | 10LOC-8RMS | 7250-16545 | 5/8 | 15.9 | 3/4–16 | 1.13 | 28.7 |
| ⚠ G36195-1010 | 10LOC-10RMS | 7250-16555 | 5/8 | 15.9 | 7/8–14 | 1.27 | 32.3 |
| ⚠ G36195-1210 | 12LOC-10RMS | 7250-16565 | 3/4 | 19.1 | 7/8–14 | 1.27 | 32.3 |
| ⚠ G36195-1212 | 12LOC-12RMS | 7250-16575 | 3/4 | 19.1 | 1 1/16–14 | 1.83 | 46.5 |


⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Female SAE 45° Flare Swivel





| Part No. | Descr. | Prod. No. | A1 | | | C | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G36200-0406 | 4LOC-6RFSX | 7250-16585 | 1/4 | 6.4 | 5/8–18 | .69 | 17.5 |
| ⚠ G36200-0506 | 5LOC-6RFSX | 7250-18295 | 5/16 | 7.9 | 5/8–18 | .81 | 20.6 |
| ⚠ G36200-0606 | 6LOC-6RFSX | 7250-04695 | 3/8 | 9.5 | 5/8–18 | .84 | 21.3 |
| ⚠ G36200-0806 | 8LOC-6RFSX | 7250-16595 | 1/2 | 12.7 | 5/8–18 | .84 | 21.3 |
| ⚠ G36200-1212 | 12LOC-12RFSX | 7250-04705 | 3/4 | 19.1 | 1 1/16–14 | 1.09 | 27.7 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


# Dual Seat Female JIC 37°/SAE 45° Flare Swivel





| Part No. | Descr. | Prod. No. | A1 | | | C | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G36210-0404 | 4LOC-4RFJSX | 7250-04715 | 1/4 | 6.4 | 7/16–20 | .75 | 19.1 |
| ⚠ G36210-0405 | 4LOC-5RFJSX | 7250-04725 | 1/4 | 6.4 | 1/2–20 | .78 | 19.8 |
| ⚠ G36210-0505 | 5LOC-5RFJSX | 7250-04735 | 5/16 | 7.9 | 1/2–20 | .81 | 20.6 |
| ⚠ G36210-0605 | 6LOC-5RFJSX | 7250-04745 | 3/8 | 9.5 | 1/2–20 | .81 | 20.6 |
| ⚠ G36210-0608 | 6LOC-8RFJSX | 7250-18305 | 3/8 | 9.5 | 3/4–16 | .97 | 24.6 |
| ⚠ G36210-0808 | 8LOC-8RFJSX | 7250-04755 | 1/2 | 12.7 | 3/4–16 | .97 | 24.6 |
| ⚠ G36210-0810 | 8LOC-10RFJSX | 7250-18315 | 1/2 | 12.7 | 7/8–14 | 1.00 | 25.4 |
| ⚠ G36210-1010 | 10LOC-10RFJSX | 7250-04765 | 5/8 | 15.9 | 7/8–14 | 1.00 | 25.4 |
| ⚠ G36210-1210 | 12LOC-10RFJSX | 7250-04775 | 3/4 | 19.1 | 7/8–14 | 1.00 | 25.4 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Male SAE Inverted Flare Swivel









| Part No. | Descr. | Prod. No. | A1 | | | C | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G36500-0403 | 4LOC-3RMIX | 7250-04785 | 1/4 | 6.4 | 3/8–24 | .78 | 19.8 |
| ⚠ G36500-0404 | 4LOC-4RMIX | 7250-04795 | 1/4 | 6.4 | 7/16–24 | .78 | 19.8 |
| ⚠ G36500-0405 | 4LOC-5RMIX | 7250-04805 | 1/4 | 6.4 | 1/2–20 | .78 | 19.8 |
| ⚠ G36500-0504 | 5LOC-4RMIX | 7250-04815 | 5/16 | 7.9 | 1/2–20 | .78 | 19.8 |
| ⚠ G36500-0505 | 5LOC-5RMIX | 7250-04825 | 5/16 | 7.9 | 1/2–20 | .82 | 20.8 |
| ⚠ G36500-0506 | 5LOC-6RMIX | 7250-04835 | 5/16 | 7.9 | 5/8–18 | .86 | 21.8 |
| ⚠ G36500-0605 | 6LOC-5RMIX | 7250-04845 | 3/8 | 9.5 | 1/2–20 | .82 | 20.8 |
| ⚠ G36500-0606 | 6LOC-6RMIX | 7250-04855 | 3/8 | 9.5 | 5/8–18 | .97 | 24.6 |
| ⚠ G36500-0608 | 6LOC-8RMIX | 7250-16605 | 3/8 | 9.5 | 3/4–18 | 1.00 | 25.4 |
| ⚠ G36500-0806 | 8LOC-6RMIX | 7250-16615 | 1/2 | 12.7 | 5/8–18 | .97 | 24.6 |
| ⚠ G36500-0808 | 8LOC-8RMIX | 7250-04865 | 1/2 | 12.7 | 3/4–18 | 1.00 | 25.4 |
| ⚠ G36500-1010 | 10LOC-10RMIX | 7250-18325 | 5/8 | 15.9 | 7/8–18 | 1.00 | 25.4 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Female SAE Inverted Flare





| Part No. | Descr. | Prod. No. | A1 | | | C | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G36508-0403 | 4LOC-3RFI | 7250-04875 | 1/4 | 6.4 | 3/8–24 | .75 | 19.1 |
| ⚠ G36508-0404 | 4LOC-4RFI | 7250-04885 | 1/4 | 6.4 | 7/16–24 | .75 | 19.1 |
| ⚠ G36508-0405 | 4LOC-5RFI | 7250-04895 | 1/4 | 6.4 | 1/2–20 | .75 | 19.1 |
| ⚠ G36508-0505 | 5LOC-5RFI | 7250-04905 | 5/16 | 7.9 | 1/2–20 | .75 | 19.1 |
| ⚠ G36508-0605 | 6LOC-5RFI | 7250-04915 | 3/8 | 9.5 | 1/2–20 | .75 | 19.1 |
| ⚠ G36508-0606 | 6LOC-6RFI | 7250-04925 | 3/8 | 9.5 | 5/8–18 | .88 | 22.4 |
| ⚠ G36508-0808 | 8LOC-8RFI | 7250-04935 | 1/2 | 12.7 | 5/8–18 | .93 | 23.6 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


## North American Stand Pipe




| Part No. | Descr. | Prod. No. | A1 | | C | |
|---|---|---|---|---|---|---|
| | | | " | mm | " | mm |
| ⚠ G36520-0403 | 4LOC-3RFT | 7250-04945 | 1/4 | 6.4 | .75 | 19.1 |
| ⚠ G36520-0404 | 4LOC-4RFT | 7250-04955 | 1/4 | 6.4 | 1.00 | 25.4 |
| ⚠ G36520-0405 | 4LOC-5RFT | 7250-04965 | 1/4 | 6.4 | 1.13 | 28.7 |
| ⚠ G36520-0505 | 5LOC-5RFT | 7250-04975 | 5/16 | 7.9 | 1.13 | 28.7 |
| ⚠ G36520-0606 | 6LOC-6RSP | 7250-04985 | 3/8 | 9.5 | 1.25 | 31.8 |
| ⚠ G36520-0808 | 8LOC-8RSP | 7250-16625 | 1/2 | 12.7 | 1.00 | 25.4 |
| ⚠ G36520-1010 | 10LOC-10RSP | 7250-16635 | 5/8 | 15.9 | 1.00 | 25.4 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


## Hose Length Extenders




| Part No. | Descr. | Prod. No. | A1 | A2 |
|---|---|---|---|---|
| | | | " | " |
| ⚠ G36535-0404 | 4LOC-4RHM | 7250-04995 | 1/4 | 1/4 |
| ⚠ G36535-0505 | 5LOC-5RHM | 7250-05005 | 5/16 | 5/16 |
| ⚠ G36535-0606 | 6LOC-6RHM | 7250-05015 | 3/8 | 3/8 |
| ⚠ G36535-0808 | 8LOC-8RHM | 7250-05025 | 1/2 | 1/2 |
| ⚠ G36535-1010 | 10LOC-10RHM | 7250-18335 | 5/8 | 5/8 |
| ⚠ G36535-1212 | 12LOC-12RHM | 7250-18345 | 3/4 | 3/4 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Male British Standard Pipe Tapered




| Part No. | Descr. | Prod. No. | A1 | | | C | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G36795-0504 | 5LOC-4MBSPT | 7250-10225 | 5/16 | 7.9 | 1/4–19 | .63 | 16.0 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

**Recommended For:** Low pressure fuel, oil, compressed air and water lines used in small engines, vacuum advance and evaporative emission control systems.

**Used With:** Low pressure hose such as multi-purpose or general purpose hose.

**Features and Benefits:** Single bead fittings are quick connecting, field attachable and reusable. An economical choice for general purpose fluid applications. Single bead is sometimes referred to as beaded nipple.

**Conformance:** Contact Gates to verify compliance to desired specifications and suitability for particular applications.

**Working Pressure:** 60 psi (4 bar)


**Temperature Range:** -40°F to +250°F (-40°C to +121°C)

**Material:** 360 Brass

## Assembly Instructions:

1. Cut hose as straight as possible.
2. Slide clamp on hose then lubricate hose or fitting.
3. Push hose on fitting until hose bottoms against hex or stop ring.
4. Position hose clamp between fitting bead on stem and end of hose and tighten.
5. Hose clamps required.


# Male Pipe with Cone Seat




| Part No. | Descr. | Prod. No. | A1 | | | L | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G37100-0302 | 3SB-2RMP | 7250-05035 | 3/16 | 4.8 | 1/8–27 | 1.26 | 32.0 |
| ⚠ G37100-0402 | 4SB-2RMP | 7250-05045 | 1/4 | 6.4 | 1/8–27 | 1.32 | 33.5 |
| ⚠ G37100-0404 | 4SB-4RMP | 7250-05055 | 1/4 | 6.4 | 1/4–18 | 1.63 | 41.4 |
| ⚠ G37100-0502 | 5SB-2RMP | 7250-05065 | 5/16 | 7.9 | 1/8–27 | 1.55 | 39.4 |
| ⚠ G37100-0504 | 5SB-4RMP | 7250-05075 | 5/16 | 7.9 | 1/4–18 | 1.55 | 39.4 |
| ⚠ G37100-0602 | 6SB-2RMP | 7250-05085 | 3/8 | 9.7 | 1/8–27 | 1.55 | 39.4 |
| ⚠ G37100-0604 | 6SB-4RMP | 7250-05095 | 3/8 | 9.7 | 1/4–18 | 1.63 | 41.4 |
| ⚠ G37100-0606 | 6SB-6RMP | 7250-05105 | 3/8 | 9.7 | 3/8–18 | 1.72 | 43.7 |
| ⚠ G37100-0806 | 8SB-6RMP | 7250-05115 | 1/2 | 12.7 | 3/8–18 | 1.72 | 43.7 |
| ⚠ G37100-0808 | 8SB-8RMP | 7250-05125 | 1/2 | 12.7 | 1/2–14 | 1.79 | 45.5 |
| ⚠ G37100-1006 | 10SB-6RMP | 7250-05135 | 5/8 | 15.9 | 3/8–18 | 1.78 | 45.2 |
| ⚠ G37100-1008 | 10SB-8RMP | 7250-05145 | 5/8 | 15.9 | 1/2–14 | 1.78 | 45.2 |
| ⚠ G37100-1012 | 10SB-12RMP | 7250-16645 | 5/8 | 15.9 | 3/4–14 | 1.92 | 48.8 |
| ⚠ G37100-1208 | 12SB-8RMP | 7250-05155 | 3/4 | 19.1 | 1/2–14 | 1.78 | 45.2 |
| ⚠ G37100-1212 | 12SB-12RMP | 7250-16655 | 3/4 | 19.1 | 3/4–14 | 1.92 | 48.8 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Male Straight Thread Connector





| Part No. | Descr. | Prod. No. | A1 | | |
|---|---|---|---|---|---|
| | | | " | mm | T1 (in) |
| ⚠ G37103-0609 | 6SB-9MSC | 7250-05165 | 3/8 | 9.7 | 9/16–24 |
| ⚠ G37103-0610 | 6SB-10MSC | 7250-05175 | 3/8 | 9.7 | 5/8–20 |
| ⚠ G37103-0614 | 6SB-14MSC | 7250-05185 | 3/8 | 9.7 | 7/8–20 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Male Pipe 90° Block Cone Seat




| Part No. | Descr. | Prod. No. | A1 | | | L | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G37106-0402 | 4SB-2RMP90 | 7250-05195 | 1/4 | 6.4 | 1/8–27 | 1.00 | 25.4 |
| ⚠ G37106-0502 | 5SB-2RMP90 | 7250-05205 | 5/16 | 7.9 | 1/8–27 | 1.01 | 25.7 |
| ⚠ G37106-0504 | 5SB-4RMP90 | 7250-05215 | 5/16 | 7.9 | 1/4–18 | 1.01 | 25.7 |
| ⚠ G37106-0602 | 6SB-2RMP90 | 7250-05225 | 3/8 | 9.7 | 1/8–27 | 1.01 | 25.7 |
| ⚠ G37106-0604 | 6SB-4RMP90 | 7250-05235 | 3/8 | 9.7 | 1/4–18 | 1.04 | 26.4 |
| ⚠ G37106-0606 | 6SB-6RMP90 | 7250-05245 | 3/8 | 9.7 | 3/8–14 | 1.08 | 27.4 |
| ⚠ G37106-0806 | 8SB-6RMP90 | 7250-16665 | 1/2 | 12.7 | 3/8–14 | 1.08 | 27.4 |
| ⚠ G37106-0808 | 8SB-8RMP90 | 7250-16675 | 1/2 | 12.7 | 1/2–14 | 1.16 | 29.5 |
| ⚠ G37106-1006 | 10SB-6RMP90 | 7250-05255 | 5/8 | 15.9 | 3/8–18 | 1.13 | 28.7 |
| ⚠ G37106-1008 | 10SB-8RMP90 | 7250-16685 | 5/8 | 15.9 | 1/2–14 | 1.21 | 30.7 |
| ⚠ G37106-1208 | 12SB-8RMP90 | 7250-16695 | 3/4 | 19.1 | 1/2–14 | 1.28 | 32.5 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


# Male SAE 45° Flare Connector




| Part No. | Descr. | Prod. No. | A1 | | | L | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G37195-0605 | 6SB-5RMS | 7250-05265 | 3/8 | 9.7 | 1/2–20 | 2.00 | 50.8 |
| ⚠ G37195-0606 | 6SB-6RMS | 7250-16705 | 3/8 | 9.7 | 3/8–18 | 2.00 | 50.8 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


# Male SAE Inverted Flare Swivel




| Part No. | Descr. | Prod. No. | A1 | | | L | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G37500-0404 | 4SB-4RMIX | 7250-16715 | 1/4 | 6.4 | 7/16–24 | 1.72 | 43.7 |
| ⚠ G37500-0405 | 4SB-5RMIX | 7250-16725 | 1/4 | 6.4 | 1/2–20 | 1.78 | 45.2 |
| ⚠ G37500-0504 | 5SB-4RMIX | 7250-05275 | 5/16 | 7.9 | 7/16–24 | 1.58 | 40.1 |
| ⚠ G37500-0505 | 5SB-5RMIX | 7250-05285 | 5/16 | 7.9 | 1/2–20 | 1.58 | 40.1 |
| ⚠ G37500-0506 | 5SB-6RMIX | 7250-05295 | 5/16 | 7.9 | 5/8–18 | 1.63 | 41.4 |
| ⚠ G37500-0605 | 6SB-5RMIX | 7250-05305 | 3/8 | 9.7 | 1/2–20 | 1.73 | 44.0 |
| ⚠ G37500-0606 | 6SB-6RMIX | 7250-05315 | 3/8 | 9.7 | 5/8–18 | 2.00 | 50.8 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Male SAE Inverted Flare Swivel - 45°





| Part No. | Descr. | Prod. No. | A1 | | | L | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G37503-0605 | 6SB-5RMIX45 | 7250-05325 | 3/8 | 9.7 | 1/2–20 | 1.25 | 31.8 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS


# Male SAE Inverted Flare Swivel - 90°




| Part No. | Descr. | Prod. No. | A1 | | | L | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G37504-0404 | 4SB-4RMIX90 | 7250-05345 | 1/4 | 6.4 | 7/16–24 | 1.01 | 25.7 |
| ⚠ G37504-0405 | 4SB-5RMIX90 | 7250-05355 | 1/4 | 6.4 | 1/2–20 | 1.01 | 25.7 |
| ⚠ G37504-0506 | 5SB-6RMIX90 | 7250-05365 | 5/16 | 7.9 | 5/8–18 | 1.21 | 30.7 |
| ⚠ G37504-0605 | 6SB-5RMIX90 | 7250-05375 | 3/8 | 9.7 | 1/2–20 | 1.21 | 30.7 |
| ⚠ G37504-0606 | 6SB-6RMIX90 | 7250-05385 | 3/8 | 9.7 | 5/8–18 | 1.40 | 35.6 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Female SAE Inverted Flare




| Part No. | Descr. | Prod. No. | A1 | | | L | |
|---|---|---|---|---|---|---|---|
| | | | " | mm | T1 (in) | " | mm |
| ⚠ G37508-0505 | 5SB-5RFI | 7250-16735 | 5/16 | 7.9 | 1/2–20 | 2.03 | 51.6 |
| ⚠ G37508-0605 | 6SB-5RFI | 7250-16745 | 3/8 | 9.7 | 1/2–20 | 2.09 | 53.1 |
| ⚠ G37508-0606 | 6SB-6RFI | 7250-16755 | 3/8 | 9.7 | 5/8–18 | 2.16 | 54.9 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

**Recommended For:** Low pressure fuel, oil, compressed air, water and cooling lines. Typically used in heavy-duty truck, construction, industrial and mobile applications.

**Used With:** Low pressure multi-purpose or general purpose rubber hose and thermoplastic tubing.

**Features and Benefits:** Field attachable and reusable. An economical choice for general purpose fluid and pneumatic applications. The one-piece fitting is compact and great for use in tight spaces.

**Conformance:** Contact Gates to verify compliance to desired specifications and suitability for particular applications.

**Working Pressure:** 150 psi (10 bar)

**Temperature Range:** -40°F to +160°F (-40°C to +71°C)


**Material:** 360 Brass

## Assembly Instructions:

1. Cut hose as straight as is possible.
2. Slide clamp on hose, then lubricate hose.
3. Push hose on fitting until hose bottoms against hex or stop ring.
4. Position hose clamp between fitting end and end of hose. Tighten the clamp.
5. Hose clamps are recommended when using a barbed stem.

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# Male Pipe NPTF with Cone Seat




| Part No. | Descr. | Prod. No. | A1 " | T1 (in) |
|---|---|---|---|---|
| ⚠ G38100-0202 | 2BS-2MP | 7250-05395 | 1/8 | 1/8–27 |
| ⚠ G38100-0302 | 3BS-2MP | 7250-05405 | 3/16 | 1/8–27 |
| ⚠ G38100-0304 | 3BS-4MP | 7250-05415 | 3/16 | 1/4–18 |
| ⚠ G38100-0402 | 4BS-2MP | 7250-05425 | 1/4 | 1/8–27 |
| ⚠ G38100-0404 | 4BS-4MP | 7250-05435 | 1/4 | 1/4–18 |
| ⚠ G38100-0406 | 4BS-6MP | 7250-05445 | 1/4 | 3/8–18 |
| ⚠ G38100-0502 | 5BS-2MP | 7250-05455 | 5/16 | 1/8–27 |
| ⚠ G38100-0504 | 5BS-4MP | 7250-05465 | 5/16 | 1/4–18 |
| ⚠ G38100-0602 | 6BS-2MP | 7250-05475 | 3/8 | 1/8–27 |
| ⚠ G38100-0604 | 6BS-4MP | 7250-05485 | 3/8 | 1/4–18 |
| ⚠ G38100-0606 | 6BS-6MP | 7250-05495 | 3/8 | 3/8–18 |
| ⚠ G38100-0608 | 6BS-8MP | 7250-05505 | 3/8 | 1/2–14 |
| ⚠ G38100-0804 | 8BS-4MP | 7250-05515 | 1/2 | 1/4–18 |
| ⚠ G38100-0806 | 8BS-6MP | 7250-05525 | 1/2 | 3/8–18 |
| ⚠ G38100-0808 | 8BS-8MP | 7250-05535 | 1/2 | 1/2–14 |
| ⚠ G38100-0812 | 8BS-12MP | 7250-05545 | 1/2 | 3/4–14 |
| ⚠ G38100-1006 | 10BS-6MP | 7250-05555 | 5/8 | 3/8–18 |
| ⚠ G38100-1008 | 10BS-8MP | 7250-05565 | 5/8 | 1/2–14 |
| ⚠ G38100-1012 | 10BS-12MP | 7250-05575 | 5/8 | 3/4–14 |
| ⚠ G38100-1208 | 12BS-8MP | 7250-05585 | 3/4 | 1/2–14 |
| ⚠ G38100-1212 | 12BS-12MP | 7250-05595 | 3/4 | 3/4–14 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Female Pipe NPTF




| Part No. | Descr. | Prod. No. | A1 " | T1 (in) |
|---|---|---|---|---|
| ⚠ G38110-0202 | 2BS-2FP | 7250-05605 | 1/8 | 1/8–27 |
| ⚠ G38110-0302 | 3BS-2FP | 7250-05615 | 3/16 | 1/8–27 |
| ⚠ G38110-0402 | 4BS-2FP | 7250-05625 | 1/4 | 1/8–27 |
| ⚠ G38110-0404 | 4BS-4FP | 7250-05635 | 1/4 | 1/4–18 |
| ⚠ G38110-0502 | 5BS-2FP | 7250-05645 | 5/16 | 1/8–27 |
| ⚠ G38110-0504 | 5BS-4FP | 7250-05655 | 5/16 | 1/4–18 |
| ⚠ G38110-0602 | 6BS-2FP | 7250-05665 | 3/8 | 1/8–27 |
| ⚠ G38110-0604 | 6BS-4FP | 7250-05675 | 3/8 | 1/4–18 |
| ⚠ G38110-0606 | 6BS-6FP | 7250-05685 | 3/8 | 3/8–18 |
| ⚠ G38110-0804 | 8BS-4FP | 7250-05695 | 1/2 | 1/4–18 |
| ⚠ G38110-0806 | 8BS-6FP | 7250-05705 | 1/2 | 3/8–18 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# Female Pipe NPTF - Continued

| Part No. | Descr. | Prod. No. | A1 | |
|---|---|---|---|---|
| | | | " | T1 (in) |
| ⚠ G38110-0808 | 8BS-8FP | 7250-05715 | 1/2 | 1/2–14 |

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

## NOTES

EQUIPMENT
HOSE/CPLG. SELECTION
G8K COUPLINGS
GLOBALSPIRAL COUPLINGS
STAINLESS STEEL SPIRAL
MEGACRIMP COUPLINGS
STAINLESS STEEL BRAID
POWER CRIMP COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 COUPLINGS
C14 COUPLINGS
GL COUPLINGS
GLX COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
POLARSEAL COUPLINGS (ACA)
POLARSEAL II COUPLINGS (ACC)
POLARSEAL II COUPLINGS (ACB)
POWER STEERING
ADAPTERS
QUICK DISCONNECT COUPLERS
BALL VALVES
LIVE SWIVEL
ASSEMBLY FABRICATION
ACCESSORIES
EQUIPMENT AND PARTS
KITS
AIR BRAKE HOSE ASSY
BRASS

# INDEX


| Category | Page |
|---|---|
| **Hydraulic Hose** | |
| G8K Spiral Wire Hose | A19 |
| EFG6K Spiral Wire Hose - SAE 100R15 | A19 |
| EFG6K Spiral Wire Hose - SAE 100R15 - MegaTuff® Cover | A21 |
| EFG6KL Low Temp Spiral Wire Hose | A22 |
| EFG5K Spiral Wire Hose - SAE 100R13 | A22 |
| EFG5K Spiral Wire Hose - SAE 100R13 - MegaTuff® Cover | A24 |
| EFG5K Spiral Wire Hose - SAE 100R13 - XtraTuff® Cover | A25 |
| EFG5KL Low Temp Spiral Wire Hose | A25 |
| ID5K Spiral Wire Hose - ISO 18752 Grade D | A26 |
| EFG4K Spiral Wire Hose - SAE 100R12 | A27 |
| EFG4K Spiral Wire Hose - SAE 100R12 - MegaTuff® Cover | A28 |
| EFG4K Spiral Wire Hose - SAE 100R12 - XtraTuff® Cover | A29 |
| EFG4KL Low Temp Spiral Wire Hose | A30 |
| EFG3K Spiral Wire Hose - SAE 100R12 | A30 |
| EFG3K Spiral Wire Hose - SAE 100R12 - MegaTuff® Cover | A31 |
| Global M6K Mega6000™ Hose | A32 |
| Global M5K Mega5000™ Hose | A32 |
| Global M5K Mega5000™ Hose - MegaTuff® Cover | A33 |
| Global M5K Mega5000™ Hose - XtraTuff® Cover | A33 |
| Global M4K Mega4000™ Hose - SAE 100R19 | A34 |
| Global M4K Mega4000™ Hose - SAE 100R19 - MegaTuff® Cover | A35 |
| Global M4K Mega4000™ Hose - SAE 100R19 - XtraTuff® Cover | A36 |
| Global M4KH Mega4000™ Hose - High-Temp - SAE 100R19 | A37 |
| Global M4KH Mega4000™ Hose - High-Temp - SAE 100R19 - MegaTuff® Cover | A38 |
| Global M4KL Mega4000™ PolarFlex® Hose - SAE 100R19 | A39 |
| Global M3K Mega3000® Hose - SAE 100R17 | A39 |
| Global M3K Mega3000® Hose - SAE 100R17 - MegaTuff® Cover | A41 |
| Global M3K Mega3000® Hose - SAE 100R17 - XtraTuff® Cover | A42 |
| Global M3KH Mega3000® Hose - High-Temp - SAE 100R17 | A43 |
| Global M3KH Mega3000® Hose - High-Temp - SAE 100R17 - MegaTuff® Cover | A43 |
| MXT™ MegaSys® Wire Braid Hose - SAE 100R16 | A44 |
| M2T® MegaFlex® 2-Wire Braid Hose - SAE 100R16 | A45 |
| M2T® MegaFlex® 2-Wire Braid Hose - SAE 100R16 - MegaTuff® Cover | A46 |
| M2T® MegaFlex® 2-Wire Braid Hose - SAE 100R16 - XtraTuff® Cover | A47 |
| CM2TDL MegaFlex® Connected Dual-Line 2-Wire Braid - SAE 100R16 - XtraTuff® Cover | A48 |
| Global G2 2-Wire Braid Hose - SAE 100R2 Type AT | A48 |
| Global G2H High-Temp 2-Wire Braid Hose - SAE 100R2 Type AT | A49 |
| Global G2H High-Temp - MegaTuff® Cover - SAE 100R2 Type AT | A50 |
| Global G2XH 2-Wire Braid XTreme® Heat Hose - SAE 100R2 Type AT | A50 |
| Global G2L PolarFlex® Hose - SAE 100R2 Type AT | A51 |
| M-XP™ Million Impulse Xtra Performance Wire Braid Hose | A52 |
| Global G1 1-Wire Braid Hose - SAE 100R1 Type AT | A52 |
| Global G1H 1-Wire Braid Hose - High-Temp - SAE 100R1 Type AT | A53 |
| TH7 Hydraulic Hose - SAE 100R7 | A54 |
| TH7NC Non Conductive Hydraulic Hose - SAE 100R7 | A55 |
| TH7DL Dual Line Hydraulic Hose - SAE 100R7 | A56 |
| TH7NCDL Non Conductive Dual Line Hydraulic Hose - SAE 100R7 | A56 |
| TH7S Hydraulic Hose - SAE 100R7 | A57 |
| TH7SNC Non Conductive Hydraulic Hose - SAE 100R7 | A58 |
| TH8 Hydraulic Hose - SAE 100R8 | A58 |
| TH8NC Non Conductive Hydraulic Hose - SAE 100R8 | A59 |
| TH18 Constant Pressure Hydraulic Hose - SAE 100R18 | A59 |
| TH18NC Constant Pressure Non Conductive Hydraulic Hose - SAE 100R18 | A60 |
| G3H High-Temp 2-Fiber Braid Hose - SAE 100R3 | A61 |
| GTH High-Temp 1-Fiber Braid Hose - SAE 100R6 | A61 |
| GTHX High-Temp Fiber Spiral Hose - SAE 100R6 | A62 |
| M500 Wire Braid Hose | A63 |
| M500 Wire Braid Hose - MegaTuff® Cover | A63 |
| M500 Wire Braid Hose - XtraTuff® Cover | A64 |
| Multi Master® GMV™ MegaFlex® Return Line and Suction Hose - SAE 100R4 | A64 |
| GMV Global MegaVac® Return Line and Suction Hose - SAE 100R4 | A65 |
| RLA 1-Fiber Braid Return Line and Low Pressure Hose | A66 |
| RLC 3-Fiber Braid Return Line and Low Pressure Hose | A67 |
| MegaTech® LOC 1-Fiber Braid High-Temp Lock-On Hose | A67 |
| LOC 1-Fiber Braid Lock-On Hose | A68 |
| LOL Plus Lock-On Hose | A69 |
| AB Series Air Brake Hose | A70 |
| Heavy-Duty Green Stripe® Air Brake Hose | A71 |
| Green Stripe® Vacuum Brake Hose | A71 |
| TR500 High-Temp/Air Brake/Engine Hose | A72 |
| MegaTech® G5TB Oil-Air Return | A72 |
| MegaTech® II - SAE 100R2 Type AT - ACP | A73 |
| MegaTech® 3000 High-Temp Oil-Air Return | A74 |
| MegaTech® 1000 High-Temp Oil-Air Return | A74 |
| MegaTech® 500 High-Temp Oil-Air Return | A75 |
| MegaTech® 250 High-Temp Transmission Oil Cooler (TOC) Hose | A76 |
| C5C Hydraulic Hose - SAE 100R5 | A77 |
| C5C-XH XTreme® Heat Hose - SAE 100R5 | A78 |

| Category | Page |
|---|---|
| **Hydraulic Hose (Continued)** | |
| C5D High-Temp Multi-Fluid Hose | A79 |
| C5M Marine Fuel Line Hose | A80 |
| C5E High-Temp Flexline Hose | A80 |
| C14 PTFE Hose - SAE 100R14 Type A - Nonconductive | A81 |
| C14CT PTFE Hose - SAE 100R14 Type B - Conductive | A82 |
| PolarSeal® Hose | A83 |
| PolarSeal® II Hose | A83 |
| PS188 Power Steering Hose | A84 |
| J2AT 2-Wire Braid Jack Hose - 10,000 Static Pressure Only | A85 |
| J2AT 2-Wire Braid Jack Hose - MegaTuff® Cover - 10,000 Static Pressure Only | A85 |
| Hot Oiler 2-Wire Braid Hose | A86 |
| Hot Oiler 2-Wire Braid Hose - MegaTuff® Cover | A86 |
| RFS Red Fire Suppressant Hose | A87 |
| Plant Master® 150-200 | A87 |
| Plant Master® 250 | A89 |
| Plant Master® 300 | A90 |
| Plant Master® XTreme® 501 AR | A91 |
| Plant Master® Plus | A91 |
| Plant Master® XTreme® | A93 |
| Plant Master® XTreme® 300 AR | A94 |
| Plant Master® Plus Lock-On | A95 |
| Ag Master® | A96 |
| Clean Master® Pressure Wash | A96 |
| Clean Master® Pressure Wash Assemblies | A97 |
| LP350X Hose | A98 |
| LP350 Hose | A98 |
| Fuel Master® Delivery | A99 |
| LPG Vapor | A100 |
| Fuel Master® Curb Pump | A100 |
| Fuel Master® Diesel Curb Pump | A101 |
| **Equipment** | |
| Equipment | B1 |
| **Hose/Cplg. Selection** | |
| Hose/Cplg. Selection | C1 |
| **G8K Couplings** | |
| Caterpillar Style O-Ring Flange | D2 |
| 12G8K-12FLC | D2 |
| 16G8K-16FLC | D2 |
| Caterpillar Style O-Ring Flange - 45° Bent Tube | D2 |
| 12G8K-12FLC45-034 | D2 |
| 16G8K-16FLC45-050 | D2 |
| Caterpillar Style O-Ring Flange - 90° Bent Tube | D3 |
| 12G8K-12FLC90-070 | D3 |
| 16G8K-16FLC90-093 | D3 |
| 16G8K-16FLC90-117 | D3 |
| G8K Ferrule for G8K Spiral Hose | D3 |
| 12G8K1F | D3 |
| 16G8K1F | D3 |
| **GlobalSpiral™ Couplings** | |
| Male Pipe (NPTF - 30° Cone Seat) | E4 |
| 6GS-6MP | E4 |
| 6GS-8MP | E4 |
| 8GS-8MP | E4 |
| 8GS-12MP | E4 |
| 10GS-8MP | E4 |
| 10GS-12MP | E4 |
| 12GS-8MP | E4 |
| 12GS-12MP | E4 |
| 12GS-16MP | E4 |
| 16GS-12MP | E4 |
| 16GS-16MP | E4 |
| 16GS-20MP | E4 |
| 20GS-20MP | E4 |
| API Line Pipe Connection | E4 |
| 20GS-20API-LP | E4 |
| Male Pipe (NPTF - 30° Cone Seat) - Long Hex | E5 |
| 16GS-16MPLH | E5 |
| Male O-Ring Boss | E5 |
| 6GS-6MB | E5 |
| 8GS-8MB | E5 |

# INDEX


| Category | Page |
|---|---|
| **GlobalSpiral™ Couplings (Continued)** | |
| Male O-Ring Boss (Continued) | E5 |
| 8GS-10MB | E5 |
| 10GS-10MB | E5 |
| 10GS-12MB | E5 |
| 12GS-12MB | E5 |
| 12GS-16MB | E5 |
| 16GS-12MB | E5 |
| 16GS-16MB | E5 |
| 16GS-20MB | E5 |
| 20GS-20MB | E5 |
| Female MegaSeal® Swivel | E6 |
| 12GS-12FMX | E6 |
| 12GS-16FMX | E6 |
| 16GS-16FMX | E6 |
| 20GS-20FMX | E6 |
| Female MegaSeal® Swivel - 45° Bent Tube | E6 |
| 12GS-12FMX45-032 | E6 |
| 16GS-16FMX45-038 | E6 |
| 20GS-20FMX45-041 | E6 |
| Female MegaSeal® Swivel - 90° Bent Tube | E7 |
| 12GS-12FMX90-048 | E7 |
| 12GS-12FMX90-058 | E7 |
| 12GS-12FMX90-096 | E7 |
| 12GS-16FMX90-056 | E7 |
| 16GS-16FMX90-056 | E7 |
| 16GS-16FMX90-071 | E7 |
| Male JIC 37° Flare | E7 |
| 6GS-6MJ | E7 |
| 6GS-8MJ | E7 |
| 6GS-10MJ | E7 |
| 8GS-8MJ | E7 |
| 8GS-10MJ | E7 |
| 10GS-10MJ | E7 |
| 10GS-12MJ | E7 |
| 12GS-12MJ | E7 |
| 12GS-14MJ | E7 |
| 12GS-16MJ | E7 |
| 16GS-16MJ | E7 |
| 16GS-20MJ | E7 |
| 20GS-20MJ | E7 |
| Female JIC 37° Flare Swivel | E8 |
| 6GS-6FJX | E8 |
| 6GS-8FJX | E8 |
| 8GS-8FJX | E8 |
| 8GS-10FJX | E8 |
| 8GS-12FJX | E8 |
| 10GS-10FJXMM | E8 |
| 10GS-12FJX | E8 |
| 12GS-10FJX | E8 |
| 12GS-12FJX | E8 |
| 12GS-14FJX | E8 |
| 12GS-16FJX | E8 |
| 16GS-12FJX | E8 |
| 16GS-14FJX | E8 |
| 16GS-16FJX | E8 |
| 16GS-20FJX | E8 |
| 20GS-16FJX | E8 |
| 20GS-20FJX | E8 |
| 20GS-24FJX | E8 |
| Female JIC 37° Flare Swivel - 30° Bent Tube | E8 |
| 16GS-16FJX30M | E8 |
| Female JIC 37° Flare Swivel - 45° Bent Tube | E9 |
| 6GS-6FJX45S | E9 |
| 6GS-8FJX45S | E9 |
| 8GS-8FJX45S | E9 |
| 8GS-10FJX45S | E9 |
| 10GS-10FJXMM45-018 | E9 |
| 10GS-12FJX45S | E9 |
| 12GS-12FJX45S | E9 |
| 12GS-16FJX45S | E9 |
| 16GS-16FJX45S | E9 |
| 16GS-16FJX45M | E9 |
| 16GS-20FJX45S | E9 |
| 20GS-20FJX45-038 | E9 |
| Female JIC 37° Flare Swivel - 60° Bent Tube | E9 |
| 12GS-12FJX60-043 | E9 |

| Category | Page |
|---|---|
| **GlobalSpiral™ Couplings (Continued)** | |
| Female JIC 37° Flare Swivel - 90° Bent Tube | E10 |
| 6GS-6FJX90S | E10 |
| 6GS-6FJXMM90M | E10 |
| 6GS-6FJX90L | E10 |
| 6GS-8FJX90M | E10 |
| 6GS-8FJX90-083 | E10 |
| 8GS-8FJX90S | E10 |
| 8GS-8FJX90M | E10 |
| 8GS-8FJX90L | E10 |
| 8GS-8FJX90XL | E10 |
| 8GS-10FJX90S | E10 |
| 8GS-10FJX90M | E10 |
| 8GS-10FJX90L | E10 |
| 8GS-12FJX90S | E10 |
| 10GS-10FJXMM90-036 | E10 |
| 10GS-10FJXMM90M | E10 |
| 10GS-12FJX90M | E10 |
| 12GS-12FJX90S | E10 |
| 12GS-12FJX90M | E10 |
| 12GS-12FJX90L | E10 |
| 12GS-14FJX90-060 | E10 |
| 12GS-16FJX90S | E10 |
| 12GS-16FJX90M | E10 |
| 12GS-16FJX90L | E10 |
| 16GS-16FJX90S | E10 |
| 16GS-16FJX90M | E10 |
| 16GS-16FJX90L | E10 |
| 16GS-20FJX90L | E10 |
| 20GS-20FJX90S | E10 |
| 20GS-20FJX90M | E10 |
| 20GS-20FJX90L | E10 |
| 20GS-24FJX90M | E10 |
| Male Flat-Face O-Ring | E11 |
| 6GS-6MFFOR | E11 |
| 8GS-8MFFOR | E11 |
| 8GS-10MFFOR | E11 |
| 10GS-10MFFOR | E11 |
| 10GS-12MFFOR | E11 |
| 12GS-12MFFOR | E11 |
| 12GS-16MFFOR | E11 |
| 16GS-16MFFOR | E11 |
| 16GS-20MFFOR | E11 |
| 20GS-20MFFOR | E11 |
| Female Flat-Face O-Ring Swivel | E11 |
| 6GS-6FFORX | E11 |
| 6GS-8FFORX | E11 |
| 8GS-8FFORX | E11 |
| 8GS-10FFORX | E11 |
| 8GS-12FFORX | E11 |
| 10GS-10FFORX | E11 |
| 10GS-12FFORX | E11 |
| 12GS-10FFORX | E11 |
| 12GS-12FFORX | E11 |
| 12GS-16FFORX | E11 |
| 12GS-20FFORX | E11 |
| 16GS-12FFORX | E11 |
| 16GS-16FFORX | E11 |
| 16GS-20FFORX | E11 |
| 20GS-20FFORX | E12 |
| 20GS-24FFORX | E12 |
| Female Flat-Face O-Ring Swivel - 22 1/2° Bent Tube | E12 |
| 16GS-16FFORX22-011 | E12 |
| Female Flat-Face O-Ring Swivel - 30° Bent Tube | E12 |
| 16GS-16FFORX30-14 | E12 |
| Female Flat-Face O-Ring Swivel - 45° Bent Tube | E13 |
| 6GS-6FFORX45S | E13 |
| 6GS-8FFORX45S | E13 |
| 8GS-8FFORX45S | E13 |
| 8GS-10FFORX45S | E13 |
| 8GS-12FFORX45S | E13 |
| 10GS-10FFORX45S | E13 |
| 12GS-12FFORX45S | E13 |
| 12GS-16FFORX45S | E13 |
| 16GS-16FFORX45S | E13 |
| 16GS-20FFORX45S | E13 |
| 20GS-20FFORX45-032 | E13 |

## GlobalSpiral™ Couplings (Continued)


| Category | Page |
|---|---|
| Female Flat-Face O-Ring Swivel - 90° Bent Tube | E13 |
| 6GS-6FFORX90S | E13 |
| 6GS-6FFORX90L | E13 |
| 6GS-8FFORX90M | E13 |
| 8GS-8FFORX90S | E13 |
| 8GS-8FFORX90M | E13 |
| 8GS-8FFORX90-083 | E13 |
| 8GS-10FFORX90S | E13 |
| 8GS-10FFORX90M | E13 |
| 8GS-10FFORX90L | E13 |
| 8GS-12FFORX90S | E13 |
| 10GS-10FFORX90S | E13 |
| 10GS-10FFORX90M | E13 |
| 10GS-10FFORX90L | E13 |
| 10GS-12FFORX90S | E14 |
| 12GS-10FFORX90S | E14 |
| 12GS-12FFORX90S | E14 |
| 12GS-12FFORX90M | E14 |
| 12GS-12FFORX90L | E14 |
| 12GS-16FFORX90S | E14 |
| 12GS-16FFORX90M | E14 |
| 12GS-16FFORX90L | E14 |
| 16GS-16FFORX90S | E14 |
| 16GS-16FFORX90M | E14 |
| 16GS-16FFORX90L | E14 |
| 16GS-20FFORX90S | E14 |
| 16GS-20FFORX90M | E14 |
| 16GS-20FFORX90L | E14 |
| 20GS-20FFORX90S | E14 |
| 20GS-20FFORX90M | E14 |
| 20GS-20FFORX90L | E14 |
| 20GS-24FFORX90-064 | E14 |
| Female Flat-Face O-Ring Swivel - 135° Bent Tube | E14 |
| 12GS-16FFORX135 | E14 |
| Code 61 O-Ring Flange | E15 |
| 6GS-8FL | E15 |
| 8GS-8FL | E15 |
| 8GS-12FL | E15 |
| 8GS-16FL | E15 |
| 10GS-12FL | E15 |
| 12GS-8FL | E15 |
| 12GS-12FL | E15 |
| 12GS-16FL | E15 |
| 12GS-20FL | E15 |
| 16GS-12FL | E15 |
| 16GS-16FL | E15 |
| 16GS-20FL | E15 |
| 16GS-24FL | E15 |
| 20GS-16FL | E15 |
| 20GS-20FL | E15 |
| 20GS-24FL | E15 |
| 20GS-32FL | E15 |
| Code 61 Komatsu Style O-Ring Flange | E15 |
| 8GS-10FLK | E15 |
| 10GS-10FLK | E15 |
| 12GS-10FLK | E15 |
| Code 61 O-Ring Flange Long Neck | E16 |
| 12GS-12FLL | E16 |
| 16GS-16FLL | E16 |
| 20GS-20FLL | E16 |
| Code 61 O-Ring Flange - 22 1/2° Bent Tube | E16 |
| 8GS-8FL22M | E16 |
| 12GS-12FL22M | E16 |
| 12GS-16FL22M | E16 |
| 16GS-16FL22M | E16 |
| 16GS-20FL22M | E16 |
| 20GS-20FL22M | E16 |
| 20GS-24FL22M | E16 |
| Code 61 O-Ring Flange - 30° Bent Tube | E17 |
| 8GS-12FL30M | E17 |
| 12GS-12FL30M | E17 |
| 12GS-16FL30M | E17 |
| 16GS-16FL30M | E17 |
| 16GS-20FL30M | E17 |
| 20GS-20FL30M | E17 |
| 20GS-24FL30M | E17 |
| Code 61 O-Ring Flange - 45° Bent Tube | E17 |
| 6GS-8FL45M | E17 |
| 8GS-8FL45M | E17 |
| 8GS-12FL45M | E17 |
| 10GS-12FL45M | E17 |
| 12GS-12FL45M | E17 |
| 12GS-16FL45S | E17 |
| 16GS-16FL45M | E17 |
| 16GS-20FL45M | E17 |
| 20GS-16FL45M | E17 |
| 20GS-20FL45S | E17 |
| 20GS-24FL45S | E17 |
| Code 61 Komatsu Style O-Ring Flange - 45° Bent Tube | E18 |
| 10GS-10FLK45-026 | E18 |
| Code 61 O-Ring Flange - 60° Bent Tube | E18 |
| 8GS-8FL60M | E18 |
| 12GS-12FL60M | E18 |
| 12GS-16FL60M | E18 |
| 16GS-16FL60M | E18 |
| 16GS-20FL60M | E18 |
| 20GS-20FL60M | E18 |
| 20GS-24FL60M | E18 |
| Code 61 O-Ring Flange - 67 1/2° Bent Tube | E19 |
| 8GS-12FL67-032 | E19 |
| 12GS-12FL67M | E19 |
| 12GS-16FL67M | E19 |
| 16GS-16FL67M | E19 |
| 16GS-20FL67M | E19 |
| 20GS-20FL67M | E19 |
| 20GS-24FL67S | E19 |
| Code 61 O-Ring Flange - 90° Bent Tube | E19 |
| 6GS-8FL90M | E19 |
| 8GS-8FL90M | E19 |
| 8GS-8FL90L | E19 |
| 8GS-12FL90M | E19 |
| 10GS-12FL90M | E19 |
| 12GS-8FL90-050 | E19 |
| 12GS-12FL90M | E19 |
| 12GS-12FL90-100 | E19 |
| 12GS-12FL90-125 | E20 |
| 12GS-16FL90S | E20 |
| 12GS-16FL90M | E20 |
| 12GS-16FL90-080 | E20 |
| 12GS-16FL90-178 | E20 |
| 12GS-20FL90-054 | E20 |
| 12GS-20FL90-125 | E20 |
| 16GS-12FL90M | E20 |
| 16GS-12FL90 | E20 |
| 16GS-16FL90S | E20 |
| 16GS-16FL90M | E20 |
| 16GS-16FL90-120 | E20 |
| 16GS-16FL90-150 | E20 |
| 16GS-16FL90-210 | E20 |
| 16GS-20FL90S | E20 |
| 16GS-20FL90M | E20 |
| 16GS-20FL90-120 | E20 |
| 16GS-24FL90-060 | E20 |
| 16GS-24FL90S | E20 |
| 20GS-16FL90M | E20 |
| 20GS-16FL90-215 | E20 |
| 20GS-20FL90S | E20 |
| 20GS-20FL90M | E20 |
| 20GS-20FL90-168 | E20 |
| 20GS-24FL90S | E20 |
| 20GS-24FL90-118 | E20 |
| Code 61 Komatsu Style O-Ring Flange - 90° Bent Tube | E20 |
| 10GS-10FLK90-055 | E20 |
| 12GS-10FLK90-055 | E20 |
| Code 61 O-Ring Flange - 100° Bent Tube | E21 |
| 12GS-16FL100-059 | E21 |
| Code 61 O-Ring Flange - 110° Bent Tube | E21 |
| 12GS-12FL110-064 | E21 |
| 16GS-16FL110-073 | E21 |
| 16GS-20FL110-073 | E21 |
| 20GS-20FL110-080 | E21 |
| 20GS-24FL110-080 | E21 |

# INDEX


| Category | Page |
|---|---|
| **GlobalSpiral™ Couplings (Continued)** | |
| Code 61 O-Ring Flange - 135° Bent Tube | E22 |
| 12GS-12FL135-070 | E22 |
| Code 62 O-Ring Flange Heavy | E22 |
| 8GS-8FLH | E22 |
| 8GS-12FLH | E22 |
| 10GS-8FLH | E22 |
| 10GS-12FLH | E22 |
| 12GS-12FLH | E22 |
| 12GS-16FLH | E22 |
| 16GS-12FLH | E22 |
| 16GS-16FLH | E22 |
| 16GS-20FLH | E22 |
| 20GS-16FLH | E22 |
| 20GS-20FLH | E22 |
| 20GS-24FLH | E22 |
| Code 62 O-Ring Flange Heavy - 22 1/2° Bent Tube | E23 |
| 12GS-16FLH22M | E23 |
| 16GS-16FLH22M | E23 |
| 16GS-20FLH22M | E23 |
| 20GS-20FLH22M | E23 |
| 20GS-24FLH22M | E23 |
| Code 62 O-Ring Flange Heavy - 30° Bent Tube | E23 |
| 12GS-12FLH30M | E23 |
| 12GS-16FLH30M | E23 |
| 16GS-16FLH30M | E23 |
| 16GS-20FLH30M | E23 |
| 20GS-20FLH30M | E23 |
| 20GS-24FLH30M | E23 |
| Code 62 O-Ring Flange Heavy - 45° Bent Tube | E24 |
| 8GS-8FLH45M | E24 |
| 8GS-12FLH45M | E24 |
| 10GS-12FLH45M | E24 |
| 12GS-8FLH45M | E24 |
| 12GS-12FLH45M | E24 |
| 12GS-16FLH45M | E24 |
| 16GS-12FLH45M | E24 |
| 16GS-16FLH45M | E24 |
| 16GS-20FLH45M | E24 |
| 20GS-16FLH45M | E24 |
| 20GS-20FLH45M | E24 |
| 20GS-24FLH45M | E24 |
| Code 62 O-Ring Flange Heavy - 60° Bent Tube | E24 |
| 12GS-12FLH60M | E24 |
| 12GS-16FLH60M | E24 |
| 16GS-16FLH60M | E24 |
| 20GS-20FLH60M | E24 |
| 20GS-24FLH60M | E24 |
| Code 62 O-Ring Flange Heavy - 67 1/2° Bent Tube | E25 |
| 16GS-16FLH67M | E25 |
| Code 62 O-Ring Flange Heavy - 90° Bent Tube | E25 |
| 8GS-8FLH90M | E25 |
| 8GS-8FLH90-080 | E25 |
| 8GS-12FLH90M | E25 |
| 10GS-8FLH90M | E25 |
| 10GS-12FLH90M | E25 |
| 12GS-12FLH90M | E25 |
| 12GS-12FLH90-100 | E25 |
| 12GS-12FLH90-122 | E25 |
| 12GS-16FLH90S | E25 |
| 12GS-16FLH90M | E25 |
| 12GS-16FLH90-140 | E25 |
| 12GS-20FLH90M | E25 |
| 16GS-12FLH90M | E25 |
| 16GS-16FLH90S | E25 |
| 16GS-16FLH90M | E26 |
| 16GS-16FLH90-120 | E26 |
| 16GS-16FLH90-090 | E26 |
| 16GS-20FLH90S | E26 |
| 16GS-20FLH90M | E26 |
| 16GS-24FLH90S | E26 |
| 20GS-16FLH90S | E26 |
| 20GS-16FLH90M | E26 |
| 20GS-16FLH90-100 | E26 |
| 20GS-20FLH90-076 | E26 |
| 20GS-20FLH90M | E26 |
| 20GS-20FLH90-120 | E26 |

| Category | Page |
|---|---|
| **GlobalSpiral™ Couplings (Continued)** | |
| Code 62 O-Ring Flange Heavy - 90° Bent Tube (Continued) | E26 |
| 20GS-20FLH90-152 | E26 |
| 20GS-24FLH90S | E26 |
| Code 62 O-Ring Flange Heavy - 110° Bent Tube | E26 |
| 12GS-12FLH110-064 | E26 |
| Caterpillar Style O-Ring Flange | E27 |
| 12GS-12FLC | E27 |
| 12GS-16FLC | E27 |
| 16GS-16FLC | E27 |
| 16GS-20FLC | E27 |
| 20GS-20FLC | E27 |
| 20GS-24FLC | E27 |
| Caterpillar Style O-Ring Flange - 22 1/2° Bent Tube | E27 |
| 12GS-12FLC22-016 | E27 |
| 16GS-16FLC22-017 | E27 |
| 16GS-20FLC22-017 | E27 |
| 20GS-20FLC22-017 | E27 |
| 20GS-24FLC22-017 | E27 |
| Caterpillar Style O-Ring Flange - 30° Bent Tube | E28 |
| 12GS-12FLC30-022 | E28 |
| 12GS-16FLC30-022 | E28 |
| 16GS-16FLC30-023 | E28 |
| 16GS-20FLC30-023 | E28 |
| 20GS-20FLC30-024 | E28 |
| 20GS-24FLC30-024 | E28 |
| Caterpillar Style O-Ring Flange - 45° Bent Tube | E28 |
| 12GS-12FLC45-035 | E28 |
| 12GS-12FLC45-066 | E28 |
| 12GS-16FLC45-035 | E28 |
| 16GS-16FLC45-037 | E28 |
| 16GS-20FLC45-037 | E28 |
| 20GS-20FLC45-037 | E28 |
| 20GS-24FLC45-037 | E28 |
| Caterpillar Style O-Ring Flange - 60° Bent Tube | E29 |
| 12GS-16FLC60-048 | E29 |
| 16GS-16FLC60-050 | E29 |
| 16GS-20FLC60-050 | E29 |
| 20GS-20FLC60-052 | E29 |
| 20GS-24FLC60-052 | E29 |
| Caterpillar Style O-Ring Flange - 67 1/2° Bent Tube | E29 |
| 16GS-16FLC67-057 | E29 |
| 16GS-20FLC67-057 | E29 |
| 20GS-20FLC67-059 | E29 |
| 20GS-24FLC67-059 | E29 |
| Caterpillar Style O-Ring Flange - 90° Bent Tube | E30 |
| 12GS-12FLC90-068 | E30 |
| 12GS-12FLC90-128 | E30 |
| 12GS-16FLC90-068 | E30 |
| 16GS-16FLC90-074 | E30 |
| 16GS-16FLC90-132 | E30 |
| 16GS-20FLC90-074 | E30 |
| 16GS-20FLC90-132 | E30 |
| 20GS-20FLC90-077 | E30 |
| 20GS-20FLC90-150 | E30 |
| 20GS-24FLC90-077 | E30 |
| 20GS-24FLC90-150 | E30 |
| Female French GAZ (Poclain) 24° High Pressure Flange | E30 |
| 8GS-17FPFL | E30 |
| 10GS-21FPFL | E30 |
| 12GS-27FPFL | E30 |
| 16GS-34FPFL | E30 |
| 20GS-42FPFL | E30 |
| Male French GAZ (Poclain) 24° High Pressure Flange | E31 |
| 8GS-17MPFL | E31 |
| 10GS-21MPFL | E31 |
| 12GS-27MPFL | E31 |
| 16GS-34MPFL | E31 |
| 20GS-42MPFL | E31 |
| Male French GAZ (Poclain) 24° High Pressure Flange - 90° Bent Tube | E31 |
| 10GS-21MPFL90 | E31 |
| 20GS-42MPFL90 | E31 |
| Hose Length Extender Caterpillar | E31 |
| 12GS-12HLEC | E31 |
| 16GS-16HLEC | E31 |

## GlobalSpiral™ Couplings (Continued)


| Category | Page |
|---|---|
| Hose Length Extender | E32 |
| 8GS-8HLE | E32 |
| 12GS-12HLE | E32 |
| 16GS-16HLE | E32 |
| 20GS-20HLE | E32 |
| Hose Length Extender - 45° Bent Tube | E32 |
| 20GS-20HLE45-103 | E32 |
| Hose Length Extender - 90° Bent Tube | E33 |
| 8GS-8HLE90-086 | E33 |
| 12GS-12HLE90 | E33 |
| 16GS-16HLE90-127 | E33 |
| 20GS-20HLE90-155 | E33 |
| Male DIN 24° Cone - Light Series | E33 |
| 6GS-12MDL | E33 |
| 8GS-15MDL | E33 |
| 12GS-22MDL | E33 |
| 16GS-28MDL | E33 |
| Female DIN 24° Cone Swivel - Light Series with O-Ring | E34 |
| 6GS-12FDLORX | E34 |
| 8GS-15FDLORX | E34 |
| 10GS-18FDLORX | E34 |
| 12GS-22FDLORX | E34 |
| 12GS-28FDLORX | E34 |
| 16GS-28FDLORX | E34 |
| 20GS-35FDLORX | E34 |
| Female DIN 24° Cone Swivel - Light Series with O-Ring - 45° Bent Tube | E34 |
| 8GS-15FDLORX45 | E34 |
| 12GS-22FDLORX45 | E34 |
| 16GS-28FDLORX45 | E34 |
| Female DIN 24° Cone Swivel - Light Series with O-Ring - 90° Bent Tube | E35 |
| 6GS-12FDLORX90 | E35 |
| 8GS-15FDLORX90 | E35 |
| 10GS-18FDLORX90 | E35 |
| 12GS-22FDLORX90M | E35 |
| 16GS-28FDLORX90M | E35 |
| Male French GAZ | E35 |
| 8GS-17MFG | E35 |
| 12GS-21MFG | E35 |
| 12GS-27MFG | E35 |
| 16GS-34MFG | E35 |
| Female French GAZ Swivel (Female Kobelco) | E36 |
| 8GS-17FFGX | E36 |
| 10GS-21FFGX | E36 |
| 12GS-21FFGX | E36 |
| 12GS-27FFGX | E36 |
| 16GS-27FFGX | E36 |
| 16GS-34FFGX | E36 |
| Female French GAZ Swivel - 90° Bent Tube (Female Kobelco) | E36 |
| 10GS-21FFGX90 | E36 |
| 12GS-21FFGX90 | E36 |
| 12GS5K-27FFGX90-060 | E36 |
| 16GS-27FFGX90 | E36 |
| 16GS5K-34FFGX90-065 | E36 |
| Male DIN 24° Cone - Heavy Series | E37 |
| 6GS-12MDH | E37 |
| 6GS-14MDH | E37 |
| 8GS-16MDH | E37 |
| 10GS-20MDH | E37 |
| 12GS-20MDH | E37 |
| 12GS-25MDH | E37 |
| 12GS-30MDH | E37 |
| 16GS-25MDH | E37 |
| 16GS-30MDH | E37 |
| 20GS-38MDH | E37 |
| Female DIN 24° Cone Swivel - Heavy Series with O-Ring | E37 |
| 6GS-10FDHORX | E37 |
| 6GS-12FDHORX | E37 |
| 6GS-14FDHORX | E37 |
| 8GS-12FDHORX | E37 |
| 8GS-14FDHORX | E37 |
| 8GS-16FDHORX | E37 |
| 8GS-20FDHORX | E37 |
| 10GS-20FDHORX | E37 |
| 10GS-25FDHORX | E37 |


## GlobalSpiral™ Couplings (Continued)


| Category | Page |
|---|---|
| Female DIN 24° Cone Swivel - Heavy Series with O-Ring (Continued) | E37 |
| 12GS-20FDHORX | E37 |
| 12GS-25FDHORX | E37 |
| 16GS-25FDHORX | E37 |
| 16GS-30FDHORX | E37 |
| 16GS-38FDHORX | E37 |
| 20GS-38FDHORX | E37 |
| Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 45° Bent Tube | E38 |
| 6GS-12FDHORX45 | E38 |
| 6GS-14FDHORX45 | E38 |
| 8GS-16FDHORX45 | E38 |
| 10GS-20FDHORX45 | E38 |
| 12GS-20FDHORX45 | E38 |
| 12GS-25FDHORX45M | E38 |
| 16GS-25FDHORX45M | E38 |
| 16GS-30FDHORX45 | E38 |
| 20GS-38FDHORX45M | E38 |
| Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 90° Bent Tube | E38 |
| 6GS-12FDHORX90 | E38 |
| 6GS-14FDHORX90 | E38 |
| 8GS-16FDHORX90M | E38 |
| 10GS-20FDHORX90M | E38 |
| 12GS-20FDHORX90 | E38 |
| 12GS-25FDHORX90M | E38 |
| 16GS-25FDHORX90 | E38 |
| 16GS-30FDHORX90M | E38 |
| 20GS-38FDHORX90M | E39 |
| Male Kobelco (Male French GAZ) | E39 |
| 12GS-22MKB | E39 |
| 12GS-28MKB | E39 |
| 16GS-28MKB | E39 |
| 16GS-35MKB | E39 |
| Male British Standard Pipe Parallel | E39 |
| 6GS-6MBSPP | E39 |
| 8GS-8MBSPP | E39 |
| 10GS-10MBSPP | E39 |
| 10GS-12MBSPP | E39 |
| 12GS-12MBSPP | E39 |
| 16GS-16MBSPP | E39 |
| 20GS-20MBSPP | E39 |
| Female British Standard Parallel Pipe O-Ring Swivel | E40 |
| 6GS-6FBSPORX | E40 |
| 6GS-8FBSPORX | E40 |
| 8GS-8FBSPORX | E40 |
| 10GS-10FBSPORX | E40 |
| 10GS-12FBSPORX | E40 |
| 12GS-12FBSPORX | E40 |
| 12GS-16FBSPORX | E40 |
| 16GS-16FBSPORX | E40 |
| 16GS-20FBSPORX | E40 |
| 20GS-20FBSPORX | E40 |
| Female British Standard Parallel Pipe O-Ring Swivel - 45° Bent Tube | E40 |
| 6GS-6FBSPORX45 | E40 |
| 8GS-8FBSPORX45M | E40 |
| 10GS-10FBSPORX45 | E40 |
| 12GS-12FBSPORX45 | E40 |
| 16GS-16FBSPORX45M | E40 |
| 20GS-20FBSPORX45M | E40 |
| Female British Standard Parallel Pipe O-Ring Swivel - 90° Bent Tube | E41 |
| 6GS-6FBSPORX90 | E41 |
| 8GS-8FBSPORX90M | E41 |
| 10GS-10FBSPORX90 | E41 |
| 12GS-12FBSPORX90 | E41 |
| 16GS-16FBSPORX90 | E41 |
| 20GS-20FBSPORX90M | E41 |
| Female British Standard Parallel Pipe O-Ring Swivel - 90° Block | E41 |
| 12GS-12FBSPORX90BL | E41 |
| Female British Flat-Face Swivel | E42 |
| 16GS-16FBFFX | E42 |
| Female Komatsu Style Japanese Metric Swivel | E42 |
| 8GS-8FKX | E42 |
| 10GS-10FKX | E42 |
| 12GS-12FKX | E42 |
| 16GS-16FKX | E42 |

# INDEX


| Category | Page |
|---|---|
| **GlobalSpiral™ Couplings (Continued)** | |
| Female Japanese Industrial Standard 30° Flare Swivel | E42 |
| 12GS-12FJISX | E42 |
| 16GS-16FJISX | E42 |
| 20GS-20FJISX | E43 |
| GS Ferrule for Wire Braid Hose | E43 |
| 6GS1F-1 | E43 |
| 6GS1F-2 | E43 |
| 8GS1F-2 | E43 |
| 10GS1F-2 | E43 |
| 12GS1F-2 | E43 |
| 16GS1F-2 | E43 |
| 20GS1F-2 | E43 |
| GS Ferrule for 4-Spiral Hose | E43 |
| 6GS1F-4 | E43 |
| 8GS1F-4 | E43 |
| 10GS1F-4 | E43 |
| 12GS1F-4 | E43 |
| 16GS1F-4 | E43 |
| 20GS1F-4 | E43 |
| GS Ferrule for 6-Spiral Hose | E44 |
| 20GS1F-6 | E44 |
| GS Ferrule for ID5K Hose | E44 |
| 8GSID1F-4 | E44 |
| 10GSID1F-4 | E44 |
| 12GSID1F-4 | E44 |
| 16GSID1F-4 | E44 |
| 1 1/4" Special One-Piece Couplings - Male Pipe (NPTF - 30° Cone Seat) | E44 |
| 20MGS-20MP | E44 |
| 1 1/4" Special One-Piece Couplings - Male JIC 37° Flare | E45 |
| 20MGS-20MJ | E45 |
| 1 1/4" Special One-Piece Couplings - Female JIC 37° Flare Swivel | E45 |
| 20MGS-20FJX | E45 |
| 1 1/4" Special One-Piece Couplings - Female JIC 37° Flare Swivel - 90° Bent Tube | E46 |
| 20MGS-20FJX90M-078 | E46 |
| 1 1/4" Special One-Piece Couplings - Female Flat-Face O-Ring Swivel | E46 |
| 20MGS-20FFORX | E46 |
| 1 1/4" Special One-Piece Couplings - Female Flat-Face O-Ring Swivel - 90° Bent Tube | E47 |
| 20MGS-20FFORX90M | E47 |
| 1 1/4" Special One-Piece Couplings - Code 61 O-Ring Flange | E47 |
| 20MGS-20FL | E47 |
| 1 1/4" Special One-Piece Couplings - Code 61 O-Ring Flange - 45° Bent Tube | E48 |
| 20MGS-20FL45S-032 | E48 |
| 1 1/4" Special One-Piece Couplings - Code 61 O-Ring Flange - 90° Bent Tube | E48 |
| 20MGS-20FL90M-090 | E48 |
| 1 1/4" Special One-Piece Couplings - Code 62 O-Ring Flange | E49 |
| 20MGS-20FLH | E49 |
| 1 1/4" Special One-Piece Couplings - Male DIN 24° Cone - Heavy Series | E49 |
| 20MGS-38MDH | E49 |
| 1 1/4" Special One-Piece Couplings - Female DIN 24° Cone Swivel - Heavy Series with O-Ring | E49 |
| 20MGS-38FDHORX | E49 |
| 1 1/4" Special One-Piece Couplings - Female British Standard Pipe Parallel O-Ring Swivel | E50 |
| 20MGS-20FBSPORX | E50 |
| **GlobalSpiral™ Plus Couplings** | |
| Male Pipe (NPTF - 30° Cone Seat) | E51 |
| 24GSP-24MP | E51 |
| 32GSP-32MP | E51 |
| API Line Pipe Connection | E51 |
| 24GSP-24API-LP | E51 |
| 32GSP-32MPAPI | E51 |
| Male Pipe (NPTF - 30° Cone Seat) - Long Hex | E51 |
| 24GSP-24MPLH | E51 |
| Male JIC 37° Flare | E52 |
| 24GSP-20MJ | E52 |
| 24GSP-24MJ | E52 |
| 32GSP-32MJ | E52 |
| Female JIC 37° Flare Swivel | E52 |
| 24GSP-24FJX | E52 |

| Category | Page |
|---|---|
| **GlobalSpiral™ Plus Couplings (Continued)** | |
| Female JIC 37° Flare Swivel (Continued) | E52 |
| 24GSP-32FJX | E52 |
| 32GSP-32FJX | E52 |
| Female JIC 37° Flare Swivel - 45° Bent Tube | E52 |
| 24GSP-24FJX45-050 | E52 |
| Female JIC 37° Flare Swivel - 90° Bent Tube | E53 |
| 24GSP-24FJX90-089 | E53 |
| 24GSP-24FJX90-118 | E53 |
| 32GSP-32FJX90M | E53 |
| Male Flat-Face O-Ring | E53 |
| 24GSP-24MFFOR | E53 |
| Female Flat-Face O-Ring Swivel | E53 |
| 24GSP-24FFORX | E53 |
| Female Flat-Face O-Ring Swivel - 45° Bent Tube | E54 |
| 24GSP-24FFORX45-036 | E54 |
| Female Flat-Face O-Ring Swivel - 90° Bent Tube | E54 |
| 24GSP-24FFORX90M | E54 |
| 24GSP-24FFORX90L | E54 |
| Code 61 O-Ring Flange | E55 |
| 24GSP-20FL | E55 |
| 24GSP-24FL | E55 |
| 24GSP-32FL | E55 |
| 32GSP-24FL | E55 |
| 32GSP-32FL | E55 |
| 32GSP-40FL | E55 |
| Code 61 O-Ring Flange - 22 1/2° Bent Tube | E55 |
| 24GSP-24FL22M | E55 |
| 24GSP-32FL22M | E55 |
| 32GSP-32FL22M | E55 |
| Code 61 O-Ring Flange - 30° Bent Tube | E56 |
| 24GSP-24FL30S | E56 |
| 24GSP-32FL30M | E56 |
| 32GSP-32FL30M | E56 |
| Code 61 O-Ring Flange - 45° Bent Tube | E56 |
| 24GSP-20FL45S | E56 |
| 24GSP-24FL45S | E56 |
| 24GSP-32FL45S | E56 |
| 32GSP-24FL45S | E56 |
| 32GSP-32FL45-066 | E56 |
| Code 61 O-Ring Flange - 60° Bent Tube | E57 |
| 24GSP-24FL60S | E57 |
| 24GSP-32FL60S | E57 |
| 32GSP-32FL60S | E57 |
| Code 61 O-Ring Flange - 67 1/2° Bent Tube | E57 |
| 24GSP-24FL67S | E57 |
| 24GSP-32FL67S | E57 |
| 32GSP-32FL67S | E57 |
| Code 61 O-Ring Flange - 90° Bent Tube | E58 |
| 24GSP-20FL90S | E58 |
| 24GSP-24FL90S | E58 |
| 24GSP-24FL90M | E58 |
| 24GSP-24FL90-148 | E58 |
| 24GSP-32FL90S | E58 |
| 24GSP-32FL90-080 | E58 |
| 24GSP-32FL90-170 | E58 |
| 32GSP-24FL90S | E58 |
| 32GSP-32FL90-114 | E58 |
| 32GSP-32FL90-165 | E58 |
| 32GSP-32FL90-200 | E58 |
| 32GSP-40FL90-110 | E58 |
| Code 61 O-Ring Flange - 110° Bent Tube | E58 |
| 24GSP-24FL110-094 | E58 |
| 32GSP-32FL110-140 | E58 |
| Code 61 O-Ring Flange - 120° Bent Tube | E59 |
| 24GSP-24FL120-119 | E59 |
| Code 61 O-Ring Flange - 125° Bent Tube | E59 |
| 32GSP-32FL125-150 | E59 |
| Code 62 O-Ring Flange Heavy | E60 |
| 24GSP-24FLH | E60 |
| 24GSP-32FLH | E60 |
| 32GSP-32FLH | E60 |

Category — Page

## GlobalSpiral™ Plus Couplings (Continued)

Code 62 O-Ring Flange Heavy - 45° Bent Tube E60
24GSP-24FLH45M E60
24GSP-32FLH45S E60
32GSP-32FLH45-066 E60

Code 62 O-Ring Flange Heavy - 90° Bent Tube E61
24GSP-24FLH90-094 E61
24GSP-32FLH90S E61
32GSP-32FLH90M E61

Code 61 Flange without O-Ring Groove E61
24GSP-24FLFF E61

Hose Length Extender E61
24GSP-24HLE E61
32GSP-32HLE E62

Hose Length Extender - 90° Bent Tube E62
24GSP-24HLE90-182 E62

Male DIN 24° Cone - Light Series E62
24GSP-42MDL E62

Female DIN 24° Cone Swivel - Light Series with O-Ring E63
24GSP-42FDLORX E63
32GSP-42FDLORX E63

Female DIN 24° Cone Swivel - Light Series with O-Ring - 45° Bent Tube E63
24GSP-42FDLORX45 E63

Female DIN 24° Cone Swivel - Light Series with O-Ring - 90° Bent Tube E63
24GSP-42FDLORX90 E63

Female DIN 24° Cone Swivel - Heavy Series with O-Ring E64
24GSP-38FDHORX E64

Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 90° Bent Tube E64
24GSP-38FDHORX90 E64

Male British Standard Pipe Tapered E64
24GSP-24MBSPT E64

Female British Standard Parallel Pipe O-Ring Swivel E65
24GSP-24FBSPORX E65
32GSP-32FBSPORX E65

Female British Standard Parallel Pipe O-Ring Swivel - 45° Bent Tube E65
24GSP-24FBSPORX45 E65
32GSP-32FBSPORX45 E65

Female British Standard Parallel Pipe O-Ring Swivel - 90° Bent Tube E66
24GSP-24FBSPORX90 E66
32GSP-32FBSPORX90 E66

Female Komatsu Style Japanese Metric Swivel E66
24GSP-24FKX E66

Female Japanese Industrial Standard 30° Flare Swivel E67
24GSP-24FJISX E67

GSP Ferrule for Wire Braid Hose E67
24GSP1F-2 E67
32GSP1F-2 E67

GSP Ferrule for 4-Spiral Hose E67
24GSP1F-4 E67
32GSP1F-4 E67

## GlobalSpiral™ MAX Pressure Couplings

Male Pipe (NPTF - 30° Cone Seat) E68
24GSM-24MP E68
32GSM-32MP E68

API Line Pipe Connection E68
24GSM-24API-LP E68
32GSM-32API-LP E68
40GSM-40API-LP E68
48GSM-48API-LP E68

Male JIC 37° Flare E68
24GSM-24MJ E68
32GSM-32MJ E68

Female JIC 37° Flare Swivel E69
24GSM-24FJX E69
32GSM-32FJX E69

Female JIC 37° Flare Swivel - 45° Bent Tube E69
24GSM-24FJX45-034 E69

Category — Page

## GlobalSpiral™ MAX Pressure Couplings (Continued)

Female JIC 37° Flare Swivel - 90° Bent Tube E69
24GSM-24FJX90M E69

Female Flat-Face Swivel E70
24GSM4K-24FFORX E70
32GSM-32FFORX E70

Female Flat-Face Swivel - 45° Bent Tube E70
24GSM4K-24FFORX45-038 E70

Female Flat-Face Swivel - 90° Bent Tube E70
24GSM4K-24FFORX90M E70

Code 61 O-Ring Flange E71
24GSM-24FL E71
24GSM-32FL E71
32GSM-32FL E71
40GSM-40FL E71

Code 61 O-Ring Flange - 30° Bent Tube E71
24GSM-24FL30M E71

Code 61 O-Ring Flange - 45° Bent Tube E72
24GSM-24FL45M E72
24GSM-32FL45S E72
32GSM-32FL45M E72

Code 61 O-Ring Flange - 60° Bent Tube E72
24GSM-24FL60M E72

Code 61 O-Ring Flange - 90° Bent Tube E73
24GSM-24FL90S E73
32GSM-32FL90-130 E73

Code 62 O-Ring Flange Heavy E73
24GSM-20FLH E73
24GSM-24FLH E73
24GSM-32FLH E73
32GSM-24FLH E73
32GSM-32FLH E73

Code 62 O-Ring Flange Heavy - 22° Bent Tube E74
24GSM-24FLH22M E74
24GSM-24FLH20-024 E74

Code 62 O-Ring Flange Heavy - 30° Bent Tube E74
24GSM-24FLH30M E74
24GSM-24FLH30-28 E74
32GSM-32FLH30-040 E74

Code 62 O-Ring Flange Heavy - 45° Bent Tube E74
24GSM-24FLH45M E74
24GSM-32FLH45M E74
32GSM-32FLH45-063 E75

Code 62 O-Ring Flange Heavy - 60° Bent Tube E75
24GSM-24FLH60M E75
32GSM-32FLH60M E75

Code 62 O-Ring Flange Heavy - 90° Bent Tube E75
24GSM-24FLH90-094 E75
24GSM-24FLH90-150 E75
24GSM-32FLH90S E75
32GSM-32FLH90S E75
32GSM-32FLH90M E75
32GSM-32FLH90-159 E75

Code 62 O-Ring Flange Heavy with Captive Flange E76
24GSM-24FLHCFM E76
32GSM-32FLHCFM E76

Code 62 O-Ring Flange Heavy with Captive Flange - 45° Bent Tube E76
24GSM-24FLHCFM45M E76
32GSM-32FLHCFM45-063 E76

Code 62 O-Ring Flange Heavy with Captive Flange - 90° Bent Tube E76
24GSM-24FLHCFM90-094 E76
32GSM-32FLHCFM90-120 E77

Code 62 O-Ring Flange Heavy Captive Flange Metric Bolts E77
40GSM-40FLHCFM E77
48GSM-48FLHCFM E77

Caterpillar Style O-Ring Flange E77
24GSM-24FLC E77
24GSM-24FLCL E77
24GSM-32FLC E77
32GSM-32FLC E77

# INDEX


| Category | Page |
|---|---|
| **GlobalSpiral™ MAX Pressure Couplings (Continued)** | |
| Caterpillar Style O-Ring Flange - 22° Bent Tube | E78 |
| 24GSM-24FLC22-017 | E78 |
| 24GSM-32FLC22-022 | E78 |
| Caterpillar Style O-Ring Flange - 30° Bent Tube | E78 |
| 24GSM-24FLC30-023 | E78 |
| 24GSM-32FLC30-035 | E78 |
| 32GSM-32FLC30-035 | E78 |
| Caterpillar Style O-Ring Flange - 45° Bent Tube | E79 |
| 24GSM-24FLC45-039 | E79 |
| 24GSM-32FLC45-059 | E79 |
| 32GSM-32FLC45-064 | E79 |
| Caterpillar Style O-Ring Flange - 60° Bent Tube | E79 |
| 24GSM-24FLC60-055 | E79 |
| 24GSM-32FLC60-087 | E79 |
| 32GSM-32FLC60-083 | E79 |
| Caterpillar Style O-Ring Flange - 90° Bent Tube | E80 |
| 24GSM-24FLC90-087 | E80 |
| 24GSM-32FLC90-140 | E80 |
| 32GSM-32FLC90-130 | E80 |
| Hose Length Extender | E80 |
| 32GSM-32HLE | E80 |
| 40GSM-40HLE | E80 |
| 48GSM-48HLE | E80 |
| Hose Length Extender for Caterpillar with Clamping Area | E81 |
| 24GSM-24HLEC | E81 |
| Female DIN 24° Cone Swivel - Heavy Series with O-Ring | E81 |
| 24GSM-38FDHORX | E81 |
| Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 45° Bent Tube | E81 |
| 24GSM-38FDHORX45 | E81 |
| Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 90° Bent Tube | E82 |
| 24GSM-38FDHORX90 | E82 |
| Male British Standard Pipe Parallel | E82 |
| 24GSM-24MBSPP | E82 |
| 32GSM-32MBSPP | E82 |
| Female British Standard Parallel Pipe O-Ring Swivel | E82 |
| 24GSM-24FBSPORX | E82 |
| 32GSM-32FBSPORX | E82 |
| Female British Standard Parallel Pipe O-Ring Swivel - 45° Bent Tube | E83 |
| 24GSM-24FBSPORX45 | E83 |
| 32GSM-32FBSPORX45 | E83 |
| Female British Standard Parallel Pipe O-Ring Swivel - 90° Bent Tube | E83 |
| 24GSM-24FBSPORX90 | E83 |
| 32GSM-32FBSPORX90 | E83 |
| ISO 6164 4-bolt Square Heavy Captive Flange | E83 |
| 40GSM-63FLSHCF | E83 |
| 48GSM-80FLSHCF | E83 |
| GSM Butt Weld | E84 |
| 40GSM-40XXSBW | E84 |
| 48GSM-48XXSBW | E84 |
| **Stainless Steel Spiral Couplings** | |
| Male Pipe (NPTF - 30° Cone Seat) | F2 |
| 6S-6MP-SS | F2 |
| 8S-8MP-SS | F2 |
| 12S-12MP-SS | F2 |
| 16S-16MP-SS | F2 |
| 20S-20MP-SS | F2 |
| API Line Pipe Connection | F2 |
| 24S-24MPAPI-SS | F2 |
| Female JIC 37° Flare Swivel | F2 |
| 6S-6FJX-SS | F2 |
| 8S-8FJSX-SS | F3 |
| 10S-10FJX-SS | F3 |
| 12S-12FJX-SS | F3 |
| 16S-16FJX-SS | F3 |
| 20S-20FJX-SS | F3 |
| 24S-24FJX-SS | F3 |
| 32S-32FJX-SS | F3 |

| Category | Page |
|---|---|
| **Stainless Steel Spiral Couplings (Continued)** | |
| Female Flat-Face O-Ring Swivel Metric Hex | F3 |
| 6S-6FFORX-SS | F3 |
| 8S-8FFORX-SS | F3 |
| 10S-10FFORX-SS | F3 |
| 12S-12FFORX-SS | F3 |
| 16S-16FFORX-SS | F3 |
| 20S-20FFORX-SS | F3 |
| 24S-24FFORX-SS | F3 |
| Code 61 O-Ring Flange | F3 |
| 12S-12FL-SS | F3 |
| 16S-16FL-SS | F3 |
| 20S-20FL-SS | F3 |
| Code 62 O-Ring Flange Heavy | F4 |
| 12S-12FLH-SS | F4 |
| 16S-16FLH-SS | F4 |
| 20S-20FLH-SS | F4 |
| 24S-24FLH-SS | F4 |
| 32S-32FLH-SS | F4 |
| Female DIN 24° Cone Swivel - Heavy Series with O-Ring | F4 |
| 16S-30FDHORX-SS | F4 |
| Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 90° Bent Tube | F5 |
| 16S-30FDHORX90-SS | F5 |
| Non-Skive Ferrules | F5 |
| 10S1F-2SS | F5 |
| 12S1F-2SS | F5 |
| 16S1F-2SS | F5 |
| 6S1F-4SS | F5 |
| 8S1F-4SS | F5 |
| 10S1F-4SS | F5 |
| 12S1F-4SS | F5 |
| 16S1F-4SS | F5 |
| 20S1F-4SS | F5 |
| 20S1F-6SS | F5 |
| Skive Ferrules | F6 |
| 24S2F-6SS | F6 |
| 32S2F-6SS | F6 |
| **MegaCrimp® Couplings** | |
| Male Pipe (NPTF - 30° Cone Seat) | G5 |
| 4G-2MP | G5 |
| 4G-4MP | G5 |
| 4G-6MP | G5 |
| 4G-8MP | G5 |
| 5G-4MP | G5 |
| 5G-6MP | G5 |
| 6G-4MP | G5 |
| 6G-6MP | G5 |
| 6G-8MP | G5 |
| 8G-4MP | G5 |
| 8G-6MP | G5 |
| 8G-8MP | G5 |
| 8G-12MP | G5 |
| 10G-8MP | G5 |
| 10G-12MP | G5 |
| 12G-8MP | G5 |
| 12G-12MP | G5 |
| 12G-16MP | G5 |
| 16G-12MP | G5 |
| 16G-16MP | G5 |
| 20G-20MP | G5 |
| Male Pipe Long Nose | G5 |
| 4G-4MPLN | G5 |
| 4G-6MPLN | G5 |
| 6G-4MPLN | G5 |
| 6G-6MPLN | G5 |
| Male Pipe Swivel (NPTF - without 30° Cone Seat) | G6 |
| 4G-2MPX | G6 |
| 4G-4MPX | G6 |
| 4G-6MPX | G6 |
| 4G-8MPX | G6 |
| 6G-4MPX | G6 |
| 6G-6MPX | G6 |
| 6G-8MPX | G6 |
| 8G-6MPX | G6 |
| 8G-8MPX | G6 |

## MegaCrimp® Couplings (Continued)


| Category | Page |
|---|---|
| Male Pipe Swivel (NPTF - without 30° Cone Seat) (Continued) | G6 |
| 10G-12MPX | G6 |
| 12G-8MPX | G6 |
| 12G-12MPX | G6 |
| 16G-16MPX | G6 |
| Male Pipe Swivel - 90° Block (NPTF - without 30° Cone Seat) | G6 |
| 4G-2MPX90 | G6 |
| 4G-4MPX90 | G6 |
| 4G-6MPX90 | G6 |
| 6G-4MPX90 | G6 |
| 6G-6MPX90 | G6 |
| 6G-8MPX90 | G6 |
| 8G-6MPX90 | G6 |
| 8G-8MPX90 | G6 |
| 12G-12MPX90 | G6 |
| Male Pipe Swivel - 90° Long Block (NPTF - without 30° Cone Seat) | G7 |
| 6G-8MPX90L | G7 |
| 8G-8MPX90L | G7 |
| 12G-12MPX90L | G7 |
| Female Pipe (NPTF - without 30° Cone Seat) | G7 |
| 4G-2FP | G7 |
| 4G-4FP | G7 |
| 4G-6FP | G7 |
| 6G-4FP | G7 |
| 6G-6FP | G7 |
| 6G-8FP | G7 |
| 8G-6FP | G7 |
| 8G-8FP | G7 |
| 12G-12FP | G7 |
| Female Pipe Swivel (NPSM - 30° Cone Seat) | G8 |
| 4G-4FPX | G8 |
| 6G-6FPX | G8 |
| 6G-8FPX | G8 |
| 8G-8FPX | G8 |
| 12G-12FPX | G8 |
| 16G-16FPX | G8 |
| 20G-20FPX | G8 |
| Male O-Ring Boss | G8 |
| 4G-4MB | G8 |
| 4G-5MB | G8 |
| 4G-6MB | G8 |
| 6G-5MB | G8 |
| 6G-6MB | G8 |
| 6G-8MB | G8 |
| 6G-10MB | G8 |
| 6G-12MB | G8 |
| 8G-8MB | G8 |
| 8G-10MB | G8 |
| 8G-12MB | G8 |
| 10G-8MB | G8 |
| 10G-10MB | G8 |
| 10G-12MB | G8 |
| 12G-10MB | G8 |
| 12G-12MB | G8 |
| 12G-14MB | G8 |
| 12G-16MB | G8 |
| 16G-14MB | G8 |
| 16G-16MB | G8 |
| 16G-20MB | G8 |
| 20G-20MB | G9 |
| Male O-Ring Boss Swivel | G9 |
| 4G-4MBX | G9 |
| 4G-6MBX | G9 |
| 6G-6MBX | G9 |
| 6G-8MBX | G9 |
| 6G-10MBX | G9 |
| 8G-8MBX | G9 |
| 8G-10MBX | G9 |
| 10G-10MBX | G9 |
| 12G-12MBX | G9 |
| Male O-Ring Boss Swivel - 45° Block | G9 |
| 6G-6MBX45BL | G9 |
| 6G-8MBX45BL | G9 |
| 8G-8MBX45BL | G9 |
| 8G-10MBX45BL | G10 |

| Category | Page |
|---|---|
| Male O-Ring Boss Swivel - 90° Block | G10 |
| 4G-5MBX90BL | G10 |
| 4G-6MBX90BL | G10 |
| 6G-6MBX90BL | G10 |
| 6G-8MBX90BL | G10 |
| 6G-10MBX90BL | G10 |
| 8G-8MBX90BL | G10 |
| 8G-8MBX90BLL | G10 |
| 8G-10MBX90BL | G10 |
| 8G-10MBX90BLL | G10 |
| 8G-12MBX90BL | G10 |
| 8G-12MBX90BLL | G10 |
| 10G-10MBX90BL | G10 |
| 10G-10MBX90BLL | G10 |
| 12G-12MBX90BL | G10 |
| 12G-12MBX90BLL | G10 |
| Male O-Ring Boss Swivel - 45° Bent Tube | G11 |
| 6G-6MBX45 | G11 |
| 6G-8MBX45 | G11 |
| 8G-8MBX45 | G11 |
| 8G-10MBX45 | G11 |
| Male O-Ring Boss Swivel - 90° Bent Tube | G11 |
| 4G-6MBX90 | G11 |
| 6G-6MBX90 | G11 |
| 6G-8MBX90 | G11 |
| 6G-10MBX90 | G11 |
| 8G-8MBX90 | G11 |
| 8G-10MBX90 | G11 |
| 8G-12MBX90 | G11 |
| 10G-10MBX90 | G11 |
| 10G-12MBX90 | G11 |
| 12G-12MBX90 | G11 |
| Male O-Ring Boss Adapterless Swivel - 90° Bent Tube | G12 |
| 4G-4MBAX90M | G12 |
| 6G-6MBAX90M | G12 |
| 8G-8MBAX90M | G12 |
| 10G-10MBAX90M | G12 |
| 12G-12MBAX90M | G12 |
| Male JIC 37° Flare | G12 |
| 4G-4MJ | G12 |
| 4G-5MJ | G12 |
| 4G-6MJ | G12 |
| 5G-5MJ | G12 |
| 5G-6MJ | G12 |
| 6G-6MJ | G12 |
| 6G-8MJ | G12 |
| 6G-10MJ | G12 |
| 8G-8MJ | G12 |
| 8G-10MJ | G12 |
| 8G-12MJ | G12 |
| 10G-8MJ | G12 |
| 10G-10MJ | G12 |
| 10G-12MJ | G12 |
| 12G-10MJ | G12 |
| 12G-12MJ | G12 |
| 12G-14MJ | G13 |
| 12G-16MJ | G13 |
| 16G-14MJ | G13 |
| 16G-16MJ | G13 |
| 16G-20MJ | G13 |
| 20G-20MJ | G13 |
| 20G-24MJ | G13 |
| Female JIC 37° Flare Swivel | G13 |
| 4G-4FJX | G13 |
| 4G-5FJX | G13 |
| 4G-6FJX | G13 |
| 5G-5FJX | G13 |
| 5G-6FJX | G13 |
| 6G-4FJXSP | G13 |
| 6G-4FJX | G13 |
| 6G-5FJXSP | G13 |
| 6G-5FJX | G13 |
| 6G-6FJX | G13 |
| 6G-8FJX | G13 |
| 6G-10FJX | G13 |
| 6G-12FJX | G13 |
| 8G-6FJXSP | G13 |
| 8G-6FJX | G13 |

# INDEX


| Category | Page |
|---|---|
| **MegaCrimp® Couplings (Continued)** | |
| Female JIC 37° Flare Swivel (Continued) | G13 |
| 8G-8FJX | G13 |
| 8G-10FJX | G13 |
| 8G-12FJX | G13 |
| 8G-16FJX | G13 |
| 10G-8FJXSP | G13 |
| 10G-8FJX | G13 |
| 10G-10FJX | G13 |
| 10G-12FJX | G13 |
| 10G-14FJX | G13 |
| 12G-8FJX | G13 |
| 12G-10FJXSP | G13 |
| 12G-10FJX | G13 |
| 12G-12FJX | G13 |
| 12G-14FJX | G13 |
| 12G-16FJX | G13 |
| 16G-12FJXSP | G14 |
| 16G-12FJX | G14 |
| 16G-14FJXSP | G14 |
| 16G-14FJX | G14 |
| 16G-16FJX | G14 |
| 16G-20FJX | G14 |
| 20G-20FJX | G14 |
| 20G-24FJX | G14 |
| Female JIC 37° Flare Swivel - 30° Bent Tube | G14 |
| 10G-12FJX30-018 | G14 |
| 12G-10FJX30-018 | G14 |
| Female JIC 37° Flare Swivel - 45° Bent Tube | G14 |
| 4G-4FJX45S | G14 |
| 4G-5FJX45-011 | G14 |
| 4G-6FJX45S | G14 |
| 5G-5FJX45-011 | G14 |
| 5G-6FJX45S | G14 |
| 6G-4FJX45S | G14 |
| 6G-6FJX45S | G14 |
| 6G-8FJX45S | G14 |
| 8G-8FJX45S | G14 |
| 8G-10FJX45S | G14 |
| 10G-10FJX45S | G15 |
| 10G-12FJX45S | G15 |
| 12G-10FJX45S | G15 |
| 12G-12FJX45S | G15 |
| 12G-16FJX45S | G15 |
| 16G-12FJX45S | G15 |
| 16G-16FJX45S | G15 |
| 20G-20FJX45-035 | G15 |
| Female JIC 37° Flare Swivel - 90° Bent Tube | G15 |
| 4G-4FJX90S | G15 |
| 4G-4FJX90M | G15 |
| 4G-4FJX90L | G15 |
| 4G-5FJX90-023 | G15 |
| 4G-5FJX90M | G15 |
| 4G-5FJX90L | G15 |
| 4G-6FJX90S | G15 |
| 4G-6FJX90M | G15 |
| 4G-6FJX90L | G15 |
| 5G-6FJX90S | G15 |
| 5G-6FJX90M | G15 |
| 6G-4FJX90S | G15 |
| 6G-4FJX90L | G15 |
| 6G-6FJX90S | G15 |
| 6G-6FJX90M | G15 |
| 6G-6FJX90L | G15 |
| 6G-8FJX90S | G15 |
| 6G-8FJX90M | G15 |
| 6G-8FJX90L | G15 |
| 6G-10FJX90M | G15 |
| 8G-6FJX90S | G15 |
| 8G-8FJX90S | G15 |
| 8G-8FJX90M | G15 |
| 8G-8FJX90L | G15 |
| 8G-10FJX90S | G15 |
| 8G-10FJX90M | G15 |
| 8G-10FJX90L | G15 |
| 8G-10FJX90-089 | G15 |
| 8G-12FJX90S | G15 |
| 10G-10FJX90-036 | G16 |
| 10G-10FJX90M | G16 |
| 10G-10FJX90L | G16 |

| Category | Page |
|---|---|
| **MegaCrimp® Couplings (Continued)** | |
| Female JIC 37° Flare Swivel - 90° Bent Tube (Continued) | G16 |
| 10G-12FJX90S | G16 |
| 10G-12FJX90M | G16 |
| 10G-12FJX90L | G16 |
| 12G-10FJX90M | G16 |
| 12G-12FJX90S | G16 |
| 12G-12FJX90M | G16 |
| 12G-12FJX90L | G16 |
| 12G-14FJX90-054 | G16 |
| 12G-14FJX90-100 | G16 |
| 12G-16FJX90S | G16 |
| 12G-16FJX90M | G16 |
| 16G-16FJX90S | G16 |
| 16G-16FJX90M | G16 |
| 16G-16FJX90L | G16 |
| 16G-20FJX90S | G16 |
| 20G-20FJX90M | G16 |
| 20G-20FJX90L | G16 |
| 20G-20FJX90-089 | G16 |
| Female JIC 37° Flare Swivel - 90° Block | G16 |
| 12G-16FJX90BLK | G16 |
| Male SAE 45° Flare | G17 |
| 4G-4MS | G17 |
| 4G-5MS | G17 |
| 6G-6MS | G17 |
| 6G-8MS | G17 |
| 8G-8MS | G17 |
| 8G-10MS | G17 |
| 12G-12MS | G17 |
| Female SAE 45° Flare Swivel | G17 |
| 4G-4FSX | G17 |
| 4G-5FSX | G17 |
| 4G-6FSX | G17 |
| 5G-6FSX | G17 |
| 6G-6FSX | G17 |
| 6G-8FSX | G17 |
| 8G-8FSX | G17 |
| 8G-10FSX | G17 |
| 12G-12FSX | G17 |
| Female SAE 45° Flare Swivel - 45° Bent Tube | G18 |
| 4G-4FSX45 | G18 |
| 4G-5FSX45-009 | G18 |
| 6G-6FSX45 | G18 |
| 6G-8FSX45-014 | G18 |
| 8G-8FSX45 | G18 |
| 8G-10FSX45-016 | G18 |
| 12G-12FSX45 | G18 |
| Female SAE 45° Flare Swivel - 90° Bent Tube | G18 |
| 4G-4FSX90 | G18 |
| 4G-5FSX90-046 | G18 |
| 5G-6FSX90-022 | G18 |
| 6G-6FSX90 | G18 |
| 6G-6FSX90-055 | G18 |
| 6G-8FSX90 | G18 |
| 8G-8FSX90 | G18 |
| 8G-10FSX90-031 | G18 |
| 12G-12FSX90 | G18 |
| Male Flat-Face O-Ring | G19 |
| 4G-4MFFOR | G19 |
| 4G-6MFFOR | G19 |
| 5G-6MFFOR | G19 |
| 6G-6MFFOR | G19 |
| 6G-8MFFOR | G19 |
| 6G-10MFFOR | G19 |
| 8G-8MFFOR | G19 |
| 8G-10MFFOR | G19 |
| 8G-12MFFOR | G19 |
| 10G-10MFFOR | G19 |
| 10G-12MFFOR | G19 |
| 12G-12MFFOR | G19 |
| 12G-16MFFOR | G19 |
| 16G-16MFFOR | G19 |
| 16G-20MFFOR | G19 |
| 20G-20MFFOR | G19 |
| Male Flat-Face O-Ring Bulk Head Long Nose | G19 |
| 6G-6MFFORBKHDLN | G19 |

## MegaCrimp® Couplings (Continued)


| Category | Page |
|---|---|
| Male Flat-Face O-Ring Bulk Head Long Nose (Continued) | G19 |
| 8G-8MFFORBKHDLN | G19 |
| Male Flat-Face O-Ring Bulk Head | G20 |
| 4G-4MFFORBKHD | G20 |
| 6G-6MFFORBKHD | G20 |
| Female Flat-Face O-Ring Swivel | G20 |
| 4G-4FFORX | G20 |
| 4G-6FFORX | G20 |
| 4G-8FFORX | G20 |
| 5G-6FFORX | G20 |
| 6G-4FFORX | G20 |
| 6G-6FFORX | G20 |
| 6G-8FFORX | G20 |
| 6G-10FFORX | G20 |
| 8G-6FFORX | G20 |
| 8G-8FFORX | G20 |
| 8G-10FFORX | G20 |
| 8G-12FFORX | G20 |
| 10G-8FFORX | G20 |
| 10G-10FFORX | G20 |
| 10G-12FFORX | G20 |
| 12G-10FFORX | G20 |
| 12G-12FFORX | G20 |
| 12G-16FFORX | G20 |
| 16G-12FFORX | G20 |
| 16G-16FFORX | G20 |
| 16G-20FFORX | G20 |
| 20G-20FFORX | G20 |
| 20G-24FFORX | G20 |
| Female Flat-Face O-Ring Swivel - 30° Bent Tube | G21 |
| 8G-10FFORX30-010 | G21 |
| Female Flat-Face O-Ring Swivel - 45° Bent Tube | G21 |
| 4G-4FFORX45S | G21 |
| 4G-6FFORX45S | G21 |
| 5G-6FFORX45S | G21 |
| 6G-4FFORX45S | G21 |
| 6G-6FFORX45S | G21 |
| 6G-8FFORX45S | G21 |
| 8G-6FFORX45S | G21 |
| 8G-8FFORX45S | G21 |
| 8G-10FFORX45S | G21 |
| 8G-12FFORX45S | G21 |
| 10G-8FFORX45S | G21 |
| 10G-10FFORX45S | G21 |
| 10G-12FFORX45S | G21 |
| 12G-10FFORX45S | G21 |
| 12G-12FFORX45S | G21 |
| 12G-16FFORX45S | G21 |
| 16G-12FFORX45S | G21 |
| 16G-16FFORX45S | G21 |
| 20G-20FFORX45S | G21 |
| Female Flat-Face O-Ring Swivel - 67 1/2° Bent Tube | G22 |
| 8G-8FFORX67-022 | G22 |
| Female Flat-Face O-Ring Swivel - 90° Bent Tube | G22 |
| 4G-4FFORX90S | G22 |
| 4G-4FFORX90M | G22 |
| 4G-4FFORX90L | G22 |
| 4G-6FFORX90S | G22 |
| 4G-6FFORX90M | G22 |
| 4G-6FFORX90L | G22 |
| 4G-8FFORX90S | G22 |
| 4G-8FFORX90L | G22 |
| 5G-6FFORX90S | G22 |
| 6G-4FFORX90S | G22 |
| 6G-6FFORX90S | G22 |
| 6G-6FFORX90M | G22 |
| 6G-6FFORX90L | G22 |
| 6G-8FFORX90S | G22 |
| 6G-8FFORX90M | G22 |
| 6G-8FFORX90L | G22 |
| 8G-6FFORX90S | G22 |
| 8G-6FFORX90L | G22 |
| 8G-8FFORX90S | G22 |
| 8G-8FFORX90M | G22 |
| 8G-8FFORX90L | G22 |
| 8G-10FFORX90S | G22 |
| 8G-10FFORX90M | G23 |


## MegaCrimp® Couplings (Continued)


| Category | Page |
|---|---|
| Female Flat-Face O-Ring Swivel - 90° Bent Tube (Continued) | G23 |
| 8G-10FFORX90L | G23 |
| 8G-12FFORX90S | G23 |
| 10G-8FFORX90S | G23 |
| 10G-8FFORX90L | G23 |
| 10G-10FFORX90S | G23 |
| 10G-10FFORX90M | G23 |
| 10G-10FFORX90L | G23 |
| 10G-12FFORX90S | G23 |
| 12G-10FFORX90S | G23 |
| 12G-12FFORX90S | G23 |
| 12G-12FFORX90M | G23 |
| 12G-12FFORX90L | G23 |
| 12G-16FFORX90S | G23 |
| 16G-12FFORX90S | G23 |
| 16G-16FFORX90S | G23 |
| 16G-16FFORX90M | G23 |
| 16G-16FFORX90L | G23 |
| 16G-20FFORX90S | G23 |
| 16G-20FFORX90M | G23 |
| 20G-20FFORX90S | G23 |
| 20G-20FFORX90M | G23 |
| 20G-20FFORX90L | G23 |
| Code 61 O-Ring Flange | G23 |
| 8G-8FL | G23 |
| 8G-12FL | G23 |
| 12G-12FL | G23 |
| 12G-16FL | G23 |
| 16G-12FL | G23 |
| 16G-16FL | G23 |
| 16G-20FL | G23 |
| 16G-24FL | G23 |
| 20G-20FL | G23 |
| 20G-24FL | G23 |
| Komatsu O-Ring Flange - Straight | G24 |
| 8G-10FLK | G24 |
| 10G-10FLK | G24 |
| Code 61 O-Ring Flange - 22 1/2° Bent Tube | G24 |
| 12G-12FL22M | G24 |
| 12G-16FL22M-014 | G24 |
| 16G-16FL22M | G24 |
| 20G-20FL22M | G24 |
| Code 61 O-Ring Flange - 30° Bent Tube | G24 |
| 12G-12FL30M | G24 |
| 12G-16FL30M | G24 |
| 16G-16FL30M | G24 |
| 16G-20FL30M | G24 |
| 20G-20FL30S | G25 |
| Code 61 O-Ring Flange - 45° Bent Tube | G25 |
| 8G-8FL45M | G25 |
| 8G-12FL45M | G25 |
| 10G-12FL45M | G25 |
| 12G-12FL45M | G25 |
| 12G-16FL45S | G25 |
| 16G-16FL45S | G25 |
| 16G-20FL45S | G25 |
| 16G-24FL45 | G25 |
| 20G-20FL45S | G25 |
| Komatsu O-Ring Flange - 45° Bent Tube | G25 |
| 10G-10FLK45 | G25 |
| Code 61 O-Ring Flange - 60° Bent Tube | G26 |
| 12G-12FL60M | G26 |
| 12G-16FL60M | G26 |
| 16G-16FL60M | G26 |
| 20G-20FL60S | G26 |
| Code 61 O-Ring Flange - 67 1/2° Bent Tube | G26 |
| 12G-12FL67M | G26 |
| 20G-20FL67S | G26 |
| Code 61 O-Ring Flange - 90° Bent Tube | G27 |
| 8G-8FL90M | G27 |
| 8G-12FL90M | G27 |
| 10G-12FL90M | G27 |
| 12G-12FL90M | G27 |
| 12G-16FL90S | G27 |
| 16G-12FL90M | G27 |

| Category | Page |
|---|---|
| **MegaCrimp® Couplings (Continued)** | |
| Code 61 O-Ring Flange - 90° Bent Tube (Continued) | G27 |
| 16G-16FL90S | G27 |
| 16G-20FL90S | G27 |
| 16G-24FL90S-081 | G27 |
| 20G-20FL90S | G27 |
| 20G-20FL90M | G27 |
| 20G-20FL90-102 | G27 |
| 20G-24FL90S | G27 |
| Komatsu O-Ring Flange - 90° Bent Tube | G27 |
| 10G-10FLK90 | G27 |
| SAE Male Inverted Swivel | G28 |
| 4G-3MIX | G28 |
| 4G-4MIX | G28 |
| 4G-5MIX | G28 |
| 6G-4MIX | G28 |
| 6G-5MIX | G28 |
| 6G-6MIX | G28 |
| 6G-7MIX | G28 |
| 8G-6MIX | G28 |
| 8G-8MIX | G28 |
| 10G-10MIX | G28 |
| SAE Male Inverted Swivel - 45° Bent Tube | G28 |
| 4G-3MIX45-018 | G28 |
| 4G-4MIX45-024 | G28 |
| 6G-4MIX45 | G28 |
| 6G-5MIX45 | G28 |
| 6G-6MIX45 | G28 |
| 6G-7MIX45 | G28 |
| 8G-8MIX45 | G28 |
| 10G-10MIX45 | G28 |
| SAE Male Inverted Swivel - 90° Bent Tube | G29 |
| 4G-4MIX90 | G29 |
| 4G-5MIX90 | G29 |
| 5G-6MIX90-035 | G29 |
| 6G-4MIX90 | G29 |
| 6G-5MIX90 | G29 |
| 6G-6MIX90 | G29 |
| 6G-7MIX90 | G29 |
| 8G-8MIX90 | G29 |
| 10G-10MIX90 | G29 |
| SAE Male Flareless Assembly | G29 |
| 4G-4MFA | G29 |
| 4G-5MFA | G29 |
| 5G-5MFA | G29 |
| 5G-6MFA | G29 |
| 6G-4MFA | G29 |
| 6G-5MFA | G29 |
| 6G-6MFA | G29 |
| 6G-8MFA | G29 |
| 8G-8MFA | G29 |
| 8G-10MFA | G29 |
| 12G-12MFA | G29 |
| 16G-16MFA | G29 |
| North American Stand Pipe | G30 |
| 4G-4NASP | G30 |
| 6G-6NASP | G30 |
| 8G-8NASP | G30 |
| 12G-12NASP | G30 |
| 16G-16NASP | G30 |
| Hose Length Extender | G30 |
| 20G-20HLE | G30 |
| Female Air Brake Swivel | G30 |
| 6G-6FABX | G30 |
| 8G-6FABX | G30 |
| 8G-8FABX | G30 |
| Female Grease | G31 |
| 4G-8FG | G31 |
| 6G-8FG | G31 |
| Female Parker Triple Thread Flare | G31 |
| 16G-16FZX | G31 |
| Pressure Wash Swivel | G31 |
| 4G-6PWX | G31 |
| 6G-6PWX | G31 |

| Category | Page |
|---|---|
| **MegaCrimp® Couplings (Continued)** | |
| US Banjo | G32 |
| 6G-6BJ | G32 |
| Male DIN 24° Cone - Light Series | G32 |
| 4G-6MDL | G32 |
| 4G-8MDL | G32 |
| 4G-10MDL | G32 |
| 6G-10MDL | G32 |
| 6G-12MDL | G32 |
| 6G-15MDL | G32 |
| 8G-15MDL | G32 |
| 10G-18MDL | G32 |
| 10G-22MDL | G32 |
| 12G-18MDL | G32 |
| 12G-22MDL | G32 |
| 16G-28MDL | G32 |
| 20G-35MDL | G32 |
| Female DIN 24° Cone Swivel - Light Series with O-Ring | G33 |
| 4G-6FDLORX | G33 |
| 4G-8FDLORX | G33 |
| 4G-10FDLORX | G33 |
| 4G-12FDLORX | G33 |
| 5G-10FDLORX | G33 |
| 5G-12FDLORX | G33 |
| 6G-10FDLORX | G33 |
| 6G-12FDLORX | G33 |
| 6G-14FDLORX | G33 |
| 6G-15FDLORX | G33 |
| 8G-15FDLORX | G33 |
| 8G-18FDLORX | G33 |
| 10G-18FDLORX | G33 |
| 12G-18FDLORX | G33 |
| 12G-22FDLORX | G33 |
| 16G-28FDLORX | G33 |
| 20G-35FDLORX | G33 |
| 20G-42FDLORX | G33 |
| Female DIN 24° Cone Swivel - Light Series with O-Ring - 45° Bent Tube | G33 |
| 4G-8FDLORX45 | G33 |
| 4G-10FDLORX45 | G33 |
| 5G-10FDLORX45 | G33 |
| 6G-10FDLORX45 | G33 |
| 6G-12FDLORX45 | G33 |
| 6G-15FDLORX45 | G33 |
| 8G-15FDLORX45 | G33 |
| 8G-18FDLORX45 | G34 |
| 10G-18FDLORX45 | G34 |
| 12G-22FDLORX45 | G34 |
| 16G-28FDLORX45 | G34 |
| 20G-35FDLORX45 | G34 |
| Female DIN 24° Cone Swivel - Light Series with O-Ring - 90° Bent Tube | G34 |
| 4G-6FDLORX90 | G34 |
| 4G-8FDLORX90 | G34 |
| 4G-10FDLORX90 | G34 |
| 5G-10FDLORX90 | G34 |
| 6G-10FDLORX90 | G34 |
| 6G-12FDLORX90 | G34 |
| 6G-15FDLORX90 | G34 |
| 8G-15FDLORX90 | G34 |
| 8G-18FDLORX90 | G34 |
| 10G-18FDLORX90 | G34 |
| 12G-18FDLORX90 | G34 |
| 12G-22FDLORX90 | G34 |
| 16G-28FDLORX90 | G34 |
| 20G-35FDLORX90 | G34 |
| Female French GAZ Swivel | G35 |
| 8G-17FFGX | G35 |
| 10G-21FFGX | G35 |
| 12G-27FFGX | G35 |
| Male DIN 24° Cone - Heavy Series | G35 |
| 4G-8MDH | G35 |
| 4G-10MDH | G35 |
| 5G-12MDH | G35 |
| 6G-10MDH | G35 |
| 6G-12MDH | G35 |
| 6G-14MDH | G35 |
| 8G-12MDH | G35 |
| 8G-16MDH | G35 |
| 10G-20MDH | G35 |

## MegaCrimp® Couplings (Continued)


| Category | Page |
|---|---|
| Male DIN 24° Cone - Heavy Series (Continued) | G35 |
| 12G-20MDH | G35 |
| 12G-25MDH | G35 |
| 16G-30MDH | G35 |
| 20G-38MDH | G35 |
| Female DIN 24° Cone Swivel - Heavy Series with O-Ring | G36 |
| 4G-8FDHORX | G36 |
| 4G-10FDHORX | G36 |
| 4G-12FDHORX | G36 |
| 5G-12FDHORX | G36 |
| 5G-14FDHORX | G36 |
| 6G-10FDHORX | G36 |
| 6G-12FDHORX | G36 |
| 6G-14FDHORX | G36 |
| 8G-12FDHORX | G36 |
| 8G-14FDHORX | G36 |
| 8G-16FDHORX | G36 |
| 8G-20FDHORX | G36 |
| 10G-16FDHORX | G36 |
| 10G-20FDHORX | G36 |
| 12G-20FDHORX | G36 |
| 12G-25FDHORX | G36 |
| 16G-25FDHORX | G36 |
| 16G-30FDHORX | G36 |
| 20G-38FDHORX | G36 |
| Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 45° Bent Tube | G36 |
| 4G-8FDHORX45 | G36 |
| 4G-10FDHORX45 | G36 |
| 6G-10FDHORX45 | G36 |
| 6G-12FDHORX45 | G36 |
| 6G-14FDHORX45 | G36 |
| 8G-14FDHORX45 | G36 |
| 8G-16FDHORX45 | G37 |
| 10G-20FDHORX45 | G37 |
| 12G-20FDHORX45 | G37 |
| 12G-25FDHORX45 | G37 |
| Female DIN 24° Cone Swivel - Heavy Series with O-Ring - 90° Bent Tube | G37 |
| 4G-8FDHORX90 | G37 |
| 4G-10FDHORX90 | G37 |
| 5G-12FDHORX90 | G37 |
| 5G-14FDHORX90 | G37 |
| 6G-10FDHORX90 | G37 |
| 6G-12FDHORX90 | G37 |
| 6G-14FDHORX90 | G37 |
| 8G-14FDHORX90 | G37 |
| 8G-16FDHORX90 | G37 |
| 10G-20FDHORX90 | G37 |
| 10G-25FDHORX90 | G37 |
| 12G-20FDHORX90 | G37 |
| 12G-25FDHORX90 | G37 |
| 16G-25FDHORX90 | G37 |
| 20G-38FDHORX90 | G37 |
| Metric Light Stand Pipe | G38 |
| 4G-6MSP | G38 |
| 4G-8MSP | G38 |
| 4G-10MSP | G38 |
| 6G-10MSP | G38 |
| 6G-12MSP | G38 |
| 8G-15MSP | G38 |
| 10G-18MSP | G38 |
| 10G-22MSP | G38 |
| 12G-18MSP | G38 |
| 12G-22MSP | G38 |
| 16G-28MSP | G38 |
| International Thread Metric 7642 DIN Banjo | G38 |
| 4G-12DBJ | G38 |
| 6G-12DBJ | G38 |
| 6G-14DBJ | G38 |
| 6G-16DBJ | G38 |
| 6G-18DBJ | G38 |
| 8G-18DBJ | G38 |
| 10G-22DBJ | G38 |
| 12G-26DBJ | G38 |
| 16G-30DBJ | G38 |
| Male British Standard Pipe Tapered/Japanese Tapered Thread | G39 |
| 4G-4MBSPT | G39 |
| 6G-6MBSPT | G39 |
| 8G-8MBSPT | G39 |
| 10G-10MBSPT | G39 |
| 12G-12MBSPT | G39 |
| 16G-16MBSPT | G39 |
| Male British Standard Parallel Pipe | G39 |
| 4G-4MBSPP | G39 |
| 6G-4MBSPP | G39 |
| 6G-6MBSPP | G39 |
| 6G-8MBSPP | G39 |
| 8G-6MBSPP | G39 |
| 8G-8MBSPP | G39 |
| 10G-10MBSPP | G39 |
| 10G-12MBSPP | G39 |
| 12G-12MBSPP | G39 |
| 16G-16MBSPP | G39 |
| 20G-20MBSPP | G39 |
| Female British Standard Parallel Pipe O-Ring Swivel | G40 |
| 4G-2FBSPPX | G40 |
| 4G-4FBSPORX | G40 |
| 4G-6FBSPORX | G40 |
| 5G-6FBSPORX | G40 |
| 5G-8FBSPORX | G40 |
| 6G-6FBSPORX | G40 |
| 6G-8FBSPORX | G40 |
| 8G-6FBSPORX | G40 |
| 8G-8FBSPORX | G40 |
| 8G-10FBSPORX | G40 |
| 8G-12FBSPORX | G40 |
| 10G-10FBSPORX | G40 |
| 10G-12FBSPORX | G40 |
| 12G-12FBSPORX | G40 |
| 12G-16FBSPORX | G40 |
| 16G-16FBSPORX | G40 |
| 20G-20FBSPORX | G40 |
| Female British Standard Parallel Pipe O-Ring Swivel - 45° Bent Tube | G40 |
| 4G-4FBSPORX45 | G40 |
| 6G-6FBSPORX45 | G40 |
| 6G-8FBSPORX45 | G40 |
| 8G-8FBSPORX45 | G40 |
| 8G-10FBSPORX45 | G40 |
| 10G-10FBSPORX45 | G40 |
| 10G-12FBSPORX45 | G40 |
| 12G-12FBSPORX45 | G40 |
| 16G-16FBSPORX45 | G40 |
| 20G-20FBSPORX45 | G40 |
| Female British Standard Parallel Pipe O-Ring Swivel - 90° Bent Tube | G41 |
| 4G-4FBSPORX90 | G41 |
| 6G-6FBSPORX90 | G41 |
| 6G-8FBSPORX90 | G41 |
| 8G-8FBSPORX90 | G41 |
| 8G-10FBSPORX90 | G41 |
| 10G-10FBSPORX90 | G41 |
| 10G-12FBSPORX90 | G41 |
| 12G-12FBSPORX90 | G41 |
| 12G-16FBSPORX90 | G41 |
| 16G-16FBSPORX90 | G41 |
| 20G-20FBSPORX90 | G41 |
| Female British Standard Parallel Pipe O-Ring Swivel - 90° BIock | G41 |
| 4G-4FBSPORX90BL | G41 |
| 6G-6FBSPORX90BL | G41 |
| 8G-8FBSPORX90BL | G41 |
| 16G-16FBSPORX90BL | G41 |
| International Thread British Std Pipe Banjo | G42 |
| 4G-4BSPBJ | G42 |
| 6G-6BSPBJ | G42 |
| 8G-8BSPBJ | G42 |
| 12G-12BSPBJ | G42 |
| Female British Flat-Face Swivel | G42 |
| 6G-6FBFFX | G42 |
| 6G-8FBFFX | G42 |
| 8G-8FBFFX | G42 |
| 8G-12FBFFX | G42 |
| 10G-12FBFFX | G42 |
| 12G-12FBFFX | G42 |

| Category | Page |
|---|---|
| **MegaCrimp® Couplings (Continued)** | |
| Female Komatsu Style Japanese Metric Swivel | G43 |
| 4G-4FKX | G43 |
| 4G-6FKX | G43 |
| 6G-6FKX | G43 |
| 8G-8FKX | G43 |
| 10G-10FKX | G43 |
| 12G-12FKX | G43 |
| 16G-16FKX | G43 |
| 20G-20FKX | G43 |
| Female Komatsu Style Japanese Metric Swivel - 45° Bent Tube | G43 |
| 4G-4FKX45 | G43 |
| 6G-6FKX45 | G43 |
| 8G-8FKX45 | G43 |
| 10G-10FKX45 | G43 |
| 12G-12FKX45 | G43 |
| Female Komatsu Style Japanese Metric Swivel - 90° Bent Tube | G44 |
| 4G-4FKX90 | G44 |
| 6G-6FKX90 | G44 |
| 8G-8FKX90 | G44 |
| 10G-10FKX90 | G44 |
| 12G-12FKX90 | G44 |
| Female Japanese Industrial Standard Swivel | G44 |
| 4G-4FJISX | G44 |
| 6G-6FJISX | G44 |
| 8G-8FJISX | G44 |
| 12G-12FJISX | G44 |
| 16G-16FJISX | G44 |
| 20G-20FJISX | G44 |
| Female Japanese Inverted Flare Parallel Threads | G45 |
| 4G-4FJISPX | G45 |
| 6G-6FJISPX | G45 |
| 8G-8JISPX | G45 |
| 12G-12JISPX | G45 |
| 16G-16JISPX | G45 |
| 20G-20FJISPX | G45 |
| Male Quick-Lok® High | G45 |
| 4G-4MQLH | G45 |
| 6G-6MQLH | G45 |
| 8G-8MQLH | G45 |
| 10G-10MQLH | G45 |
| 12G-12MQLH | G45 |
| 16G-16MQLH | G45 |
| Male Quick-Lok® High - 45° Bent Tube | G46 |
| 4G-4MQLH45S-008 | G46 |
| 6G-6MQLH45S-008 | G46 |
| 8G-8MQLH45S-010 | G46 |
| 10G-10MQLH45S-013 | G46 |
| 12G-12MQLH45S-014 | G46 |
| 16G-16MQLH45S-017 | G46 |
| Male Quick-Lok® High - 90° Bent Tube | G46 |
| 4G-4MQLH90S-018 | G46 |
| 4G-4MQLH90L-039 | G46 |
| 6G-6MQLH90S-020 | G46 |
| 6G-6MQLH90L-046 | G46 |
| 8G-8MQLH90S-026 | G46 |
| 8G-8MQLH90L-057 | G46 |
| 10G-10MQLH90S-033 | G46 |
| 10G-10MQLH90L-065 | G46 |
| 12G-12MQLH90S-037 | G46 |
| 12G-12MQLH90L-075 | G46 |
| 16G-16MQLH90S-044 | G46 |
| 16G-16MQLH90L-103 | G46 |
| Female Quick-Lok® High to Male O-Ring Boss Adapter | G47 |
| 4FQLH-4MB | G47 |
| 4FQLH-6MB | G47 |
| 6FQLH-4MB | G47 |
| 6FQLH-6MB | G47 |
| 6FQLH-8MB | G47 |
| 8FQLH-6MB | G47 |
| 8FQLH-8MB | G47 |
| 8FQLH-10MB | G47 |
| 10FQLH-8MB | G47 |
| 10FQLH-10MB | G47 |
| 10FQLH-12MB | G47 |
| 12FQLH-10MB | G47 |
| 12FQLH-12MB | G47 |

| Category | Page |
|---|---|
| **MegaCrimp® Couplings (Continued)** | |
| Female Quick-Lok® High to Male O-Ring Boss Adapter (Continued) | G47 |
| 12FQLH-16MB | G47 |
| 16FQLH-12MB | G47 |
| 16FQLH-16MB | G47 |
| Female Quick-Lok® High to Female JIC 37° Flare | G47 |
| 4FQLH-4FJ | G47 |
| 6FQLH-6FJ | G47 |
| 8FQLH-8FJ | G47 |
| 10FQLH-10FJ | G47 |
| 16FQLH-16FJ | G47 |
| Female Quick-Lok® High to Female Flat-Face | G48 |
| 6FQLH-6FFOR | G48 |
| 8FQLH-8FFOR | G48 |
| 10FQLH-10FFOR | G48 |
| 12FQLH-12FFOR | G48 |
| Male Quick-Lok® Low | G48 |
| 4G-6MQLL | G48 |
| 6G-6MQLL | G48 |
| 8G-8MQLL | G48 |
| 12G-12MQLL | G48 |
| 16G-16MQLL | G48 |
| Male Quick-Lok® Low - 45° Bent Tube | G49 |
| 4G-6MQLL45-026 | G49 |
| 8G-8MQLL45-033 | G49 |
| 12G-12MQLL45-030 | G49 |
| 12G-12MQLL45-038 | G49 |
| Male Quick-Lok® Low - 90° Bent Tube | G49 |
| 4G-6MQLL90-037 | G49 |
| 6G-6MQLL90-051 | G49 |
| 6G-6MQLL90-117 | G49 |
| 6G-6MQLL90-168 | G49 |
| 8G-8MQLL90-050 | G49 |
| 12G-12MQLL90-061 | G49 |
| **MegaCrimp® Couplings with TuffCoat® XTreme™ Plating** | |
| Male Pipe (NPTF - 30° Cone Seat) | G50 |
| 4G-2MP-TCX | G50 |
| 4G-4MP-TCX | G50 |
| 4G-6MP-TCX | G50 |
| 4G-8MP-TCX | G50 |
| 6G-4MP-TCX | G50 |
| 6G-6MP-TCX | G50 |
| 6G-8MP-TCX | G50 |
| 8G-6MP-TCX | G50 |
| 8G-8MP-TCX | G50 |
| 8G-12MP-TCX | G50 |
| 10G-8MP-TCX | G50 |
| 10G-12MP-TCX | G50 |
| 12G-8MP-TCX | G50 |
| 12G-12MP-TCX | G50 |
| 12G-16MP-TCX | G50 |
| 16G-12MP-TCX | G50 |
| 16G-16MP-TCX | G50 |
| 20G-20MP-TCX | G50 |
| Female Pipe (NPTF - without 30° Cone Seat) | G50 |
| 4G-2FP-TCX | G50 |
| 4G-4FP-TCX | G50 |
| 6G-4FP-TCX | G50 |
| 6G-6FP-TCX | G50 |
| 6G-8FP-TCX | G50 |
| 8G-6FP-TCX | G50 |
| 8G-8FP-TCX | G50 |
| 12G-12FP-TCX | G50 |
| Male JIC 37° Flare | G51 |
| 12G-12MJ-TCX | G51 |
| Female JIC 37° Flare Swivel | G51 |
| 4G-4FJX-TCX | G51 |
| 4G-5FJX-TCX | G51 |
| 4G-6FJX-TCX | G51 |
| 6G-6FJX-TCX | G51 |
| 6G-8FJX-TCX | G51 |
| 6G-10FJX-TCX | G51 |
| 8G-6FJX-TCX | G51 |
| 8G-8FJX-TCX | G51 |
| 8G-10FJX-TCX | G51 |

| Category | Page |
|---|---|
| **MegaCrimp® Couplings with TuffCoat® XTreme™ Plating (Continued)** | |
| Female JIC 37° Flare Swivel (Continued) | G51 |
| 8G-12FJX-TCX | G51 |
| 10G-8FJX-TCX | G51 |
| 10G-10FJX-TCX | G51 |
| 10G-12FJX-TCX | G51 |
| 12G-10FJX-TCX | G51 |
| 12G-12FJX-TCX | G51 |
| 12G-14FJX-TCX | G51 |
| 12G-16FJX-TCX | G51 |
| 16G-12FJX-TCX | G51 |
| 16G-16FJX-TCX | G51 |
| 16G-20FJX-TCX | G51 |
| 20G-20FJX-TCX | G51 |
| Female JIC 37° Flare Swivel - 45° Bent Tube | G52 |
| 4G-6FJX45S-TCX | G52 |
| 6G-6FJX45S-TCX | G52 |
| 6G-8FJX45S-TCX | G52 |
| 8G-8FJX45S-TCX | G52 |
| 8G-10FJX45S-TCX | G52 |
| 10G-10FJX45S-TCX | G52 |
| 10G-12FJX45S-TCX | G52 |
| 12G-12FJX45S-TCX | G52 |
| Female JIC 37° Flare Swivel - 90° Bent Tube | G52 |
| 8G-8FJX90M-TCX | G52 |
| 10G-10FJX90M-TCX | G52 |
| Female Flat-Face O-Ring Swivel | G53 |
| 4G-4FFORX-TCX | G53 |
| 4G-6FFORX-TCX | G53 |
| 6G-4FFORX-TCX | G53 |
| 6G-6FFORX-TCX | G53 |
| 6G-8FFORX-TCX | G53 |
| 8G-6FFORX-TCX | G53 |
| 8G-8FFORX-TCX | G53 |
| 8G-10FFORX-TCX | G53 |
| 8G-12FFORX-TCX | G53 |
| 10G-10FFORX-TCX | G53 |
| 10G-12FFORX-TCX | G53 |
| 12G-10FFORX-TCX | G53 |
| 12G-12FFORX-TCX | G53 |
| 12G-16FFORX-TCX | G53 |
| 16G-16FFORX-TCX | G53 |
| 16G-20FFORX-TCX | G53 |
| 20G-20FFORX-TCX | G53 |
| Female Flat-Face O-Ring Swivel - 45° Bent Tube | G53 |
| 4G-4FFORX45S-TCX | G53 |
| 4G-6FFORX45S-TCX | G53 |
| 6G-4FFORX45S-TCX | G53 |
| 6G-6FFORX45S-TCX | G53 |
| 6G-8FFORX45S-TCX | G53 |
| 8G-8FFORX45S-TCX | G53 |
| 8G-10FFORX45S-TCX | G53 |
| 10G-10FFORX45S-TCX | G53 |
| 12G-10FFORX45S-TCX | G53 |
| 12G-12FFORX45S-TCX | G54 |
| 12G-16FFORX45S-TCX | G54 |
| 16G-16FFORX45S-TCX | G54 |
| 20G-20FFORX45S-TCX | G54 |
| Female Flat-Face O-Ring Swivel - 90° Bent Tube | G54 |
| 4G-4FFORX90S-TCX | G54 |
| 4G-6FFORX90S-TCX | G54 |
| 6G-6FFORX90S-TCX | G54 |
| 6G-8FFORX90S-TCX | G54 |
| 8G-8FFORX90S-TCX | G54 |
| 8G-10FFORX90S-TCX | G54 |
| 10G-10FFORX90S-TCX | G54 |
| 12G-10FFORX90S-TCX | G54 |
| 12G-12FFORX90S-TCX | G54 |
| 16G-16FFORX90S-TCX | G54 |
| 20G-20FFORX90S-TCX | G54 |
| Code 61 O-Ring Flange | G54 |
| 8G-8FL-TCX | G54 |
| 12G-12FL-TCX | G55 |
| 12G-16FL-TCX | G55 |
| 16G-16FL-TCX | G55 |
| Code 61 O-Ring Flange - 90° Bent Tube | G55 |
| 12G-12FL90M-TCX | G55 |

| Category | Page |
|---|---|
| **MegaCrimp® Couplings with TuffCoat® XTreme™ Plating (Continued)** | |
| Code 61 O-Ring Flange - 90° Bent Tube (Continued) | G55 |
| 20G-20FL90S-TCX | G55 |
| **Stainless Steel Braid Couplings** | |
| Male Pipe (NPTF - 30° Cone Seat) | H3 |
| 4B-4MP-SS | H3 |
| 6B-6MP-SS | H3 |
| 8B-8MP-SS | H3 |
| 12B-12MP-SS | H3 |
| 16B-16MP-SS | H3 |
| 20B-20MP-SS | H3 |
| 24B-24MP-SS | H3 |
| 32B-32MP-SS | H3 |
| Female JIC 37° Flare Swivel | H3 |
| 6B-6FJX-SS | H3 |
| 12B-12FJX-SS | H3 |
| 16B-16FJX-SS | H3 |
| 20B-20FJX-SS | H3 |
| 24B-24FJX-SS | H3 |
| 32B-32FJX-SS | H3 |
| Female JIC 37° Flare Swivel - 45° Bent Tube | H4 |
| 6B-6FJX45S-SS | H4 |
| 12B-12FJX45S-SS | H4 |
| 16B-16FJX45S-SS | H4 |
| Female JIC 37° Flare Swivel - 90° Bent Tube | H4 |
| 6B-6FJX90M-SS | H4 |
| 12B-12FJX90S-SS | H4 |
| 12B-12FJX90M-SS | H4 |
| 16B-16FJX90M-SS | H4 |
| Female SAE 45° Flare Swivel | H4 |
| 12B-12FSX-SS | H4 |
| Dual Seat Female JIC 37°/SAE 45° Flare Swivel | H5 |
| 4B-4FJSX-SS | H5 |
| 8B-8FJSX-SS | H5 |
| 10B-10FJSX-SS | H5 |
| Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 45° Bent Tube | H5 |
| 4B-4FJSX45S-SS | H5 |
| 8B-8FJSX45S-SS | H5 |
| 10B-10FJSX45S-SS | H5 |
| Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 90° Bent Tube | H5 |
| 4B-4FJSX90S-SS | H5 |
| 4B-4FJSX90M-SS | H6 |
| 8B-8FJSX90S-SS | H6 |
| 8B-8FJSX90M-SS | H6 |
| 10B-10FJSX90S-SS | H6 |
| 10B-10FJSX90M-SS | H6 |
| Female Flat-Face O-Ring Swivel Metric Hex | H6 |
| 4B-4FFORX-SS | H6 |
| 8B-8FFORX-SS | H6 |
| 10B-10FFORX-SS | H6 |
| 12B-12FFORX-SS | H6 |
| 16B-16FFORX-SS | H6 |
| 20B-20FFORX-SS | H6 |
| 24B-24FFORX-SS | H6 |
| Code 61 O-Ring Flange | H6 |
| 24B-24FL-SS | H6 |
| 32B-32FL-SS | H6 |
| Female DIN 24° Cone Swivel - Heavy Series with O-Ring | H7 |
| 4B-10FDHORX-SS | H7 |
| 6B-12FDHORX-SS | H7 |
| 8B-16FDHORX-SS | H7 |
| 12B-20FDHORX-SS | H7 |
| 16B-25FDHORX-SS | H7 |
| 16B-30FDHORX-SS | H7 |
| 20B-38FDHORX-SS | H7 |
| 24B-38FDHORX-SS | H7 |
| Non-Skive Ferrule | H7 |
| 4B1F-1SS | H7 |
| 6B1F-1SS | H7 |
| 4B1F-2SS | H7 |
| 6B1F-2SS | H7 |
| 8B1F-1SS | H7 |
| 10B1F-1SS | H7 |

Category — Page

## Stainless Steel Braid Couplings (Continued)

Non-Skive Ferrule (Continued) H7
12B1F-2SS H7
12B1F-1SS H7
16B1F-2SS H7
16B1F-3SS H7
20B1F-1SS H7
24B1F-2SS H7
32B1F-2SS H7
24B1F-4SS H7
32B1F-4SS H7

## Power Crimp® Couplings

Male Pipe (NPTF - 30° Cone Seat) I2
3-2MP I2
3-4MP I2
4-4MP I2
5-4MP I2
6-6MP I2
6-8MP I2
8-6MP I2
8-8MP I2
12-12MP I2
16-16MP I2
24-24MP I2
32-32MP I2

Male Special Grease Fitting I2
3-2MPG I2
3-2MPGB I2

Male Pipe Swivel (NPTF - without 30° Cone Seat) I3
3-2MPX I3
8-8MPX I3

Female Pipe (NPTF - without 30° Cone Seat) I3
3-2FP I3

Male JIC 37° Flare I3
3-4MJ I3

Female JIC 37° Flare Swivel I4
3-3FJX I4
3-4FJX I4
4-4FJX I4
4-5FJX I4
4-6FJX I4
5-5FJX I4
5-6FJX I4
6-6FJX I4
6-8FJX I4
8-8FJX I4
8-10FJX I4
10-10FJX I4
10-12FJX I4
12-12FJX I4
16-16FJX I4

Female JIC 37° Flare Swivel - 45° Bent Tube I4
3C2-4FJX45S I4

Female JIC 37° Flare Swivel - 90° Bent Tube I5
3C2-4FJX90S I5
24C2-24FJX90S I5

Female Flat-Face O-Ring Swivel I5
3C2-6FFORX I5

SAE Male Inverted Swivel I5
3C2-3MIX I5

SAE Male Inverted Swivel - 45° Bent Tube I6
3C2-3MIX45 I6

SAE Male Inverted Swivel - 90° Bent Tube I6
3C2-3MIX90 I6

Female Braze-On Stems I6
3-4FBO I6
4-4FBO I6
4-5FBO I6
6-6FBO I6
6-8FBO I6
8-8FBO I6
8-10FBO I6
12-12FBO I6

Category — Page

## Power Crimp® Couplings (Continued)

Female Braze-On Stems (Continued) I6
12-16FBO I6
16-16FBO I7
20-20FBO I7
24-24FBO I7

Female DIN 24° Cone Swivel - Light Series I7
3C2-6FDLX I7

Female DIN 24° Cone Swivel - Light Series - 90° Bent Tube I7
3C2-6FDLX90 I7

Power Crimp® Two Ferrules (Steel) - PC2F Series I8
3PC2F-2 I8
4PC2F-2 I8
4PC2F-4 I8
5PC2F-2 I8
6PC2F-2 I8
6PC2F-4 I8
8PC2F-2 I8
8PC2F-4 I8
10PC2F-2B I8
10PC2F-2C I8
12PC2F-2 I8
12PC2F-4 I8
16PC2F-2 I8
16PC2F-4 I8
20PC2F-2 I8
20PC2F-4 I8
24PC2F-4 I8
32PC2F-4 I8

Power Crimp® One Non-Skive Ferrules (Steel) - PC1FS Series I8
3PC1FS I8
4M3KPC I8
4PC1F-M2S I8
4PC1FS I8
5PC1FS I8
6M3KPC I8
6PC1F-M2S I8
6PC1FS I8
8M3KPC I8
8PC1F-M2S I8
8PC1FS I8
10PC1F-M2S I9
10PC1FS-M3K I9
12PC1F-M2S I9
12PC1FS-M3K I9
16PC1F-M2S I9
16PC1FS I9
20PC1FS I9
24PC1FS I9
32PC1FS I9

## Field Attachable Type T for G1 Hose (1 Wire)

Male Pipe (NPTF - 30° Cone Seat) J1
4C1T-2RMP J1
4C1T-4RMP J1
6C1T-4RMP J1
6C1T-6RMP J1
8C1T-6RMP J1
8C1T-8RMP J1
8C1T-12RMP J1
12C1T-12RMP J1
16C1T-16RMP J1

Male Pipe Swivel (NPTF - without 30° Cone Seat) J1
4C1T-4RMPX J1
6C1T-6RMPX J1
8C1T-8RMPX J1
12C1T-12RMPX J1

Male O-Ring Boss J2
6C1T-6RMB J2
6C1T-8RMB J2
8C1T-8RMB J2
8C1T-10RMB J2

Male JIC 37° Flare J2
6C1T-6RMJ J2
8C1T-8RMJ J2
8C1T-10RMJ J2
12C1T-12RMJ J2

Category — Page

## Field Attachable Type T for G1 Hose (1 Wire) (Continued)

Female JIC 37° Flare Swivel J2
4C1T-4RFJX J2
4C1T-5RFJX J2
6C1T-6RFJX J2
6C1T-8RFJX J2
8C1T-8RFJX J3
8C1T-10RFJX J3
12C1T-12RFJX J3
16C1T-16RFJX J3

Female JIC 37° Flare Swivel - 45° Bent Tube J3
4C1T-4RFJX45 J3
6C1T-6RFJX45 J3
8C1T-8RFJX45 J3
12C1T-12RFJX45 J3

Female JIC 37° Flare Swivel - 90° Bent Tube J3
4C1T-4RFJX90 J3
6C1T-6RFJX90 J3
6C1T-8RFJX90 J3
8C1T-8RFJX90 J3
8C1T-10RFJX90 J3
12C1T-12RFJX90 J3

## Field Attachable Type T for G2 Hose (2 Wire)

Male Pipe (NPTF - 30° Cone Seat) J4
4C2AT-2RMP J4
4C2AT-4RMP J4
6C2AT-4RMP J4
6C2AT-6RMP J4
8C2AT-6RMP J4
8C2AT-8RMP J4
8C2AT-12RMP J4
12C2AT-12RMP J4
16C2AT-16RMP J4
20C2AT-20RMP J4
24C2AT-24RMP J4

Male Pipe Swivel (NPTF - without 30° Cone Seat) J4
4C2AT-4RMPX J4
6C2AT-6RMPX J4
8C2AT-8RMPX J4
12C2AT-12RMPX J4

Male O-Ring Boss J5
6C2AT-6RMB J5
6C2AT-8RMB J5
8C2AT-8RMB J5
8C2AT-10RMB J5

Male JIC 37° Flare J5
6C2AT-6RMJ J5
8C2AT-8RMJ J5
8C2AT-10RMJ J5
12C2AT-12RMJ J5

Female JIC 37° Flare Swivel J5
4C2AT-4RFJX J5
4C2AT-5RFJX J5
6C2AT-6RFJX J5
6C2AT-8RFJX J5
8C2AT-8RFJX J5
8C2AT-10RFJX J5
12C2AT-12RFJX J6
16C2AT-16RFJX J6
20C2AT-20RFJX J6
24C2AT-24RFJX J6

Female JIC 37° Flare Swivel - 45° Bent Tube J6
4C2AT-4RFJX45 J6
6C2AT-6RFJX45 J6
8C2AT-8RFJX45 J6
12C2AT-12RFJX45 J6

Female JIC 37° Flare Swivel - 90° Bent Tube J6
4C2AT-4RFJX90 J6
6C2AT-6RFJX90 J6
6C2AT-8RFJX90 J6
8C2AT-8RFJX90 J6
8C2AT-10RFJX90 J6
12C2AT-12RFJX90 J6

Female Flat-Face O-Ring Swivel J7
4C2AT-4RFFORX J7

Category — Page

## Field Attachable Type T for G2 Hose (2 Wire) (Continued)

Female Flat-Face O-Ring Swivel (Continued) J7
6C2AT-6RFFORX J7
8C2AT-8RFFORX J7
12C2AT-12RFFORX J7

Female Flat-Face O-Ring Swivel - 45° Bent Tube J7
4C2AT-4RFFORX45S J7
6C2AT-6RFFORX45S J7
8C2AT-8RFFORX45S J7
12C2AT-12RFFORX45S J7

Female Flat-Face O-Ring Swivel - 90° Bent Tube J8
4C2AT-4RFFORX90S J8
6C2AT-6RFFORX90S J8
8C2AT-8RFFORX90S J8
12C2AT-12RFFORX90S J8

## Field Attachable for C5CXH, C5C, C5D & C5M Hose

Male Pipe (NPTF - 30° Cone Seat) - Steel K2
4C5-2RMP K2
4C5-4RMP K2
5C5X-2RMP K2
5C5X-4RMP K2
6C5-4RMP K2
6C5-6RMP K2
8C5X-6RMP K2
8C5X-8RMP K2
10C5-8RMP K2
10C5-12RMP K2
12C5X-8RMP K2
12C5X-12RMP K2
16C5-12RMP K2
16C5-16RMP K2
20C5-20RMP K2
24C5-24RMP K2
32C5-32RMP K2

Male Pipe (NPTF - 30° Cone Seat) - Brass K2
6C5-6RMPB K2
8C5-8RMPB K2
10C5-8RMPB K2
16C5-16RMPB K2

Male O-Ring Boss - Steel K3
4C5-4RMB K3
6C5-6RMB K3
8C5X-8RMB K3

Male JIC 37° Flare - Steel K3
4C5-4RMJ K3
5C5X-5RMJ K3
6C5-6RMJ K3
8C5X-8RMJ K3
10C5-10RMJ K3
12C5X-12RMJ K3
16C5-16RMJ K3

Female JIC 37° Flare Swivel - Steel K3
6C5-6RFJX K3
8C5X-6RFJX K3
10C5-12RFJX K4
12C5X-12RFJX K4
16C5-16RFJX K4
20C5-20RFJX K4
24C5-24RFJX K4
32C5-32RFJX K4

Female JIC 37° Flare Swivel - Brass K4
6C5-6RFJXB K4
12C5-12RFJXB K4
16C5-16RFJXB K4

Female JIC 37° Flare Swivel - 45° Bent Tube - Steel K4
6C5-6RFJX45 K4
12C5X-12RFJX45S K4
16C5-16RFJX45 K4

Female JIC 37° Flare Swivel - 90° Bent Tube - Steel K5
6C5-6RFJX90 K5
6C5-6RFJX90L K5
12C5X-12RFJX90S K5
12C5X-12RFJX90L K5
16C5-16RFJX90 K5
16C5-16RFJX90L K5

# INDEX


| Category | Page |
|---|---|
| **Field Attachable for C5CXH, C5C, C5D & C5M Hose (Continued)** | |
| Female JIC 37° Flare Swivel - 90° Bent Tube - Steel (Continued) | K5 |
| 20C5-20RFJX90S | K5 |
| 20C5-20RFJX90L | K5 |
| Male SAE 45° Flare - Steel | K5 |
| 4C5-4RMS | K5 |
| 5C5X-5RMS | K5 |
| 6C5-6RMS | K5 |
| 8C5X-8RMS | K5 |
| 10C5-10RMS | K5 |
| 12C5X-12RMS | K5 |
| Female SAE 45° Flare Swivel - Steel | K6 |
| 6C5-6RFSX | K6 |
| 10C5-12RFSX | K6 |
| 12C5X-12RFSX | K6 |
| Female SAE 45° Flare Swivel - Brass | K6 |
| 6C5-6RFSXB | K6 |
| 12C5-12RFSXB | K6 |
| Female SAE 45° Flare Swivel - 45° Bent Tube - Steel | K6 |
| 6C5-6RFSX45 | K6 |
| 12C5X-12RFSX45S | K7 |
| Female SAE 45° Flare Swivel - 90° Bent Tube - Steel | K7 |
| 6C5-6RFSX90 | K7 |
| 6C5-6RFSX90L | K7 |
| 12C5X-12RFSX90S | K7 |
| 12C5X-12RFSX90L | K7 |
| Dual Seat Female JIC 37°/SAE 45° Flare Swivel - Steel | K7 |
| 4C5-4RFJSX | K7 |
| 5C5X-4RFJSX | K7 |
| 5C5X-5RFJSX | K7 |
| 6C5-8RFJSX | K7 |
| 8C5X-8RFJSX | K7 |
| 10C5-8RFJSX | K7 |
| 10C5-10RFJSX | K7 |
| Dual Seat Female JIC 37°/SAE 45° Flare Swivel - Brass | K8 |
| 5C5-5RFJSXB | K8 |
| 8C5-8RFJSXB | K8 |
| 10C5-10RFJSXB | K8 |
| Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 45° Bent Tube - Steel | K8 |
| 4C5-4RFJSX45 | K8 |
| 5C5X-5RFJSX45S | K8 |
| 6C5-8RFJSX45 | K8 |
| 8C5X-8RFJSX45S | K8 |
| 10C5-10RFJSX45 | K8 |
| Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 90° Bent Tube - Steel | K9 |
| 4C5-4RFJSX90 | K9 |
| 4C5-4RFJSX90L | K9 |
| 5C5X-5RFJSX90S | K9 |
| 5C5X-5RFJSX90L | K9 |
| 8C5X-8RFJSX90S | K9 |
| 8C5X-8RFJSX90L | K9 |
| 10C5-10RFJSX90 | K9 |
| 10C5-10RFJSX90L | K9 |
| Female Flat-Face Swivel - Steel | K9 |
| 4C5-4RFFORX | K9 |
| 6C5-6RFFORX | K9 |
| 8C5X-8RFFORX | K9 |
| 10C5-10RFFORX | K9 |
| 12C5X-12RFFORX | K9 |
| Female Flat-Face Swivel - 45° Bent Tube - Steel | K10 |
| 4C5-4RFFORX45 | K10 |
| Female Flat-Face Swivel - 90° Bent Tube - Steel | K10 |
| 4C5-4RFFORX90 | K10 |
| 6C5-6RFFORX90S | K10 |
| Special Flange - 90° - Engine Oil Connection (Code 61 2-Bolt) | K11 |
| 20C5-20RFL90S | K11 |
| Male SAE 45° Flare Inverted Swivel - Steel | K11 |
| 4C5-4RMIX | K11 |
| 5C5X-5RMIX | K11 |
| 5C5X-6RMIX | K11 |
| 6C5-5RMIX | K11 |
| 6C5-6RMIX | K11 |
| 6C5-8RMIX | K11 |
| 8C5X-6RMIX | K11 |

| Category | Page |
|---|---|
| **Field Attachable for C5CXH, C5C, C5D & C5M Hose (Continued)** | |
| Male SAE 45° Flare Inverted Swivel - Steel (Continued) | K11 |
| 8C5X-8RMIX | K11 |
| Male SAE 45° Flare Inverted Swivel - 45° Bent Tube - Steel | K12 |
| 4C5-4RMIX45 | K12 |
| 6C5-6RMIX45 | K12 |
| 8C5X-8RMIX45-028 | K12 |
| Male SAE 45° Flare Inverted Swivel - 90° Bent Tube - Steel | K12 |
| 4C5-4RMIX90 | K12 |
| 5C5X-5RMIX90-042 | K12 |
| 6C5-6RMIX90 | K12 |
| 6C5-8RMIX90 | K12 |
| 8C5X-6RMIX90-043 | K12 |
| 8C5X-8RMIX90-045 | K12 |
| SAE Male Flareless Assembly - Steel | K13 |
| 4C5-4RMFA | K13 |
| 5C5X-5RMFA | K13 |
| 6C5-4RMFA | K13 |
| 6C5-6RMFA | K13 |
| 8C5X-8RMFA | K13 |
| 10C5-10RMFA | K13 |
| Female Air Brake Swivel - Steel | K13 |
| 6C5-6RFABX | K13 |
| 8C5X-6RFABX | K13 |
| Parker Triple Thread Female Swivel - Steel | K13 |
| 16C5-16RFZX | K13 |
| **Field Attachable for C5E Hose** | |
| Male Pipe (NPTF - 30° Cone Seat) - Steel | K14 |
| 4C5E-2RMP | K14 |
| 4C5E-4RMP | K14 |
| 5C5E-4RMP | K14 |
| 6C5E-4RMP | K14 |
| 6C5E-6RMP | K14 |
| 8C5E-6RMP | K14 |
| 8C5E-8RMP | K14 |
| 10C5E-8RMP | K14 |
| 12C5E-12RMP | K14 |
| 12C5E-16RMP | K14 |
| 16C5E-12RMP | K14 |
| 16C5E-16RMP | K14 |
| 20C5E-20RMP | K14 |
| Female JIC 37° Flare Swivel - Steel | K14 |
| 6C5E-6RFJX | K14 |
| 12C5E-12RFJX | K14 |
| 16C5E-16RFJX | K14 |
| 20C5E-20RFJX | K14 |
| Female JIC 37° Flare Swivel - 45° Bent Tube - Steel | K15 |
| 6C5E-6RFJX45 | K15 |
| 12C5E-12RFJX45 | K15 |
| Female JIC 37° Flare Swivel - 90° Bent Tube - Steel | K15 |
| 6C5E-6RFJX90 | K15 |
| 12C5E-12RFJX90 | K15 |
| 16C5E-16RFJX90 | K15 |
| 20C5E-20RFJX90 | K15 |
| Female SAE 45° Flare Swivel - Steel | K16 |
| 6C5E-6RFSX | K16 |
| 12C5E-12RFSX | K16 |
| Female SAE 45° Flare Swivel - 45° Bent Tube - Steel | K16 |
| 6C5E-6RFSX45 | K16 |
| 12C5E-12RFSX45 | K16 |
| Female SAE 45° Flare Swivel - 90° Bent Tube - Steel | K17 |
| 6C5E-6RFSX90 | K17 |
| 12C5E-12RFSX90 | K17 |
| Dual Seat Female JIC 37°/SAE 45° Flare Swivel - Steel | K17 |
| 4C5E-4RFJSX | K17 |
| 5C5E-5RFJSX | K17 |
| 8C5E-8RFJSX | K17 |
| 10C5E-10RFJSX | K17 |
| Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 45° Bent Tube - Steel | K18 |
| 4C5E-4RFJSX45 | K18 |
| 8C5E-8RFJSX45 | K18 |
| 10C5E-10RFJSX45 | K18 |

## Field Attachable for C5E Hose (Continued)


| Category | Page |
|---|---|
| Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 90° Bent Tube - Steel | K18 |
| 4C5E-4RFJSX90 | K18 |
| 8C5E-8RFJSX90 | K18 |
| 10C5E-10RFJSX90 | K18 |
| Special Flange - 90° - Engine Oil Connection (Code 61 2-Bolt) - Steel | K19 |
| 20C5E-20RFL90S | K19 |
| Male SAE 45° Flare Inverted Swivel - Steel | K19 |
| 4C5E-4RMIX | K19 |
| 5C5E-5RMIX | K19 |
| 6C5E-5RMIX | K19 |
| 6C5E-6RMIX | K19 |
| 8C5E-8RMIX | K19 |
| Male SAE 45° Flare Inverted Swivel - 45° Bent Tube - Steel | K20 |
| 6C5E-6RMIX45 | K20 |
| 8C5E-8RMIX45 | K20 |
| Male SAE 45° Flare Inverted Swivel - 90° Bent Tube - Steel | K20 |
| 4C5E-4RMIX90 | K20 |
| 5C5E-5RMIX90 | K20 |
| 6C5E-5RMIX90 | K20 |
| 6C5E-6RMIX90 | K20 |
| 8C5E-8RMIX90 | K20 |
| SAE Male Flareless Assembly - Steel | K21 |
| 4C5E-4RMFA | K21 |
| 5C5E-5RMFA | K21 |
| 6C5E-4RMFA | K21 |
| 6C5E-6RMFA | K21 |
| 8C5E-8RMFA | K21 |
| 10C5E-10RMFA | K21 |
| Parker Triple Thread Female Swivel - Steel | K21 |
| 16C5E-16RFZX | K21 |


## C14 Couplings


| Category | Page |
|---|---|
| Male Pipe (NPTF - 30° Cone Seat) - Stainless Steel | L2 |
| 4C14-2MP-SS | L2 |
| 4C14-4MP-SS | L2 |
| 5C14-4MP-SS | L2 |
| 6C14-4MP-SS | L2 |
| 6C14-6MP-SS | L2 |
| 8C14-6MP-SS | L2 |
| 8C14-8MP-SS | L2 |
| 10C14-8MP-SS | L2 |
| 12C14-12MP-SS | L2 |
| 16C14-16MP-SS | L2 |
| Male Pipe (NPTF - 30° Cone Seat) - Brass | L2 |
| 4C14-2MP-B | L2 |
| 4C14-4MP-B | L2 |
| 5C14-4MP-B | L2 |
| 6C14-4MP-B | L2 |
| 6C14-6MP-B | L2 |
| 8C14-6MP-B | L2 |
| 8C14-8MP-B | L2 |
| 10C14-8MP-B | L2 |
| 12C14-12MP-B | L2 |
| 16C14-16MP-B | L2 |
| Dual Seat Female JIC 37°/SAE 45° Flare Swivel - Stainless Steel | L3 |
| 4C14-4FJSX-SS | L3 |
| 5C14-5FJSX-SS | L3 |
| 8C14-8FJSX-SS | L3 |
| 10C14-10FJSX-SS | L3 |
| 16C14-16FJSX-SS | L3 |
| Dual Seat Female JIC 37°/SAE 45° Flare Swivel - Brass | L3 |
| 4C14-4FJSX-B | L3 |
| 5C14-5FJSX-B | L3 |
| 8C14-8FJSX-B | L3 |
| 10C14-10FJSX-B | L3 |
| 16C14-16FJSX-B | L3 |
| Female JIC 37° Flare Swivel - Stainless Steel | L4 |
| 6C14-6FJX-SS | L4 |
| 12C14-12FJX-SS | L4 |
| Female JIC 37° Flare Swivel - Brass | L4 |
| 6C14-6FJX-B | L4 |
| 12C14-12FJX-B | L4 |


## C14 Couplings (Continued)


| Category | Page |
|---|---|
| Female JIC 37° Flare Swivel - 45° Bent Tube - Steel | L4 |
| 4C14-4FJX45 | L4 |
| 5C14-5FJX45 | L5 |
| 6C14-6FJX45 | L5 |
| 8C14-8FJX45 | L5 |
| 10C14-10FJX45 | L5 |
| 12C14-12FJX45 | L5 |
| 16C14-16FJX45 | L5 |
| Female JIC 37° Flare Swivel - 90° Bent Tube - Steel | L5 |
| 4C14-4FJX90 | L5 |
| 5C14-5FJX90 | L5 |
| 6C14-6FJX90 | L5 |
| 8C14-8FJX90 | L5 |
| 10C14-10FJX90 | L5 |
| 12C14-12FJX90 | L5 |
| 16C14-16FJX90 | L5 |
| Female SAE 45° Flare Swivel - Brass | L6 |
| 6C14-6FSX-B | L6 |
| 12C14-12FSX-B | L6 |
| Female SAE 45° Flare Swivel - 45° Bent Tube - Steel | L6 |
| 4C14-4FSX45 | L6 |
| 5C14-5FSX45 | L6 |
| 6C14-6FSX45 | L6 |
| 8C14-8FSX45 | L6 |
| 10C14-10FSX45 | L6 |
| 12C14-12FSX45 | L6 |
| Female SAE 45° Flare Swivel - 90° Bent Tube - Steel | L7 |
| 4C14-4FSX90 | L7 |
| 5C14-5FSX90 | L7 |
| 6C14-6FSX90 | L7 |
| 8C14-8FSX90 | L7 |
| 10C14-10FSX90 | L7 |
| 12C14-12FSX90 | L7 |
| Air Brake Compression - Brass | L7 |
| 8C14-8ABC-B | L7 |
| 10C14-10ABC-B | L7 |
| 12C14-12ABC-B | L7 |
| Straight Tube Assembly - Brass | L8 |
| 10C14-8STA-B | L8 |
| 10C14-10STA-B | L8 |
| 12C14-12STA-B | L8 |
| SAE Male Inverted Swivel - Steel | L8 |
| 4C14-4MIX | L8 |
| 5C14-5MIX | L8 |
| 6C14-6MIX | L8 |
| 8C14-8MIX | L8 |
| 10C14-10MIX | L8 |
| SAE Male Inverted Swivel - 45° Bent Tube - Steel | L9 |
| 4C14-4MIX45 | L9 |
| 6C14-6MIX45 | L9 |
| 8C14-8MIX45 | L9 |
| 10C14-10MIX45 | L9 |
| 12C14-12MIX45 | L9 |
| SAE Male Inverted Swivel - 90° Bent Tube - Steel | L9 |
| 4C14-4MIX90 | L9 |
| 5C14-5MIX90 | L9 |
| 6C14-6MIX90 | L9 |
| 8C14-8MIX90 | L9 |
| 10C14-10MIX90 | L9 |
| 12C14-12MIX90 | L9 |
| Two-Bolt Flange Swivel - Brass (Steel Flange) - Laundry Flange | L10 |
| 12C14-12TBFLX | L10 |
| 16C14-16TBFLX | L10 |
| C14 Assembly with Two Female Dual Seat JIC 37°/SAE 45° Flare Swivel (FJSX) Couplings-Steel | L10 |
| 10C14-10FJSX-10FJSX-18 | L10 |
| 10C14-10FJSX-10FJSX-24 | L10 |
| 10C14-10FJSX-10FJSX-30 | L10 |
| 10C14-10FJSX-10FJSX-36 | L10 |
| 10C14-10FJSX-10FJSX-42 | L10 |
| 10C14-10FJSX-10FJSX-48 | L10 |
| 10C14-10FJSX-10FJSX-54 | L10 |
| 10C14-10FJSX-10FJSX-72 | L10 |
| 10C14-10FJSX-10FJSX-84 | L10 |

# INDEX


| Category | Page |
|---|---|
| **C14 Couplings (Continued)** | |
| C14 Assembly with Two Air Brake Compression (ABC) Couplings - Steel | L10 |
| 10C14-10ABC-10ABC-18 | L10 |
| 10C14-10ABC-10ABC-24 | L10 |
| C14 Assembly with Two Straight Tube Assembly (STA) Couplings - Steel | L11 |
| 10C14-10STA-10STA-24 | L11 |
| 10C14-10STA-10STA-36 | L11 |
| 12C14-12STA-12STA-24 | L11 |
| C14 One Straight Tube Assembly (STA) and One Air Brake Compression (ABC) Couplings - Steel | L11 |
| 10C14-10STA-10ABC-18 | L11 |
| 10C14-10STA-10ABC-24 | L11 |
| 10C14-10STA-10ABC-36 | L11 |
| 10C14-10STA-10ABC-48 | L11 |
| **GL Couplings** | |
| Male Pipe (NPTF - 30° Cone Seat) | M2 |
| 12GL-12MP | M2 |
| 12GL-16MP | M2 |
| 16GL-16MP | M2 |
| 20GL-20MP | M2 |
| 24GL-24MP | M2 |
| 32GL-32MP | M2 |
| Male Pipe Swivel (NPTF - without 30° Cone Seat) | M2 |
| 16GL-16MPX | M2 |
| Female JIC 37° Flare Swivel | M2 |
| 12GL-12FJX | M2 |
| 12GL-14FJX | M3 |
| 12GL-16FJX | M3 |
| 16GL-16FJX | M3 |
| 20GL-20FJX | M3 |
| 24GL-20FJX | M3 |
| 24GL-24FJX | M3 |
| 32GL-32FJX | M3 |
| 40GL-40FJX | M3 |
| Female JIC 37° Flare Swivel - 45° Bent Tube | M3 |
| 12GL-12FJX45S-021 | M3 |
| Female JIC 37° Flare Swivel - 90° Bent Tube | M3 |
| 12GL-12FJX90S | M3 |
| 16GL-16FJX90S | M3 |
| 20GL-20FJX90M | M3 |
| 24GL-20FJX90M | M3 |
| 24GL-20FJX90L | M3 |
| 24GL-24FJX90-092 | M4 |
| Female Flat-Face Swivel | M4 |
| 12GL-12FFORX | M4 |
| 16GL-16FFORX | M4 |
| 20GL-20FFORX | M4 |
| 24GL-24FFORX | M4 |
| Female Flat-Face Swivel - 45° Bent Tube | M4 |
| 12GL-12FFORX45S | M4 |
| 16GL-16FFORX45S | M4 |
| 20GL-20FFORX45S | M4 |
| Female Flat-Face Swivel - 90° Bent Tube | M5 |
| 12GL-12FFORX90S | M5 |
| 12GL-12FFORX90M | M5 |
| 16GL-16FFORX90S | M5 |
| 20GL-20FFORX90S | M5 |
| 24GL-24FFORX90M | M5 |
| Code 61 O-Ring Flange | M5 |
| 12GL-12FL | M5 |
| 16GL-16FL | M5 |
| 20GL-20FL | M5 |
| 24GL-24FL | M5 |
| 32GL-32FL | M5 |
| 32GL-40FL | M5 |
| 40GL-40FL | M5 |
| 40GL-48FL | M5 |
| 40GL-56FL | M5 |
| 40GL-64FL | M5 |
| 48GL-48FL | M5 |
| 56GL-56FL | M5 |
| 64GL-64FL | M5 |
| Code 61 O-Ring Flange - 22° Bent Tube | M6 |
| 24GL-24FL22M-018 | M6 |

| Category | Page |
|---|---|
| **GL Couplings (Continued)** | |
| Code 61 O-Ring Flange - 22° Bent Tube (Continued) | M6 |
| 40GL-40FL22 | M6 |
| 40GL-48FL22 | M6 |
| Code 61 O-Ring Flange - 30° Bent Tube | M6 |
| 12GL-12FL30M | M6 |
| 16GL-16FL30M | M6 |
| 20GL-20FL30M | M6 |
| 24GL-24FL30M | M6 |
| 32GL-32FL30M | M6 |
| 40GL-40FL30 | M6 |
| 40GL-48FL30 | M6 |
| 48GL-48FL30 | M6 |
| Code 61 O-Ring Flange - 45° Bent Tube | M7 |
| 12GL-12FL45M | M7 |
| 16GL-16FL45S | M7 |
| 20GL-20FL45S | M7 |
| 24GL-24FL45S | M7 |
| 32GL-32FL45S | M7 |
| 32GL-40FL45S | M7 |
| 40GL-40FL45 | M7 |
| 40GL-48FL45 | M7 |
| 48GL-48FL45 | M7 |
| 56GL-56FL45 | M7 |
| 56GL-64FL45 | M7 |
| 64GL-64FL45 | M7 |
| Code 61 O-Ring Flange - 60° Bent Tube | M7 |
| 12GL-12FL60M | M7 |
| 16GL-16FL60M | M7 |
| 20GL-20FL60S | M7 |
| 24GL-24FL60S | M7 |
| 32GL-32FL60S | M7 |
| 40GL-40FL60 | M7 |
| 48GL-48FL60 | M7 |
| Code 61 O-Ring Flange - 67 1/2° Bent Tube | M8 |
| 32GL-32FL67S | M8 |
| 40GL-40FL67 | M8 |
| 48GL-48FL67 | M8 |
| 64GL-64FL67 | M8 |
| Code 61 O-Ring Flange - 90° Bent Tube | M8 |
| 12GL-12FL90M | M8 |
| 12GL-16FL90S | M8 |
| 16GL-16FL90S | M8 |
| 16GL-20FL90S | M8 |
| 20GL-20FL90S | M8 |
| 20GL-24FL90-068 | M8 |
| 24GL-24FL90S | M8 |
| 32GL-32FL90S | M8 |
| 32GL-40FL90-114 | M8 |
| 40GL-40FL90 | M8 |
| 40GL-48FL90 | M8 |
| 48GL-48FL90 | M8 |
| 56GL-56FL90 | M8 |
| 56GL-64FL90 | M8 |
| 64GL-64FL90 | M8 |
| Code 61 Captive O-Ring Flange | M9 |
| 56GL-56FLCF | M9 |
| 64GL-64FLCF | M9 |
| Code 61 Captive O-Ring Flange - 45° Bent Tube | M9 |
| 56GL-56FLCF45-054 | M9 |
| Code 61 Captive O-Ring Flange - 90° Bent Tube | M10 |
| 56GL-56FLCF90-143 | M10 |
| **GLX® Couplings** | |
| Male Pipe (NPTF 30° Cone Seat) | N2 |
| 4GLX-2MP | N2 |
| 4GLX-4MP | N2 |
| 6GLX-4MP | N2 |
| 6GLX-6MP | N2 |
| 8GLX-6MP | N2 |
| 8GLX-8MP | N2 |
| 8GLX-12MP | N2 |
| 10GLX-8MP | N2 |
| 12GLX-8MP | N2 |
| 12GLX-12MP | N2 |
| 16GLX-16MP | N2 |

| Category | Page |
|---|---|
| **GLX® Couplings (Continued)** | |
| Male Pipe (NPTF 30° Cone Seat) (Continued) | N2 |
| 20GLX-20MP | N2 |
| MPX Male NPTF Swivel | N2 |
| 4GLX-4MPX | N2 |
| 6GLX-6MPX | N2 |
| 8GLX-8MPX | N2 |
| 12GLX-12MPX | N2 |
| 16GLX-16MPX | N2 |
| 20GLX-20MPX | N2 |
| FP Female NPTF | N3 |
| 4GLX-4FP | N3 |
| 6GLX-4FP | N3 |
| 6GLX-6FP | N3 |
| 8GLX-6FP | N3 |
| 8GLX-8FP | N3 |
| 12GLX-12FP | N3 |
| 16GLX-16FP | N3 |
| FPX Female NPSM Swivel | N3 |
| 4GLX-4FPX | N3 |
| 6GLX-4FPX | N3 |
| 6GLX-6FPX | N3 |
| 8GLX-6FPX | N3 |
| 8GLX-8FPX | N3 |
| 12GLX-12FPX | N3 |
| 16GLX-16FPX | N3 |
| Female JIC 37° Flare Swivel | N4 |
| 4GLX-4FJX | N4 |
| 6GLX-6FJX | N4 |
| 8GLX-8FJX | N4 |
| 10GLX-10FJX | N4 |
| 12GLX-12FJX | N4 |
| 16GLX-16FJX | N4 |
| 20GLX-20FJX | N4 |
| MS 45° SAE Male Solid | N4 |
| 4GLX-4MS | N4 |
| 6GLX-6MS | N4 |
| 8GLX-8MS | N4 |
| 12GLX-12MS | N4 |
| FSX 45° SAE Female Swivel | N5 |
| 4GLX-4FSX | N5 |
| 6GLX-6FSX | N5 |
| 8GLX-8FSX | N5 |
| 12GLX-12FSX | N5 |
| **PCTS Thermoplastic Couplings (One-Piece)** | |
| Male Pipe (NPTF - 30° Cone Seat) | O2 |
| 2PCTS-2MP | O2 |
| 2PCTS-4MP | O2 |
| 3PCTS-2MP | O2 |
| 3PCTS-4MP | O2 |
| 4PCTS-4MP | O2 |
| 4PCTS-6MP | O2 |
| 6PCTS-4MP | O2 |
| 6PCTS-6MP | O2 |
| 6PCTS-8MP | O2 |
| 8PCTS-8MP | O2 |
| Male Pipe Swivel (NPTF - without 30° Cone Seat) | O2 |
| 2PCTS-2MPX | O2 |
| 3PCTS-2MPX | O2 |
| 3PCTS-4MPX | O2 |
| 4PCTS-4MPX | O2 |
| Female JIC 37° Flare Swivel | O3 |
| 2PCTS-3FJX | O3 |
| 4PCTS-6FJX | O3 |
| 8PCTS-12FJX | O3 |
| 12PCTS-12FJX | O3 |
| 16PCTS-16FJX | O3 |
| Female JIC 37° Flare Swivel - 90° Bent Tube | O3 |
| 3PCTS-4FJX90S | O3 |
| 6PCTS-6FJX90S | O3 |
| 8PCTS-8FJX90L | O3 |
| Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 45° Bent Tube | O3 |
| 2PCTS-4FJSX | O3 |
| 3PCTS-4FJSX | O3 |

| Category | Page |
|---|---|
| **PCTS Thermoplastic Couplings (One-Piece) (Continued)** | |
| Dual Seat Female JIC 37°/SAE 45° Flare Swivel - 45° Bent Tube (Continued) | O3 |
| 4PCTS-4FJSX | O3 |
| 5PCTS-5FJSX | O3 |
| **PolarSeal® Couplings (ACA)** | |
| Male SAE 45° Flare - Aluminum | P2 |
| 6ACA-6MS | P2 |
| 8ACA-8MS | P2 |
| 10ACA-10MS | P2 |
| 12ACA-12MS | P2 |
| Male SAE 45° Flare - 45° Bent Tube - Aluminum | P2 |
| 6ACA-6MS45 | P2 |
| 8ACA-8MS45 | P2 |
| 10ACA-10MS45 | P2 |
| 12ACA-12MS45 | P2 |
| Male SAE 45° Flare - 90° Bent Tube - Aluminum | P2 |
| 6ACA-6MS90 | P2 |
| 8ACA-8MS90 | P3 |
| 10ACA-10MS90 | P3 |
| 12ACA-12MS90 | P3 |
| Female SAE 45° Flare Swivel - Aluminum | P3 |
| 6ACA-6FSX | P3 |
| 6ACA-8FSX | P3 |
| 8ACA-6FSX | P3 |
| 8ACA-8FSX | P3 |
| 10ACA-8FSX | P3 |
| 10ACA-10FSX | P3 |
| 12ACA-10FSX | P3 |
| 12ACA-12FSX | P3 |
| Female SAE 45° Flare Swivel - Steel | P3 |
| 6ACA-6FSX-S | P3 |
| 8ACA-8FSX-S | P3 |
| 10ACA-10FSX-S | P3 |
| Female SAE 45° Flare Swivel - 45° Bent Tube - Aluminum | P4 |
| 6ACA-6FSX45 | P4 |
| 8ACA-6FSX45 | P4 |
| 8ACA-8FSX45 | P4 |
| 10ACA-10FSX45 | P4 |
| 12ACA-10FSX45 | P4 |
| 12ACA-12FSX45 | P4 |
| Female SAE 45° Flare Swivel - 90° Bent Tube - Aluminum | P4 |
| 6ACA-6FSX90 | P4 |
| 6ACA-8FSX90 | P4 |
| 8ACA-6FSX90 | P4 |
| 8ACA-8FSX90 | P4 |
| 10ACA-8FSX90 | P4 |
| 10ACA-10FSX90 | P4 |
| 12ACA-10FSX90 | P4 |
| 12ACA-12FSX90 | P4 |
| Female SAE 45° Flare Swivel - 90° Bent Tube - Steel | P5 |
| 6ACA-6FSX90-S | P5 |
| 8ACA-8FSX90-S | P5 |
| 10ACA-10FSX90-S | P5 |
| Male SAE Flareless Assembly - Aluminum | P5 |
| 6ACA-6MFA | P5 |
| 6ACA-8MFA | P5 |
| 8ACA-6MFA | P5 |
| 8ACA-8MFA | P5 |
| 8ACA-10MFA | P5 |
| 10ACA-8MFA | P5 |
| 10ACA-10MFA | P5 |
| 12ACA-10MFA | P5 |
| 12ACA-12MFA | P5 |
| Male SAE Flareless Assembly - 90° Block - Aluminum | P6 |
| 6ACA-6MFA90 | P6 |
| 6ACA-8MFA90 | P6 |
| 8ACA-6MFA90 | P6 |
| 8ACA-8MFA90 | P6 |
| 8ACA-10MFA90 | P6 |
| 10ACA-8MFA90 | P6 |
| 10ACA-10MFA90 | P6 |
| 12ACA-10MFA90 | P6 |
| 12ACA-12MFA90 | P6 |

## PolarSeal® Couplings (ACA) (Continued)


| Category | Page |
|---|---|
| Female Braze-On Stems - Aluminum | P6 |
| 6ACA-6FBO | P6 |
| 8ACA-8FBO | P6 |
| 10ACA-10FBO | P6 |
| 12ACA-10FBO | P6 |
| 12ACA-12FBO | P6 |
| Female Braze-On Stems - Steel | P7 |
| 6ACA-6FBO-S | P7 |
| 8ACA-8FBO-S | P7 |
| 10ACA-10FBO-S | P7 |
| 12ACA-10FBO-S | P7 |
| 12ACA-12FBO-S | P7 |
| Hose Length Extender - Aluminum | P7 |
| 6ACA-6HLE | P7 |
| 6ACA-8HLE | P7 |
| 8ACA-8HLE | P7 |
| 8ACA-10HLE | P7 |
| 10ACA-10HLE | P7 |
| 12ACA-10HLE | P7 |
| 12ACA-12HLE | P7 |
| Hose Length Extender - Steel | P7 |
| 12ACA-10HLE-S | P7 |
| Hose Length Extender - 90° Bent Tube - Aluminum | P8 |
| 6ACA-6HLE90 | P8 |
| 8ACA-8HLE90 | P8 |
| 10ACA-10HLE90 | P8 |
| 12ACA-12HLE90 | P8 |
| Hose Length Extender with Sight Glass - Aluminum | P8 |
| 6ACA-6HLESG | P8 |
| Hose Length Extender - Tee - Aluminum | P9 |
| 6ACA-6HLET | P9 |
| 8ACA-8HLET | P9 |
| 10ACA-10HLET | P9 |
| 12ACA-10HLET | P9 |
| 12ACA-12HLET | P9 |
| Hose Length Extender - 180° Bent Tube - Aluminum | P9 |
| 6ACA-6HLE180 | P9 |
| 8ACA-8HLE180 | P9 |
| 12ACA-12HLE180 | P9 |
| Male SAE Tube O-Ring Nut Swivel with R134a Service Port - Aluminum | P10 |
| 6ACA-6MTON134SP | P10 |
| 8ACA-8MTON134SP | P10 |
| 10ACA-10MTON134SP | P10 |
| 12ACA-12MTON134SP | P10 |
| Male SAE Tube O-Ring Nut Swivel with R134a Service Port - 90° Bent Tube - Aluminum | P10 |
| 10ACA-10MTON134SP90 | P10 |
| Male SAE Tube O-Ring Nut Swivel - Aluminum | P11 |
| 6ACA-6MTON | P11 |
| 6ACA-7MTON | P11 |
| 6ACA-8MTON | P11 |
| 8ACA-6MTON | P11 |
| 8ACA-8MTON | P11 |
| 10ACA-10MTON | P11 |
| 12ACA-10MTON | P11 |
| 12ACA-12MTON | P11 |
| Male SAE Tube O-Ring Nut Swivel - Steel | P11 |
| 6ACA-6MTON-S | P11 |
| 6ACA-7MTON-S | P11 |
| 10ACA-10MTON-S | P11 |
| Male SAE Tube O-Ring Nut - 45° Bent Tube - Aluminum | P12 |
| 6ACA-6MTON45 | P12 |
| 6ACA-8MTON45 | P12 |
| 8ACA-6MTON45 | P12 |
| 8ACA-8MTON45 | P12 |
| 10ACA-10MTON45 | P12 |
| 12ACA-12MTON45 | P12 |
| Male SAE Tube O-Ring Nut - 45° Bent Tube - Steel | P12 |
| 6ACA-6MTON45-S | P12 |
| 10ACA-10MTON45-S | P12 |
| Male SAE Tube O-Ring Nut - 90° Bent Tube - Aluminum | P13 |
| 6ACA-6MTON90 | P13 |
| 6ACA-7MTON90 | P13 |
| 6ACA-8MTON90 | P13 |
| 8ACA-6MTON90 | P13 |
| 8ACA-8MTON90 | P13 |
| 10ACA-10MTON90 | P13 |
| 12ACA-10MTON90 | P13 |
| 12ACA-12MTON90 | P13 |
| Male SAE Tube O-Ring Nut - 90° Bent Tube - Steel | P13 |
| 6ACA-6MTON90-S | P13 |
| 8ACA-8MTON90-S | P13 |
| 10ACA-10MTON90-S | P13 |
| Female SAE Tube O-Ring Nut Swivel with R12 Service Port - Aluminum | P14 |
| 6ACA-6FTONR12SP | P14 |
| 8ACA-8FTONR12SP | P14 |
| 10ACA-10FTONR12SP | P14 |
| Female SAE Tube O-Ring Nut Swivel with R12 Service Port - 90° Bent Tube - Aluminum | P14 |
| 6ACA-6FTONR12SP90 | P14 |
| 8ACA-8FTONR12SP90 | P14 |
| 10ACA-10FTONR12SP90 | P14 |
| 12ACA-10FTONR12SP90 | P14 |
| Female SAE Tube O-Ring Nut Swivel with R134a Service Port - Aluminum | P15 |
| 6ACA-6FTON134SP | P15 |
| 8ACA-8FTON134SP | P15 |
| 10ACA-10FTON134SP | P15 |
| 12ACA-10FTON134SP | P15 |
| Female SAE Tube O-Ring Nut Swivel with R134a Service Port - Steel | P15 |
| 6ACA-6FTON134SP-S | P15 |
| 8ACA-8FTON134SP-S | P15 |
| 10ACA-10FTON134SP-S | P15 |
| Female SAE Tube O-Ring Nut Swivel with R134a Service Port - 90° Bent Tube - Aluminum | P16 |
| 6ACA-6FTON134SP90 | P16 |
| 8ACA-8FTON134SP90 | P16 |
| 10ACA-10FTON134SP90 | P16 |
| 12ACA-10FTON134SP90 | P16 |
| Female SAE Tube O-Ring Nut Swivel with R134a Service Port - 90° Bent Tube - Steel | P16 |
| 6ACA-6FTON134SP90-S | P16 |
| 8ACA-8FTON134SP90-S | P16 |
| 10ACA-10FTON134SP90-S | P16 |
| 12ACA-10FTON134SP90-S | P16 |
| Female SAE Tube O-Ring Nut Swivel - Aluminum | P17 |
| 6ACA-5FTON | P17 |
| 6ACA-6FTON | P17 |
| 6ACA-8FTON | P17 |
| 8ACA-6FTON | P17 |
| 8ACA-8FTON | P17 |
| 10ACA-8FTON | P17 |
| 10ACA-10FTON | P17 |
| 10ACA-12FTON | P17 |
| 12ACA-10FTON | P17 |
| 12ACA-12FTON | P17 |
| Female SAE Tube O-Ring Nut Swivel - Steel | P17 |
| 6ACA-6FTON-S | P17 |
| 8ACA-8FTON-S | P17 |
| 10ACA-10FTON-S | P17 |
| 12ACA-10FTON-S | P17 |
| 12ACA-12FTON-S | P17 |
| Female SAE Tube O-Ring Nut Swivel - 45° Bent Tube - Aluminum | P18 |
| 6ACA-6FTON45 | P18 |
| 8ACA-6FTON45 | P18 |
| 8ACA-8FTON45 | P18 |
| 10ACA-8FTON45 | P18 |
| 10ACA-10FTON45 | P18 |
| 12ACA-10FTON45 | P18 |
| 12ACA-12FTON45 | P18 |
| Female SAE Tube O-Ring Nut Swivel - 45° Bent Tube - Steel | P18 |
| 6ACA-6FTON45-S | P18 |
| 8ACA-8FTON45-S | P18 |
| 10ACA-10FTON45-S | P18 |
| Female SAE Tube O-Ring Nut Swivel - 90° Bent Tube - Aluminum | P19 |
| 6ACA-5FTON90 | P19 |
| 6ACA-6FTON90 | P19 |
| 6ACA-8FTON90 | P19 |
| 8ACA-6FTON90 | P19 |
| 8ACA-8FTON90 | P19 |
| 10ACA-8FTON90 | P19 |

## PolarSeal® Couplings (ACA) (Continued)


| Category | Page |
|---|---|
| Female SAE Tube O-Ring Nut Swivel - 90° Bent Tube - Aluminum (Continued) | P19 |
| 10ACA-10FTON90 | P19 |
| 10ACA-12FTON90 | P19 |
| 12ACA-10FTON90 | P19 |
| 12ACA-12FTON90 | P19 |
| Female SAE Tube O-Ring Nut Swivel - 90° Bent Tube - Steel | P19 |
| 6ACA-6FTON90-S | P19 |
| 8ACA-8FTON90-S | P19 |
| 10ACA-10FTON90-S | P19 |
| 12ACA-10FTON90-S | P19 |
| Female SAE Tube O-Ring Metric Nut Swivel - Aluminum | P20 |
| 6ACA-16FTOMN | P20 |
| 6ACA-18FTOMN | P20 |
| 6ACA-20FTOMN | P20 |
| 8ACA-20FTOMN | P20 |
| 10ACA-22FTOMN | P20 |
| 10ACA-24FTOMN | P20 |
| 12ACA-27FTOMN | P20 |
| Female SAE Tube O-Ring Metric Nut Swivel - 45° Bent Tube - Aluminum | P20 |
| 6ACA-14FTOMN45 | P20 |
| 6ACA-16FTOMN45 | P20 |
| 6ACA-18FTOMN45 | P20 |
| 6ACA-20FTOMN45 | P20 |
| 8ACA-20FTOMN45 | P20 |
| 10ACA-22FTOMN45 | P20 |
| 10ACA-24FTOMN45 | P20 |
| 12ACA-27FTOMN45 | P20 |
| Female SAE Tube O-Ring Metric Nut Swivel - 90° Bent Tube - Aluminum | P21 |
| 6ACA-16FTOMN90 | P21 |
| 6ACA-18FTOMN90 | P21 |
| 6ACA-20FTOMN90 | P21 |
| 8ACA-20FTOMN90 | P21 |
| 10ACA-22FTOMN90 | P21 |
| 10ACA-24FTOMN90 | P21 |
| 12ACA-27FTOMN90 | P21 |
| Female SAE Tube O-Ring Nut Swivel - 90° Block - Steel | P21 |
| 8ACA-8FTON90BL-S | P21 |
| 10ACA-10FTON90BL-S | P21 |
| 12ACA-10FTON90BL-S | P21 |
| Male Inverted O-Ring - Aluminum | P22 |
| 6ACA-6MIO | P22 |
| 8ACA-8MIO | P22 |
| 10ACA-10MIO | P22 |
| 12ACA-12MIO | P22 |
| Male Inverted O-Ring - Steel | P22 |
| 6ACA-6MIO-S | P22 |
| 8ACA-8MIO-S | P22 |
| 10ACA-10MIO-S | P22 |
| Male Inverted O-Ring - 45° Bent Tube - Aluminum | P22 |
| 6ACA-6MIO45 | P22 |
| 8ACA-8MIO45 | P22 |
| 10ACA-10MIO45 | P22 |
| Male Inverted O-Ring - 90° Bent Tube - Aluminum | P23 |
| 6ACA-6MIO90 | P23 |
| 8ACA-8MIO90 | P23 |
| 10ACA-10MIO90 | P23 |
| Male Inverted O-Ring Bulkhead - Aluminum | P23 |
| 6ACA-6MIOBKHD | P23 |
| 8ACA-8MIOBKHD | P23 |
| 10ACA-10MIOBKHD | P23 |
| Male Inverted O-Ring Bulkhead - Steel | P23 |
| 6ACA-6MIOBKHD-S | P23 |
| 10ACA-10MIOBKHD-S | P23 |
| Male Inverted O-Ring Bulkhead - 90° Bent Tube - Aluminum | P24 |
| 6ACA-6MIOBKHD90 | P24 |
| 8ACA-8MIOBKHD90 | P24 |
| 10ACA-10MIOBKHD90 | P24 |
| Female SAE Tube Dual O-Ring Nut - Aluminum | P24 |
| 8ACA-8FTDON | P24 |
| 10ACA-10FTDON | P24 |
| 12ACA-12FTDON | P24 |
| Female SAE Tube Dual O-Ring Nut - 45° Bent Tube - Aluminum | P25 |
| 8ACA-8FTDON45 | P25 |
| 12ACA-12FTDON45 | P25 |
| Female SAE Tube Dual O-Ring Nut - 90° Bent Tube - Aluminum | P25 |
| 8ACA-8FTDON90 | P25 |
| 10ACA-10FTDON90 | P25 |
| 12ACA-12FTDON90 | P25 |
| Female SAE Tube Dual O-Ring Metric Nut - Aluminum | P25 |
| 8ACA-24FTDOMN | P25 |
| 10ACA-24FTDOMN | P26 |
| 12ACA-27FTDOMN | P26 |
| Female SAE Tube Dual O-Ring Metric Nut - 45° Bent Tube - Aluminum | P26 |
| 8ACA-24FTDOMN45 | P26 |
| 10ACA-24FTDOMN45 | P26 |
| 12ACA-27FTDOMN45 | P26 |
| Female SAE Tube Dual O-Ring Metric Nut - 90° Bent Tube - Aluminum | P26 |
| 8ACA-24FTDOMN90 | P26 |
| 10ACA-24FTDOMN90 | P26 |
| 12ACA-27FTDOMN90 | P26 |
| Female SAE Tube O-Ring Nut - 180° Bent Tube - Aluminum | P27 |
| 6ACA-6FTON180 | P27 |
| 8ACA-8FTON180 | P27 |
| 12ACA-12FTON180 | P27 |
| Male Inverted O-Ring with R134a Service Port - Aluminum | P27 |
| 6ACA-6MIO134SP | P27 |
| 8ACA-8MIO134SP | P27 |
| 10ACA-10MIO134SP | P27 |
| 12ACA-12MIO134SP | P27 |
| Male Inverted O-Ring with R134a Service Port - 90° Bent Tube - Aluminum | P28 |
| 6ACA-6MIO134SP90 | P28 |
| 8ACA-8MIO134SP90 | P28 |
| 10ACA-10MIO134SP90 | P28 |
| Universal Tee O-Ring Splicer English Threads - Aluminum | P28 |
| 6ACA-6TORSP | P28 |
| 6ACA-8TORSP | P28 |
| 10ACA-10TORSP | P28 |
| 10ACA-12TORSP | P28 |
| Female SAE Tube O-Ring Nut Swivel with R134a High Pressure Service Port - Aluminum | P29 |
| 10ACA-10FTON134SPH | P29 |
| Male Metric Flareless Assembly - Aluminum | P29 |
| 6ACA-8MMFA | P29 |
| 8ACA-12MMFA | P29 |
| 10ACA-14.5MMFA | P29 |
| Female (Ford) Spring Lock Tee O-Ring Splicer - Aluminum | P29 |
| 6ACA-8FSLTORSP | P29 |
| Female (Ford) Spring Lock Liquid Line Splicer - Aluminum | P30 |
| 6ACA-8FSLSP | P30 |
| Male (Ford) Spring Lock - 45° Bent Tube - Aluminum | P30 |
| 6ACA-6MSL45 | P30 |
| 6ACA-8MSL45 | P30 |
| 8ACA-8MSL45 | P30 |
| 10ACA-10MSL45 | P30 |
| 12ACA-10MSL45 | P30 |
| 12ACA-12MSL45 | P30 |
| Male (Ford) Spring Lock - Aluminum | P30 |
| 6ACA-6MSL | P30 |
| 6ACA-8MSL | P30 |
| 8ACA-8MSL | P31 |
| 10ACA-10MSL | P31 |
| 12ACA-10MSL | P31 |
| 12ACA-12MSL | P31 |
| Male (Ford) Spring Lock - 90° Bent Tube - Aluminum | P31 |
| 6ACA-6MSL90 | P31 |
| 6ACA-8MSL90 | P31 |
| 8ACA-8MSL90 | P31 |
| 10ACA-10MSL90 | P31 |
| 12ACA-10MSL90 | P31 |
| Female (Ford) Spring Lock - Aluminum | P31 |
| 6ACA-6FSL | P31 |
| 6ACA-8FSL | P31 |
| 8ACA-8FSL | P31 |
| 10ACA-10FSL | P31 |

| Category | Page |
|---|---|
| **PolarSeal® Couplings (ACA) (Continued)** | |
| Female (Ford) Spring Lock - Aluminum (Continued) | P31 |
| 12ACA-10FSL | P31 |
| 12ACA-12FSL | P31 |
| Female (Ford) Spring Lock - 90° Bent Tube - Aluminum | P32 |
| 6ACA-6FSL90 | P32 |
| 6ACA-8FSL90 | P32 |
| 8ACA-8FSL90 | P32 |
| 10ACA-10FSL90 | P32 |
| 12ACA-10FSL90 | P32 |
| 12ACA-12FSL90 | P32 |
| Hose Splicer with R12 Thread Service Port - Aluminum | P32 |
| 6ACA-R12SP | P32 |
| 8ACA-R12SP | P32 |
| 10ACA-R12SP | P32 |
| 12ACA-R12SP | P32 |
| Female (Ford) Spring Lock - 45° Bent Tube - Aluminum | P33 |
| 6ACA-6FSL45 | P33 |
| 6ACA-8FSL45 | P33 |
| 8ACA-8FSL45 | P33 |
| 10ACA-10FSL45 | P33 |
| 12ACA-10FSL45 | P33 |
| 12ACA-12FSL45 | P33 |
| Hose Splicer with R134a Service Port - Aluminum | P33 |
| 6ACA-R134SP | P33 |
| 8ACA-R134SP | P33 |
| 10ACA-R134SP | P33 |
| 12ACA-R134SP | P33 |
| Hose Splicer with R134a Service Port - Steel | P34 |
| 6ACA-R134SP-S | P34 |
| 8ACA-R134SP-S | P34 |
| 10ACA-R134SP-S | P34 |
| 12ACA-R134SP-S | P34 |
| Female Rotalok (Compressor Connection) with R134a Service Port - 90° Block - Aluminum | P34 |
| 8ACA-R134SP-RL | P34 |
| 10ACA-R134SP-RL | P34 |
| Compressor Female SAE Tube O-Ring Nut Swivel - 90° Bent Tube - Steel | P35 |
| 6ACA-6CFTON90-S | P35 |
| 8ACA-10CFTON90-S | P35 |
| 10ACA-10CFTON90-S | P35 |
| 12ACA-10CFTON90-S | P35 |
| Compressor Female SAE Tube O-Ring Nut Swivel - 90° Block - Steel | P35 |
| 8ACA-10CFTON90BL-S | P35 |
| 12ACA-10CFTON90BL-S | P35 |
| Compressor Female Tube O-Ring Nut with 134a Service Port - 90° Block - Steel | P36 |
| 8ACA-10CFTON134SP90BL-S | P36 |
| 10ACA-10CFTON134SP90BL-S | P36 |
| 12ACA-10CFTON134SP90BL-S | P36 |
| Compressor Block - Single w/Switch or Service Port - 90° Bent Tube - Aluminum | P36 |
| 8ACA-8CBSR12SP90 | P36 |
| 10ACA-8CBSR12SP90 | P36 |
| 12ACA-8CBSR12SP90 | P36 |
| Compressor Block - Single Reverse w/Switch or Service Port - 90° Bent Tube - Aluminum | P37 |
| 8ACA-8CBSRR12SP90 | P37 |
| 10ACA-8CBSRR12SP90 | P37 |
| 12ACA-8CBSRR12SP90 | P37 |
| R12 Ferrules | P37 |
| 6PCACF | P37 |
| 8PCACF | P37 |
| 10PCACF | P37 |
| 12PCACF | P37 |
| Inline Orifice Tube | P37 |
| IOT-RED | P37 |
| IOT-WHITE | P38 |
| IOT-BLUE | P38 |
| IOT-BLACK | P38 |
| Female Flareless Nut - Aluminum | P38 |
| 6ACFFN | P38 |
| 8ACFFN | P38 |
| 10ACFFN | P38 |
| 12ACFFN | P38 |
| Female Flareless Sleeve | P38 |
| 6ACFFS | P38 |

| Category | Page |
|---|---|
| **PolarSeal® Couplings (ACA) (Continued)** | |
| Female Flareless Sleeve (Continued) | P38 |
| 8ACFFS | P38 |
| 10ACFFS | P38 |
| 12ACFFS | P38 |
| Metric Female Flareless Sleeve | P39 |
| 8ACMFFS | P39 |
| 12ACMFFS | P39 |
| 14.5ACMFFS | P39 |
| Accumulator/Compressor Sealing Washer | P39 |
| 10CPWTN | P39 |
| 10CPWTK | P39 |
| 12ACMW | P39 |
| 12CPWTN | P39 |
| Valve Core | P39 |
| .210VC | P39 |
| Valve Cap for R12 Service Port | P40 |
| 4R12CAP | P40 |
| Red High Side Cap R134a Port | P40 |
| 8HS134CAP | P40 |
| Blue Low Side Cap R134a Port | P40 |
| 8LS134CAP | P40 |
| O-Ring for Switch | P41 |
| 6SWOR | P41 |
| O-Rings for PolarSeal® Couplings | P41 |
| 6ACOR | P41 |
| 8ACOR | P41 |
| 10ACOR | P41 |
| 12ACOR | P41 |
| O-Ring for Ford Spring Lock | P41 |
| 6FSLOR | P41 |
| 8FSLOR | P41 |
| 10FSLOR | P41 |
| 12FSLOR | P41 |
| **PolarSeal® II Couplings (ACC)** | |
| Male Flareless Assembly | Q2 |
| 6ACC-6MFA | Q2 |
| 8ACC-8MFA | Q2 |
| 10ACC-10MFA | Q2 |
| 12ACC-12MFA | Q2 |
| Male Flareless Assembly - 90° Bent Tube | Q2 |
| 6ACC-6MFA90 | Q2 |
| 8ACC-8MFA90 | Q2 |
| 10ACC-10MFA90 | Q2 |
| 12ACC-12MFA90 | Q2 |
| Weld On Hose End | Q2 |
| 6ACC-6FBO | Q2 |
| 8ACC-8FBO | Q2 |
| 10ACC-10FBO | Q2 |
| 12ACC-10FBO | Q2 |
| 12ACC-12FBO | Q2 |
| 12ACC-16FBO | Q2 |
| Splicer | Q3 |
| 6ACC-6HLE | Q3 |
| 8ACC-8HLE | Q3 |
| 10ACC-10HLE | Q3 |
| 12ACC-12HLE | Q3 |
| T Splicer | Q3 |
| 6ACC-6HLET | Q3 |
| 8ACC-8HLET | Q3 |
| 10ACC-10HLET | Q3 |
| 12ACC-12HLET | Q3 |
| Y Splicer | Q3 |
| 8ACC-8HLEY | Q3 |
| 10ACC-10HLEY | Q3 |
| 12ACC-12HLEY | Q3 |
| Male O-Ring - 180° Bent Tube | Q4 |
| 6ACC-6MTON180 | Q4 |
| 10ACC-10MTON180 | Q4 |
| Male O-Ring with Switch or Service Port - 90° Bent Tube | Q4 |
| 8ACC-8MTON90134SWPH | Q4 |

| Category | Page |
|---|---|
| **PolarSeal® II Couplings (ACC) (Continued)** | |
| Male O-Ring | Q4 |
| 6ACC-6MTON | Q4 |
| 8ACC-6MTON | Q4 |
| 8ACC-8MTON | Q4 |
| 10ACC-10MTON | Q4 |
| 12ACC-10MTON | Q4 |
| 12ACC-12MTON | Q4 |
| 16ACC-10MTON | Q4 |
| 16ACC-12MTON | Q4 |
| Male O-Ring - 45° Bent Tube | Q5 |
| 6ACC-6MTON45 | Q5 |
| 12ACC-10MTON45 | Q5 |
| Male O-Ring - 90° Bent Tube | Q5 |
| 6ACC-6MTON90 | Q5 |
| 8ACC-6MTON90 | Q5 |
| 8ACC-8MTON90 | Q5 |
| 10ACC-8MTON90 | Q5 |
| 10ACC-10MTON90 | Q5 |
| 12ACC-10MTON90 | Q5 |
| 12ACC-12MTON90 | Q5 |
| Straight Female O-Ring with R134 Service Port H | Q5 |
| 8ACC-8FTON134SPH | Q5 |
| 10ACC-8FTON134SPH | Q6 |
| Straight Female O-Ring with R134 Service Port L | Q6 |
| 10ACC-10FTON134SPL | Q6 |
| 12ACC-10FTON134SPL | Q6 |
| 12ACC-12FTON134SPL | Q6 |
| 16ACC-10FTON134SPL | Q6 |
| Straight Female O-Ring with Switch Port M | Q6 |
| 12ACC-10FTONMSWP | Q6 |
| 12ACC-12FTONMSWP | Q6 |
| Straight Female O-Ring with Switch Port P | Q7 |
| 8ACC-8FTONSWP | Q7 |
| 12ACC-12FTONSWP | Q7 |
| Female O-Ring with R134 Service Port H - 90° Bent Tube | Q7 |
| 6ACC-8FTON134SPH90 | Q7 |
| 8ACC-8FTON134SPH90 | Q7 |
| 10ACC-8FTON134SPH90 | Q7 |
| 10ACC-10FTON134SPH90 | Q7 |
| Female O-Ring with R134 Service Port L - 90° Bent Tube | Q7 |
| 10ACC-10FTON134SPL90 | Q7 |
| 12ACC-10FTON134SPL90 | Q8 |
| Female O-Ring with Switch Port M - 90° Bent Tube | Q8 |
| 10ACC-10FTONMSWP90 | Q8 |
| 12ACC-12FTONMSWP90 | Q8 |
| Female O-Ring with Switch Port P - 90° Bent Tube | Q8 |
| 8ACC-8FTONSWP90 | Q8 |
| 10ACC-8FTONSWP90 | Q8 |
| 12ACC-10FTONMSWP90 | Q8 |
| 12ACC-12FTONSWP90 | Q8 |
| Straight Female O-Ring | Q9 |
| 6ACC-6FTON | Q9 |
| 6ACC-8FTON | Q9 |
| 8ACC-6FTON | Q9 |
| 8ACC-8FTON | Q9 |
| 8ACC-10FTON | Q9 |
| 10ACC-8FTON | Q9 |
| 10ACC-10FTON | Q9 |
| 12ACC-10FTON | Q9 |
| 12ACC-12FTON | Q9 |
| 16ACC-10FTON | Q9 |
| 16ACC-12FTON | Q9 |
| Female O-Ring - 45° Bent Tube | Q9 |
| 6ACC-6FTON45 | Q9 |
| 8ACC-8FTON45 | Q9 |
| 10ACC-8FTON45 | Q9 |
| 10ACC-10FTON45 | Q9 |
| 12ACC-10FTON45 | Q9 |
| 12ACC-12FTON45 | Q9 |
| 16ACC-12FTON45 | Q9 |
| Female O-Ring - 90° Bent Tube | Q10 |
| 6ACC-6FTON90 | Q10 |
| 6ACC-8FTON90 | Q10 |

| Category | Page |
|---|---|
| **PolarSeal® II Couplings (ACC) (Continued)** | |
| Female O-Ring - 90° Bent Tube (Continued) | Q10 |
| 8ACC-6FTON90 | Q10 |
| 8ACC-8FTON90 | Q10 |
| 8ACC-10FTON90 | Q10 |
| 10ACC-8FTON90 | Q10 |
| 10ACC-10FTON90 | Q10 |
| 12ACC-10FTON90 | Q10 |
| 12ACC-12FTON90 | Q10 |
| 16ACC-10FTON90 | Q10 |
| 16ACC-12FTON90 | Q10 |
| Metric Female O-Ring | Q10 |
| 8ACC-20FTOMN | Q10 |
| 10ACC-27FTOMN | Q10 |
| Metric Female O-Ring - 90° Bent Tube | Q11 |
| 6ACC-18FTOMN90 | Q11 |
| 8ACC-20FTOMN90 | Q11 |
| 12ACC-27FTOMN90 | Q11 |
| Male Insert O-Ring | Q11 |
| 6ACC-6MIO | Q11 |
| 8ACC-6MIO | Q11 |
| 8ACC-8MIO | Q11 |
| 12ACC-10MIO | Q11 |
| Male Insert O-Ring - 90° Bent Tube | Q11 |
| 6ACC-6MIO90 | Q11 |
| 8ACC-6MIO90 | Q11 |
| 8ACC-8MIO90 | Q11 |
| 10ACC-8MIO90 | Q11 |
| 10ACC-10MIO90 | Q12 |
| 12ACC-10MIO90 | Q12 |
| Male Insert O-Ring Bulkhead | Q12 |
| 6ACC-6MIOBKHD | Q12 |
| 8ACC-8MIOBKHD | Q12 |
| 10ACC-10MIOBKHD | Q12 |
| 12ACC-10MIOBKHD | Q12 |
| 16ACC-12MIOBKHD | Q12 |
| Male Insert O-Ring Bulkhead - 90° Bent Tube | Q12 |
| 6ACC-6MIOBKHD90 | Q12 |
| 8ACC-8MIOBKHD90 | Q12 |
| 10ACC-10MIOBKHD90 | Q12 |
| 12ACC-10MIOBKHD90 | Q12 |
| Splicer with R134 Service Port H | Q13 |
| 6ACC-6HLE134SPH | Q13 |
| 8ACC-8HLE134SPH | Q13 |
| 10ACC-10HLE134SPH | Q13 |
| Splicer with R134 Service Port L | Q13 |
| 10ACC-10HLE134SPL | Q13 |
| 12ACC-12HLE134SPL | Q13 |
| 16ACC-16HLE134SPL | Q13 |
| Splicer with Switch Port M | Q13 |
| 8ACC-8HLEMSWP | Q13 |
| 10ACC-10HLEMSWP | Q13 |
| 12ACC-12HLEMSWP | Q13 |
| Splicer with Switch Port P | Q14 |
| 6ACC-6HLESWP | Q14 |
| 8ACC-8HLESWP | Q14 |
| 10ACC-10HLESWP | Q14 |
| 12ACC-12HLESWP | Q14 |
| Metric Female O-Ring with Switch or Service Port - 90° Bent Tube | Q14 |
| 6ACC-10FTOMN90134SPH | Q14 |
| Metric Male Insert O-Ring | Q14 |
| 10ACC-20MIOM | Q14 |
| Clamp Assemblies | Q15 |
| 6CLAMP | Q15 |
| 8CLAMP | Q15 |
| 10CLAMP | Q15 |
| 12CLAMP | Q15 |
| 16CLAMP | Q15 |
| **PolarSeal® II Couplings (ACB)** | |
| Female SAE 45° Flare Swivel - Aluminum | R1 |
| 6ACB-6FSX | R1 |
| 6ACB-8FSX | R1 |

## PolarSeal® II Couplings (ACB) (Continued)


| Category | Page |
|---|---|
| Female SAE 45° Flare Swivel - Aluminum (Continued) | R1 |
| 8ACB-6FSX | R1 |
| 8ACB-8FSX | R1 |
| 10ACB-8FSX | R1 |
| 10ACB-10FSX | R1 |
| 12ACB-12FSX | R1 |
| Female SAE 45° Flare Swivel - Steel | R1 |
| 6ACB-6FSX-S | R1 |
| 8ACB-8FSX-S | R1 |
| 12ACB-10FSX-S | R1 |
| Female SAE 45° Flare Swivel - 45° Bent Tube - Aluminum | R1 |
| 6ACB-6FSX45 | R1 |
| 8ACB-8FSX45 | R1 |
| 10ACB-10FSX45 | R1 |
| 12ACB-12FSX45 | R1 |
| Female SAE 45° Flare Swivel - 45° Bent Tube - Steel | R2 |
| 10ACB-8FSX45-S | R2 |
| Female SAE 45° Flare Swivel - 90° Bent Tube - Aluminum | R2 |
| 6ACB-6FSX90 | R2 |
| 8ACB-8FSX90 | R2 |
| 10ACB-10FSX90 | R2 |
| 12ACB-10FSX90 | R2 |
| 12ACB-12FSX90 | R2 |
| Female SAE 45° Flare Swivel - 90° Bent Tube - Steel | R2 |
| 6ACB-6FSX90-S | R2 |
| 8ACB-8FSX90-S | R2 |
| 10ACB-8FSX90-S | R3 |
| 10ACB-10FSX90-S | R3 |
| 12ACB-10FSX90-S | R3 |
| 12ACB-12FSX90-S | R3 |
| Male SAE Flareless Assembly - Steel | R3 |
| 6ACB-6MFA-S | R3 |
| 6ACB-8MFA-S | R3 |
| 8ACB-6MFA-S | R3 |
| 8ACB-8MFA-S | R3 |
| 8ACB-10MFA-S | R3 |
| 10ACB-8MFA-S | R3 |
| 10ACB-10MFA-S | R3 |
| 12ACB-10MFA-S | R3 |
| 12ACB-12MFA-S | R3 |
| Male SAE Flareless Assembly - 90° Block - Steel | R3 |
| 6ACB-6MFA90-S | R3 |
| 6ACB-8MFA90-S | R3 |
| 8ACB-8MFA90-S | R3 |
| 8ACB-10MFA90-S | R4 |
| 10ACB-8MFA90-S | R4 |
| 10ACB-10MFA90-S | R4 |
| 12ACB-10MFA90-S | R4 |
| 12ACB-12MFA90-S | R4 |
| Female Braze-On Stems - Aluminum | R4 |
| 6ACB-6FBO | R4 |
| 8ACB-8FBO | R4 |
| 10ACB-10FBO | R4 |
| 12ACB-10FBO | R4 |
| 12ACB-12FBO | R4 |
| Female Braze-On Stems - Steel | R4 |
| 6ACB-6FBO-S | R4 |
| 8ACB-8FBO-S | R4 |
| 10ACB-10FBO-S | R4 |
| 12ACB-10FBO-S | R4 |
| 12ACB-12FBO-S | R4 |
| Hose Length Extender - Aluminum | R5 |
| 6ACB-6HLE | R5 |
| 6ACB-8HLE | R5 |
| 8ACB-8HLE | R5 |
| 8ACB-10HLE | R5 |
| 10ACB-10HLE | R5 |
| 12ACB-10HLE | R5 |
| 12ACB-12HLE | R5 |
| Hose Length Extender - Steel | R5 |
| 6ACB-6HLE-S | R5 |
| 6ACB-8HLE-S | R5 |
| 8ACB-8HLE-S | R5 |
| 8ACB-10HLE-S | R5 |


## PolarSeal® II Couplings (ACB) (Continued)


| Category | Page |
|---|---|
| Hose Length Extender - Steel (Continued) | R5 |
| 10ACB-10HLE-S | R5 |
| 12ACB-10HLE-S | R5 |
| 12ACB-12HLE-S | R5 |
| Hose Length Extender - 90° Bent Tube - Steel | R6 |
| 6ACB-6HLE90-S | R6 |
| 8ACB-8HLE90-S | R6 |
| 10ACB-10HLE90-S | R6 |
| 12ACB-12HLE90-S | R6 |
| Hose Length Extender with Sight Glass - Steel | R6 |
| 6ACB-6HLESG-S | R6 |
| Hose Length Extender - Tee - Aluminum | R7 |
| 6ACB-6HLET | R7 |
| 10ACB-10HLET | R7 |
| 12ACB-12HLET | R7 |
| Hose Length Extender - Tee - Steel | R7 |
| 6ACB-6HLET-S | R7 |
| 8ACB-8HLET-S | R7 |
| 10ACB-10HLET-S | R7 |
| 12ACB-12HLET-S | R7 |
| Female O-Ring with R134 Service Port - 45° Bent Tube - Aluminum | R8 |
| 8ACB-8FTON134SP45 | R8 |
| 10ACB-10FTON134SP45 | R8 |
| Female O-Ring with R134 Service Port - 45° Bent Tube - Steel | R8 |
| 6ACB-6FTON134SP45-S | R8 |
| 8ACB-8FTON134SP45-S | R8 |
| 10ACB-10FTON134SP45-S | R8 |
| 12ACB-10FTON134SP45-S | R8 |
| Female O-Ring with R12 Service Port - 45° Bent Tube - Steel | R9 |
| 6ACB-6FTONR12SP45-S | R9 |
| 8ACB-8FTONR12SP45-S | R9 |
| 10ACB-10FTONR12SP45-S | R9 |
| Male SAE Tube O-Ring Nut Swivel with R134a Service Port - Steel | R9 |
| 6ACB-6MTON134SP-S | R9 |
| 10ACB-10MTON134SP-S | R9 |
| Male SAE Tube O-Ring Nut Swivel with R134a Service Port - 90° Bent Tube - Steel | R10 |
| 10ACB-10MTON134SP90-S | R10 |
| Male SAE Tube O-Ring Nut Swivel - Aluminum | R10 |
| 6ACB-6MTON | R10 |
| 8ACB-6MTON | R10 |
| 8ACB-8MTON | R10 |
| 10ACB-10MTON | R10 |
| 12ACB-10MTON | R10 |
| 12ACB-12MTON | R10 |
| Male SAE Tube O-Ring Nut Swivel - Steel | R11 |
| 6ACB-6MTON-S | R11 |
| 6ACB-7MTON-S | R11 |
| 8ACB-6MTON-S | R11 |
| 8ACB-8MTON-S | R11 |
| 10ACB-8MTON-S | R11 |
| 10ACB-10MTON-S | R11 |
| 12ACB-10MTON-S | R11 |
| 12ACB-12MTON-S | R11 |
| Male SAE Tube O-Ring Nut - 45° Bent Tube - Aluminum | R11 |
| 6ACB-6MTON45 | R11 |
| 8ACB-8MTON45 | R11 |
| 10ACB-10MTON45 | R11 |
| 12ACB-12MTON45 | R11 |
| Male SAE Tube O-Ring Nut - 45° Bent Tube - Steel | R12 |
| 6ACB-6MTON45-S | R12 |
| 8ACB-6MTON45-S | R12 |
| 8ACB-8MTON45-S | R12 |
| 10ACB-10MTON45-S | R12 |
| 12ACB-12MTON45-S | R12 |
| Male SAE Tube O-Ring Nut - 90° Bent Tube - Aluminum | R12 |
| 6ACB-6MTON90 | R12 |
| 8ACB-6MTON90 | R12 |
| 8ACB-8MTON90 | R12 |
| 10ACB-10MTON90 | R12 |
| 12ACB-10MTON90 | R12 |
| 12ACB-12MTON90 | R12 |

Category Page

## PolarSeal® II Couplings (ACB) (Continued)


Male SAE Tube O-Ring Nut - 90° Bent Tube - Steel R13
6ACB-6MTON90-S R13
6ACB-7MTON90-S R13
8ACB-6MTON90-S R13
8ACB-8MTON90-S R13
10ACB-10MTON90-S R13
12ACB-10MTON90-S R13
12ACB-12MTON90-S R13

Female SAE Tube O-Ring Nut Swivel with R12 Service Port - Aluminum R13
8ACB-8FTONR12SP R13

Female SAE Tube O-Ring Nut Swivel with R12 Service Port - Steel R14
6ACB-6FTONR12SP-S R14
8ACB-8FTONR12SP-S R14
10ACB-10FTONR12SP-S R14

Female SAE Tube O-Ring Nut Swivel with R12 Service Port - 90° Bent Tube - Aluminum R14
6ACB-6FTONR12SP90 R14

Female SAE Tube O-Ring Nut Swivel with R12 Service Port - 90° Bent Tube - Steel R15
6ACB-6FTONR12SP90-S R15
8ACB-8FTONR12SP90-S R15
10ACB-10FTONR12SP90-S R15
12ACB-10FTONR12SP90-S R15

Female SAE Tube O-Ring Nut Swivel with R134a Service Port - Aluminum R15
6ACB-6FTON134SP R15
8ACB-8FTON134SP R15
10ACB-10FTON134SP R15
12ACB-10FTON134SP R15

Female SAE Tube O-Ring Nut Swivel with R134a Service Port - Steel R16
6ACB-6FTON134SP-S R16
8ACB-8FTON134SP-S R16
10ACB-10FTON134SP-S R16
12ACB-10FTON134SP-S R16
12ACB-12FTON134SP-S R16

Female SAE Tube O-Ring Nut Swivel with R134a Service Port - 90° Bent Tube - Aluminum R16
6ACB-6FTON134SP90 R16
8ACB-8FTON134SP90 R16
10ACB-10FTON134SP90 R16
12ACB-10FTON134SP90 R16

Female SAE Tube O-Ring Nut Swivel with R134a Service Port - 90° Bent Tube - Steel R17
6ACB-6FTON134SP90-S R17
8ACB-8FTON134SP90-S R17
10ACB-10FTON134SP90-S R17
12ACB-10FTON134SP90-S R17

Female SAE Tube O-Ring Nut Swivel - Aluminum R17
6ACB-6FTON R17
6ACB-8FTON R17
8ACB-6FTON R17
8ACB-8FTON R17
10ACB-8FTON R17
10ACB-10FTON R17
10ACB-12FTON R17
12ACB-10FTON R17
12ACB-12FTON R17

Female SAE Tube O-Ring Nut Swivel - Steel R18
6ACB-6FTON-S R18
6ACB-8FTON-S R18
8ACB-6FTON-S R18
8ACB-8FTON-S R18
10ACB-8FTON-S R18
10ACB-10FTON-S R18
10ACB-12FTON-S R18
12ACB-10FTON-S R18
12ACB-12FTON-S R18

Female SAE Tube O-Ring Nut Swivel - 45° Bent Tube - Aluminum R18
6ACB-6FTON45 R18
8ACB-6FTON45 R18
8ACB-8FTON45 R18
10ACB-8FTON45 R18
10ACB-10FTON45 R18
12ACB-10FTON45 R18
12ACB-12FTON45 R18

Female SAE Tube O-Ring Nut Swivel - 45° Bent Tube - Steel R19
6ACB-6FTON45-S R19
8ACB-6FTON45-S R19
8ACB-8FTON45-S R19


Category Page

## PolarSeal® II Couplings (ACB) (Continued)


Female SAE Tube O-Ring Nut Swivel - 45° Bent Tube - Steel (Continued) R19
10ACB-8FTON45-S R19
10ACB-10FTON45-S R19
12ACB-10FTON45-S R19
12ACB-12FTON45-S R19

Female SAE Tube O-Ring Nut Swivel - 90° Bent Tube - Aluminum R19
6ACB-6FTON90 R19
6ACB-8FTON90 R19
8ACB-6FTON90 R19
8ACB-8FTON90 R19
10ACB-8FTON90 R19
10ACB-10FTON90 R19
10ACB-12FTON90 R19
12ACB-10FTON90 R19
12ACB-12FTON90 R19

Female SAE Tube O-Ring Nut Swivel - 90° Bent Tube - Steel R20
6ACB-6FTON90-S R20
6ACB-8FTON90-S R20
8ACB-6FTON90-S R20
8ACB-8FTON90-S R20
10ACB-8FTON90-S R20
10ACB-10FTON90-S R20
10ACB-12FTON90-S R20
12ACB-10FTON90-S R20
12ACB-12FTON90-S R20

Female SAE Tube O-Ring Metric Nut Swivel - Aluminum R20
6ACB-20FTOMN R20
8ACB-20FTOMN R20
10ACB-22FTOMN R20

Female SAE Tube O-Ring Metric Nut Swivel - Steel R21
8ACB-20FTOMN-S R21
12ACB-27FTOMN-S R21

Female SAE Tube O-Ring Metric Nut Swivel - 45° Bent Tube - Aluminum R21
6ACB-18FTOMN45 R21
6ACB-20FTOMN45 R21
8ACB-20FTOMN45 R21
12ACB-27FTOMN45 R21

Female SAE Tube O-Ring Metric Nut Swivel - 45° Bent Tube - Steel R21
8ACB-20FTOMN45-S R21
12ACB-27FTOMN45-S R21

Female SAE Tube O-Ring Metric Nut Swivel - 90° Bent Tube - Aluminum R22
6ACB-18FTOMN90 R22
8ACB-20FTOMN90 R22
12ACB-27FTOMN90 R22

Female SAE Tube O-Ring Metric Nut Swivel - 90° Bent Tube - Steel R22
8ACB-20FTOMN90-S R22
12ACB-27FTOMN90-S R22

Female SAE Tube O-Ring Nut Swivel - 90° Block - Steel R23
8ACB-8FTON90BL-S R23
10ACB-10FTON90BL-S R23
12ACB-10FTON90BL-S R23

Male Inverted O-Ring - Aluminum R23
6ACB-6MIO R23
8ACB-8MIO R23
10ACB-10MIO R23
12ACB-12MIO R23

Male Inverted O-Ring - Steel R23
6ACB-6MIO-S R23
8ACB-8MIO-S R23
10ACB-10MIO-S R23
12ACB-12MIO-S R23

Male Inverted O-Ring - 45° Bent Tube - Aluminum R24
6ACB-6MIO45 R24
8ACB-8MIO45 R24
10ACB-10MIO45 R24

Male Inverted O-Ring - 45° Bent Tube - Steel R24
10ACB-10MIO45-S R24

Male Inverted O-Ring - 90° Bent Tube - Aluminum R24
6ACB-6MIO90 R24
8ACB-8MIO90 R24
10ACB-10MIO90 R24

| Category | Page |
|---|---|
| **PolarSeal® II Couplings (ACB) (Continued)** | |
| Male Inverted O-Ring - 90° Bent Tube - Steel | R25 |
| 6ACB-6MIO90-S | R25 |
| 8ACB-8MIO90-S | R25 |
| 10ACB-10MIO90-S | R25 |
| Male Inverted O-Ring Bulkhead - Steel | R25 |
| 6ACB-6MIOBKHD-S | R25 |
| 8ACB-8MIOBKHD-S | R25 |
| 10ACB-10MIOBKHD-S | R25 |
| Male Inverted O-Ring Bulkhead - 90° Bent Tube - Steel | R25 |
| 6ACB-6MIOBKHD90-S | R25 |
| 8ACB-8MIOBKHD90-S | R26 |
| 10ACB-10MIOBKHD90-S | R26 |
| Female SAE Tube O-Ring Nut - 180° Bent Tube - Aluminum | R26 |
| 6ACB-6FTON180 | R26 |
| 8ACB-8FTON180 | R26 |
| 12ACB-12FTON180 | R26 |
| Female SAE Tube O-Ring Nut - 180° Bent Tube - Steel | R26 |
| 6ACB-6FTON180-S | R26 |
| 10ACB-10FTON180-S | R26 |
| Universal Tee O-Ring Splicer English Threads - Aluminum | R27 |
| 10ACB-10TORSP | R27 |
| Male (Ford) Spring Lock - 45° Bent Tube - Aluminum | R27 |
| 6ACB-6MSL45 | R27 |
| 8ACB-8MSL45 | R27 |
| 10ACB-10MSL45 | R27 |
| 12ACB-12MSL45 | R27 |
| Male (Ford) Spring Lock - Aluminum | R27 |
| 6ACB-6MSL | R27 |
| 8ACB-8MSL | R27 |
| 10ACB-10MSL | R28 |
| Male (Ford) Spring Lock - 90° Bent Tube - Aluminum | R28 |
| 6ACB-8MSL90 | R28 |
| 8ACB-8MSL90 | R28 |
| 10ACB-10MSL90 | R28 |
| Female (Ford) Spring Lock - 90° Bent Tube - Aluminum | R28 |
| 6ACB-6FSL90 | R28 |
| 10ACB-10FSL90 | R28 |
| Hose Splicer with R12 Thread Service Port - Aluminum | R29 |
| 6ACB-R12SP | R29 |
| 10ACB-R12SP | R29 |
| 12ACB-R12SP | R29 |
| Hose Splicer with R12 Thread Service Port - Steel | R29 |
| 6ACB-R12SP-S | R29 |
| 8ACB-R12SP-S | R29 |
| 10ACB-R12SP-S | R29 |
| Hose Splicer with R134a Service Port - Aluminum | R29 |
| 6ACB-R134SP | R29 |
| 8ACB-R134SP | R29 |
| 10ACB-R134SP | R29 |
| 12ACB-R134SP | R29 |
| Hose Splicer with R134a Service Port - Steel | R30 |
| 6ACB-R134SP-S | R30 |
| 8ACB-R134SP-S | R30 |
| 10ACB-R134SP-S | R30 |
| 12ACB-R134SP-S | R30 |
| Compressor Female SAE Tube O-Ring Nut Swivel - 90° Bent Tube - Steel | R30 |
| 6ACB-6CFTON90-S | R30 |
| 10ACB-10CFTON90-S | R30 |
| Compressor Female Tube O-Ring Nut with 134a Service Port - 90° Block - Steel | R31 |
| 8ACB-10CFTON134SP90BL-S | R31 |
| 10ACB-10CFTON134SP90BL-S | R31 |
| 12ACB-10CFTON134SP90BL-S | R31 |
| **Power Steering Couplings** | |
| SAE Male Flareless (includes Sleeve and Nut) | S1 |
| 6PS-4MFA | S1 |
| 6PS-5MFA | S1 |
| 6PS-6MFA | S1 |
| SAE Metric Male Flareless (includes Sleeve and Nut) | S1 |
| 6PSM-8MFA | S1 |
| 6PSM-10MFA | S1 |

| Category | Page |
|---|---|
| **Power Steering Couplings (Continued)** | |
| SAE Metric Male Flareless (includes Sleeve and Nut) (Continued) | S1 |
| 6PSM-12MFA | S1 |
| **SAE to SAE Adapters** | |
| Male Pipe NPTF Plug | T1 |
| 2MP-PLUG | T1 |
| 4MP-PLUG | T1 |
| 6MP-PLUG | T1 |
| 8MP-PLUG | T1 |
| 12MP-PLUG | T1 |
| 16MP-PLUG | T1 |
| 20MP-PLUG | T1 |
| 24MP-PLUG | T1 |
| 32MP-PLUG | T1 |
| Male Pipe NPTF to Male Pipe NPTF | T1 |
| 2MP-2MP | T1 |
| 4MP-2MP | T1 |
| 4MP-4MP | T1 |
| 6MP-2MP | T1 |
| 6MP-4MP | T1 |
| 6MP-6MP | T1 |
| 8MP-4MP | T1 |
| 8MP-6MP | T1 |
| 8MP-8MP | T1 |
| 12MP-4MP | T1 |
| 12MP-6MP | T1 |
| 12MP-8MP | T1 |
| 12MP-12MP | T1 |
| 16MP-6MP | T1 |
| 16MP-8MP | T1 |
| 16MP-12MP | T1 |
| 16MP-16MP | T1 |
| 20MP-12MP | T1 |
| 20MP-16MP | T1 |
| 20MP-20MP | T1 |
| 24MP-12MP | T1 |
| 24MP-16MP | T1 |
| 24MP-20MP | T2 |
| 24MP-24MP | T2 |
| 32MP-24MP | T2 |
| 32MP-32MP | T2 |
| Male Pipe NPTF to Male Pipe NPTF - 90° | T2 |
| 2MP-2MP90 | T2 |
| 4MP-4MP90 | T2 |
| 6MP-4MP90 | T2 |
| 6MP-6MP90 | T2 |
| 8MP-4MP90 | T2 |
| 8MP-6MP90 | T2 |
| 8MP-8MP90 | T2 |
| 12MP-8MP90 | T2 |
| 12MP-12MP90 | T2 |
| 16MP-12MP90 | T2 |
| 16MP-16MP90 | T2 |
| 20MP-20MP90 | T2 |
| 24MP-24MP90 | T2 |
| Male Pipe NPTF to Female Pipe NPTF Reducer Bushing - Short | T2 |
| 4MP-2FPS | T2 |
| 6MP-2FPS | T2 |
| 6MP-4FPS | T2 |
| 8MP-2FPS | T2 |
| 8MP-4FPS | T3 |
| 8MP-6FPS | T3 |
| 12MP-2FPS | T3 |
| 12MP-4FPS | T3 |
| 12MP-6FPS | T3 |
| 12MP-8FPS | T3 |
| 16MP-2FPS | T3 |
| 16MP-4FPS | T3 |
| 16MP-6FPS | T3 |
| 16MP-8FPS | T3 |
| 16MP-12FPS | T3 |
| 20MP-4FPS | T3 |
| 20MP-8FPS | T3 |
| 20MP-12FPS | T3 |
| 20MP-16FPS | T3 |
| 24MP-12FPS | T3 |
| 24MP-16FPS | T3 |
| 24MP-20FPS | T3 |

Category — Page

## SAE to SAE Adapters (Continued)

Male Pipe NPTF to Female Pipe NPTF Reducer Bushing - Short (Continued) T3
32MP-20FPS T3
32MP-24FPS T3

Male Pipe NPTF to Female Pipe NPTF Increasing Bushing - Long T3
2MP-4FPL T3
2MP-6FPL T3
4MP-2FPL T3
4MP-4FPL T3
4MP-6FPL T3
4MP-8FPL T3
6MP-4FPL T3
6MP-6FPL T3
6MP-8FPL T3
8MP-8FPL T3
8MP-12FPL T3
8MP-16FPL T3
12MP-8FPL T3
12MP-12FPL T3
12MP-16FPL T3
16MP-12FPL T3
16MP-16FPL T3
16MP-20FPL T3
16MP-24FPL T3
20MP-20FPL T3
20MP-24FPL T4
24MP-32FPL T4

Female Pipe NPTF to Male Pipe NPTF - 45° T4
6FP-6MP45 T4
8FP-8MP45 T4

Male Pipe NPTF to Female Pipe NPTF - 90° T4
2MP-2FP90 T4
2MP-4FP90 T4
4MP-2FP90 T4
4MP-4FP90 T4
4MP-6FP90 T4
6MP-4FP90 T4
6MP-6FP90 T4
6MP-8FP90 T4
8MP-4FP90 T4
8MP-6FP90 T4
8MP-8FP90 T4
8MP-12FP90 T4
12MP-8FP90 T4
12MP-12FP90 T5
12MP-16FP90 T5
16MP-12FP90 T5
16MP-16FP90 T5
20MP-16FP90 T5
20MP-20FP90 T5
24MP-24FP90 T5
32MP-32FP90 T5

Male Pipe NPTF to Female Pipe Swivel NPSM T5
2MP-2FPX T5
2MP-4FPX T5
4MP-2FPX T5
4MP-4FPX T5
4MP-6FPX T5
4MP-8FPX T5
6MP-4FPX T5
6MP-6FPX T5
6MP-8FPX T5
8MP-6FPX T5
8MP-8FPX T5
8MP-12FPX T5
12MP-6FPX T5
12MP-8FPX T5
12MP-12FPX T5
12MP-16FPX T5
12MP-20FPX T5
16MP-12FPX T5
16MP-16FPX T5
16MP-20FPX T5
20MP-16FPX T5
20MP-20FPX T5
20MP-24FPX T5
24MP-20FPX T5
24MP-24FPX T5
32MP-32FPX T5

Category — Page

## SAE to SAE Adapters (Continued)

Male Pipe NPTF to Female Pipe Swivel NPSM - 45° T6
2MP-2FPX45 T6
2MP-4FPX45 T6
4MP-2FPX45 T6
4MP-4FPX45 T6
4MP-6FPX45 T6
6MP-4FPX45 T6
6MP-6FPX45 T6
6MP-8FPX45 T6
8MP-4FPX45 T6
8MP-6FPX45 T6
8MP-8FPX45 T6
8MP-12FPX45 T6
12MP-8FPX45 T6
12MP-12FPX45 T6
12MP-16FPX45 T6
16MP-12FPX45 T6
16MP-16FPX45 T6
16MP-20FPX45 T6
20MP-16FPX45 T6
20MP-20FPX45 T6
24MP-24FPX45 T6
32MP-32FPX45 T6

Male Pipe NPTF to Female Pipe Swivel NPSM - 90° T6
2MP-2FPX90 T6
2MP-4FPX90 T6
4MP-2FPX90 T6
4MP-4FPX90 T6
4MP-6FPX90 T6
4MP-8FPX90 T7
6MP-4FPX90 T7
6MP-6FPX90 T7
6MP-8FPX90 T7
8MP-4FPX90 T7
8MP-6FPX90 T7
8MP-8FPX90 T7
8MP-12FPX90 T7
12MP-6FPX90 T7
12MP-8FPX90 T7
12MP-12FPX90 T7
12MP-16FPX90 T7
12MP-20FPX90 T7
16MP-8FPX90 T7
16MP-12FPX90 T7
16MP-16FPX90 T7
16MP-20FPX90 T7
20MP-12FPX90 T7
20MP-16FPX90 T7
20MP-20FPX90 T7
20MP-24FPX90 T7
24MP-20FPX90 T7
24MP-24FPX90 T7
32MP-32FPX90 T7

Female Pipe NPTF to Female Pipe NPTF T7
2FP-2FP T7
4FP-2FP T7
4FP-4FP T7
6FP-2FP T7
6FP-4FP T7
6FP-6FP T7
8FP-4FP T7
8FP-6FP T7
8FP-8FP T7
12FP-8FP T7
12FP-12FP T7
16FP-8FP T7
16FP-12FP T7
16FP-16FP T7
20FP-16FP T7
20FP-20FP T7
24FP-24FP T8
32FP-32FP T8

Female Pipe NPTF to Female Pipe NPTF - 90° T8
2FP-2FP90 T8
4FP-2FP90 T8
4FP-4FP90 T8
6FP-4FP90 T8
6FP-6FP90 T8
8FP-4FP90 T8

# INDEX


| Category | Page |
|---|---|
| **SAE to SAE Adapters (Continued)** | |
| Female Pipe NPTF to Female Pipe NPTF - 90° (Continued) | T8 |
| 8FP-6FP90 | T8 |
| 8FP-8FP90 | T8 |
| 12FP-8FP90 | T8 |
| 12FP-12FP90 | T8 |
| 16FP-12FP90 | T8 |
| 16FP-16FP90 | T8 |
| 20FP-20FP90 | T8 |
| 24FP-24FP90 | T8 |
| 32FP-32FP90 | T8 |
| Female Pipe NPTF to Female Pipe Swivel NPSM | T8 |
| 2FP-2FPX | T8 |
| 2FP-4FPX | T8 |
| 4FP-2FPX | T8 |
| 4FP-4FPX | T8 |
| 4FP-6FPX | T9 |
| 6FP-4FPX | T9 |
| 6FP-6FPX | T9 |
| 6FP-8FPX | T9 |
| 8FP-4FPX | T9 |
| 8FP-6FPX | T9 |
| 8FP-8FPX | T9 |
| 8FP-12FPX | T9 |
| 12FP-8FPX | T9 |
| 12FP-12FPX | T9 |
| 12FP-16FPX | T9 |
| 16FP-12FPX | T9 |
| 16FP-16FPX | T9 |
| 20FP-20FPX | T9 |
| 24FP-24FPX | T9 |
| 32FP-32FPX | T9 |
| Female Pipe NPTF to Female Pipe Swivel NPSM - 45° | T9 |
| 2FP-2FPX45 | T9 |
| 2FP-4FPX45 | T9 |
| 4FP-4FPX45 | T9 |
| 6FP-4FPX45 | T9 |
| 6FP-6FPX45 | T9 |
| 6FP-8FPX45 | T9 |
| 8FP-6FPX45 | T9 |
| 8FP-8FPX45 | T9 |
| 12FP-12FPX45 | T9 |
| 16FP-12FPX45 | T9 |
| 16FP-16FPX45 | T9 |
| 20FP-20FPX45 | T9 |
| Female Pipe NPTF to Female Pipe Swivel NPSM - 90° | T10 |
| 2FP-2FPX90 | T10 |
| 2FP-4FPX90 | T10 |
| 4FP-2FPX90 | T10 |
| 4FP-4FPX90 | T10 |
| 4FP-6FPX90 | T10 |
| 6FP-4FPX90 | T10 |
| 6FP-6FPX90 | T10 |
| 6FP-8FPX90 | T10 |
| 8FP-6FPX90 | T10 |
| 8FP-8FPX90 | T10 |
| 8FP-12FPX90 | T10 |
| 12FP-8FPX90 | T10 |
| 12FP-12FPX90 | T10 |
| 16FP-12FPX90 | T10 |
| 16FP-16FPX90 | T10 |
| 20FP-16FPX90 | T10 |
| 20FP-20FPX90 | T10 |
| 24FP-24FPX90 | T10 |
| 32FP-32FPX90 | T10 |
| Female Pipe NPTF - Tee | T10 |
| 2FP-2FP-2FP | T10 |
| 4FP-4FP-4FP | T10 |
| 6FP-6FP-6FP | T10 |
| 8FP-8FP-8FP | T10 |
| 12FP-12FP-12FP | T10 |
| 16FP-16FP-16FP | T10 |
| 20FP-20FP-20FP | T10 |
| 24FP-24FP-24FP | T11 |
| 32FP-32FP-32FP | T11 |
| Female Pipe NPTF on Run to Male Pipe NPTF - Tee | T11 |
| 2FP-2FP-2MP | T11 |
| 4FP-4FP-4MP | T11 |
| 6FP-6FP-6MP | T11 |

| Category | Page |
|---|---|
| **SAE to SAE Adapters (Continued)** | |
| Female Pipe NPTF on Run to Male Pipe NPTF - Tee (Continued) | T11 |
| 8FP-8FP-8MP | T11 |
| 12FP-12FP-12MP | T11 |
| 16FP-16FP-16MP | T11 |
| 20FP-20FP-20MP | T11 |
| 24FP-24FP-24MP | T11 |
| Female Pipe Swivel NPSM - Tee | T11 |
| 2FPX-2FPX-2FPX | T11 |
| 4FPX-4FPX-4FPX | T11 |
| 6FPX-6FPX-6FPX | T11 |
| 8FPX-8FPX-8FPX | T11 |
| 12FPX-12FPX-12FPX | T11 |
| 16FPX-16FPX-16FPX | T11 |
| 20FPX-20FPX-20FPX | T11 |
| Female Pipe Swivel NPSM on Run to Male Pipe NPTF - Tee | T12 |
| 2FPX-2FPX-2MP | T12 |
| 4FPX-4FPX-4MP | T12 |
| 6FPX-6FPX-6MP | T12 |
| 8FPX-8FPX-8MP | T12 |
| 12FPX-12FPX-12MP | T12 |
| 16FPX-16FPX-16MP | T12 |
| 20FPX-20FPX-20MP | T12 |
| 24FPX-24FPX-24MP | T12 |
| Male O-Ring Boss Plug | T12 |
| 2MB-PLUG | T12 |
| 3MB-PLUG | T12 |
| 4MB-PLUG | T12 |
| 5MB-PLUG | T12 |
| 6MB-PLUG | T12 |
| 8MB-PLUG | T12 |
| 10MB-PLUG | T12 |
| 12MB-PLUG | T12 |
| 14MB-PLUG | T12 |
| 16MB-PLUG | T12 |
| 20MB-PLUG | T12 |
| 24MB-PLUG | T12 |
| 32MB-PLUG | T12 |
| Male O-Ring Boss to Male Pipe NPTF | T13 |
| 8MB-8MP | T13 |
| 10MB-8MP | T13 |
| Male O-Ring Boss to Female Pipe NPTF | T13 |
| 3MB-2FP | T13 |
| 4MB-2FP | T13 |
| 4MB-4FP | T13 |
| 4MB-6FP | T13 |
| 5MB-2FP | T13 |
| 5MB-4FP | T13 |
| 6MB-2FP | T13 |
| 6MB-4FP | T13 |
| 6MB-6FP | T13 |
| 6MB-8FP | T13 |
| 8MB-4FP | T13 |
| 8MB-6FP | T13 |
| 8MB-8FP | T13 |
| 8MB-12FP | T13 |
| 10MB-4FP | T13 |
| 10MB-6FP | T13 |
| 10MB-8FP | T13 |
| 10MB-12FP | T13 |
| 12MB-8FP | T13 |
| 12MB-12FP | T13 |
| 12MB-16FP | T13 |
| 14MB-12FP | T13 |
| 16MB-8FP | T13 |
| 16MB-12FP | T13 |
| 16MB-16FP | T13 |
| 20MB-16FP | T13 |
| Male O-Ring Boss to Female Pipe Swivel NPSM | T14 |
| 4MB-2FPX | T14 |
| 4MB-4FPX | T14 |
| 4MB-6FPX | T14 |
| 5MB-4FPX | T14 |
| 5MB-8FPX | T14 |
| 6MB-4FPX | T14 |
| 6MB-6FPX | T14 |
| 6MB-8FPX | T14 |
| 8MB-4FPX | T14 |

## SAE to SAE Adapters (Continued)


| Category | Page |
|---|---|
| Male O-Ring Boss to Female Pipe Swivel NPSM (Continued) | T14 |
| 8MB-6FPX | T14 |
| 8MB-8FPX | T14 |
| 8MB-12FPX | T14 |
| 10MB-6FPX | T14 |
| 10MB-8FPX | T14 |
| 10MB-12FPX | T14 |
| 12MB-8FPX | T14 |
| 12MB-12FPX | T14 |
| 12MB-16FPX | T14 |
| 14MB-12FPX | T14 |
| 16MB-12FPX | T14 |
| 16MB-16FPX | T14 |
| 16MB-20FPX | T14 |
| 20MB-12FPX | T14 |
| 20MB-16FPX | T14 |
| 20MB-20FPX | T14 |
| 24MB-20FPX | T14 |
| 24MB-24FPX | T14 |
| 32MB-32FPX | T14 |
| Male O-Ring Boss to Female Pipe Swivel NPSM - 45° | T15 |
| 4MB-2FPX45 | T15 |
| 4MB-4FPX45 | T15 |
| 4MB-6FPX45 | T15 |
| 6MB-4FPX45 | T15 |
| 6MB-6FPX45 | T15 |
| 6MB-8FPX45 | T15 |
| 8MB-4FPX45 | T15 |
| 8MB-6FPX45 | T15 |
| 8MB-8FPX45 | T15 |
| 8MB-12FPX45 | T15 |
| 10MB-6FPX45 | T15 |
| 10MB-8FPX45 | T15 |
| 10MB-12FPX45 | T15 |
| 12MB-8FPX45 | T15 |
| 12MB-12FPX45 | T15 |
| 12MB-16FPX45 | T15 |
| 16MB-12FPX45 | T15 |
| 16MB-16FPX45 | T15 |
| 20MB-20FPX45 | T15 |
| 24MB-24FPX45 | T15 |
| Male O-Ring Boss to Female Pipe Swivel NPSM - 90° | T15 |
| 4MB-2FPX90 | T15 |
| 4MB-4FPX90 | T15 |
| 4MB-6FPX90 | T15 |
| 6MB-4FPX90 | T15 |
| 6MB-6FPX90 | T15 |
| 6MB-8FPX90 | T15 |
| 8MB-4FPX90 | T16 |
| 8MB-6FPX90 | T16 |
| 8MB-8FPX90 | T16 |
| 8MB-12FPX90 | T16 |
| 10MB-6FPX90 | T16 |
| 10MB-8FPX90 | T16 |
| 10MB-12FPX90 | T16 |
| 12MB-6FPX90 | T16 |
| 12MB-8FPX90 | T16 |
| 12MB-12FPX90 | T16 |
| 12MB-16FPX90 | T16 |
| 14MB-12FPX90 | T16 |
| 16MB-12FPX90 | T16 |
| 16MB-16FPX90 | T16 |
| 16MB-20FPX90 | T16 |
| 20MB-12FPX90 | T16 |
| 20MB-16FPX90 | T16 |
| 20MB-20FPX90 | T16 |
| 24MB-24FPX90 | T16 |
| 32MB-32FPX90 | T16 |
| Female O-Ring Boss to Male Pipe NPTF | T16 |
| 4FB-2MP | T16 |
| 4FB-4MP | T16 |
| 5FB-2MP | T16 |
| 6FB-4MP | T16 |
| 6FB-6MP | T16 |
| 6FB-8MP | T16 |
| 8FB-6MP | T16 |
| 8FB-8MP | T16 |
| 10FB-8MP | T16 |
| 12FB-8MP | T16 |

| Category | Page |
|---|---|
| Female O-Ring Boss to Male Pipe NPTF (Continued) | T16 |
| 12FB-12MP | T16 |
| 16FB-12MP | T16 |
| 16FB-16MP | T16 |
| Male O-Ring Boss to Male JIC 37° Flare | T17 |
| 2MB-2MJ | T17 |
| 2MB-4MJ | T17 |
| 3MB-4MJ | T17 |
| 4MB-3MJ | T17 |
| 4MB-4MJ | T17 |
| 4MB-5MJ | T17 |
| 4MB-6MJ | T17 |
| 4MB-8MJ | T17 |
| 5MB-3MJ | T17 |
| 5MB-4MJ | T17 |
| 5MB-5MJ | T17 |
| 5MB-6MJ | T17 |
| 6MB-4MJ | T17 |
| 6MB-5MJ | T17 |
| 6MB-6MJ | T17 |
| 6MB-8MJ | T17 |
| 6MB-10MJ | T17 |
| 6MB-12MJ | T17 |
| 8MB-4MJ | T17 |
| 8MB-5MJ | T17 |
| 8MB-6MJ | T17 |
| 8MB-8MJ | T17 |
| 8MB-10MJ | T17 |
| 8MB-12MJ | T17 |
| 8MB-16MJ | T17 |
| 10MB-4MJ | T17 |
| 10MB-6MJ | T17 |
| 10MB-8MJ | T17 |
| 10MB-10MJ | T17 |
| 10MB-12MJ | T17 |
| 10MB-16MJ | T17 |
| 12MB-4MJ | T17 |
| 12MB-6MJ | T17 |
| 12MB-8MJ | T17 |
| 12MB-10MJ | T17 |
| 12MB-12MJ | T17 |
| 12MB-14MJ | T17 |
| 12MB-16MJ | T17 |
| 12MB-20MJ | T17 |
| 14MB-10MJ | T17 |
| 14MB-12MJ | T17 |
| 14MB-14MJ | T17 |
| 14MB-16MJ | T17 |
| 16MB-8MJ | T17 |
| 16MB-10MJ | T17 |
| 16MB-12MJ | T17 |
| 16MB-16MJ | T17 |
| 16MB-20MJ | T17 |
| 20MB-10MJ | T18 |
| 20MB-12MJ | T18 |
| 20MB-16MJ | T18 |
| 20MB-20MJ | T18 |
| 20MB-24MJ | T18 |
| 24MB-16MJ | T18 |
| 24MB-20MJ | T18 |
| 24MB-24MJ | T18 |
| 32MB-24MJ | T18 |
| 32MB-32MJ | T18 |
| Male O-Ring Boss to Male JIC 37° Flare - 45° | T18 |
| 4MB-4MJ45 | T18 |
| 4MB-6MJ45 | T18 |
| 5MB-5MJ45 | T18 |
| 5MB-6MJ45 | T18 |
| 6MB-4MJ45 | T18 |
| 6MB-6MJ45 | T18 |
| 6MB-8MJ45 | T18 |
| 8MB-6MJ45 | T18 |
| 8MB-8MJ45 | T18 |
| 8MB-10MJ45 | T18 |
| 8MB-12MJ45 | T18 |
| 10MB-8MJ45 | T18 |
| 10MB-10MJ45 | T18 |
| 10MB-12MJ45 | T18 |
| 12MB-10MJ45 | T18 |

| Category | Page |
|---|---|
| **SAE to SAE Adapters (Continued)** | |
| Male O-Ring Boss to Male JIC 37° Flare - 45° (Continued) | T18 |
| 12MB-12MJ45 | T18 |
| 12MB-16MJ45 | T18 |
| 14MB-14MJ45 | T18 |
| 16MB-12MJ45 | T18 |
| 16MB-16MJ45 | T18 |
| 16MB-20MJ45 | T18 |
| 20MB-16MJ45 | T18 |
| 20MB-20MJ45 | T18 |
| 24MB-24MJ45 | T18 |
| Male O-Ring Boss to Male JIC 37° Flare - 90° | T19 |
| 2MB-2MJ90 | T19 |
| 3MB-3MJ90 | T19 |
| 4MB-4MJ90 | T19 |
| 4MB-5MJ90 | T19 |
| 4MB-6MJ90 | T19 |
| 4MB-8MJ90 | T19 |
| 5MB-4MJ90 | T19 |
| 5MB-5MJ90 | T19 |
| 5MB-6MJ90 | T19 |
| 5MB-8MJ90 | T19 |
| 6MB-4MJ90 | T19 |
| 6MB-5MJ90 | T19 |
| 6MB-6MJ90 | T19 |
| 6MB-8MJ90 | T19 |
| 6MB-10MJ90 | T19 |
| 6MB-12MJ90 | T19 |
| 8MB-4MJ90 | T19 |
| 8MB-5MJ90 | T19 |
| 8MB-6MJ90 | T19 |
| 8MB-8MJ90 | T19 |
| 8MB-10MJ90 | T19 |
| 8MB-12MJ90 | T19 |
| 8MB-16MJ90 | T19 |
| 10MB-5MJ90 | T19 |
| 10MB-6MJ90 | T19 |
| 10MB-8MJ90 | T19 |
| 10MB-10MJ90 | T19 |
| 10MB-12MJ90 | T19 |
| 10MB-16MJ90 | T19 |
| 12MB-6MJ90 | T19 |
| 12MB-8MJ90 | T19 |
| 12MB-10MJ90 | T19 |
| 12MB-12MJ90 | T19 |
| 12MB-14MJ90 | T19 |
| 12MB-16MJ90 | T19 |
| 12MB-20MJ90 | T19 |
| 14MB-12MJ90 | T19 |
| 14MB-14MJ90 | T19 |
| 14MB-16MJ90 | T19 |
| 14MB-20MJ90 | T19 |
| 16MB-8MJ90 | T19 |
| 16MB-10MJ90 | T19 |
| 16MB-12MJ90 | T20 |
| 16MB-14MJ90 | T20 |
| 16MB-16MJ90 | T20 |
| 16MB-20MJ90 | T20 |
| 16MB-24MJ90 | T20 |
| 20MB-10MJ90 | T20 |
| 20MB-12MJ90 | T20 |
| 20MB-16MJ90 | T20 |
| 20MB-20MJ90 | T20 |
| 20MB-24MJ90 | T20 |
| 24MB-20MJ90 | T20 |
| 24MB-24MJ90 | T20 |
| 32MB-32MJ90 | T20 |
| Male O-Ring Boss to Female JIC 37° Flare Swivel | T20 |
| 6MB-6FJX | T20 |
| 8MB-8FJX | T20 |
| Male JIC 37° Flare on Run to Male O-Ring Boss - Tee | T20 |
| 4MJ-4MJ-4MB | T20 |
| 5MJ-5MJ-5MB | T20 |
| 6MJ-6MJ-6MB | T20 |
| 6MJ-6MJ-8MB | T21 |
| 8MJ-8MJ-8MB | T21 |
| 8MJ-8MJ-10MB | T21 |
| 10MJ-10MJ-10MB | T21 |
| 12MJ-12MJ-10MB | T21 |
| 12MJ-12MJ-12MB | T21 |

| Category | Page |
|---|---|
| **SAE to SAE Adapters (Continued)** | |
| Male JIC 37° Flare on Run to Male O-Ring Boss - Tee (Continued) | T21 |
| 14MJ-14MJ-14MB | T21 |
| 16MJ-16MJ-16MB | T21 |
| 20MJ-20MJ-20MB | T21 |
| 24MJ-24MJ-24MB | T21 |
| Male O-Ring Boss to Male JIC 37° Flare to Male JIC 37° Flare - Tee | T21 |
| 4MB-4MJ-4MJ | T21 |
| 5MB-5MJ-5MJ | T21 |
| 6MB-6MJ-6MJ | T21 |
| 6MB-8MJ-6MJ | T21 |
| 8MB-8MJ-8MJ | T21 |
| 10MB-10MJ-10MJ | T21 |
| 12MB-12MJ-12MJ | T21 |
| 12MB-12MJ-16MJ | T21 |
| 14MB-14MJ-14MJ | T21 |
| 16MB-16MJ-16MJ | T21 |
| 20MB-20MJ-20MJ | T21 |
| 24MB-24MJ-24MJ | T21 |
| Female JIC 37° Flare Cap | T22 |
| 2FJ-CAP | T22 |
| 3FJ-CAP | T22 |
| 4FJ-CAP | T22 |
| 5FJ-CAP | T22 |
| 6FJ-CAP | T22 |
| 8FJ-CAP | T22 |
| 10FJ-CAP | T22 |
| 12FJ-CAP | T22 |
| 14FJ-CAP | T22 |
| 16FJ-CAP | T22 |
| 20FJ-CAP | T22 |
| 24FJ-CAP | T22 |
| 32FJ-CAP | T22 |
| Male JIC 37° Flare Plug | T22 |
| 3MJ-PLUG | T22 |
| 4MJ-PLUG | T22 |
| 5MJ-PLUG | T22 |
| 6MJ-PLUG | T22 |
| 8MJ-PLUG | T22 |
| 10MJ-PLUG | T22 |
| 12MJ-PLUG | T22 |
| 14MJ-PLUG | T22 |
| 16MJ-PLUG | T22 |
| 20MJ-PLUG | T22 |
| 24MJ-PLUG | T22 |
| 32MJ-PLUG | T22 |
| Male JIC 37° Flare to Female Braze - On | T23 |
| 20MJ-20FBO | T23 |
| Male JIC 37° Flare to Male JIC 37° Flare | T23 |
| 2MJ-2MJ | T23 |
| 3MJ-2MJ | T23 |
| 3MJ-3MJ | T23 |
| 4MJ-3MJ | T23 |
| 4MJ-4MJ | T23 |
| 5MJ-4MJ | T23 |
| 5MJ-5MJ | T23 |
| 6MJ-4MJ | T23 |
| 6MJ-5MJ | T23 |
| 6MJ-6MJ | T23 |
| 8MJ-4MJ | T23 |
| 8MJ-5MJ | T23 |
| 8MJ-6MJ | T23 |
| 8MJ-8MJ | T23 |
| 10MJ-4MJ | T23 |
| 10MJ-6MJ | T23 |
| 10MJ-8MJ | T23 |
| 10MJ-10MJ | T23 |
| 12MJ-4MJ | T23 |
| 12MJ-6MJ | T23 |
| 12MJ-8MJ | T23 |
| 12MJ-10MJ | T23 |
| 12MJ-12MJ | T23 |
| 14MJ-12MJ | T23 |
| 14MJ-14MJ | T23 |
| 16MJ-8MJ | T23 |
| 16MJ-10MJ | T23 |
| 16MJ-12MJ | T23 |
| 16MJ-16MJ | T23 |
| 20MJ-12MJ | T24 |

## SAE to SAE Adapters (Continued)


| Category | Page |
|---|---|
| Male JIC 37° Flare to Male JIC 37° Flare (Continued) | T24 |
| 20MJ-16MJ | T24 |
| 20MJ-20MJ | T24 |
| 24MJ-12MJ | T24 |
| 24MJ-20MJ | T24 |
| 24MJ-24MJ | T24 |
| 32MJ-32MJ | T24 |
| Male JIC 37° Flare to Male JIC 37° Flare - 90° | T24 |
| 2MJ-2MJ90 | T24 |
| 4MJ-4MJ90 | T24 |
| 5MJ-5MJ90 | T24 |
| 6MJ-4MJ90 | T24 |
| 6MJ-6MJ90 | T24 |
| 8MJ-6MJ90 | T24 |
| 8MJ-8MJ90 | T24 |
| 10MJ-10MJ90 | T24 |
| 12MJ-12MJ90 | T24 |
| 14MJ-14MJ90 | T24 |
| 16MJ-12MJ90 | T24 |
| 16MJ-16MJ90 | T24 |
| 20MJ-20MJ90 | T24 |
| 24MJ-24MJ90 | T24 |
| 32MJ-32MJ90 | T24 |
| Male JIC 37° Flare to Female JIC 37° Flare | T25 |
| 4MJ-6FJ | T25 |
| 5MJ-4FJ | T25 |
| 5MJ-6FJ | T25 |
| 6MJ-4FJ | T25 |
| 6MJ-6FJ | T25 |
| 6MJ-8FJ | T25 |
| 6MJ-10FJ | T25 |
| 8MJ-4FJ | T25 |
| 8MJ-8FJ | T25 |
| 8MJ-10FJ | T25 |
| 8MJ-12FJ | T25 |
| 10MJ-4FJ | T25 |
| 10MJ-6FJ | T25 |
| 10MJ-8FJ | T25 |
| 10MJ-12FJ | T25 |
| 10MJ-16FJ | T25 |
| 12MJ-4FJ | T25 |
| 12MJ-6FJ | T25 |
| 12MJ-8FJ | T25 |
| 12MJ-12FJ | T25 |
| 12MJ-16FJ | T25 |
| 12MJ-20FJ | T25 |
| 16MJ-16FJ | T25 |
| 16MJ-20FJ | T25 |
| 20MJ-16FJ | T25 |
| Male JIC 37° Flare to Female JIC 37° Flare Swivel - 90° | T25 |
| 4MJ-4FJX90 | T25 |
| 5MJ-5FJX90 | T26 |
| 6MJ-4FJX90 | T26 |
| 6MJ-6FJX90 | T26 |
| 8MJ-6FJX90 | T26 |
| 8MJ-8FJX90 | T26 |
| 8MJ-10FJX90 | T26 |
| 10MJ-10FJX90 | T26 |
| 12MJ-12FJX90 | T26 |
| 14MJ-14FJX90 | T26 |
| 16MJ-16FJX90 | T26 |
| 20MJ-20FJX90 | T26 |
| 24MJ-24FJX90 | T26 |
| 32MJ-32FJX90 | T26 |
| Male JIC 37° Flare to Female JIC 37° Flare Swivel - 45° | T26 |
| 4MJ-4FJX45 | T26 |
| 5MJ-5FJX45 | T26 |
| 6MJ-6FJX45 | T26 |
| 8MJ-8FJX45 | T26 |
| 10MJ-10FJX45 | T26 |
| 12MJ-12FJX45 | T26 |
| 14MJ-14FJX45 | T26 |
| 16MJ-16FJX45 | T26 |
| 20MJ-20FJX45 | T26 |
| 24MJ-24FJX45 | T26 |
| 32MJ-32FJX45 | T26 |
| Male JIC 37° Flare to Male JIC 37° Flare Bulkhead | T27 |
| 3MJ-3BKHD | T27 |

| Category | Page |
|---|---|
| Male JIC 37° Flare to Male JIC 37° Flare Bulkhead (Continued) | T27 |
| 4MJ-4BKHD | T27 |
| 5MJ-5BKHD | T27 |
| 6MJ-6BKHD | T27 |
| 8MJ-8BKHD | T27 |
| 10MJ-10BKHD | T27 |
| 12MJ-12BKHD | T27 |
| 14MJ-14BKHD | T27 |
| 16MJ-16BKHD | T27 |
| 20MJ-20BKHD | T27 |
| 24MJ-24BKHD | T27 |
| Male JIC 37° Flare to Male JIC 37° Flare Bulkhead - 45° | T27 |
| 4MJ-4BKHD45 | T27 |
| 5MJ-5BKHD45 | T27 |
| 6MJ-6BKHD45 | T27 |
| 8MJ-8BKHD45 | T27 |
| 10MJ-10BKHD45 | T27 |
| 12MJ-12BKHD45 | T27 |
| 16MJ-16BKHD45 | T27 |
| Male JIC 37° Flare to Male JIC 37° Flare Bulkhead - 90° | T28 |
| 4MJ-4BKHD90 | T28 |
| 5MJ-5BKHD90 | T28 |
| 6MJ-6BKHD90 | T28 |
| 8MJ-8BKHD90 | T28 |
| 10MJ-10BKHD90 | T28 |
| 12MJ-12BKHD90 | T28 |
| 14MJ-14BKHD90 | T28 |
| 16MJ-16BKHD90 | T28 |
| 20MJ-20BKHD90 | T28 |
| 24MJ-24BKHD90 | T28 |
| Male JIC 37° Flare Tee | T28 |
| 2MJ-2MJ-2MJ | T28 |
| 3MJ-3MJ-3MJ | T28 |
| 4MJ-4MJ-4MJ | T28 |
| 5MJ-5MJ-5MJ | T28 |
| 6MJ-6MJ-6MJ | T28 |
| 6MJ-6MJ-8MJ | T28 |
| 8MJ-8MJ-8MJ | T28 |
| 10MJ-10MJ-10MJ | T28 |
| 12MJ-12MJ-12MJ | T28 |
| 14MJ-14MJ-14MJ | T29 |
| 16MJ-16MJ-12MJ | T29 |
| 16MJ-16MJ-16MJ | T29 |
| 20MJ-20MJ-20MJ | T29 |
| 24MJ-24MJ-24MJ | T29 |
| 32MJ-32MJ-32MJ | T29 |
| Male JIC 37° Flare on Run to Female JIC 37° Flare Swivel - Tee | T29 |
| 4MJ-4MJ-4FJX | T29 |
| 5MJ-5MJ-5FJX | T29 |
| 6MJ-6MJ-6FJX | T29 |
| 8MJ-8MJ-8FJX | T29 |
| 10MJ-10MJ-10FJX | T29 |
| 12MJ-12MJ-12FJX | T29 |
| 14MJ-14MJ-14FJX | T29 |
| 16MJ-16MJ-16FJX | T29 |
| 20MJ-20MJ-20FJX | T29 |
| 24MJ-24MJ-24FJX | T29 |
| 32MJ-32MJ-32FJX | T29 |
| Male JIC 37° Flare on Run to Male JIC 37° Flare Bulkhead - Tee | T30 |
| 4MJ-4MJ-4BKHD | T30 |
| 5MJ-5MJ-5BKHD | T30 |
| 6MJ-6MJ-6BKHD | T30 |
| 8MJ-8MJ-8BKHD | T30 |
| 10MJ-10MJ-10BKHD | T30 |
| 12MJ-12MJ-12BKHD | T30 |
| 16MJ-16MJ-16BKHD | T30 |
| Male JIC 37° Flare to Male JIC 37° Flare Bulkhead to Male JIC 37° Flare - Tee | T30 |
| 4MJ-4BKHD-4MJ | T30 |
| 6MJ-6BKHD-6MJ | T30 |
| 8MJ-8BKHD-8MJ | T30 |
| 10MJ-10BKHD-10MJ | T30 |
| 12MJ-12BKHD-12MJ | T30 |
| 16MJ-16BKHD-16MJ | T30 |
| Male JIC 37° Flare to Female JIC 37° Flare Swivel to Male JIC 37° Flare - Tee | T31 |
| 4MJ-4FJX-4MJ | T31 |
| 5MJ-5FJX-5MJ | T31 |

| Category | Page |
|---|---|
| **SAE to SAE Adapters (Continued)** | |
| Male JIC 37° Flare to Female JIC 37° Flare Swivel to Male JIC 37° Flare - Tee (Continued) | T31 |
| 6MJ-6FJX-6MJ | T31 |
| 8MJ-8FJX-8MJ | T31 |
| 10MJ-10FJX-10MJ | T31 |
| 12MJ-12FJX-12MJ | T31 |
| 14MJ-14FJX-14MJ | T31 |
| 16MJ-16FJX-16MJ | T31 |
| 20MJ-20FJX-20MJ | T31 |
| 24MJ-24FJX-24MJ | T31 |
| 32MJ-32FJX-32MJ | T31 |
| Male JIC 37° Flare to Male Pipe NPTF | T31 |
| 2MJ-2MP | T31 |
| 3MJ-2MP | T31 |
| 4MJ-2MP | T31 |
| 4MJ-4MP | T31 |
| 4MJ-6MP | T31 |
| 4MJ-8MP | T31 |
| 4MJ-12MP | T31 |
| 5MJ-2MP | T31 |
| 5MJ-4MP | T31 |
| 5MJ-6MP | T31 |
| 5MJ-8MP | T31 |
| 6MJ-2MP | T32 |
| 6MJ-4MP | T32 |
| 6MJ-6MP | T32 |
| 6MJ-8MP | T32 |
| 6MJ-12MP | T32 |
| 8MJ-2MP | T32 |
| 8MJ-4MP | T32 |
| 8MJ-6MP | T32 |
| 8MJ-8MP | T32 |
| 8MJ-12MP | T32 |
| 8MJ-16MP | T32 |
| 10MJ-4MP | T32 |
| 10MJ-6MP | T32 |
| 10MJ-8MP | T32 |
| 10MJ-12MP | T32 |
| 12MJ-6MP | T32 |
| 12MJ-8MP | T32 |
| 12MJ-12MP | T32 |
| 12MJ-16MP | T32 |
| 12MJ-20MP | T32 |
| 12MJ-24MP | T32 |
| 14MJ-12MP | T32 |
| 14MJ-16MP | T32 |
| 16MJ-8MP | T32 |
| 16MJ-12MP | T32 |
| 16MJ-16MP | T32 |
| 16MJ-20MP | T32 |
| 16MJ-24MP | T32 |
| 20MJ-12MP | T32 |
| 20MJ-16MP | T32 |
| 20MJ-20MP | T32 |
| 20MJ-24MP | T32 |
| 24MJ-16MP | T32 |
| 24MJ-20MP | T32 |
| 24MJ-24MP | T32 |
| 24MJ-32MP | T32 |
| 32MJ-16MP | T32 |
| 32MJ-20MP | T32 |
| 32MJ-24MP | T32 |
| 32MJ-32MP | T32 |
| Male JIC 37° Flare to Male Pipe NPTF - 45° | T33 |
| 2MJ-2MP45 | T33 |
| 3MJ-2MP45 | T33 |
| 4MJ-2MP45 | T33 |
| 4MJ-4MP45 | T33 |
| 4MJ-6MP45 | T33 |
| 4MJ-8MP45 | T33 |
| 5MJ-2MP45 | T33 |
| 5MJ-4MP45 | T33 |
| 5MJ-6MP45 | T33 |
| 6MJ-2MP45 | T33 |
| 6MJ-4MP45 | T33 |
| 6MJ-6MP45 | T33 |
| 6MJ-8MP45 | T33 |
| 6MJ-12MP45 | T33 |
| 8MJ-4MP45 | T33 |
| 8MJ-6MP45 | T33 |

| Category | Page |
|---|---|
| **SAE to SAE Adapters (Continued)** | |
| Male JIC 37° Flare to Male Pipe NPTF - 45° (Continued) | T33 |
| 8MJ-8MP45 | T33 |
| 8MJ-12MP45 | T33 |
| 10MJ-6MP45 | T33 |
| 10MJ-8MP45 | T33 |
| 10MJ-12MP45 | T33 |
| 12MJ-8MP45 | T33 |
| 12MJ-12MP45 | T33 |
| 12MJ-16MP45 | T33 |
| 14MJ-12MP45 | T33 |
| 16MJ-8MP45 | T33 |
| 16MJ-12MP45 | T33 |
| 16MJ-16MP45 | T33 |
| 16MJ-20MP45 | T33 |
| 20MJ-16MP45 | T33 |
| 20MJ-20MP45 | T33 |
| 20MJ-24MP45 | T33 |
| 24MJ-24MP45 | T33 |
| 32MJ-32MP45 | T33 |
| Male JIC 37° Flare to Male Pipe NPTF - 90° | T34 |
| 2MJ-2MP90 | T34 |
| 3MJ-2MP90 | T34 |
| 4MJ-2MP90 | T34 |
| 4MJ-4MP90 | T34 |
| 4MJ-6MP90 | T34 |
| 4MJ-8MP90 | T34 |
| 4MJ-12MP90 | T34 |
| 5MJ-2MP90 | T34 |
| 5MJ-4MP90 | T34 |
| 5MJ-6MP90 | T34 |
| 6MJ-2MP90 | T34 |
| 6MJ-4MP90 | T34 |
| 6MJ-6MP90 | T34 |
| 6MJ-8MP90 | T34 |
| 6MJ-12MP90 | T34 |
| 8MJ-4MP90 | T34 |
| 8MJ-6MP90 | T34 |
| 8MJ-8MP90 | T34 |
| 8MJ-12MP90 | T34 |
| 8MJ-16MP90 | T34 |
| 10MJ-6MP90 | T34 |
| 10MJ-8MP90 | T34 |
| 10MJ-12MP90 | T34 |
| 10MJ-16MP90 | T34 |
| 12MJ-6MP90 | T34 |
| 12MJ-8MP90 | T34 |
| 12MJ-12MP90 | T34 |
| 12MJ-16MP90 | T34 |
| 12MJ-20MP90 | T34 |
| 14MJ-8MP90 | T34 |
| 14MJ-12MP90 | T34 |
| 16MJ-8MP90 | T34 |
| 16MJ-12MP90 | T34 |
| 16MJ-16MP90 | T34 |
| 16MJ-20MP90 | T34 |
| 16MJ-24MP90 | T34 |
| 20MJ-16MP90 | T34 |
| 20MJ-20MP90 | T34 |
| 20MJ-24MP90 | T34 |
| 24MJ-20MP90 | T34 |
| 24MJ-24MP90 | T34 |
| 32MJ-24MP90 | T34 |
| 32MJ-32MP90 | T34 |
| Male JIC 37° Flare to Female Pipe NPTF | T35 |
| 2MJ-2FP | T35 |
| 3MJ-2FP | T35 |
| 3MJ-4FP | T35 |
| 4MJ-2FP | T35 |
| 4MJ-4FP | T35 |
| 4MJ-6FP | T35 |
| 4MJ-8FP | T35 |
| 5MJ-2FP | T35 |
| 5MJ-4FP | T35 |
| 6MJ-2FP | T35 |
| 6MJ-4FP | T35 |
| 6MJ-6FP | T35 |
| 6MJ-8FP | T35 |
| 8MJ-4FP | T35 |
| 8MJ-6FP | T35 |

## SAE to SAE Adapters (Continued)


| Category | Page |
|---|---|
| Male JIC 37° Flare to Female Pipe NPTF (Continued) | T35 |
| 8MJ-8FP | T35 |
| 8MJ-12FP | T35 |
| 10MJ-6FP | T35 |
| 10MJ-8FP | T35 |
| 10MJ-12FP | T35 |
| 12MJ-8FP | T35 |
| 12MJ-12FP | T35 |
| 12MJ-16FP | T35 |
| 14MJ-12FP | T35 |
| 16MJ-12FP | T35 |
| 16MJ-16FP | T35 |
| 16MJ-20FP | T35 |
| 20MJ-16FP | T35 |
| 20MJ-20FP | T35 |
| 24MJ-24FP | T35 |
| 32MJ-32FP | T35 |
| Male JIC 37° Flare to Female Pipe NPTF - 90° | T36 |
| 4MJ-2FP90 | T36 |
| 4MJ-4FP90 | T36 |
| 5MJ-2FP90 | T36 |
| 5MJ-4FP90 | T36 |
| 6MJ-2FP90 | T36 |
| 6MJ-4FP90 | T36 |
| 6MJ-6FP90 | T36 |
| 6MJ-8FP90 | T36 |
| 8MJ-4FP90 | T36 |
| 8MJ-6FP90 | T36 |
| 8MJ-8FP90 | T36 |
| 10MJ-8FP90 | T36 |
| 12MJ-8FP90 | T36 |
| 12MJ-12FP90 | T36 |
| 14MJ-12FP90 | T36 |
| 16MJ-16FP90 | T36 |
| 20MJ-20FP90 | T36 |
| 24MJ-24FP90 | T36 |
| Female JIC 37° Flare Swivel to Male Pipe NPTF | T36 |
| 4FJX-2MP | T36 |
| 4FJX-4MP | T36 |
| 6FJX-4MP | T36 |
| 6FJX-6MP | T36 |
| 8FJX-6MP | T36 |
| 8FJX-8MP | T36 |
| 10FJX-8MP | T36 |
| 12FJX-8MP | T36 |
| 12FJX-12MP | T36 |
| 16FJX-16MP | T36 |
| 20FJX-20MP | T36 |
| Female JIC 37° Flare Swivel to Male Pipe NPTF - 90° | T37 |
| 4FJX-2MP90 | T37 |
| 4FJX-4MP90 | T37 |
| 6FJX-4MP90 | T37 |
| 6FJX-6MP90 | T37 |
| 8FJX-6MP90 | T37 |
| 8FJX-8MP90 | T37 |
| 10FJX-8MP90 | T37 |
| 12FJX-12MP90 | T37 |
| 16FJX-16MP90 | T37 |
| 20FJX-20MP90 | T37 |
| 24FJX-24MP90 | T37 |
| Female JIC 37° Flare Swivel to Female Pipe NPTF | T37 |
| 4FJX-2FP | T37 |
| 4FJX-4FP | T37 |
| 6FJX-6FP | T37 |
| 8FJX-6FP | T37 |
| 8FJX-8FP | T37 |
| 10FJX-8FP | T37 |
| 12FJX-12FP | T37 |
| 16FJX-16FP | T37 |
| 20FJX-20FP | T37 |
| Male JIC 37° Flare Bulkhead to Male Pipe NPTF | T38 |
| 4MJBKHD-2MP | T38 |
| 4MJBKHD-4MP | T38 |
| 6MJBKHD-4MP | T38 |
| 8MJBKHD-6MP | T38 |
| 8MJBKHD-8MP | T38 |
| 10MJBKHD-8MP | T38 |
| 12MJBKHD-8MP | T38 |
| Male JIC 37° Flare Bulkhead to Male Pipe NPTF (Continued) | T38 |
| 12MJBKHD-12MP | T38 |
| 16MJBKHD-16MP | T38 |
| 20MJBKHD-20MP | T38 |
| Male JIC 37° Flare on Run to Male Pipe NPTF - Tee | T38 |
| 3MJ-3MJ-2MP | T38 |
| 4MJ-4MJ-2MP | T38 |
| 4MJ-4MJ-4MP | T38 |
| 4MJ-4MJ-6MP | T38 |
| 5MJ-5MJ-2MP | T38 |
| 5MJ-5MJ-4MP | T38 |
| 6MJ-6MJ-4MP | T38 |
| 6MJ-6MJ-6MP | T38 |
| 6MJ-6MJ-8MP | T38 |
| 8MJ-8MJ-6MP | T38 |
| 8MJ-8MJ-8MP | T38 |
| 8MJ-8MJ-12MP | T38 |
| 10MJ-10MJ-8MP | T38 |
| 12MJ-12MJ-8MP | T38 |
| 12MJ-12MJ-12MP | T38 |
| 12MJ-12MJ-16MP | T38 |
| 14MJ-14MJ-12MP | T38 |
| 16MJ-16MJ-12MP | T38 |
| 16MJ-16MJ-16MP | T39 |
| 20MJ-20MJ-20MP | T39 |
| 24MJ-24MJ-24MP | T39 |
| Female Flat-Face O-Ring Cap | T39 |
| 4FFOR-CAP | T39 |
| 6FFOR-CAP | T39 |
| 8FFOR-CAP | T39 |
| 10FFOR-CAP | T39 |
| 12FFOR-CAP | T39 |
| 16FFOR-CAP | T39 |
| 20FFOR-CAP | T39 |
| 24FFOR-CAP | T39 |
| Male Flat-Face O-Ring Plug | T39 |
| 4MFFOR-PLUG | T39 |
| 6MFFOR-PLUG | T39 |
| 8MFFOR-PLUG | T39 |
| 10MFFOR-PLUG | T39 |
| 12MFFOR-PLUG | T39 |
| 16MFFOR-PLUG | T39 |
| 20MFFOR-PLUG | T39 |
| 24MFFOR-PLUG | T39 |
| 32MFFOR-PLUG | T39 |
| Male Flat-Face O-Ring to Male Flat-Face O-Ring | T40 |
| 4MFFOR-4MFFOR | T40 |
| 6MFFOR-4MFFOR | T40 |
| 6MFFOR-6MFFOR | T40 |
| 8MFFOR-6MFFOR | T40 |
| 8MFFOR-8MFFOR | T40 |
| 10MFFOR-10MFFOR | T40 |
| 12MFFOR-12MFFOR | T40 |
| 16MFFOR-16MFFOR | T40 |
| 20MFFOR-20MFFOR | T40 |
| 24MFFOR-24MFFOR | T40 |
| Male Flat-Face O-Ring to Male Flat-Face O-Ring - 90° | T40 |
| 4MFFOR-4MFFOR90 | T40 |
| 8MFFOR-8MFFOR90 | T40 |
| Male Flat-Face O-Ring to Female Flat-Face Swivel - 90° | T41 |
| 4MFFOR-4FFORX90 | T41 |
| 6MFFOR-6FFORX90 | T41 |
| 8MFFOR-8FFORX90 | T41 |
| 10MFFOR-10FFORX90 | T41 |
| 12MFFOR-12FFORX90 | T41 |
| 16MFFOR-16FFORX90 | T41 |
| 20MFFOR-20FFORX90 | T41 |
| 24MFFOR-24FFORX90 | T41 |
| Male Flat-Face O-Ring Tee | T41 |
| 4MFFOR-4MFFOR-4MFFOR | T41 |
| 6MFFOR-6MFFOR-6MFFOR | T41 |
| 8MFFOR-8MFFOR-8MFFOR | T41 |
| 10MFFOR-10MFFOR-10MFFOR | T41 |
| 12MFFOR-12MFFOR-12MFFOR | T41 |
| 16MFFOR-16MFFOR-16MFFOR | T41 |
| 20MFFOR-20MFFOR-20MFFOR | T41 |

| Category | Page |
|---|---|
| **SAE to SAE Adapters (Continued)** | |
| Male Flat-Face O-Ring on Run to Female Flat-Face Swivel - Tee | T42 |
| 4MFFOR-4MFFOR-4FFORX | T42 |
| 6MFFOR-6MFFOR-6FFORX | T42 |
| 8MFFOR-8MFFOR-8FFORX | T42 |
| 10MFFOR-10MFFOR-10FFORX | T42 |
| 12MFFOR-12MFFOR-12FFORX | T42 |
| 16MFFOR-16MFFOR-16FFORX | T42 |
| 20MFFOR-20MFFOR-20FFORX | T42 |
| Male Flat-Face O-Ring to Female Flat-Face O-Ring to Male Flat-Face O-Ring - Tee | T42 |
| 4MFFOR-4FFORX-4MFFOR | T42 |
| 6MFFOR-6FFORX-6MFFOR | T42 |
| 8MFFOR-8FFORX-8MFFOR | T42 |
| 10MFFOR-10FFORX-10MFFOR | T42 |
| 12MFFOR-12FFORX-12MFFOR | T42 |
| 16MFFOR-16FFORX-16MFFOR | T42 |
| 20MFFOR-20FFORX-20MFFOR | T42 |
| Male Flat-Face O-Ring to Male Pipe NPTF | T43 |
| 4MFFOR-2MP | T43 |
| 4MFFOR-4MP | T43 |
| 4MFFOR-6MP | T43 |
| 6MFFOR-4MP | T43 |
| 6MFFOR-6MP | T43 |
| 6MFFOR-8MP | T43 |
| 8MFFOR-4MP | T43 |
| 8MFFOR-6MP | T43 |
| 8MFFOR-8MP | T43 |
| 8MFFOR-12MP | T43 |
| 10MFFOR-8MP | T43 |
| 10MFFOR-12MP | T43 |
| 12MFFOR-8MP | T43 |
| 12MFFOR-12MP | T43 |
| 12MFFOR-16MP | T43 |
| 16MFFOR-12MP | T43 |
| 16MFFOR-16MP | T43 |
| 20MFFOR-20MP | T43 |
| 24MFFOR-24MP | T43 |
| Male Flat-Face O-Ring to Female JIC 37° Flare Swivel | T43 |
| 4MFFOR-4FJX | T43 |
| 6MFFOR-6FJX | T43 |
| 8MFFOR-8FJX | T43 |
| 10MFFOR-10FJX | T43 |
| 12MFFOR-12FJX | T43 |
| 16MFFOR-16FJX | T43 |
| Male Flat-Face O-Ring to Male O-Ring Boss | T44 |
| 4MFFOR-4MB | T44 |
| 4MFFOR-6MB | T44 |
| 4MFFOR-8MB | T44 |
| 6MFFOR-4MB | T44 |
| 6MFFOR-6MB | T44 |
| 6MFFOR-8MB | T44 |
| 6MFFOR-10MB | T44 |
| 8MFFOR-6MB | T44 |
| 8MFFOR-8MB | T44 |
| 8MFFOR-10MB | T44 |
| 8MFFOR-12MB | T44 |
| 8MFFOR-16MB | T44 |
| 10MFFOR-8MB | T44 |
| 10MFFOR-10MB | T44 |
| 10MFFOR-12MB | T44 |
| 12MFFOR-8MB | T44 |
| 12MFFOR-10MB | T44 |
| 12MFFOR-12MB | T44 |
| 12MFFOR-16MB | T44 |
| 16MFFOR-12MB | T44 |
| 16MFFOR-16MB | T44 |
| 16MFFOR-20MB | T44 |
| 20MFFOR-16MB | T44 |
| 20MFFOR-20MB | T44 |
| 20MFFOR-24MB | T44 |
| 24MFFOR-20MB | T44 |
| 24MFFOR-24MB | T44 |
| 32MFFOR-32MB | T44 |
| Male Flat-Face O-Ring to Male O-Ring Boss - 45° | T45 |
| 4MFFOR-4MB45 | T45 |
| 4MFFOR-6MB45 | T45 |
| 6MFFOR-4MB45 | T45 |
| 6MFFOR-6MB45 | T45 |
| 6MFFOR-8MB45 | T45 |

| Category | Page |
|---|---|
| **SAE to SAE Adapters (Continued)** | |
| Male Flat-Face O-Ring to Male O-Ring Boss - 45° (Continued) | T45 |
| 8MFFOR-6MB45 | T45 |
| 8MFFOR-8MB45 | T45 |
| 8MFFOR-10MB45 | T45 |
| 8MFFOR-12MB45 | T45 |
| 10MFFOR-8MB45 | T45 |
| 10MFFOR-10MB45 | T45 |
| 10MFFOR-12MB45 | T45 |
| 12MFFOR-10MB45 | T45 |
| 12MFFOR-12MB45 | T45 |
| 12MFFOR-16MB45 | T45 |
| 16MFFOR-12MB45 | T45 |
| 16MFFOR-16MB45 | T45 |
| 16MFFOR-20MB45 | T45 |
| 20MFFOR-20MB45 | T45 |
| 24MFFOR-24MB45 | T45 |
| Male Flat-Face O-Ring to Male O-Ring Boss - 90° | T45 |
| 4MFFOR-4MB90 | T45 |
| 4MFFOR-6MB90 | T45 |
| 4MFFOR-8MB90 | T45 |
| 6MFFOR-4MB90 | T45 |
| 6MFFOR-6MB90 | T45 |
| 6MFFOR-8MB90 | T46 |
| 6MFFOR-12MB90 | T46 |
| 8MFFOR-6MB90 | T46 |
| 8MFFOR-8MB90 | T46 |
| 8MFFOR-10MB90 | T46 |
| 8MFFOR-12MB90 | T46 |
| 10MFFOR-8MB90 | T46 |
| 10MFFOR-10MB90 | T46 |
| 10MFFOR-12MB90 | T46 |
| 12MFFOR-8MB90 | T46 |
| 12MFFOR-10MB90 | T46 |
| 12MFFOR-12MB90 | T46 |
| 12MFFOR-16MB90 | T46 |
| 16MFFOR-12MB90 | T46 |
| 16MFFOR-16MB90 | T46 |
| 16MFFOR-20MB90 | T46 |
| 20MFFOR-16MB90 | T46 |
| 20MFFOR-20MB90 | T46 |
| 20MFFOR-24MB90 | T46 |
| 24MFFOR-20MB90 | T46 |
| 24MFFOR-24MB90 | T46 |
| Male Flat-Face O-Ring to Male O-Ring Boss - 90° Long Drop | T46 |
| 4MFFOR-4MB90L | T46 |
| 6MFFOR-6MB90L | T46 |
| 12MFFOR-12MB90L | T46 |
| 16MFFOR-16MB90L | T46 |
| Male Flat-Face O-Ring on Run to Male O-Ring Boss - Tee | T47 |
| 4MFFOR-4MFFOR-4MB | T47 |
| 6MFFOR-6MFFOR-6MB | T47 |
| 8MFFOR-8MFFOR-8MB | T47 |
| 10MFFOR-10MFFOR-10MB | T47 |
| 12MFFOR-12MFFOR-12MB | T47 |
| 16MFFOR-16MFFOR-16MB | T47 |
| 20MFFOR-20MFFOR-20MB | T47 |
| Male Flat-Face O-Ring to Male O-Ring Boss to Male Flat-Face O-Ring - Tee | T47 |
| 4MFFOR-4MB-4MFFOR | T47 |
| 6MFFOR-6MB-6MFFOR | T47 |
| 8MFFOR-8MB-8MFFOR | T47 |
| 10MFFOR-10MB-10MFFOR | T47 |
| 12MFFOR-12MB-12MFFOR | T47 |
| 16MFFOR-16MB-16MFFOR | T47 |
| 20MFFOR-20MB-20MFFOR | T47 |
| 24MFFOR-24MB-24MFFOR | T47 |
| Female Flat-Face Swivel to Male JIC 37° Flare | T48 |
| 4FFORX-4MJ | T48 |
| 6FFORX-6MJ | T48 |
| 8FFORX-8MJ | T48 |
| 10FFORX-10MJ | T48 |
| 12FFORX-12MJ | T48 |
| 16FFORX-16MJ | T48 |
| **SAE to SAE - High Pressure Adapters** | |
| Code 61 O-Ring Flange to Male JIC 37° Flare | T49 |
| 8FL-8MJ | T49 |
| 12FL-12MJ | T49 |

| Category | Page |
|---|---|
| **SAE to SAE - High Pressure Adapters (Continued)** | |
| Code 61 O-Ring Flange to Male JIC 37° Flare (Continued) | T49 |
| 16FL-16MJ | T49 |
| 20FL-20MJ | T49 |
| 24FL-24MJ | T49 |
| 32FL-32MJ | T49 |
| Code 61 O-Ring Flange to Male JIC 37° Flare - High Pressure | T49 |
| 12FL5K-12MJ | T49 |
| 16FL5K-12MJ | T49 |
| 16FL5K-16MJ | T49 |
| 16FL5K-20MJ | T49 |
| 20FL4K-16MJ | T49 |
| 20FL4K-20MJ | T49 |
| Code 61 O-Ring Flange to Male JIC 37° Flare - 45° | T50 |
| 8FL-8MJ45 | T50 |
| 12FL-12MJ45 | T50 |
| 16FL-16MJ45 | T50 |
| 20FL-20MJ45 | T50 |
| 24FL-24MJ45 | T50 |
| 32FL-32MJ45 | T50 |
| Code 61 O-Ring Flange to Male JIC 37° Flare - 45° - High Pressure | T50 |
| 12FL5K-12MJ45 | T50 |
| 16FL5K-16MJ45 | T50 |
| 20FL4K-16MJ45 | T50 |
| 20FL4K-20MJ45 | T50 |
| Code 61 O-Ring Flange to Male JIC 37° Flare - 90° | T51 |
| 8FL-8MJ90 | T51 |
| 12FL-12MJ90 | T51 |
| 16FL-16MJ90 | T51 |
| 20FL-20MJ90 | T51 |
| 24FL-24MJ90 | T51 |
| 32FL-32MJ90 | T51 |
| Code 61 O-Ring Flange to Male JIC 37° Flare - 90° - High Pressure | T51 |
| 12FL5K-12MJ90 | T51 |
| 16FL5K-12MJ90 | T51 |
| 16FL5K-16MJ90 | T51 |
| 20FL4K-16MJ90 | T51 |
| 20FL4K-20MJ90 | T51 |
| Code 61 O-Ring Flange to Male Flat-Face O-Ring - High Pressure | T52 |
| 12FL5K-12MFFOR | T52 |
| 16FL5K-12MFFOR | T52 |
| 16FL5K-16MFFOR | T52 |
| 20FL4K-20MFFOR | T52 |
| Code 61 O-Ring Flange to Male Flat-Face O-Ring 45° - High Pressure | T52 |
| 12FL5K-12MFFOR45 | T52 |
| 16FL5K-16MFFOR45 | T52 |
| 20FL4K-20MFFOR45 | T52 |
| Code 61 O-Ring Flange to Male Flat-Face O-Ring 90° - High Pressure | T53 |
| 12FL5K-12MFFOR90 | T53 |
| 16FL5K-16MFFOR90 | T53 |
| 20FL4K-20MFFOR90 | T53 |
| Code 62 O-Ring Flange Heavy to Male JIC 37° Flare - (6,000 psi) | T53 |
| 12FLH6K-12MJ | T53 |
| 16FLH6K-12MJ | T53 |
| 16FLH6K-16MJ | T53 |
| 16FLH6K-20MJ | T53 |
| 20FLH6K-16MJ | T53 |
| 20FLH6K-20MJ | T53 |
| 24FLH6K-20MJ | T53 |
| 24FLH6K-24MJ | T53 |
| Code 62 O-Ring Flange Heavy to Male JIC 37° Flare 45° - (6,000 psi) | T54 |
| 12FLH6K-12MJ45 | T54 |
| 16FLH6K-16MJ45 | T54 |
| 20FLH6K-20MJ45 | T54 |
| Code 62 O-Ring Flange Heavy to Male JIC 37° Flare 90° - (6,000 psi) | T54 |
| 12FLH6K-12MJ90 | T54 |
| 12FLH6K-16MJ90 | T54 |
| 16FLH6K-12MJ90 | T54 |
| 16FLH6K-16MJ90 | T54 |
| 16FLH6K-20MJ90 | T54 |
| 20FLH6K-16MJ90 | T54 |
| 20FLH6K-20MJ90 | T54 |
| 24FLH6K-20MJ90 | T54 |
| Code 62 O-Ring Flange Heavy to Male Flat-Face O-Ring - (6,000 psi) | T55 |
| 12FLH6K-12MFFOR | T55 |

| Category | Page |
|---|---|
| **SAE to SAE - High Pressure Adapters (Continued)** | |
| Code 62 O-Ring Flange Heavy to Male Flat-Face O-Ring - (6,000 psi) (Continued) | T55 |
| 16FLH6K-16MFFOR | T55 |
| 20FLH6K-20MFFOR | T55 |
| Code 62 O-Ring Flange Heavy to Male Flat-Face O-Ring 45° - (6,000 psi) | T55 |
| 12FLH6K-12MFFOR45 | T55 |
| 16FLH6K-16MFFOR45 | T55 |
| 20FLH6K-20MFFOR45 | T55 |
| Code 62 O-Ring Flange Heavy to Male Flat-Face O-Ring 90° - (6,000 psi) | T55 |
| 12FLH6K-12MFFOR90 | T55 |
| 16FLH6K-12MFFOR90 | T56 |
| 16FLH6K-16MFFOR90 | T56 |
| 20FLH6K-20MFFOR90 | T56 |
| **British to SAE Adapters** | |
| Male British Standard Pipe Tapered Thread to Male JIC 37° Flare | T57 |
| 2MBSPT-4MJ | T57 |
| 2MBSPT-5MJ | T57 |
| 2MBSPT-6MJ | T57 |
| 4MBSPT-4MJ | T57 |
| 4MBSPT-5MJ | T57 |
| 4MBSPT-6MJ | T57 |
| 4MBSPT-8MJ | T57 |
| 6MBSPT-4MJ | T57 |
| 6MBSPT-5MJ | T57 |
| 6MBSPT-6MJ | T57 |
| 6MBSPT-8MJ | T57 |
| 6MBSPT-10MJ | T57 |
| 8MBSPT-6MJ | T57 |
| 8MBSPT-8MJ | T57 |
| 8MBSPT-10MJ | T57 |
| 8MBSPT-12MJ | T57 |
| 12MBSPT-8MJ | T57 |
| 12MBSPT-10MJ | T57 |
| 12MBSPT-12MJ | T57 |
| 12MBSPT-14MJ | T57 |
| 12MBSPT-16MJ | T57 |
| 16MBSPT-12MJ | T57 |
| 16MBSPT-16MJ | T57 |
| 16MBSPT-20MJ | T57 |
| 20MBSPT-16MJ | T57 |
| 20MBSPT-20MJ | T57 |
| 24MBSPT-24MJ | T57 |
| 32MBSPT-32MJ | T57 |
| Male British Standard Pipe Tapered Thread to Male JIC 37° Flare - 45° | T57 |
| 2MBSPT-4MJ45 | T57 |
| 4MBSPT-4MJ45 | T58 |
| 4MBSPT-6MJ45 | T58 |
| 6MBSPT-6MJ45 | T58 |
| 6MBSPT-8MJ45 | T58 |
| 8MBSPT-8MJ45 | T58 |
| 8MBSPT-10MJ45 | T58 |
| 12MBSPT-12MJ45 | T58 |
| 12MBSPT-16MJ45 | T58 |
| 16MBSPT-16MJ45 | T58 |
| Male British Standard Pipe Tapered Thread to Male JIC 37° Flare - 90° | T58 |
| 2MBSPT-4MJ90 | T58 |
| 4MBSPT-4MJ90 | T58 |
| 4MBSPT-5MJ90 | T58 |
| 4MBSPT-6MJ90 | T58 |
| 6MBSPT-6MJ90 | T58 |
| 6MBSPT-8MJ90 | T58 |
| 8MBSPT-6MJ90 | T58 |
| 8MBSPT-8MJ90 | T58 |
| 8MBSPT-10MJ90 | T58 |
| 8MBSPT-12MJ90 | T58 |
| 12MBSPT-12MJ90 | T58 |
| 12MBSPT-16MJ90 | T58 |
| 16MBSPT-16MJ90 | T58 |
| 20MBSPT-20MJ90 | T58 |
| 24MBSPT-24MJ90 | T58 |
| Male British Standard Pipe Parallel to Male Pipe NPTF | T59 |
| 2MBSPP-2MP | T59 |
| 2MBSPP-4MP | T59 |
| 4MBSPP-2MP | T59 |
| 4MBSPP-4MP | T59 |
| 4MBSPP-6MP | T59 |
| 4MBSPP-8MP | T59 |

## British to SAE Adapters (Continued)


| Category | Page |
|---|---|
| Male British Standard Pipe Parallel to Male Pipe NPTF (Continued) | T59 |
| 6MBSPP-2MP | T59 |
| 6MBSPP-4MP | T59 |
| 6MBSPP-6MP | T59 |
| 6MBSPP-8MP | T59 |
| 6MBSPP-12MP | T59 |
| 6MBSPP-16MP | T59 |
| 8MBSPP-4MP | T59 |
| 8MBSPP-6MP | T59 |
| 8MBSPP-8MP | T59 |
| 8MBSPP-12MP | T59 |
| 8MBSPP-16MP | T59 |
| 10MBSPP-8MP | T59 |
| 10MBSPP-12MP | T59 |
| 12MBSPP-8MP | T59 |
| 12MBSPP-12MP | T59 |
| 12MBSPP-16MP | T59 |
| 12MBSPP-20MP | T59 |
| 16MBSPP-12MP | T59 |
| 16MBSPP-16MP | T59 |
| 16MBSPP-20MP | T59 |
| 20MBSPP-16MP | T59 |
| 20MBSPP-20MP | T59 |
| 20MBSPP-24MP | T59 |
| 24MBSPP-20MP | T59 |
| 24MBSPP-24MP | T59 |
| 32MBSPP-32MP | T59 |
| Male British Standard Pipe Parallel to Female Pipe NPTF | T59 |
| 2MBSPP-2FP | T59 |
| 2MBSPP-4FP | T60 |
| 4MBSPP-2FP | T60 |
| 4MBSPP-4FP | T60 |
| 4MBSPP-6FP | T60 |
| 6MBSPP-2FP | T60 |
| 6MBSPP-4FP | T60 |
| 6MBSPP-6FP | T60 |
| 8MBSPP-4FP | T60 |
| 8MBSPP-6FP | T60 |
| 8MBSPP-8FP | T60 |
| 12MBSPP-8FP | T60 |
| 12MBSPP-12FP | T60 |
| 16MBSPP-16FP | T60 |
| 20MBSPP-16FP | T60 |
| 20MBSPP-20FP | T60 |
| 24MBSPP-20FP | T60 |
| 24MBSPP-24FP | T60 |
| 32MBSPP-32FP | T60 |
| Male British Standard Pipe Parallel to Male JIC 37° Flare | T60 |
| 2MBSPP-4MJ | T60 |
| 2MBSPP-5MJ | T60 |
| 2MBSPP-6MJ | T60 |
| 4MBSPP-4MJ | T60 |
| 4MBSPP-5MJ | T60 |
| 4MBSPP-6MJ | T60 |
| 4MBSPP-8MJ | T60 |
| 6MBSPP-4MJ | T60 |
| 6MBSPP-5MJ | T60 |
| 6MBSPP-6MJ | T60 |
| 6MBSPP-8MJ | T60 |
| 8MBSPP-6MJ | T60 |
| 8MBSPP-8MJ | T60 |
| 8MBSPP-10MJ | T60 |
| 8MBSPP-12MJ | T60 |
| 10MBSPP-8MJ | T60 |
| 10MBSPP-10MJ | T60 |
| 10MBSPP-12MJ | T60 |
| 12MBSPP-8MJ | T60 |
| 12MBSPP-10MJ | T60 |
| 12MBSPP-12MJ | T60 |
| 12MBSPP-14MJ | T60 |
| 12MBSPP-16MJ | T61 |
| 16MBSPP-12MJ | T61 |
| 16MBSPP-14MJ | T61 |
| 16MBSPP-16MJ | T61 |
| 16MBSPP-20MJ | T61 |
| 20MBSPP-16MJ | T61 |
| 20MBSPP-20MJ | T61 |
| 20MBSPP-24MJ | T61 |
| 24MBSPP-20MJ | T61 |

| Category | Page |
|---|---|
| Male British Standard Pipe Parallel to Male JIC 37° Flare (Continued) | T61 |
| 24MBSPP-24MJ | T61 |
| 32MBSPP-32MJ | T61 |
| Male British Standard Pipe Parallel to Male JIC 37° Flare - 45° | T61 |
| 2MBSPP-4MJ45 | T61 |
| 4MBSPP-4MJ45 | T61 |
| 4MBSPP-6MJ45 | T61 |
| 6MBSPP-6MJ45 | T61 |
| 6MBSPP-8MJ45 | T61 |
| 8MBSPP-8MJ45 | T61 |
| 8MBSPP-10MJ45 | T61 |
| 8MBSPP-12MJ45 | T61 |
| 12MBSPP-12MJ45 | T61 |
| 16MBSPP-16MJ45 | T61 |
| Male British Standard Pipe Parallel to Male JIC 37° Flare - 90° | T62 |
| 2MBSPP-4MJ90 | T62 |
| 4MBSPP-4MJ90 | T62 |
| 4MBSPP-5MJ90 | T62 |
| 4MBSPP-6MJ90 | T62 |
| 4MBSPP-8MJ90 | T62 |
| 6MBSPP-4MJ90 | T62 |
| 6MBSPP-5MJ90 | T62 |
| 6MBSPP-8MJ90 | T62 |
| 8MBSPP-6MJ90 | T62 |
| 8MBSPP-10MJ90 | T62 |
| 8MBSPP-12MJ90 | T62 |
| 12MBSPP-8MJ90 | T62 |
| 12MBSPP-10MJ90 | T62 |
| 12MBSPP-16MJ90 | T62 |
| 16MBSPP-12MJ90 | T62 |
| 16MBSPP-16MJ90 | T62 |
| 16MBSPP-20MJ90 | T62 |
| 20MBSPP-16MJ90 | T62 |
| 20MBSPP-20MJ90 | T62 |
| 24MBSPP-24MJ90 | T62 |
| Male British Standard Pipe Parallel to Female JIC 37° Flare Swivel | T62 |
| 2MBSPP-4FJX | T62 |
| 4MBSPP-4FJX | T62 |
| 4MBSPP-5FJX | T62 |
| 4MBSPP-6FJX | T62 |
| 6MBSPP-4FJX | T62 |
| 6MBSPP-6FJX | T62 |
| 6MBSPP-8FJX | T63 |
| 8MBSPP-4FJX | T63 |
| 8MBSPP-6FJX | T63 |
| 8MBSPP-8FJX | T63 |
| 8MBSPP-10FJX | T63 |
| 8MBSPP-12FJX | T63 |
| 10MBSPP-8FJX | T63 |
| 10MBSPP-10FJX | T63 |
| 12MBSPP-8FJX | T63 |
| 12MBSPP-12FJX | T63 |
| 12MBSPP-16FJX | T63 |
| 16MBSPP-16FJX | T63 |
| 16MBSPP-20FJX | T63 |
| 20MBSPP-16FJX | T63 |
| 20MBSPP-20FJX | T63 |
| 24MBSPP-24FJX | T63 |
| 32MBSPP-32FJX | T63 |
| Male British Standard Pipe Parallel with O-Ring to Male JIC 37° Flare | T63 |
| 2MBSPPOR-4MJ | T63 |
| 4MBSPPOR-4MJ | T63 |
| 4MBSPPOR-5MJ | T63 |
| 4MBSPPOR-6MJ | T63 |
| 6MBSPPOR-4MJ | T63 |
| 6MBSPPOR-5MJ | T63 |
| 6MBSPPOR-6MJ | T63 |
| 6MBSPPOR-8MJ | T63 |
| 8MBSPPOR-6MJ | T63 |
| 8MBSPPOR-8MJ | T63 |
| 8MBSPPOR-10MJ | T63 |
| 8MBSPPOR-12MJ | T63 |
| 12MBSPPOR-8MJ | T63 |
| 12MBSPPOR-10MJ | T63 |
| 12MBSPPOR-12MJ | T63 |
| 12MBSPPOR-16MJ | T63 |
| 16MBSPPOR-12MJ | T63 |
| 16MBSPPOR-16MJ | T63 |

## British to SAE Adapters (Continued)


| Category | Page |
|---|---|
| Male British Standard Pipe Parallel with O-Ring to Male JIC 37° Flare (Continued) | T63 |
| 20MBSPPOR-20MJ | T63 |
| 20MBSPPOR-24MJ | T63 |
| 24MBSPPOR-24MJ | T63 |
| Male British Standard Pipe Parallel with O-Ring to Male JIC 37° Flare - 90° | T64 |
| 6MBSPPOR-6MJ90 | T64 |
| 8MBSPPOR-8MJ90 | T64 |
| 12MBSPPOR-12MJ90 | T64 |
| Male British Standard Pipe Parallel with O-Ring to Male Flat-Face O-Ring | T64 |
| 2MBSPPOR-4MFFOR | T64 |
| 4MBSPPOR-4MFFOR | T64 |
| 4MBSPPOR-6MFFOR | T64 |
| 6MBSPPOR-6MFFOR | T64 |
| 6MBSPPOR-8MFFOR | T64 |
| 8MBSPPOR-6MFFOR | T64 |
| 8MBSPPOR-8MFFOR | T64 |
| 8MBSPPOR-10MFFOR | T64 |
| 12MBSPPOR-12MFFOR | T64 |
| 12MBSPPOR-16MFFOR | T64 |
| 16MBSPPOR-12MFFOR | T64 |
| 16MBSPPOR-16MFFOR | T64 |
| 20MBSPPOR-20MFFOR | T64 |
| 24MBSPPOR-24MFFOR | T64 |
| Male British Standard Pipe Parallel with O-Ring to Male Flat-Face O-Ring - Long | T65 |
| 6MBSPPOR-8MFFORL | T65 |
| 8MBSPPOR-8MFFORL | T65 |
| 8MBSPPOR-10MFFORL | T65 |
| 12MBSPPOR-10MFFORL | T65 |
| 12MBSPPOR-12MFFORL | T65 |
| 16MBSPPOR-16MFFORL | T65 |
| 20MBSPPOR-20MFFORL | T65 |
| Male British Standard Pipe Parallel with O-Ring to Male Flat-Face O-Ring - 45° | T65 |
| 2MBSPPOR-4MFFOR45 | T65 |
| 4MBSPPOR-4MFFOR45 | T65 |
| 4MBSPPOR-6MFFOR45 | T65 |
| 6MBSPPOR-6MFFOR45 | T65 |
| 6MBSPPOR-8MFFOR45 | T65 |
| 8MBSPPOR-8MFFOR45 | T65 |
| 8MBSPPOR-10MFFOR45 | T65 |
| Male British Standard Pipe Parallel with O-Ring to Male Flat-Face O-Ring - 90° | T66 |
| 2MBSPPOR-4MFFOR90 | T66 |
| 4MBSPPOR-4MFFOR90 | T66 |
| 4MBSPPOR-6MFFOR90 | T66 |
| 4MBSPPOR-8MFFOR90 | T66 |
| 6MBSPPOR-6MFFOR90 | T66 |
| 6MBSPPOR-8MFFOR90 | T66 |
| 8MBSPPOR-6MFFOR90 | T66 |
| 8MBSPPOR-8MFFOR90 | T66 |
| 8MBSPPOR-10MFFOR90 | T66 |
| 8MBSPPOR-12MFFOR90 | T66 |
| 12MBSPPOR-12MFFOR90 | T66 |
| 12MBSPPOR-16MFFOR90 | T66 |
| 16MBSPPOR-12MFFOR90 | T66 |
| 16MBSPPOR-16MFFOR90 | T66 |
| 20MBSPPOR-16MFFOR90 | T66 |
| 20MBSPPOR-20MFFOR90 | T66 |
| 24MBSPPOR-24MFFOR90 | T66 |
| Female British Standard Pipe Parallel to Male Pipe NPTF | T66 |
| 2FBSPP-2MP | T66 |
| 2FBSPP-4MP | T66 |
| 4FBSPP-4MP | T66 |
| 4FBSPP-6MP | T66 |
| 4FBSPP-8MP | T66 |
| 6FBSPP-6MP | T66 |
| 6FBSPP-8MP | T66 |
| 8FBSPP-8MP | T66 |
| 8FBSPP-12MP | T66 |
| 12FBSPP-12MP | T66 |
| 12FBSPP-16MP | T66 |
| 16FBSPP-16MP | T66 |
| 20FBSPP-20MP | T67 |
| 20FBSPP-24MP | T67 |
| 24FBSPP-24MP | T67 |
| 32FBSPP-32MP | T67 |
| Female British Standard Pipe Parallel to Female Pipe NPTF | T67 |
| 4FBSPP-4FP | T67 |
| Female British Standard Pipe Parallel to Female Pipe NPTF (Continued) | T67 |
| 6FBSPP-6FP | T67 |
| 8FBSPP-8FP | T67 |
| 12FBSPP-12FP | T67 |
| 16FBSPP-16FP | T67 |
| 20FBSPP-20FP | T67 |
| Female British Standard Pipe Parallel to Male JIC 37° Flare | T67 |
| 2FBSPP-4MJ | T67 |
| 4FBSPP-4MJ | T67 |
| 4FBSPP-6MJ | T67 |
| 6FBSPP-6MJ | T67 |
| 8FBSPP-8MJ | T67 |
| 12FBSPP-12MJ | T67 |
| 16FBSPP-16MJ | T67 |
| 20FBSPP-20MJ | T67 |
| 24FBSPP-24MJ | T67 |
| Female British Standard Pipe Parallel Swivel to Male Pipe NPTF - 90° | T68 |
| 2FBSPPX-2MP90 | T68 |
| 4FBSPPX-4MP90 | T68 |
| 6FBSPPX-6MP90 | T68 |
| 8FBSPPX-8MP90 | T68 |
| 12FBSPPX-12MP90 | T68 |
| 16FBSPPX-16MP90 | T68 |
| 20FBSPPX-20MP90 | T68 |
| 24FBSPPX-24MP90 | T68 |
| Female British Standard Pipe Parallel Swivel to Male JIC 37° Flare | T68 |
| 2FBSPPX-4MJ | T68 |
| 4FBSPPX-4MJ | T68 |
| 4FBSPPX-5MJ | T68 |
| 4FBSPPX-6MJ | T68 |
| 6FBSPPX-4MJ | T68 |
| 6FBSPPX-5MJ | T68 |
| 6FBSPPX-6MJ | T68 |
| 6FBSPPX-8MJ | T68 |
| 6FBSPPX-10MJ | T68 |
| 8FBSPPX-6MJ | T68 |
| 8FBSPPX-8MJ | T68 |
| 8FBSPPX-10MJ | T68 |
| 10FBSPPX-8MJ | T68 |
| 10FBSPPX-10MJ | T68 |
| 12FBSPPX-8MJ | T68 |
| 12FBSPPX-10MJ | T68 |
| 12FBSPPX-12MJ | T68 |
| 12FBSPPX-16MJ | T68 |
| 16FBSPPX-12MJ | T68 |
| 16FBSPPX-16MJ | T68 |
| 20FBSPPX-20MJ | T68 |
| 24FBSPPX-24MJ | T68 |
| Female British Standard Pipe Parallel Swivel to Female JIC 37° Flare Swivel | T69 |
| 4FBSPPX-4FJX | T69 |
| 4FBSPPX-6FJX | T69 |
| 6FBSPPX-6FJX | T69 |
| 6FBSPPX-8FJX | T69 |
| 8FBSPPX-6FJX | T69 |
| 8FBSPPX-8FJX | T69 |
| 10FBSPPX-10FJX | T69 |
| 12FBSPPX-12FJX | T69 |
| 16FBSPPX-16FJX | T69 |
| 20FBSPPX-20FJX | T69 |
| Female British Flat-Face O-Ring to Male JIC 37° Flare | T69 |
| 6FBFFOR-6MJ | T69 |
| 8FBFFOR-6MJ | T69 |
| 8FBFFOR-8MJ | T69 |
| 8FBFFOR-10MJ | T69 |
| 10FBFFOR-8MJ | T69 |
| 12FBFFOR-8MJ | T69 |
| 12FBFFOR-10MJ | T69 |
| 12FBFFOR-12MJ | T69 |


## Metric Conversion Adapters


| | |
|---|---|
| Male Metric O-Ring Plug | T70 |
| 12MMOR-PLUG | T70 |
| 14MMOR-PLUG | T70 |
| 16MMOR-PLUG | T70 |
| 18MMOR-PLUG | T70 |
| 20MMOR-PLUG | T70 |
| 22MMOR-PLUG | T70 |

| Category | Page |
|---|---|
| **Metric Conversion Adapters (Continued)** | |
| Male Metric O-Ring Plug (Continued) | T70 |
| 24MMOR-PLUG | T70 |
| 26MMOR-PLUG | T70 |
| 30MMOR-PLUG | T70 |
| 36MMOR-PLUG | T70 |
| 42MMOR-PLUG | T70 |
| Male Metric with O-Ring to Female Pipe NPTF | T70 |
| 10MM-2FP | T70 |
| 12MM-2FP | T70 |
| 12MM-4FP | T70 |
| 12MM-6FP | T70 |
| 14MM-4FP | T70 |
| 16MM-6FP | T70 |
| 16MM-8FP | T70 |
| 18MM-6FP | T70 |
| 18MM-8FP | T70 |
| 20MM-4FP | T70 |
| 20MM-6FP | T70 |
| 20MM-8FP | T70 |
| 22MM-6FP | T70 |
| 22MM-8FP | T70 |
| 22MM-12FP | T70 |
| 24MM-12FP | T70 |
| 26MM-12FP | T70 |
| 27MM-12FP | T70 |
| 33MM-16FP | T70 |
| Male Metric with O-Ring to Male JIC 37° Flare | T71 |
| 10MM-4MJ | T71 |
| 12MM-4MJ | T71 |
| 12MM-5MJ | T71 |
| 12MM-6MJ | T71 |
| 14MM-4MJ | T71 |
| 14MM-6MJ | T71 |
| 14MM-8MJ | T71 |
| 16MM-5MJ | T71 |
| 16MM-6MJ | T71 |
| 16MM-8MJ | T71 |
| 18MM-8MJ | T71 |
| 18MM-10MJ | T71 |
| 20MM-10MJ | T71 |
| 22MM-8MJ | T71 |
| 22MM-10MJ | T71 |
| 22MM-12MJ | T71 |
| 26MM-12MJ | T71 |
| 27MM-12MJ | T71 |
| 27MM-16MJ | T71 |
| 33MM-16MJ | T71 |
| 33MM-20MJ | T71 |
| 42MM-20MJ | T71 |
| 48MM-24MJ | T71 |
| Male Metric with O-Ring to Male JIC 37° Flare - 90° | T71 |
| 10MM-4MJ90 | T71 |
| 12MM-4MJ90 | T71 |
| 12MM-5MJ90 | T71 |
| 12MM-6MJ90 | T71 |
| 14MM-4MJ90 | T71 |
| 14MM-6MJ90 | T71 |
| 16MM-6MJ90 | T72 |
| 16MM-8MJ90 | T72 |
| 18MM-8MJ90 | T72 |
| 18MM-10MJ90 | T72 |
| 20MM-10MJ90 | T72 |
| 22MM-8MJ90 | T72 |
| 22MM-10MJ90 | T72 |
| 22MM-12MJ90 | T72 |
| 26MM-12MJ90 | T72 |
| 27MM-16MJ90 | T72 |
| 33MM-16MJ90 | T72 |
| 42MM-20MJ90 | T72 |
| Male DIN 24° Cone - Light Series to Male JIC 37° Flare | T72 |
| 6MDL-4MJ | T72 |
| 8MDL-4MJ | T72 |
| 8MDL-6MJ | T72 |
| 10MDL-4MJ | T72 |
| 10MDL-6MJ | T72 |
| 10MDL-8MJ | T72 |
| 12MDL-6MJ | T72 |
| 12MDL-8MJ | T72 |

| Category | Page |
|---|---|
| **Metric Conversion Adapters (Continued)** | |
| Male DIN 24° Cone - Light Series to Male JIC 37° Flare (Continued) | T72 |
| 15MDL-8MJ | T72 |
| 15MDL-10MJ | T72 |
| 15MDL-12MJ | T72 |
| 18MDL-10MJ | T72 |
| 18MDL-12MJ | T72 |
| 22MDL-12MJ | T72 |
| 28MDL-16MJ | T72 |
| 35MDL-20MJ | T72 |
| 42MDL-24MJ | T72 |
| Female DIN 24° Cone Swivel - Light Series to Male JIC 37° Flare | T73 |
| 6FDLX-4MJ | T73 |
| 6FDLX-5MJ | T73 |
| 8FDLX-4MJ | T73 |
| 8FDLX-6MJ | T73 |
| 10FDLX-6MJ | T73 |
| 10FDLX-8MJ | T73 |
| 12FDLX-6MJ | T73 |
| 12FDLX-8MJ | T73 |
| 12FDLX-10MJ | T73 |
| 15FDLX-6MJ | T73 |
| 15FDLX-8MJ | T73 |
| 15FDLX-10MJ | T73 |
| 22FDLX-12MJ | T73 |
| 28FDLX-16MJ | T73 |
| Male DIN 24° Cone - Heavy Series to Male JIC 37° Flare | T73 |
| 6MDH-4MJ | T73 |
| 8MDH-4MJ | T73 |
| 8MDH-6MJ | T73 |
| 10MDH-4MJ | T73 |
| 10MDH-8MJ | T73 |
| 12MDH-6MJ | T73 |
| 12MDH-8MJ | T73 |
| 12MDH-10MJ | T73 |
| 14MDH-6MJ | T73 |
| 14MDH-8MJ | T73 |
| 16MDH-8MJ | T73 |
| 16MDH-10MJ | T73 |
| 16MDH-12MJ | T73 |
| 20MDH-10MJ | T73 |
| 20MDH-12MJ | T73 |
| 25MDH-12MJ | T73 |
| 25MDH-16MJ | T73 |
| 30MDH-16MJ | T73 |
| 38MDH-20MJ | T73 |
| 38MDH-24MJ | T74 |
| Female DIN 24° Cone Swivel - Heavy Series to Male JIC 37° Flare | T74 |
| 10FDHX-4MJ | T74 |
| 12FDHX-5MJ | T74 |
| 12FDHX-6MJ | T74 |
| 12FDHX-8MJ | T74 |
| 12FDHX-10MJ | T74 |
| 14FDHX-6MJ | T74 |
| 16FDHX-8MJ | T74 |
| 20FDHX-10MJ | T74 |
| 25FDHX-12MJ | T74 |
| 30FDHX-16MJ | T74 |
| 38FDHX-20MJ | T74 |
| Male Kobelco Plug | T74 |
| 22MKB-PLUG | T74 |
| Male Kobelco to Male JIC 37° Flare | T75 |
| 22MKB-12MJ | T75 |
| 28MKB-12MJ | T75 |
| 28MKB-16MJ | T75 |
| 35MKB-16MJ | T75 |
| 35MKB-20MJ | T75 |
| **International to International Adapters** | |
| British Bonded Seal | T76 |
| 2BBDS | T76 |
| 4BBDS | T76 |
| 6BBDS | T76 |
| 8BBDS | T76 |
| 10BBDS | T76 |
| 12BBDS | T76 |
| 16BBDS | T76 |
| 20BBDS | T76 |

## International to International Adapters (Continued)


| Category | Page |
|---|---|
| British Bonded Seal (Continued) | T76 |
| 24BBDS | T76 |
| 32BBDS | T76 |
| 40BBDS | T76 |
| 48BBDS | T76 |
| Male British Standard Pipe Parallel with O-Ring Plug | T76 |
| 2MBSPOR-PLUG | T76 |
| 4MBSPOR-PLUG | T76 |
| 6MBSPOR-PLUG | T76 |
| 8MBSPOR-PLUG | T76 |
| 12MBSPOR-PLUG | T76 |
| 16MBSPOR-PLUG | T76 |
| 20MBSPOR-PLUG | T76 |
| Female British Standard Pipe Parallel Cap | T77 |
| 2FBSPP-CAP | T77 |
| 4FBSPP-CAP | T77 |
| 6FBSPP-CAP | T77 |
| 8FBSPP-CAP | T77 |
| 10FBSPP-CAP | T77 |
| 12FBSPP-CAP | T77 |
| 16FBSPP-CAP | T77 |
| 20FBSPP-CAP | T77 |
| 24FBSPP-CAP | T77 |
| 32FBSPP-CAP | T77 |
| Male British Standard Pipe Tapered Thread Plug | T77 |
| 2MBSPT-PLUG | T77 |
| 4MBSPT-PLUG | T77 |
| 6MBSPT-PLUG | T77 |
| 8MBSPT-PLUG | T77 |
| 10MBSPT-PLUG | T77 |
| 12MBSPT-PLUG | T77 |
| 16MBSPT-PLUG | T77 |
| 20MBSPT-PLUG | T77 |
| 24MBSPT-PLUG | T77 |
| Male British Standard Pipe Parallel Plug | T78 |
| 2MBSPP-PLUG | T78 |
| 4MBSPP-PLUG | T78 |
| 6MBSPP-PLUG | T78 |
| 8MBSPP-PLUG | T78 |
| 10MBSPP-PLUG | T78 |
| 12MBSPP-PLUG | T78 |
| 16MBSPP-PLUG | T78 |
| 20MBSPP-PLUG | T78 |
| 24MBSPP-PLUG | T78 |
| 32MBSPP-PLUG | T78 |
| Male British Standard Pipe Parallel to Female British Standard Pipe Parallel Swivel | T78 |
| 2MBSPP-2FBSPPX | T78 |
| 2MBSPP-4FBSPPX | T78 |
| 4MBSPP-2FBSPPX | T78 |
| 4MBSPP-4FBSPPX | T78 |
| 4MBSPP-6FBSPPX | T78 |
| 4MBSPP-8FBSPPX | T78 |
| 6MBSPP-4FBSPPX | T78 |
| 6MBSPP-6FBSPPX | T78 |
| 6MBSPP-8FBSPPX | T78 |
| 8MBSPP-6FBSPPX | T78 |
| 8MBSPP-8FBSPPX | T78 |
| 8MBSPP-10FBSPPX | T78 |
| 8MBSPP-12FBSPPX | T78 |
| 10MBSPP-8FBSPPX | T78 |
| 10MBSPP-10FBSPPX | T78 |
| 10MBSPP-12FBSPPX | T78 |
| 12MBSPP-6FBSPPX | T78 |
| 12MBSPP-8FBSPPX | T78 |
| 12MBSPP-10FBSPPX | T78 |
| 12MBSP-12FBSPX | T78 |
| 12MBSPP-16FBSPPX | T78 |
| 12MBSPP-20FBSPPX | T78 |
| 16MBSPP-12FBSPPX | T79 |
| 16MBSPP-16FBSPPX | T79 |
| 16MBSPP-20FBSPPX | T79 |
| 20MBSPP-16FBSPPX | T79 |
| 20MBSPP-20FBSPPX | T79 |
| 20MBSPP-24FBSPPX | T79 |
| 24MBSPP-20FBSPPX | T79 |
| 24MBSPP-24FBSPPX | T79 |
| 32MBSPP-32FBSPPX | T79 |


## International to International Adapters (Continued)


| Category | Page |
|---|---|
| Metric Bonded Seal | T79 |
| 6MBDS | T79 |
| 8MBDS | T79 |
| 10MBDS | T79 |
| 12MBDS | T79 |
| 14MBDS | T79 |
| 16MBDS | T79 |
| 18MBDS | T79 |
| 20MBDS | T79 |
| 22MBDS | T79 |
| 24MBDS | T79 |
| 26MBDS | T79 |
| 27MBDS | T79 |
| 30MBDS | T79 |
| 33MBDS | T79 |
| 36MBDS | T79 |
| 42MBDS | T79 |
| 45MBDS | T79 |
| 50MBDS | T79 |
| 52MBDS | T79 |
| Male Metric Plug | T80 |
| 8MM-PLUG | T80 |
| 10MM-PLUG | T80 |
| 12MM-PLUG | T80 |
| 14MM-PLUG | T80 |
| 16MM-PLUG | T80 |
| 18MM-PLUG | T80 |
| 20MM-PLUG | T80 |
| 22MM-PLUG | T80 |
| 24MM-PLUG | T80 |
| 26MM-PLUG | T80 |
| 30MM-PLUG | T80 |
| Male DIN 24° Cone - Light Series Plug | T80 |
| 6MDL-PLUG | T80 |
| 8MDL-PLUG | T80 |
| 10MDL-PLUG | T80 |
| 12MDL-PLUG | T80 |
| 15MDL-PLUG | T80 |
| 18MDL-PLUG | T80 |
| 22MDL-PLUG | T80 |
| 28MDL-PLUG | T80 |
| 35MDL-PLUG | T80 |
| 42MDL-PLUG | T80 |
| Female DIN 24° Cone - Light Series Cap | T81 |
| 6FDL-CAP | T81 |
| 8FDL-CAP | T81 |
| 10FDL-CAP | T81 |
| 12FDL-CAP | T81 |
| 15FDL-CAP | T81 |
| 18FDL-CAP | T81 |
| 22FDL-CAP | T81 |
| 28FDL-CAP | T81 |
| 35FDL-CAP | T81 |
| 42FDL-CAP | T81 |
| Male DIN 24° Cone - Heavy Series Plug | T81 |
| 8MDH-PLUG | T81 |
| 10MDH-PLUG | T81 |
| 12MDH-PLUG | T81 |
| 14MDH-PLUG | T81 |
| 16MDH-PLUG | T81 |
| 20MDH-PLUG | T81 |
| 25MDH-PLUG | T81 |
| 30MDH-PLUG | T81 |
| 38MDH-PLUG | T81 |
| Female DIN 24° Cone - Heavy Series Cap | T82 |
| 8FDH-CAP | T82 |
| 10FDH-CAP | T82 |
| 12FDH-CAP | T82 |
| 14FDH-CAP | T82 |
| 16FDH-CAP | T82 |
| 20FDH-CAP | T82 |
| 25FDH-CAP | T82 |
| 30FDH-CAP | T82 |
| 38FDH-CAP | T82 |

| Category | Page |
|---|---|
| **Japanese Conversion Adapters** | |
| Female Japanese Industrial Standard Cap | T83 |
| 4FJIS-CAP | T83 |
| 6FJIS-CAP | T83 |
| 8FJIS-CAP | T83 |
| 12FJIS-CAP | T83 |
| 16FJIS-CAP | T83 |
| 20FJIS-CAP | T83 |
| 32FJIS-CAP | T83 |
| Male Japanese Industrial Standard Plug | T83 |
| 4MJIS-PLUG | T83 |
| 6MJIS-PLUG | T83 |
| 8MJIS-PLUG | T83 |
| 12MJIS-PLUG | T83 |
| 16MJIS-PLUG | T83 |
| 20MJIS-PLUG | T83 |
| 24MJIS-PLUG | T83 |
| 32MJIS-PLUG | T83 |
| Female Japanese Industrial Standard to Male JIC 37° Flare | T83 |
| 4FJIS-4MJ | T83 |
| 6FJIS-4MJ | T83 |
| 6FJIS-6MJ | T83 |
| 8FJIS-8MJ | T84 |
| 12FJIS-12MJ | T84 |
| 16FJIS-16MJ | T84 |
| 20FJIS-20MJ | T84 |
| Female Komatsu Cap | T84 |
| 4FK-CAP | T84 |
| 6FK-CAP | T84 |
| 8FK-CAP | T84 |
| 10FK-CAP | T84 |
| 12FK-CAP | T84 |
| 16FK-CAP | T84 |
| Male Komatsu Plug | T84 |
| 4MK-PLUG | T84 |
| 6MK-PLUG | T84 |
| 8MK-PLUG | T84 |
| 10MK-PLUG | T84 |
| 12MK-PLUG | T84 |
| 16MK-PLUG | T84 |
| Female Komatsu to Male JIC 37° Flare | T85 |
| 4FK-4MJ | T85 |
| 6FK-6MJ | T85 |
| 8FK-8MJ | T85 |
| 10FK-10MJ | T85 |
| 12FK-12MJ | T85 |
| 16FK-16MJ | T85 |
| Male Komatsu to Male Komatsu | T85 |
| 4MK-4MK | T85 |
| 6MK-6MK | T85 |
| 8MK-8MK | T85 |
| 10MK-10MK | T85 |
| 12MK-12MK | T85 |
| 16MK-16MK | T85 |
| Male Komatsu to Male JIC 37° Flare | T85 |
| 4MK-4MJ | T85 |
| 6MK-6MJ | T85 |
| 8MK-8MJ | T85 |
| 10MK-10MJ | T85 |
| 12MK-12MJ | T85 |
| 16MK-16MJ | T85 |
| Male Komatsu to Female Komatsu - 90° | T86 |
| 4MK-4FK90 | T86 |
| 6MK-6FK90 | T86 |
| 8MK-8FK90 | T86 |
| 10MK-10FK90 | T86 |
| 12MK-12FK90 | T86 |
| 16MK-16FK90 | T86 |
| Male Komatsu to Female Komatsu to Male Komatsu - Tee | T86 |
| 4MK-4FK-4MK | T86 |
| 6MK-6FK-6MK | T86 |
| 8MK-8FK-8MK | T86 |
| 10MK-10FK-10MK | T86 |
| 12MK-12FK-12MK | T86 |

| Category | Page |
|---|---|
| **Ermeto Adapters** | |
| Bite Sleeve | T87 |
| 3ERBS | T87 |
| 4ERBS | T87 |
| 6ERBS | T87 |
| 8ERBS | T87 |
| Tube Sleeve Nut | T87 |
| 6ERTSN | T87 |
| Ermeto to Male Pipe | T87 |
| 4ERT-2MP | T87 |
| 4ERT-4MP | T87 |
| Ermeto to Male Pipe - 90° | T88 |
| 4ERT-2MP90 | T88 |
| Ermeto to Ermeto | T88 |
| 3ERT-3ERT | T88 |
| 4ERT-4ERT | T88 |
| 5ERT-5ERT | T88 |
| 6ERT-6ERT | T88 |
| 8ERT-8ERT | T88 |
| 10ERT-10ERT | T88 |
| **G940 Series (Agriculture Standard-Ball Valve)** | |
| Male Ball Valve to Female Pipe | U1 |
| 4MQBA-4FP | U1 |
| 6MQBA-6FP | U1 |
| 8MQBA-8FP | U1 |
| 8MQBA-12FP | U1 |
| 12MQBA-12FP | U1 |
| Male Ball Valve to Female O-Ring Boss | U1 |
| 8MQBA-8FB | U1 |
| Female Ball Valve To Female Pipe | U1 |
| 4FQBA-4FP | U1 |
| 6FQBADA-6FP | U1 |
| 8FQBADA-8FP | U1 |
| 8FQBA-8FP | U1 |
| 8FQBADA-12FP | U1 |
| 12FQBA-12FP | U1 |
| Female Ball Valve To Female O-Ring Boss | U2 |
| 8FQBA-8FB | U2 |
| O-Ring | U2 |
| 4QDAOR | U2 |
| 6QDAOR | U2 |
| 8QDAOR | U2 |
| 12QDAOR | U2 |
| **G940 and G941 Series (Agricultural)** | |
| QD Dust Plug | U3 |
| 4QDADP | U3 |
| 6QDADP | U3 |
| 8QDADP | U3 |
| QD Dust Cap | U3 |
| 4QDADC | U3 |
| 6QDADC | U3 |
| 8QDADC | U3 |
| **G941 Series (Agriculture Standard-Poppet Valve)** | |
| Male Poppet Valve to Female Pipe | U4 |
| 4MQPA-4FP | U4 |
| 6MQPA-6FP | U4 |
| 8MQPA-8FP | U4 |
| 16MQPA-16FP | U4 |
| Female Poppet Valve to Female Pipe | U4 |
| 4FQPA-4FP | U4 |
| 6FQPA-6FP | U4 |
| 8FQPA-8FP | U4 |
| 16FQPA-16FP | U4 |
| **G942 Series (John Deere Old Style)** | |
| Male Ball Valve to Female Pipe | U5 |
| 8MQBAJD-8FP | U5 |
| Male Ball Valve to Female O-Ring Boss | U5 |
| 8MQBAJD-8FB | U5 |

| Category | Page |
|---|---|
| **G942 Series (John Deere Old Style) (Continued)** | |
| Female Ball Valve to Female Pipe | U5 |
| 8FQBAJD-8FP | U5 |
| **G943 Series (International Harvester Old Style)** | |
| Male Tip - Ball Valve to Female Pipe | U6 |
| 8MQBAIHC-8FP | U6 |
| **G944 Series (J.I. Case Old Style)** | |
| 8MQBAJIC-8FP | U7 |
| **G945 Series (Industrial ISO 7241-1 - Series B)** | |
| Male Poppet Valve to Female Pipe | U8 |
| 4MQPI-4FP | U8 |
| 6MQPI-6FP | U8 |
| 8MQPI-8FP | U8 |
| 12MQPI-12FP | U8 |
| 16MQPI-16FP | U8 |
| Female Poppet Valve to Female Pipe | U8 |
| 4FQPI-4FP | U8 |
| 6FQPI-6FP | U8 |
| 8FQPI-8FP | U8 |
| 12FQPI-12FP | U8 |
| 16FQPI-16FP | U8 |
| O-Ring | U8 |
| 4QDIOR | U8 |
| 6QDIOR | U8 |
| 8QDIOR | U8 |
| 12QDIOR | U9 |
| 16QDIOR | U9 |
| Backup Ring | U9 |
| 4QDIBR | U9 |
| 6QDIBR | U9 |
| 8QDIBR | U9 |
| 12QDIBR | U9 |
| 16QDIBR | U9 |
| QD Plug - Cap Combination | U9 |
| 4QDIDP/C | U9 |
| 6QDIDP/C | U9 |
| 8QDIDP/C | U9 |
| 12QDIDP/C | U9 |
| 16QDIDP/C | U9 |
| **G949 Series (Flush Face - HTMA)** | |
| Male Flush Face Valve to Female Pipe | U10 |
| 4MQFF-4FP | U10 |
| 6MQFF-6FP | U10 |
| 6MQFF-8FP | U10 |
| 8MQFF-8FP | U10 |
| 8CPMQFF-8FP | U10 |
| 12MQFF-12FP | U10 |
| 16MQFF-16FP | U10 |
| Male Flush Face Valve to Female O-Ring Boss | U10 |
| 4MQFF-4FB | U10 |
| 6MQFF-8FB | U10 |
| 8MQFF-8FB | U10 |
| 8CPMQFF-8FB | U10 |
| 8CPMQFF-10FB | U10 |
| 8MQFF-12FB | U10 |
| 8CPMQFF-12FB | U10 |
| 10MQFF-12FB | U10 |
| 12MQFF-12FB | U10 |
| 16MQFF-16FB | U10 |
| Male Flush Face Valve to JIC 37° Flare Bulkhead | U11 |
| 8MQFF-10BKHD | U11 |
| 10MQFF-12BKHD | U11 |
| Male Flush Face Valve to Female British Pipe Parallel | U11 |
| 4MQFF-4FBPP | U11 |
| 8MQFF-8FBPP | U11 |
| 12MQFF-12FBPP | U11 |
| 16MQFF-16FBPP | U11 |
| Female Flush Face Valve to Female Pipe | U11 |
| 4FQFF-4FP | U11 |
| 6FQFF-6FP | U11 |

| Category | Page |
|---|---|
| **G949 Series (Flush Face - HTMA) (Continued)** | |
| Female Flush Face Valve to Female Pipe (Continued) | U11 |
| 6FQFF-8FP | U11 |
| 8FQFF-8FP | U11 |
| 8CPFQFF-8FP | U11 |
| 12FQFF-12FP | U11 |
| 16FQFF-16FP | U11 |
| Female Flush Face Valve to Female O-Ring Boss | U12 |
| 4FQFF-4FB | U12 |
| 6FQFF-8FB | U12 |
| 8FQFF-8FB | U12 |
| 8CPFQFF-8FB | U12 |
| 8CPFQFF-10FB | U12 |
| 8FQFF-12FB | U12 |
| 8CPFQFF-12FB | U12 |
| 10FQFF-12FB | U12 |
| 12FQFF-12FB | U12 |
| 16FQFF-16FB | U12 |
| Female Flush Face to JIC 37° Flare Bulkhead | U12 |
| 8FQFF-10BKHD | U12 |
| 10FQFF-12BKHD | U12 |
| Female Flush Face Valve to Female British Pipe Parallel | U12 |
| 8FQFF-8FBPP | U12 |
| 12FQFF-12FBPP | U12 |
| 16FQFF-16FBPP | U12 |
| Dust Plug | U13 |
| 4QDFFDP | U13 |
| 6QDFFDP | U13 |
| 8QDFFDP | U13 |
| 10QDFFDP | U13 |
| 12QDFFDP | U13 |
| 16QDFFDP | U13 |
| Dust Cap | U13 |
| 4QDFFDC | U13 |
| 6QDFFDC | U13 |
| 8QDFFDC | U13 |
| 10QDFFDC | U13 |
| 12QDFFDC | U13 |
| 16QDFFDC | U13 |
| **G950 Series (Flush Face - High Pressure)** | |
| Male Flush Face Valve | U14 |
| 6MQFFH-4FP | U14 |
| 6MQFFH-6FP | U14 |
| 8MQFFH-8FP | U14 |
| 12MQFFH-12FP | U14 |
| 16MQFFH-16FPA | U14 |
| 16MQFFH-16FP | U14 |
| Female Flush Face Valve | U14 |
| 6FQFFH-4FP | U14 |
| 6FQFFH-6FP | U14 |
| 8FQFFH-8FP | U14 |
| 12FQFFH-12FP | U14 |
| 16FQFFH-16FPA | U14 |
| 16FQFFH-16FP | U14 |
| QD Dust Plug | U14 |
| 6QDFFHDP | U14 |
| 8QDFFHDP | U14 |
| 12QDFFHDP | U14 |
| 16QDFFHDP | U14 |
| QD Dust Cap | U15 |
| 6QDFFHDC | U15 |
| 8QDFFHDC | U15 |
| 12QDFFHDC | U15 |
| 16QDFFHDC | U15 |
| **G951 Series (Wing Nut)** | |
| Male (Brass) - Less Flange | U16 |
| 12MQW-12FP | U16 |
| 16MQW-16FP | U16 |
| 20MQW-20FP | U16 |
| 24MQW-24FP | U16 |
| Female (Brass) - Wing Nut (Cast Iron) | U16 |
| 12FQW-12FP | U16 |
| 16FQW-16FP | U16 |

# INDEX


| Category | Page |
|---|---|
| **G951 Series (Wing Nut) (Continued)** | |
| Female (Brass) - Wing Nut (Cast Iron) (Continued) | U16 |
| 20FQW-20FP | U16 |
| 24FQW-24FP | U16 |
| Dust Plug | U16 |
| 12QWDP | U16 |
| 16QWDP | U16 |
| 20QWDP | U17 |
| 24QWDP | U17 |
| Dust Cap | U17 |
| 12QWDC | U17 |
| 16QWDC | U17 |
| 20QWDC | U17 |
| 24QWDC | U17 |
| **G952 Series (High Pressure Wing Nut)** | |
| Male Acme Flat Threads to Female Pipe | U18 |
| 12MQWH-12FP | U18 |
| 16MQWH-16FP | U18 |
| 20MQWH-20FP | U18 |
| 24MQWH-24FP | U18 |
| 32MQWH-32FP | U18 |
| Female Wing Nut to Female Pipe | U18 |
| 12FQWH-12FP | U18 |
| 16FQWH-16FP | U18 |
| 20FQWH-20FP | U18 |
| 24FQWH-24FP | U18 |
| 32FQWH-32FP | U18 |
| Dust Plug | U18 |
| 12QWHDP | U18 |
| 16QWHDP | U18 |
| 20QWHDP | U18 |
| 24QWHDP | U18 |
| 32QWHDP | U18 |
| Dust Cap | U19 |
| 12QWHDC | U19 |
| 16QWHDC | U19 |
| 20QWHDC | U19 |
| 24QWHDC | U19 |
| 32QWHDC | U19 |
| **G953 Series (Very High Pressure)** | |
| Male Poppet Valve to Female Pipe | U20 |
| 6MQFFVH-6FP | U20 |
| Female Screw to Connect to Female Pipe | U20 |
| 6FQFFVH-6FP | U20 |
| **G956 Series (Industrial ISO 7241 - Series A)** | |
| Male Poppet Valve to Female Pipe | U21 |
| 4MQP-4FP | U21 |
| 6MQP-6FP | U21 |
| 8MQP-8FP | U21 |
| 12MQP-12FP | U21 |
| 16MQP-16FP | U21 |
| Female Poppet Valve to Female Pipe | U21 |
| 4FQP-4FP | U21 |
| 6FQP-6FP | U21 |
| 12FQP-12FP | U21 |
| 16FQP-16FP | U21 |
| O-Ring | U21 |
| 4QDOR | U21 |
| 6QDOR | U21 |
| 8QDOR | U21 |
| 12QDOR | U21 |
| 16QDOR | U21 |
| Backup Ring | U22 |
| 4QDBR | U22 |
| 6QDBR | U22 |
| 8QDBR | U22 |
| 12QDBR | U22 |
| 16QDBR | U22 |
| QD Dust Plug | U22 |
| 4QDDP | U22 |

| Category | Page |
|---|---|
| **G956 Series (Industrial ISO 7241 - Series A) (Continued)** | |
| QD Dust Plug (Continued) | U22 |
| 6QDDP | U22 |
| 8QDDP | U22 |
| 12QDDP | U22 |
| 16QDDP | U22 |
| QD Dust Cap | U22 |
| 4QDDC | U22 |
| 6QDDC | U22 |
| 8QDDC | U22 |
| 12QDDC | U22 |
| 16QDDC | U22 |
| **G959 Series (Agriculture QD Adapters)** | |
| John Deere Old Style to ISO Style | U23 |
| 8MJD-8FISO | U23 |
| ISO Style to John Deere Old Style | U23 |
| 8MISO-8FJD | U23 |
| Int'l Harvester to John Deere Old Style | U23 |
| 8MIHC-8FJD | U23 |
| Int'l Harvester Old Style to ISO Style | U23 |
| 8MIHC-8FISO | U23 |
| ISO Style to Int'l Harvester Old Style | U24 |
| 8MISO-8FIHC | U24 |
| ISO Style to John Deere Old Style - (Double Shutoff) | U24 |
| 8MISO-8FJDDSO | U24 |
| ISO Style to Int'l Harvester Old Style - (Double Shutoff) | U24 |
| 8MISO-8FIHCDSO | U24 |
| **Two Way Block Style** | |
| Female Pipe NPTF | V1 |
| 4FP-4FPBV | V1 |
| 6FP-6FPBV | V1 |
| 8FP-8FPBV | V1 |
| 12FP-12FPBV | V1 |
| 16FP-16FPBV | V1 |
| 20FP-16FPBV | V1 |
| Female O-Ring Boss | V1 |
| 4FB-4FBBV | V1 |
| 6FB-6FBBV | V1 |
| 8FB-8FBBV | V1 |
| 12FB-12FBBV | V1 |
| 16FB-16FBBV | V1 |
| Code 61 O-Ring Flange | V1 |
| 8FL-8FLBV | V1 |
| 12FL-12FLBV | V1 |
| 16FL-16FLBV | V1 |
| 20FL-20FLBV | V1 |
| 24FL-24FLBV | V2 |
| 32FL-32FLBV | V2 |
| Code 62 O-Ring Flange | V2 |
| 8FLH-8FLHBV | V2 |
| 12FLH-12FLHBV | V2 |
| 16FLH-16FLHBV | V2 |
| 20FLH-20FLHBV | V2 |
| 24FLH-24FLHBV | V2 |
| 32FLH-32FLHBV | V2 |
| **Two Way Round Style Large ID** | |
| Female Pipe NPTF | V3 |
| 20FP-20FPBV | V3 |
| 24FP-24FPBV | V3 |
| 32FP-32FPBV | V3 |
| **Three Way Block Style** | |
| Ball Valve Lock Out Kits | V4 |
| 1/4" THRU 1/2" BV LOCK OUT KIT | V4 |
| 3/4" THRU 1" BV LOCK OUT KIT | V4 |
| 1 1/4" THRU 2" BV LOCK OUT KIT | V4 |
| Female Pipe NPTF | V4 |
| 4FP-4FP-4FPBV | V4 |
| 6FP-6FP-6FPBV | V4 |

Category — Page

## Three Way Block Style (Continued)

Female Pipe NPTF (Continued) V4
8FP-8FP-8FPBV V4
12FP-12FP-12FPBV V4
16FP-16FP-16FPBV V4
20FP-20FP-20FPBV V4

## Live Swivel

Male Pipe to Female Pipe - 90° W1
6MP-6FP-LX90 W1
8MP-8FP-LX90 W1
12MP-12FP-LX90 W1
16MP-16FP-LX90 W1

Male BSPP to Male BSPP W1
8BSPP-8BSPP-LX W1
12BSPP-12BSPP-LX W1
16BSPP-16BSPP-LX W1

Male JIC to Male JIC W1
6MJ-6MJ-LX W1
8MJ-8MJ-LX W1
12MJ-12MJ-LX W1
16MJ-16MJ-LX W1
20MJ-20MJ-LX W1
24MJ-24MJ-LX W1
32MJ-32MJ-LX W1

Male JIC to Male JIC - 90° W2
6MJ-6MJ-LX90S W2
8MJ-8MJ-LX90 W2
8MJ-8MJ-LX90S W2
12MJ-12MJ-LX90 W2
12MJ-12MJ-LX90S W2
16MJ-16MJ-LX90 W2
16MJ-16MJ-LX90S W2
20MJ-20MJ-LX90 W2

Male JIC to Female JIC/Boss W2
8MJ-8FJ/FB-LX W2
12MJ-12FJ/FB-LX W2
16MJ-16FJ/FB-LX W2
20MJ-20FJ/FB-LX W2
24MJ-24FJ/FB-LX W2
32MJ-32FJ/FB-LX W2

Male JIC to Female Boss - 90° W2
8MJ-8FB-LX90 W2
12MJ-12FB-LX90 W2
16MJ-16FB-LX90 W2
20MJ-20FB-LX90 W3

Male Boss to Female JIC/Boss - 90° W3
6MB-6FJ/FB-LX90S W3
8MB-8FJ/FB-LX90S W3
12MB-12FJ/FB-LX90S W3
16MB-16FJ/FB-LX90S W3

JIC Seal Kit W3
6JIC SWIVEL SEAL KIT W3
8JIC SWIVEL SEAL KIT W3
12JIC SWIVEL SEAL KIT W3
16JIC SWIVEL SEAL KIT W3
20JIC SWIVEL SEAL KIT W3
24JIC SWIVEL SEAL KIT W3
32JIC SWIVEL SEAL KIT W3

Male JIC to Female Pipe W3
8MJ-8FP-LX W3
12MJ-12FP-LX W3
16MJ-16FP-LX W3

Male Boss to Female Pipe - 90° W4
6MB-6FP-LX90S W4
8MB-8FP-LX90S W4
12MB-12FP-LX90S W4
16MB-16FP-LX90S W4

Male Boss to Male JIC - 90° W4
6MB-6MJ-LX90S W4
8MB-8MJ-LX90S W4
12MB-12MJ-LX90S W4
16MB-16MJ-LX90S W4

ORS Seal Kit W4
12ORS LIVE SWIVEL SEAL KIT W4

Category — Page

## Live Swivel (Continued)

ORS Seal Kit (Continued) W4
16ORS LIVE SWIVEL SEAL KIT W4

ORS/BSPP Seal Kit W4
8ORS/8BSPP LIVE SWVL SEAL KIT W4

Male ORFS to Female ORFS W5
12MFFOR-12FFORX-LX W5
16MFFOR-16FFORX-LX W5

Male ORFS to Male ORFS W5
8MFFOR-8MFFOR-LX W5
12MFFOR-12MFFOR-LX W5
16MFFOR-16MFFOR-LX W5

## Assembly Fabrication

Tube Assembly Equipment X1
Bend–N–Fit Tube Bender X1

Steel Power Steering & Transmission Oil Cooler Tubing - Male O-Ring X1
24" – 5/16" Male O–Ring X1
24" – 3/8" Male O–Ring X1
24" – 7/16" Male O–Ring X1
24" – 14mm Male O–Ring X1
24" – 16mm Male O–Ring X1

Steel Power Steering & Transmission Oil Cooler Tubing - Male Inverted Flare X1
24" – 3/8" Inverted Male Flare X1
24" – 14mm Male Inverted Flare X1
24" – 16mm Male Inverted Flare X1

Steel Power Steering & Transmission Oil Cooler Tubing - Male SAE X2
24" – 3/8" Male SAE X2

Steel Power Steering & Transmission Oil Cooler Tubing - Long Swivel O-Ring X2
24" – 16mm Long Swivel O–Ring X2

Steel Power Steering & Transmission Oil Cooler Tubing - Swivel O-Ring Type I X2
24" – 3/8" Swivel O–Ring Type I X2

Steel Power Steering & Transmission Oil Cooler Tubing - Swivel O-Ring Type II X2
24" – 5/16" Swivel O–Ring Type II X2

Steel Power Steering & Transmission Oil Cooler Tubing - Swivel O-Ring Type III X3
24" – 16mm Swivel O–Ring Type III X3

Steel Power Steering & Transmission Oil Cooler Tubing - Male Captive O-Ring X3
24" – 12mm Male Captive O–Ring X3

Steel Power Steering & Transmission Oil Cooler Tubing - Captive O-Ring X3
24" – 18mm Captive O–Ring X3

Steel Power Steering & Transmission Oil Cooler Tubing - Female SAE X4
24" – 3/8" Female SAE X4
24" – 1/2" Female SAE X4
24" – 16mm Female SAE X4

Steel Power Steering & Transmission Oil Cooler Tubing - Beaded Tube X4
24" – 3/8" Beaded Tube X4

Steel Power Steering & Transmission Oil Cooler Tubing - Male Single Bead Quick Connect X4
24" – 3/8" Male Single Bead Quick Connect X4

Steel Power Steering & Transmission Oil Cooler Tubing - Double Beaded Pipe X4
24" – 3/8" Double Beaded Pipe X4

Steel Power Steering & Transmission Oil Cooler Tubing - GM Quick Connect X5
24" – 3/8" GM Quick Connect X5

Aluminum Air Conditioning Tubing - Male Tube O-Ring X5
24" – 3/8" Male Tube O–Ring X5
24" – 1/2" Male Tube O–Ring X5

Aluminum Air Conditioning Tubing - Male SAE X5
24" – 3/8" Male SAE X5
24" – 1/2" Male SAE X5

Aluminum Air Conditioning Tubing - Male Inverted O-Ring X5
24" – 3/8" Male Inverted O–Ring X5
24" – 1/2" Male Inverted O–Ring X5

Aluminum Air Conditioning Tubing - Female Tube O-Ring X6
24" – 3/8" Female Tube O–Ring X6
24" – 1/2" Female Tube O–Ring X6
24" – 16mm Female Tube O–Ring X6
24" – 18mm Female Tube O–Ring X6
24" – 20mm Female Tube O–Ring X6

Aluminum Air Conditioning Tubing - Female SAE X6
24" – 3/8" Female SAE X6

| Category | Page |
|---|---|
| **Assembly Fabrication (Continued)** | |
| Aluminum Air Conditioning Tubing - Female SAE (Continued) | X6 |
| 24" – 1/2" Female SAE | X6 |
| Aluminum Air Conditioning Tubing - Male Ford Spring Lock | X6 |
| 24" – 3/8" Male Ford Spring Lock | X6 |
| 24" – 1/2" Male Ford Spring Lock | X6 |
| Aluminum Air Conditioning Tubing - Female Ford Spring Lock | X7 |
| 24" – 3/8" Female Ford Spring Lock | X7 |
| 24" – 1/2" Female Ford Spring Lock | X7 |
| **Nylon Protective Sleeve** | |
| LifeGuard® Tools | Y1 |
| LifeGuard Sleeve Guide Table | Y1 |
| LifeGuard Sleeve Bullets –4, –6, –8 | Y1 |
| LifeGuard® 3000, 4000 and 5000 | Y1 |
| 14LG3K | Y1 |
| 16LG3K | Y1 |
| 20LG3K | Y1 |
| 22LG3K | Y1 |
| 26LG3K | Y1 |
| 32LG3K | Y1 |
| 14LG4K | Y1 |
| 16LG4K | Y1 |
| 20LG4K | Y1 |
| 22LG4K | Y1 |
| 26LG4K | Y1 |
| 32LG4K | Y1 |
| 14LG5K | Y1 |
| 16LG5K | Y1 |
| 20LG5K | Y1 |
| 22LG5K | Y1 |
| 26LG5K | Y1 |
| LifeGuard® Clamp Collars - Stainless Steel | Y1 |
| 6SC-4-SS | Y1 |
| 8SC-4-SS | Y1 |
| 10SC-4-SS | Y1 |
| 12SC-4-SS | Y1 |
| 16SC-5-SS | Y1 |
| Clamp Collar for Nylon Sleeve and LifeGuard® Sleeve | Y2 |
| 4SC-1 | Y2 |
| 4SC-1 XBULK | Y2 |
| 6SC-1 | Y2 |
| 6SC-1 XBULK | Y2 |
| 8SC-1 | Y2 |
| 8SC-1 XBULK | Y2 |
| 10SC-1 | Y2 |
| 10SC-1 XBULK | Y2 |
| 12SC-1 | Y2 |
| 12SC-1 XBULK | Y2 |
| 16SC-2 XBULK | Y2 |
| 4SC-2 XBULK | Y2 |
| 10SC-2 | Y2 |
| 10SC-2 XBULK | Y2 |
| 12SC-2 | Y2 |
| 12SC-2 XBULK | Y2 |
| 6SC-3 | Y2 |
| 6SC-3 XBULK | Y2 |
| 6SC-4 | Y2 |
| 6SC-4 XBULK | Y2 |
| 8SC-4 | Y2 |
| 8SC-4 XBULK | Y2 |
| 10SC-4 | Y2 |
| 10SC-4 XBULK | Y2 |
| 12SC-4 | Y2 |
| 12SC-4 XBULK | Y2 |
| 16SC-4 | Y2 |
| Nylon Protective Sleeve | Y3 |
| HG-10 | Y3 |
| HG-14 | Y3 |
| HG-16 | Y3 |
| HG-20 | Y3 |
| HG-24 | Y3 |
| HG-26 | Y3 |
| HG-28 | Y3 |
| HG-32 | Y3 |
| HG-38 | Y3 |
| HG-42 | Y3 |

| Category | Page |
|---|---|
| **Nylon Protective Sleeve (Continued)** | |
| Nylon Protective Sleeve (Continued) | Y3 |
| HG-46 | Y3 |
| HG-64 | Y3 |
| HG 14 X25FT | Y3 |
| HG 16 X25FT | Y3 |
| HG 20 X25FT | Y3 |
| HG 24 X25FT | Y3 |
| HG 26 X25FT | Y3 |
| HG 28 X25FT | Y3 |
| HG 32 X25FT | Y3 |
| HG 38 X25FT | Y3 |
| **Hose Guards** | |
| PolySleeve™ High Density Polyethylene Hose Wrap | Y4 |
| 6PSB POLY SLEEVE | Y4 |
| 8PSB POLY SLEEVE | Y4 |
| 12PSB POLY SLEEVE | Y4 |
| 16PSB POLY SLEEVE | Y4 |
| 20PSB POLY SLEEVE | Y4 |
| 24PSB POLY SLEEVE | Y4 |
| 28PSB POLY SLEEVE | Y4 |
| 36PSB POLY SLEEVE | Y4 |
| 44PSB POLY SLEEVE | Y4 |
| 48PSB POLY SLEEVE | Y4 |
| 56PSB POLY SLEEVE | Y4 |
| 72PSB POLY SLEEVE | Y4 |
| 6PSY POLY SLEEVE | Y4 |
| 8PSY POLY SLEEVE | Y4 |
| 12PSY POLY SLEEVE | Y4 |
| 16PSY POLY SLEEVE | Y4 |
| 20PSY POLY SLEEVE | Y4 |
| 24PSY POLY SLEEVE | Y4 |
| 28PSY POLY SLEEVE | Y4 |
| 36PSY POLY SLEEVE | Y4 |
| 44PSY POLY SLEEVE | Y4 |
| 48PSY POLY SLEEVE | Y4 |
| 56PSY POLY SLEEVE | Y4 |
| Plastic Protective Coil Sleeves | Y5 |
| 1/4" CS1151-100FT | Y5 |
| 3/8" CS1152-100FT | Y5 |
| 1/2" CS1153-100FT | Y5 |
| 5/8" CS1154-50FT | Y5 |
| 3/4" CS1155-50FT | Y5 |
| 1" CS1156-50FT | Y5 |
| 1 3/8" CS1157-25FT | Y5 |
| 1 7/8" CS1158-25FT | Y5 |
| Plated Flat Armor Spring Guards | Y5 |
| 35/64" FSG-25FT | Y5 |
| 21/32" FSG-25FT | Y5 |
| 39/64" FSG-25FT | Y5 |
| 22/32" FSG-25FT | Y5 |
| 13/16" FSG-25FT | Y5 |
| 51/64" FSG-25FT | Y5 |
| 7/8" FSG-25FT | Y5 |
| 61/64" FSG-25FT | Y5 |
| 1" FSG-25FT | Y5 |
| 1 3/32" FSG-25FT | Y5 |
| 1 7/32" FSG-25FT | Y5 |
| 1 9/32" FSG-25FT | Y5 |
| 1 3/8" FSG-25FT | Y5 |
| 1 9/16" FSG-25FT | Y5 |
| 1 5/8" FSG-25FT | Y5 |
| 1 11/16" FSG-5FT | Y6 |
| 1 51/64" FSG-15FT | Y6 |
| 1 27/32" FSG-15FT | Y6 |
| 2 3/32" FSG-10FT | Y6 |
| 2 11/32" FSG-5FT | Y6 |
| 2 7/8" FSG-5FT | Y6 |
| Plated Wire Spring Guards | Y6 |
| 35/64" RSG-25FT | Y6 |
| 49/64" RSG-25FT | Y6 |
| 11/16" RSG-25FT | Y6 |
| 47/64" RSG-25FT | Y6 |
| 55/64" RSG-25FT | Y6 |
| 59/64" RSG-25FT | Y6 |
| 63/64" RSG-25FT | Y6 |
| 1 3/64" RSG-25FT | Y6 |
| 1 1/8" RSG-25FT | Y6 |

| Category | Page |
|---|---|
| **Hose Guards (Continued)** | |
| Plated Wire Spring Guards (Continued) | Y6 |
| 1 9/32" RSG-25FT | Y6 |
| 1 11/32" RSG-25FT | Y6 |
| 1 37/64" RSG-25FT | Y6 |
| 1 5/8" RSG-25FT | Y6 |
| 1 27/32" RSG-10FT | Y6 |
| 2 1/8" RSG-7FT | Y6 |
| 2 7/64" RSG-7FT | Y6 |
| **HeatGuard®** | |
| HeatGuard® Tape | Y7 |
| HTG–1" Wide HeatGuard Tape | Y7 |
| HTG–2" Wide HeatGuard Tape | Y7 |
| HTG–3" Wide HeatGuard Tape | Y7 |
| HTG–4" Wide HeatGuard Tape | Y7 |
| HTG–5" Wide HeatGuard Tape | Y7 |
| HeatGuard® Protective Sheathing | Y7 |
| HTG-4 | Y7 |
| HTG-5 | Y7 |
| HTG-6 | Y7 |
| HTG-7 | Y7 |
| HTG-8 | Y7 |
| HTG-9 | Y7 |
| HTG-10 | Y7 |
| HTG-11 | Y7 |
| HTG-12 | Y7 |
| HTG-13 | Y7 |
| HTG-14 | Y7 |
| HTG-15 | Y7 |
| HTG-16 | Y8 |
| HTG-18 | Y8 |
| HTG-20 | Y8 |
| HTG-22 | Y8 |
| HTG-24 | Y8 |
| HTG-26 | Y8 |
| HTG-28 | Y8 |
| HTG-30 | Y8 |
| HTG-32 | Y8 |
| HTG-34 | Y8 |
| HTG-36 | Y8 |
| HTG-38 | Y8 |
| HTG-40 | Y8 |
| HTG-44 | Y8 |
| HTG-56 | Y8 |
| HTG-64 | Y8 |
| HeatGuard® High-Temp Protective Sheathing | Y8 |
| 24-HTGH | Y8 |
| 28-HTGH | Y8 |
| 34-HTGH | Y8 |
| 52-HTGH | Y8 |
| **Gates OE-Style Clamp Collars** | |
| Clamp Collars | Y9 |
| CC1.12 | Y9 |
| CC1.20 | Y9 |
| CC1.25 | Y9 |
| CC1.37 | Y9 |
| **Vinyl Bend Restrictor** | |
| Vinyl Bend Restrictor | Y10 |
| HBR1051 | Y10 |
| HBR1051 XBULK | Y10 |
| HBR1052 | Y10 |
| HBR1052 XBULK | Y10 |
| HBR1053 | Y10 |
| HBR1053 XBULK | Y10 |
| HBR1050 | Y10 |
| HBR1050 XBULK | Y10 |
| HBR1054 | Y10 |
| HBR1054 XBULK | Y10 |
| HBR1056 | Y10 |
| HBR1055 | Y10 |
| HBR1055 XBULK | Y10 |
| HBR1098 | Y10 |
| HBR1098 XBULK | Y10 |
| HBR1097 | Y10 |
| HBR1097 XBULK | Y10 |

| Category | Page |
|---|---|
| **Flange Fittings** | |
| Code 61 Flange Cap | Y11 |
| 12FL-CAP | Y11 |
| 16FL-CAP | Y11 |
| 20FL-CAP | Y11 |
| 24FL-CAP | Y11 |
| 32FL-CAP | Y11 |
| Flange Half Sets (Code 61 - SAE J518) | Y11 |
| 8CFHS | Y11 |
| 12CFHS | Y11 |
| 16CFHS | Y11 |
| 20CFHS | Y11 |
| 24CFHS | Y11 |
| 32CFHS | Y11 |
| 40CFHS | Y11 |
| 48CFHS | Y11 |
| 56CFHS | Y11 |
| 64CFHS | Y11 |
| Code 62 Flange Cap | Y12 |
| 12FLH-CAP | Y12 |
| 16FLH-CAP | Y12 |
| 20FLH-CAP | Y12 |
| 24FLH-CAP | Y12 |
| 32FLH-CAP | Y12 |
| Flange Half Sets (Code 62 - SAE J518) | Y12 |
| 8FHHS | Y12 |
| 12FHHS | Y12 |
| 16FHHS | Y12 |
| 20FHHS | Y12 |
| 24FHHS | Y12 |
| 32FHHS | Y12 |
| Caterpillar-Style Flange Half Sets | Y13 |
| 12CATFHS | Y13 |
| 16CATFHS | Y13 |
| 20CATFHS | Y13 |
| 24CATFHS | Y13 |
| 32CATFHS | Y13 |
| **O-Rings** | |
| O-Rings for Straight Thread Boss Fittings | Y14 |
| 3 O-RING | Y14 |
| 4 O-RING | Y14 |
| 5 O-RING | Y14 |
| 6 O-RING | Y14 |
| 8 O-RING | Y14 |
| 10 O-RING | Y14 |
| 12 O-RING | Y14 |
| 14 O-RING | Y14 |
| 16 O-RING | Y14 |
| 20 O-RING | Y14 |
| O-Rings for Flat-Face Fittings | Y14 |
| 4 O-RING FF | Y14 |
| 6 O-RING FF | Y14 |
| 8 O-RING FF | Y14 |
| 10 O-RING FF | Y14 |
| 12 O-RING FF | Y14 |
| 16 O-RING FF | Y14 |
| 20 O-RING FF | Y14 |
| 24 O-RING FF | Y14 |
| O-Rings for Code 61, Code 62, and Caterpillar-Style Flange Fittings | Y15 |
| 8 FLANGE O-RING | Y15 |
| 10 FLANGE O-RING | Y15 |
| 12 FLANGE O-RING | Y15 |
| 16 FLANGE O-RING | Y15 |
| 20 FLANGE O-RING | Y15 |
| 24 FLANGE O-RING | Y15 |
| 32 FLANGE O-RING | Y15 |
| 40 FLANGE O-RING | Y15 |
| 48 FLANGE O-RING | Y15 |
| 56 FLANGE O-RING | Y15 |
| 64 FLANGE O-RING | Y15 |
| O-Rings for British Standard Parallel Pipe (BSPP Couplings) | Y15 |
| 4 O-RING FBSPP | Y15 |
| 6 O-RING FBSPP | Y15 |
| 8 O-RING FBSPP | Y15 |
| 10 O-RING FBSPP | Y15 |
| 12 O-RING FBSPP | Y15 |

# INDEX


| Category | Page |
|---|---|
| **O-Rings (Continued)** | |
| O-Rings for British Standard Parallel Pipe (BSPP Couplings) (Continued) | Y15 |
| 16 O-RING FBSPP | Y15 |
| 20 O-RING FBSPP | Y15 |
| O-Rings for DIN Light & Heavy Series (MegaCrimp® and GlobalSpiral™ Couplings) | Y16 |
| 18 O-RING DIN L | Y16 |
| 22 O-RING DIN L | Y16 |
| 28 O-RING DIN L | Y16 |
| 35 O-RING DIN L | Y16 |
| 42 O-RING DIN L | Y16 |
| 6 O-RING DIN H | Y16 |
| 8 O-RING DIN H | Y16 |
| 10 O-RING DIN H | Y16 |
| 12 O-RING DIN H | Y16 |
| 14 O-RING DIN H | Y16 |
| 15/16 O-RING DIN L/H | Y16 |
| 20 O-RING DIN H | Y16 |
| 25 O-RING DIN H | Y16 |
| 30 O-RING DIN H | Y16 |
| 38 O-RING DIN H | Y16 |
| O-Rings for DIN Heavy Series (MegaCrimp® and GlobalSpiral™ Couplings) | Y16 |
| 8 O-RING DIN H | Y16 |
| 10 O-RING DIN H | Y16 |
| 12 O-RING DIN H | Y16 |
| 14 O-RING DIN H | Y16 |
| 16 O-RING DIN H | Y16 |
| 20 O-RING DIN H | Y16 |
| 25 O-RING DIN H | Y16 |
| 30 O-RING DIN H | Y16 |
| 38 O-RING DIN H | Y16 |
| **Tube Nuts and Sleeves** | |
| Female Flareless Nut | Y17 |
| 4FFN | Y17 |
| 5FFN | Y17 |
| 6FFN | Y17 |
| 8FFN | Y17 |
| 10FFN | Y17 |
| 12FFN | Y17 |
| 16FFN | Y17 |
| Female Flareless Sleeve | Y17 |
| 4FFS | Y17 |
| 5FFS | Y17 |
| 6FFS | Y17 |
| 8FFS | Y17 |
| 10FFS | Y17 |
| 12FFS | Y17 |
| 16FFS | Y17 |
| Tube Sleeve | Y17 |
| 3TS | Y17 |
| 4TS | Y18 |
| 5TS | Y18 |
| 6TS | Y18 |
| 8TS | Y18 |
| 10TS | Y18 |
| 12TS | Y18 |
| 14TS | Y18 |
| 16TS | Y18 |
| 20TS | Y18 |
| 24TS | Y18 |
| 32TS | Y18 |
| Tube Sleeve Nut | Y18 |
| 2TSN | Y18 |
| 3TSN | Y18 |
| 4TSN | Y18 |
| 5TSN | Y18 |
| 6TSN | Y18 |
| 6TSN XBULK | Y18 |
| 8TSN | Y18 |
| 10TSN | Y18 |
| 12TSN | Y18 |
| 14TSN | Y18 |
| 16TSN | Y18 |
| 20TSN | Y18 |
| 32TSN | Y18 |
| Locknuts for Bulkhead Fittings | Y19 |
| 4LN-SH | Y19 |

| Category | Page |
|---|---|
| **Tube Nuts and Sleeves (Continued)** | |
| Locknuts for Bulkhead Fittings (Continued) | Y19 |
| 5LN | Y19 |
| 6LN-SH | Y19 |
| 8LN-SH | Y19 |
| 10LN-SH | Y19 |
| 16LN-SH | Y19 |
| SAE Tubing Sleeve Nut | Y19 |
| 4STSN | Y19 |
| 5STSN | Y19 |
| 6STSN | Y19 |
| 8STSN | Y19 |
| 10STSN | Y19 |
| 12STSN | Y19 |
| Metric Bite Sleeve | Y19 |
| 6BS | Y19 |
| 8BS | Y19 |
| 10BS | Y20 |
| 12BS | Y20 |
| 14BS | Y20 |
| 15BS | Y20 |
| 16BS | Y20 |
| 18BS | Y20 |
| 20BS | Y20 |
| 22BS | Y20 |
| 25BS | Y20 |
| 28BS | Y20 |
| 30BS | Y20 |
| 35BS | Y20 |
| 38BS | Y20 |
| 42BS | Y20 |
| Metric Bite Nut | Y20 |
| 6MNL | Y20 |
| 6MNLL | Y20 |
| 8MNL | Y20 |
| 10MNL | Y20 |
| 12MNL | Y20 |
| 15MNL | Y20 |
| 18MNL | Y20 |
| 22MNL | Y20 |
| 28MNL | Y20 |
| 35MNL | Y20 |
| 42MNL | Y20 |
| 6MNH | Y20 |
| 8MNH | Y20 |
| 10MNH | Y20 |
| 12MNH | Y20 |
| 14MNH | Y20 |
| 16MNH | Y20 |
| 20MNH | Y20 |
| 25MNH | Y20 |
| 30MNH | Y20 |
| 38MNH | Y20 |
| **Diagnostic** | |
| Diagnostic Equipment | Y21 |
| RFID BAND TAG - ORANGE | Y21 |
| RFID KEY TAG - ORANGE | Y21 |
| RFID LANYARD TAG 12 IN ORANGE | Y21 |
| RFID LANYARD TAG 24 IN ORANGE | Y21 |
| RFID LANYARD TAG 36 IN ORANGE | Y21 |
| **Equipment and Parts** | |
| Gates GC®16XD™ Parts | Z1 |
| GC16XD Handle Assembly | Z1 |
| GC16XD Foam Filler | Z1 |
| GC16XD Die Tub | Z1 |
| QC Tool (QCT) GC16–XD | Z1 |
| GC16XD End Caps | Z1 |
| GC16XD Stand Off Assembly (Long Version) | Z1 |
| GC16XD Die Retainer Sets | Z1 |
| GC16XD Dial Vernier Assembly | Z1 |
| GC16XD Bracket Assembly | Z1 |
| GC16XD Start Up Kit | Z1 |
| MobileCrimp® 4-20 Positive Stop Spacers | Z1 |
| B1 Spacer, PS | Z1 |
| W1 Spacer, PS | Z1 |
| R1 Spacer, PS | Z1 |

| Category | Page |
|---|---|
| **Equipment and Parts (Continued)** | |
| MobileCrimp® 4-20 Positive Stop Spacers (Continued) | Z1 |
| B2 Spacer, PS | Z1 |
| W2 Spacer, PS | Z1 |
| R2 Spacer, PS | Z1 |
| B3 Spacer, PS | Z1 |
| W3 Spacer, PS | Z1 |
| R3 Spacer, PS | Z1 |
| B4 Spacer, PS | Z1 |
| W4 Spacer, PS | Z1 |
| R4 Spacer, PS | Z1 |
| B5 Spacer, PS | Z1 |
| W5 Spacer, PS | Z1 |
| R5 Spacer, PS | Z1 |
| MobileCrimp® 4-20 Parts | Z1 |
| Magnet for Handling Die Sets | Z1 |
| Stand | Z1 |
| Pivot Spacer | Z1 |
| Stand Clamp | Z2 |
| Pivot Knob | Z2 |
| Positive Stop Pressure Plate | Z2 |
| DD Computer Pressure Plate | Z2 |
| Hose Assembly | Z2 |
| Pusher | Z2 |
| Cover Plate | Z2 |
| Seal Kit Includes: Seal, Washer and Backup Ring | Z2 |
| DD Pressure Plate for 20G/MC38 | Z2 |
| Computer Cable | Z2 |
| Digital Dial Assy. Kit (To Upgrade PS) | Z2 |
| Ball Plunger for Top of Cylinder | Z2 |
| Die Spring | Z2 |
| Die Link | Z2 |
| Shoulder Screws | Z2 |
| Slydring for Piston | Z2 |
| Tall Handle for DD | Z2 |
| Locking Pin | Z2 |
| Chain for Locking Pin | Z2 |
| Cable Assy. for DD | Z2 |
| DD Top Mt Contrl Kit (side to top mount) | Z2 |
| DD Controller Top Mount | Z2 |
| Retaining Ring for Piston | Z2 |
| Power Crimp® 707 Parts | Z2 |
| PC703 to PC707 Conversion Kit | Z2 |
| Crimp Switch Button for PC603/PC707 | Z2 |
| Piston New Design (Seals Included) | Z2 |
| Piston Rod | Z2 |
| Piston Rod Guide | Z2 |
| Base Plate (Machine) | Z2 |
| Tie Rod | Z2 |
| Pusher Cup (update design) | Z2 |
| Cylinder and Top Plate | Z2 |
| Spring Anchor | Z2 |
| Mounting Bracket | Z2 |
| O–Ring Between Piston and Rod | Z2 |
| Actuator Rod | Z2 |
| Die Cone With Notch | Z3 |
| Tie Rod Nut | Z3 |
| Switch Box Complete w/115V Cord Assy. | Z3 |
| Digital Readout Meter | Z3 |
| PC707 Shroud Only | Z3 |
| PC707 Hose Assy. (Pump to Crimper) | Z3 |
| Magnet for Removing Dies | Z3 |
| Die Cone (No Notch) | Z3 |
| Microswitch | Z3 |
| 230V Cord Assy. for Digital Readout | Z3 |
| PC707 230V Converter Kit | Z3 |
| 115V Cord Assy for Digital Readout | Z3 |
| Die Cage Halves (Set of 2) for 700 Series | Z3 |
| Stainless Steel Washer | Z3 |
| Die Cage Halves for 739 | Z3 |
| PC707 Seal Kit for New Aluminum Piston Serial Nos. 14,000 and Up | Z3 |
| Silver Die Back Up Ring | Z3 |
| LifeGuard Plate | Z3 |
| LifeGuard Plate and Die Kit | Z3 |
| Screw for Die Fingers | Z3 |
| Molykote 3 oz. Jar G Die Lubricant | Z3 |
| Piston Return Spring for PC707/3000B | Z3 |
| GC®32 Parts | Z3 |
| Head Replacement Kit | Z3 |
| Panel Replacement Kit | Z3 |

| Category | Page |
|---|---|
| **Equipment and Parts (Continued)** | |
| GC®32 Parts (Continued) | Z3 |
| Valve Block Adapters | Z3 |
| Pilot Operated Check | Z3 |
| Quick Change Tool | Z3 |
| Dial Vernier | Z3 |
| Depth Stop | Z3 |
| Mirror | Z3 |
| Foot Pedal | Z3 |
| Control Panel Post | Z3 |
| Kicker Tubing (Upper) | Z3 |
| Kicker Tubing (Lower) | Z3 |
| Foam Fillers GC32–XD Set of 8 | Z3 |
| Die Tubs | Z4 |
| Head Seal | Z4 |
| Breather Cap | Z4 |
| Kicker | Z4 |
| 2 Position 3–Way Solenoid | Z4 |
| Dial Vernier Locking Plate | Z4 |
| Relief Valve | Z4 |
| Back Press. Cont. Cartridge | Z4 |
| Oil Filter Element | Z4 |
| Control Box CSA | Z4 |
| Surge Protector w/Hubbell Plug | Z4 |
| QTC Repair Kit GC32/96 series up to 2" | Z4 |
| GC96TS, TSi, GC32TSi Power Supply | Z4 |
| GC96 GC32XD Transformer | Z4 |
| GC32 Inverter | Z4 |
| Die Retention Plate Kit | Z4 |
| Gates GC®96 Parts | Z4 |
| GC96TS Control Box with Potentiometer | Z4 |
| GC96TS Die Release Tool | Z4 |
| **Kits** | |
| Kits | AA1 |
| **Air Brake Hose Assemblies** | |
| 1/2" ID Hose with 1/2" Female SAE Swivel at Both Ends | AB1 |
| 8AB-8FSX-8FSX-18 | AB1 |
| 8AB-8FSX-8FSX-24 | AB1 |
| 8AB-8FSX-8FSX-30 | AB1 |
| 8AB-8FSX-8FSX-36 | AB1 |
| 8AB-8FSX-8FSX-42 | AB1 |
| 8AB-8FSX-8FSX-48 | AB1 |
| 8AB-8FSX-8FSX-60 | AB1 |
| AB-8FSX-8FSX-54 | AB1 |
| 1/2" ID Hose with 3/8" Male Pipe NPTF Swivel at Both Ends | AB1 |
| 8AB-6MPX-6MPX-08 | AB1 |
| 8AB-6MPX-6MPX-12 | AB1 |
| 8AB-6MPX-6MPX-16 | AB1 |
| 8AB-6MPX-6MPX-20 | AB1 |
| 8AB-6MPX-6MPX-24 | AB1 |
| 8AB-6MPX-6MPX-28 | AB1 |
| 8AB-6MPX-6MPX-32 | AB1 |
| 8AB-6MPX-6MPX-36 | AB1 |
| 8AB-6MPX-6MPX-42 | AB1 |
| 8AB-6MPX-6MPX-48 | AB1 |
| 8AB-6MPX-6MPX-54 | AB1 |
| 8AB-6MPX-6MPX-60 | AB1 |
| 8AB-6MPX-6MPX-66 | AB1 |
| 8AB-6MPX-6MPX-72 | AB1 |
| 8AB-6MPX-6MPX-84 | AB1 |
| 3/8" ID Hose with 1/4" Male Pipe NPTF Swivel at Both Ends | AB1 |
| 6AB-4MPX-4MPX-08 | AB1 |
| 6AB-4MPX-4MPX-12 | AB1 |
| 6AB-4MPX-4MPX-16 | AB2 |
| 6AB-4MPX-4MPX-20 | AB2 |
| 6AB-4MPX-4MPX-24 | AB2 |
| 6AB-4MPX-4MPX-28 | AB2 |
| 6AB-4MPX-4MPX-32 | AB2 |
| 6AB-4MPX-4MPX-36 | AB2 |
| 6AB-4MPX-4MPX-42 | AB2 |
| 6AB-4MPX-4MPX-48 | AB2 |
| 6AB-4MPX-4MPX-52 | AB2 |
| 6AB-4MPX-4MPX-60 | AB2 |
| 6AB-4MPX-4MPX-66 | AB2 |
| 6AB-4MPX-4MPX-72 | AB2 |
| 6AB-4MPX-4MPX-84 | AB2 |

# INDEX


| Category | Page |
|---|---|
| **Air Brake Hose Assemblies (Continued)** | |
| 3/8" ID Hose with 3/8" Male Pipe NPTF Swivel at Both Ends | AB2 |
| 6AB-6MPX-6MPX-08 | AB2 |
| 6AB-6MPX-6MPX-12 | AB2 |
| 6AB-6MPX-6MPX-16 | AB2 |
| 6AB-6MPX-6MPX-20 | AB2 |
| 6AB-6MPX-6MPX-24 | AB2 |
| 6AB-6MPX-6MPX-28 | AB2 |
| 6AB-6MPX-6MPX-32 | AB2 |
| 6AB-6MPX-6MPX-36 | AB2 |
| 6AB-6MPX-6MPX-42 | AB2 |
| 6AB-6MPX-6MPX-45 | AB2 |
| 6AB-6MPX-6MPX-48 | AB2 |
| 6AB-6MPX-6MPX-52 | AB2 |
| 6AB-6MPX-6MPX-60 | AB2 |
| 6AB-6MPX-6MPX-66 | AB2 |
| 6AB-6MPX-6MPX-72 | AB2 |
| 6AB-6MPX-6MPX-84 | AB2 |
| 3/8" ID Hose with 3/8" Female SAE Swivel at Both Ends | AB3 |
| 6AB-6FSX-6FSX-18 | AB3 |
| 6AB-6FSX-6FSX-24 | AB3 |
| 6AB-6FSX-6FSX-30 | AB3 |
| 6AB-6FSX-6FSX-36 | AB3 |
| 6AB-6FSX-6FSX-42 | AB3 |
| 6AB-6FSX-6FSX-48 | AB3 |
| 6AB-6FSX-6FSX-54 | AB3 |
| 6AB-6FSX-6FSX-60 | AB3 |
| **Air Brake Couplings For Rubber Hose** | |
| Male Air Brake to Male Pipe Adapter | AC2 |
| 6MAB-4MP | AC2 |
| 6MAB-6MP | AC2 |
| 6MAB-8MP | AC2 |
| 8MAB-6MP | AC2 |
| 8MAB-8MP | AC2 |
| Gladhand | AC2 |
| 8GH-S | AC2 |
| 8GH-U | AC2 |
| 8GH-E | AC2 |
| Gladhand Seal | AC3 |
| 6GH-SEAL | AC3 |
| Sleeve | AC3 |
| 6TS-6ABR | AC3 |
| 8TS-8ABR | AC3 |
| Nut | AC3 |
| 6TSN-6ABR | AC3 |
| 8TSN-8ABR | AC3 |
| Spring Guard Nut | AC4 |
| 6SGN-6ABR | AC4 |
| 8SGN-8ABR | AC4 |
| Air Brake to Male Pipe with Nut and Sleeve | AC4 |
| 6ABR-4MP | AC4 |
| 6ABR-6MP | AC4 |
| 6ABR-8MP | AC4 |
| 8ABR-6MP | AC4 |
| 8ABR-8MP | AC4 |
| Air Brake to Male Pipe with Spring Guard | AC5 |
| 6ABRSG-4MP | AC5 |
| 6ABRSG-6MP | AC5 |
| 6ABRSG-8MP | AC5 |
| 8ABRSG-6MP | AC5 |
| 8ABRSG-8MP | AC5 |
| Air Brake to Male Pipe without Nut and Sleeve | AC5 |
| 6ABRI-4MP | AC5 |
| 6ABRI-6MP | AC5 |
| 6ABRI-8MP | AC5 |
| 8ABRI-6MP | AC5 |
| 8ABRI-8MP | AC5 |
| Air Brake Spring Guard | AC5 |
| 6SGABR | AC5 |
| 8SGABR | AC5 |
| Air Brake to Female Air Brake Swivel | AC6 |
| 6ABR-6FABX | AC6 |
| 8ABR-8FABX | AC6 |

| Category | Page |
|---|---|
| **Air Brake Couplings For Rubber Hose (Continued)** | |
| Air Brake to Female Air Brake Swivel with Adapter | AC6 |
| 6ABR-6FABX-4MPA | AC6 |
| 6ABR-6FABX-6MPA | AC6 |
| 6ABR-8FABX-8MPA | AC6 |
| 8ABR-6FABX-6MPA | AC6 |
| Air Brake Union | AC6 |
| 6ABR-6ABR | AC6 |
| 8ABR-8ABR | AC6 |
| **Brass Lock-On Field Attachable Couplings for LOC & LOL Hose** | |
| Male Pipe with Cone Seat | AC8 |
| 4LOC-2RMP | AC8 |
| 4LOC-4RMP | AC8 |
| 4LOC-6RMP | AC8 |
| 5LOC-2RMP | AC8 |
| 5LOC-4RMP | AC8 |
| 6LOC-2RMP | AC8 |
| 6LOC-4RMP | AC8 |
| 6LOC-6RMP | AC8 |
| 6LOC-8RMP | AC8 |
| 8LOC-4RMP | AC8 |
| 8LOC-6RMP | AC8 |
| 8LOC-8RMP | AC8 |
| 8LOC-12RMP | AC8 |
| 10LOC-6RMP | AC8 |
| 10LOC-8RMP | AC8 |
| 10LOC-12RMP | AC8 |
| 12LOC-8RMP | AC8 |
| 12LOC-12RMP | AC8 |
| Male Pipe Swivel without Cone Seat | AC8 |
| 4LOC-4RMPX | AC8 |
| 6LOC-6RMPX | AC8 |
| 8LOC-8RMPX | AC8 |
| 12LOC-12RMPX | AC8 |
| Male Pipe 90° Block with Cone Seat | AC9 |
| 4LOC-2RMP90 | AC9 |
| 4LOC-4RMP90 | AC9 |
| 5LOC-2RMP90 | AC9 |
| 5LOC-4RMP90 | AC9 |
| 6LOC-2RMP90 | AC9 |
| 6LOC-4RMP90 | AC9 |
| 6LOC-6RMP90 | AC9 |
| 8LOC-8RMP90 | AC9 |
| 12LOC-12RMP90 | AC9 |
| Female Pipe without Cone Seat | AC9 |
| 4LOC-4RFP | AC9 |
| 5LOC-4RFP | AC9 |
| 6LOC-6RFP | AC9 |
| 8LOC-6RFP | AC9 |
| 8LOC-8RFP | AC9 |
| 10LOC-8RFP | AC9 |
| 12LOC-12RFP | AC9 |
| Female Pipe Swivel with Cone Seat | AC10 |
| 4LOC-2RFPX | AC10 |
| 4LOC-4RFPX | AC10 |
| 4LOC-6RFPX | AC10 |
| 6LOC-4RFPX | AC10 |
| 6LOC-6RFPX | AC10 |
| 6LOC-8RFPX | AC10 |
| 8LOC-8RFPX | AC10 |
| 8LOC-12RFPX | AC10 |
| 10LOC-12RFPX | AC10 |
| 12LOC-12RFPX | AC10 |
| Male JIC 37° Flare | AC10 |
| 4LOC-4RMJ | AC10 |
| 4LOC-5RMJ | AC10 |
| 4LOC-6RMJ | AC10 |
| 6LOC-4RMJ | AC10 |
| 6LOC-5RMJ | AC10 |
| 6LOC-6RMJ | AC10 |
| 6LOC-8RMJ | AC10 |
| 8LOC-8RMJ | AC10 |
| 8LOC-10RMJ | AC10 |
| 10LOC-8RMJ | AC10 |
| 10LOC-10RMJ | AC10 |
| 12LOC-10RMJ | AC10 |

## Brass Lock-On Field Attachable Couplings for LOC & LOL Hose (Continued)


| Category | Page |
|---|---|
| Male JIC 37° Flare (Continued) | AC10 |
| 12LOC-12RMJ | AC10 |
| Female JIC 37° Flare Swivel | AC11 |
| 4LOC-6RFJX | AC11 |
| 6LOC-6RFJX | AC11 |
| 12LOC-12RFJX | AC11 |
| Male SAE 45° Flare | AC11 |
| 4LOC-4RMS | AC11 |
| 4LOC-5RMS | AC11 |
| 4LOC-6RMS | AC11 |
| 5LOC-5RMS | AC11 |
| 6LOC-4RMS | AC11 |
| 6LOC-5RMS | AC11 |
| 6LOC-6RMS | AC11 |
| 6LOC-8RMS | AC11 |
| 8LOC-8RMS | AC11 |
| 8LOC-10RMS | AC11 |
| 10LOC-8RMS | AC11 |
| 10LOC-10RMS | AC11 |
| 12LOC-10RMS | AC11 |
| 12LOC-12RMS | AC11 |
| Female SAE 45° Flare Swivel | AC12 |
| 4LOC-6RFSX | AC12 |
| 5LOC-6RFSX | AC12 |
| 6LOC-6RFSX | AC12 |
| 8LOC-6RFSX | AC12 |
| 12LOC-12RFSX | AC12 |
| Dual Seat Female JIC 37°/SAE 45° Flare Swivel | AC12 |
| 4LOC-4RFJSX | AC12 |
| 4LOC-5RFJSX | AC12 |
| 5LOC-5RFJSX | AC12 |
| 6LOC-5RFJSX | AC12 |
| 6LOC-8RFJSX | AC12 |
| 8LOC-8RFJSX | AC12 |
| 8LOC-10RFJSX | AC12 |
| 10LOC-10RFJSX | AC12 |
| 12LOC-10RFJSX | AC12 |
| Male SAE Inverted Flare Swivel | AC13 |
| 4LOC-3RMIX | AC13 |
| 4LOC-4RMIX | AC13 |
| 4LOC-5RMIX | AC13 |
| 5LOC-4RMIX | AC13 |
| 5LOC-5RMIX | AC13 |
| 5LOC-6RMIX | AC13 |
| 6LOC-5RMIX | AC13 |
| 6LOC-6RMIX | AC13 |
| 6LOC-8RMIX | AC13 |
| 8LOC-6RMIX | AC13 |
| 8LOC-8RMIX | AC13 |
| 10LOC-10RMIX | AC13 |
| Female SAE Inverted Flare | AC13 |
| 4LOC-3RFI | AC13 |
| 4LOC-4RFI | AC13 |
| 4LOC-5RFI | AC13 |
| 5LOC-5RFI | AC13 |
| 6LOC-5RFI | AC13 |
| 6LOC-6RFI | AC13 |
| 8LOC-8RFI | AC13 |
| North American Stand Pipe | AC14 |
| 4LOC-3RFT | AC14 |
| 4LOC-4RFT | AC14 |
| 4LOC-5RFT | AC14 |
| 5LOC-5RFT | AC14 |
| 6LOC-6RSP | AC14 |
| 8LOC-8RSP | AC14 |
| 10LOC-10RSP | AC14 |
| Hose Length Extenders | AC14 |
| 4LOC-4RHM | AC14 |
| 5LOC-5RHM | AC14 |
| 6LOC-6RHM | AC14 |
| 8LOC-8RHM | AC14 |
| 10LOC-10RHM | AC14 |
| 12LOC-12RHM | AC14 |
| Male British Standard Pipe Tapered | AC15 |
| 5LOC-4MBSPT | AC15 |


## Single Bead


| Category | Page |
|---|---|
| Male Pipe with Cone Seat | AC17 |
| 3SB-2RMP | AC17 |
| 4SB-2RMP | AC17 |
| 4SB-4RMP | AC17 |
| 5SB-2RMP | AC17 |
| 5SB-4RMP | AC17 |
| 6SB-2RMP | AC17 |
| 6SB-4RMP | AC17 |
| 6SB-6RMP | AC17 |
| 8SB-6RMP | AC17 |
| 8SB-8RMP | AC17 |
| 10SB-6RMP | AC17 |
| 10SB-8RMP | AC17 |
| 10SB-12RMP | AC17 |
| 12SB-8RMP | AC17 |
| 12SB-12RMP | AC17 |
| Male Straight Thread Connector | AC17 |
| 6SB-9MSC | AC17 |
| 6SB-10MSC | AC17 |
| 6SB-14MSC | AC17 |
| Male Pipe 90° Block Cone Seat | AC18 |
| 4SB-2RMP90 | AC18 |
| 5SB-2RMP90 | AC18 |
| 5SB-4RMP90 | AC18 |
| 6SB-2RMP90 | AC18 |
| 6SB-4RMP90 | AC18 |
| 6SB-6RMP90 | AC18 |
| 8SB-6RMP90 | AC18 |
| 8SB-8RMP90 | AC18 |
| 10SB-6RMP90 | AC18 |
| 10SB-8RMP90 | AC18 |
| 12SB-8RMP90 | AC18 |
| Male SAE 45° Flare Connector | AC18 |
| 6SB-5RMS | AC18 |
| 6SB-6RMS | AC18 |
| Male SAE Inverted Flare Swivel | AC19 |
| 4SB-4RMIX | AC19 |
| 4SB-5RMIX | AC19 |
| 5SB-4RMIX | AC19 |
| 5SB-5RMIX | AC19 |
| 5SB-6RMIX | AC19 |
| 6SB-5RMIX | AC19 |
| 6SB-6RMIX | AC19 |
| Male SAE Inverted Flare Swivel - 45° | AC19 |
| 6SB-5RMIX45 | AC19 |
| Male SAE Inverted Flare Swivel - 90° | AC20 |
| 4SB-4RMIX90 | AC20 |
| 4SB-5RMIX90 | AC20 |
| 5SB-6RMIX90 | AC20 |
| 6SB-5RMIX90 | AC20 |
| 6SB-6RMIX90 | AC20 |
| Female SAE Inverted Flare | AC20 |
| 5SB-5RFI | AC20 |
| 6SB-5RFI | AC20 |
| 6SB-6RFI | AC20 |


## Barb Stem


| Category | Page |
|---|---|
| Male Pipe NPTF with Cone Seat | AC22 |
| 2BS-2MP | AC22 |
| 3BS-2MP | AC22 |
| 3BS-4MP | AC22 |
| 4BS-2MP | AC22 |
| 4BS-4MP | AC22 |
| 4BS-6MP | AC22 |
| 5BS-2MP | AC22 |
| 5BS-4MP | AC22 |
| 6BS-2MP | AC22 |
| 6BS-4MP | AC22 |
| 6BS-6MP | AC22 |
| 6BS-8MP | AC22 |
| 8BS-4MP | AC22 |
| 8BS-6MP | AC22 |
| 8BS-8MP | AC22 |
| 8BS-12MP | AC22 |
| 10BS-6MP | AC22 |
| 10BS-8MP | AC22 |

Category Page

## Barb Stem (Continued)


Male Pipe NPTF with Cone Seat (Continued) AC22
10BS-12MP AC22
12BS-8MP AC22
12BS-12MP AC22

Female Pipe NPTF AC22
2BS-2FP AC22
3BS-2FP AC22
4BS-2FP AC22
4BS-4FP AC22
5BS-2FP AC22
5BS-4FP AC22
6BS-2FP AC22
6BS-4FP AC22
6BS-6FP AC22
8BS-4FP AC22
8BS-6FP AC22
8BS-8FP AC23

DRIVEN BY POSSIBILITY™




Automotive 431-2080
Industrial 35093

Please recycle this catalog!

Printed in the U.S.A.

For more information on Gates Hydraulic hose, visit **www.gates.com/hydraulics**

For in-depth technical support, contact Gates Industrial Technical & Engineering Support at **303.744.5070** or **pa0000@gates.com**

Gates Industrial Corporation
1144 15th Street, Suite 1400
Denver, CO 80202, U.S.A.
303.744.1911